include\config.h

```
// Define configuration constants for the project
#ifndef CONFIG_H
#define CONFIG_H

#include <Arduino.h>
#include <avr/io.h>
#include <stdint.h>
#include <stdbool.h>

#ifndef F_CPU
#define F_CPU 20000000UL    // better to define in .ini file: build_flags = -DF_CPU=20000000UL/board_build.f_cpu = 20000000L
#endif

// ---------------------------------------------------------
//  Timing
// ---------------------------------------------------------

#define BAUD_US             104
#define TURNAROUND_US       (BAUD_US * 3)
#define CHILD_TIMEOUT_US    15000
#define PARENT_TIMEOUT_US   15000
#define FRAME_TIMEOUT_US    15000

// ---------------------------------------------------------
// Counts / Limits
// ---------------------------------------------------------
#define CHILD_COUNT             2
#define CHILD_RETRIES           3
#define UPSTREAM_FAIL_LIMIT     3

// ??????????
#define NODE_HEADER_LEN         3
```

```
33 //macht so nicht so viel sinn, weil letztes child in upstream reihe ja eigentliche alle payloads von allen anderen bekommt -> child payload lenght kann nicht einfach so mit max_length durch anzahl kinder berechnet werden
34 #define MAX_PAYLOAD_LEN          128 // must be <256 for 1 byte LEN field, but should also be limited to avoid long transmission times and large buffers. For prototype_v3, we can set it to 128 as a reasonable limit for testing.
35 #define MAX_CHILD_PAYLOAD_LEN    128  //I don´t need this
36
37 // ------------------------------------------------------------
38 //  Protocol bytes
39 // ------------------------------------------------------------
40
41 #define CMD_STATUS          0xAA
42 #define ACK_BUSY            0x55
43 #define DATA_BYTE           0x42
44 #define SYNC_BYTE           0xA5
45
46 // ------------------------------------------------------------
47 // Node data
48 // ------------------------------------------------------------
49
50 #define NODE_ID             0x10
51
52 #endif // CONFIG_H
```