University of Applied Sciences Augsburg

Faculty of Electrical Engineering
Creative Engineering

Bachelor Thesis

Design and Development of a Tangible Learning System for Special Education

submitted by
Elena Spitzer

Supervisor:	Claudia Meitinger
Second Supervisor:	Christoph Zeuke
Submission Date:	18. August 2026

Abstract

This thesis …

Table of Contents

1 Special Education Context 1
1.1 Implications for Learning and Teaching 1
1.2 Existing Learning Materials 2
1.3 Objectives and Scope 3
2 Theoretical Background 4
2.1 Fundamentals of Learning Theory 4
2.2 Embodied Cognition and Interaction 6
2.3 Graphical vs Tangible User Interface 7
2.4 Design Factors for TUI 9
2.5 Feedback for TUI 13
2.6 Potentials of TUIs for children (with dissorders) (liang) 15
3 Requirements Analysis 18
3.1 Context of Use and Didactic Application Scenario 18
3.2 Pedagogical and Interaction-related Requirements 18
3.3 Requirements for Feedback and Assistance 19
3.4 Geometrical and Ergonomic Requirements 20
3.5 Functional Requirements for Detection 21
3.6 Electrical and Technical Requirements 21
3.7 Safety and Economic Requirements 22
4 Concept Development 23
4.1 Design Basis and Concept Objective 23
4.2 Usage Scenario 23
4.3 Overall System Architecture 25
4.4 Conceptual definition of the levels of connection 25
4.5 Physical Design and Connection Subsystem 26
4.6 Electronic Detection and Power Subsystem 28
4.7 Data, Communication and Software Subsystem 32
4.8 Task and Interaction Subsystem 36
4.9 Visualisation and Feedback Subsystem 37
4.10 Concept Summary 41
5 Technical Realisation 42
5.1 Mechanical and Electronic Realisation 42
5.2 Communication Protocol 44
5.3 Firmware of Bricks and Baseplate 50
5.4 Software Architecture and Backend Processing 54
5.5 Frontend, Visualisation and Feedback 56
6 Evaluation 60
6.1 Aim and Scope 60
6.2 Methodology 60
6.3 Results 63
6.4 Overall Requirement Fulfilment 64
6.5 Discussion 64
6.6 Notizen 65
7 List of Abbreviations 66
References 66

1 Special Education Context

Students with special educational focus in the areas of Special education focus on intellectual development (**GE**) (*German: Förderschwerpunkt Geistige Entwicklung, GE*) , Special education focus on learning (**LE**) (*German: Förderschwerpunkt Lernen, LE*), and Autism Spectrum Disorder (**ASD**) may face a common range of challenges in the learning process. These may include difficulties with fundamental prerequisites for learning, such as perseverance, memory, and motivation, as well as with learning how to learn. Learners may experience difficulties reflecting on their own learning, evaluating their learning processes, and transferring acquired knowledge and skills to everyday situations. Challenges related to independent thinking, action planning, and problem-solving may also be relevant, as these abilities enable learners to structure sequences of actions and cope with emerging problems independently [1], [2], [3].

Against the background of these challenges, the following areas of development and competence are particularly relevant [1], [2], [3], [4]:

- Action planning
- Problem-solving
- Recognition of relationships
- Attention and memory
- Motor skills and perception
- Independence and self-regulation

Special educational provision therefore aims to support students in developing these competencies, enabling them to act with increasing independence and self-determination in both educational and everyday contexts and to participate more fully in society. These competencies extend beyond the possession of knowledge and include the ability to make decisions, plan and carry out actions, evaluate their outcomes, and seek appropriate support when required [1], [4], [5].

1.1 Implications for Learning and Teaching

As shown in Table 1, the different difficulties and needs and consequently, the heterogeneity of learner groups resulting from the three areas considered, **GE**, **LE** and **ASD**, makes it difficult to select educational opportunities that are equally suitable for all learners [5].

Area	Description	Support Approach
GE	Varying levels of cognitive development, motor skills and perception	Concrete, action-oriented approaches, individual support and sufficient processing time
LE	Difficulties with academic learning such as learning strategies and the transfer of acquired knowledge	Clear subtasks, repetition and comprehensible feedback
ASD	Individually varying characteristics in perception, communication and interaction	Clear structures, visualised processes and individually adapted levels of sensory stimulation

Table 1: *Relevant Developmental Areas in Special Education and Support Approaches [1], [2], [3]*

In the area of learning, for example, the acquisition of basic academic skills and their transfer to other situations represents a central educational objective [2], whereas students in the area of intellectual development may require a more development-oriented form of support that addresses fundamental cognitive competencies such as cognition, perception and motor skills [1]. At the same time, students within each of the three areas do not form a homogeneous group and therefore

require individually adapted support. This is particularly evident in autism spectrum disorder, as each child presents a unique combination of characteristics. The disorder may occur in conjunction with severe cognitive impairments, but also with high cognitive abilities [3]. This heterogeneity therefore requires an inclusive educational approach that builds on the individual prerequisites of each child and provides appropriately adapted learning opportunities and support measures.

Despite these differences, several common principles for the design of suitable learning opportunities can be derived across the three areas [1], [2], [3]:

- Individual adaptation rather than standardised requirements
- Clear and manageable task structures
- Visualisation of processes and sequences of actions
- Sufficient processing time and opportunities for repetition
- Playful and action-oriented tasks
- Timely and comprehensible feedback
- Promotion of independence and self-efficacy

One way of addressing different learning prerequisites is to make learning content accessible through different perceptual and action-based approaches. In this context, the interaction between motor and perceptual experience plays a particularly important role, since learners can develop sensorimotor integration processes and support learning at an elementary level through active engagement and the conscious perception of their own movements and environment [1].

A suitable framework for such action-oriented experiences provide playful and constructive forms of learning, as they offer opportunities to develop and strengthen sensory, motor, and cognitive abilities within concrete contexts of action. At the same time, they enable exploratory experimentation in which errors are accepted as part of the learning process [6].

In addition to designing appropriate learning approaches, the promotion of self-directed learning represents another important educational objective intended to strengthen students independence [7]. However, the ability to complete a task independently requires learners to recognise the effects of their actions and adapt their subsequent approach accordingly. Timely and comprehensible feedback is therefore essential, because otherwise there will be a risk that incorrect procedures are continued unnoticed or uncertainty arise regarding how to proceed with the task. In heterogeneous or inclusive classrooms, however, a teacher cannot continuously observe every action of every student and provide immediate feedback. Particularly during phases of independent practice, a delay may therefore occur between an action and the corresponding feedback. For learners who depend on clear confirmation or correction in order to continue a task, this can make independent task completion more difficult [8].

1.2 Existing Learning Materials

Construction materials such as building blocks are generally well suited to action-oriented and self-directed forms of learning because they combine concrete actions with the exploration of spatial and logical relationships. Through active construction, experimentation, and problem-solving, children can engage with learning content in a playful manner. At the same time, the result remains visible as a physical artefact and can be directly examined and modified.However, constrcution materials are generally unable to independently detect or evaluate the resulting construction. The feedback required for self-directed learning must therefore be provided either by the learners themselves or by a teacher (quelle Steffie?).

At the same time, digital technologies such as tablets make it possible to present learning content through multimedia, adapt tasks to individual needs, and provide automated feedback. However,

spatial content is often represented only on a two-dimensional screen, while interaction is largely limited to mouse or touch input. Although these forms of input also enable active interaction, they do not provide the same haptic and spatially differentiated experience as the manipulation of three-dimensional objects. This reduces the physical and motor interaction with learning objects, which is highly relevant for successful learning, to a minimum (quelle Steffie?).

1.3 Objectives and Scope

In this context, the Objective of this thesis is to develop a modular, brick-based learning game that combines the haptic and spatial properties of conventional construction materials with the possibilities of digital detection, visualisation, and feedback. Within a guided construction task, children can use the bricks to build a three-dimensional structure and receive immediate feedback on whether their construction corresponds to the target structure or contains errors. Feedback is provided both directly through the bricks and through an additional visualization on a display. The power is thereby supplied centrally from the baseplate and distributed through all the connected bricks

The physical manipulation of the bricks combines visual, haptic, and motor experiences, while the digital representation provides additional information about the detected state of the construction. Through immediate feedback, the learning game is intended to enable learners to independently monitor and correct individual action steps. In this way, it aims to support self-directed learning, action planning, spatial and relational thinking, and problem-solving.

The thesis is limited to the development and technical validation of a functional prototype. The size and complexity of supported structures are constrained by the available bricks and the system architecture. Product maturity, large-scale manufacturing, and a dedicated tablet application for mobile devices are outside the scope of this work and remain subjects for future development.

1.3.1 Structure

to that end, first …

2 Theoretical Background

2.1 Fundamentals of Learning Theory

The ways in which children acquire and apply new knowledge can be explained through different theoretical perspectives. These perspectives differ primarily in their understanding of how knowledge is formed, which role learners assume within the learning process and how learning environments should be designed. The three approaches discussed in the following, instructivism, constructivism, and constructionism, pursue different educational objectives but are all relevant to the development of learning systems. While instructivism primarily conceptualises learners as recipients of externally structured knowledge, constructivism and constructionism emphasise their active participation in the learning process [9], [10].

2.1.1 Instructivism

Instructivism is based on the assumption that knowledge can be systematically structured and transmitted by a teacher. Learning primarily takes place through explanation and the reproduction of predefined content or procedures. The learner therefore assumes a comparatively receptive role, while the teacher determines the learning objectives, organises the subject matter, and provides the intended solution path [9].

2.1.2 Constructivism

In contrast to the instructivist approach, constructivism defines learning as an active process in which learners independently engage with and shape the subject matter. Vollmers illustrates a fundamental principle of Piaget's theory of learning using the following quotation from Piaget [9, p. 7]:

> "Thinking means constructing relationships. The individual comprehends the external world only by establishing relationships between its elements."

Knowledge is therefore not conceived as a complete and objective representation of reality that exists independently of the learner. Instead, it is proposed that this phenomenon occurs as learners establish relationships between elements of their environment, interpret these relationships, and integrate them into their existing knowledge structures. The conceptual understanding of such abstract relationships is preceded by concrete experiences arising from physical interaction with objects in the environment. It is recommended that objects be touched, moved, compared with one another, or arranged spatially, with a view to generating experiences that provide the basis for the development of cognitive structures [9].

Based on Piaget's theory, learning is therefore described as an "interactive process between the learner and the external world" [9, p. 75]. New knowledge does not emerge solely through the presentation of information, but primarily through active engagement with the object of learning.

2.1.3 Constructionism

The mathematician and psychologist Seymour Papert extends the constructivist approach by adding an external dimension in his constructionist theory of learning. He argues that the construction of knowledge in the mind is most effective when it is supported by the construction of a tangible object in the physical world. Following the principle of "learning by making," learners reconstruct knowledge while creating something of their own, thereby connecting the external construction of an artefact with the internal construction of knowledge [10].

The constructed artefact fulfils several functions: On the one hand, it makes abstract theoretical considerations concrete, tangible, and, in the literal sense, comprehensible. Relationships that may be difficult to understand when represented solely through language or graphics can become visible through the spatial arrangement of a physical model. On the other hand, modifying the model enables learners to test different assumptions and directly observe their effects [11], [12].

Papert even goes beyond the physical act of construction by emphasising the importance of personal meaning. Following the principle that "love is a better master than duty" [11, p,6], he argues that learning is enhanced when children create something that is personally meaningful to them.

Building on the explanations of the three learning theories, the central characteristics and differences are again summarised in Table 2:

Approach	**Guiding Principle**	**Construction of Knowledge**	**Learning Process**	**Role of learner**	**Role of Teacher**
Instructivism	*Learning by listening*	presented and transmitted through structured instruction	Predetermined content and solution paths	Passive recipient	Transmits and explains knowledge
Constructivism	*Learning by doing*	constructed through cognitive processes, reflection, and the recognition of relationships	Exploration and problem-solving	Active participant	Guides and supports learning
Constructionism	*Learning by making*	constructed through creation of a tangible, personally meaningful artefact	Exploration, problem-solving and iterative construction	Active creator	Guides and supports learning

Table 2: *Comparison of Learning Approaches [9], [11], [12]*

2.1.4 Synthesis and Conclusion

Within the context of constructivism and constructionism, success is as important as failure and the occurrence of errors. Learning does not result merely from carrying out an activity. Instead, it develops through cognitive engagement with the constructed object and with the problems encountered during the construction process. Such difficulties create an opportunity for learners to review their planning and procedures and to reflect consciously on how the situation can be resolved and how their actions might be coordinated more effectively in future attempts [9].

Compared to instructivism this conception of learning consequently also brings about a transformation in the role of the teacher: Rather than being responsible for transmitting knowledge in its entirety, the teacher is expected to create appropriate learning opportunities, prepare didactically structured tasks, and support learners when difficulties arise without anticipating or prescribing the complete solution [12].

However, the theoretical perspectives are not necessarily mutually exclusive in practical educational settings. Instructive elements may provide essential background knowledge or initial guidance, while constructivist and constructionist activities allow learners to actively apply, examine, and further develop this knowledge. The appropriate combination therefore depends on the learning objective, the learners prior knowledge, and the degree of guidance required.

2.2 Embodied Cognition and Interaction

While constructivism and constructionism explain why actively creating an externally perceivable artefact can support learning, they do not fully state the role played by bodily action and sensory perception during the construction process. This relationship is addressed by the theory of embodied cognition, which assumes that cognitive processes are inseparably connected to the body. Embodied interaction transfers this theoretical perspective to the design of interactive digital systems .

2.2.1 Embodied Cognition

Embodied cognition assumes that cognitive processes do not occur independently of the body but are shaped by perception, movement, and interaction with the environment. From this perspective, the physical manipulation of a learning object is not merely a means of executing an action that has already been fully planned mentally. Instead, the manipulation itself can form part of the processes of thinking and understanding and may therefore be considered as an integral component of the cognitive system. Knowledge consequently emerges through the reciprocal relationship between the brain, the body, and the environment [13], [14].

For learning processes, this implies that physical activities can be particularly relevant when they correspond meaningfully to the subject matter becuase arbitrary movement alone does not necessarily improve learning. Rather, the correspondence between the physical action and the concept to be learned is crucial. When learners are expected to understand a spatial relationship, for example, it may be beneficial for them to establish this relationship by physically positioning and rotating objects. In this case, the action does not merely represent the learning content symbolically but makes it directly accessible through bodily experience [13], [14].

However, the educational value of physical interaction depends on the relationship between the performed action and the concept to be learned. Movement alone does not necessarily improve learning. The physical action must meaningfully correspond to the underlying content and make relevant properties or relationships directly perceivable [14].

2.2.2 Embodied Interaction

While embodied cognition provides a theoretical perspective on the relationship between the body and cognition, Paul Dourish formulated embodied interaction as a framework for understanding and designing interactive computer systems. Rather than viewing interaction as abstract information processing, this framework emphasises how meaning emerges through users' engaged actions with artefacts and within social practices [14].

Dourish distinguishes between two dimensions of embodiment: physical presence in the world and social embeddedness within established practices and systems of meaning. Again, an object is not embodied merely because it exists in material form, what is decisive is how it is used and interpreted within a specific situation. Similarly, a user interface does not automatically enable embodied interaction simply because it involves physical actions. The actions performed through the interface must be comprehensible to users and must have a recognisable relationship to the system's responses [14].

The aim of embodied interaction is therefore to design computer systems that do not restrict users to purely abstract forms of interaction but instead make effective use of their natural, everyday abilities and established ways of acting [14].

2.2.3 Conclusion

Taken together, these theories indicate that the educational value of a tangible learning system does not result from physical activity or digital technology alone. It emerges from the coherent relationship between the learning objective, the actions performed by learners and the physical artefacts being manipulated. A suitable learning environment should therefore combine structured guidance with opportunities for independent exploration, construction, and meaningful bodily interaction.

2.3 Graphical vs Tangible User Interface

A User Interface (**UI**) can be defined as the point of contact through which people communicate and interact with a technical system. The most common **UI** is the Graphical User Interface (**GUI**), in which digital information is visually represented on a screen and manipulated through input devices such as a mouse, a keyboard, or a touchscreen [6].

Shaer and Hornecker contrast this mode of interaction with people's everyday experience of the physical environment [15, p. 3]:

> "We live in a complex world, filled with myriad objects, tools, toys, and people. Our lives are spent in diverse interaction with this environment. Yet, for the most part, our computing takes place sitting in front of, and staring at, a single glowing screen attached to an array of buttons and a mouse"

The quotation highlights the separation between traditional computer interaction and people's embodied experience of the physical world: In everyday life, objects can be grasped, combined and explored through several senses, whereas conventional **GUI**, by contrast, translate these actions into interactions with visual representations on a two-dimensional display. Consequently, digital interaction frequently utilizes only a limited extent of people's innate physical capabilities, potentially resulting in a reduced level of intuitiveness [15].

The concept of Ishii and Ullmer's Tangible Bits responds to this separation by coupling digital information with everyday physical and graspable objects and the surrounding environment. Its central aim is to bridge the divide between the digital domain of bits and the physical world of atoms, thereby making digital information directly accessible through physical manipulation. Tangible Bits consequently provided an important conceptual foundation for the development of Tangible User Interface (**TUI**) [16], [17].

Different to a **GUI**, in a **TUI**, the computer becomes a natural extension of the physical environment. Interaction does not occur exclusively through graphical elements on a screen, instead, users manipulate real world objects, reffered to physical objects, so called phicons in order to interact with the digital system. These phicons do not merely serve as input devices but they also fulfil a representational function [6].

The fundamental principle of a **TUI** is predicated on two closely related characteristics [18]:

1. Phicons, are used as representations of digital information and computational operations
2. The physical manipulation of these phicons is used to interact with the associated computational operation

Because different types of information or functions can be represented by separate physical elements, multiple phicons may remain available for simultaneous manipulation. They may also be operated in parallel or with both hands. This principle, known as *space multiplexing*, can improve interaction efficiency and facilitate collaborative use by groups, which is typically more restricted in conventional GUI-based interaction [18].

2.3.1 MVC and MCRpd Model

The difference between these styles of user interfaces becomes more obvious when comparing their undelying interaction models shown in the figure Figure 1 [19].

MVC model for GUI

Within the Model View Controller (**MVC**) architecture, an interactive software system is divided into three functional components: The *model* represents the underlying data and the current state of the system, the *view* presents this information graphically, while the *control* processes user input and translates it into changes to the model. Therefore, in the interaction model of a **GUI**, there is a clear separation between the control devices, such as the mouse and keyboard and the digital representation displayed on the screen [19].

MCRpd model for TUI

The interaction model for a **TUI** retains the **MVC** *model* and *control* components but replaces the exclusively graphical *view* with both a Physical Representation (**rep_p**) and a Digital Representation (**rep_d**). It thereby accounts for the fact that, in a **TUI**, digital information is not represented solely on a screen but is also given a tangible physical form. The structure of the physical components can be characterised by three central properties:

1. The physical representation is coupled with digital information
2. The physical representation incorporates mechanisms for interactive control
3. The physical state of the object contains information about the digital state of the system

Consequently, the physical representation performs a dual function: On the one hand, it represents digital information and system states, and on the other, it serves as an interactive control element. Hence, the position, orientation or arrangement of a phicon for example can encode information about the corresponding digital state. At the same time, moving, rotating or connecting the object modifies that state. Thus, *representation* and *control* are connected not only conceptually, but also physically [19].




Figure 1: a) interaction model of GUI: MVC model; b) interaction Model of TUI: MCRpd model [19]

2.3.2 Conclusion

The distinctive characteristic of a **TUI** lies in the close coupling between representation and action. Whereas a **GUI** typically separates the visual representation of digital information on a screen from interaction through an input device, a **TUI** uses physical artefacts both to represent digital content and to manipulate it [19]. This coupling can support the constructivist and constructionist learning

approaches discussed in Section 2.1 by enabling learners to explore relationships through physical manipulation and to externalise their ideas in the form of tangible, directly modifiable artefacts [6].

2.4 Design Factors for TUI

wie müssen tuis gestaltet sein generell und auf kinder bezogen

2.4.1 Coupling Objects with Digital Information

(But how does digital information become linked to physical objects? And what format can this link be presented? Ullmer and Ishii answer these questions by providing an overview of the various types of digital bindings,coupling methods and approaches to physical representation [19].

Ullmer and Ishii provide an overview of various types of represented digital information, coupling methods and approaches to physical representation in order to describe the coupling between phicons and digital information

Types of Represented Digital Information

A phicon in a **TUI** can represent different kinds of digital information. These include *static media*, such as images and three-dimensional models, *dynamic content*, such as video streams or computationally generated graphics, and *digital attributes*, including colours or material properties. Within a TUI, a physical object does not necessarily correspond to a single digital file but can have different digital meanings. For example, a physical figure placed on an audio player may represent an entire audiobook, while another object may control playback. To the user, these objects represent a story or an action rather than the underlying files and computational processes. What matters most is therefore the meaning of an object and the actions associated with it [19].

Methods of Coupling

In addition to the different types of information represented, coupling methods serve to categorise how and when the relationship between a phicon and its digital representation is formed:

- In *static coupling*, the meaning of an object is defined in advance. The physical object is permanently associated with a specific digital geometry, property or function, and this association cannot be altered during interaction.
- By contrast, a *dynamic coupling* is established or modified during use. For instance, inserting a Phicon into a specific slot or performing an action within a graphical user interface can associate it with new digital content or alter its existing assignment.
- *Interactive coupling* occurs when the meaning of an object changes depending on the other objects with which it is connected or combined.

Static coupling therefore provide a stable and often more easily understandable meaning, whereas *dynamic* and *interactive coupling* enable the same physical objects to be used more flexibly. Regardless of which coupling method is used, it is esssential for the system that changes to the physical object are reflected immediately transparently in the digital representation. If this correspondence is delayed, missing or inconsistent, the relationship between the physical and digital representations becomes difficult to understand [19].

Approaches to Physical Representation

Not only the temporal precision of coupling influences how clearly its digital meaning and potential interactions can be understood but also the appearance of it. There are four approaches to choose from, which are presented in Table 3. These approaches are not necessarily mutually exclusive and may be combined within a single system[19].

Approach	Description	Illustrative Example
Found objects	Existing objects augmented with technology and placed in a new digital context	A sensor-equipped toy car moved across a table to control a digital vehicle
Engineering-driven	Physical form determined by electronic and mechanical requirements	Appearance of a prototype determined by its electronic components
Design-driven	Physical form designed to communicate meaning and indicate possible interactions	Tokens shaped like musical instruments to select the corresponding digital sounds
Work-practice-based	design based on existing physical artefacts from specific professional or application contexts	Digitally tagged library cards retain the familiar process of assigning borrowed books to individual users

Table 3: *Approaches to physical representation in a **TUI** [19]*

Conclusion ?? vlt gesammt am ende von level2 kapitel

The coupling between physical objects and digital information can differ in content, flexibility, and physical representation. Selecting an appropriate approach therefore requires a careful consideration of the intended users and their abilities, as well as the specific application context. Regardless of the chosen approach, an effective TUI requires a clear and immediately perceptible relationship between the phiconand the associated digital meaning. The design of this coupling therefore directly influences the system's comprehensibility, usability, and flexibility.

2.4.2 The *Token and Constraint* Framework

Once digital information has been assigned to a phicon, it must be determined how this object can be physically arranged and how changes in its configuration can be translated into digital operations [18].

One approach to structuring tangible interaction is the *Token and Constraint* framework. The discrete physical objects that represent digital information are referred to as *tokens* within this framework. They correspond to the physical representations previously introduced as *phicons*. However, the term *token* is retained in this section to remain consistent with the framework's original terminology. *Tokens* are placed or manipulated within physical structures known as constraints. These constraints define where and how a token can be positioned or moved and are mapped to specific digital operations [18].

Phases of Interaction

The Interaction within *Token and Constraint* systems can involve two phases: *Associate* and *Manipulate*: During the *Associate* phase a *token* is placed within a constraint, thereby establishing a logical relationship between the information represented by the *token* and the operation assigned to the constraint. This initially creates a discrete state, such as presence or absence, activation or deactivation, or selection and deselection. The same *token* may be inserted into different constraints in order to associate its digital information with different predefined operations [18].

The *Manipulate* phase starts once the *token* has been physically engaged with the *constraint*. The *token* can now be moved within the *constraint*'s mechanical boundaries to modify parameters of the associated operation. The absolute and relative positions of *tokens*, both in relation to the *constraint* and to one another, can result in different digital interpretations. The meaning of an interaction therefore emerges from the interplay between the *token*, the *constraint*, and the overall physical configuration. Translating or rotating of the *token* may result for example in the continuous

adjustment of a value, the navigation through a list, or the alteration of another variable of the digital system. However, not every *Token and Constraint* system needs to support both phases of interaction since in some systems, inserting and removing a *token* may already constitute the complete interaction [18].

Physical Syntax and Interaction Guidance

Physical constraints influence not only the digital interpretation of an action but also its haptic and perceptual qualities, since the physical syntax renders some of the available interaction possibilities directly perceivable. In this context, syntax refers to the rules according to which individual phicons can be combined to form an input that can be meaningfully interpreted by the system. The configuration and mechanical configuration of the constraints function as a physical grammar by directly indicating which actions are possible and which are prevented. This supports the creation of physical configurations that are interpretable both by the user and by the underlying computational system. By reducing the range of possible manipulations, invalid states can be avoided and the available courses of action can be made easier to understand [18].




Figure 2: Interaction phases and physical syntax within the Token and Constraint framework

Styles of Mapping

Mapping styles describe how the resulting physical configuration is translated into a computer-interpretable representation. Three principal styles can be distinguished: *spatial*, *relational* and *constructive* mapping.

- In the *spatial mapping*, interpretation is based on the geometric position, distance, or orientation of phicons in the physical space. The pivotal factor, therefore, is the object's position within a spatial frame of reference.
- In the context of *relational mapping*, the absolute position of a phicon is less significant than its relationship to other phicons or to a particular *constraint*. The digital interpretation may therefore depend on properties such as sequence, proximity, adjacency, or assignment.
- In *constructive mapping*, the digital meaning of a given structure is derived from the manner in which several physical components are assembled into a larger structure. The interpretation is therefore not based on a single element, but rather on the resulting overall physical structure.

These mapping styles are not mutually exclusive and may be combined within a single **TUI**. An assembled structure may for example be interpreted based on both the connections between its components and their spatial positions or orientations [18].

Conclusion

The *Token and Constraint* framework demonstrates how physical actions can be translated into comprehensible digital operations. *Tokens* enable direct manipulation, while constraints guide interaction and prevent invalid configurations. These characteristics can support constructivist and constructionist learning by enabling structured exploration and making the consequences of physical actions observable. However, their educational value ultimately depends on the design of the learning task.

2.4.3 Child appropriate TUIs in the Field of Special Education

Whether a **TUI** is perceived as accessible, exploratory, and supportive of learning depends not only on its general design, but also on its adaptation to the specific needs of children. A literature review of TUIs for children's creative learning highlights the factors of abstractness, openness, richness and complexity, as well as a smooth experience. Since these factors were also not specifically formulated for students with a special educational focus, they are discussed below with consideration of the heterogeneous learning abilities and conditions for action within the defined target group [13].

Abstractness

The factor of *Abstractness* describes how concrete or ambiguous the meaning of a phicon is designed to be. While abstract and not fully predetermined representations can promote imagination and divergent thinking, an overly abstract design can lead to confusion, particularly among children without the required prior knowledge or additional explanation. The choice of physical representation and the manner in which it is coupled with digital information, explained in Section 2.4.1, therefore directly influence how comprehensible the meaning of the phicon is perceived to be [13].

For students within the selected special educational focus, a balance between abstraction and clarity is therefore required. Phicons should provide sufficient indications of their function and possible use, but at the same time, the design should not be unnecessarily simplified or infantilising, so that it still provides sufficient depth for exploration [1], [2], [3].

Openness

Openness defines the scope that a TUI provides for individual actions, solution strategies, and interpretations and is indirectly influenced by the number and restrictiveness of its physical *constraints* (Section 2.4.2). While excessive instruction can restrict creativity, insufficient support or scaffolding often leads to frustration [13].

For students with a special educational focus on **GE**, **LE** and **ASD** *structured Openness* is particularly relevant. Clear intermediate goals can prevent children from becoming overwhelmed. When these are supplemented by step-by-step support that is adapted to the individual learner's current level and can be reduced as confidence increases, a comprehensible framework for action is created without providing excessive instruction [1], [2], [3].

Richness and Complexity

While *Richness* refers to the variety of possible content, actions, and combinations within a system, *Complexity* describes the demands that arise from this variety. A design that is too simple does not provide sufficient inspiration, whereas overly complex interfaces can overwhelm children. The system should support children in overcoming difficulties independently without removing the challenge entirely [13].

Due to the different learning conditions associated with the considered support needs, the complexity of the **TUI** should not be reduced uniformly but should instead be individually adaptable. Different levels of difficulty can be designed to introduce new content and possibilities for action

gradually. The objective should therefore not be to create the simplest possible design, but to provide an appropriate level of challenge for each child [1], [2], [3].

Smooth Experience

Faulty hardware or software can severely impair the learning experience. Unreliable systems make children feel uncertain and discourage them from learning from mistakes or taking risks, particularly when it is not clearly recognisable whether an error was caused by the system or by their own actions [13].

For students with special educational needs, this can considerably reduce both motivation and confidence in acting independently. The in Section 2.5 described Feedback should therefore be reliable, immediate, and clearly attributable. Multimodal feedback can provide access through different perceptual channels, but its intensity and quantity must remain limited or adaptable in order to prevent unnecessary sensory overload [1], [2], [3].

The factors discussed above originate from the literature review on **TUI** for children's creative learning. Based on the learning needs of students within the considered areas of special educational support, two additional factors are proposed: *Adaptability* and *Multimodal Accessibility*.

Adaptability

Adaptability describes the extent to which a TUI can be adjusted to learners' individual abilities and needs. Task difficulty, pace and level of suuport should be configurable without changing the fundamental interaction concept. Such adaptations can provide sufficient guidance while allowing learners to work as independently as possible [1], [2], [3].

Multimodal Accessibility

Multimodal Accessibility requires relevant information and feedback to be available through more than one perceptual channel. Information should therefore not be communicated exclusively through text, colour, or sound, as each of these may create barriers for individual learners. But combining those modes can provide alternative means of access. However, the number and intensity of stimuli should remain adaptable to avoid sensory overload [4].

Teachers

For use in schools, the requirements of teachers must also be considered, and teachers should be included as stakeholders in the TUI design process. Nevertheless, the system should be usable without programming knowledge or time-consuming calibration. Tasks must be easy to select and understand, the components must be transportable, and the system must be capable of being set up with minimal preparation time [13]:

ABBILDUNG DREIECK?

Conclusion

The Design Factors show that there is no universally child-appropriate TUI. Its suitability depends on how well the interaction design responds to individual abilities, support needs, and sensory preferences. The central design challenge is therefore to provide sufficient structure and accessibility without unnecessarily restricting independent exploration.

2.5 Feedback for TUI

In a **TUI**, feedback informs users whether an action has been detected, how it has been interpreted, and how it has affected the state of the system. It thereby closes the perception action loop between physical manipulation and digital processing and supports the independent use of the system.

2.5.1 Feedback Modalities

As shown in Table 4, a system can communicate the consequences of an action through different output modalities. The physical properties of a **TUI** already provide automatically intrinsic feedback that arises directly from manipulating its objects. Additional system-generated feedback may be presented visually, auditorily, haptically, or through a coordinated combination of these modalities. This multimodal feedback does not imply presenting as many signals as possible simultaneously since this may cause sensory overload. Instead, different modalities should offer alternative ways of accessing the same or complementary information, which can then be combined when a perceptual channel cannot be used, or can only be used to a limited extent.

Regardless of its modality, feedback can also be characterised along several dimensions:
- Local or global: presented directly at the manipulated object or through a separate display
- Discrete or continuous: confirming an individual event or continuously indicating a state
- Immediate or delayed: responding directly to an action or providing a later summary
- Persistent or transient: remaining available until a correction is made or disappearing after a short period

Feedback Form	Function	Examples
Intrinsic	Provides information arising directly from the physical action	Mechanical resistance, form fit, or snapping into place
Visual	Communicates states, errors, and changes visually	LEDs, displays, projections, or animations
Auditory	Attracts attention and communicates information autitory	Sounds, signals, or spoken information
Haptic	Makes system responses physically perceptible	Vibration, movement, or force feedback
Multimodal	Provides complementary or alternative access through different perceptual channels	Coordinated combinations of visual, auditory, or haptic signals

Table 4: *Feedback modalities in tangible user interfaces*

2.5.2 Feedback learning TUI

In learning-oriented **TUI**, two levels of feedback should be distinguished:
- *Interaction feedback* communicates whether and how a physical action has been technically detected and processed
- *Pedagogical feedback* evaluates the action or its outcome in relation to the learning task

A system may therefore detect an action correctly while evaluating it as incorrect in relation to the task. Conversely, a failure to detect an action must not be presented as an error made by the learner. Reliable interaction feedback is therefore a prerequisite for meaningful pedagogical feedback.

Interaction Feedback

Interaction Feedback makes the technical response of the system comprehensible. It should indicate wheter a physical action has been detected and interpreted correctly or not. If an action cannot be processed, the system should immediately distinguish a technical recognition problem from an incorrect solution to the learning task. Otherwise, learners may incorrectly attribute system failures to their own actions and become uncertain about how to proceed.

Pedagogical Feedback

While *interaction feedback* primarily confirms whether an action has been technically processed, *pedagogical feedback* concerns the meaning of that action within the learning process. It supports learners in assesing their current progress and recognising deviations from the intended outcome to adapt their subsequent actions.

Pedagogical feedback can fulfil different functions:
- Outcome feedback indicates whether a result is correct or incorrect.
- Process feedback provides information about the approach taken or a possible cause of error.
- Feedforward offers guidance for the next step.
- Progress feedback indicates what has already been achieved

Additionally, as it would restrict independent planning and problem-solving, the system should not prescribe every step, but provide graduated feedback, in which support increases according to the learner's needs. This preserves opportunities for independent error analysis while preventing learners from becoming unable to continue because the feedback is insufficient or incomprehensible.

Criteria for Effective Feedback/design factors for children

The effectiveness of feedback depends not only on its technical form but, more importantly, on whether it is understandable and relevant to the user's subsequent actions. Effective feedback should therefore meet the following criteria:

- Timeliness: Feedback should occur in a recognisable temporal relationship to the action that triggered it. If it is delayed, users may no longer be able to identify its cause
- Clarity: It should be evident which action, object, or system state the feedback refers to
- Consistency: Similar states and events should be represented by consistent signals Colours, sounds, and symbols should not change their meaning without a comprehensible reason.
- Perceptibility: Feedback should be sufficiently noticeable without obscuring other relevant information
- Proportionality: The intensity and extent of feedback should correspond to the significance of the event. A routine confirmation, for example, should be less prominent than a critical error message
- Actionability: Feedback should not only communicate the current state but, where necessary, also indicate how the interaction can be continued or corrected

Gerade bei unterschiedlichen sensorischen, kognitiven und kommunikativen Voraussetzungen sind anpassbare und redundante Rückmeldungen relevant.

MEHR AUF FÖRDERSCHWERPUNKT EINGEHEN

2.5.3 Conclusion

2.6 Potentials of TUIs for children (with dissorders) (liang)

ÜBERGANG - stellt eigentlich end conclusio des theorethischen backgrounds dar

Research attributes various potentials to TUIs for children's learning. However, since these findings often originate from studies involving children without specifically identified special educational support needs, they cannot be transferred without qualification to students in the areas of intellectual development, learning, and autism. The following potentials are therefore considered in an extended manner that takes into account the target-group-specific conditions and ?the shared learning objectives defined in the introduction.?

2.6.1 Supporting Novices through Scaffolding and Accessibility

Kompetenzbereich By representing complex technical details in a simplified manner through phicons, tangible user interfaces can translate abstract and complex technical processes into directly perceivable actions and thereby lower the knowledge threshold required for interaction. The use of familiar objects and physically comprehensible actions, such as grasping or matching, can facilitate access to complex content, particularly for novices, and reduce cognitive load.

?This can be especially relevant for students who require support with memory, concept formation, or the structuring of actions?. However, for children with the considered support needs, the meaning of an object and the actions it enables must be clearly recognisable, as physical properties may otherwise create expectations that do not correspond to the object's digital function. Clearly distinguishable objects and structured, manageable interaction possibilities are therefore required. Possible motor, visual, auditory, or communicative impairments must also be considered, and information should be accessible through alternative perceptual channels. But, this multimodality does not mean presenting as many stimuli as possible simultaneously, but rather providing equivalent and individually adaptable forms of access.

2.6.2 Playful Exploration and Error-Tolerant Learning

Kompetenzbereich In accordance with the principles of constructionism (bezug), familiar objects not only facilitate initial access but can also create a protected environment in which children are able to experiment without fear of risk or failure. When actions can easily be reversed and errors do not result in lasting negative consequences, autonomous and exploratory experimentation becomes possible. Different solution strategies can then be tested through trial and error. This may also lead to approaches that extend beyond predefined instructions and encourage the development of independent solutions.

However, a large number of simultaneously available options can make orientation more difficult and lead to cognitive overload for students in the selected special educational focus areas. Structured exploration is therefore appropriate, in which clear intermediate goals, limited choices, and gradual assistance provide a comprehensible framework for action. Errors should not remain unnoticed but should be communicated immediately and unambiguously without fully prescribing the subsequent course of action, as this could otherwise lead to confusion and frustration. Sufficient processing time, repeatable action sequences, and individually adaptable support enable learners to complete tasks at their own pace.

2.6.3 Promoting Initiative and Motivation

Kompetenzbereich Exploratory activity creates opportunities for learners to develop personal ideas and creative solution strategies. As explicitly emphasised in constructionism, children shift from being recipients of information to becoming active creators and can thereby express their individual ideas, preferences, and emotional states. The immediate relationship between their own actions and a perceptible effect can support experiences of autonomy and competence.

For learners with different support needs, however, the available choices must remain comprehensible, manageable, and adapted to their individual abilities. Achievable intermediate goals and visible learning progress can help to reduce uncertainty and repeated experiences of failure.

2.6.4 Supporting Cognitive Development and Spatial Learning

Kompetenzbereich To enable children to concentrate on experimenting with new elements, the possible range of actions can be restricted through a token-and-constraint system. As described previously, such systems make part of the interaction rules perceptible through their physical form

and arrangement. Consequently, not all possible action sequences need to be remembered and processed mentally, which can reduce the cognitive demands placed on the learner. The manipulation of tangible objects also combines visual perception with haptic and motor experiences and thereby relates to the theory of embodied cognition (bezug). Actions such as grasping, rotating, and spatially arranging objects can help learners physically comprehend positions, orientations, and relationships. This may support spatial awareness and the ability to form mental spatial representations.

For learners with the considered support needs, these characteristics can particularly support the recognition of relationships and the development of problem-solving abilities. However, the number and complexity of spatial relationships should be adapted to the individual learner's current level and expanded gradually.

2.6.5 Promoting Communication and Collaboration

Kompetenzbereich The possibility of space multiplexing described in (bezug) can also benefit children. The simultaneous and shared manipulation of objects in physical space can naturally encourage cooperation and mutual inspiration. Ideas that are difficult to express verbally can be demonstrated, explained, and discussed through the constructions that have been created. Due to the physical nature of the interaction, TUIs can therefore provide a shared point of reference for learning in groups.

This may be particularly relevant for learners who use augmentative and alternative communication or whose receptive and expressive language abilities differ. In addition to spoken language, gestures, pointing, and other communication aids can be incorporated into the interaction.

TUIs can therefore support concrete and accessible learning activities, structured exploration, personal initiative, spatial and cognitive processes, as well as communication and collaboration. They are particularly relevant for learning with children because they support learning through embodied interaction and physical movement, which can contribute to children's thinking and understanding (Pookkottuvariam, p. 2). However, these potentials can only be realised when children's individual motor, sensory, cognitive, and communicative needs are systematically considered throughout the design process.

FAZIT FIGURE/TABELLE die die potenziale und gestaltungsfaktoren und vlt auch kompetenzen vereint

3 Requirements Analysis

The requirements analysis translates the findings from the theoretical background and the design principles derived from the special educational context into concrete requirements for the prototype. Following a constructionist approach, the objective is to develop a modular, cube-based **TUI** in the form of a learning game suitable for use in special education. The prototype is intended to enable students to complete three-dimensional construction tasks independently while receiving immediate feedback on whether their construction corresponds to the target structure or not.

The requirements are derived from three perspectives:
- The learning prerequisites of the target group and the resulting educational implications
- The characteristics and design principles of tangible user interfaces discussed in the theoretical background
- The technical, financial, and time constraints of prototype development

The following sections describe the context of use, the application scenario, and the core requirements guiding the system's design and development.

3.1 Context of Use and Didactic Application Scenario

The primary target group consists of students with special educational needs related to **GE**, **LE**, and **ASD**. Teachers and other educational professionals represent a further key stakeholder group, as they integrate the learning game into classroom activities and support the learning process.

By enabling students to complete three-dimensional construction tasks independently, the learning game is intended to address the following competencies:
- Primary: spatial thinking, action planning, and self-directed learning
- Secondary: problem-solving, error detection, and self-correction
- Additional: fine motor skills, concentration, and hand–eye coordination

The primary application scenario is a spatial reconstruction task, where students select a three-dimensional target structure appropriate to their individual level and attempt to recreate it using the available bricks. Although this type of task can also be carried out using conventional construction materials, the proposed system extends the building process through automated feedback and can indicate whether the construction is correct or needs to be modified. selbstständiges bearbeiten

The level of difficulty can be varied through the number of bricks, their spatial arrangement and the required rotations. Simple tasks may consist of a small number of bricks connected primarily in a linear arrangement, whereas more challenging tasks may involve multiple spatial directions, different orientations, and branching structures. Future task types could include completing unfinished structures, identifying incorrect connections, or constructing freely without a predefined target.

3.2 Pedagogical and Interaction-related Requirements

In accordance with the constructionist understanding of learning described in Chapter Section 2.1.3, the active creation of a physical artefact must form the core of the learning activity [TASK1] . Learners must be able to observe, inspect, and directly modify the emerging construction throughout the task [IA1] . This enables them to translate their mental representation into a concrete spatial structure through which the effects of individual actions become observable. To support independent use, the system must also be operable without technical or programming knowledge and without requiring recalibration [IA2] .

At the same time, the tasks must must accommodate the diverse learning prerequisites of the target group and thus provide a clear and manageable framework for action [IA3] , without describing every individual action. Processes and sub-goals must be presented in a way that is easy to follow, whilst allowing sufficient time for completion [IA4] and opportunities for repetition [IA5] .

The design factors described in Section 2.4.3 must also be considered. The principle of *structured openness* requires tasks to provide a clear framework while allowing learners to explore different approaches and solution attempts [TUI1] . Tasks must be structured in such a way that the objective remains clear and step-by-step guidance can be accessed where necessary. The factors of *richness*, *complexity*, and *adaptability* further require the learning game to accommodate different levels of ability. This can be achieved by adapting the level of difficulty and scope of the feedback to different learning requirements as far as possible, so that the same basic principle of interaction can be applied to tasks of varying difficulty levels [TUI2] . Finally, the bricks must provide sufficiently clear physical cues for learners to understand their meaning and possible uses. Their physical design and digital functions must therefore be consistently aligned [TUI3] .

ID	Requirement
TASK1	The task must be completed through the active construction and modification of a physical artefact
IA1	The resulting construction must remain visible, inspectable, and modifiable throughout the task
IA2	The system must be usable without technical or programming knowledge and without requiring recalibration
IA3	The objective and structure of the task must be presented clearly and comprehensibly
IA4	Learners must be able to complete the task at their own pace
IA5	Previously completed action steps must be correctable and repeatable
TUI1	The task should provide a structured framework while allowing different approaches and solution attempts within that framework
TUI2	The level of difficulty should be adaptable by varying the number of bricks, their spatial arrangement, and the required rotations
TUI3	The physical design of the bricks and their digital functions must be consistently aligned

Table 5: *Educational and interaction related requirements*

3.3 Requirements for Feedback and Assistance

To complete a construction task independently, learners must be able to determine whether their actions have been detected by the system and how those actions are evaluated within the learning task. In accordance with the distinction introduced in Section 2.5.2, the system must therefore provide both interaction feedback and pedagogical feedback [FB1] . Each feedback signal must be clearly attributable to the action that triggered it or to the affected part of the construction, allowing learners to understand what it refers to [FB2] . In this context, feedback and assistance should be available in graduated levels according to the learner's individual support needs [FB3] , [FB4] . As discussed in relation to multimodal accessibility in Section 2.4.3, providing feedback through multiple output modalities can improve accessibility which is therefore diserable [IA6] . But, when multiple modalities are used, their signals must be coordinated and consistent in order to avoid distraction.

ID	Requirement
FB1	Interaction and educational feedback must be ensured
FB2	Feedback must be clearly linked to the action that triggered it or the area concerned
FB3	Feedback should be provided on a tiered basis, je nachdem ob der fehler schon mit weniger feedback ausgebessert werden kann
FB4	Assistance should be provided on a tiered basis, depending on the learners level
IA6	Feedback can be provided through multiple output modalities

Table 6: *Requirements for feedback and assistance*

3.4 Geometrical and Ergonomic Requirements

ID	Requirement
G1	The body of the cube must be based on a square base
G2	One cube type must be a cube shaped cube with six sides/faces
G3	Other cube types could also be implemented in other geometric shapes
C1	Each cube must have at least one defined docking side where to connect with other cubes (Docking side = the side via which the building block can connect to another building block)
C2	Other cubes must be able to connect with the cube via its remaining sides
C3	The cubes must be able to be arranged or stacked in three dimensions
C4	The cubes must be able to be positioned relative to one another in different orientations
C5	The cubes must be graspable and connected with one hand
C6	Cube connections must be strong enough to hold the structure together and easy enough to disconnect with minimal effort

Table 7: *Physical design requirements*

The building blocks form the central element of the learning game: They serve as physical representations of digital information while simultaneously functioning as controls for interacting with the system (phicons). Their geometric and mechanical design therefore influences both the range of possible constructions and the comprehensibility and accessibility of the interaction. As already established by the educational requirements, the shape and connection mechanisms must clearly indicate how and where the blocks can be connected [TUI3] .

For the prototype, each building block must have a square base [G1] , enabling the implementation of a cubic block with six square faces [G2] . Additional block types could subsequently be implemented using other geometric forms [G3] . Each block must have one defined docking face through which it connects to another block [C1] . The remaining faces serve as receiving connection faces to which additional blocks can be attached using their respective docking faces [C2] . This arrangement enables branching three-dimensional constructions along clearly defined directions while limiting the complexity of manufacturing and connection detection [C3] . The square faces also allow blocks to be connected in rotations of 90-degree increments [C4] .

In order to hold the structure together, the connection between the building blocks must be stable enough to be undone with minimal effort, while also being strong enough to be created without

requiring precise positioning that demands fine motor skills [C6] . In addition, each block must be capable of being securely grasped, positioned, and connected using one hand [C5] .

3.5 Functional Requirements for Detection

The functional requirements define which information the system must detect and process in order to reconstruct the physical three-dimensional structure digitally: Each building block must be uniquely identifiable to enable reliable construction detection and targeted feedback [DET1] . In addition, the system must also determine which blocks are connected, through which faces they are connected [DET2] , and how they are oriented relative to one another [DET3] . Only by combining these relationships can the system reconstruct the complete spatial configuration and compare it with the target structure [DET4] . This functionality should remain reliable when multiple blocks are connected simultaneously within a larger construction [DET5] . To prevent the system from providing misleading information to users, ambiguous or contradictory configurations should be recognised as error states [DET6] .

ID	Requirement
DET1	the system must be able to uniquely detect each cube
DET2	the system must be able to detect which cubes are connected with each other and on what side the connection occurs
DET3	the system must be able to detect the relative rotation of a two cubes in relation each other
DET4	the system must be able to compare the detected cube structure with a target structure
DET5	The system should continue to operate reliably even when multiple cubes are connected simultaneously
DET6	Configurations that cannot be clearly identified or are contradictory should be reported as technical faults
DET7	Connections and changes to the structure must be detected reliably and within a short time of max. 550ms

Table 8: *requirements for the construction detection*

The maximum response time of 550 ms, which has been specified for detecting changes to the design, is initially a target value [DET7] . It is intended to ensure that an action and the resulting feedback are perceived as belonging together.

3.6 Electrical and Technical Requirements

The technical implementation should be as simple, modular, and low-maintenance as possible, with individual components remaining replaceable at reasonable effort. To reduce maintenance requirements and avoid the need to charge multiple devices separately, the building blocks must operate without individual batteries or rechargeable power sources [EL1] . For the initial proof of concept, the prototype should include at least ten building blocks, as this number is sufficient to demonstrate multi-part and spatially branching constructions [EL2] . In the future, the system should be expandable with additional blocks without requiring changes to its fundamental operating principle [EL3] .

ID	Requirement
EL1	The cubes must be operated without their own battery or individual rechargeable battery
EL2	The system must consist of at least 10 cubes
EL3	the system should be extendable without changing any basic operating principles

Table 9: *Electrical and technical requirements*

3.7 Safety and Economic Requirements

The prototype is not a certified toy and may therefore only be used under supervision. Nevertheless, potential risks must already be reduced through the physical design and electronic components and potentially detachable small parts must be enclosed and protected against direct access [S2] . The building blocks must also withstand repeated grasping, connecting, and disconnecting [S1] . In addition, each block should be easy to assemble and disassemble without damaging its components [S3] . The cost per building block should preferably remain between one and three euros. However, the total system cost cannot yet be determined precisely, as it also depends on the base station, control electronics, and potential output devices [EC1] .

ID	Requirement
S1	The cubes must be able to withstand repeated gripping, connecting and disconnecting
S2	Electronic components and small parts that could come loose must be protected from direct access by the cube housing
S3	the cubes should be assembled and disassembled easily without being distroyed
EC1	The total cost of a brick should not exceed 3 euros

Table 10: *safety and Economic requirements*

4 Concept Development

This chapter presents the solutions selected for the proposed system and explains how they address the requirements established in the preceding requirements analysis. At this stage, the requirements serve as design criteria for developing and justifying the system concept. Whether they are actually fulfilled can only be determined after implementation and is therefore assessed in the evaluation chapter (Bezug).

4.1 Design Basis and Concept Objective

The requirements analysis conducted in Section 3 provides the foundation for the system concept. The objective of the concept development is to translate the individual pedagogical, interaction-related, functional, mechanical and technical requirements into a coherent overall system.

The concept development covers five closely related areas:

- The physical design of the building bricks and their connections (kapitel)
- The electronic detection of physical connections and the central distribution of power (kapitel)
- The communication and transfer of construction data and the digital reconstruction of the physical structure (kapitel)
- The design of the task and interaction (kapitel)
- The visualisation and feedback principles (kapitel)

Together, these areas define how physical construction activities are connected with digital processing and feedback.

4.2 Usage Scenario

The usage scenario describes the general sequence of a guided construction task from the learners perspective:

At the beginning, a target structure is selected from a predefined variety of tasks in the learning application and presented as a reference. It is selected either by the teacher or, where appropriate for the learning context, by the learner itself. Afterwards, the learner begins connecting the first cube to the baseplate followed by adding further cubes until the specified target structure has been reconstructed. Already completed steps keep being able to be modified as cubes can be detached, repositioned and reconnected at any point during the task. Following each modification, the system detects the current physical configuration and updates its digital representation, which is then compared with the target and, depending on whether it is correct, may result in one of two outcomes: If the current configuration constitutes a valid part of the target structure, the learner can continue with the next construction step. But if a deviation is detected, the system provides corresponding feedback so that the affected step can be reviewed and corrected. The task is completed once the physical construction fully matches the target structure. It can then either be repeated or a new target structure is selected.

The task is completed at the learner's individual pace and does not impose a fixed time limit. Additionaly, a specific construction sequence is required only where it follows necessarily from the spatial dependencies of the target structure.

Throughout the process, the teacher retains responsibility for the pedagogical guidance of the learner and can adapt the available selection of tasks or provide additional explanations if the feedback or assistance offered by the system is insufficient or not understood. Automated feedback is therefore intended to support the teacher during periods of independent work and should not replace individual pedagogical guidance.

SCHREIBEN DASS DAS DIAGRAMM NUR EINE AUFGABE BESCHREIBT UND ES BEENDET IST SOBALD SIE FERTIG IST



Figure 3: task flow, Ablaufdiagramm

4.2.1 Functional Structure

Based on the described usage scenario, the general functions that need to be provided in order to carry out the construction task are derived. The functional structure shown in Figure x initially describes these tasks independently of their subsequent technical implementation

FUNKTIONSDIAGRAMM whats app

The individual system functions can be assigned to five functional areas (TABELLE?):

1. Physical Design and Connection Subsystem: provision of the physical building bricks, housings, mechanical connections
2. Electronic Detection and Power Subsystem: identification of individual building bricks, detection of connections and relative rotations, provision of the central power supply
3. Data, Communication and Software Subsystem: transmission of the detected structural data, generation of a digital structure model, spatial reconstruction of the physical construction
4. Task and Interaction Subsystem: selection and presentation of the target structure, provision of the basic task workflow
5. Visualisation and Feedback Subsystem: comparison of the detected and target structures, visualisation of the current construction, generation and output of feedback

The functional structure emphasises that a physical action cannot be interpreted directly by the learning application. Instead, the connection must first be established mehcannícally and detected electronically before its local connection data is transformed into a digital model of the overall structure. Only once this model is available, the learning application can compare the detected construction with the selected target structure and generate task related feedback.

4.3 Overall System Architecture

The System Architecture assigns the in the functional structure described systems functions to the components of the overall system. The technical system consists of

- Several active bricks
- One baseplate
- One digital computer based learning application

Learners and pedagogical professionals are external actors and therefore not part of the technical system components

4.3.1 System Components and Responsibilities

Table Table 11 provides an overview of components of the overall system and their primary responsibilities within the overall system

Element	Classification	Primary Responsibility
Learner	External actor	Select the target structure, assemble the current physical structure, respond to feedback
Teacher	External actor	Adapts the selection of tasks, guides the learning process, provides additional support
Building bricks	Technical component	Form the physical construction, provide local connection data, present local feedback
Baseplate	Technical component	Provide the starting point and central power supply, mediate between the building-brick system and the learning application
Learning application	Technical component	Provide the target structure, process structural data, visualise the current construction, compare it with the target structure, generate feedback

Table 11: *System Components and Responsibilities*



Figure 4: DIAGRAMM: konzeptionelle Systemarchitektur mit User, Smart Cube System und Learning application

4.4 Conceptual definition of the levels of connection

To describe the system unambiguously, a distinction is made between the terminology used at the mechanical, electronic, and logical connection levels: Each building brick has one docking face through which it is connected to the existing construction and, depending on its type, one or more receiving faces to which further building bricks can be attached. The docking face contains the electronic upstream interface, whereas each receiving face contains a downstream interface. In the

digital model, the building brick already connected to the system is represented by the parent node, while the newly added building brick is represented by the child node. A connection can therefore be described at the three levels presented in the following Table Table 12:

Level	Term	Definition
Mechanics	Connection face	General term for all physical building-brick faces through which a connection can be established
Mechanics	Docking face and Receiving face	Connection faces of the building bricks
Electronics	Upstream and downstream interface	Electrical contacts located on the connection faces
Data model	Parent and child nodes	Directed relationship within the digital tree
Data model	Parent brick	Building brick that is already connected to the system
Data model	Child brick	Building brick whose docking face is connected to a receiving face of the parent brick

Table 12: *Terminology across the connection levels*

4.5 Physical Design and Connection Subsystem

- Im Folgenden werden gemäß der Begriffsdefinition in Abschnitt X.3.3 die Bezeichnungen Andockseite und Aufnahmeseite verwendet.

Das Kapitel beschreibt:
- Grundformen und Abmessungen der Bausteine
- gerichtete Gestaltung der Verbindungsseiten
- mechanisches Verbindungsprinzip
- ergonomische Gestaltung
- Gehäuse- und Wartungskonzept
- mechanischen Aufbau der Baseplate

4.5.1 Basic Geometry and Block Types

In accordance with requirement [G1] , the connection faces of all building bricks have a square geometry with standardised dimensions. This geometry permits a rotationally symmetrical contact arrangement and allows four mechanically valid orientations in increments of 90°. It therefore ensures compatibility between different brick types and provides the mechanical basis for the electronic detection of relative rotation required by [C4] . Based on the standardised connection geometry, two building-brick types are defined in accordance with [G3]
- The *cube brick* wth six square connection faces, as specified by [G2]
- The *smashed brick* with two opposing square connection faces, while its remaining faces cannot be used to establish connections

Whereas the cube brick supports linear as well as branched two- and three-dimensional constructions along its three mutually orthogonal spatial axes, the flat brick permits only linear connections along its local z-axis. Figure X illustrates the two brick types and an example of a physical construction.

For the square connection faces a side lenght of approximately 40mm is specified. The selected dimension represents a compromise between the one-handed grasping and positioning required by [C5] and the internal space needed for electrical contacts and electronic components. Whether the chosen size is in fact ergonomically suitable is assessed in Chapter (EVALUATION).

The consistent brick geometry also establishes a direct visual correspondence between the physical building bricks and conventional construction bricks such as ?LEGO or ?. The implications of the physical–digital correspondence for interaction are discussed in Section ???.



Figure 1: Würfeltypen (physisch)



Figure 2: Beispiel Konstruktion (physisch)

Directed Design of the Connection Faces

As required by requirement [C1] and [C2] , each building brick has exactly one *Docking face* and at least one *Receiving face* depending on the type. To identify the intended target connection and orientation between two bricks, the *Receiving faces* are differentiated by colour. This directed design provides the physical basis for representing the resulting construction as a parent child structure. The corresponding digital structure model is described in Section 4.7.2.

?A valid mechanical connection can only be established between a *Receiving face* of the parent brick and the *Docking face* of the child brick, wie es mechanisch umgesetzt wird, wird im nächsten kapitel beschrieben?

Mechanical Connection Principle

The mechanical connection principle was selected with regard to stability, unambiguous alignment, and the low operating force specified by [C6] . For the prototype a combination of a mechanical form fit mechanism and magnetic assistance is used: The docking face contains recessed guiding elements, while the receiving faces contain corresponding protruding elements. This is supplemented by magnets which are positioned on every interface type but with complementary polarities.

This guiding geometry determines which interface types can be connected and aligns their electrical contact areas. The magnets assist this approach and also stabilise the resulting connection without requiring the force associated with a conventional snap-fit mechanism. Together, these elements form a mechanical constraint as described in Section 2.4.2: Incompatible connections are impeded because the interface geometries do not fit or the equally polarised magnets repel one another. The available connection possibilities are therefore partly conveyed through the physical design itself.

The mechanical and magnetic engagement also produces intrinsic haptic feedback, allowing learners to perceive immediately that two faces have been physically connected. However, this feedback only confirms the mechanical connection and does not indicate whether the connection has been detected electronically or not. The relationship between intrinsic feedback and system-generated feedback is discussed in Section 4.9.

4.5.2 Housing and Maintainability

The housing must completely enclose the electronic components and magnets and prevent small parts from becoming detached unintentionally, as specified by [S2] . At the same time, it must remain possible to be disassembled without damaging it in order to support assembly, maintenance and component replacement in accordance with [S3] .

For this purpose, a modular brick housing structure is proposed which consists of three separate parts:

- A supporting frame incorporating the docking face
- Interchangeable side-wall modules containing the receiving faces
- a final cover that closes the housing

This structure offers two main advantages: It allows the electronic components of the individual connection faces to be mounted separately before the modules are assembled into a complete building brick [S3] . And, as the receiving-side modules follow the same design regardless of their position or the brick type, they can be installed interchangeably and replaced individually when necessary.

4.5.3 Mechanical Concept of the Baseplate

The baseplate forms the starting point of every physical construction and consists of an enclosed housing for its technical components such as one receiving face, whose mechanical geometry corresponds to that of the building bricks. The first brick is placed on the baseplate using its defined docking face which establishes it spatially and logically as the first building brick of the construction.

Additional receiving faces could enable several constructions with multiple starting points but would require an extension of the digital structure model and additional rules for comparison with the target structure. Consequently, the basic concept is limited to a single connection point.



Figure 5: Baseplate (physisch)

4.5.4 Conclusion

The mechanical design determines which types of connection faces can be joined and which of the four relative rotational orientations can be assumed. The following section describes how these mechanically defined states are detected electronically and how the connected building bricks are supplied with power from a central source.

4.6 Electronic Detection and Power Subsystem

- Das Kapitel verwendet die in X.3.3 definierten Begriffe:

  - Upstream-Schnittstelle auf der Andockseite,
  - Downstream-Schnittstelle auf jeder Aufnahmeseite.
- Damit die physische Konstruktion digital rekonstruiert werden kann, müssen diese Verbindungszustände elektronisch erfasst werden

=> das vorliegende kapitel beschreibt die dafür erforderliche elektonische Architektur enthält:
- elektronische Systemarchitektur
- funktionalen Aufbau der Bausteine und Baseplate
- elektrische Schnittstellen und lokales Erkennungsprinzip
- zentrale Energieversorgung
- (lokale Feedbackausgabe)

4.6.1 elektronische Systemarchitektur

aktiv/passiv/? - related work abhängig

4.6.2 Functional Structure

The building bricks and the Baseplate share several fundamental electronic functions, including control, electrical interfacing, and power distribution. However, they perform these functions at different levels of the system. While each building brick processes information locally and forwards data and power within the physical construction, the baseplate acts as the central root and mediates between the building-brick system and the learning application. Figure Figure 6 summarises the functional structures of the building bricks and the baseplate.

Functional Structure of the Building Bricks

Each building brick conceptually contains five electronic functional units:
1. A local control unit: It maintains the identity and type of the brick and processes the signals received through its electrical interfaces
2. The upstream interface: It establishes the electrical connection to the parent brick through the docking face
3. The downstream interface: It provides electrical connections to child bricks through the receiving face
4. Internal power distribution: It supplies the local electronics and forwards the incoming supply to the downstream interfaces
5. Local visual feedback output: It shows the system generated feedback

Depending on its type, a building brick provides either five downstream interfaces in the cube configuration or a single downstream interface in the smashed configuration.

Fuctional Structure of the Baseplate

The Baseplate contains four electronic functional units:
1. A central? control unit: It initiates the detection process and mediates between the physical cube system and the learning application
2. The downstream interface: It establishes the electrical connection to the first building brick
3. Central power supply: It provedes energy to the connected construction
4. Application interface: it enables the exhange of data with the learning application

As the baseplate constitutes the root of the construction, it does not contain an upstream interface.

(EIGENTLICH IN SOFTWARE CONCEPT: It forwards the serialised representation of the detected construction to the learning application. The spatial reconstruction and comparison with the target structure are performed by the learning application rather than the baseplate. Figure X summarises the functional structures of the building bricks and the baseplate.)



Figure 6: Blockdiagramme brick und baseplate

4.6.3 Electrical Interfaces and Local Detection Principle

BEZUG AUF BLOCKDIAGRAMM

Each mechanically defined connection is complemented by an electrical interface. The upstream and downstream interfaces contain both the same contacts for the power supply and the shared reference potential but differ in the arrangement and function of their signal contacts. The docking face of each building brick contains four upstream orientation contacts corresponding to the four mechanically possible rotations and arranged at the corners of the docking face. Each receiving face contains just one downstream child contact for detecting and communicating with an attached child brick. It is positioned so that it connects to exactly one of these four upstream orientation contacts in each permissible orientation. This arrangement allows the four relative rotations to be distinguished unambiguously [DET3] . The power and ground contacts are rotationally symmetrical so that the power connection remains functional in every permissible orientation.

(The recessed interface regions and the mechanical guiding elements additionally protect these electrical interfaces. They reduce the risk of incorrect contacting and unintended short circuits by aligning the connecting faces before contact is established.) -> VLT AUCH IMPLEMENTIERUNG



Figure 3: Andockseite kontaktanordnung



Figure 4: Aufnahmeseite kontaktanordnung)

Detection of the Connection Face and Relative Rotation

A valid electrical connection is established between the downstream child contact of a parent brick and one of the four upstream contacts of the newly attached child brick. Which upstream contact is reached by the parent block's downstream contact depends on the orientation of the child brick and therefore encodes its relative rotation, as required by [DET3] . Once the connection has been established, the same signal path is used for communication between the parent and child bricks. Because each receiving face has a separate downstream interface, the local control unit can query the faces individually to determine whether a child brick is connected to a particular receiving face or not and if so establish the communication with that child.

(The identity and type of the connected brick are subsequently determined from the information transmitted by its local control unit. The corresponding communication and data representation are described in Section 4.7.2.)

The detected connection face and rotation initially describe only the position and orientation of a brick relative to its immediate parent. Its global position and orientation within the complete construction are calculated later by the learning application based on all locally detected relationships (KAPITEL).

4.6.4 Centralised Power Supply

In accordance with [EL1] , the building bricks operate without individual batteries or rechargeable cells. Instead, power is supplied centrally by the baseplate and transmitted through the electrical contacts to the connected bricks. Each brick uses the incoming supply for its own electronics and forwards it to its available downstream interfaces so that subsequent child bricks can also be powered. This centralised approach reduces maintenance because individual batteries do not need to be charged or replaced. It also decreases the space required within each building brick and prevents differing states of charge within the same construction.

POWER SUPPLY EIGENTLICH VOM COMPUTER??

4.6.5 Local Electronic Feedback Output

To have feedback directly assigened to the physical bricks and not exlusively through the learning application, each building brick contains a simple visual feedback. The meaning, presentation, and coordination of local and global feedback are specified in Section ????.

4.6.6 Conclusion

The electrical concept is based on active bricks, each of which has its own local control unit, an upstream interface and downstream interfaces with which it can communicate and detect its relative rotation. the baseplate forms the electronic starting point by supplying the power and

connecting the physical brick construction with the learning application. The electrical subsystem therefore provides the physical interfaces and signals neccesary for the digital recontruction of the physical construction

(How this local electrical information is retrieved and processed by the learning application is described by the following data, communications and software concept)

4.7 Data, Communication and Software Subsystem

Das Kapitel legt fest, wie diese bereitgestellten elektrischen Informationen über die Würfelstruktur übertragen, zu einer serialisierten Beschreibung der Gesamtkonstruktion zusammengeführt und anschließend in der Lernanwendung verarbeitet werden.

terminologie kindknoten

enthält:
- übergeordneten Datenfluss
- Struktur und Datenmodell
- Erfassungs- und Kommunikationskonzept
- Verarbeitung in der Lernanwendung
- Feedbackrückkanal

4.7.1 übergeordneter Datenfluss

- Der Verarbeitungsablauf beginnt in der Lernanwendung:
  - Das Kind wählt eine Zielkonstruktion aus
  - Die Zielkonstruktion wird für den späteren Vergleich gespeichert
  - Die Lernanwendung sendet ein Startsignal an die Baseplate
- Die Baseplate:
  - startet den zyklischen Erfassungsprozess
  - fragt den ersten angeschlossenen Baustein ab
  - Die Bausteine ermitteln ihre lokalen Verbindungsinformationen und führen diese rekursiv zu einer serialisierten Beschreibung der vollständigen Baumstruktur zusammen
  - empfängt die serialisierte Baumdarstellung
  - leitet diese inhaltlich unverändert an die Lernanwendung weiter
- Die Lernanwendung:
  - deserialisiert die empfangene Baumdarstellung
  - stellt das digitale Strukturmodell wieder her
  - berechnet Position und Orientierung der Bausteine
  - vergleicht die Ist-Konstruktion mit der Zielkonstruktion
  - erzeugt die Feedbackzustände
  - visualisiert die erkannte Konstruktion und die globale Rückmeldung
  - sendet bausteinspezifische Feedbacknachricht an die Baseplate
- Die Baseplate leitet die Feedbacknachricht an die Bausteine weiter
- Anschließend beginnt der nächste Erfassungszyklus
- Der Vorgang wiederholt sich, bis die Aufgabe abgeschlossen oder beendet wird
- Beim Beenden sendet die Lernanwendung ein Stoppsignal an die Baseplate, die noch eine letzte vordefinierte Schluss-feedbacknachricht an die Bausteine rausschickt
- baseplate wartet wieder auf ein Startsignal

- lernanwendung wartet auf eine ausgewählte Zielkonstruktion

=> zwei voneinander abgetrennte Systeme:
- baseplate und cubes
  - Basisstation und aktive Bausteine,
  - erfasst und überträgt die physische Konstruktion,
  - ist unabhängig von der ausgewählten Zielkonstruktion
- lernanwendung:
  - Computer
  - interagiert mit den Lernenden
  - verwaltet die Zielkonstruktion
  - interpretiert die erfassten Daten
  - führt den Zielvergleich durch
  - erzeugt Visualisierung und Rückmeldung



Figure 7: Sequenzdiagramm

4.7.2 Logical Structure and Data Model

The physical construction is conceptually represented as a directed tree: The baseplate forms the root of the tree, each connected building brick is represented by a node and each physical connection constitutes a directed edge between a parent and a child node. The model reflects also the directed interface structure introduced in Section 4.6.3: The defined docking face connects each brick to its parent, while its receiving faces allow one or more child bricks to be attached. Consequently, each brick can have no more than one parent but may have several children. As required by [C3] , both linear and branching three-dimensional constructions can therefore be represented by the model. By deriving the digital interpretation from the parent–child relationships and the resulting overall construction, the structure model applies the relational and constructive mapping principles introduced in Section 2.4.2.3.

To identify and interpret each building brick within this tree, however, the parent–child relationship alone is insufficient. Table Table 13 summarises the additional information contained in each node for this purpose:

Information	Meaning
Identity	Unique assignment of the node to a physical building brick
Brick type	Geometric and functional properties of the building brick
Relative rotation	Orientation of the building brick in relation to its parent
Occupied connection faces	Assignment of child nodes to the corresponding receiving faces
Child nodes	Node information of the directly connected child bricks and their subordinate structures

Table 13: *Node Information*

The identity is used to recognise an individual physical building brick and subsequently assign local feedback to it, whereas the brick type is required to interpret its geometry and compare it with the corresponding element of the target structure. Lastly, the relative rotation and occupied connection faces describe the local spatial relationship between the node and its parent and children.

4.7.3 Detection and Communication Concept

Communication within the physical construction follows the parent child relationships of the structure model: A parent requests information from a directly connected child, which responds with its own node information and the serialised descriptions of all subordinate structures connected to it. This communication takes place through the upstream interface of the child and the corresponding downstream interface of the parent described in Section 4.6.2. It follows a request response principle since the parent initiates the exchange, and the child responds to the request. When the child subsequently queries its own receiving faces, it assumes the role of a parent in relation to the bricks connected below it.

Since only one signal path is available between a parent's downstream child contact and the contacted upstream contact of its child, the line must be used alternately for both transmission directions. The communication concept consequently employs a bidirectional single-wire half-duplex protocol. The exact message format, timing parameters, and concrete protocol implementation are described in the realisation chapter (BEZUG).

Sequential Interface Query and Recursive Detectionn

During each detection cycle, the downstream interfaces of a building brick are examined sequentially in a predefined order, following the *round robin principle*. This ensures that every available receiving face is checked regularly. If no child is detected at an interface, the control unit continues with the next available interface. But if a child brick is detected, its complete subordinate structure is acquired before the parent continues with the next downstream interface.

The overall construction is therefore detected using a *depth first search*. Starting from the baseplate as the root, the system follows a detected branch to its outermost building brick before processing the next downstream interface of the preceding brick. Once all downstream interfaces of a brick have been queried, the brick combines its own node information with the collected representations of its child nodes. The resulting description of the complete subtree is then returned to the parent.

This procedure is applied recursively until the baseplate receives a serialised representation of the entire construction from the first connected building brick. It allows every brick to process only its

local connections while the complete structure emerges through the aggregation of the individual subtrees.

Serialisation of the Tree Structure

For the serialisation of the detected tree a *pre-ordre traversal* is used. This means that the information of the current parent node is placed before the serialised representations of its child nodes. The child nodes are then appended according to the predefined order of the parent's downstream interfaces. Together with the information about occupied receiving faces, this consistent ordering enables the learning application to assign each deserialised child node to the correct connection face.

The sequence in which requests propagate through the physical construction must be distinguished from the order of the data within the resulting representation: Detection requests travel from the baseplate towards the outer nodes of the construction but the collected subtree data subsequently return in the opposite direction towards the baseplate. Within each serialised subtree, however, the parent node is placed before its child nodes in accordance with the *pre-order traversal*. Figure Figure 8 can illustrate this distinction using a physical example tree/brick construction and its resulting serialisation order.



Figure 8: ABBILDUNG PHYSISCHER BAUM UND WIE DIE NACHRICHT DANN AUSSCHAUT

4.7.4 Processing in the Learning Application

The serialised description of the detected construction is then transmitted to the learning application by the baseplate. The learning application then deserialises the data so that the individual nodes and their parent child relationships are restored as a digital tree. The predefined ordering of the downstream interfaces and the transmitted connection face information allow the child nodes to be reassigned to their corresponding receiving faces, as required by [DET2] .

Starting from the baseplate, the learning application then calculates the global position and orientation of every building brick. For each connection, a local transformation is defined based on three elements:

1. The receiving face used for the connection
2. The types of the two connected building bricks
3. The detected relative rotation

The global pose of a child brick is therefore derived from the global pose of its parent and the local transformation associated with their connection. By recursively applying this procedure to all nodes, the complete construction can be placed within a shared coordinate system.

The resulting spatial model forms then the basis for the three dimensional visualisation and the comparison with the selected target structure in accordance with [DET4] .

Comparison with the Target Structure

As already mentioned, the comparison is primarily based on the brick types and their spatial relationships rather than on the individual identities of them. Building bricks of the same type can therefore be exchanged without changing the semantic correctness of the construction. The comparison determines whether the detected current structure

- Corresponds to a permissible partial structure of the target
- Completely matches the target structure, or
- Contains a connection, brick type, orientation, or position that deviates from the target

The individual identity of each brick remains relevant for the local feedback.

4.7.5 Feedback Channel

Based on the comparison with the target, the learning application calculates a feedback status for the overall structure as well as for the individual building bricks. The reconstructed digital construction and the global feedback are displayed directly in the learning application.

For local feedback, the relevant physical bricks are addressed through their identities. The learning application combines the brick-specific feedback states into a feedback frame and sends it to the baseplate, which forwards the feedback information through all the connected bricks. Each brick then checks if its identity is part of the feedback frame and if so activates its local visual output.

The pedagogical meaning and visual presentation of the individual feedback states are defined separately in Section 4.9.

4.7.6 Conclusion

????????????

4.8 Task and Interaction Subsystem

The task and interaction concept specifies how learners complete the reconstruction task and which actions are available to them during this process. It furthermore defines the rules according to which a physical construction is evaluated while preserving sufficient flexibility for learners to explore, revise, and correct their chosen construction process.

4.8.1 Physical–Digital Coupling

The interaction concept combines the static and interactive forms of coupling introduced in Section 2.4.1.2. At the representational level, each physical brick type is statically linked to a corresponding digital model. The cube brick and the smashed brick are therefore always represented by digital models that reflect their respective physical geometry and appearance. The meaning of an individual brick within a construction, however, is determined interactively. Its position and orientation, its role within the parent child structure and its evaluation in relation to the target structure depend on the current physical configuration. Whenever bricks are connected, detached, rotated, or repositioned, these properties are recalculated by the learning application. The digital meaning of the construction therefore emerges from the relationships between the physical bricks rather than from the individual elements in isolation.

4.8.2 Task Logic

The construction task is governed by a set of structural and procedural rules.

Following each detected change, the current construction is compared with the selected target structure. A partial construction is considered valid if its building brick type and connections form part of the target structure. The comparison therefore considers the type, the connection face used

and the spatial position and the orientation of each brick. Building bricks of the same type are interchangeable within the construction task.

The individual identity of a brick is not relevant to the correctness of the solution but is required only for technical identification and for assigning local feedback to the corresponding physical brick.

The construction sequence is not prescribed in full. Different sequences may lead to the same valid result, thereby providing the openness required by [TUI1] . However, the directed parent child structure imposes a necessary dependency: a child brick can only be attached after its parent is present in the physical construction.

The task is completed once the detected current construction fully corresponds to the target structure in terms of the brick types, connections, positions, and orientations.

4.8.3 Available Actions and Error Correction

Within the defined task objective, learners can explore different construction paths and revise previously completed steps. Connected bricks can therefore be detached from the construction, rotated, attached to a different receiving face or replaced by another brick of the correct type.

As required in [IA5] , errors are explicitely permitted and incorrect actions neither terminate the task nor result in other penalties. Since the physical construction remains visible, inspectable, and directly modifiable throughout the task, the interaction provides also structured openness required by [TUI1] .

4.8.4 Adaptation of Task Difficulty

According to [TUI2] , The difficulty of the construction tasks must be adaptable to different learning prerequisites and can be varied through the following characteristics:

- Number of building bricks: Tasks with fewer bricks provide a simpler starting point, whereas a larger number enables more extensive constructions
- Spatial extent: Structures may extend along one, two, or all three spatial axes.
- Structural complexity: Tasks may involve linear constructions or branching structures with several child bricks
- Relative rotation: Blocks may use consistent orientations or different rotations in increments of 90°
- Block types: A task may require only one brick type or a combination of different types.
- Presentation of the target: The complete target structure may be displayed from the beginning or revealed incrementally
- Level of support: Feedback may be limited to an evaluation of the current result or supplemented with guidance concerning possible subsequent actions

These characteristics can be combined to create tasks of varying complexity without changing the fundamental interaction principle.

4.8.5 Conclusion

??? The specific presentation and gradation of the corresponding feedback and assistance are defined in the following visualisation and feedback concept

4.9 Visualisation and Feedback Subsystem

ÜBERLEITUNG

enthält:

- Visualisierung der Ziel- und ist- Konstruktion
- Verbindung von Visualisierung und Feedback
- Feedbackebenen und -Arten
- Das in Kapitel X.6 beschriebene digitale Strukturmodell bildet Grundlage für die Darstellung und Bewertung der physischen Konstruktion
- Lernanwendung soll Lernenden sichtbar machen, welchen Aufbau das System erkannt hat und darauf aufbauend die ergebnisse des Vergleichs zwischen Ist- und Zielkonstruktion als Feedback darstellen
- Visualisierung und Feedback erfüllen unterschiedliche, aber eng miteinander verbundene Funktionen:
  - Visualisierung: repräsentiert erkannten Systemzustand = interaktionsfeedback
  - Feedback: bewertet Zustand im Hinblick auf Bauaufgabe = pädagogisches Feedback

  => Lernenden können zuerst nachvollziehen, ob und wie ihre handlung vom System erkannt wurde und anschließend erkennen, ob eine Korrektur erforderlich ist

4.9.1 Visualization of the Target Structure

At the beginning of a construction task, a target structure is selected in the learning application. This structure remains available as a visual reference throughout the construction process and can be presented either completely or imcrementally. A complete representation enables lerners to analyse the target independently and plan their own construction process. An incremental representation provides additional guidance by presenting or highlighting only the currently relevant part of the target structure. As required by [TUI2] and [FB4] , different levels of difficulty and support can therefore have different target structure visualisations.

4.9.2 Visualisierung der erkannten Ist-Konstruktion

Following each detection cycle, the current structure reconstructed by the learning application is represented as a three-dimensional model. Each detected building brick is thereby inserted into the scene according to its type, calculated position and orientation. Its digital representation is based on the geometry and appearance of the physical bricks to preserve a comprehensible relationship between the physical and digital representations in accordance with [TUI3] . The target and the detected current structure must remain visually distinguishable to prevent learners from confusing the reference with their own construction. They should therefore be displayed in separate views or be clearly separated spatially within the application.

The scene is embedded in a three-dimensional view to support rotation and zooming, allowing the construction to be inspected from different perspectives. This is particularly relevant for branching structures in which individual bricks or spatial relationships may be obscured from a single viewpoint. When the visualisation is initially displayed, the camera is automatically aligned with the defined front view of the construction along the positive y-axis.

4.9.3 Integration of Visualisation and Feedback

The representation of the current structure is supplemented with its brick specific feedback derived from the comparison with the target. While the relationship between a physical brick type and its digital geometry remains statically defined (see Section 2.4.1.2), the feedback state assigned to a brick changes dynamically according to its current position within the construction.

This feedback visualisation distinguishes four relevant state:
1. A detected brick that is correctly positioned

2. A detected brick that deviates from the target structure
3. An unoccupied position that constitutes a permissible next construction step
4. A target position that is not yet accessible because its required parent brick is missing

To make the different states visible to the learners, different coloured highlights are used for the building bricks. Correct and deviating bricks are distinguished through contrasting visual highlights, such as green and red outlines. Permissible next positions can be represented as transparent placeholders or *ghost cubes*. Not displayed are positions that are not yet accessible, as their presentation could suggest an action that cannot yet be performed within the directed parent child structure. By attaching each visual state directly to the affected brick or position, the feedback can be clearly associated with the relevant part of the construction in accordance with [FB2] .



Figure 5: physischer brick



Figure 6: digitaler brick)



Figure 7: correcter brick)



Figure 8: correcter brick)



Figure 9: correcter brick)

4.9.4 Feedback Levels

The concept combines three levels of feedback and draws on the different feedback modalities introduced in Section 2.5.1. Intrinsic physical feedback results from the mechanical guiding elements and magnetic assistance. When connecting two bricks, learners can physically perceive that the two faces have engaged. But this confirms only the mechanical connection and does not indicate whether the connection has been detected electronically or whether the brick is correct in relation to the target structure. It is therefore supplemented by digital feedback. Its local from is presented directly on the affected physical brick at which a green or red light indicates whether the connected brick has been placed correctly or needs to be reviewed. The global digital feedback is presented through the learning application. In addition to the state of individual bricks, it can represent the complete construction, the progress made towards the target and possible subsequent actions. It therefore supports more detailed information than can be communicated through the limited output capabilities of an individual brick.

The local and global outputs must remain semantically consistent: if a brick is marked as correct locally, the corresponding digital brick must display the same state in the learning application.

4.9.5 Types of Feedback

Based on the distinction established in the theoretical background in Section 2.5.2, the concept differentiates between interaction feedback and pedagogical feedback, as required by [FB1] .

By showing which digital structure the system has derived from the physical construction, the visualisation the interaction feedback is provided: The learner can infer that its connection has been detected and processed, if an added brick appears at the position and orientation in which it was physically placed. If the brick is absent or appears differently from the physical arrangement, this indicates a possible detection or reconstruction problem.

The pedagogical feedback evaluates the detected state in relation to the target structure and can fulfil three functions:

- Outcome feedback indicates whether a brick or connection is correct
- Progress feedback shows how much of the target structure has already been completed

- Feedforward indicates a permissible subsequent action or position

Outcome and progress feedback constitute the basic feedback provided by the prototype while feedforward can supplement these forms depending on the configured level of support. Table Table 14 summarises the principal feedback cases and their presentation at the local and global levels

Feedback case	Local feedback	Visualisation in the learning application	Type of feedback
Physical change detected	No separate local output	The detected current construction is updated to show the recognised brick, position, and orientation	Interaction feedback
Connection detected and correct	Positive light signal on the affected brick	The brick is visually highlighted as correct	Outcome feedback
Connection detected but inconsistent with the target	Negative light signal on the affected brick	The brick or affected area is visually highlighted as deviating	Outcome feedback
Permissible next position	No local output	Optional representation as a transparent ghost cube	Feedforward
Partial progress achieved	No local output	The progress indicator is updated	Progress feedback
Target structure completed	No local output	Successful completion of the task is displayed	Outcome feedback

Graduated Support

Different types of feedback should be provided at different points in time: Interaction feedback should be provided promptly after the action that triggered it, as required by [DET7] , so that learners can associate the system response with the corresponding physical connection. Outcome feedback should likewise indicate promptly whether the detected construction step corresponds to the target structure.

According to [FB3] as well as [FB4] , more extensive assistance is provided incrementally according to the learner's support needs. To allow the learner to inspect the physical and digital construction and attempt an independent correction only the affected brick is initially marked as deviating. If further support is required, the learning application may provide an additional explanation. At a higher level of assistance, permissible next positions can be displayed as ghost cubes to provide feedforward. As already mentioned can the representation of the target structure also be adapted to the required level of support. It may remain fully visible to facilitate independent planning or be presented incrementally to direct attention towards the next relevant part.

This graduated approach preserves opportunities for independent error analysis while providing additional orientation when required.

4.9.6 Conclusion??

auf Section 2.5.2.3 kapitel eingehen

4.10 Concept Summary

5 Technical Realisation

The following chapter describes how the concept of the proposed learning system was implemented in the physical prototype. The focus is placed on the manufactured components, the electronic hardware, the implemented communication protocol, the embedded firmware and the learning application.

NOCH WAS DAZU?

5.1 Mechanical and Electronic Realisation

??AUCH LEARNING APPLICATION ERKLÄREN??

The physical and electonic implementation of the building bricks and the baseplate is described here. The section focuses on the components and construction methods used in the prototype as well as on deviations that occurred during manufacturing.

5.1.1 Mechanical Implementation

The prototype comprises two physically implemented building-brick types: the *cube brick* and the *smashed brick*. Both types use the standardised square connection interface defined in Section 4.5.1, but differ in their geometry and number of receiving faces. In contrast to the cube brick, the smashed brick has only half its height and provides a single receiving face opposite its docking face. Its four remaining lateral faces do not permit further connections.

Both brick types were modelled using Autodesk Inventor and manufactured using a 3D printer. Their housings implement the modular structure introduced in the concept chapter and consist of a black structural frame, colour-coded connection-side modules and a removable black cover. The side modules are inserted individually into the supporting frame and can be removed separately. This allowes the electronic components to be mounted and tested before the complete brick is assembled. In addition, individual modules can also be replaced without manufacturing an entirely new housing.



Figure 10: explosionszeichnung cube



Figure 11: explosionszeichnung smashed



Figure 12: explosionszeichnung baseplate

The docking and receiving sides contain mechanical guiding structures that align connected bricks and restrict their relative orientation the four positions. The connection is additionally secured by 4 magnets on every docking and recieving face. Die 4 contacte der docking seite befinden sich in den ecken der quadratischen fläche und der downstream kontakt in einer definierten ecke davon. Due to platzmangel muss der downstream contact of one receiving face anders platziert werden. the resulting rotational offset is compensated in the firmware, described in (section ???) der kontakt für GND und Versorgun ist in der Mitte der fläche platziert

The baseplate is implemented as the root element of the construction. Its housing contains the baseplate electronics and provides one receiving sides for connecting the first brick.

5.1.2 Electronic Implementation

VERWEIS AUF SCHALTPLAN UND KICAD DESIGN IM ANHANG Both brick types are equipped with an ATtiny1616 microcontroller that serves as their local control unit. The mechanical interfaces contain spring-loaded Pogo pins that establish the electrical connections while compensating for minor manufacturing tolerances and small movements between connected bricks. The recessed guiding structures surrounding the contacts additionally protect the electrical interface against accidental contact, incorrect alignment and short circuits.

The electrical implementation differs between the docking and receiving faces. On a receiving face, the data, supply and ground connections are implemented using spring-loaded contacts. The docking face contains the corresponding contact surfaces for the data connections, whereas the power connection uses a different construction consisting of a neodymium ring and a Pogo pin mounted directly on the printed circuit board. (ABBILDUNG)

The four upstream data contacts of the docking face are located in the corners of the square connection area. Ground and power of this face are transmitted through rotationally symmetrical contacts. The ground contact is positioned at the centre of the interface, while the supply contact forms a concentric connection around it. Both electrical connections therefore remain unchanged when a brick is rotated in increments of 90°. A receiving face provides a single downstream data contact in one defined corner as well as the power and ground contact in the center. Because of the limited installation space, the downstream data contact of one receiving face of the cube brick is placed in a different corner from the otherwise uniform arrangement. The resulting rotational offset is compensated for in the building-brick firmware, as described in Section 5.3.1.2.



Figure 13: aufnahmeseite pogo pins



Figure 14: docking seite pogo pins

Four red-green-blue (**RGB**) side view Light-Emitting Diode (**LED**) on each cube side provide local feedback directly on the building brick. The assignment of the resulting colours to the implemented feedback states is described in INTERACTION??

The ATtiny1616, the four **RGB LED** and the electrical elements of the docking face are mounted on a printed circuit board designed using *KiCad*. The PCB is attached to the inside of the docking face using screws. The receiving face contacts are connected to the main board through the internal cable wiring of the brick.

The baseplate is also controlled by an ATtiny1616 and communicates with the computer through the microcontroller's hardware USART interface and a connected USB-to-TTL UART adapter. The prototype is supplied with 5 V from the computer's USB interface through this adapter. The base-

plate transfers the supply voltage to the connected root brick, from which it is forwarded through the subsequent brick connections.



Figure 15: blockdiagramm brick



Figure 16: blockdiagram baseplate

5.1.3 Conclusion?

5.2 Communication Protocol

The communication concept introduced in Section 4.7 is implemented using two separat communication interfaces: The communication within the physical construction and its parent child communication is based of a ?selbst erstelltes? software-controlled single-wire protocol whereas the communicaiton between the learning application and the baseplate uses the hardware USART of the baseplate microcontroller TABELLE

Communication Interface	Physical Implementation	Transmission Rate
Learning application–baseplate	Hardware USART through a USB-to-TTL UART adapter	115200 bit/s
Baseplate–brick and brick–brick	Software-controlled single-wire half-duplex connection	approximately 9.6 kbit/s

Table 15: *Implemented communication interfaces*

5.2.1 Single-Wire Communication Between the Building Bricks

The communication between two directly connected modules is implemented as a bidirectional single-wire half-duplex interface. The same data line is used alternately by the parent and child brick, and only one participant may transmit at a time.

The idle state of the line is logic high. However, the line is not actively driven high. Instead, the transmitting microcontroller either pulls the line to ground to transmit a logic low or releases it and activates its internal pull-up resistor to obtain a logic high. This open-drain-like behaviour reduces the risk of electrical contention because connected devices do not actively drive the line to opposing voltage levels. Each byte is transmitted using a software-implemented UART-like format: (FIGURE):



Figure 9: Timing of one byte on the single-wire interface

The logic-low start bit indicates the beginning of a byte. It is followed by eight data bits transmitted least significant bit first and a logic-high stop bit. No parity bit is used. A bit duration of 104 µs results in a transmission rate of approximately 9.6 kbit/s and a total transmission time of approximately 1.04 ms per byte. After a participant has completed a transmission, the line is released before the other participant responds. A turnaround interval of 312 µs, corresponding to three bit periods, is used whenever the direction of transmission changes. This Communication type is used for construction detection and feedbackframe forwarding.

5.2.2 Common Frame Format

Construction and feedback data have different contents but are transmitted using the same variable-length binary frame format. This format is used for communication between the building bricks as well as between the baseplate and the learning application:

SYNC	LEN	PAYLOAD	CHECKSUM
1 byte	1 byte	0-128 bytes	1 byte

Table 16: Implemented binary frame format

vlt die Infos auch in Figure einfügen

Field	Size	Implemented meaning
SYNC	1 byte	Start marker 0xA5
LEN	1 byte	Number of bytes contained in the payload
Payload	0-128 bytes	Detection or feedback data
Checksum	1 byte	XOR checksum over LEN and all payload bytes

Table 17: *Fields of the implemented binary frame format*

The synchronisation byte enables the receiver to identify the beginning of a frame. The length field specifies the number of payload bytes that must subsequently be read. A frame with LEN = 0 contains an empty payload. I Although the one-byte length field could theoretically represent up to 255 payload bytes, the prototype limits the payload to 128 bytes to restrict the required buffer size and transmission duration.

The payload contains the information transmitted by the frame. Its structure depends wether it contains the detected tree structure or the feedback message. Both payload formats are described in detail in Section 5.2.3.1.1 and Section 5.2.3.2.1.

To detect transmission errors, an XOR checksum is calculated from the length field and all payload bytes:

$$C = L \oplus P_0 \oplus P_1 \oplus \cdots \oplus P_{L-1}$$

beim Empfang wird die Prüfsumme erneut berechnet und mit dem übertragenen Wert verglichen. Stimmen beide Werte nicht überein, wird der Frame verworfen.

5.2.3 Parent Child Communication

The communication within the physical construction follows a *request–response* procedure and is always initiated by the parent brick. Depending on the current process, the communication is used either to retrieve the detected construction or to transmit feedback towards the connected bricks.

The command and acknowledgment bytes used in the two processes, are summarised in the following table Table 18

Message	Value	Direction	Meaning
CMD_STATUS	0xAA	Parent ⟶ child	Request the detected subtree
ACK_BUSY	0x55	Child ⟶ parent	Request received and being processed
CMD_FEEDBACK	0xCC	Parent ⟶ child	Announce the transmission of a feedback frame
ACK_FINISHED	0x66	Child ⟶ parent	Feedback successfully processed and forwarded
ACK_FAILED	0x77	Child ⟶ parent	Feedback frame invalid or forwarding failed

Table 18: *Command and acknowledgement bytes of the parent–child protocol*

Detection Communication

To request the detected subtree of a connected child, the parent (node) sends *CMD_STATUS* through the corresponding downstream interface. After receiving this valid request, the child (node) changes the transmission direction and responds with *ACK_BUSY* . This confirms that the request haas been received and the child is going to begin collecting the required information with subsequently querying its own receiving interfaces. Once the subordinate information has been collected, it returns a *DATA_FRAME* containing its own Payload and the Payload of its complete subtree. This procedure is applied recursively throughout the connected construction. FIGURE



Figure 10: COMMUNICATION SEQUENCE DIAGRAM Recursive communication sequence for detecting the connected building-brick structure

BYTE EBENE??



Figure 11: SINGLE WIRE PARENT CHILD COMMUNICATION

5.2.3.1.1 Detection Payload

The payload returned during this sequence represents the detected construction tree. Each brick contributes a three-byte node header, followed by the serialised representations of its subordinate bricks:

NODE_ID	ORIENTATION	CHILD_MASK	CHILD_NODE_PAYLOAD
1 byte	1 byte	1 byte	variable

Table 19: Detection payload

vlt die Infos auch in Figure einfügen

Field	Size	Implemented meaning
NODE_ID	1 byte	Brick type and individual instance number
ORIENTATION	1 byte	Relative rotation represented by a value from 0 to 3
CHILD_MASK	1 byte	Bit mask of occupied receiving interfaces
Child-node Payload	variable	Subtree payloads of the subordinate bricks

Table 20: *Structure of a serialised building-brick node*

The *NODE_IDs* three most significant bits encode the brick type, whereas the five least significant bits encode the individual instance number. This allows the learning application to distinguish between the cube and smashed brick types while retaining an individual address for assigning local feedback. *ORIENTATION* contains a value from 0 to 3, representing the four possible rotations of the brick relative to its parent. Within *CHILD_MASK*, bit (i) indicates whether a child was detected at receiving interface (i). The cube brick can use bits 0 to 4 for its five receiving interfaces whereas the smashed brick only needs one bit assigned to its single receiving interface. The node representations of the connected children follow the node header in ascending order of the receiving-interface indices. The precise procedure through which the firmware collects and combines these node representations is described in Section

The baseplate does not add a node header of its own. Instead, it transfers the payload beginning with the first brick connected to it. If no root brick is detected, the baseplate transmits a DATA_FRAME with an empty payload.e.

Feedback Communication

The feedback communication is also initialised by the parent node but with another command message. The *CMD_FEEDBACK* singalises the child node the upcoming transmission of a *FEEEDBACK_FRAME*. After receiving the command, the child responds with *ACK_BUSY*, indicating that it is ready to receive the frame. The parent then transmits the complete FEEDBACK_FRAME. After processing and forwarding the frame, the child reports the result using either ACK_FINISHED or ACK_FAILED. The internal processing and forwarding logic is described in Section 5.3.1.

5.2.3.2.1 Feedback Payload

The Feedback Payload uses the common frame format but contains pairs of brick identifiers and LED states:

NODE_ID	LED_STATE	NODE_ID	LED_STATE	...
1 byte	1 byte	1 byte	1byte	...

Table 21: feedback payload

LED_STATE can assume one of two values: *LED_GREEN* or *LED_RED*. If a brick's *NODE_ID* is not included in the feedback payload, that brick switches off its **LED**. An empty feedback payload can therefore be used to deactivate all local feedback simultaneously.

5.2.4 Communication between Learning Application and Baseplate

The connection between the learning application and the baseplate uses the ATtiny1616 hardware USART at 115200 bit/s with eight data bits, no parity and one stop bit. The learning application controls an interaction session using the following single-byte commands and responses:

Message	Value	Direction	Meaning
PC_CMD_START	0x53 (S)	Application⟶ Baseplate	Start cyclic construction detection
DATA_FRAME	Variable	Baseplate ⟶ Application	Current serialised construction
FEEDBACK_FRAME	Variable	Application ⟶ Baseplate	Feedback calculated by the application
PC_RESP_DONE	0x44 (D)	Baseplate ⟶ Application	Feedback successfully forwarded
PC_RESP_FB_FAILED	0x4E (N)	Baseplate ⟶ Application	Invalid feedback frame or forwarding failure
PC_CMD_STOP	0x58 (X)	Application ⟶ Baseplate	Stop detection and switch off local feedback

Table 22: *Messages exchanged between the learning application and the baseplate*

After receiving *PC_CMD_START*, the baseplate begins the detection process and transmits the detected construction to the learning application using the DATA_FRAME format defined above.

After receiving the DATA_FRAME, the learning application answers with the FEEDBACK_FRAME calculated from the target comparison. The baseplate forwards this frame through the physical construction and responds with PC_RESP_DONE if all detected bricks confirmed the feedback. If the received frame is invalid or at least one brick fails to confirm the feedback transmission, it responds with PC_RESP_FB_FAILED.

When the basplate receives a *PC_CMD_STOP* from the learning application, it forwards an empty FEEDBACK_FRAME so that all local **LED** are switched off. It then terminates the cyclic detection by returning to its idle state.



Figure 12: KOMMUNIKATIONSSEQUENZDIAGRAMM Cube baseplate learning application

5.2.5 Validation and Error Handling

Several validation mechanisms were implemented to prevent incomplete or corrupted transmissions from being interpreted as valid construction data:

- Each received byte is checked for a valid start and stop bit.
- The SYNC byte allows the receiver to locate the beginning of a frame.
- The received length is checked against the maximum payload size of 128 bytes.
- Timeouts terminate the reception of incomplete bytes or frames.
- The XOR checksum detects changes to the payload or length field.
- On the computer interface, incomplete or invalid frames are discarded and reception resumes by searching for the next valid SYNC byte.

The baseplate waits up to two seconds for the first byte of the application's feedback response and allows a maximum interval of 100 ms between bytes within that frame. Detection cycles are currently separated by a delay of 550 ms, in addition to the time required for communication within the connected construction. These values describe the implemented prototype and are not general protocol requirements.

5.2.6 Conclusion?

5.3 Firmware of Bricks and Baseplate

ÜBERLEITUNG The firmware is implemented in C++ using PlatformIO and compiled for the ATtiny1616 microcontrollers with an internal clock frequency of 20MHz. Separate firmware variants control the building bricks and the baseplate, while shared modules provide the functions required for single-wire communication, child-brick detection and feedback transmission.

5.3.1 Brick Firmware

The brick firmware is responsible for collecting its local and untergeordnete tree structure and controlling the feedback output. Its implemented control flow is shown in figure Figure 13



Figure 13: State machine of the brick firmware

After initialisation, all communication lines are released and the **LED** outputs are configured. The firmware then monitors the four upstream contacts of the docking face. The index of the contact through which the first valid request is received determines the relative rotation of the brick. The corresponding communication line and orientation value are stored and used for all subsequent communication with the parent. This orientation detection is determined just once after the microcontroller has started. Disconnecting the brick interrupts its centrally supplied power, causing the firmware to restart when the brick is connected again. The orientation is therefore detected again after every new physical connection.

Detection Process

When the brick/state machine enters the detection state, it queries the available downstream interfaces in ascending order. Depending on the brick type this means querying five or for the smashed brick only one interface. The communication with an individual child is handled by a dedicated child-polling function. A sucessful response provides the serialised payload of the child´s complete subtree. This subtree payload is stored temporarily until all configured downstream interfaces have been processed. If a child does not return a valid payload within the available attempts, its subtree is omitted from the current detection result. Successfully received child-subtree payloads are appended in ascending interface order to the brick's own node payload according to the format specified in Section 5.2.3.1.1. For each included child, the corresponding bit in CHILD_MASK is set to one. The resulting complete payload therefore consists of the current bricks own node payload followed by the payloads of its successfully detected child subtrees. It is then transmitted to the parent using the frame and message sequence defined in Section 5.2.

Because every child performs the same processing before returning its result, the complete construction is acquired recursively without requiring an individual brick to store a global representation of the structure.

Correction of the Contact Offset

As described in the mechanical realisation, the downstream data contact of one receiving face of the cube brick could not be placed in the same relative corner as the other downstream contacts. This causes the orientation reported by a child connected to this interface to contain an offset of one quarter turn. The bricks firmware compensates this deviation before it incorpoates the child payload into the parent payload with an incremented modulo four:

$$o_{\text{corrected}} = (o_{\text{detected}} + 1) \bmod 4$$

The learning application therefore does not require an additional interface specific correction because it consequently receives orientation values with a consistent interpretation for all receiving interfaces.

Feedack Processing

When the brick/state machine enters the feedback state, the cube receives and validates the FEEDBACK_FRAME according to Section 5.2.3.2.1. It searches the payload for its own NODE_ID and if it is enthalten it applies the corresponding state to the local **LED** output. If the NODE_ID is not a part of the frame, the **LED** are switched off.

The same FEEDBACK_FRAME is subsequently forwarded to the interfaces marked as occpudied during the preceding detection cycle. With the in Section 5.2 defined messages, the brick then reports to its parent whether the frame was successfully processed and forwarded or not.

5.3.2 Baseplate Firmware

The behaviour of the building-brick firmware is coordinated by the baseplate firmware, which initiates the detection and feedback processes. In addition to controlling the communication session, the baseplate mediates between the learning application and the physical building-brick structure. It does not parse the construction, calculate spatial positions or evaluate the task. These operations are performed by the learning application described in the following Section 5.4.

The implemented control flow of the baseplate is shown in Figure Figure 14.



Figure 14: State machine of the baseplate firmware

After initialisation, the baseplate releases its downstream communication line, configures its hardware USART and enters the idle state. It remains in this state until the learning application starts a new communication session. During an active session, the baseplate repeatedly initiates the detection of the connected construction by querying the brick attached to its single receiving interface. Since this is the first brick of the construction its response already contains the serialised payload of the complete root subtree. If no valid root payload is received, the current construction is represneted by an empty payload. Otherwise, the received subtree payload is forwarded without structural modification to the learning application.

Payload Transmission Control

To avoid transmitting identical construction data during every cycle gibt es bestimmte bedingungen wann die baseplate es zur lwarning application schickt und wann nicht.

The first payload after the beginning of a session is always transmitted, irrespective of a potentially retained result from a preceding session. For every other payload transmission the baseplate compares the current detection payload with the payload transmitted most recently. A new DATA_FRAME is only transmitted when the current payload differs from the preceding one. If the construction remains unchanged, the baseplate sends the unchanged payload erst after 50 detection cycles as a heartbeat. This confirms that the communication link and the detection process remain active without continuously transmitting identical frames.

The current implementation inserts a delay of 550 ms between consecutive detection cycles. The complete interval between two results additionally depends on the number and arrangement of connected bricks as well as on possible retransmission attempts.

Feedback Forwarding and Session Termination

After tranmitting a DATA_FRAME, the baseplate waits for the corresponding FEEDBACK_FRAME from the learning application.It then forwards the frame to the root brick using the same procedure as the feedback processing of the building bricks described in Section 5.3.1.3. Afterwards, the

baseplate reports to the learning application whether the frame was confirmed by the connected construction or not. The baseplate does not interpret the individual feedback entries and nor control the **LED** of the bricks directly. Its role is limited to receiving the frame from the learning application and initiating its distribution through the physical construction.

When the learning application terminates the session, the baseplate forwards an empty feedback frame to the root brick and since no brick NODE_IDs are contained in this payload, all local feedback outputs are switched off. The baseplate then ends cyclic detection and returns to the idle state shown in Figure 14.

5.3.3 Conclusion?

5.4 Software Architecture and Backend Processing

The learning application consists of a Python based backend and a browser based frontend implemented in JavaScript. The backend processes the data exchanged with the baseplate, while the frontend provides the selected target structure and presents the visualised results to the user. In the following chapters the implemented software architecture as well as the backend processing are described. (The implementation of the three-dimensional visualisation as well as the user-facing presentation of feedback are described separately in Section 5.5.)

5.4.1 Implemented Software Architecture

The backend acts as an intermediary between the browser frontend and the baseplate. It communicates with the frontend through a WebSocket connection using JSON objects, while PySerial is used to exchange the binary frames defined in Section 5.2 with the baseplate.

A construction session begins when the frontend transmits the selected target structure to the backend. For each construction received from the baseplate, the backend reconstructs the detected tree, compares it with the selected target and generates a feedback frame for the physical bricks as well as an evaluated tree for the frontend.

The Serial communication is handled by a dedicated worker thread, whereas the WebSocket server operates asynchronously. The two interfaces exchange different data representations: compact binary frames are used for communication with the baseplate, while JSON objects are exchanged with the frontend. Since the prototype uses a single serial interface connected to one baseplate, only one browser based construction session can be active at a time.



Figure 15: Implemented software architecture of the learning application

5.4.2 Deserialisation and Internal Tree Models

The backend receives the detected construction in the payload format defined in Section 5.2.3.1.1. A recursive parser converts this linear byte sequence into an object based tree representation. Starting

with the root node, the parser reads each node header and uses the transmitted CHILD_MASK to identify and recursively reconstruct its subordinate nodes in ascending port order. Each child node is thereby assigned to the receiving port through which it is connected to its parent. Each detected brick is consequently represented by a CubeNode containing

- The complete node identifier
- The relative orientation
- The receiving port through which it is connected to its parent
- The child mask
- The subordinate nodes

After reconstruction, the parser verifies that the complete payload has been consumed. Incomplete node data or remaining bytes cause the payload to be rejected as invalid.

The target construction uses a separate but structurally equivalent tree representation. It is stored as a JSON object and converted by the backend into a TargetNode. Each target node contains the required brick type and orientation, while its child nodes are assigned to the expected receiving ports. Since physical bricks of the same type are interchangeable within the task, the target structure does not contain individual brick identifiers. Both representations nevertheless share the same hierarchical organisation and can therefore be compared recursively.

VLT BEISPIEL EINER SOLCHEN DESERIALIZED NODE/SERIALISED NODE? und TARGET REPRESENTATION ODER TABELLE

5.4.3 Target Comparison and Feedback Data Generation

Once the detected payload has been reconstructed, the comparisons begins at the root nodes of the detected and target strucutres and proceeds recursively through the receiving ports of each brick.

For every position occurring in either structure, the algorithm compares the presence, type, relative orientation and structural placement of the corresponding brick.The individual node identifier is not used to determine if a brick is correctly positioned or not but is retained to address the physical brick when generating local feedback.

The comparison then creates an evaluated tree that combines actual and expected information. Each position is assigned to one of five internal states, as summarised in Table 23

State	Assignment by the comparison algorithm
`CORRECT`	A brick is present with the required type, orientation and connection
`WRONG`	A brick is present but differs from the target
`ATTACHABLE`	A target brick is missing, but its parent has already been placed correctly
`BLOCKED`	A target brick is missing and cannot yet be placed because its parent is missing or incorrect
`UNEXPECTED`	A brick is present where the target does not contain a brick

Table 23: *Internal states of the evaluated construction tree*

If a brick is connected to a receiving port that is not occupied in the target structure, the algorithm searches the remaining unoccupied ports of the same parent for an expected brick of the same type. If such a position exists, the brick is classified as WRONG and the expected port is stored in the comparison result. Otherwise, the brick and its subordinate structure are classified as UNEXPECTED. The comparison also considers the validity of the complete structural path. If a parent brick is missing or incorrect, its subordinate bricks cannot yet occupy valid positions within

the target structure and are therefore marked as `WRONG`. Conversely, an unoccupied target position is classified as `ATTACHABLE` only if its parent path is correct.

In addition to these general internal states, each evaluated node also contains an error mask. Its individual bits indicate wheter the deviation relates to the brick type, orientation, receiving port, parent path or the presence of an unexpected element. This additional separation allows the same comparison result to support different forms and levels of feedback.

When the comparison is done, two output representations are genereted from the evaluated tree: For the physical construction a brick specific feedback data set for all physically present nodes is generetad and converted into the feedback frame defined in Section 5.2.3.2.1. For the frontend, the evaluated tree is converted into a JSON-compatible representation. This representation contains both detected bricks and currently unoccupied target positions, together with their assigned states and expected properties.

(-> The manner in which these results are presented locally and globally is described in Section 5.5.)

5.4.4 Conclusion?

?The backend transfers the evaluated tree to the frontend as a JSON object. Based on the structural and feedback information contained in this representation, the frontend calculates the spatial poses of the individual bricks and generates the user-facing visualisation described in the following section.?

5.5 Frontend, Visualisation and Feedback

ÜBERLEITUNG

5.5.1 Calculation of Spatial Poses

The evaluated tree received from the backend contains no absolute spatial coordinates. Instead, the frontend calculates the position and orientation of each brick from its type, receiving port, relative orientation and parent–child relationship. The same calculation is used for target structures and evaluated constructions.

For the Calulation the implementation uses a local coordinate system for every brick: The z axis represents the vertical axis of the brick and the docking face is oriented towards its local negative z direction. For the cube brick, receiving ports (0) to (4) correspond to the directions (-x), (-y), (+z), (+x) and (+y). The smashed brick provides only one receiving port in its local (+z)-direction. Figure 17 and Figure 18 illustrate this local coordinate system and the orientation values detected at the docking interface.



Figure 17: cube render bild mit koordinatensystem



Figure 18: Local coordinate system and receiving-port assignment of the implemented brick types

For every connection, the local position of a child brick is determined by the direction and distance assigned to the receiving port of its parent:

$$\boldsymbol{p}_{\text{local}} = \boldsymbol{d}_{t,p} \times l_{t,p}$$

where t denotes the type of the parent brick, p the receiving port, $\boldsymbol{d}_{t,p}$ its direction vector and $l_{t,p}$ the distance between the model origins. The distance $l_{t,p}$ depends on the geometry of the parent brick and the selected receiving port. The reduced height of the smashed brick is therefore considered when positioning a child connected to its upper receiving face.

The local orientation of a child is represented using a quaternion which consists an attachment rotation and an additional twist rotation:

$$q_{\text{local}} = q_{\text{attachment}}(t, p) \times q_{\text{twist}}(o).$$

The attachment quaternion $q_{\text{attachment}}(t, p)$ aligns the docking face of the child with the selected receiving face of the parent. The twist quaternion $q_{\text{twist}})(o)$ represents the detected relative rotation o. The four transmitted orientation values are mapped to rotations of 90°, 0°, −90° and −180° around the local z-axis. This assignments aligns the orientation of the digital models with the orientation convention used by the connection-detection system

The first brcik connected to the baseplate forms root of the displayed construction and has therefore no parent brick. Beause of that, its local positon is set to the origin of the scene and its local orientation is derived solely from its transmitted relative rotation value. For every other subordinate brick, the local transformation is combined with the transfomration of its parent:

$$T_{\text{global},c} = T_{\text{global},p} \times T_{\text{local},c}.$$

This calculation is applied recursively throughout the tree. Local connection information is therefore sufficient to derive the global position and orientation of every brick and the backend does not require to transmit absolute coordinates.

Three-Dimensional Visualisation

The resulting construction is then displayed using corresponding GLB Models of the two brick types and placed within a Three.js scene. With the help of orbit controls the scene can be rotated and enlarged through mouse or touch input, allowing the construction to be inspected from different perspectives.



Figure 16: Abbild physische Construction und digitales Abbild

5.5.2 Feedback Presentation/Visual and Local Feedback

The three-dimensional representation of the evaluated construction is extended by visual cues derived from the comparison states described in Section 5.4. These cues are complemented by local

feedback from the LEDs integrated into the physical bricks. Table Table 24 summarises how each state is represented on both feedback levels.

Evaluation state	Representation in the frontend	Feedback on the physical brick
Correct	Green pulsing outline	Green LED light
Wrong or unexpected	Red pulsing outline	Red LED light
Attachable	Semi-transparent ghost brick	No physical output
Blocked	Not displayed	No physical output

Table 24: *Implemented presentation of the evaluation states*



Figure 17: bild mit allen 3 brick types also outline und ghost

Physically present bricks retain the appearance of their corresponding digital models, while coloured outlines indicate the evaluation result. Green represents a correctly positioned brick, whereas red indicates an incorrect or unexpected brick. A currently attachable target brick is displayed semi-transparentlyas a visual indication of an available next construction step. Not displayed are target bricks that cannot yet be reached because their preceding construction path is incomplete.

The global feedback in the frontend is coordinated with the local **LED** feedback of the physical bricks.A brick shown with a green or red outline is illuminated in the corresponding colour. Missing target bricks have no physical counterpart and are therefore represented exclusively in the frontend. Missing target positions do not have a corresponding physical output and are therefore represented only in the frontend.

To signalise both the current construction progress and the completion of the task, a progress bar additionally shows the proportion of the target construction that has already been completed correctly. BILD???

5.5.3 User Interface and Task Selection

The visualisation process is not limited to displaying the detected bricks and their feedback states during the construction task. It begins on the dashboard, where the learner selects the target strucutre that defines the subsequent task.

The dashboard presents the available target constructions as selectable cards. Each card contains a three-dimensional preview generated from the corresponding target-tree data. Selecting a card opens an enlarged preview window in which the construction can be rotated and inspected

from different viewing angles. The learner can then either cancel the selection and return to the dashboard or confirm the selected construction.

The preview window additionally contains two level options from which the learner can choose. Although the selected level is transferred together with the target structure, it does not currently affect the task behaviour. It is intended to support a future differentiation of task difficulty.

After the target structure has been confirmed, the live construction view is opened and the selected target is transferred to the backend. During the task, this view displays the evaluated construction using the spatial reconstruction and feedback representations described in the preceding sections. The progress bar is placed at the top of the interface and indicates the proportion of the target construction that has already been completed correctly.

The construction session can be terminated using the button in the upper area of the live view. The frontend then returns to the dashboard, where another target construction can be selected.

ABBILDUNG so drei oder vier bilder die den process visualisieren mit zuerst auswahl interface dann preview und dann aufgabe



Figure 19: Target selection



Figure 20: review and confirmation



Figure 21: Construction and feedback

5.5.4 Conclusion?

sagen dass nur aus lokalen informationen der bausteine ausreichen umd die gloablen positionen zu berechnen - oder das vlt am ende in conclusion zusammen mit dem fact dass lokale informationen ausreichen um global die konstruktion zu bewerten/vergleichen The same tree-building implementation is used for the target

additional separation of error mask -> different feedback possible

anforderungen
- rot grün

550ms

6 Evaluation

ca 10 seiten

6.1 Aim and Scope

- Ziel: Erfüllung der Anforderungen aus der Anforderungsanalyse prüfen
- Zielgruppentest umfasst Würfelgestaltung und Lernanwendung
- automatische elektronische Erkennung war nicht funktionsfähig
- technische Komponenten werden deshalb nur separat beziehungsweise analytisch bewertet (requirements based prototype assessment)
- keine Untersuchung der langfristigen Lernwirkung

6.2 Methodology

6.2.1 Target-Group Evaluation

A formative evaluation was conducted to investigate the accessibility of the physical building bricks and the usability of the learning application for the intended target group. At the time of the target-group evaluation, the electronic construction-detection system was not yet sufficiently reliable for use during the construction tasks. The evaluation therefore focused on the physical interaction with the building bricks and the use of the learning application, including the selection and visualisation of target structures and the learners ability to relate the digital representations to the physical bricks.

Participants and Setting

The evaluation took place with 10 students attending the sixth year of a special education school. The class included students with educational support needs related to **GE**, **LE** and **ASD**. The evaluation took place in the students' regular school environment and lasted approximately two hours. The tasks were initially completed individually. During the later part of the session, several students also worked together in pairs. The session was supervised by the researcher and the attending teachers, who provided assistance when necessary.

Materials and Tasks

Eight physical prototype bricks were available, comprising four bricks of each of the two implemented brick types. The electronic components were not used during the session. The learning application was presented on a touchscreen tablet. It displayed a selection of target structures from which the students could choose. After confirming their selection, the chosen target structure was displayed as an interactive three-dimensional model in full-screen mode. The model could be rotated to inspect the construction from different perspectives. The available tasks varied in complexity. Simple target structures consisted of three bricks with similar orientations, whereas more complex structures contained up to all eight available bricks and included different spatial arrangements and orientations.



einfach 22: Bild 1



mittel 23: Bild 2



schwer 24: Bild 3

- elektronik (bedeutet die erfassung der aktuellen construction, die visualisierung dieser und das daraus resultierende abgleich mit der ziel konstruktion sowie das feedback) wurde nicht verwendet -> deshalb wurden nur die physischen würfel (also wie die kinder die würfel greifen und verbinden können, ob es sich gut auseinander und verbinden lässt, ob sie verstehen welche seiten miteinander verbunden werden können und welche nicht (constraint), ob sie generell verstehen dass es sich bei den objekten um zusammensteckbare würfel handelt, ob das gleichgewicht zwischen stabilität (von den magneten) und leichtes verbinden stimmt) und die lernanwendung mit der funktion auswahl einer zielkonstruktion und darstellung der kompletten zielkonstruktion, damit man sieht was man bauen muss, getestet (es wurde deshalb wie verständlich die zielstruktur auswahl ist, ob die kinder anhand der visualisierten ziel construktion erkennen können was sie bauen müssen und ob die physischen würfel mit ihrem digitalen abbild verknüpft werden konnten, geprüft)

Procedure

At the beginning of the session, the students were introduced to the general purpose of the system and the reconstruction task. Each student was subsequently invited to select a target structure in the learning application and reproduce it using the physical bricks. Depending on interest and available time, students could complete more than one task. During construction, the students could interact with the three-dimensional target visualisation and rotate it to inspect the structure from different viewing angles. In the later part of the session, students were also allowed to complete tasks collaboratively in pairs. Assistance was provided gradually when required. Initially, verbal hints were given. If these were insufficient, the target visualisation was rotated to provide a more suitable viewing angle or the relevant brick was indicated on the screen. At the next level of assistance, the appropriate physical brick was provided to the student. Only when these forms of support were insufficient did the researcher or a teacher demonstrate or perform the required connection.

—-deutsch Ablauf:

- zuerst wurde erklärt worum es generell geht und was die aufgabe ist
- dann durfte jedes kind der reihe nach vorkommen und eine oder auch mehrere aufgaben bewältigen
  - kind hat sich eigenständig seine zielkonstruktion ausgewählt, nur vereinzelt wurde dabei geholfen
  - kind hat eigenständig versucht zu bauen, wieder nur bei manchen musste geholfen werden
  - kinder haben dabei auch immer wieder die digitale visualisierung der zielkonstruktion genutzt und diese gedreht sodass sie die konstruktion von verschiedenen winkeln aus betrachten konnten
  - im späteren verlauf haben dann auch viele kinder zu zweit an einer aufgabe gebaut und zusammen veruscht es zu lösen

- hilfestellung wurde nur beim akzeptieren der ausgewählten zielkonstruktion (lag daran dass der button auf dem bidlschirm zu klein war bzw nicht sofort reagiert hat) und auch beim konstruieren und vor allem beim relativen anordnen von einem baustein auf den anderen gegeben. das feedback sah so aus, dass zuerst verbal versucht wurde den kindern tipps zu geben, dann wurde für die kinder die digitale darstellung der zielkonstruktion gedreht sodass sie den gerade zu verbindenden baustein besser sehen können oder man hat mit dem finger auf diesen baustein gezeigt. und wenn das auch nicht gereicht hat dann wurde dem kind zuerst der richtige baustein gegeben und wenn nicht ausgereicht hat habe dann ich oder die lehrkraft den baustein mit dem ziel parent baustein verbunden.
- manche kinder haben auch sofort verstanden dass sie die zielkonstruktion mit dne bausteinen nachbauen müssen und bei manchen hat man es zuerst ein paar mal vorgemacht und die bausteine verbunden und dann sie es aber selber machen lassen

6.2.2 Data Collection

Data were collected through qualitative observation of the students' interaction with the physical bricks and the learning application. The evaluation did not aim to measure learning outcomes. Instead, it examined the comprehensibility and usability of the interaction concept during the session.

Regarding the physical bricks, the observation focused on:
- whether the students recognised the objects as building bricks intended to be connected
- whether they understood which faces could be connected and how the two brick types differed
- whether they could grasp, position, connect and disconnect the bricks
- whether the magnetic connections provided sufficient stability while remaining easy to separate
- whether the students could use the bricks to construct three-dimensional arrangements

Regarding the learning application, the observation focused on:
- whether the students understood the construction task presented by the application
- whether they could relate the digital representations to the corresponding physical bricks
- whether they could select and confirm a target structure
- whether buttons and other interactive elements were recognised and operated correctly
- whether they could manipulate the three-dimensional model
- what type and level of assistance they required during these interactions

FEHLT: wie habe ich die beobachtungen festgehalten: durch notizen während und unmittelbar nach der Durchführung

—deutsch also wie die kinder die würfel greifen und verbinden können, ob es sich gut auseinander und verbinden lässt, ob sie verstehen welche seiten miteinander verbunden werden können und welche nicht (constraint), ob sie generell verstehen dass es sich bei den objekten um zusammensteckbare würfel handelt, ob das gleichgewicht zwischen stabilität (von den magneten) und leichtes verbinden stimmt) und die lernanwendung mit der funktion auswahl einer zielkonstruktion und darstellung der kompletten zielkonstruktion, damit man sieht was man bauen muss, getestet (es wurde deshalb wie verständlich die zielstruktur auswahl ist, ob die kinder anhand der visualisierten ziel construktion erkennen können was sie bauen müssen und ob die physischen würfel mit ihrem digitalen abbild verknüpft werden konnten, geprüft. und noch wie intuitiv und verständlich die lernanwendung ist, mit buttons und allem)

6.2.3 Requirements-Based Assessment/Assessment of the Remaining Requirements

Inspection and Software-Based Assessment

Assessment Criteria

nur bewertungsstufen definieren -> anforderung kann
- fulfilled
- partially fulfilled
- implemented but not verified
- conceptually addressed
- not fulfilled
- not evaluated

6.3 Results

6.3.1 Results of the Target-Group Evaluation

Physical Interaction with the Building Bricks

Hier behandelst du ausschließlich die physische Handhabung:
- Erkannten die Kinder, dass die Bausteine verbunden werden können?
- Konnten sie die Bausteine greifen und positionieren?
- War eine einhändige Bedienung möglich?
- Konnten die Magnete ohne zu viel Kraft verbunden und getrennt werden?
- Waren die Verbindungen stabil genug?
- Wurden Andock- und Aufnahmeseiten unterschieden?
- Wurden ungültige Seitenkombinationen ausprobiert?
- Konnten dreidimensionale und verzweigte Strukturen gebaut werden?
- Gab es Unterschiede zwischen den beiden Bausteintypen?
- Kam es zu unbeabsichtigtem Lösen, Verrutschen oder falscher Ausrichtung?

Hier kannst du auf C3–C6, TASK1, IA1, IA5 und TUI3 Bezug nehmen.

Usability of the Learning Application

Hier geht es um die Bedienung, nicht primär um das räumliche Verständnis:
- Konnten die Kinder selbstständig eine Zielkonstruktion auswählen?
- Wurde die Auswahlübersicht verstanden?
- Wurde der Bestätigungsbutton gefunden und zuverlässig ausgelöst?
- Wie häufig war bei der Auswahl Hilfe nötig?
- Konnten die Kinder die 3D-Ansicht selbstständig drehen?
- War die Touchbedienung verständlich?
- Welche Buttons oder Interaktionen bereiteten Schwierigkeiten?
- Wurde die Vollbilddarstellung sinnvoll genutzt?

Deine Beobachtung, dass der Bestätigungsbutton zu klein war oder nicht sofort reagierte, gehört genau hierher. Beispiel: Most students were able to select a target structure independently. However, confirming the selection occasionally required assistance because the corresponding button was comparatively small and did not always respond immediately to touch input.

Anforderung IA2 IA3 TUI3

Comprehension of Tasks and visual representations

Hier geht es darum, ob die Kinder verstanden, was sie bauen sollten:

- Verstanden sie nach der Einführung das Prinzip des Nachbauens?
- Bei wie vielen Kindern war zunächst eine Demonstration notwendig?
- Konnten sie die digitale Zielkonstruktion den physischen Bausteinen zuordnen?
- Wurden die beiden Bausteintypen korrekt unterschieden?
- Konnten sie Anzahl, Position und Orientierung der Bausteine erkennen?
- Half das Drehen der Visualisierung beim räumlichen Verständnis?
- Waren einfache Zielstrukturen verständlicher als komplexe?
- Wo traten Fehler bei der relativen Anordnung auf?
- Wurde aus unterschiedlichen Perspektiven erkannt, welcher Würfel mit welchem verbunden werden musste?
- Welche Rolle spielte die Zusammenarbeit zu zweit?

Deine Aussage, dass manche Kinder die Aufgabe sofort verstanden und andere zunächst eine Demonstration benötigten, gehört hierher.

(observed difficulties and required assistance)
braucht es nicht unbedingt Dieses Unterkapitel ist sinnvoll, wenn du die unterschiedlichen Hilfestufen gezielt auswertest. Behandle: häufigste Schwierigkeiten
- Situation, in der sie auftraten
- Art der benötigten Hilfe
- niedrigste ausreichende Hilfestufe
- Unterschiede zwischen Auswahl, räumlichem Verständnis und physischem Bauen
- wiederkehrende Probleme
- Situationen, die vollständig übernommen werden mussten
- ob Kinder nach einer Demonstration weitere Schritte selbstständig ausführten

Du kannst deine Hilfestufen als Ordnung verwenden:
- keine Unterstützung
- verbaler Hinweis
- Drehen oder Zeigen in der Visualisierung
- Bereitstellen des richtigen Bausteins
- Demonstration oder physisches Verbinden durch eine betreuende Person

6.3.2 Results of the Requirements-Based Assessment

Physical and Mechanical Requirements

Detection and Data Processing

Target Comparison and Feedback

Technical, Safety and Economic Requirements

6.4 Overall Requirement Fulfilment

tabelle

6.5 Discussion

6.5.1 Interpretation of the Results

6.5.2 Limitations

Methodology: Was wurde wie, mit wem und nach welchen Kriterien geprüft? Results: Was wurde dabei beobachtet beziehungsweise festgestellt? Discussion: Was bedeuten diese Ergebnisse?

6.6 Notizen

- kinder haben den anderen kindern geholfen - space multiplexing, automatisch zur gruppenarbeit gefördert
- viel ausprobiert, keine angst vor fehlern

aus dem grsrpäch mit lehrerin

- lernanwendung multimodal - auch feedback hören und nicht nur sehen, hilfetext der auch vorgelesen werden kann
- bausteine farben noch mehr conträr
- viele bilder wenig text in der learning application

The system-generated feedback is primarily visual and therefore does not constitute fully multidimensional feedback in the sense of IA6. It is nevertheless distributed across several complementary levels.

7 List of Abbreviations

ASD	Autism Spectrum Disorder	**RGB**	red-green-blue
GE	Special education focus on intellectual development	**TUI**	Tangible User Interface
GUI	Graphical User Interface	**UI**	User Interface
LE	Special education focus on learning	**rep_d**	Digital Representation
LED	Light-Emitting Diode	**rep_p**	Physical Representation
MVC	Model View Controller		

References

[1] Kulusministerium, "Empfehlungen Zur Schulischen Bildung, Beratung Und Unterstützung Im Sonderpädagogischen Schwerpunkt Geistige Entwicklung," Mar. 2021.

[2] S. Asmussen, "Empfehlungen zur schulischen Bildung, Beratung und Unterstützung von Kindern und Jugendlichen im sonderpädagogischen Schwerpunkt LERNEN: Beschluss der Kultusministerkonferenz vom 14. März 2019," *Sonderpädagogische Förderung heute*, no. 2, pp. 122–128, Jul. 2020, doi: 10.3262/SZ2002122.

[3] Kulusministerium, "Leitlinien Des Bundesverbandes_autismus Deutschland e.V. Zur_inklusiven Beschulung von Schuelern mitASS," Feb. 2013.

[4] Kulusministerium, "Inklusive Bildung von Kindern und Jugendlichen mit Behinderungen in Schulen," Oct. 2011.

[5] Kultusministerium, "Empfehlung Zum Förderschwerpunkt Sprache." Jun. 26, 1989.

[6] N. Pookkottuvariam, "Tangible User Interfaces for Children with Learning Disorders." Accessed: Mar. 04, 2026. [Online]. Available: https://nivedithaartist.medium.com/tangible-user-interfaces-for-children-with-learning-disorders-ec083378de6a

[7] B. Zimmerman, "Becoming a Self-Regulated Learner: An Overview," *Theory Into Practice*, vol. 41, pp. 64–70, Jun. 2002, doi: 10.1207/s15430421tip4102_2.

[8] D. Butler and P. Winne, "Feedback and Self-Regulated Learning: A Theoretical Synthesis," *Review of Educational Research*, vol. 65, p. 245, Sep. 1995, doi: 10.2307/1170684.

[9] B. Vollmers, "LEARNING BY DOING – PIAGETS KONSTRUKTIVISTISCHE LERNTHEORIE UND IHRE KONSEQUENZEN FÜR DIE PÄDAGOGISCHE PRAXIS," *International Review of Education*, vol. 43, no. 1, pp. 73–85, Jan. 1997, doi: 10.1023/A:1002918202220.

[10] I. Harel and S. Papert, "Constructionism: Research Reports and Essays, 1985–1990," *Ablex Publishing Corporation*, pp. 1–12, 1991.

[11] A. Semenov, "Seymour Papert and Us. Constructionism as the Educational Philosophy of the 21st Century," *Voprosy Obrazovaniya / Educational Studies Moscow*, no. 1, pp. 269–294, Mar. 2017, doi: 10.17323/1814-9545-2017-1-269-294.

[12] S. Papert, *Mindstorms: Children, Computers, and Powerful Ideas*, 2nd edition. New York, NY: Basic Books, 1993.

[13] M. Liang, Y. Li, T. Weber, and H. Hussmann, "Tangible Interaction for Children's Creative Learning: A Review," in *Creativity and Cognition*, Virtual Event Italy: ACM, Jun. 2021, pp. 1–14. doi: 10.1145/3450741.3465262.

[14] P. Dourish, "Embodied Interaction: Exploring the Foundations of a New Approach to HCI," Feb. 1999.

[15] O. Shaer and E. Hornecker, "Tangible User Interfaces: Past, Present, and Future Directions," *Foundations and Trends® in Human–Computer Interaction*, vol. 3, no. 1–2, pp. 1–137, 2009, doi: 10.1561/1100000026.

[16] H. Ishii and B. Ullmer, "Tangible Bits: Towards Seamless Interfaces between People, Bits and Atoms," in *Proceedings of the ACM SIGCHI Conference on Human Factors in Computing Systems*, Atlanta Georgia USA: ACM, Mar. 1997, pp. 234–241. doi: 10.1145/258549.258715.

[17] H. Ishii, "Tangible Bits: Beyond Pixels," in *Proceedings of the 2nd International Conference on Tangible and Embedded Interaction*, Bonn Germany: ACM, Feb. 2008. doi: 10.1145/1347390.1347392.

[18] B. Ullmer, H. Ishii, and R. Jacob, "Token+constraint Systems for Tangible Interaction with Digital Information," *ACM Trans. Comput.-Hum. Interact.*, vol. 12, pp. 81–118, Mar. 2005, doi: 10.1145/1057237.1057242.

[19] B. Ullmer and H. Ishii, "Emerging Frameworks for Tangible User Interfaces," *IBM Systems Journal*, vol. 39, no. 3.4, pp. 915–931, Aug. 2001, doi: 10.1147/sj.393.0915.