

Projeto 1 - Sistemas Operacionais

Elton Mauricio Da Silva - RA 11201810955

link de arquivos: <https://github.com/eltonmds/ufabc_operational_systems>

1 Problema 1

Código

Para melhor organização do código, foram criadas as seguintes classes:

MQP - Uma implementação que representa a Multilevel Queue Priority

```
from process import Process
from typing import List
import operator

class MQP:
    def __init__(self) -> None:
        self.priority_0: List[Process] = []
        self.priority_1: List[Process] = []
        self.priority_2: List[Process] = []
        self.priority_3: List[Process] = []

    def is_empty(self) -> bool:
        for i in range(4):
            if eval(f"len(self.priority_{i}) > 0"):
                return False

        return True

    def insert_process(self, process: Process) -> None:
        eval(f"self.priority_{process.priority}.append(process)")

    def remove_process(self, process: Process) -> None:
        eval(f"self.priority_{process.priority}.remove(process)")

    def increase_priority(self, process: Process) -> None:
        process.priority -= 1
        eval(f"self.priority_{process.priority}.append(process)")
        eval(f"self.priority_{process.priority + 1}.remove(process)")

    def find_biggest_cpu_burst(self, priority_list: List[Process]) -> None:
        priority_list.sort(key=operator.attrgetter("CPU_burst"))
        biggest_process: Process = priority_list[-1]
```

```

        return biggest_process

def find_smallest_cpu_burst(self, priority_list: List[Process])
    -> None:
    priority_list.sort(key=operator.attrgetter("CPU_burst"))
    biggest_process: Process = priority_list[0]
    return biggest_process

def change_smallest_priority_process(self) -> None:
    for i in range(3, 0, -1):
        current_level = eval(f"self.priority_{i}")
        if len(current_level) > 0:
            biggest_process = self.find_biggest_cpu_burst(
                current_level)
            self.increase_priority(biggest_process)
            break

def increase_wait_time(self, current_process: Process) -> None:
    for priority in range(4):
        for process in eval(f"self.priority_{priority}"):
            if process != current_process:
                process.wait_time += 10

def print_processes(self) -> None:
    print("  "+"-" * 15 + "+" + "-" * 8 + "+" + "-" * 9 + "+"
          )
    print(f"    |{'process_name':15}|{'priority':8}|{'CPU_burst':9}
          |")
    print("  "+"-" * 15 + "+" + "-" * 8 + "+" + "-" * 9 + "+"
          )

    for i in range(4):
        for process in eval(f"self.priority_{i}"):
            process.print_table()

    print("  "+"-" * 15 + "+" + "-" * 8 + "+" + "-" * 9 + "+" \
          n")

```

Process - implementação de uma estrutura de dados para representar os processos

```

class Process:
def __init__(self, name: str, priority: int, CPU_burst: int) ->
    None:

    self.name = name
    self.priority = priority

```

```

        self.CPU_burst = CPU_burst
        self.wait_time = 0

    def print_table(self) -> None:
        print(f"    |{self.name:15}|{self.priority:8}|{self.CPU_burst:9}|")

    def print_info(self) -> None:
        print("    " + "+" + "-" * 18 + "+" + "-" * 13 + "+")
        print(f"    |{'Process name':18}: {str(self.name):12}|")
        print(f"    |{'Process priority':18}: {str(self.priority):12}|")
        print(f"    |{'Process CPU_burst':18}: {str(self.CPU_burst):12}|")
        print(f"    |{'Process wait_time':18}: {str(self.wait_time):12}|")
        print("    " + "+" + "-" * 18 + "+" + "-" * 13 + "+")

```

E então, utilizadas as classes no código principal

```

from time import sleep
from typing import Tuple, List
import logging

from process import Process
from mqp import MQP
from scheduler import Scheduler

logging.basicConfig()
logger = logging.getLogger("")
logger.setLevel(logging.INFO)

def create_process(input: Tuple[str]) -> Process:
    process = Process(input[0], int(input[1]), int(input[2]))
    if process.priority not in range(4):
        Exception("Priority must be between 0 and 3")
        pass

    return process

def receive_user_input() -> List[tuple]:
    processes_attributes: List[str] = []

    with open("processes.txt", "r") as processes:
        lines = processes.readlines()
        for line in lines:

```

```
        line = line.split(", ")
        processes_attributes.append(tuple(line))

    processes.close()

    return processes_attributes

def receive_processes(processes_attributes: List[tuple]) -> MQP:
    mqp: MQP = MQP()

    for process_attribute in processes_attributes:
        new_process: Process = create_process(process_attribute)
        logger.info(f"New process created: {new_process.name}")

        mqp.insert_process(new_process)

    return mqp

def select_process(mqp: MQP) -> Process:
    for i in range(4):
        current_priority_level = eval(f"mqp.priority_{i}")
        if current_priority_level:
            chosen_process = mqp.find_smallest_cpu_burst(
                                                                    current_priority_level
                                                                    )

            return chosen_process
    else:
        logger.info("No processes to select")
        return None

def main():
    processes_input = receive_user_input()
    mqp = receive_processes(processes_input)

    print("This are the processes received: ")
    mqp.print_processes()

    while not mqp.is_empty():
        current_process = select_process(mqp)
        logger.info("Executing the following process:")
        current_process.print_info()
        while current_process.CPU_burst > 0:
```

```
        current_process.CPU_burst -= 10
        sleep(10)
        mqp.increase_wait_time(current_process)
        mqp.change_smallest_priority_process()

        logger.info(f"Process finished: {current_process.name}\n")
        mqp.remove_process(current_process)

    logger.info("All processes terminated")

if __name__ == "__main__":
    main()
```

O programa recebe os processos através do arquivo ‘processes.txt’. A partir do texto recebido, cria instâncias da classe Process para representar os processos.

Após isso, instancia a classe MQP para trabalhar com a Multilevel Queue Priority. E então printa uma tabela contendo os processos recebidos.

A partir disso entra em um loop principal, que só será interrompido quando não há mais processos para rodar, isto é, quando todas as listas de prioridades estiverem vazias.

A cada iteração, é feito o processo de seleção do processo atual, que segue as seguintes regras: - Maior prioridades * Maior CPU-Burst

Escolhido o processo atual, são printadas as informações a respeito do mesmo. E então entra em um segundo loop, onde é simulada a execução do processo. Onde a cada 10 unidades de tempo (determinadas pela função sleep): - É aumentado o $wait_time$ dos demais processos em 10 – É aumentada em 1 a prioridade do processo com o maior CPU_Burst

Resultados

```

INFO:root:New process created: Paint
INFO:root:New process created: Meu joguinho
INFO:root:New process created: Firefox
These are the processes received:
+-----+-----+-----+
|process_name|priority|CPU_burst|
+-----+-----+-----+
|Meu joguinho|        0|       190|
|Firefox     |        0|        20|
|Paint       |        2|         1|
+-----+-----+-----+

INFO:root:Starting the scheduling process...
INFO:root:Executing the following process:
+-----+-----+
|Process name      : Firefox|
|Process priority  : 0|
|Process CPU_burst : 20|
|Process wait_time : 0|
+-----+-----+
INFO:root:Process finished: Firefox

INFO:root:Executing the following process:
+-----+-----+
|Process name      : Paint|
|Process priority  : 0|
|Process CPU_burst : 1|
|Process wait_time : 20|
+-----+-----+
INFO:root:Process finished: Paint

INFO:root:Executing the following process:
+-----+-----+
|Process name      : Meu joguinho|
|Process priority  : 0|

```

Os primeiros outputs indicam a criação dos processos que vieram do arquivo ‘processes.txt’. Mais informações a respeito deles é mostrada na primeira tabela.

Então é printado "Starting the scheduling process" que indica que entrou na fase de escolar os processos. E então, para cada processo executado, é printada uma tabela com as seguintes informações: * Nome do processo * Prioridade do processo * CPU_{burst} do processo * $tempo de espera$ do processo

Após cada processo ser finalizado, é printado "Process finished" indicando que aquele processo foi finalizado.

2 Problema 2

Código

```

1  #include <sys/wait.h> /* system call - wait */
2  #include <stdint.h> /* system call - wait */
3  #include <stdlib.h> /* system call - exit */
4  #include <unistd.h> /* system call - fork, exec, sleep */
5  #include <stdio.h>
6  /* Lib - System Call Signal */
7  #include <signal.h>
8
9  // Variaveis globais
10 int file1Open = 1; /* Arquivo hipotetico 1 */
11 int file2Open = 1; /* Arquivo hipotetico 2 */
12 int valor1 = 500;
13
14 void finish_process() {
15     file1Open = 0;
16     file2Open = 0;
17     printf("Arquivos fechados!\n");
18     printf("O conte do de 'valor1' : %d\n", valor1);
19     printf("Encerrando o processo...\n");
20     exit(0);
21 }
22
23 /* Definicao da funcao em C que ira tratar das interrupcoes */
24 void signal_handler(int signum) {
25     if (signum == SIGTERM) {
26         finish_process();
27     }
28     else if (signum == SIGINT) {
29         char deseja_parar;
30         printf("Deseja realmente parar o processo? Se sim, digite x.\n"
31 );
32         scanf("%c", &deseja_parar);
33         if (deseja_parar == 'x' || deseja_parar == 'X') {
34             finish_process();
35         }
36     }
37 }
38
39 int main() {

```

```
41     signal(SIGINT, signal_handler);
42     signal(SIGTERM, signal_handler);
43
44     pid_t pid;
45     pid = fork();
46     if (!pid) {
47         printf( "Sou o FILHO. %d\n", getpid() );
48         return 0;
49     }
50     else if (pid) {
51         printf( "Sou o PAI. %d\n", getpid() );
52         valor1 /= 20;
53         wait(NULL);
54         while (1);
55         printf(
56             "O status do file1Open eh %d e o file2Open eh %d \n",
57             file1Open, file2Open
58         );
59         printf( " O valor1 = %d\n", valor1 );
60         return 0;
61     }
62 }
```