



DETAIL A

- | | |
|---------------------------------------------------------|----------------------------------------------------|
| 1. Airspeed indicator | 26. Gearbox oil temperature and pressure indicator |
| 2. Marker beacon light | 27. Dual DC ammeter |
| 3. NAV CMD CPLT PLT light | 28. Fire 2 pull handle |
| 4. PITCH ROLL YAW light | 29. Engine 1 out indicator |
| 5. Attitude indicator | 30. Gas producer tachometer indicator |
| 6. Horizontal situation indicator | 31. Inter turbine temperature indicator |
| 7. Clock | 32. Engine oil temperature and pressure indicator |
| 8. Master caution light | 33. Fuel pressure indicator |
| 9. Altimeter | 34. Dual AC and DC voltmeter |
| 10. Vertical speed indicator | 35. Engine 2 out indicator |
| 11. RPM caution light | 36. DME indicator |
| 12. Triple tachometer | 37. Radar altimeter indicator |
| 13. Dual torque pressure indicator | 38. NAV fail lights |
| 14. Fire 1 pull handle | 39. Panel typical to PT6T-3B engines |
| 15. Cargo release — armed indicator | 40. Static source switch |
| 16. Baggage compartment fire indicator | |
| 17. Airspeed limits — typical | |
| 18. Hydraulic temperature and pressure indicator | |
| 19. Fuel quantity selector switch | |
| 20. Master caution panel | |
| 21. Fire extinguisher test switch | |
| 22. Fire extinguisher selector switch | |
| 23. Baggage compartment fire test switch | |
| 24. Fuel quantity indicator | |
| 25. Transmission oil temperature and pressure indicator | |

NOTES

- 1 Helicopter S/N 31125 and subsequent
- 2 Helicopters with alternate static air.

212-M-95-2
212-075-718K
212-075-043B

Figure 95-2. Instrument panel (S/N 30597 and subsequent)