

VERO STATUS 4.1.0 - COMPLETE SOURCE FOR REBUILD

Jira ASPF-1578 · Quality AI Automation · a document only: nothing in it runs

What this is: the full source (27 text files) of "Vero Status", a small program that shows in the browser whether Vero is available and which model it uses. Python 3.8+ standard library only. The guide PDF is sent separately.

INSTRUCTIONS FOR THE AI ASSISTANT (Vero CLI or other) - recreate the project folder EXACTLY:

- 1. Create the folder vero-status in the location the user gives (default C:\Tools\).
- 2. Every file starts with a row "=== FILE: <path> (<n> lines) ===" and ends with "=== END FILE: <path> ===".
- 3. Rows between them encode the file, one source line per numbered row:
 - " 12 | content" -> line 12. Every `␣` (open box) in the content is ONE SPACE. It marks leading spaces, runs of 2+ spaces and spaces at a row edge; single spaces between words are printed normally. The `␣` character never occurs in the real files.
 - " 12 |" -> line 12 is an empty line.
 - " + more" -> continuation of the previous line: append "more" directly (no space, no newline). Ignore page headers/footers ("Vero Status ... source for rebuild", "page N").
- Line numbers must run 1..n without gaps; n is in the FILE row. Every file ends with a newline.
- 4. Write files as UTF-8 without BOM, LF line endings. Do not reformat, translate, summarise or "fix" anything.
- 5. Create verify_rebuild.py from the section VERIFY SCRIPT at the end (same row rules), OUTSIDE the project folder, and run: `py verify_rebuild.py C:\Tools\vero-status`
It checks every file's SHA-256 and sets CRLF line endings where Windows needs them (.cmd, START_HERE.txt).
Recreate any file reported MISSING or DIFFERENT, then run it again until it prints "OK: all files match".
- 6. Run the tests inside the folder: `py -m unittest discover -s tests -t .` Expected: OK (43 tests).
- 7. Tell the user it is ready: double-click "Vero Status.pyw" to open the dashboard (see START_HERE.txt).
Do not start the program or call the real Vero CLI unless the user asks.

FILE LIST (path · lines · line endings · SHA-256 of the content with LF endings)

.gitattributes	7	LF	efa38e63b1747daed572feeff39747d40fd4cfa3a4568b11815cb0bf24332d96
.gitignore	8	LF	b592d17a523d7d8d8bd950419afdeb5f502d4aedd8b65a2887bd71f0c514aa33
CHANGELOG.md	26	LF	c204aa6705f127ab83838a09b86bf53d81f01302f3fa4ecc421a16a5638d7fb3
README.md	56	LF	a8c51af5d383ee16112064a4dd3b7cfa2611f3cbb1dbf2346728a7f59a31958c
START_HERE.txt	20	CRLF	e3e61140954e96168ca25e366ccb9384c45ef2a66fc04baa2f845eaf2da4ab25
VERO_CONTEXT.md	90	LF	4d0096cbb9c0611382b7c7ebbe7f973113cbe9592b4d1613d6fe946a560e5879
Vero Status.pyw	10	LF	d225f8171b6196c264964f66cba8c2992695a171db6c2f047f9c694fb8358197
pyproject.toml	23	LF	7c7fb77552e509d6f9a045acc9572b1d58fc39be77641b7f2a1c0d053816d4de
scripts/build_source_pdf.py	224	LF	b9a3be159fd0cc1b45cd61fb7cca9fc3e3bf695782a5094b01f547bd71275e5b
scripts/fake_session.py	40	LF	5fa5b85d17b1e8ae07e72460a01f242d7e5223c55eb96f4d6d31fb8087a007a7
scripts/fake_vero.py	56	LF	4908eb33e4a64621f955e551ef0efce2e644ca3a6ba51e9c202b80cf01d35ae8
scripts/vero	2	LF	45890958a3fcd4e02f1d4c41412869e6f71a9efe2d2d237cd54cf8d84e001fa
scripts/vero.cmd	2	CRLF	15e9a293d205d911b2e2746af1c4361906c0b4138dc111be5acc2a653a6cd0ca
tests/__init__.py	1	LF	8d8ab1348161355b2c6856609575f5becac99c397071c7dcdad95d00597f39fb
tests/helpers.py	29	LF	1ee6057626c3d29cae5cca50a5a4583151c3c6d109d17927c066263c15523e03
tests/test_monitor_server.py	210	LF	746821fbefb1f1169423819dc22cde42ea4ec76fd90691c8c291462e95c19b07
tests/test_sessions.py	179	LF	43bdad94e16e14218b6f56db17f214e935b1f8cb2bf1cc66465a3a74badba395
tests/test_settings.py	46	LF	d5c501ab341e42d07021d55e29832d40a0780fa8bac8fae525af14359183b836
tests/test_vero.py	98	LF	00f1697582183a59e1b0c852dd3f37bbd6fa8d4a0df42ae1294d3b2cde09a44e
vero_status/__init__.py	4	LF	0aaed8f1fa0dec4641e0b02b86f420873f32b599a1887f1d17ad297f0ded25e7
vero_status/app.py	84	LF	e1149390fa4df886d89d37f0fd6f4be93ca73f383e47b8e6b8196711764641b0
vero_status/monitor.py	221	LF	50184a8628ae8d551895cdd6289d783ece06017a85e20ca59b39fee73ffded29
vero_status/server.py	104	LF	4fe22178766d0357e85bb164bbcfbac66555c8914a9b8b68b026e2365c3cc851
vero_status/sessions.py	288	LF	5d218fb0c05c05def10b3e1b0e4be13ffff6f7e179ceed82930281be810f62fb
vero_status/settings.py	65	LF	d362a34291c878bc40a6a3998a3a19633e9918aa1ac8d4352f0add2618c47d2d
vero_status/vero.py	203	LF	47fe1603472d1c5950d5a499de60694a2cad4d4ee016f2cb7f5c1c16cd30b87b
vero_status/web/index.html	335	LF	9755757eea237912426b9b46d008fb665514dd1d2fe4f05841ee5c0b33f00b59

```
=== FILE: .gitattributes (7 lines) ===
1 | * text=auto
2 | *.py text eol=lf
3 | *.pyw text eol=lf
4 | *.md text
5 | *.cmd text eol=crlf
6 | START_HERE.txt text eol=crlf
7 | scripts/vero text eol=lf
=== END FILE: .gitattributes ===
```

=== FILE: .gitignore (8 lines) ===

```
1 | __pycache__/  
2 | *.py[cod]  
3 | data/  
4 | dist/  
5 | .venv/  
6 | .mypy_cache/  
7 | .ruff_cache/  
8 | *.egg-info/
```

=== END FILE: .gitignore ===

```
=== FILE: CHANGELOG.md (26 lines) ===
```

```

1 | # Changelog
2 |
3 | ## 4.1.0
4 | - New panel **Vero open now**: when a Vero CLI is running, or a Vero CLI / VS Code session was active in the last
5 |   10 minutes, it shows the model in use right now (idle CLI: Vero's configured model). "Waiting for the model for N s"
6 |   while a request runs.
7 | - New panel **Your Vero sessions: response time**: for every model request in your own sessions (CLI and VS Code),
8 |   the time until the model started answering, read from Vero's own task logs (`ui_messages.json`). Median and p95 for
9 |   the last hour, median for 24 h, and the last 40 requests as bars with details on hover.
10 | - Privacy: only timestamps, event kinds, model names and token counts are read; prompts and answers never. Files are
11 |   only read. The dashboard's own test questions are excluded (by task id and prompt). Setting to switch it off.
12 | - Process detection is structural (vero / vero.cmd / node running a `vero` package), so Vero Status itself, admin
13 |   commands (`vero version`, `config`, ...) and its own checks are never mistaken for an open session.
14 |
15 | ## 4.0.0
16 | Rewritten as a simple program with a dashboard (feedback on 3.0: too many command windows and steps).
17 | - Double-click `Vero Status.pyw`: no console, no setup, no Task Scheduler. A second double-click just opens the dashboard.
18 | - The dashboard shows whether Vero is available and **which model Vero uses**: the configured model (`vero config`)
19 |   and the model asked in the last check (`modelInfo`). Also the Vero version, response time, 24 h availability and the last checks.
20 | - Check now, Settings (interval: off / 5 / 15 / 30 / 60 min, check model, timeout, Vero location) and Quit on the page.
21 | - Keeps the safe parts of 3.0: `--json` stream with `completion_result` only, no `--yolo`, empty working folder,
22 |   the whole process tree killed on timeout, Host and Origin checks, nothing secret stored. Errors at start show a Windows message box.
23 | - 30 tests (fake Vero), ruff, mypy strict for Linux and Windows, checked in a real browser.
24 |
25 | ## 3.0.0 and older
26 | Vero Availability Monitor (3.0) and Vero Latency Monitor (0.x): command-line tools with installer scripts. Superseded.
=== END FILE: CHANGELOG.md ===
```

```
=== FILE: README.md (56 lines) ===
```

```

1 | # Vero Status
2 |
3 | Double-click Vero Status and a dashboard opens in your browser showing:
4 |
5 | - Is Vero available? Big green or red status, since when, and the reason if not.
6 | - Which model does Vero use? The model Vero is configured with (`vero config`), and the model that answered the last check.
7 | - The Vero CLI version, how long the last answer took, availability over the last 24 h, and the last checks.
8 | - Vero open now: when you have a Vero CLI open, or are using Vero in VS Code, the model in use right now.
9 | - Your Vero sessions: response time: how long the model takes to start answering in your CLI and VS Code
10 | sessions (median and p95 for the last hour, 24 h median, last 40 requests as bars).
11 |
12 | Buttons: Check now, Settings (how often to check, which model to use for the check, Vero location), Quit.
13 |
14 | Jira ASPF-1578 · Version 4.1.0 · Python 3.8+ standard library only, no install, no command window.
15 |
16 | ## Use it
17 |
18 | 1. Put the folder somewhere fixed, e.g. `C:\Tools\vero-status`.
19 | 2. Double-click Vero Status.pyw. The dashboard opens at http://127.0.0.1:8767.
20 | 3. Optional: right-click `Vero Status.pyw` and choose Send to > Desktop (create shortcut).
21 | To start it with Windows, put that shortcut in the folder that opens with `Win+R` -> `shell:startup`.
22 |
23 | Double-clicking again while it runs just opens the dashboard. Quit stops it.
24 |
25 | ## How a check works
26 |
27 | 1. `vero version`: is Vero installed?
28 | 2. `vero config`: which model and provider Vero is set to (free).
29 | 3. `vero task --json -t 120 -c <empty folder> -m <check model> "Reply with exactly: OK"`.
30 | Vero is available when the `completion_result` answer arrives. This costs 2 small model calls and takes about 1 minute.
31 | The check model defaults to the cheap Haiku 4.5; leave it empty in Settings to test Vero's own model.
32 |
33 | The checks never use `--yolo`, run in an empty folder, and never store answers or secrets.
34 | The data lives in the program's `data/` folder (`settings.json`, `history.json`, `vero-status.log`).
35 |
36 | ## How your own sessions are measured
37 |
38 | Vero writes every task's events to `ui_messages.json`: for the CLI in `%USERPROFILE%\vero\data\tasks\<id>`,
39 | for VS Code in the extension's storage (`%APPDATA%\Code\User\globalStorage\<vero extension>\tasks\<id>`).
40 | Each model request starts with an `api_req_started` event; the next event is the model's first response.
41 | The difference is the response time, using Vero's own timestamps. A running `vero` / `node ...vero...` process
42 | means the CLI is open. Only timestamps, event kinds, model names and token counts are read, never your prompts
43 | or answers, and nothing is changed. The dashboard's own test questions are left out. Switch it off in Settings.
44 |
45 | ## Try it without Vero
46 |
47 | In Settings, set Vero CLI location to `scripts\vero.cmd` (Windows) or `scripts/vero` (Linux/macOS; run `chmod +x scripts/vero` once): a fake Vero that answers like the real one.
48 |
49 | ## Develop
50 |
51 | ```
52 | python -m unittest discover -s tests -t .# 43 tests, fake Vero only
53 | uvx ruff check . && uvx ruff format --check .# lint + format
54 | uvx mypy && uvx mypy --platform win32# strict typing
55 | uv run --no-project --with reportlab python scripts/build_source_pdf.py# source as PDF for rebuild
56 | ```

```

```
=== END FILE: README.md ===
```

```
=== FILE: START_HERE.txt (20 lines) ===
```

```

1 | VERO STATUS 4 (ASPF-1578)
2 | =====
3 |
4 | Shows in your browser whether Vero is available and which model it uses.
5 | Needs Python 3.8+ only. Nothing to install. No command window.
6 |
7 | 1. Put this folder somewhere fixed, e.g. C:\Tools\vero-status
8 |
9 | 2. Double-click "Vero Status.pyw"
10 | Your browser opens the dashboard (http://127.0.0.1:8767). The first check takes about a minute.
11 |
12 | 3. Optional: right-click "Vero Status.pyw" -> Send to -> Desktop (create shortcut).
13 | To start it with Windows: Win+R -> shell:startup -> put that shortcut there.
14 |
15 | In the dashboard: Check now | Settings (how often, which model, Vero location) | Quit
16 |
17 | If an older version is installed (Vero Latency Monitor or Vero Availability Monitor), run
18 | uninstall.bat in its folder so it stops calling Vero.
19 |
20 | Problems: open data\vero-status.log, or read Vero_Status_Guide.pdf.
=== END FILE: START_HERE.txt ===
```

```
=== FILE: VERO_CONTEXT.md (90 lines) ===
```

```
1 | # VERO_CONTEXT: Vero Status 4.1.0
2 |
3 | > **For the AI reading this:** this file describes the whole program. Read a file before changing it, and keep the rules at the end.
4 |
5 | ## What it is
6 |
7 | A small program for one laptop. When you double-click `Vero Status.pyw`, it opens a dashboard in the browser at `http://127.0.0.1:8767`. The dashboard shows:
8 |
9 | - whether **Vero is available** (Vero CLI 2.3.x);
10 | - **which model Vero uses**: the configured model from `vero config`, and the model the last check used (`modelInfo` in the `--json` stream);
11 | - the Vero version, the response time, availability over 24 h, and the last 48 checks;
12 | - **Vero open now**: the model in use in your own open Vero CLI or VS Code session;
13 | - **Your Vero sessions: response time**: median and p95 per hour, the 24 h median, and the last 40 requests;
14 | - buttons for Check now, Settings and Quit.
15 |
16 | It uses only the Python 3.8+ standard library. It opens no console window (`pythonw`), and every child process starts with `CREATE_NO_WINDOW`.
17 |
18 | The Jira story is ASPF-1578, for the Quality AI Automation team at NXP. Version 4.0.0 replaces the 3.0 "Vero Availability Monitor", which was command-line based.
19 |
20 | ## Files
21 |
22 | ```
23 | Vero Status.pyw: double-click entry: adds the folder to sys.path, calls vero_status.app.run()
24 | vero_status/
25 |   __init__.py: version = "4.0.0", APP_ID = "vero-status"
26 |   app.py: single instance (GET /api/health), logging to data/vero-status.log, opens the browser,
27 |           shows a Windows message box on errors (no console)
28 |   vero.py: find_vero, run (no window, kills the process tree on timeout), and pure parsers:
29 |           parse_version, parse_config, parse_task_stream, task_args, clean (masks credentials)
30 |   sessions.py: your own Vero sessions: parse_ui_messages (pure: request latency = first event after
31 |               api_req_started; model from modelInfo), Scanner (finds tasks/*ui_messages.json for CLI
32 |               and VS Code, cached by mtime, every 15 s), is_interactive_vero / process_command_lines
33 |               (a vero / vero.cmd / node-with-vero-package process = an open CLI), summarize
34 |   monitor.py: perform_check(settings, workdir, run) -> record; Monitor: timer thread, check_now,
35 |               history (data/history.json, last 500), update_settings, state() for the page
36 |   settings.py: Settings (frozen dataclass), validation, load/save of data/settings.json
37 |   server.py: 127.0.0.1 only. GET /, /api/state, /api/health; POST /api/check, /api/settings, /api/quit.
38 |               Host and Origin are checked.
39 |   web/index.html: the dashboard (one file, vanilla JS, light and dark, polls /api/state)
40 |   scripts/fake_vero.py: stand-in Vero: version, config, task --json (FAKE_VERO_MODE ok|down|auth|hang|nocompletion|refuse)
41 |   scripts/fake_session.py: writes a realistic session log into a folder (demo and tests; never your real ~/.vero)
42 |   scripts/vero, vero.cmd: launch the fake Vero (point "Vero CLI location" at one of these for a demo)
43 |   scripts/build_source_pdf.py: writes the source as a PDF for rebuilding (developer tool, needs reportlab)
44 |   tests/: unittest; never calls the real Vero
45 |   ```
46 |
47 | ## One check (`monitor.perform_check`)
48 |
49 | 1. `find_vero(settings.vero_path)` looks for the Vero CLI in this order: the configured path, `vero` on the PATH (`vero.cmd` on Windows), then `%APPDATA%\npm\vero.cmd`. If nothing is found, the r
+ result is "not available" with the reason "not found".
50 | 2. `vero version`: if this fails, the result is "not available".
51 | 3. `vero config` reads the settings `actModeApiModelId`, `actModeApiProvider` and `awsRegion`, given either as `key : value` lines or as JSON. If this step fails, the configured model is simply u
+ nknown; it does not affect the status.
52 | 4. `vero task --json -t <timeout> -c data/sandbox [-m <check_model>]` "Reply with exactly: OK", killed at timeout + 30 s.
53 | --- **Available** if and only if a `completion_result` event arrives. A different answer still counts as available, with a note.
54 | --- `partial` events are ignored. `api_req_started`, which holds the full prompt, is never kept.
55 | --- The record holds `time`, `available`, `reason`, `seconds` (only when there is an answer), `asked_model`, `provider`, `vero_version`, `configured` {`model`, `provider`, `region`} and `trigger
+ ` (start, auto or manual).
56 |
57 | ## Settings
58 |
59 | Stored in `data/settings.json` and editable on the page:
60 |
61 | | Setting | Default | Allowed values |
62 | |---|---|---|
63 | | `vero_path` | `` (find it automatically) | any path |
```

```

64 | | `check_model` | Haiku 4.5 | a model id, or `` to use Vero's own model |
65 | | `interval_minutes` | 15 | 0 (off), 5, 15, 30, 60 |
66 | | `timeout_seconds` | 120 | 30-600 |
67 | | `port` | 8767 | 1024-65535; change it in the file only |
68 | | `track_sessions` | true | show your own sessions' model and response time |
69 |
70 | A broken settings file falls back to the defaults.
71 |
72 | ## Quality gates
73 |
74 | ```
75 | python -m unittest discover -s tests -t .(43 tests, Python 3.8-3.13)
76 | uvx ruff check . && uvx ruff format --check .
77 | uvx mypy && uvx mypy --platform win32(strict)
78 | ```
79 |
80 | ## Rules
81 |
82 | 1. Keep it simple for the user: double-click, a dashboard, no command windows, no installer.
83 | 2. Standard library only. No CDN and no external scripts in the page.
84 | 3. Never pass `--yolo`. Run the task in the empty `data/sandbox` folder. On timeout, kill the whole process tree.
85 | 4. Store no answers, no secrets and no `api_req_started` content. Mask credentials in error text.
86 | From the user's task logs, read only `ts`, event kinds, `modelInfo` and token counts. Only read those files, never change them.
87 | Exclude our own probe tasks, by task id and by prompt.
88 | 5. Bind to 127.0.0.1 only, and keep the Host and Origin checks on every request.
89 | 6. Tests use the fake Vero only.
90 | 7. Commit messages and PR titles have the form `ASPF-1578: <summary>`. Update the CHANGELOG and this file when behaviour changes.
=== END FILE: VERO_CONTEXT.md ===

```

```
=== FILE: Vero Status.pyw (10 lines) ===
1 | """Double-click to open the Vero Status dashboard (no console window)."""
2 |
3 | import sys
4 | from pathlib import Path
5 |
6 | sys.path.insert(0, str(Path(__file__).resolve().parent))
7 |
8 | from vero_status.app import run_# noqa: E402
9 |
10 | run()
=== END FILE: Vero Status.pyw ===
```

```
=== FILE: pyproject.toml (23 lines) ===
```

```

1 | [project]
2 | name = "vero-status"
3 | version = "4.1.0"
4 | description = "Dashboard: is Vero available, and which model does it use? (ASPF-1578)"
5 | requires-python = ">=3.8"
6 | dependencies = []
7 |
8 | [tool.ruff]
9 | line-length = 130
10 | target-version = "py38"
11 |
12 | [tool.ruff.lint]
13 | select = ["E", "F", "W", "I", "B", "UP", "S", "SIM", "RUF"]
14 | ignore = ["S603", "S607", "S310", "UP006", "UP007", "UP035", "UP045", "RUF001", "RUF003"]
15 |
16 | [tool.ruff.lint.per-file-ignores]
17 | "tests/**" = ["S101", "S108"]
18 | "scripts/**" = ["S311"] ## demo randomness, not security
19 |
20 | [tool.mypy]
21 | python_version = "3.9"
22 | files = ["vero_status"]
23 | strict = true

```

```
=== END FILE: pyproject.toml ===
```

```
=== FILE: scripts/build_source_pdf.py (224 lines) ===
```

```

1 | #!/usr/bin/env python3
2 | """Build dist/Vero_Status_<version>_Source.pdf: the complete source as a PDF document.
3 |
4 | For channels that accept only documents. Developer tool (needs reportlab):
5 | uv run --no-project --with reportlab python scripts/build_source_pdf.py
6 |
7 | Listing format (survives PDF text extraction, which drops blank lines and collapses spaces):
8 | """
9 | line 12 | content"
10 | line 12 of the file; every MARK (U+2423, open box) in content is one space
11 | (used for leading spaces, runs of 2+ spaces and spaces at a row edge)
12 | line 12 | "
13 | line 12 is empty
14 | "
15 | + more"
16 | continuation of the previous line (joined with nothing in between)
17 | The MARK character never appears in the sources (checked at build time).
18 | """
19 |
20 | import hashlib
21 | import re
22 | import sys
23 | from pathlib import Path
24 |
25 | from reportlab.lib.pagesizes import A4, landscape
26 | from reportlab.pdfbase import pdfmetrics
27 | from reportlab.pdfbase.ttfonts import TTFont
28 | from reportlab.pdfgen import canvas
29 |
30 | ROOT = Path(__file__).resolve().parents[1]
31 | sys.path.insert(0, str(ROOT))
32 | from vero_status import __version__# noqa: E402
33 |
34 | SKIP_DIRS = {
35 |     "data",
36 |     "data-demo",
37 |     "reports",
38 |     "dist",
39 |     "__pycache__",
40 |     ".pytest_cache",
41 |     ".mypy_cache",
42 |     ".ruff_cache",
43 |     ".venv",
44 |     "venv",
45 | }
46 | SKIP_SUFFIXES = (".pyc", ".log", ".egg-info")
47 | SKIP_FILES = {"docs/Vero_Status_Guide.html"}
48 | CRLF = (".bat", ".cmd")
49 | CRLF_FILES = {"START_HERE.txt"}
50 | FONT_PATHS = ["/usr/share/fonts/truetype/dejavu/DejaVuSansMono.ttf", "C:/Windows/Fonts/consola.ttf"]
51 | SIZE, LEADING, MARGIN = 6.4, 7.7, 28
52 | PAGE_W, PAGE_H = landscape(A4)
53 | MARK = "\u2423" # open box, shown for a space that extraction could lose
54 |
55 | def files():
56 |     for f in sorted(ROOT.rglob("*")):
57 |         rel = f.relative_to(ROOT)
58 |         if (
59 |             f.is_dir()
60 |             or SKIP_DIRS & set(rel.parts)
61 |             or any(part.endswith(SKIP_SUFFIXES) for part in rel.parts)
62 |             or rel.as_posix() in SKIP_FILES
63 |         ):
64 |             continue
65 |         yield rel.as_posix(), f.read_bytes().decode("utf-8").replace("\r\n", "\n")
66 |
67 | def lf_sha(text: str) -> str:
68 |     return hashlib.sha256(text.encode("utf-8")).hexdigest()

```

```

67 |
68 | def protect(chunk: str) -> str:
69 |     """Mark every space an extractor could drop: leading, trailing, and runs of 2+."""
70 |     chunk = re.sub(r" {2,}", lambda m: MARK * len(m.group()), chunk)
71 |     if chunk.startswith(" "):
72 |         chunk = MARK + chunk[1:]
73 |     if chunk.endswith(" "):
74 |         chunk = chunk[:-1] + MARK
75 |     return chunk
76 |
77 |
78 | def encode(lines, width):
79 |     """Source lines -> listing rows (see module docstring)."""
80 |     rows = []
81 |     for n, line in enumerate(lines, 1):
82 |         head = f"{n:>4} |"
83 |         if not line:
84 |             rows.append(head)
85 |             continue
86 |         chunks = [line[i : i + width] for i in range(0, len(line), width)]
87 |         rows.append(f"{head} {protect(chunks[0])}")
88 |         rows.extend(f"      {protect(c)}" for c in chunks[1:])
89 |     return rows
90 |
91 |
92 | VERIFY_TEMPLATE = """import hashlib, pathlib, sys
93 | # usage: py verify_rebuild.py C:\\Tools\\vero-status
94 | root = pathlib.Path(sys.argv[1] if len(sys.argv) > 1 else "vero-status")
95 | CRLF = {crlf!r}
96 | FILES = {{
97 |     {entries}}}
98 | bad = 0
99 | for path, sha in FILES.items():
100 |     p = root / path
101 |     if not p.exists():
102 |         print("MISSING", path); bad += 1; continue
103 |     text = p.read_bytes().decode("utf-8").replace("\\r\\n", "\\n")
104 |     if hashlib.sha256(text.encode("utf-8")).hexdigest() != sha:
105 |         print("DIFFERENT", path); bad += 1; continue
106 |     want = text.replace("\\n", "\\r\\n") if path in CRLF else text
107 |     if p.read_bytes() != want.encode("utf-8"):
108 |         p.write_bytes(want.encode("utf-8")); print("fixed line endings", path)
109 |     print("OK: all files match" if not bad else str(bad) + " file(s) wrong: recreate them from the document")
110 |     sys.exit(1 if bad else 0)
111 | """
112 |
113 |
114 | class Doc:
115 |     def __init__(self, path: Path, font: str):
116 |         self.c = canvas.Canvas(str(path), pagesize=(PAGE_W, PAGE_H))
117 |         self.c.setTitle(f"Vero Status {__version__} - complete source for rebuild")
118 |         self.c.setAuthor("Quality AI Automation (ASPF-1578)")
119 |         self.c.setSubject("Source listing. A document only: nothing in it runs.")
120 |         self.font = font
121 |         self.page = 0
122 |         self.y = 0.0
123 |         self.new_page()
124 |
125 |     def new_page(self):
126 |         if self.page:
127 |             self.c.showPage()
128 |             self.page += 1
129 |             self.c.setFont(self.font, 6)
130 |             self.c.setFillGray(0.45)
131 |             self.c.drawString(MARGIN, PAGE_H - 16, f"Vero Status {__version__} · source for rebuild · ASPF-1578")
132 |             self.c.drawRightString(PAGE_W - MARGIN, 12, f"page {self.page}")
133 |             self.c.setFillGray(0)

```

```

134 |         self.y = PAGE_H - MARGIN - 8
135 |
136 |     def row(self, text: str, size: float = SIZE, gray: float = 0):
137 |         if self.y < MARGIN:
138 |             self.new_page()
139 |             self.c.setFont(self.font, size)
140 |             self.c.setFillGray(gray)
141 |             self.c.drawString(MARGIN, self.y, text)
142 |             self.y -= max(LEADING, size * 1.25)
143 |
144 |     def gap(self, n: float = 1):
145 |         self.y -= LEADING * n
146 |
147 |     def save(self):
148 |         self.c.save()
149 |
150 |
151 | def main() -> None:
152 |     font_path = next((p for p in FONT_PATHS if Path(p).exists()), None)
153 |     if not font_path:
154 |         sys.exit("no monospace TTF font found (DejaVu Sans Mono or Consolas)")
155 |     pdfmetrics.registerFont(TTFont("Mono", font_path))
156 |     char_w = pdfmetrics.stringWidth("M", "Mono", SIZE)
157 |     width = int((PAGE_W - 2 * MARGIN) / char_w) - 8 # minus the "NNNN | " gutter
158 |     items = list(files())
159 |     bad = [p for p, t in items if MARK in t]
160 |     if bad:
161 |         sys.exit(f"MARK character found in {bad}: the listing would be ambiguous")
162 |     crlf = sorted(p for p, _ in items if p.endswith(CRLF) or p in CRLF_FILES)
163 |     out = ROOT / "dist" / f"Vero_Status_{__version__}_Source.pdf"
164 |     out.parent.mkdir(exist_ok=True)
165 |     d = Doc(out, "Mono")
166 |
167 |     d.row(f"VERO STATUS {__version__} - COMPLETE SOURCE FOR REBUILD", 13)
168 |     d.row("Jira ASPF-1578 · Quality AI Automation · a document only: nothing in it runs", 8, 0.35)
169 |     d.gap()
170 |     intro = f"""\
171 | What this is: the full source ({len(items)} text files) of "Vero Status", a small program that shows in the browser whether
172 | Vero is available and which model it uses. Python 3.8+ standard library only. The guide PDF is sent separately.
173 |
174 | INSTRUCTIONS FOR THE AI ASSISTANT (Vero CLI or other) - recreate the project folder EXACTLY:
175 | 1. Create the folder vero-status in the location the user gives (default C:\\Tools\\).
176 | 2. Every file starts with a row{u}"" FILE: <path> (<n> lines) "" and ends with{u}"" END FILE: <path> "" .
177 | 3. Rows between them encode the file, one source line per numbered row:
178 | {u}12 | content{u}-> line 12. Every {MARK} (open box) in the content is ONE SPACE. It marks leading
179 | spaces, runs of 2+ spaces and spaces at a row edge; single spaces between words
180 | are printed normally. The {MARK} character never occurs in the real files.
181 | {u}12 | ""-> line 12 is an empty line.
182 | {u}+ more{u}-> continuation of the previous line: append "more" directly (no space, no newline).
183 | Ignore page headers/footers ("Vero Status ... source for rebuild", "page N").
184 | Line numbers must run 1..n without gaps; n is in the FILE row. Every file ends with a newline.
185 | 4. Write files as UTF-8 without BOM, LF line endings. Do not reformat, translate, summarise or "fix" anything.
186 | 5. Create verify_rebuild.py from the section VERIFY SCRIPT at the end (same row rules), OUTSIDE the project
187 | folder, and run: {u}py verify_rebuild.py C:\\Tools\\vero-status
188 | It checks every file's SHA-256 and sets CRLF line endings where Windows needs them (.cmd, START_HERE.txt).
189 | Recreate any file reported MISSING or DIFFERENT, then run it again until it prints "OK: all files match".
190 | 6. Run the tests inside the folder: {u}py -m unittest discover -s tests -t {u}Expected: OK (43 tests).
191 | 7. Tell the user it is ready: double-click "Vero Status.pyw" to open the dashboard (see START_HERE.txt).
192 | Do not start the program or call the real Vero CLI unless the user asks.
193 | """
194 |     for line in intro.splitlines():
195 |         d.row(line, 7.2)
196 |         d.gap()
197 |     d.row("FILE LIST (path · lines · line endings · SHA-256 of the content with LF endings)", 7.2)
198 |     for p, t in items:
199 |         lines = t.split("\n")[:-1] if t.endswith("\n") else t.split("\n")
200 |         d.row(f'{u}{p[:52]} {len(lines):>5}{u}' 'CRLF' if p in crlf else 'LF{u}'{lf_sha(t)}', 6.2)

```

```

201 |
202 |     for p, t in items:
203 |         lines = t.split("\n")[:-1] if t.endswith("\n") else t.split("\n")
204 |         d.new_page()
205 |         d.row(f"=== FILE: {p} ({len(lines)} lines) ===", 7.5)
206 |         for r in encode(lines, width):
207 |             d.row(r)
208 |         d.row(f"=== END FILE: {p} ===", 7.5)
209 |
210 |     entries = "".join(f"{p!r}: {lf_sha(t)!r},\n" for p, t in items)
211 |     verify = VERIFY_TEMPLATE.format(crlf=crlf, entries=entries)
212 |     d.new_page()
213 |     vlines = verify.split("\n")[:-1]
214 |     d.row(f"=== VERIFY SCRIPT: verify_rebuild.py ({len(vlines)} lines) ===", 7.5)
215 |     for r in encode(vlines, width):
216 |         d.row(r)
217 |     d.row("=== END VERIFY SCRIPT ===", 7.5)
218 |     d.save()
219 |     (ROOT / "dist" / "verify_rebuild.py").write_text(verify, encoding="utf-8")
220 |     print(f"wrote {out} ({len(items)} files, {d.page} pages, {out.stat().st_size // 1024} KB, {width} chars per row)")
221 |
222 |
223 | if __name__ == "__main__":
224 |     main()
=== END FILE: scripts/build_source_pdf.py ===

```

```
=== FILE: scripts/fake_session.py (40 lines) ===
```

```

1 | #!/usr/bin/env python3
2 | """Simulate a user's Vero session for demos and tests: appends events to <tasks-dir>/<id>/ui_messages.json
3 | in the same shape Vero writes them (Cline-style events with ts, say, modelInfo).
4 |
5 | usage: python scripts/fake_session.py <tasks-dir> [--requests 6] [--model us.anthropic.claude-opus-5]
6 | Never point it at your real ~/.vero folder.
7 | """
8 |
9 | import argparse
10 | import json
11 | import random
12 | import time
13 | from pathlib import Path
14 |
15 | a = argparse.ArgumentParser()
16 | a.add_argument("tasks_dir")
17 | a.add_argument("--requests", type=int, default=6)
18 | a.add_argument("--model", default="us.anthropic.claude-opus-5")
19 | a.add_argument("--pause", type=float, default=1.5, help="seconds between requests")
20 | args = a.parse_args()
21 |
22 | info = {"providerId": "bedrock", "modelId": args.model, "mode": "act"}
23 | task = Path(args.tasks_dir) / f"demo-{int(time.time()) * 1000}"
24 | task.mkdir(parents=True, exist_ok=True)
25 | events = []
26 |
27 |
28 | def add(ev):
29 |     events.append({"ts": int(time.time()) * 1000, **ev, "modelInfo": info})
30 |     (task / "ui_messages.json").write_text(json.dumps(events), encoding="utf-8")
31 |
32 |
33 | add({"type": "say", "say": "task", "text": "demo task"})
34 | for _ in range(args.requests):
35 |     add({"type": "say", "say": "api_req_started", "text": json.dumps({"tokensIn": random.randint(800, 9000), "tokensOut": 0})})
36 |     time.sleep(random.uniform(1.5, 6.0))
37 |     add({"type": "say", "say": "text", "text": "...", "partial": True})
38 |     time.sleep(args.pause)
39 |     add({"type": "say", "say": "completion_result", "text": "done"})
40 |     print(f"wrote {task}")

```

```
=== END FILE: scripts/fake_session.py ===
```

```
=== FILE: scripts/fake_vero.py (56 lines) ===
```

```

1 | #!/usr/bin/env python3
2 | """Stand-in for the Vero CLI (demo and tests): `version`, `config`, `task --json ...` like Vero CLI 2.3.x.
3 |
4 | FAKE_VERO_MODE: ok (default) | down | auth | hang | nocompletion | refuse
5 | FAKE_VERO_DELAY: seconds before answering (default 2)
6 | """
7 |
8 | import json
9 | import os
10 | import sys
11 | import time
12 |
13 |
14 | def emit(obj):
15 |     print(json.dumps(obj), flush=True)
16 |
17 |
18 | def main(argv):
19 |     cmd = argv[0] if argv else "version"
20 |     if cmd in ("version", "--version"):
21 |         print("vero 2.3.3 (fake0000)")
22 |         return 0
23 |     if cmd == "config":
24 |         print("actModeApiProvider : bedrock")
25 |         print("actModeApiModelId: us.anthropic.claude-opus-5")
26 |         print("awsRegion: us-west-2")
27 |         return 0
28 |     if cmd not in ("task", "t"):
29 |         print(f"unknown command {cmd}", file=sys.stderr)
30 |         return 2
31 |     args = argv[1:]
32 |     model = args[args.index("-m") + 1] if "-m" in args else "us.anthropic.claude-opus-5"
33 |     info = {"providerId": "bedrock", "modelId": model, "mode": "act"}
34 |     mode = os.environ.get("FAKE_VERO_MODE", "ok")
35 |     delay = float(os.environ.get("FAKE_VERO_DELAY", "2"))
36 |     emit({"type": "task_started", "taskId": str(int(time.time() * 1000))})
37 |     emit({"type": "say", "say": "task", "text": args[-1], "modelInfo": info})
38 |     emit({"type": "say", "say": "api_req_started", "text": "SYSTEM PROMPT FAKE-SECRET-PROMPT", "modelInfo": info})
39 |     if mode == "hang":
40 |         time.sleep(3600)
41 |     if mode == "auth":
42 |         print("error: Unauthorized token=abc123secret", file=sys.stderr)
43 |         return 1
44 |     if mode == "down":
45 |         print("error: provider unavailable (connect ETIMEDOUT)", file=sys.stderr)
46 |         return 1
47 |     time.sleep(delay)
48 |     answer = "I cannot do that." if mode == "refuse" else "OK"
49 |     emit({"type": "say", "say": "text", "text": answer[1:], "partial": True, "modelInfo": info})
50 |     if mode != "nocompletion":
51 |         emit({"type": "say", "say": "completion_result", "text": answer, "modelInfo": info})
52 |     return 0
53 |
54 |
55 | if __name__ == "__main__":
56 |     sys.exit(main(sys.argv[1:]))
=== END FILE: scripts/fake_vero.py ===
```

```
=== FILE: scripts/vero (2 lines) ===
  1 | #!/bin/sh
  2 | exec python3 "${dirname "$0"}/fake_vero.py" "$@"
=== END FILE: scripts/vero ===
```

```
=== FILE: scripts/vero.cmd (2 lines) ===  
1 | @echo off  
2 | py -3 "%~dp0fake_vero.py" %*  
=== END FILE: scripts/vero.cmd ===
```

```
=== FILE: tests/__init__.py (1 lines) ===
  1 | """Tests (never call the real Vero)."""
=== END FILE: tests/__init__.py ===
```

```

=== FILE: tests/helpers.py (29 lines) ===
1 | """Shared helpers: run the bundled fake Vero CLI through the real process code."""
2 |
3 | import sys
4 | from pathlib import Path
5 |
6 | ROOT = Path(__file__).resolve().parents[1]
7 | sys.path.insert(0, str(ROOT))
8 |
9 | from vero_status import vero_# noqa: E402
10 |
11 | FAKE = ROOT / "scripts" / "fake_vero.py"
12 |
13 |
14 | def fake_run(args, timeout_s, cwd=None):
15 |     """Like vero.run, but 'vero' is the fake script started with this Python."""
16 |     return vero.run([sys.executable, str(FAKE), *args[1:]], timeout_s, cwd)
17 |
18 |
19 | def quiet_scanner():
20 |     """A session scanner that looks nowhere (tests must not read the real ~/.vero)."""
21 |     from vero_status.sessions import Scanner
22 |
23 |     return Scanner(roots=[], list_processes=lambda: [])
24 |
25 |
26 | def fake_settings(**over):
27 |     from vero_status.settings import Settings
28 |
29 |     return Settings(vero_path=sys.executable, **over)
=== END FILE: tests/helpers.py ===

```

```
=== FILE: tests/test_monitor_server.py (210 lines) ===
```

```

1 | import json
2 | import os
3 | import socket
4 | import tempfile
5 | import threading
6 | import time
7 | import unittest
8 | import urllib.error
9 | import urllib.request
10 | from pathlib import Path
11 | from unittest import mock
12 |
13 | from tests.helpers import fake_run, fake_settings, quiet_scanner
14 | from vero_status.monitor import Monitor, perform_check
15 | from vero_status.server import create
16 |
17 |
18 | def free_port():
19 |     with socket.socket() as s:
20 |         s.bind(("127.0.0.1", 0))
21 |         return s.getsockname()[1]
22 |
23 |
24 | class PerformCheckTest(unittest.TestCase):
25 |     def setUp(self):
26 |         self.tmp = tempfile.TemporaryDirectory()
27 |         self.work = Path(self.tmp.name) / "sandbox"
28 |         self.env = mock.patch.dict(os.environ, {"FAKE_VERO_DELAY": "0.05", "FAKE_VERO_MODE": "ok"})
29 |         self.env.start()
30 |
31 |     def tearDown(self):
32 |         self.env.stop()
33 |         self.tmp.cleanup()
34 |
35 |     def check(self, mode="ok", **settings):
36 |         os.environ["FAKE_VERO_MODE"] = mode
37 |         return perform_check(fake_settings(**settings), self.work, fake_run)
38 |
39 |     def test_available_with_both_models(self):
40 |         r = self.check()
41 |         self.assertTrue(r["available"], r["reason"])
42 |         self.assertEqual(r["asked_model"], "us.anthropic.claude-haiku-4-5-20251001-v1:0")_# pinned cheap model
43 |         self.assertEqual(r["configured"]["model"], "us.anthropic.claude-opus-5")_# Vero's own setting
44 |         self.assertEqual(r["vero_version"], "vero 2.3.3 (fake0000)")
45 |         self.assertEqual(r["reason"], "")
46 |         self.assertIsNotNone(r["seconds"])
47 |
48 |     def test_empty_model_uses_veros_own(self):
49 |         self.assertEqual(self.check(check_model="")["asked_model"], "us.anthropic.claude-opus-5")
50 |
51 |     def test_failures_are_not_available_with_reason(self):
52 |         down = self.check("down")
53 |         self.assertEqual(down["reason"], "Vero reported an error (exit code 1): provider unavailable (connect ETIMEDOUT)")
54 |         self.assertIsNone(down["seconds"])_# no answer, no response time
55 |         r = self.check("auth")
56 |         self.assertFalse(r["available"])
57 |         self.assertNotIn("abc123secret", r["reason"])
58 |         self.assertEqual(self.check("nocompletion")["reason"], "Vero finished without an answer")
59 |
60 |     def test_refusal_is_available_with_note(self):
61 |         r = self.check("refuse")
62 |         self.assertTrue(r["available"])
63 |         self.assertIn("not with OK", r["reason"])
64 |
65 |     def test_vero_missing(self):
66 |         with mock.patch("vero_status.monitor.vero.find_vero", return_value=None):

```

```

67 | r = perform_check(fake_settings(), self.work, lambda *a: self.fail("must not run"))
68 | self.assertFalse(r["available"])
69 | self.assertTrue(r["reason"].startswith("Vero CLI not found"))
70 |
71 | def test_hang_times_out(self):
72 |     os.environ["FAKE_VERO_MODE"] = "hang"
73 |     s = fake_settings(timeout_seconds=30)
74 |     t0 = time.time()
75 |     r = perform_check(s, self.work, lambda a, t, c=None: fake_run(a, min(t, 1.0), c))_# shorten the wait
76 |     self.assertFalse(r["available"])
77 |     self.assertIn("no answer within", r["reason"])
78 |     self.assertLess(time.time() - t0, 6)
79 |
80 | def test_secret_prompt_never_in_record(self):
81 |     self.assertNotIn("FAKE-SECRET-PROMPT", json.dumps(self.check()))
82 |
83 |
84 | class MonitorTest(unittest.TestCase):
85 |     def setUp(self):
86 |         self.tmp = tempfile.TemporaryDirectory()
87 |         self.dir = Path(self.tmp.name)
88 |         self.env = mock.patch.dict(os.environ, {"FAKE_VERO_DELAY": "0.05", "FAKE_VERO_MODE": "ok"})
89 |         self.env.start()
90 |
91 |     def tearDown(self):
92 |         self.env.stop()
93 |         self.tmp.cleanup()
94 |
95 |     def wait_idle(self, m):
96 |         for _ in range(100):
97 |             if not m.checking:
98 |                 return
99 |             time.sleep(0.05)
100 |         self.fail("check did not finish")
101 |
102 |     def make(self):
103 |         m = Monitor(self.dir, fake_run, quiet_scanner())
104 |         m.settings = fake_settings()
105 |         return m
106 |
107 |     def test_check_history_state_and_persistence(self):
108 |         m = self.make()
109 |         self.assertTrue(m.check_now())
110 |         self.assertFalse(m.check_now())_# one at a time
111 |         self.wait_idle(m)
112 |         st = m.state()
113 |         self.assertTrue(st["last"]["available"])
114 |         self.assertEqual(st["availability_24h"], st["checks_24h"], (100.0, 1))
115 |         self.assertEqual(st["configured"]["model"], "us.anthropic.claude-opus-5")
116 |         self.assertIsNotNone(st["next_check"])
117 |         self.assertEqual(len(Monitor(self.dir, fake_run, quiet_scanner()).history), 1)_# saved to disk
118 |         m.scan_sessions()
119 |         self.assertEqual(m.state()["sessions"]["tasks_seen"], 0)
120 |         self.assertEqual(m.own_task_ids(), [st["last"]["task_id"]])_# our probe task is remembered
121 |
122 |     def test_since_tracks_the_current_streak(self):
123 |         m = self.make()
124 |         m.history = [{"time": 10, "available": True}, {"time": 20, "available": False}, {"time": 30, "available": False}]
125 |         self.assertEqual(m.state()["since"], 20)
126 |
127 |     def test_settings_update_and_interval_off(self):
128 |         m = self.make()
129 |         m.update_settings({"interval_minutes": 0})
130 |         self.assertIsNone(m.next_check)
131 |         self.assertEqual(json.loads((self.dir / "settings.json").read_text())["interval_minutes"], 0)
132 |
133 |     def test_scheduler_runs_when_due(self):

```

```

134 |         m = self.make()
135 |         m.start(check_at_start=False)
136 |         m.next_check = time.time() + 0.2
137 |         m._wake.set()
138 |         for _ in range(100):
139 |             if m.history:
140 |                 break
141 |             time.sleep(0.05)
142 |         m.stop()
143 |         self.assertEqual(m.history[-1]["trigger"], "auto")
144 |
145 |
146 | class ServerTest(unittest.TestCase):
147 |     def setUp(self):
148 |         self.tmp = tempfile.TemporaryDirectory()
149 |         self.env = mock.patch.dict(os.environ, {"FAKE_VERO_DELAY": "0.05", "FAKE_VERO_MODE": "ok"})
150 |         self.env.start()
151 |         self.port = free_port()
152 |         self.mon = Monitor(Path(self.tmp.name), fake_run, quiet_scanner())
153 |         self.mon.settings = fake_settings()
154 |         self.quit = threading.Event()
155 |         self.srv = create(self.mon, self.port, self.quit.set)
156 |         threading.Thread(target=self.srv.serve_forever, daemon=True).start()
157 |         self.base = f"http://127.0.0.1:{self.port}"
158 |
159 |     def tearDown(self):
160 |         self.env.stop()
161 |         if not self.quit.is_set():
162 |             self.srv.shutdown()
163 |         self.srv.server_close()
164 |         self.tmp.cleanup()
165 |
166 |     def req(self, path, data=None, **headers):
167 |         body = json.dumps(data).encode() if data is not None else (b"" if headers.pop("post", False) else None)
168 |         r = urllib.request.Request(self.base + path, data=body, headers={"Content-Type": "application/json", **headers})
169 |         try:
170 |             with urllib.request.urlopen(r) as resp:
171 |                 return resp.status, json.loads(resp.read() or b"null")
172 |         except urllib.error.HTTPError as e:
173 |             return e.code, json.loads(e.read() or b"null")
174 |
175 |     def test_page_state_health(self):
176 |         with urllib.request.urlopen(self.base + "/") as r:
177 |             self.assertIn(b"Vero Status", r.read())
178 |             code, st = self.req("/api/state")
179 |             self.assertEqual((code, st["last"]), (200, None))
180 |             self.assertEqual(self.req("/api/health")[1]["app"], "vero-status")
181 |             self.assertEqual(self.req("/nope")[0], 404)
182 |
183 |     def test_check_now(self):
184 |         self.assertEqual(self.req("/api/check", post=True)[0], 202)
185 |         for _ in range(100):
186 |             if self.mon.history and not self.mon.checking:
187 |                 break
188 |             time.sleep(0.05)
189 |         self.assertTrue(self.req("/api/state")[1]["last"]["available"])
190 |
191 |     def test_settings_endpoint(self):
192 |         self.assertEqual(self.req("/api/settings", {"interval_minutes": 30})[0], 200)
193 |         self.assertEqual(self.mon.settings.interval_minutes, 30)
194 |         code, body = self.req("/api/settings", {"interval_minutes": 7})
195 |         self.assertEqual(code, 400)
196 |         self.assertIn("interval", body["error"])
197 |         self.assertEqual(self.req("/api/settings", [1])[0], 400)
198 |
199 |     def test_foreign_host_and_origin_rejected(self):
200 |         self.assertEqual(self.req("/api/state", Host="evil.example")[0], 403)

```

```
201 |         self.assertEqual(self.req("/api/check", post=True, Origin="http://evil.example")[0], 403)
202 |         self.assertEqual(self.req("/api/quit", post=True, Origin="http://evil.example")[0], 403)
203 |
204 |     def test_quit(self):
205 |         self.assertEqual(self.req("/api/quit", post=True)[1], {"stopping": True})
206 |         self.assertTrue(self.quit.wait(5))
207 |
208 |
209 | if __name__ == "__main__":
210 |     unittest.main()
=== END FILE: tests/test_monitor_server.py ===
```

```
=== FILE: tests/test_sessions.py (179 lines) ===
```

```

1 | import json
2 | import os
3 | import tempfile
4 | import time
5 | import unittest
6 | from pathlib import Path
7 |
8 | import tests.helpers_ as # noqa: F401
9 | from vero_status import sessions
10 | from vero_status.vero import PROMPT
11 |
12 | HAIKU = {"providerId": "bedrock", "modelId": "us.anthropic.claude-haiku-4-5-20251001-v1:0", "mode": "act"}
13 | OPUS = {"providerId": "bedrock", "modelId": "us.anthropic.claude-opus-5", "mode": "act"}
14 |
15 |
16 | PROMPT_TEXT = "SECRET PROMPT TEXT"  # stands for the full prompt Vero logs; must never be kept
17 |
18 |
19 | def req(ts, tokens_in=1200, tokens_out=80):
20 |     text = json.dumps({"request": PROMPT_TEXT, "tokensIn": tokens_in, "tokensOut": tokens_out, "cost": 0.01})
21 |     return {"ts": ts, "type": "say", "say": "api_req_started", "text": text, "modelInfo": OPUS}
22 |
23 |
24 | def session(t0_ms, task_text="refactor the parser"):
25 |     """A user's task: two model requests answered after 4.0 s and 2.5 s, then a completion."""
26 |     return [
27 |         {"ts": t0_ms, "type": "say", "say": "task", "text": task_text, "modelInfo": OPUS},
28 |         req(t0_ms + 100),
29 |         {"ts": t0_ms + 4100, "type": "say", "say": "text", "text": "Let me look", "partial": True, "modelInfo": OPUS},
30 |         {"ts": t0_ms + 9000, "type": "ask", "ask": "tool", "text": "read file"},
31 |         req(t0_ms + 20000),
32 |         {"ts": t0_ms + 20000 + 2500, "type": "say", "say": "completion_result", "text": "done", "modelInfo": OPUS},
33 |     ]
34 |
35 |
36 | class ParseTest(unittest.TestCase):
37 |     def test_latency_per_request_from_veros_timestamps(self):
38 |         s = sessions.parse_ui_messages(session(1_000_000), "t1", "CLI", now=2000)
39 |         self.assertEqual([r.seconds for r in s.requests], [4.0, 2.5])
40 |         self.assertEqual((s.model, s.provider), ("us.anthropic.claude-opus-5", "bedrock"))
41 |         self.assertEqual((s.requests[0].tokens_in, s.requests[0].tokens_out), (1200, 80))
42 |         self.assertAlmostEqual(s.last_activity, 1022.5)
43 |         self.assertIsNone(s.waiting_since)
44 |         self.assertFalse(s.first_prompt_is_probe)
45 |
46 |     def test_prompt_and_answer_text_never_kept(self):
47 |         s = sessions.parse_ui_messages(session(1_000_000), "t1", "CLI", now=2000)
48 |         summary = sessions.summarize([s], False, 2000, [])
49 |         blob = repr(s) + json.dumps(summary)
50 |         for text in ("SECRET PROMPT TEXT", "refactor the parser", "Let me look", "read file"):
51 |             self.assertNotIn(text, blob)
52 |
53 |     def test_request_in_progress_and_failed(self):
54 |         evs = [*session(1_000_000)[:2], req(1_030_000)]
55 |         s = sessions.parse_ui_messages(evs, "t", "CLI", now=1040)
56 |         self.assertEqual(s.waiting_since, 1030)
57 |         failed = [req(1_000_000), {"ts": 1_003_000, "type": "ask", "ask": "api_req_failed", "text": "429"}]
58 |         self.assertTrue(sessions.parse_ui_messages(failed, "t", "CLI", now=2000).requests[0].failed)
59 |
60 |     def test_long_pause_and_bad_events_ignored(self):
61 |         evs = [req(0), {"ts": 31 * 60 * 1000, "say": "text", "junk": {"no_ts": 1}, {"ts": "x"}}]
62 |         s = sessions.parse_ui_messages(evs, "t", "CLI", now=99999)
63 |         self.assertEqual(s.requests, [])
64 |
65 |     def test_probe_task_recognised(self):
66 |         evs = session(1_000_000, task_text=PROMPT)

```

```

67 |         self.assertTrue(sessions.parse_ui_messages(evs, "t", "CLI").first_prompt_is_probe)
68 |
69 |     def test_percentile(self):
70 |         self.assertIsNone(sessions.percentile([], 50))
71 |         self.assertEqual(sessions.percentile([1, 2, 3, 4], 50), 2.5)
72 |         self.assertEqual(sessions.percentile([5], 95), 5)
73 |
74 |
75 | class ProcessDetectionTest(unittest.TestCase):
76 |     IGN = ("C:\\Tools\\vero-status\\data\\sandbox", "vero_status")
77 |
78 |     def test_user_vero_cli(self):
79 |         for cmd in (
80 |             "C:\\Program Files\\nodejs\\node.exe "
81 |             "C:\\Users\\me\\AppData\\Roaming\\npm\\node_modules\\@npx\\vero\\bin\\vero.js",
82 |             "node /usr/lib/node_modules/vero/dist/cli.js",
83 |             "vero",
84 |             "vero task fix the build",
85 |             "C:\\npm\\vero.cmd --continue",
86 |         ):
87 |             self.assertTrue(sessions.is_interactive_vero(cmd, self.IGN), cmd)
88 |
89 |     def test_not_user_vero(self):
90 |         for cmd in (
91 |             "node server.js",
92 |             "node build.js --verbose",
93 |             "C:\\npm\\vero.cmd task --json -c C:\\Tools\\vero-status\\data\\sandbox Reply",
94 |             "pythonw C:\\Tools\\vero-status\\vero_status\\app.py",
95 |             "vero version",
96 |             "vero config",
97 |             "python3 Vero Status.pyw",
98 |             "C:\\Python312\\pythonw.exe " "C:\\Tools\\vero-status\\Vero Status.pyw",
99 |             "code --extensions-dir C:\\Users\\me\\.vscode\\extensions\\npx.vero-1.0",
100 |             "node C:\\work\\averone\\index.js",
101 |             "",
102 |         ):
103 |             self.assertFalse(sessions.is_interactive_vero(cmd, self.IGN), cmd)
104 |
105 |
106 | class ScannerTest(unittest.TestCase):
107 |     def setUp(self):
108 |         self.tmp = tempfile.TemporaryDirectory()
109 |         self.root = Path(self.tmp.name)
110 |         self.cli = self.root / "home" / ".vero" / "data" / "tasks"
111 |         self.code = self.root / "Code" / "User" / "globalStorage" / "npx.vero-assistant" / "tasks"
112 |         self.procs = []
113 |
114 |     def tearDown(self):
115 |         self.tmp.cleanup()
116 |
117 |     def write(self, base, task_id, events, age_s=0):
118 |         p = base / task_id / "ui_messages.json"
119 |         p.parent.mkdir(parents=True, exist_ok=True)
120 |         p.write_text(json.dumps(events))
121 |         t = time.time() - age_s
122 |         os.utime(p, (t, t))
123 |         return p
124 |
125 |     def scanner(self):
126 |         roots = [(str(self.cli), "CLI"), (str(self.root / "Code" / "User" / "globalStorage" / "*vero*" / "tasks"), "VS Code")]
127 |         return sessions.Scanner(roots, ignore_processes=["sandbox"], list_processes=lambda: self.procs)
128 |
129 |     def test_open_session_latency_and_own_tasks_excluded(self):
130 |         now_ms = int(time.time() * 1000)
131 |         self.write(self.cli, "user1", session(now_ms - 60_000))
132 |         self.write(self.cli, "probe1", session(now_ms - 50_000))  # one of our availability checks (by id)
133 |         self.write(self.cli, "probe2", session(now_ms - 40_000, task_text=PROMPT))  # ours (by prompt)

```

```

134 |         self.scanner().state(own_task_ids=["probe1"])
135 |         self.assertEqual(st["tasks_seen"], 1)
136 |         self.assertTrue(st["open"])
137 |         self.assertEqual(st["current"]["model"], "us.anthropic.claude-opus-5")
138 |         self.assertEqual(st["current"]["source"], "CLI")
139 |         self.assertEqual(st["latency"]["hour"], {"n": 2, "p50": 3.2, "p95": 3.9})
140 |         self.assertEqual([r["s"] for r in st["recent"]], [4.0, 2.5])
141 |
142 |     def test_vscode_extension_storage_found(self):
143 |         now_ms = int(time.time() * 1000)
144 |         self.write(self.code, "vs1", session(now_ms - 30_000))
145 |         st = self.scanner().state()
146 |         self.assertEqual(st["current"]["source"], "VS Code")
147 |
148 |     def test_idle_history_is_not_open_but_open_cli_is(self):
149 |         old_ms = int((time.time() - 3 * 3600) * 1000)
150 |         self.write(self.cli, "old", session(old_ms), age_s=3 * 3600)
151 |         s = self.scanner()
152 |         st = s.state()
153 |         self.assertFalse(st["open"])
154 |         self.assertIsNone(st["current"])
155 |         self.assertEqual(st["latency"]["day"]["n"], 2)
156 |         self.procs = ["node /x/node_modules/vero/bin/vero.js"]
157 |         st = s.state(force=True)
158 |         self.assertTrue(st["open"] and st["cli_process"])
159 |         self.assertIsNone(st["current"]) # idle CLI: the page shows Vero's configured model
160 |
161 |     def test_cache_and_old_files_skipped(self):
162 |         now_ms = int(time.time() * 1000)
163 |         self.write(self.cli, "week_old", session(now_ms - 9 * 86400_000), age_s=9 * 86400)
164 |         s = self.scanner()
165 |         self.assertEqual(s.state()["tasks_seen"], 0)
166 |         self.assertIs(s.state(), s.state()) # cached between scans
167 |         p = self.write(self.cli, "new", session(now_ms))
168 |         self.assertEqual(s.state(force=True)["tasks_seen"], 1)
169 |         p.write_text("{not json}")
170 |         os.utime(p, (time.time() + 5, time.time() + 5))
171 |         self.assertEqual(s.state(force=True)["tasks_seen"], 0) # a broken file is skipped, not fatal
172 |
173 |     def test_missing_folders(self):
174 |         st = self.scanner().state()
175 |         self.assertEqual((st["open"], st["tasks_seen"], st["recent"]), (False, 0, []))
176 |
177 |
178 | if __name__ == "__main__":
179 |     unittest.main()
=== END FILE: tests/test_sessions.py ===

```

```
=== FILE: tests/test_settings.py (46 lines) ===
```

```

1 | import json
2 | import tempfile
3 | import unittest
4 | from pathlib import Path
5 |
6 | import tests.helpers_ as noqa: F401
7 | from vero_status.settings import CHEAP_MODEL, Settings, SettingsError, load, save
8 |
9 |
10 | class SettingsTest(unittest.TestCase):
11 |     def test_defaults(self):
12 |         s = Settings()
13 |         s.validate()
14 |         self.assertEqual((s.check_model, s.interval_minutes, s.port), (CHEAP_MODEL, 15, 8767))
15 |
16 |     def test_merge_validates(self):
17 |         self.assertEqual(Settings().merged({"interval_minutes": 0, "check_model": ""}).interval_minutes, 0)
18 |         for bad in (
19 |             {"interval_minutes": 7},
20 |             {"interval_minutes": "15"},
21 |             {"timeout_seconds": 5},
22 |             {"port": 80},
23 |             {"check_model": "two words"},
24 |             {"evil": 1},
25 |             {"vero_path": 3},
26 |             {"track_sessions": "yes"},
27 |         ):
28 |             with self.assertRaises(SettingsError, msg=bad):
29 |                 Settings().merged(bad)
30 |
31 |     def test_load_save_and_broken_file(self):
32 |         with tempfile.TemporaryDirectory() as d:
33 |             p = Path(d) / "settings.json"
34 |             self.assertEqual(load(p), Settings())
35 |             save(p, Settings().merged({"interval_minutes": 30}))
36 |             self.assertEqual(load(p).interval_minutes, 30)
37 |             p.write_bytes(b"\xef\xbb\xbf" + json.dumps({"interval_minutes": 60, "old_key": 1}).encode())
38 |             self.assertEqual(load(p).interval_minutes, 60) # BOM and unknown keys tolerated
39 |             p.write_text("{broken}")
40 |             self.assertEqual(load(p), Settings())
41 |             p.write_text('{"interval_minutes": 7}')
42 |             self.assertEqual(load(p), Settings())
43 |
44 |
45 | if __name__ == "__main__":
46 |     unittest.main()

```

```
=== END FILE: tests/test_settings.py ===
```

=== FILE: tests/test_vero.py (98 lines) ===

```

1 | import os
2 | import sys
3 | import tempfile
4 | import time
5 | import unittest
6 | from pathlib import Path
7 | from unittest import mock
8 |
9 | import tests.helpers_ as noqa: F401
10 | from vero_status import vero
11 |
12 | GUIDE_STREAM = [
13 |     {'type': "task_started", "taskId": "1790868292727"},
14 |     {'type': "say", "say": "task", "text": "Reply with exactly: OK", "modelInfo": {"providerId": "bedrock",
15 |     'modelId': "us.anthropic.claude-haiku-4-5-20251001-v1:0", "mode": "act"}},
16 |     {'type': "say", "say": "api_req_started", "text": "\\request\\": \\secret prompt\\\"}},
17 |     {'type': "say", "say": "text", "text": "0", "partial": true},
18 |     {'type': "say", "say": "error", "text": "[ERROR] You did not use a tool in your previous response!"},
19 |     {'type': "say", "say": "completion_result", "text": "OK"}
20 | ]
21 |
22 |
23 | class ParseTaskStreamTest(unittest.TestCase):
24 |     def test_stream_from_integration_guide(self):
25 |         s = vero.parse_task_stream(GUIDE_STREAM)
26 |         self.assertEqual((s.answer, s.provider, s.model), ("OK", "bedrock", "us.anthropic.claude-haiku-4-5-20251001-v1:0"))
27 |         self.assertEqual(s.events, 6)
28 |
29 |     def test_only_completion_result_counts_andpartials_ignored(self):
30 |         s = vero.parse_task_stream(['say': "text", "text": "OK"}, {'say': "completion_result", "text": "0", "partial": true}])
31 |         self.assertIsNone(s.answer)
32 |
33 |     def test_garbage_ignored(self):
34 |         s = vero.parse_task_stream(["", "banner", "{bad", "[1]", '{"type": "error", "message": "Bearer abc.def failed"}'])
35 |         self.assertEqual((s.events, s.error), (1, "[hidden] failed"))
36 |
37 |
38 | class ParseConfigTest(unittest.TestCase):
39 |     def test_key_value_lines_as_in_the_guide(self):
40 |         text = (
41 |             "actModeApiProvider : bedrock\n"
42 |             "actModeApiModelId: us.anthropic.claude-opus-5\n"
43 |             "awsRegion: us-west-2\n"
44 |             "other : x"
45 |         )
46 |         self.assertEqual(
47 |             vero.parse_config(text), {"provider": "bedrock", "model": "us.anthropic.claude-opus-5", "region": "us-west-2"}
48 |         )
49 |
50 |     def test_json_and_quoted_variants(self):
51 |         self.assertEqual(vero.parse_config({'actModeApiModelId': "m1", "awsRegion": "eu"}), {"model": "m1", "region": "eu"})
52 |         self.assertEqual(vero.parse_config(' "actModeApiModelId": "m2", ', {"model": "m2"})
53 |         self.assertEqual(vero.parse_config("nothing useful"), {})
54 |
55 |
56 | class SmallParsersTest(unittest.TestCase):
57 |     def test_version_and_clean(self):
58 |         self.assertEqual(vero.parse_version("vero 2.3.3 (35b52374)\nmore"), "vero 2.3.3 (35b52374)")
59 |         self.assertEqual(vero.parse_version(""), "")
60 |         self.assertNotIn("abc123", vero.clean("error token=abc123 password=x"))
61 |         self.assertEqual(len(vero.clean("x" * 999)), vero.DETAIL_MAX)
62 |
63 |     def test_task_args(self):
64 |         a = vero.task_args("vero", "", 120, Path("w"))
65 |         self.assertEqual(a, ["vero", "task", "--json", "-t", "120", "-c", "w", vero.PROMPT])
66 |         self.assertIn("-m", vero.task_args("vero", "m1", 120, Path("w")))

```

```

67 |         self.assertNotIn("--yolo", a)
68 |
69 |
70 |     class RunAndFindTest(unittest.TestCase):
71 |     def test_run_collects_output(self):
72 |         r = vero.run([sys.executable, "-c", "print('hi'); import sys; sys.exit(3)"], 10)
73 |         self.assertEqual((r.started, r.code, r.out.strip(), r.timed_out), (True, 3, "hi", False))
74 |
75 |     def test_run_missing_program(self):
76 |         self.assertFalse(vero.run(["no-such-program-xyz"], 5).started)
77 |
78 |     @unittest.skipIf(os.name == "nt", "POSIX process group")
79 |     def test_timeout_kills_the_whole_tree_fast(self):
80 |         t0 = time.time()
81 |         r = vero.run(["sh", "-c", "sleep 30 & sleep 30; echo late"], 0.5)
82 |         self.assertTrue(r.timed_out)
83 |         self.assertLess(time.time() - t0, 3)
84 |
85 |     def test_find_vero(self):
86 |         self.assertEqual(vero.find_vero(sys.executable), sys.executable)
87 |         with mock.patch("vero_status.vero.shutil.which", return_value=None), mock.patch.dict(os.environ, {"APPDATA": ""}):
88 |             self.assertIsNone(vero.find_vero("/nope/vero-xyz"))
89 |             with tempfile.TemporaryDirectory() as d:
90 |                 npm = Path(d) / "npm"
91 |                 npm.mkdir()
92 |                 (npm / "vero.cmd").write_text("@echo off")
93 |                 with mock.patch("vero_status.vero.shutil.which", return_value=None), mock.patch.dict(os.environ, {"APPDATA": d}):
94 |                     self.assertEqual(vero.find_vero(""), str(npm / "vero.cmd"))_# npm default location on Windows
95 |
96 |
97 | if __name__ == "__main__":
98 |     unittest.main()
=== END FILE: tests/test_vero.py ===

```

```
=== FILE: vero_status/__init__.py (4 lines) ===
 1 | """Vero Status: a small dashboard that shows whether Vero is available and which model it uses."""
 2 |
 3 | __version__ = "4.1.0"
 4 | APP_ID = "vero-status"
=== END FILE: vero_status/__init__.py ===
```

=== FILE: vero_status/app.py (84 lines) ===

```

1 | """Program start: one instance, dashboard in the browser, no console window."""
2 |
3 | from __future__ import annotations
4 |
5 | import json
6 | import logging
7 | import logging.handlers
8 | import sys
9 | import threading
10 | import urllib.request
11 | import webbrowser
12 | from pathlib import Path
13 |
14 | from . import APP_ID
15 | from .monitor import Monitor
16 | from .server import create
17 |
18 | ROOT = Path(__file__).resolve().parents[1]
19 | DATA = ROOT / "data"
20 | log = logging.getLogger("vero_status")
21 |
22 |
23 | def message(text: str) -> None:
24 |     """Tell the user something without a console (pythonw): a Windows message box."""
25 |     if sys.platform == "win32":
26 |         import ctypes
27 |
28 |         ctypes.windll.user32.MessageBoxW(None, text, "Vero Status", 0x40)
29 |     else:
30 |         print(text)
31 |
32 |
33 | def already_running(port: int) -> bool:
34 |     try:
35 |         with urllib.request.urlopen(f"http://127.0.0.1:{port}/api/health", timeout=2) as r:
36 |             return bool(json.load(r).get("app") == APP_ID)
37 |     except Exception:
38 |         return False
39 |
40 |
41 | def setup_logging() -> None:
42 |     DATA.mkdir(parents=True, exist_ok=True)
43 |     handler = logging.handlers.RotatingFileHandler(DATA / "vero-status.log", maxBytes=500_000, backupCount=2, encoding="utf-8")
44 |     logging.basicConfig(level=logging.INFO, handlers=[handler], format="%(asctime)s %(levelname)s %(message)s", force=True)
45 |
46 |
47 | def main() -> int:
48 |     setup_logging()
49 |     monitor = Monitor(DATA)
50 |     port = monitor.settings.port
51 |     url = f"http://127.0.0.1:{port}/"
52 |     if already_running(port):
53 |         webbrowser.open(url) # second double-click: just show the dashboard
54 |         return 0
55 |     try:
56 |         srv = create(monitor, port)
57 |     except OSError as e:
58 |         log.error("cannot use port %s: %s", port, e)
59 |         message(
60 |             f"Vero Status cannot start: port {port} is used by another program.\n\n"
61 |             f'Change "port" in {DATA / "settings.json"} and start it again.'
62 |         )
63 |         return 1
64 |     monitor.start(check_at_start=True)
65 |     log.info("dashboard %s", url)
66 |     threading.Timer(0.3, webbrowser.open, args=(url,)).start()

```

```

67 |     try:
68 |         srv.serve_forever()
69 |     except KeyboardInterrupt:
70 |         pass
71 |     finally:
72 |         monitor.stop()
73 |         srv.server_close()
74 |         log.info("stopped")
75 |     return 0
76 |
77 |
78 | def run() -> None:
79 |     try:
80 |         sys.exit(main())
81 |     except Exception as e: # last resort: never die silently
82 |         logging.getLogger("vero_status").exception("crash")
83 |         message(f"Vero Status stopped because of an error:\n{e}\n\nDetails: {DATA / 'vero-status.log'}")
84 |         sys.exit(1)
=== END FILE: vero_status/app.py ===

```

```
=== FILE: vero_status/monitor.py (221 lines) ===
```

```

1 | """The monitor: runs a check on a timer or on demand, keeps the latest result and a short history."""
2 |
3 | from __future__ import annotations
4 |
5 | import json
6 | import logging
7 | import threading
8 | import time
9 | from pathlib import Path
10 | from typing import Any, Callable, Dict, List, Optional
11 |
12 | from . import sessions, vero
13 | from .settings import Settings, load, save
14 |
15 | log = logging.getLogger("vero_status")
16 | HISTORY_MAX = 500
17 | Runner = Callable[[List[str], float, Optional[str]], vero.Proc]
18 |
19 |
20 | def perform_check(settings: Settings, workdir: Path, run: Runner = vero.run, now: Optional[float] = None) -> Dict[str, Any]:
21 |     """One availability check. Returns a JSON-ready record; never raises for Vero problems."""
22 |     rec: Dict[str, Any] = {
23 |         "time": time.time() if now is None else now,
24 |         "available": False,
25 |         "reason": "",
26 |         "seconds": None,
27 |         "asked_model": None,
28 |         "provider": None,
29 |         "vero_version": None,
30 |         "configured": {},
31 |     }
32 |     exe = vero.find_vero(settings.vero_path)
33 |     if not exe:
34 |         rec["reason"] = "Vero CLI not found on this computer (set its path in Settings)"
35 |         return rec
36 |     ver = run([exe, "version"], 30, None)
37 |     if not ver.started or ver.timed_out or ver.code != 0:
38 |         rec["reason"] = "Vero CLI does not start: " + vero.clean(ver.err or ver.out or "no output")
39 |         return rec
40 |     rec["vero_version"] = vero.parse_version(ver.out)
41 |     cfg = run([exe, "config"], 30, None)
42 |     if cfg.started and cfg.code == 0:
43 |         rec["configured"] = vero.parse_config(cfg.out)
44 |     workdir.mkdir(parents=True, exist_ok=True) # empty folder: the agent has nothing to read or change
45 |     limit = settings.timeout_seconds
46 |     task = run(vero.task_args(exe, settings.check_model, limit, workdir), limit + 30, str(workdir))
47 |     stream = vero.parse_task_stream(task.out.splitlines())
48 |     rec["asked_model"], rec["provider"] = stream.model, stream.provider # model Vero used for the check
49 |     rec["task_id"] = stream.task_id # lets the session tracker ignore our own test tasks
50 |     if task.timed_out:
51 |         rec["reason"] = f"no answer within {limit + 30} s"
52 |     elif stream.answer is not None:
53 |         rec["available"] = True
54 |         rec["seconds"] = round(task.seconds, 1) # only a real answer has a response time
55 |         if "ok" not in stream.answer.lower():
56 |             rec["reason"] = "answered, but not with OK (a guardrail or the model replied differently)"
57 |     elif stream.error:
58 |         rec["reason"] = stream.error
59 |     elif task.code:
60 |         msg = vero.clean(task.err or task.out or "no output")
61 |         msg = msg[6:].lstrip() if msg.lower().startswith("error:") else msg
62 |         rec["reason"] = f"Vero reported an error (exit code {task.code}): {msg}"
63 |     elif stream.events == 0:
64 |         rec["reason"] = "Vero returned no JSON events (is this Vero CLI 2.3 or newer?)"
65 |     else:
66 |         rec["reason"] = "Vero finished without an answer"

```

```

67 |     return rec
68 |
69 |
70 |     class Monitor:
71 |     def __init__(self, data_dir: Path, run: Runner = vero.run, scanner: Optional[sessions.Scanner] = None):
72 |         self.data_dir = data_dir
73 |         self.run = run
74 |         self.settings_path = data_dir / "settings.json"
75 |         self.history_path = data_dir / "history.json"
76 |         self.settings = load(self.settings_path)
77 |         self.history: List[Dict[str, Any]] = self._load_history()
78 |         self.checking = False
79 |         self.next_check: Optional[float] = None
80 |         self._lock = threading.Lock()
81 |         self._wake = threading.Event()
82 |         self._stop = threading.Event()
83 |         self.scanner = scanner or sessions.Scanner(ignore_processes=[str(data_dir / "sandbox"), "vero_status", "vero-status"])
84 |
85 |     # history -----
86 |     def _load_history(self) -> List[Dict[str, Any]]:
87 |     try:
88 |         data = json.loads(self.history_path.read_text(encoding="utf-8"))
89 |         return [r for r in data if isinstance(r, dict) and "time" in r][-HISTORY_MAX:]
90 |     except (OSError, ValueError):
91 |         return []
92 |
93 |     def _save_history(self) -> None:
94 |         self.data_dir.mkdir(parents=True, exist_ok=True)
95 |         tmp = self.history_path.with_suffix(".tmp")
96 |         tmp.write_text(json.dumps(self.history[-HISTORY_MAX:]), encoding="utf-8")
97 |         tmp.replace(self.history_path)
98 |
99 |     # checks -----
100 |     def check_now(self, trigger: str = "manual") -> bool:
101 |         """Start a check in the background. False if one is already running."""
102 |         with self._lock:
103 |             if self.checking:
104 |                 return False
105 |             self.checking = True
106 |             threading.Thread(target=self._check, args=(trigger,), daemon=True).start()
107 |             return True
108 |
109 |     def _check(self, trigger: str) -> None:
110 |     try:
111 |         rec = perform_check(self.settings, self.data_dir / "sandbox", self.run)
112 |     except Exception as e: # a bug must never kill the program
113 |         log.exception("check failed")
114 |         rec = {
115 |             "time": time.time(),
116 |             "available": False,
117 |             "reason": f"monitor error: {type(e).__name__}",
118 |             "seconds": None,
119 |             "asked_model": None,
120 |             "provider": None,
121 |             "vero_version": None,
122 |             "configured": {},
123 |         }
124 |         rec["trigger"] = trigger
125 |         with self._lock:
126 |             self.history.append(rec)
127 |             self.history = self.history[-HISTORY_MAX:]
128 |             self._save_history()
129 |             self.checking = False
130 |             log.info("check: %s %s", "AVAILABLE" if rec["available"] else "NOT AVAILABLE", rec["reason"])
131 |             self._plan_next()
132 |
133 |     def _plan_next(self) -> None:

```

```

134 |         m = self.settings.interval_minutes
135 |         self.next_check = time.time() + m * 60 if m else None
136 |         self._wake.set()
137 |
138 |     def start(self, check_at_start: bool = True) -> None:
139 |         def loop() -> None:
140 |             while not self._stop.is_set():
141 |                 self._wake.clear()
142 |                 due = self.next_check
143 |                 wait = None if due is None else max(0.0, due - time.time())
144 |                 if self._wake.wait(wait) or self._stop.is_set():
145 |                     continue # plan changed: re-evaluate
146 |                 if due is not None and time.time() >= due:
147 |                     self.next_check = None
148 |                 if not self.check_now("auto"):
149 |                     self._plan_next()
150 |
151 |         threading.Thread(target=loop, daemon=True).start()
152 |         threading.Thread(target=self._scan_loop, daemon=True).start()
153 |         if check_at_start:
154 |             self.check_now("start")
155 |         else:
156 |             self._plan_next()
157 |
158 |     def own_task_ids(self) -> List[str]:
159 |         with self._lock:
160 |             return [str(r["task_id"]) for r in self.history if r.get("task_id")]
161 |
162 |     def scan_sessions(self) -> Dict[str, Any]:
163 |         """Your own Vero sessions; never raises (a bad file must not break the dashboard)."""
164 |         try:
165 |             return self.scanner.state(self.own_task_ids(), force=True)
166 |         except Exception:
167 |             log.exception("session scan failed")
168 |             return {}
169 |
170 |     def _scan_loop(self) -> None:
171 |         while not self._stop.is_set():
172 |             if self.settings.track_sessions:
173 |                 self.scan_sessions()
174 |             self._stop.wait(sessions.SCAN EVERY_S)
175 |
176 |     def stop(self) -> None:
177 |         self._stop.set()
178 |         self._wake.set()
179 |
180 |     # settings -----
181 |     def update_settings(self, changes: Dict[str, Any]) -> Settings:
182 |         new = self.settings.merged(changes)
183 |         save(self.settings_path, new)
184 |         self.settings = new
185 |         if not self.checking:
186 |             self._plan_next()
187 |         return new
188 |
189 |     # view -----
190 |     def state(self) -> Dict[str, Any]:
191 |         with self._lock:
192 |             hist = list(self.history)
193 |             day = [r for r in hist if r["time"] >= time.time() - 86400]
194 |             last = hist[-1] if hist else None
195 |             last_ok = next((r for r in reversed(hist) if r.get("available")), None)
196 |             since = None
197 |             if last:
198 |                 since = last["time"]
199 |             for r in reversed(hist):
200 |                 if bool(r.get("available")) != bool(last.get("available")):

```

```

201 | #####break
202 | #####since = r["time"]
203 | #####return {
204 | #####    "checking": self.checking,
205 | #####    "next_check": self.next_check,
206 | #####    "last": last,
207 | #####    "since": since,
208 | #####    "configured": (last or {}).get("configured") or (last_ok or {}).get("configured") or {},
209 | #####    "availability_24h": round(sum(1 for r in day if r.get("available")) / len(day) * 100, 1) if day else None,
210 | #####    "checks_24h": len(day),
211 | #####    "history": hist[-48:],
212 | #####    "settings": {
213 | #####        "vero_path": self.settings.vero_path,
214 | #####        "vero_found": vero.find_vero(self.settings.vero_path),
215 | #####        "check_model": self.settings.check_model,
216 | #####        "interval_minutes": self.settings.interval_minutes,
217 | #####        "timeout_seconds": self.settings.timeout_seconds,
218 | #####        "track_sessions": self.settings.track_sessions,
219 | #####    },
220 | #####    "sessions": self.scanner.result if self.settings.track_sessions else None,
221 | #####}
=== END FILE: vero_status/monitor.py ===

```

```

=== FILE: vero_status/server.py (104 lines) ===
1 | """Local web server for the dashboard. Binds to 127.0.0.1 only.
2 | Host and Origin are checked so other web pages cannot use it."""
3 |
4 | from __future__ import annotations
5 |
6 | import json
7 | import logging
8 | import threading
9 | from http.server import BaseHTTPRequestHandler, ThreadingHTTPServer
10 | from pathlib import Path
11 | from typing import Any, Callable, Dict, Optional, Type
12 | from urllib.parse import urlparse
13 |
14 | from . import APP_ID, __version__
15 | from .monitor import Monitor
16 | from .settings import SettingsError
17 |
18 | log = logging.getLogger("vero_status")
19 | INDEX = Path(__file__).parent / "web" / "index.html"
20 | MAX_BODY = 10_000
21 |
22 |
23 | def make_handler(monitor: Monitor, port: int, on_quit: Callable[[], None]) -> Type[BaseHTTPRequestHandler]:
24 |     """hosts = {"127.0.0.1:{port}", "localhost:{port}"}
25 |
26 |     """class Handler(BaseHTTPRequestHandler):
27 |         """server_version = f"{APP_ID}/{__version__}"
28 |
29 |         """def log_message(self, format: str, *args: Any) -> None:
30 |             """log.debug("%s " + format, self.address_string(), *args)
31 |
32 |             """def _send(self, code: int, body: bytes, ctype: str) -> None:
33 |                 """self.send_response(code)
34 |                 """self.send_header("Content-Type", ctype)
35 |                 """self.send_header("Content-Length", str(len(body)))
36 |                 """self.send_header("Cache-Control", "no-store")
37 |                 """self.send_header("X-Content-Type-Options", "nosniff")
38 |                 """self.end_headers()
39 |                 """self.wfile.write(body)
40 |
41 |             """def _json(self, obj: Any, code: int = 200) -> None:
42 |                 """self._send(code, json.dumps(obj).encode(), "application/json")
43 |
44 |             """def _allowed(self, post: bool) -> bool:
45 |                 """host = (self.headers.get("Host") or "").lower()
46 |                 """if host not in hosts:
47 |                     """return False
48 |                 """origin = self.headers.get("Origin")
49 |                 """return not post or origin is None or urlparse(origin).netloc.lower() == host
50 |
51 |             """def do_GET(self) -> None:
52 |                 """if not self._allowed(post=False):
53 |                     """return self._json({"error": "forbidden"}, 403)
54 |                 """path = urlparse(self.path).path
55 |                 """if path in ("/", "/index.html"):
56 |                     """self._send(200, INDEX.read_bytes(), "text/html; charset=utf-8")
57 |                 """elif path == "/api/state":
58 |                     """self._json({"version": __version__, **monitor.state()})
59 |                 """elif path == "/api/health":
60 |                     """self._json({"app": APP_ID, "version": __version__})
61 |                 """else:
62 |                     """self._json({"error": "not found"}, 404)
63 |
64 |             """def do_POST(self) -> None:
65 |                 """if not self._allowed(post=True):
66 |                     """return self._json({"error": "forbidden"}, 403)

```

```

67 |     path = urlparse(self.path).path
68 |     if path == "/api/check":
69 |         started = monitor.check_now("manual")
70 |         return self._json({"started": started}, 202 if started else 409)
71 |     if path == "/api/settings":
72 |         try:
73 |             length = int(self.headers.get("Content-Length") or 0)
74 |             if not 0 < length <= MAX_BODY:
75 |                 raise SettingsError("empty or too large request")
76 |             changes = json.loads(self.rfile.read(length))
77 |             if not isinstance(changes, dict):
78 |                 raise SettingsError("expected a JSON object")
79 |             monitor.update_settings(changes)
80 |         except (SettingsError, ValueError, TypeError) as e:
81 |             return self._json({"error": str(e)}, 400)
82 |         return self._json({"saved": True})
83 |     if path == "/api/quit":
84 |         self._json({"stopping": True})
85 |         threading.Thread(target=on_quit, daemon=True).start()
86 |         return None
87 |         return self._json({"error": "not found"}, 404)
88 |
89 |     return Handler
90 |
91 |
92 | def create(monitor: Monitor, port: int, on_quit: Optional[Callable[[], None]] = None) -> ThreadingHTTPServer:
93 |     holder: Dict[str, ThreadingHTTPServer] = {}
94 |
95 |     def quit_() -> None:
96 |         monitor.stop()
97 |         holder["srv"].shutdown()
98 |         if on_quit:
99 |             on_quit()
100 |
101 |     srv = ThreadingHTTPServer(("127.0.0.1", port), make_handler(monitor, port, quit_))
102 |     srv.daemon_threads = True
103 |     holder["srv"] = srv
104 |     return srv
=== END FILE: vero_status/server.py ===

```

```
=== FILE: vero_status/sessions.py (288 lines) ===
```

```

1 | """Your own Vero sessions (Vero CLI in a terminal, Vero in VS Code): latency and the model in use.
2 |
3 | How: Vero writes every task's event log to `tasks/<taskId>/ui_messages.json` (integration guide 3.5):
4 | a JSON list of events with `ts` (ms), `type`/'say' and `modelInfo`. Each model request starts with a
5 | `say: "api_req_started"` event; the first later event is the model's first response. The difference
6 | is the request latency, measured with Vero's own clock. Nothing is injected into Vero.
7 |
8 | Privacy: only timestamps, event kinds, modelInfo and the token counts inside `api_req_started` are read.
9 | Prompt and answer text are never kept. The files are only read, never changed.
10 | """
11 |
12 | from __future__ import annotations
13 |
14 | import glob
15 | import json
16 | import os
17 | import re
18 | import subprocess
19 | import sys
20 | import threading
21 | import time
22 | from dataclasses import dataclass, field
23 | from pathlib import Path
24 | from typing import Any, Dict, Iterable, List, Optional, Sequence, Set, Tuple
25 |
26 | from .vero import NO_WINDOW, PROMPT
27 |
28 | OPEN_WINDOW_S = 10 * 60_000 # a session with activity in the last 10 minutes counts as open
29 | SCAN_EVERY_S = 15
30 | MAX_TASK_AGE_S = 7 * 86400
31 | MAX_LATENCY_S = 30 * 60_000 # longer gaps are pauses (waiting for the user), not latency
32 | NOT_RESPONSES = {"api_req_started", "api_req_retried", "api_req_finished"}
33 |
34 |
35 | @dataclass(frozen=True)
36 | class Request:
37 |     start: float_000 # epoch seconds
38 |     seconds: float_000 # time to the model's first response
39 |     tokens_in: Optional[int]
40 |     tokens_out: Optional[int]
41 |     failed: bool
42 |
43 |
44 | @dataclass
45 | class TaskSummary:
46 |     task_id: str
47 |     source: str_000 # "CLI" or "VS Code"
48 |     first_prompt_is_probe: bool
49 |     model: Optional[str] = None
50 |     provider: Optional[str] = None
51 |     last_activity: float = 0.0
52 |     waiting_since: Optional[float] = None_000 # a request is running right now
53 |     requests: List[Request] = field(default_factory=list)
54 |
55 |
56 | def _int(value: Any) -> Optional[int]:
57 |     return value if isinstance(value, int) and not isinstance(value, bool) else None
58 |
59 |
60 | def parse_ui_messages(events: Sequence[Any], task_id: str, source: str, now: Optional[float] = None) -> TaskSummary:
61 |     """Pure: the event list of one task -> its model and request latencies."""
62 |     evs = sorted((e for e in events if isinstance(e, dict) and isinstance(e.get("ts"), (int, float))), key=lambda e: e["ts"])
63 |     first_text = next((str(e.get("text")) or "") for e in evs if e.get("say") == "task", "")
64 |     summary = TaskSummary(task_id, source, first_prompt_is_probe=first_text.strip() == PROMPT)
65 |     now = time.time() if now is None else now
66 |     for i, ev in enumerate(evs):

```

```

67 |         info = ev.get("modelInfo")
68 |         if isinstance(info, dict):
69 |             summary.model = info.get("modelId") or summary.model
70 |             summary.provider = info.get("providerId") or summary.provider
71 |             summary.last_activity = max(summary.last_activity, ev["ts"] / 1000)
72 |             if ev.get("say") != "api_req_started":
73 |                 continue
74 |             start = ev["ts"] / 1000
75 |             nxt = next((e for e in evs[i + 1 :] if e.get("say") not in NOT_RESPONSES), None)
76 |             if nxt is None:
77 |                 if now - start < MAX_LATENCY_S:
78 |                     summary.waiting_since = start
79 |                     continue
80 |             seconds = nxt["ts"] / 1000 - start
81 |             if not 0 <= seconds <= MAX_LATENCY_S:
82 |                 continue
83 |             tokens: Dict[str, Any] = {}
84 |             try: # only token counts; the "request" field (full prompt) is dropped immediately
85 |                 info_text = json.loads(ev.get("text") or "{}")
86 |                 if isinstance(info_text, dict):
87 |                     tokens = {k: info_text.get(k) for k in ("tokensIn", "tokensOut")}
88 |             except (TypeError, ValueError):
89 |                 pass
90 |             failed = nxt.get("say") in ("api_req_failed", "error") or nxt.get("ask") == "api_req_failed"
91 |             summary.requests.append(
92 |                 Request(start, round(seconds, 2), _int(tokens.get("tokensIn")), _int(tokens.get("tokensOut")), failed)
93 |             )
94 |             return summary
95 |
96 |
97 | def percentile(values: Sequence[float], pct: float) -> Optional[float]:
98 |     if not values:
99 |         return None
100 |     s = sorted(values)
101 |     k = (len(s) - 1) * pct / 100
102 |     lo, hi = int(k), min(int(k) + 1, len(s) - 1)
103 |     return round(s[lo] + (s[hi] - s[lo]) * (k - lo), 1)
104 |
105 |
106 | # ---- where Vero keeps its task logs -----
107 |
108 |
109 | def default_roots() -> List[Tuple[str, str]]:
110 |     """(glob pattern of a `tasks` folder, source label). CLI path measured; VS Code paths follow the
111 |     VS Code extension storage convention and are matched by an extension folder containing 'vero'."""
112 |     home = Path.home()
113 |     roots = [(str(home / ".vero" / "data" / "tasks"), "CLI")]
114 |     code_storage = [
115 |         Path(os.environ.get("APPDATA", home / "AppData" / "Roaming")) / "Code" / "User" / "globalStorage",
116 |         home / ".config" / "Code" / "User" / "globalStorage",
117 |         home / "Library" / "Application Support" / "Code" / "User" / "globalStorage",
118 |     ]
119 |     for base in code_storage:
120 |         roots.append((str(base / "*vero*" / "tasks"), "VS Code"))
121 |         roots.append((str(base / "*Vero*" / "tasks"), "VS Code"))
122 |     return roots
123 |
124 |
125 | def find_task_files(roots: Iterable[Tuple[str, str]], now: float) -> List[Tuple[Path, str]]:
126 |     seen = set()
127 |     found: List[Tuple[Path, str]] = []
128 |     for pattern, source in roots:
129 |         for tasks_dir in glob.glob(pattern):
130 |             for f in glob.glob(os.path.join(glob.escape(tasks_dir), "*", "ui_messages.json")):
131 |                 p = Path(f)
132 |                 try:
133 |                     if now - p.stat().st_mtime > MAX_TASK_AGE_S or p in seen:

```

```

134 | #####continue
135 | #####except OSError:
136 | #####continue
137 | #####seen.add(p)
138 | #####found.append((p, source))
139 | #####return found
140 |
141 |
142 | # ---- is a Vero CLI open right now? -----
143 |
144 | _TOKEN = re.compile(r'["'"\^]*"|\\S+')
145 | _VERO_SCRIPT = re.compile(r"^(?![\\\/])(?![^\\\/]+\[/\])?vero(?:[\\\/]\.js$|)$", re.I)
146 | VERO_EXES = {"vero", "vero.cmd", "vero.exe"}
147 | NODE_EXES = {"node", "node.exe"}
148 | ADMIN_COMMANDS = {"version", "--version", "-v", "config", "history", "h", "auth", "mcp", "token", "update", "dev", "--help", "-h"}
149 |
150 |
151 | def is_interactive_vero(cmdline: str, ignore: Sequence[str]) -> bool:
152 |     """True for a user's Vero CLI: the program is vero.cmd/.exe, or node running a script in a `vero`
153 |     package. Not our own checks (ignore list), not admin calls like `vero version`."""
154 |     tokens = [t.strip('') for t in _TOKEN.findall(cmdline or "")]
155 |     if not tokens:
156 |         return False
157 |     exe = re.split(r"[\\\/]", tokens[0])[-1].lower()
158 |     if exe in VERO_EXES:
159 |         args = tokens[1:]
160 |     elif exe in NODE_EXES and len(tokens) > 1 and _VERO_SCRIPT.search(tokens[1]):
161 |         args = tokens[2:]
162 |     else:
163 |         return False
164 |     low = cmdline.lower()
165 |     if any(x and x.lower() in low for x in ignore):
166 |         return False
167 |     return not (args and args[0].lower() in ADMIN_COMMANDS)
168 |
169 |
170 | def process_command_lines() -> List[str]:
171 |     """Command lines of node / vero processes. Windows: one hidden PowerShell call."""
172 |     try:
173 |         if sys.platform == "win32":
174 |             ps = (
175 |                 "Get-CimInstance Win32_Process -Filter \"Name='node.exe' OR Name='vero.exe'\" | ForEach-Object { $_.CommandLine }"
176 |             )
177 |             r = subprocess.run(
178 |                 ["powershell", "-NoProfile", "-NonInteractive", "-Command", ps],
179 |                 capture_output=True,
180 |                 text=True,
181 |                 timeout=15,
182 |                 creationflags=NO_WINDOW,
183 |                 check=False,
184 |             )
185 |         else:
186 |             r = subprocess.run(["ps", "-eo", "args"], capture_output=True, text=True, timeout=10, check=False)
187 |         return [ln.strip() for ln in r.stdout.splitlines() if ln.strip()]
188 |     except (OSError, subprocess.SubprocessError):
189 |         return []
190 |
191 |
192 | # ---- the scanner -----
193 |
194 |
195 | class Scanner:
196 |     """Re-reads changed task logs at most every SCAN_EVERY_S seconds (cached by file mtime)."""
197 |
198 |     def __init__(
199 |         self,
200 |         roots: Optional[List[Tuple[str, str]]] = None,

```

```

201 |         ignore_processes: Sequence[str] = (),
202 |         list_processes: Any = process_command_lines,
203 |         None) -> None:
204 |         self.roots = roots if roots is not None else default_roots()
205 |         self.ignore_processes = list(ignore_processes)
206 |         self.list_processes = list_processes
207 |         self._cache: Dict[Path, Tuple[float, TaskSummary]] = {}
208 |         self._last_scan = 0.0
209 |         self._result: Dict[str, Any] = {}
210 |         self._lock = threading.Lock()
211 |
212 |     @property
213 |     def result(self) -> Dict[str, Any]:
214 |         return self._result
215 |
216 |     def state(self, own_task_ids: Iterable[str] = (), now: Optional[float] = None, force: bool = False) -> Dict[str, Any]:
217 |         now = time.time() if now is None else now
218 |         with self._lock:
219 |             if not force and self._result and now - self._last_scan < SCAN_EVERY_S:
220 |                 return self._result
221 |             self._last_scan = now
222 |             self._result = self._scan(set(own_task_ids), now)
223 |             return self._result
224 |
225 |     def _scan(self, own: Set[str], now: float) -> Dict[str, Any]:
226 |         tasks: List[TaskSummary] = []
227 |         live = set()
228 |         for path, source in find_task_files(self.roots, now):
229 |             live.add(path)
230 |             try:
231 |                 mtime = path.stat().st_mtime
232 |                 cached = self._cache.get(path)
233 |                 if cached and cached[0] == mtime:
234 |                     summary = cached[1]
235 |                 else:
236 |                     data = json.loads(path.read_text(encoding="utf-8"))
237 |                     summary = parse_ui_messages(data if isinstance(data, list) else [], path.parent.name, source, now)
238 |                     self._cache[path] = (mtime, summary)
239 |             except (OSError, ValueError):
240 |                 continue
241 |             if summary.task_id in own or summary.first_prompt_is_probe:
242 |                 continue_# our own availability checks are not your sessions
243 |             tasks.append(summary)
244 |             self._cache = {p: v for p, v in self._cache.items() if p in live}
245 |             return summarize(tasks, self._cli_open(), now, [r for r, _ in self.roots])
246 |
247 |     def _cli_open(self) -> bool:
248 |         return any(is_interactive_vero(c, self.ignore_processes) for c in self.list_processes())
249 |
250 |
251 | def summarize(tasks: List[TaskSummary], cli_open: bool, now: float, roots: List[str]) -> Dict[str, Any]:
252 |     recent = sorted(tasks, key=lambda t: t.last_activity, reverse=True)
253 |     active = [t for t in recent if now - t.last_activity < OPEN_WINDOW_S or t.waiting_since]
254 |     current = active[0] if active else None_# an idle open CLI shows Vero's configured model instead
255 |     reqs = sorted([(r, t) for t in tasks for r in t.requests], key=lambda x: x[0].start)
256 |
257 |     def window(seconds: float) -> Dict[str, Any]:
258 |         vals = [r.seconds for r, _ in reqs if now - r.start <= seconds and not r.failed]
259 |         return {"n": len(vals), "p50": percentile(vals, 50), "p95": percentile(vals, 95)}
260 |
261 |     return {
262 |         "open": bool(active) or cli_open,
263 |         "cli_process": cli_open,
264 |         "current": None
265 |         if current is None
266 |         else {
267 |             "source": current.source,

```

```

268 |     "model": current.model,
269 |     "provider": current.provider,
270 |     "last_activity": current.last_activity,
271 |     "waiting_since": current.waiting_since,
272 | },
273 |     "latency": {"hour": window(3600), "day": window(86400)},
274 |     "recent": [
275 |         {
276 |             "t": r.start,
277 |             "s": r.seconds,
278 |             "failed": r.failed,
279 |             "source": t.source,
280 |             "model": t.model,
281 |             "tokens_in": r.tokens_in,
282 |             "tokens_out": r.tokens_out,
283 |         }
284 |         for r, t in reqs[-40:]
285 |     ],
286 |     "tasks_seen": len(tasks),
287 |     "searched": roots,
288 | }
=== END FILE: vero_status/sessions.py ===

```

```

=== FILE: vero_status/settings.py (65 lines) ===
1 | """User settings, changed from the dashboard and kept in data/settings.json."""
2 |
3 | from __future__ import annotations
4 |
5 | import json
6 | from dataclasses import asdict, dataclass, replace
7 | from pathlib import Path
8 | from typing import Any, Dict
9 |
10 | INTERVALS = (0, 5, 15, 30, 60)  # minutes; 0 = only when "Check now" is clicked
11 | CHEAP_MODEL = "us.anthropic.claude-haiku-4-5-20251001-v1:0"
12 |
13 |
14 | class SettingsError(ValueError):
15 |     """pass"""
16 |
17 |
18 | @dataclass(frozen=True)
19 | class Settings:
20 |     """vero_path: str = ""  # empty = find it automatically
21 |     """check_model: str = CHEAP_MODEL  # empty = Vero's own configured model
22 |     """interval_minutes: int = 15
23 |     """timeout_seconds: int = 120
24 |     """port: int = 8767
25 |     """track_sessions: bool = True  # read your own Vero sessions (CLI, VS Code) for latency and the model in use
26 |
27 |     def merged(self, changes: Dict[str, Any]) -> Settings:
28 |         """A validated copy with the given changes (unknown keys are rejected)."""
29 |         allowed = set(asdict(self))
30 |         unknown = set(changes) - allowed
31 |         if unknown:
32 |             raise SettingsError(f"unknown setting(s): {' '.join(sorted(unknown))}")
33 |         new = replace(self, **changes)
34 |         new.validate()
35 |         return new
36 |
37 |     def validate(self) -> None:
38 |         if not isinstance(self.vero_path, str) or not isinstance(self.check_model, str):
39 |             raise SettingsError("vero_path and check_model must be text")
40 |         if len(self.check_model) > 200 or any(c.isspace() for c in self.check_model):
41 |             raise SettingsError("the model id must be one word without spaces")
42 |         if self.interval_minutes not in INTERVALS:
43 |             raise SettingsError(f"interval must be one of {INTERVALS} minutes")
44 |         if not isinstance(self.timeout_seconds, int) or not 30 <= self.timeout_seconds <= 600:
45 |             raise SettingsError("timeout must be between 30 and 600 seconds")
46 |         if not isinstance(self.track_sessions, bool):
47 |             raise SettingsError("track_sessions must be true or false")
48 |         if not isinstance(self.port, int) or not 1024 <= self.port <= 65535:
49 |             raise SettingsError("port must be between 1024 and 65535")
50 |
51 |
52 | def load(path: Path) -> Settings:
53 |     """Settings from the file, or defaults. A broken file never stops the program."""
54 |     try:
55 |         raw = json.loads(path.read_text(encoding="utf-8-sig"))
56 |         return Settings().merged({k: v for k, v in raw.items() if k in asdict(Settings())})
57 |     except (OSError, ValueError, TypeError, AttributeError):
58 |         return Settings()
59 |
60 |
61 | def save(path: Path, settings: Settings) -> None:
62 |     path.parent.mkdir(parents=True, exist_ok=True)
63 |     tmp = path.with_suffix(".tmp")
64 |     tmp.write_text(json.dumps(asdict(settings), indent=2) + "\n", encoding="utf-8")
65 |     tmp.replace(path)
=== END FILE: vero_status/settings.py ===

```



```

67 | subprocess.run(
68 |     ["taskkill", "/T", "/F", "/PID", str(proc.pid)], capture_output=True, creationflags=NO_WINDOW, check=False
69 | )
70 | else:
71 |     os.killpg(proc.pid, signal.SIGKILL)
72 | with contextlib.suppress(OSError):
73 |     proc.kill()
74 |
75 |
76 | def run(args: Sequence[str], timeout_s: float, cwd: Optional[str] = None) -> Proc:
77 |     """Start a process without a window, collect output, kill the whole tree on timeout."""
78 |     t0 = time.perf_counter()
79 |     try:
80 |         proc = subprocess.Popen(
81 |             list(args),
82 |             stdin=subprocess.DEVNULL,
83 |             stdout=subprocess.PIPE,
84 |             stderr=subprocess.PIPE,
85 |             cwd=cwd,
86 |             creationflags=NO_WINDOW,
87 |             start_new_session=os.name != "nt",
88 |         )
89 |     except OSError as e:
90 |         return Proc(False, None, "", f"cannot start {Path(args[0]).name}: {e}", 0.0, False)
91 |     stdout, stderr = proc.stdout, proc.stderr
92 |     if stdout is None or stderr is None:
93 |         _kill_tree(proc)
94 |         return Proc(False, None, "", "no output pipes", 0.0, False)
95 |     out: List[bytes] = []
96 |     err: List[bytes] = []
97 |     readers = [
98 |         threading.Thread(target=lambda: out.append(stdout.read()), daemon=True),
99 |         threading.Thread(target=lambda: err.append(stderr.read()), daemon=True),
100 |     ]
101 |     for r in readers:
102 |         r.start()
103 |     timed_out = False
104 |     try:
105 |         proc.wait(timeout=timeout_s)
106 |     except subprocess.TimeoutExpired:
107 |         timed_out = True
108 |         _kill_tree(proc)
109 |         proc.wait()
110 |     seconds = time.perf_counter() - t0
111 |     for r in readers:
112 |         r.join(timeout=5)
113 |     stdout.close()
114 |     stderr.close()
115 |     return Proc(
116 |         True,
117 |         proc.returncode,
118 |         b"".join(out).decode("utf-8", "replace"),
119 |         b"".join(err).decode("utf-8", "replace"),
120 |         seconds,
121 |         timed_out,
122 |     )
123 |
124 |
125 | # ---- pure parsers -----
126 |
127 |
128 | def parse_version(text: str) -> str:
129 |     first = (text.strip().splitlines() or [""])[0]
130 |     return clean(first)[:60]
131 |
132 |
133 | CONFIG_KEYS = {

```

```

134 |     """actModeApiModelId": "model",
135 |     """actModeApiProvider": "provider",
136 |     """awsRegion": "region",
137 |     """planModeApiModelId": "plan_model",
138 | }
139 |
140 |
141 | def parse_config(text: str) -> Dict[str, str]:
142 |     """`vero config` output -> {model, provider, region, plan_model}. Accepts JSON or `key : value` lines."""
143 |     found: Dict[str, str] = {}
144 |     try:
145 |         data = json.loads(text)
146 |         if isinstance(data, dict):
147 |             for key, name in CONFIG_KEYS.items():
148 |                 if isinstance(data.get(key), (str, int, float)):
149 |                     found[name] = str(data[key])
150 |             return found
151 |     except json.JSONDecodeError:
152 |         pass
153 |     for line in text.splitlines():
154 |         m = re.match(r"^\s*['\"]?(\\w+)[\\\"]?\s*[:=]\s*['\"]?([^\"]*,)+[\\\"]?\.?\s*$", line)
155 |         if m and m.group(1) in CONFIG_KEYS:
156 |             found[CONFIG_KEYS[m.group(1)]] = m.group(2).strip()
157 |     return found
158 |
159 |
160 | @dataclass(frozen=True)
161 | class TaskStream:
162 |     answer: Optional[str]
163 |     provider: Optional[str]
164 |     model: Optional[str]
165 |     error: Optional[str]
166 |     events: int
167 |     task_id: Optional[str] = None
168 |
169 |
170 | def parse_task_stream(lines: Iterable[str]) -> TaskStream:
171 |     answer = provider = model = error = task_id = None
172 |     events = 0
173 |     for raw in lines:
174 |         raw = raw.strip()
175 |         if not raw.startswith("{"):
176 |             continue
177 |         try:
178 |             ev = json.loads(raw)
179 |         except json.JSONDecodeError:
180 |             continue
181 |         if not isinstance(ev, dict):
182 |             continue
183 |         events += 1
184 |         if ev.get("type") == "task_started" and ev.get("taskId") is not None:
185 |             task_id = str(ev["taskId"])
186 |             info = ev.get("modelInfo")
187 |             if isinstance(info, dict):
188 |                 provider = info.get("providerId") or provider
189 |                 model = info.get("modelId") or model
190 |             if ev.get("partial") is True:
191 |                 continue
192 |             if ev.get("say") == "completion_result":
193 |                 answer = str(ev.get("text") or "")
194 |             elif ev.get("say") in ("error", "api_req_failed") or ev.get("type") == "error":
195 |                 error = clean(str(ev.get("text") or ev.get("message") or "error"))
196 |             return TaskStream(answer, provider, model, error, events, task_id)
197 |
198 |
199 | def task_args(exe: str, model: str, timeout_s: int, workdir: Path, prompt: str = PROMPT) -> List[str]:
200 |     args = [exe, "task", "--json", "-t", str(timeout_s), "-c", str(workdir)]

```

```
201 |     if model:
202 |         args += ["-m", model]
203 |     return [*args, prompt]# never --yolo: the probe needs no file or shell access
=== END FILE: vero_status/vero.py ===
```

=== FILE: vero_status/web/index.html (335 lines) ===

```

1 | <!doctype html>
2 | <html lang="en">
3 | <head>
4 | <meta charset="utf-8">
5 | <meta name="viewport" content="width=device-width, initial-scale=1">
6 | <title>Vero Status</title>
7 | <link rel="icon" id="favicon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg' viewBox='0 0 16 16'%3E%3Ccircle cx='8' cy='8' r='7' fill='%238a94a3'/%3E%3C/svg%3E">
8 | <style>
9 | :root{
10 |   --ink:#1b2230; --mut:#5d6878; --line:#dde2ea; --paper:#f4f6f9; --card:#ffffff; --brand:#0a6aa1;
11 |   --ok:#1f7a45; --ok-bg:#e8f4ed; --bad:#9b1c2e; --bad-bg:#f8e7ea; --warn:#a8500b; --idle:#8a94a3; --idle-bg:#eef1f5;
12 |   --sans:"Segoe UI","IBM Plex Sans",Roboto,Helvetica,Arial,sans-serif; --mono:Consolas,"IBM Plex Mono",ui-monospace,monospace;
13 | }
14 | @media (prefers-color-scheme: dark){:root{
15 |   --ink:#e6eaf0; --mut:#9aa5b4; --line:#2c3441; --paper:#10141a; --card:#171c24; --brand:#4fa8dc;
16 |   --ok:#4cc38a; --ok-bg:#132a1f; --bad:#f06b7f; --bad-bg:#321a20; --warn:#e39a4b; --idle:#6f7a89; --idle-bg:#1c222b;
17 | }}
18 | *{box-sizing:border-box}
19 | body{margin:0;background:var(--paper);color:var(--ink);font:15px/1.5 var(--sans)}
20 | .wrap{max-width:880px;margin:0 auto;padding:22px 20px 40px}
21 | header{display:flex;align-items:center;gap:12px;flex-wrap:wrap;margin-bottom:16px}
22 | header h1{font-size:20px;margin:0;font-weight:700}
23 | header .ver{color:var(--mut);font-size:13px}
24 | header .sp{flex:1}
25 | button{font:inherit;font-size:14px;border:1px solid var(--line);background:var(--card);color:var(--ink);border-radius:8px;padding:8px 14px;cursor:pointer}
26 | button.primary{background:var(--brand);border-color:var(--brand);color:#fff;font-weight:600}
27 | button.disabled{opacity:.55;cursor:default}
28 | button:focus-visible,input:focus-visible,select:focus-visible{outline:2px solid var(--brand);outline-offset:2px}
29 | .card{background:var(--card);border:1px solid var(--line);border-radius:12px;padding:18px 20px;margin-bottom:14px}
30 | .hero{display:flex;gap:20px;align-items:center;padding:26px 24px;background:var(--idle-bg)}
31 | .hero.ok{background:var(--ok-bg);border-color:color-mix(in srgb,var(--ok) 35%,var(--line))}
32 | .hero.bad{background:var(--bad-bg);border-color:color-mix(in srgb,var(--bad) 35%,var(--line))}
33 | .lamp{width:72px;height:72px;border-radius:50%;flex:none;display:flex;align-items:center;justify-content:center;color:#fff;font-size:36px;font-weight:800;background:var(--idle)}
34 | .ok .lamp{background:var(--ok)} .bad .lamp{background:var(--bad)}
35 | .checking .lamp{animation:pulse 1.2s ease-in-out infinite}
36 | @keyframes pulse{50%{opacity:.45}}
37 | @media (prefers-reduced-motion:reduce){.checking .lamp{animation:none}}
38 | .hero h2{margin:0;font-size:28px;line-height:1.2}
39 | .hero .meta{color:var(--mut);margin-top:4px}
40 | .hero .why{margin-top:8px;font-size:14px}
41 | .ok .why{color:var(--warn)} .bad .why{color:var(--bad)}
42 | .label{font-size:12px;text-transform:uppercase;letter-spacing:.06em;color:var(--mut);margin-bottom:6px}
43 | .model{display:grid;grid-template-columns:1fr 1fr;gap:18px}
44 | .model .name{font-size:22px;font-weight:700;line-height:1.25}
45 | .model .id{font-family:var(--mono);font-size:12px;color:var(--mut);overflow-wrap:anywhere;margin-top:2px}
46 | .model .sub{font-size:13px;color:var(--mut);margin-top:4px}
47 | .facts{display:grid;grid-template-columns:repeat(3,1fr);gap:14px}
48 | .facts .v{font-size:22px;font-weight:700;font-variant-numeric:tabular-nums}
49 | .dots{display:flex;gap:4px;flex-wrap:wrap;margin-top:4px}
50 | .live{display:flex;align-items:center;gap:12px;padding:12px 18px}
51 | .live .dot{width:12px;height:12px;border-radius:50%;background:var(--idle);flex:none}
52 | .live.on .dot{background:var(--ok);box-shadow:0 0 4px color-mix(in srgb,var(--ok) 22%,transparent)}
53 | .live .what{font-weight:600}
54 | .live .mdl{margin-left:auto;text-align:right}
55 | .live .mdl b{font-size:17px}
56 | .live .mdl .id{font-family:var(--mono);font-size:11.5px;color:var(--mut)}
57 | .bars{display:flex;align-items:flex-end;gap:2px;height:96px;margin-top:6px;border-bottom:1px solid var(--line);position:relative}
58 | .bars .b{flex:1;max-width:22px;min-height:2px;background:var(--brand);border-radius:4px 4px 0 0;position:relative;cursor:default}
59 | .bars .b.fail{background:var(--bad)}
60 | .bars .b:hover,.bars .b:focus{outline:2px solid var(--ink);outline-offset:1px}
61 | .bars .p50{position:absolute;left:0;right:0;border-top:1px dashed var(--mut);pointer-events:none}
62 | .bars .p50 span{position:absolute;right:0;top:-17px;font-size:11px;color:var(--mut);background:var(--card);padding:0 3px}
63 | .tip{position:fixed;pointer-events:none;background:var(--card);border:1px solid var(--line);border-radius:6px;padding:6px 9px;font-size:12.5px;box-shadow:0 4px 14px rgba(0,0,0,.15);display:none;z
+ -index:5}
64 | .check{display:flex;align-items:center;gap:8px}
65 | .check input{width:auto}

```

```

66 | .dots span{width:14px;height:14px;border-radius:4px;background:var(--idle)}
67 | .dots span.ok{background:var(--ok)} .dots span.bad{background:var(--bad)}
68 | .muted{color:var(--mut);font-size:13px}
69 | .settings{display:none}
70 | .settings.open{display:block}
71 | .form{display:grid;grid-template-columns:220px 1fr;gap:12px 16px;align-items:center}
72 | .form input,.form select{font:inherit;font-size:14px;padding:7px 10px;border:1px solid var(--line);border-radius:8px;background:var(--card);color:var(--ink);width:100%}
73 | .form .hint{grid-column:2;font-size:12.5px;color:var(--mut);margin-top:-6px}
74 | .row{display:flex;gap:10px;align-items:center;margin-top:14px}
75 | .msg{font-size:13px}
76 | .msg.err{color:var(--bad)} .msg.ok{color:var(--ok)}
77 | .overlay{position:fixed;inset:0;background:var(--paper);display:none;align-items:center;justify-content:center;text-align:center;padding:20px}
78 | .overlay.show{display:flex}
79 | .overlay h2{margin:0 0 8px}
80 | @media (max-width:640px){.live{flex-wrap:wrap}.live .mdl{margin-left:24px;text-align:left;width:100%}.model,.facts{grid-template-columns:1fr}.form{grid-template-columns:1fr}.form .hint{grid-column
+ n:1}
81 |   .hero{flex-direction:column;align-items:flex-start}.hero h2{font-size:23px}}
82 | </style>
83 | </head>
84 | <body>
85 | <div class="wrap">
86 |   <header>
87 |     <h1>Vero Status</h1><span class="ver" id="ver"></span>
88 |     <span class="sp"></span>
89 |     <button class="primary" id="checkBtn" type="button">Check now</button>
90 |     <button id="setBtn" type="button" aria-expanded="false" aria-controls="settings">Settings</button>
91 |     <button id="quitBtn" type="button">Quit</button>
92 |   </header>
93 |
94 |   <section class="card hero" id="hero" aria-live="polite">
95 |     <div class="lamp" id="lamp">?</div>
96 |     <div>
97 |       <h2 id="title">Starting...</h2>
98 |       <div class="meta" id="meta"></div>
99 |       <div class="why" id="why"></div>
100 |     </div>
101 |   </section>
102 |
103 |   <section class="card live" id="live" aria-live="polite">
104 |     <span class="dot"></span>
105 |     <div><div class="what" id="liveWhat">Looking for an open Vero...</div><div class="muted" id="liveSub"></div></div>
106 |     <div class="mdl" id="liveModel"></div>
107 |   </section>
108 |
109 |   <section class="card">
110 |     <div class="model">
111 |       <div>
112 |         <div class="label">Vero's model</div>
113 |         <div class="name" id="cfgName">~</div>
114 |         <div class="id" id="cfgId"></div>
115 |         <div class="sub" id="cfgSub"></div>
116 |       </div>
117 |       <div>
118 |         <div class="label" id="ansLabel">Answered the last check</div>
119 |         <div class="name" id="ansName">~</div>
120 |         <div class="id" id="ansId"></div>
121 |         <div class="sub" id="ansSub"></div>
122 |       </div>
123 |     </div>
124 |   </section>
125 |
126 |   <section class="card">
127 |     <div class="facts">
128 |       <div><div class="label">Available, last 24 h</div><div class="v" id="avail">~</div><div class="muted" id="availSub"></div></div>
129 |       <div><div class="label">Last answer took</div><div class="v" id="took">~</div><div class="muted">for "Reply with exactly: OK"</div></div>
130 |       <div><div class="label">Next check</div><div class="v" id="next">~</div><div class="muted" id="every"></div></div>
131 |     </div>

```

```

132 | <div class="label" style="margin-top:16px">Last checks (oldest → newest)</div>
133 | <div class="dots" id="dots"></div>
134 | </section>
135 |
136 | <section class="card" id="latCard">
137 | <div class="label">Your Vero sessions (CLI and VS Code): response time</div>
138 | <div class="facts">
139 | <div><div class="label">Median, last hour</div><div class="v" id="latP50"></div><div class="muted" id="latN"></div></div>
140 | <div><div class="label">Slowest 5 %, last hour</div><div class="v" id="latP95"></div><div class="muted">p95</div></div>
141 | <div><div class="label">Last 24 h</div><div class="v" id="latDay"></div><div class="muted" id="latDayN"></div></div>
142 | </div>
143 | <div class="label" style="margin-top:14px">Last model requests (oldest → newest), seconds until the model started answering</div>
144 | <div class="bars" id="latBars" role="img" aria-label="Response time of your last Vero model requests"></div>
145 | <div class="muted" id="latNote" style="margin-top:8px"></div>
146 | </section>
147 |
148 | <section class="card settings" id="settings" aria-label="Settings">
149 | <div class="label">Settings</div>
150 | <div class="form">
151 | <label for="sInterval">Check automatically</label>
152 | <select id="sInterval">
153 | <option value="0">Only when I click "Check now"</option>
154 | <option value="5">Every 5 minutes</option>
155 | <option value="15">Every 15 minutes</option>
156 | <option value="30">Every 30 minutes</option>
157 | <option value="60">Every hour</option>
158 | </select>
159 | <div class="hint">Each check asks Vero one tiny question (about 1 minute, 2 small model calls).</div>
160 | <label for="sModel">Model used for the check</label>
161 | <input id="sModel" spellcheck="false" placeholder="empty = Vero's own model">
162 | <div class="hint">A cheap model keeps checks cheap. Leave empty to test the model Vero is set to.</div>
163 | <label for="sTimeout">Give up after (seconds)</label>
164 | <input id="sTimeout" type="number" min="30" max="600" step="10">
165 | <label for="sPath">Vero CLI location</label>
166 | <input id="sPath" spellcheck="false" placeholder="empty = find it automatically">
167 | <div class="hint" id="found"></div>
168 | <label for="sTrack">My own Vero sessions</label>
169 | <label class="check"><input id="sTrack" type="checkbox"> Show the model and response time of Vero CLI / VS Code sessions</label>
170 | <div class="hint">Reads only timestamps and model names from Vero's own task logs. Your prompts and answers are never read.</div>
171 | </div>
172 | <div class="row"><button class="primary" id="saveBtn" type="button">Save</button><span class="msg" id="saveMsg"></span></div>
173 | </section>
174 |
175 | <p class="muted" id="foot"></p>
176 | </div>
177 |
178 | <div class="tip" id="tip"></div>
179 | <div class="overlay" id="stopped"><div><h2>Vero Status is stopped</h2>
180 | <p class="muted">Double-click <b>Vero Status</b> to start it again. You can close this tab.</p></div></div>
181 |
182 | <script>
183 | (function(){
184 | "use strict";
185 | const $ = (id) => document.getElementById(id);
186 | let S = null, timer = null, settingsLoaded = false, offline = false;
187 |
188 | function prettyModel(id){
189 |   if (!id) return null;
190 |   const m = /claude-(opus|sonnet|haiku|fable)-(\d+)?-(\d{1,2})?(?!\\d)/i.exec(id);
191 |   if (m) return "Claude " + m[1][0].toUpperCase() + m[1].slice(1).toLowerCase() + " " + m[2] + (m[3] ? "." + m[3] : "");
192 |   return id.split(/[/:]/).filter(Boolean).slice(-1)[0] || id;
193 | }
194 | function ago(t){ const s = Math.max(0, Math.round(Date.now()/1000 - t));
195 |   if (s < 60) return s + " s ago"; if (s < 3600) return Math.round(s/60) + " min ago";
196 |   if (s < 86400) return Math.round(s/3600) + " h ago"; return Math.round(s/86400) + " d ago"; }
197 | const clock = (t) => new Date(t*1000).toLocaleTimeString(undefined, {hour:"2-digit", minute:"2-digit"});
198 | const day = (t) => new Date(t*1000).toLocaleString(undefined, {month:"short", day:"numeric", hour:"2-digit", minute:"2-digit"});

```

```

199 | function setIcon(color){ $("favicon").href = "data:image/svg+xml," + encodeURIComponent(
200 |   "<svg xmlns='http://www.w3.org/2000/svg' viewBox='0 0 16 16'><circle cx='8' cy='8' r='7' fill='${color}'/></svg>`"); }
201 |
202 | function render(){
203 |   const s = S, last = s.last;
204 |   const ver = s.ver;
205 |   const hero = s.hero;
206 |   let cls = "", title, icon = "?", meta = "", why = "";
207 |   if (s.checking && !last) { title = "Checking Vero..."; meta = "The first check takes about a minute."; }
208 |   else if (!last) { title = "Not checked yet"; meta = 'Click "Check now"'; }
209 |   else {
210 |     cls = last.available ? "ok" : "bad"; icon = last.available ? "✓" : "x";
211 |     title = last.available ? "Vero is available" : "Vero is not available";
212 |     meta = `since ${day(s.since)} · last check ${ago(last.time)}`;
213 |     if (s.checking) meta = "Checking again now... " + meta;
214 |     why = last.reason || "";
215 |   }
216 |   hero.className = "card hero " + cls + (s.checking ? " checking" : "");
217 |   const lamp = s.lamp;
218 |   document.title = (last ? (last.available ? "✓ " : "x ") : "") + "Vero Status";
219 |   setIcon(!last ? "#8a94a3" : last.available ? "#1f7a45" : "#9b1c2e");
220 |
221 |   const c = s.configured || {};
222 |   const cfgName = s.cfgName;
223 |   const cfgId = s.cfgId;
224 |   const cfgSub = s.cfgSub;
225 |   const asked = last && last.asked_model;
226 |   const ansLabel = s.ansLabel;
227 |   const ansName = s.ansName;
228 |   const ansId = s.ansId;
229 |   const ansSub = s.ansSub;
230 |
231 |   const avail = s.avail;
232 |   const availSub = s.availSub;
233 |   const took = s.took;
234 |   const iv = s.settings.interval_minutes;
235 |   const every = s.every;
236 |   tick();
237 |   const dots = s.dots;
238 |   const muted = s.muted;
239 |   const checkBtn = s.checkBtn;
240 |   const found = s.found;
241 |   const foot = s.foot;
242 |   renderSessions(s);
243 |   if (!settingsLoaded) {
244 |     const sTrack = s.sTrack;
245 |     const sInterval = s.sInterval;
246 |     const sTimeout = s.sTimeout;
247 |   }
248 | }
249 | const secs = (v) => v == null ? "-" : (v < 10 ? v.toFixed(1) : Math.round(v)) + " s";
250 | function renderSessions(s){
251 |   const on = s.settings.track_sessions, x = s.sessions;
252 |   const live = s.live;
253 |   if (!on) return;
254 |   if (!x || !x.latency) { const liveWhat = s.liveWhat; return; }
255 |   const cur = x.current, cfg = s.configured || {};
256 |   const model = cur ? cur.model : (x.cli_process ? cfg.model : null);
257 |   const live = s.live;
258 |   const liveWhat = s.liveWhat;
259 |   const cur = s.cur;
260 |   const liveSub = s.liveSub;
261 |   const cur = s.cur;
262 |   const cur = s.cur;
263 |   const liveModel = s.liveModel;
264 |   const div = s.div;

```

```

265 |   const h = x.latency.hour, d = x.latency.day;
266 |   const ("latP50").textContent = secs(h.p50); const ("latP95").textContent = secs(h.p95);
267 |   const ("latN").textContent = h.n ? `${h.n} request${h.n > 1 ? "s" : ""}` : "no requests";
268 |   const ("latDay").textContent = secs(d.p50); const ("latDayN").textContent = d.n ? `median of ${d.n} request${d.n > 1 ? "s" : ""}` : "no requests";
269 |   const rs = x.recent || [], max = Math.max(1, ...rs.map(r => r.s));
270 |   const p50 = h.p50 != null ? h.p50 : d.p50;
271 |   const ("latBars").innerHTML = rs.length ? rs.map((r, i) =>
272 |     `

page 54


```

```
332 | })();  
333 | </script>  
334 | </body>  
335 | </html>  
=== END FILE: vero_status/web/index.html ===
```

```
=== VERIFY SCRIPT: verify_rebuild.py (46 lines) ===
```

```

1 | import hashlib, pathlib, sys
2 | # usage: py verify_rebuild.py C:\Tools\vero-status
3 | root = pathlib.Path(sys.argv[1] if len(sys.argv) > 1 else "vero-status")
4 | CRLF = ['START_HERE.txt', 'scripts/vero.cmd']
5 | FILES = {
6 |     '.gitattributes': 'efa38e63b1747daed572feeff39747d40fd4cfa3a4568b11815cb0bf24332d96',
7 |     '.gitignore': 'b592d17a523d7d8d8bd950419afdeb5f502d4aedd8b65a2887bd71f0c514aa33',
8 |     'CHANGELOG.md': 'c204aa6705f127ab83838a09b86bf53d81f01302f3fa4ecc421a16a5638d7fb3',
9 |     'README.md': 'a8c51af5d383ee16112064a4dd3b7cfa2611f3cbb1dbf2346728a7f59a31958c',
10 |    'START_HERE.txt': 'e3e61140954e96168ca25e366ccb9384c45ef2a66fc04baa2f845eaf2da4ab25',
11 |    'VERO_CONTEXT.md': '4d0096cbb9c0611382b7c7ebbe7f973113cbe9592b4d1613d6fe946a560e5879',
12 |    'Vero Status.pyw': 'd225f8171b6196c264964f66cba8c2992695a171db6c2f047f9c694fb8358197',
13 |    'pyproject.toml': '7c7fb77552e509d6f9a045acc9572b1d58fc39be77641b7f2a1c0d053816d4de',
14 |    'scripts/build_source_pdf.py': 'b9a3be159fd0cc1b45cd61fb7cca9fc3e3bf695782a5094b01f547bd71275e5b',
15 |    'scripts/fake_session.py': '5fa5b85d17b1e8ae07e72460a01f242d7e5223c55eb96f4d6d31fb8087a007a7',
16 |    'scripts/fake_vero.py': '4908eb33e4a64621f955e551ef0efce2e644ca3a6ba51e9c202b80cf01d35ae8',
17 |    'scripts/vero': '45890958a3fcd4e02f1d4c41412869e6f71a9efe2d2d237cd54cf8d84e001fa',
18 |    'scripts/vero.cmd': '15e9a293d205d911b2e2746af1c4361906c0b4138dc11be5acc2a653a6cd0ca',
19 |    'tests/__init__.py': '8d8ab1348161355b2c6856609575f5becac99c397071c7dcdad95d00597f39fb',
20 |    'tests/helpers.py': '1ee6057626c3d29cae5cca50a5a4583151c3c6d109d17927c066263c15523e03',
21 |    'tests/test_monitor_server.py': '746821fbefb1f1169423819dc22cde42ea4ec76fd90691c8c291462e95c19b07',
22 |    'tests/test_sessions.py': '43bdad94e16e14218b6f56db17f214e935b1f8cb2bf1cc66465a3a74badba395',
23 |    'tests/test_settings.py': 'd5c501ab341e42d07021d55e29832d40a0780fa8bac8fae525af14359183b836',
24 |    'tests/test_vero.py': '00f1697582183a59e1b0c852dd3f37bbd6fa8d4a0df42ae1294d3b2cde09a44e',
25 |    'vero_status/__init__.py': '0aaed8f1fa0dec4641e0b02b86f420873f32b599a1887f1d17ad297f0d0d25e7',
26 |    'vero_status/app.py': 'e1149390fa4df886d89d37f0fd6f4be93ca73f383e47b8e6b8196711764641b0',
27 |    'vero_status/monitor.py': '50184a8628ae8d551895cdd6289d783ece06017a85e20ca59b39fee73ffded29',
28 |    'vero_status/server.py': '4fe22178766d0357e85bb164bbcfbac66555c8914a9b8b68b026e2365c3cc851',
29 |    'vero_status/sessions.py': '5d218fb0c05c05def10b3e1b0e4be13ffff6f7e179ceed82930281be810f62fb',
30 |    'vero_status/settings.py': 'd362a34291c878bc40a6a3998a3a19633e9918aa1ac8d4352f0add2618c47d2d',
31 |    'vero_status/vero.py': '47fe1603472d1c5950d5a499de60694a2cad4d4ee016f2cb7f5c1c16cd30b87b',
32 |    'vero_status/web/index.html': '9755757eea237912426b9b46d008fb665514dd1d2fe4f05841ee5c0b33f00b59',
33 | }
34 | bad = 0
35 | for path, sha in FILES.items():
36 |     p = root / path
37 |     if not p.exists():
38 |         print("MISSING", path); bad += 1; continue
39 |     text = p.read_bytes().decode("utf-8").replace("\r\n", "\n")
40 |     if hashlib.sha256(text.encode("utf-8")).hexdigest() != sha:
41 |         print("DIFFERENT", path); bad += 1; continue
42 |     want = text.replace("\n", "\r\n") if path in CRLF else text
43 |     if p.read_bytes() != want.encode("utf-8"):
44 |         p.write_bytes(want.encode("utf-8")); print("fixed line endings", path)
45 |     print("OK: all files match" if not bad else str(bad) + " file(s) wrong: recreate them from the document")
46 | sys.exit(1 if bad else 0)
=== END VERIFY SCRIPT ===

```