

# Chapter 12: FAIR and Reproducible Reporting of Molecular Docking Studies

Elvis Martis

## 1 Introduction

Concerns about the reproducibility of findings in computational science have attracted increasing attention in recent years. In many instances, reliance on proprietary software or datasets not available in the public domain limits independent researchers’ ability to critically evaluate the reliability of the underlying methodologies and, consequently, the validity of the reported results. The recent criticism surrounding the publication of the AlphaFold3[1] study in Nature has further reinforced the need for policies that promote transparency and open access to both data and computational methods. Such practices would enable independent validation of findings and expand the scientific impact of the work beyond the scope originally envisioned by the authors[2]. Despite the widespread use of molecular docking, many published studies still lack sufficient detail to allow another group to reproduce the simulations, let alone to systematically extend or challenge the results. This situation undermines trust in computational results and slows the progress of science in general and the computational field in particular. It also contributes to a broader *reproducibility crisis* documented across many areas of computational science[3–6].

The FAIR (*F*indable *A*ccessible *I*nteroperable *R*eusable) Guiding Principles for scientific data management and stewardship were formulated in 2016 to provide high-level, domain-independent guidance for how digital research objects, such as data, metadata, software, and workflows should be published and maintained[7–9]. Although FAIR was not written specifically for molecular modelling, its concepts map onto the needs of the computational community[10, 11]. At the same time, efforts have begun to compile practical tips and checklists for performing and reporting meaningful, reproducible

molecular docking and simulations[2, 6, 12].

## 2 The FAIR Guiding Principles

The FAIR Guiding Principles were introduced by Wilkinson *et al.* in 2016 as a concise, technology-agnostic set of recommendations for improving the management and stewardship of digital research objects[7]. Rather than prescribing specific file formats or repositories, FAIR focuses on properties that datasets, metadata, and related digital objects should contain so that both humans and machines can discover, access, integrate, and reuse them efficiently[7, 8]. Although FAIR was initially motivated by data management challenges in life sciences, it was formulated to be domain-independent and to apply to a broad collection of scholarly work, including software, workflows, vocabularies, and training materials[7, 8, 10]. Subsequent work has refined how community standards and metadata templates can adopt FAIR in specific disciplines[11, 13]. FAIR is often conflated with open data; however, they are distinct. FAIR describes how digital objects should be structured and documented; it does not mandate that access must be completely unrestricted. Sensitive or proprietary data can still be FAIR, provided that access conditions are clearly and persistently described[8, 9].

### 2.1 Findable

For an object to be reusable, it must first be *Findable*. This principle emphasises globally unique and persistent identifiers, such as DOIs, richly described metadata, and indexing in searchable resources[7, 8, 10]. For computational chemistry, these ideas translate into the following practices:

- Assign persistent identifiers, for example, DOIs from Zenodo[14] or institutional repositories, to curated datasets, input decks, workflows, and software releases.
- Provide descriptive metadata that includes, at minimum, the scientific context, such as the targets, ligands, and chemical series. For methods, include software, versions, key parameters, and citations to relevant publications.
- Register datasets and software in catalogues such as re3data or FAIR-sharing where appropriate, to improve global visibility.

In docking, findability also involves clear linking between the publication, the primary data, e.g., ligand libraries, receptor structures, and the computational workflows used to generate the scores and poses[2, 6].

## 2.2 Accessible

Accessibility in FAIR refers to the use of open, standardised communication protocols and to the idea that, even if data themselves cannot be openly released, the metadata describing them should remain accessible[8, 9]. From a computational chemistry perspective:

- Data and code should be retrievable via standard web protocols, for example, HTTPS, ideally through stable repository landing pages.
- Access conditions, such as open, embargoed, restricted via data use agreements, must be explicitly described in the metadata.
- Even for proprietary input structures or licensed software, one should provide enough information for users to request access or to reproduce the calculation within their own licensed environment[6, 8, 9].

Repositories such as Zenodo[14], Figshare[15], Dryad[16], OSF[17], and institutional data infrastructures[18–20] provide persistent identifiers and managed access controls that help satisfy the Accessible principle.

## 2.3 Interoperable

Interoperability focuses on meaningful data integration and exchange, both between datasets and with analysis tools. It depends on the use of community standards for file formats, vocabularies, and metadata schemas[7, 8, 21]. In docking and MD simulations:

- Where possible, use established, non-proprietary formats, for example, PDB or mmCIF for macromolecules, SDF or SMILES for ligands, widely used trajectory formats, alongside any software-specific representations.
- Describe key scientific concepts using community vocabularies, for example, standard residue and atom naming, ontology terms for organisms, diseases, or assay types.

- When depositing data, provide machine-readable metadata that follows community standards or templates, such as domain-specific checklists or MIXS-like schemas adapted for computational chemistry.

Interoperability is critical if one wants to screen docking datasets across targets, benchmark different docking engines, or integrate scores with experimental bioactivity databases such as ChEMBL or BindingDB.

## 2.4 Reusable

The ultimate aim of FAIR is to maximise the potential for reuse of digital objects, whether by the original authors or by others[7–9]. Reusability requires rich documentation and explicit licensing conditions. For docking studies, this means:

- Providing details such as: where the structures came from (PDB IDs, homology models), how they were processed (protonation states, missing loops, cofactors, water treatment), and how ligands were curated (sources, filters, stereochemistry, tautomers).
- Using standard, machine-readable licences, for example, Creative Commons or Open Data Commons for data; OSI-approved licences for code, so that the reuse conditions are unambiguous.
- Sharing complete input files and configuration parameters for docking runs and subsequent analyses, not just final summary tables or figures.

# 3 FAIR reporting for molecular docking workflows

## 3.1 Overview of a docking workflow

A typical structure-based virtual screening workflow consists of: (i) defining and preparing the biological target(s), (ii) assembling and curating a ligand library, (iii) configuring and running the docking engine, (iv) post-processing and analysing the results, and often (v) validating the docking protocol against known ligands or experimental data[2, 6]. At each stage,

there are choices that can affect the outcome: alternate receptor conformations and protonation states, grid definition and search parameters, ligand protonation and tautomeric states, scoring functions, and ranking criteria. Without full disclosure of these choices, it is impossible to assess whether a reported enrichment curve or pose prediction is robust or an artefact of arbitrary settings. The community guidelines for docking emphasise careful validation against reference ligands and experimental binding data, and stress that all input files, preparation steps, and docking parameters should be shared to comply with FAIR recommendations[2–4]. Journals and funders increasingly expect such practices; however, adoption remains inconsistent.

### 3.2 Reporting the biological target

A FAIR-compliant description of the target in a docking study should include:

- The biological identity of the target: species, isoform, and any relevant post-translational modifications.
- The source of the 3D structure: PDB ID(s), resolution, experimental technique, or the homology modelling protocol used if no experimental structure was available.
- Details of structure preparation: protonation state model and pH, treatment of missing loops or side chains, inclusion or exclusion of cofactors, metals, and crystallographic waters; any mutation or truncation introduced for computational convenience.
- Definition of the binding site: how the docking box or search region was defined (for example, around a co-crystallised ligand, by pocket detection, or by functional hypotheses), including numerical coordinates and box dimensions.

These details are directly analogous to system description items in MD reproducibility checklists, which ask authors to report all transformations applied to experimental structures before simulation[12].

### 3.3 Reporting ligand libraries and chemical space

On the ligand side, FAIR reporting requires transparency about the composition and processing of the chemical library:

- Library details: vendor catalogues, in-house collections, public datasets such as ZINC or ChEMBL, or enumerated virtual libraries.
- Curation steps: removal of inorganic species and counterions, standardisation of valences and charges, removal of duplicates, rule-based or machine-learning based filters, for example, Lipinski, PAINS, and toxicophores.
- Representation and enumeration: how protonation states, tautomers, stereoisomers, and conformers were generated, including pH models, enumeration rules, and any pruning heuristics.
- File formats and identifiers: use of standard identifiers, like InChI, or SMILES, alongside internal IDs to facilitate cross-database linking and reuse.

Without this information, others cannot know what chemical space was actually sampled, nor can they reuse the library in further studies. Depositing the curated library in an open repository, with clear licensing, makes the work substantially more reusable[18–20].

### 3.4 Reporting software, versions, and computational environment

Computational reproducibility often fails because critical details about software versions, compilation details, and runtime environments are missing or incompletely described[3, 4]. For docking studies, authors should, at least, report:

- The docking engine and wrapper tools used, for example, AutoDock Vina, GNINA, Glide, including the exact version number or commit hash.
- Any custom patches or forks, with links to public version-controlled repositories where possible.
- The operating system and hardware architecture (CPU and GPU models, number of cores), especially if these influence performance or stochastic behaviour.

- Random seeds and parallelisation settings, so that non-deterministic aspects of the search can be reproduced or statistically characterised.

Using containers, such as Docker or Singularity, or virtual machines, and making these images available via repositories can dramatically simplify reproducibility by capturing the full software stack[3, 4].

### 3.5 Reporting docking parameters and protocol

FAIR reporting of the docking protocol itself includes:

- The definition of the search space, such as grid spacing, box size and centre, or equivalent concepts in other engines.
- The scoring function and any re-scoring or consensus scoring steps.
- Search parameters: exhaustiveness, number of runs or poses per ligand, maximum evaluations or iterations, treatment of receptor and ligand flexibility, constraints or pharmacophore terms.
- Post-processing criteria: how poses were filtered, for example, clash removal, interaction patterns, how scores from multiple conformations or protonation states were combined, and what thresholds defined *hits*.
- Validation steps: redocking of co-crystallised ligands with RMSD thresholds, enrichment metrics on reference actives and decoys, or correlation with experimental binding data.

Reporting only top-ranked poses and scores without this context is insufficient. Community guidelines for docking now explicitly recommend that all input files and full parameter sets be shared to comply with FAIR expectations[2].

## 4 Repositories and open sharing of computational data

### 4.1 Generalist data repositories

In the last decade, a robust ecosystem of generalist data repositories has emerged, many of which support FAIR-aligned data publication at no or low

cost. Examples include Zenodo(**Figure 1**), Figshare(**Figure 2**), Dryad, the Open Science Framework (OSF)(**Figure 3**), Mendeley Data, Harvard Dataverse, Vivli, and institutional platforms operated by universities or consortia[18–20].

These services typically provide:

- Persistent identifiers, such as DOIs, for datasets and software releases, satisfying a core requirement of Findability.
- Rich metadata forms supporting descriptive fields, licensing choices, author identifiers (ORCID), and links to related publications and funding information.
- Versioning and immutable records: once published, a dataset is preserved, while newer versions can be linked as updates.
- Access control options ranging from fully open to restricted or embargoed access, enabling compliance with ethical or contractual constraints while remaining FAIR.




Figure 1: A screenshot of zenodo’s page




Figure 2: A screenshot of figshare's page




Figure 3: A screenshot of OSF's page

Comparison charts from library and society initiatives can help researchers select a repository based on factors such as size limits, curation services, and costs[19, 22]. Several funding agencies explicitly recommend or mandate depositing data and code in repositories registered in catalogues like re3data or FAIRsharing[21, 23].

## 4.2 Discipline-specific and institutional infrastructures

In addition to generalist repositories, several disciplinary and institutional infrastructures support FAIR-aligned data sharing. FAIRsharing and re3data curate registries of domain-specific repositories, for example, for structural biology, genomics, neuroimaging, and track which repositories are endorsed by journals and funders[21, 23]. For structural data, the Protein Data Bank (PDB) already provides standard deposition channels for experimental structures; docking studies should always reference these canonical entries rather than distributing modified coordinates with inconsistent or incomplete details. Some institutions operate their own repositories that issue DOIs and integrate with local research information systems. These may be particularly convenient for large MD trajectories or sensitive datasets that require controlled access while remaining FAIR[20, 21]. When institutional repositories are used, authors should still ensure that metadata are rich, open licences are selected where possible, and links to associated code repositories and generalist archives are provided.

## 4.3 Packaging a docking project for deposition

To maximise reusability and minimise barriers for reviewers and future users, we recommend organising a docking project for deposition along the following lines:

- A top-level **README** in plain text or Markdown that provides a narrative overview of the study: scientific questions, methods, and guidelines for reproducing the main results.
- Subdirectories for (i) receptor structures (**receptors/**), (ii) ligand libraries (**ligands/**), (iii) docking configuration files and scripts (**configs/** and **scripts/**), (iv) raw docking outputs (**results/raw/**), and (v) processed analysis tables and figures (**results/processed/**).
- A machine-readable environment specification, for example, a **conda** environment file, a **Dockerfile**, or a container image reference, that captures software dependencies.
- Clear licensing files specifying permissions for data and code reuse, for example, **LICENSE** for software and an explicit Creative Commons or CC0 statement for data.

Once organised, this directory tree can be archived and uploaded to a generalist repository such as Zenodo, or OSF, which in turn will assign a DOI and allow the dataset to be cited alongside the associated article[18–20].

#### 4.4 Code repositories and archival integration

For code underlying docking workflows, for example, custom preprocessing scripts, wrappers, or analysis notebooks, the best practice is to use distributed version control, for example, Git, and host the repository on platforms such as GitHub, GitLab, or Bitbucket[24–26]. These platforms provide transparent version histories, issue tracking, and collaboration features.

To align with FAIR, one should:

- Tag a release corresponding to the version of the code used in a published study.
- Archive that releases in a data repository that mints a DOI, for example, Zenodo–GitHub integration, so that the exact code snapshot can be cited and preserved.
- Include a CITATION file that instructs users how to acknowledge the software in publications.

This combination of public version control and archival DOIs has been recommended as a cornerstone of reproducible computational research[3, 5, 24].

## 5 Checklists for reproducible molecular docking

Recent work has proposed detailed checklists for reporting MD simulations and related computational methods, covering system preparation, force fields, integrators, sampling strategies, and analysis procedures[12]. These checklists are intended both as author guidelines and as tools for reviewers and editors to assess whether submissions provide enough detail to enable reproduction. A similar philosophy can be applied to molecular docking. Rather

than relying on terse method descriptions or references to software manuals, authors should explicitly confirm that they have reported each class of information necessary to re-run and extend their calculations[2].

## **5.1 A practical checklist for docking studies**

Building on published recommendations for docking[2] and general computational reproducibility, one can formulate the following checklist.

### **5.1.1 Scientific context**

- Clear statement of the biological question or design objective.
- Justification for selecting the specific targets and ligands.

### **5.1.2 Targets**

- Target identity, isoform, organism.
- Structural source, such as PDB ID, homology model, and experimental details.
- Structure preparation steps, including protonation, missing regions, co-factors, and water treatment.
- Binding site definition and numerical parameters for docking boxes or equivalent constructs.

### **5.1.3 Ligands**

- Library sources and curation pipeline.
- Enumeration of protonation states, tautomers, stereochemistry, and conformers.
- Representation formats, for example, SDF, SMILES, and identifiers.

#### **5.1.4 Software and environment**

- Names, versions, and origin of all key software components, such as dockers, preparation tools, and analysis scripts.
- Description of any custom code and its public repository.
- Operating system and hardware features relevant to performance or stochastic behaviour.
- Availability of container images or environment specifications.

#### **5.1.5 Docking protocol**

- Search space and grid parameters.
- Scoring functions and re-scoring steps.
- Search parameters, such as exhaustiveness, runs, and time limits.
- Treatment of flexibility and constraints.
- Criteria for ranking, hit selection, and post-processing.

#### **5.1.6 Validation and controls**

- Redocking results for co-crystallised ligands, with RMSD thresholds and statistics.
- Retrospective enrichment metrics on actives and decoys where possible.
- Cross-validation or sensitivity analyses, for example, alternate receptor conformations, parameter variations.

#### **5.1.7 Data and code availability**

- Persistent identifiers (DOIs) for datasets and code snapshots.
- Licences for data and code, and any access restrictions.
- Instructions in the README for reproducing key figures and tables from the raw data.

Authors and reviewers can use such a checklist as a concrete interpretation of FAIR principles for docking and related computational chemistry workflows[2, 6, 12].

## 6 Open versus closed source software and data

### 6.1 Open-source software

Open-source scientific software, that is, programs released under licences that grant users the rights to run, study, modify, and redistribute the code, has had a transformative impact on many areas of computational research[25–27]. Surveys of widely cited bioinformatics tools such as BLAST[28] and ClustalW[29] show that open availability of code is often correlated with high scientific impact, in part because others can build upon and validate the methods.

From a reproducibility perspective, open-source software offers several advantages:

- Transparency: reviewers and readers can, in principle, inspect the implementation and verify that it matches the description in the paper.
- Auditability: bugs or numerical issues can be identified and corrected by the community, and patches can be shared.
- Sustainability: when code is publicly version-controlled, it is easier to maintain, fork, and adapt beyond the lifetime or funding horizon of a single group.
- Equity: researchers in institutions or countries with limited resources are not excluded by licence fees.

These benefits align closely with FAIR expectations that software artefacts should be well documented, accessible, and reusable[5, 8, 26]. AutoDock Vina is a good example: it is one of the most widely used, open-source docking engines, distributed under a permissive Apache licence, with active development on public GitHub and extensive integration in graphical interfaces and pipelines[30, 31]. Its open status has facilitated community-driven benchmarking, method extensions, and incorporation into automated virtual screening workflows.

## 6.2 Closed-source and proprietary tools

Closed-source or proprietary software, including many commercial docking suites, can deliver sophisticated functionality, optimised performance, and professional support. However, reliance on such tools introduces several challenges for reproducibility and broader progress in open science[5, 6].

- Opaque implementations: without source access, it is often impossible to ascertain how exactly a scoring function or search heuristic is implemented, or whether it has changed between versions.
- Licence barriers: other researchers, including reviewers, may lack the funds or institutional agreements needed to run the software, undermining the practical reproducibility of published work.
- Longevity risks: if a vendor discontinues a product or changes its licensing terms, reproducing older studies can become difficult or impossible.
- Constraints on reuse: restrictive licences may prevent the community from developing and sharing extensions or automated workflows that build on proprietary binaries.

These issues do not mean that high-quality work cannot be done with proprietary tools; however, they do place a greater burden on authors to document their protocols in detail and to provide as many FAIR-compliant details as possible, such as input files and containerised environments that at least encapsulate the exact version used[6, 32].

## 6.3 Open data versus controlled access

A related debate concerns open data versus controlled-access data. FAIR does not equate to complete openness: it explicitly accommodates scenarios where data must be restricted for privacy, security, or intellectual property reasons, provided that the constraints are clearly described[8, 9]. In computational chemistry, restrictions may arise from proprietary compound libraries, confidential target information, or ongoing industrial collaborations. In such cases, authors can still improve reproducibility by:

- Sharing synthetic or down-sampled datasets that capture key statistical properties of the full data.

- Providing detailed metadata and protocol descriptions, including how qualified researchers might request access to the full data under appropriate agreements.
- Sharing all non-sensitive details openly, for example, code, container images, generic workflows, so that barriers apply only where absolutely necessary.

A useful concept here is *open verifiable reproducibility*, where the computational workflow and environment are open, however, the sensitive input data are accessed via controlled channels that nonetheless allow independent verification by authorized parties[32].

## 6.4 Towards a balanced ecosystem

The question is not whether all software and data must be open, but how to design an ecosystem in which openness and FAIR practices are the default, and proprietary components are used judiciously and transparently. Policy surveys of scientific computing journals show a growing recognition that data and software are primary research outputs and that reproducibility policies must explicitly address them[6, 33].

Concrete steps include:

- Journals requiring that, when proprietary software is used, authors disclose version details and provide maximal FAIR details such as input files, scripts, and containers.
- Funders supporting the development and maintenance of open-source scientific software and community standards as infrastructure, not as afterthoughts.
- Professional societies and training programmes emphasising FAIR and open practices as core competencies for computational chemists.

## 7 Summary

For molecular docking and related computational chemistry approaches to attain a level of credibility comparable to that of well-established experimental assays, their results must be reported in a manner that allows independent researchers to reproduce, evaluate, and extend the work. The

FAIR Guiding Principles provide a widely recognised framework for organising such transparency. However, their value depends on their translation into concrete, domain-specific practices that can be routinely adopted within computational chemistry. In practical terms, this involves careful documentation of biological targets, ligand libraries, software versions, computational environments, and docking protocols. Equally important is the systematic organisation of workflows and datasets in structured repositories that include persistent identifiers and clearly defined licenses. When feasible, the use of open-source software and openly accessible data further strengthens the transparency and longevity of computational studies. Adopting these practices requires additional effort and gradual adjustments to community standards. Nevertheless, the benefit is a more cumulative and reliable scientific enterprise. In such a framework, docking results are no longer opaque numerical outputs in a table, but reproducible digital experiments whose methods, data, and assumptions are accessible for verification and further development.

## References

- [1] . Alphafold3 - why did nature publish it without its code? *Nature*, 629 (8013):728, 2024.
- [2] Elvis AF Martis and Stéphane Téletchéa. Ten quick tips to perform meaningful and reproducible molecular docking calculations. *PLOS Computational Biology*, 21(5):e1013030, 2025.
- [3] Stephen R Piccolo and Michael B Frampton. Tools and techniques for computational reproducibility. *Gigascience*, 5(1):s13742–016, 2016.
- [4] Brett K Beaulieu-Jones and Casey S Greene. Reproducibility of computational workflows is automated using continuous analysis. *Nature biotechnology*, 35(4):342–346, 2017.
- [5] Lorena A Barba. Defining the role of open source software in research reproducibility. *Computer*, 55(8):40–48, 2022.
- [6] Jaqueline J Brito, Jun Li, Jason H Moore, Casey S Greene, Nicole A Nogoy, Lana X Garmire, and Serghei Mangul. Recommendations to

- enhance rigor and reproducibility in biomedical research. *GigaScience*, 9(6):giaa056, 2020.
- [7] Mark D Wilkinson, Michel Dumontier, IJsbrand Jan Aalbersberg, Gabrielle Appleton, Myles Axton, Arie Baak, Niklas Blomberg, Jan-Willem Boiten, Luiz Bonino da Silva Santos, Philip E Bourne, et al. The fair guiding principles for scientific data management and stewardship. *Scientific data*, 3(1):1–9, 2016.
  - [8] GO FAIR Initiative. Fair principles. <https://www.go-fair.org/fair-principles/>, 2022. Accessed: 2026-03-14.
  - [9] National Network of Libraries of Medicine. Fair principles. <https://www.nlm.gov/guides/data-thesaurus/fair-principles>, 2024. Accessed: 2026-03-14.
  - [10] Becky Arnold, Louise Bowler, Sarah Gibson, Patricia Herterich, Rosie Higman, Anna Krystalli, Alexander Morley, Martin O’Reilly, Kirstie Whitaker, et al. The turing way: a handbook for reproducible data science. *Zenodo*, 2019.
  - [11] Esther Thea Inau, Jean Sack, Dagmar Waltemath, and Atinkut Alamirrew Zeleke. Initiatives, concepts, and implementation practices of fair (findable, accessible, interoperable, and reusable) data principles in health data stewardship practice: protocol for a scoping review. *JMIR research protocols*, 10(2):e22505, 2021.
  - [12] Thereza A Soares, Zoe Cournia, Kevin Naidoo, Rommie Amaro, Habibah Wahab, and Kenneth M Merz Jr. Guidelines for reporting molecular dynamics simulations in jcim publications. *Journal of Chemical Information and Modeling*, 63(11):3227–3229, 2023.
  - [13] Mark A Musen, Martin J O’Connor, Erik Schultes, Marcos Martínez-Romero, Josef Hardi, and John Graybeal. Modeling community standards for metadata as templates makes data fair. *Scientific Data*, 9(1):696, 2022.
  - [14] Miguel-Angel Sicilia, Elena García-Barriocanal, and Salvador Sánchez-Alonso. Community curation in open dataset repositories: insights from zenodo. *Procedia Computer Science*, 106:54–60, 2017.

- [15] Mike Thelwall and Kayvan Kousha. Figshare: a universal repository for academic resource sharing? *Online Information Review*, 40(3):333–346, 2016.
- [16] Gary W Miller. Making data accessible: The dryad experience, 2016.
- [17] Erin D Foster and Ariel Deardorff. Open science framework (osf). *Journal of the Medical Library Association: JMLA*, 105(2):203, 2017.
- [18] University of Texas Libraries. Generalist repositories – research data services. <https://guides.lib.utexas.edu/research-data-services/generalist-repositories>, 2026. Accessed: 2026-03-14.
- [19] American Geophysical Union. Generalist repository comparison chart. [https://www.agu.org/-/media/files/publications/generalist-repository-comparison-chart\\_version\\_3](https://www.agu.org/-/media/files/publications/generalist-repository-comparison-chart_version_3), 2023. Accessed: 2026-03-14.
- [20] Swiss National Science Foundation. Open research data: Which data repositories can be used? <https://www.snf.ch/en/WtezJ6qxuTRnSYgF/topic/open-research-data-which-data-repositories-can-be-used>, 2026. Accessed: 2026-03-14.
- [21] Peter McQuilton, Dominique Batista, Oya Beyan, Ramon Granell, Simon Coles, Massimiliano Izzo, Allyson L Lister, Robert Pergl, Philippe Rocca-Serra, Ben Schaap, et al. Helping the consumers and producers of standards, repositories and policies to enable fair data. *Data Intelligence*, 2(1-2):151–157, 2020.
- [22] UMass Chan Medical School: Lamar Scoutter Library. Research data management resources. [https://libraryguides.umassmed.edu/research\\_data\\_management\\_resources/open\\_public\\_data](https://libraryguides.umassmed.edu/research_data_management_resources/open_public_data), 2025. Accessed: 2026-03-14.
- [23] Max Delbrück Center for Molecular Medicine. Collection of requirements from publishers for storing data in repositories. <https://www.mdc-berlin.de/content/collection-requirements-publishers-storing-data-repositories>, 2022. Accessed: 2026-03-14.

- [24] Karthik Ram. Git can facilitate greater reproducibility and increased transparency in science. *Source code for biology and medicine*, 8(1):7, 2013.
- [25] Andreas Prlić and James B Procter. Ten simple rules for the open development of scientific software. *PLoS computational biology*, 8(12): e1002802, 2012.
- [26] Haley Hunter-Zinck, Alexandre Fioravante De Siqueira, Váleri N Vásquez, Richard Barnes, and Ciera C Martinez. Ten simple rules on writing clean and reliable open-source scientific software, 2021.
- [27] Laura Fortunato and Mark Galassi. The case for free and open source software in research and scholarship. *Philosophical Transactions of the Royal Society A*, 379(2197):20200079, 2021.
- [28] Thomas Madden. The blast sequence analysis tool. *The NCBI handbook*, 2(5):425–436, 2013.
- [29] Julie D Thompson, Toby J Gibson, and Des G Higgins. Multiple sequence alignment using clustalw and clustalx. *Current protocols in bioinformatics*, 00(1):2–3, 2003.
- [30] Oleg Trott and Arthur J Olson. Autodock vina: improving the speed and accuracy of docking with a new scoring function, efficient optimization, and multithreading. *Journal of computational chemistry*, 31(2):455–461, 2010.
- [31] The Scripps Research Institute. Autodock vina github repository. <https://github.com/ccsb-scripps/AutoDock-Vina>, 2025. Accessed: 2026-03-14.
- [32] Arnim Bleier. What is computational reproducibility? (gesis guides to digital behavioral data, 2). [https://www.gesis.org/fileadmin/admin/Dateikatalog/pdf/guides/02\\_Bleier\\_computational\\_reproducibility.pdf](https://www.gesis.org/fileadmin/admin/Dateikatalog/pdf/guides/02_Bleier_computational_reproducibility.pdf), 2025. Accessed: 2026-03-14.
- [33] Jose Armando Hernandez and Miguel Colom. Reproducible research policies and software/data management in scientific computing journals: a survey, discussion, and perspectives. *Frontiers in Computer Science*, 6:1491823, 2025.