

Diameter : Ø 200 mm — min Nominal Speed: 0.20 m/sn. — max Nominal Speed: 1.60 m/sn.
Diameter : Ø 250 mm — min Nominal Speed: 0.30 m/sn. — max Nominal Speed: 2.00 m/sn.
Diameter : Ø 300 mm — min Nominal Speed: 0.50 m/sn. — max Nominal Speed: 2.50 m/sn.

TECHNICAL SPECIFICATIONS				
DIAMETER	: Ø200 mm ☐	Ø250 mm ☐	Ø300 mm ☐	
TYPE	: (–) Without coil ☐	UZ UZ (Remote Control – MRL) ☐	A3 (UCM) A3 Compatible ☐	A3 + UZ A3 Compatible + Remote Control ☐
VOLTAGE	: 24 V.DC. ☐	110 V.DC. ☐	190 V.DC. ☐	220 V.AC. ☐
DIRECTION	: Downward ▼ One-way ☐	Bidirectional ▼▲ Both directions ☐		
ROPE DIAMETER	: 6 mm ☐	8 mm ☐	10 mm ☐	12 mm ☐
CERTIFICATE	: CE (EN81-20/50) ☐	GOST-R ☐	Other ☐	
NOMINAL SPEED	: 10 _____ m/sn.			
QUANTITY	: 25 _____ piece(s)			
DELIVERY DATE	: jj/mm/aaaa _____			

CUSTOMER INFORMATION	
COMPANY NAME	ABNDO
CONTACT PERSON	
EMAIL ADDRESS	
PHONE / WHATSAPP	
ADDRESS	
COUNTRY / CITY	
NOTES / REMARKS	

_____	_____	_____
Date	Authorized Signature / Company Stamp	Received by (FAS LIFT)