REGIÓN 1. LOS ALTOS
FASE 2
MODELO yy

```
COMPUTE tianle = 0 .
EXECUTE .
DO IF (animtrab=1 & animcons=1 & tierra=1 & lengua).
RECODE
 tianle  (0=1)  .
END IF .
EXECUTE .

COMPUTE indisp = 0 .
EXECUTE .
DO IF (agua = 1 & luz = 1 & piso=1 & bao=1) .
RECODE
 indisp  (0=1)  .
END IF .
EXECUTE .

COMPUTE patron = 1 .
EXECUTE .
DO IF (p25=4) .
RECODE
 patron  (1=0)  .
END IF .
EXECUTE .

COMPUTE YYDEPEN=-18*DEPEN.
COMPUTE YYNINOS=-14*NINOS.
COMPUTE YYNOASI=-17*NOASI15.
COMPUTE YYTRAB15=-27*TRAB15.

IF ( HH1 = 1) YYHACINA=100.
IF ( HH2 = 1) YYHACINA=45.
IF ( HH3 = 1) YYHACINA=36.
IF ( HH4 = 1) YYHACINA=34.
IF ( HH5 = 1) YYHACINA=33.
IF ( HH6 = 1 ) YYHACINA=35.

IF ( ESCJ1 = 1) YYESC= 53.
IF ( ESCJ2 = 1) YYESC= 54.
IF ( ESCJ3 = 1) YYESC= 57.
IF ( ESCJ4 = 1) YYESC= 100.

IF (OCUPJ0 = 1) YYOCUP= 58.
IF (OCUPJ1 = 1) YYOCUP= 60.
IF (OCUPJ2 = 1) YYOCUP= 72.
IF (OCUPJ3_4 = 1) YYOCUP = 100.
IF (OCUPJ5_9 = 1) YYOCUP = 75.

IF (DISCAP = 0) YYDISCAP= 100.
IF (DISCAP = 1) YYDISCAP= 72.

IF (PISO = 0) YYPISO= 100.
IF (PISO = 1) YYPISO= 71.

IF (EJ1 =1) YYEJ= 60.
IF (EJ2 =1) YYEJ= 66.
IF (EJ3 =1) YYEJ= 78.
IF (EJ4 =1) YYEJ= 92.
IF (EJ5 =1) YYEJ= 100.
IF (EJ6 =1) YYEJ= 85.

IF (RADIO =0) YYRADIO = 100.
IF (RADIO =1) YYRADIO =86.

IF (TV=0) YYTV= 100.
IF (TV=1) YYTV= 68.

IF (VEHI=0) YYVEHI= 100.
```

```
IF (VEHI=1) YYVEHI= 0.

IF (REFRI=0) YYREFRI= 100.
IF (REFRI=1) YYREFRI= 0.

IF (ANIMALES=0) YYANIM= 100.
IF (ANIMALES=1) YYANIM= 0.

IF (TIERRA=0) YYTIERRA= 100.
IF (TIERRA=1) YYTIERRA= 0.

IF (LAVA=0) YYLAVA= 100.
IF (LAVA=1) YYLAVA= 0.

IF (LICUA=0) YYLICUA= 100.
IF (LICUA=1) YYLICUA= 0.

IF (PATRON=0) YYPATRON= 100.
IF (PATRON=1) YYPATRON= 0.

IF (INDISP=0) YYINDISP= 0.
IF (INDISP=1) YYINDISP= -100.

IF (TIANLE=0) YYTIANLE= 0.
IF (TIANLE=1) YYTIANLE=-100.

FREQUENCIES
  VARIABLES= yydepen yyninos yynoasi yytrab15 yyhacina yyesc yyocup yydiscap yypiso yyej
             yyradio yylicua  yytv  yyvehi yyrefri yyanim yytierra yylava yypatron yyindisp yyanitie
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

MEANS
  TABLES=agua bao depen discap ej1 ej2 ej3 ej4 ej5 ej6 escj1 escj2 escj3
  escj4 estgas hh1 hh2 hh3 hh4 hh5 hh6 ingmen15 ingmes ingmesh ingmigm
  ingmigr inmh15pc lava licua luz mu15a49 ninos noasi15 ocupj0 ocupj1 ocupj2
  ocupj3_4 ocupj5_9 piso radio refri tierra totpers trab15 tv vehi vhs  BY
  pobre
  /CELLS MEAN STDDEV COUNT
  /FORMAT= LABELS .

COMPUTE input = 0 .
EXECUTE .
DO IF (MISSING(yydepen) | MISSING(yyninos) | MISSING(yynoasi) | MISSING(yytrab15)
  | MISSING(yyhacina) | MISSING(yyesc)  | MISSING(yyocup) | MISSING(yydiscap) | MISSING(yypiso)
  | MISSING(yyej) | MISSING(yyradio) | MISSING(yylicua) | MISSING(yytv) | MISSING(yyagua)
  | MISSING(yyvehi) | MISSING(yyrefri)| MISSING(yyanim)| MISSING(yytierra)| MISSING(yylava)
  | MISSING(yypatron)| MISSING(yyindisp) | MISSING(yytianle)) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .

RECODE yydepen  (SYSMIS=-39.565)  .
RECODE yyninos  (SYSMIS=-28.882)  .
RECODE yynoasi  (SYSMIS=-3.299)  .
RECODE yytrab15  (SYSMIS=-7.276)  .
RECODE yyhacina  (SYSMIS=40.958)  .
RECODE yyesc  (SYSMIS=56.349)  .
RECODE yyocup  (SYSMIS=85.935)  .
RECODE yydiscap  (SYSMIS=99.371)  .
RECODE yypiso  (SYSMIS=75.862)  .
RECODE yyej  (SYSMIS=82.505)  .
RECODE yyradio  (SYSMIS=93.902)  .
RECODE yylicua  (SYSMIS=6.781) .
RECODE yytv  (SYSMIS=75.371)  .
RECODE yyvehi  (SYSMIS=3.411)  .
RECODE yyrefri  (SYSMIS=2.308)  .
RECODE yyanim  (SYSMIS=8.385)  .
RECODE yytierra  (SYSMIS=2.142)  .
RECODE yylava  (SYSMIS=.2694)  .
RECODE yypatron  (SYSMIS=.388)  .
```

```
RECODE yytianle (SYSMIS=-10.552) .
RECODE yyindisp  (SYSMIS=-16.739) .

COMPUTE yycalif = yydepen + yyninos + yynoasi + yytrab15 + yyhacina +  yyesc + yyocup +
                  yydiscap + yypiso + yyej + yyradio +  yytv.
EXECUTE .

DISCRIMINANT
  /GROUPS=lpnva(0 1)
  /VARIABLES=yycalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  EQUAL
  /STATISTICS=TABLE
  /CLASSIFY=NONMISSING POOLED .

COMPUTE yypobre = 0 .
EXECUTE .
DO IF (yycalif < 558.1) .
RECODE
  yypobre  (0=1)  .
END IF .
EXECUTE .

***FILTRO

COMPUTE yycalif = yycalif + yyvehi + yyrefri + yytianle + yyindisp + yylava .
EXECUTE .

IF (DIS_1=0 & DIS_2=0 & POBRE=0) SECUENCE=1.
IF (DIS_1=0 & DIS_2=0 & POBRE=1) SECUENCE=2.
IF (DIS_1=0 & DIS_2=1 & POBRE=0) SECUENCE=3.
IF (DIS_1=1 & DIS_2=0 & POBRE=0) SECUENCE=4.
IF (DIS_1=0 & DIS_2=1 & POBRE=1) SECUENCE=5.
IF (DIS_1=1 & DIS_2=0 & POBRE=1) SECUENCE=6.
IF (DIS_1=1 & DIS_2=1 & POBRE=0) SECUENCE=7.
IF (DIS_1=1 & DIS_2=1 & POBRE=1) SECUENCE=8.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=0) SECUENCE=9.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=1) SECUENCE=10.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=0) SECUENCE=11.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=1) SECUENCE=12.

FREQUENCIES
  VARIABLES=secuence  .

IF (vehi=0 & yypobre=1) yypobre=9.
RECODE yypobre (9=0).
```

REGIÓN 1. LOS ALTOS
FASE 2
MODELO aa

```
DISCRIMINANT
 /GROUPS=lpnva(0 1)
 /VARIABLES=DEPEN NINOS NOASI1 TRAB151 HACINA ESC OCUPJ_1 P08
            PISO_1 AGUABA_1 DISCAP RADIO TV ESTGAS VEHI
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS =.42 .58
 /STATISTICS=RAW TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN=-22*DEPEN.
COMPUTE AANINOS=-19*NINOS .
COMPUTE AANA15=-44*NOASI1.
COMPUTE AAT15=-62*TRAB151 .
COMPUTE AAHACINA=-10*HACINA .
COMPUTE AAESC=6*ESC .
COMPUTE AAOCUP=31*OCUPJ_1 .
COMPUTE AAEDAD=1*P08 .
COMPUTE AAPISO=12*PISO_1 .
COMPUTE AAAB=8*AGUABA_1 .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 68 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=91 .

IF (TV=0) AATV = 100.
IF (TV=1) AATV =74 .

IF (ESTGAS=0) AAESTGAS=100 .
IF (ESTGAS=1) AAESTGAS=52 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=52 .

FREQUENCIES
 VARIABLES= AADEPEN AANINOS AANA15 AAT15 AAHACINA AAESC AAOCUP AAEDAD
            AAPISO AAAB AADISCAP AARADIO AATV AAESTGAS AAVEHI
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANA15) | MISSING(AAT15) | MISSING(AAHACINA)
      | MISSING(AAESC) | MISSING(AAOCUP) | MISSING(AAEDAD) | MISSING(AAPISO) | MISSING(AAAB)
      | MISSING(AADISCAP) | MISSING(AARADIO) | MISSING(AATV) | MISSING(AAESTGAS) | MISSING(AAVEHI) ) .
RECODE
 input (0=1) .
END IF .
EXECUTE .

RECODE AADEPEN (SYSMIS=-48.35) .
RECODE AANINOS (SYSMIS=-39.19) .
RECODE AANA15 (SYSMIS=-3.31).
RECODE AAT15 (SYSMIS=-7.99).
RECODE AAHACINA (SYSMIS=-42.27).
RECODE AAESC (SYSMIS=16.06).
RECODE AAOCUP (SYSMIS=-.15).
RECODE AAEDAD (SYSMIS=40.84).
RECODE AAPISO (SYSMIS=.14).
RECODE AAAB (SYSMIS=.09) .
RECODE AADISCAP (SYSMIS=99.28).
RECODE AARADIO (SYSMIS=96.08) .
RECODE AATV (SYSMIS=79.89).
RECODE AAESTGAS (SYSMIS=54.9) .
RECODE AAVEHI (SYSMIS=53.63) .
```

```
COMPUTE aacalif = AADEPEN + AANINOS + AANA15 + AAT15 + AAHACINA + AAESC + AAOCUP +  AAEDAD +
                  AAPISO +  AAAB + AADISCAP + AARADIO + AATV    +  AAESTGAS + AAVEHI .
EXECUTE .

DISCRIMINANT
  /GROUPS=LPNVA(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_5 = 0).
VARIABLE LABEL filter_$ 'dis_5 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_5 = 1).
VARIABLE LABEL filter_$ 'dis_5 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((TOTPERS<=4  & P08<=24) | (TOTPERS<=2  & P08>=65)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .
EXECUTE .

COMPUTE AACALIF1 = AACALIF + viejitos .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 367.5) .
RECODE
aapobre (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
   VARIABLES=AAPOBRE.

IF (vehi = 0) aapobre= 0  .
EXECUTE .

COMPUTE nvopob = aapobre .
EXECUTE .

F (yypobre = 1) nvopob= 0  .
XECUTE .
```

REGIÓN 1. LOS ALTOS
FASE 6
MODELO aa

```
)ISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=DEPEN NINOS NOASI1 TRAB151 HACINA ESC OCUPJ_1 ej PISO_1
            AGUABA_1 DISCAP RADIO TV ESTGAS VEHI
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS =.42 .58
 /STATISTICS=RAW TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN=-22*DEPEN.
COMPUTE AANINOS=-19*NINOS .
COMPUTE AANA15=-44*NOASI1.
COMPUTE AAT15=-62*TRAB151 .
COMPUTE AAHACINA=-10*HACINA .
COMPUTE AAESC=6*ESC .
COMPUTE AAOCUP=31*OCUPJ_1 .
COMPUTE AAEDAD=1*ej .
COMPUTE AAPISO=12*PISO_1 .
COMPUTE AAAB=8*AGUABA_1 .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 68 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=91 .

if (TV=0) AATV = 100.
IF (TV=1) AATV =74 .

 (ESTGAS=0) AAESTGAS=100 .
iF (ESTGAS=1) AAESTGAS=52 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=52 .

FREQUENCIES
 VARIABLES= AADEPEN AANINOS AANA15 AAT15 AAHACINA AAESC AAOCUP AAEDAD AAPISO
            AAAB AADISCAP AARADIO AATV AAESTGAS AAVEHI
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANA15) | MISSING(AAT15)
     | MISSING(AAHACINA) | MISSING(AAESC) | MISSING(AAOCUP) | missing(AAEDAD)
     | MISSING(AAPISO) | MISSING(AAAB) | MISSING(AADISCAP) | MISSING(AARADIO) | MISSING(AATV)
     | MISSING(AAESTGAS) | MISSING(AAVEHI) ) .
RECODE
 input (0=1) .
END IF .
EXECUTE .

RECODE AADEPEN (SYSMIS=-71.11) .
RECODE AANINOS (SYSMIS=-40.49) .
RECODE AANA15 (SYSMIS=-8.8).
RECODE AAT15 (SYSMIS=-6.95).
RECODE AAHACINA (SYSMIS=-43.05).
RECODE AAESC (SYSMIS=16.32).
RECODE AAOCUP (SYSMIS=-4.12).
?ECODE AAEDAD (SYSMIS=41.98).
 :CODE AAPISO (SYSMIS=-7.13).
RECODE AAAB (SYSMIS=0.78) .
RECODE AADISCAP (SYSMIS=98.34).
RECODE AARADIO (SYSMIS=94.72) .
RECODE AATV (SYSMIS=80.68).
RECODE AAESTGAS (SYSMIS=55.42) .
```

```
RECODE  AAVEHI (SYSMIS=52.94) .

COMPUTE AAcalif = AADEPEN + AANINOS + AANA15 + AAT15 + AAHACINA + AAESC + AAOCUP +  AAEDAD +
                  AAPISO +  AAAB + AADISCAP + AARADIO + AATV + AAESTGAS + AAVEHI .
EXECUTE .

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

 REQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((TOT_PER<=4  & ej<=24) | (TOT_PER<=2  & ej >= 65)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .
EXECUTE .

COMPUTE AACALIF1=AACALIF + viejitos .
EXECUTE .

IF (agua1=1  & luz=1  & piso= 1) AACALIF1=AACALIF1-100 .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (AAcalif1< 367.5) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

IF (vehi = 0) aapobre= 0  .
EXECUTE .

FREQUENCIES
   VARIABLES=LP98 aapobre  .
```

REGIÓN 1. LOS ALTOS
FASE 6
MODELO bb

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=DEPEN NINOS NOASI1 TRAB151 HACINA ESC OCUPJ_1 ej PISO_1
            AGUABA_1 DISCAP RADIO TV ESTGAS VEHI
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS =.41 .59
 /STATISTICS=RAW TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE bbDEPEN=-7*DEPEN.
COMPUTE bbNINOS=-32*NINOS .
COMPUTE bbNA15=-50*NOASI1.
COMPUTE bbT15=-55*TRAB151 .
COMPUTE bbHACINA=-4*HACINA .
COMPUTE bbESC=9*ESC .
COMPUTE bbOCUP=-7*OCUPJ_1 .
COMPUTE bbEDAD=2*ej .
COMPUTE bbPISO=6*PISO_1 .
COMPUTE bbAB=-22*AGUABA_1 .

IF (DISCAP =0) bbDISCAP = 100.
IF (DISCAP =1) bbDISCAP = 68 .

IF (RADIO=0) bbRADIO=100 .
IF (RADIO=1) bbRADIO=111 .

IF (TV=0) bbTV = 100.
IF (TV=1) bbTV =90 .

F (ESTGAS=0) bbESTGAS=100 .
IF (ESTGAS=1) bbESTGAS=53 .

IF (VEHI=0) bbVEHI=100 .
IF (VEHI=1) bbVEHI=41 .

FREQUENCIES
 VARIABLES= bbDEPEN bbNINOS bbNA15 bbT15 bbHACINA bbESC bbOCUP bbEDAD bbPISO
            bbAB bbDISCAP bbRADIO bbTV bbESTGAS bbVEHI
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(bbDEPEN) | MISSING(bbNINOS) | MISSING(bbNA15) | MISSING(bbT15) | MISSING(bbHACINA)
      | MISSING(bbESC) | MISSING(bbOCUP) | missing(bbEDAD) | MISSING(bbPISO) | MISSING(bbAB)
      | MISSING(bbDISCAP) | MISSING(bbRADIO) | MISSING(bbTV) | MISSING(bbESTGAS) | MISSING(bbVEHI) ) .
RECODE
 input (0=1) .
END IF .
EXECUTE .

RECODE bbDEPEN (SYSMIS=-18.8745) .
RECODE bbNINOS (SYSMIS=-57.6375) .
RECODE bbNA15 (SYSMIS=-9.0678).
RECODE bbT15 (SYSMIS=-7.2385).
RECODE bbHACINA (SYSMIS=-14.9622).
RECODE bbESC (SYSMIS=23.8488).
RECODE bbOCUP (SYSMIS=-0.0766).
RECODE bbEDAD (SYSMIS=81.5631).
RECODE bbPISO (SYSMIS=0.09166).
 ECODE bbAB (SYSMIS=-0.4397) .
RECODE bbDISCAP (SYSMIS=98.9782).
RECODE bbRADIO (SYSMIS=105.8434) .
RECODE bbTV (SYSMIS=93.2684).
RECODE bbESTGAS (SYSMIS=58.9549) .
RECODE bbVEHI (SYSMIS=43.0122) .
```

```
COMPUTE bbcalif = bbDEPEN + bbNINOS + bbNA15 + bbT15 + bbHACINA + bbESC + bbOCUP +  bbEDAD +
                  bbPISO +  bbAB + bbDISCAP + bbRADIO + bbTV +  bbESTGAS + bbVEHI .
EXECUTE .

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=bbcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .41 .59
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((EJ<= 24 & tot_per <= 4) | (EJ >= 65 & tot_per <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE bbCALIF1=bbCALIF  + viejitos .
EXECUTE .

IF (agua1=1  & luz=1  & piso= 1) bbCALIF1=bbCALIF1-100 .
EXECUTE .

COMPUTE bbpobre = 0 .
EXECUTE .
DO IF (bbcalif1< 473.975) .
RECODE
bbpobre  (0=1)  .
END IF .
EXECUTE .

IF (vehi = 0) bbpobre= 0  .
EXECUTE .

COMPUTE nvo_pob = bbpobre .
EXECUTE .

  O IF (aapobre = 1) .
RECODE
  nvo_pob  (1=0)  .
END IF .
EXECUTE .
```

```
FREQUENCIES
  VARIABLES=LP98 BBpobre .
```

REGIÓN 1. LOS ALTOS
FASE 8
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=DEPEN NINOS NOASI1 TRAB151 HACINA ESC OCUPJ_1 ej  PISO_1
              AGUABA_1 DISCAP RADIO TV ESTGAS VEHI
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS =.42 .58
  /STATISTICS=RAW TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-22*DEPEN.
COMPUTE AANINOS=-19*NINOS .
COMPUTE AANA15=-44*NOASI1.
COMPUTE AAT15=-62*TRAB151 .
COMPUTE AAHACINA=-10*HACINA .
COMPUTE AAESC=6*ESC .
COMPUTE AAOCUP=31*OCUPJ_1 .
COMPUTE AAEDAD=1*ej .
COMPUTE AAPISO=12*PISO_1 .
COMPUTE AAAB=8*AGUABA_1 .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 68 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=91 .

if (TV=0) AATV = 100.
IF (TV=1) AATV =74  .

IF (ESTGAS=0) AAESTGAS=100 .
IF (ESTGAS=1) AAESTGAS=52 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=52 .

FREQUENCIES
  VARIABLES= AADEPEN AANINOS AANA15 AAT15 AAHACINA AAESC AAOCUP AAEDAD
              AAPISO AAAB AADISCAP AARADIO AATV AAESTGAS AAVEHI
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANA15)
        | MISSING(AAT15) | MISSING(AAHACINA)  | MISSING(AAESC)
        | MISSING(AAOCUP) | MISSING(AAEDAD) | MISSING(AAPISO)
        | MISSING(AAAB) | MISSING(AADISCAP) | MISSING(AARADIO)
        | MISSING(AATV) | MISSING(AAESTGAS) | MISSING(AAVEHI) ) .

RECODE
  input  (0=1)  .
END IF .
EXECUTE .

RECODE  AADEPEN (SYSMIS= -59.3200) .
RECODE  AANINOS (SYSMIS=-34.2223) .
 ECODE  AANA15 (SYSMIS= -7.9796).
RECODE  AAT15 (SYSMIS= -8.1597).
RECODE  AAHACINA (SYSMIS= -37.4056).
RECODE  AAESC (SYSMIS= 15.8992).
RECODE  AAOCUP (SYSMIS= 2.8024).
RECODE  AAEDAD (SYSMIS= 40.6896).
```

```
RECODE  AAPISO (SYSMIS=4.6744).
RECODE  AAAB (SYSMIS=4.0749) .
RECODE  AADISCAP (SYSMIS=98.9782).
RECODE  AARADIO (SYSMIS= 95.2191) .
RECODE  AATV (SYSMIS=82.4975).
 ECODE  AAESTGAS (SYSMIS=58.0813) .
RECODE  AAVEHI (SYSMIS= 53.6297) .
EXECUTE.

COMPUTE aacalif = AADEPEN + AANINOS + AANA15 + AAT15 + AAHACINA + AAESC + AAOCUP + AAEDAD
                  + AAPISO +  AAAB + AADISCAP + AARADIO + AATV +  AAESTGAS + AAVEHI .
EXECUTE .

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=AAcalif
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE  CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=AAcalif  /FORMAT=NOTABLE
 /STATISTICS=MINIMUM .

USE ALL.
 OMPUTE filter_$=(dis_1 = 1).
ARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=AAcalif  /FORMAT=NOTABLE
 /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((TOT_PER<=4  & ej<=24) | (TOT_PER<=2  & ej >= 65)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .
EXECUTE .

COMPUTE aaCALIF1=aaCALIF + viejitos .
EXECUTE .

IF (agua1=1  & luz=1  & piso= 1) aaCALIF1=aaCALIF1-100 .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 344) .
RECODE
aapobre  (0=1)  .
ND IF .
 ECUTE .

IF (vehi = 0) aapobre= 0  .
IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
```

```
RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .
IF (ELIMIN = 1) zzPOBRE = 0 .
EXECUTE .

FREQUENCIES
  VARIABLES = aapobre LP98.
```

REGIÓN 2. SIERRA
FASE 2
MODELO yy

```
)ISCRIMINANT
/GROUPS=lpnva(0 1)
/VARIABLES= depen ninos  trab15 noasi15 hh2 hh3 hh4 hh5 hh6 escj1 escj2 escj3
                ocupj1 ocupj2 ocupj3_4 ocupj5_9 ej2 ej3 ej4 ej5 ej6 licua tv estgas discap
/ANALYSIS ALL
/save=class
/PRIORS  EQUAL
/STATISTICS= raw TABLE
/CLASSIFY=NONMISSING POOLED  .

COMPUTE animales = 1 .
EXECUTE .
DO IF ((p721 >=  15 & p721 <  99) | (p722 >=  15 & p722 <  99) | (p723 >=  15 & p723 <  99)|
(p731 >=  20 & p731 <  99) | (p732 >=  15 & p732 <  99) | (p733 >=  25 & p733 <  99) | (p734 >=  15 & p734 <  99) |
(p735 >=  25 & p735 <  99) ) .

RECODE
  animales  (1=0)  .
END IF .
EXECUTE .

COMPUTE enseres = 0 .
EXECUTE .
DO IF (lava = 1 & refri = 1 & vehi = 1  & licua = 1 & bao = 1  & agua = 1 & luz = 1 & tv = 1  & animales = 1) .
RECODE
  enseres  (0=1)  .
END IF .
EXECUTE .

COMPUTE patron = 1 .
EXECUTE .
DO IF (p25=4) .
RECODE
  patron  (1=0)  .
END IF .
EXECUTE .

compute indisp = 0 .
execute.
do if (luz + agua + piso =3) .
recode
     indisp (0=1).
end if.
execute.

compute anitie = 0 .
execute .
do if (animtrab + animcons + tierra=3) .
recode anitie (0=1).
end if .
execute .

COMPUTE YYDEPEN=-26*DEPEN.
COMPUTE YYNINOS=-13*NINOS.
COMPUTE YYNOASI=-13*NOASI15.
COMPUTE YYTRAB15=-32*TRAB15.

IF ( HH1 = 1) YYHACINA=100.
IF ( HH2 = 1) YYHACINA=40.
IF ( HH3 = 1) YYHACINA=32.
IF ( HH4 = 1) YYHACINA=30.
IF ( HH5 = 1) YYHACINA=28.
IF ( HH6 = 1 ) YYHACINA=25.

IF ( ESCJ1 = 1) YYESC= 55.
IF ( ESCJ2 = 1) YYESC= 58.
```

```
IF ( ESCJ3 = 1) YYESC= 63.
IF ( ESCJ4 = 1) YYESC= 100.

IF (OCUPJ0 = 1) YYOCUP= 40.
IF (OCUPJ1 = 1) YYOCUP= 44.
   (OCUPJ2 = 1) YYOCUP= 90.
IF (OCUPJ3_4 = 1) YYOCUP = 100.
IF (OCUPJ5_9 = 1) YYOCUP = 34.

IF (DISCAP = 0) YYDISCAP= 100.
IF (DISCAP = 1) YYDISCAP= 80.

IF (EJ1 =1) YYEJ= 50.
IF (EJ2 =1) YYEJ= 58.
IF (EJ3 =1) YYEJ= 72.
IF (EJ4 =1) YYEJ= 87.
IF (EJ5 =1) YYEJ= 100.
IF (EJ6 =1) YYEJ= 86.

IF (estgas =0) YYestgas = 100.
IF (estgas =1) YYestgas = 74.

IF (licua =0) YYlicua = 100.
IF (licua =1) YYlicua = 66.

if (VEHI=0) YYVEHI= 100.
IF (VEHI=1) YYVEHI= 0.

IF (tv=0) YYtv= 100.
IF (tv=1) YYtv= 77.

IF (ANIMALES=0) YYANIM= 100.
IF (ANIMALES=1) YYANIM= 0.

IF (LAVA=0) YYLAVA= 100.
   (LAVA=1) YYLAVA= 0.

IF (PATRON=0) YYPATRON= 100.
IF (PATRON=1) YYPATRON= 0.

IF (ENSERES=0) YYENSER= 0.
IF (ENSERES=1) YYENSER= -100.

if (indisp=0) yyindisp = 0 .
if (indisp=1) yyindisp = -100 .

if (anitie=0) yyanitie=0 .
if (anitie=1) yyanitie=-100 .

if (refri=0) yyrefri=100 .
if (refri=1) yyrefri=0 .

if (radio=0) yyradio=0 .
if (radio=1) yyradio=-100 .

FREQUENCIES
  VARIABLES= yydepen yyninos yynoasi yytrab15 yyhacina yyesc yyocup yydiscap yyej yyestgas
             yylicua yyvehi yytv yyanim  yylava yypatron yyindisp yyenser yyanitie yyrefri yyradio
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF (MISSING(yydepen) | MISSING(yyninos) | MISSING(yynoasi) | MISSING(yytrab15) | MISSING(yyhacina)
       | MISSING(yyesc)  | MISSING(yyocup) | MISSING(yydiscap) | MISSING(yyej) | MISSING(yyestgas) | MISSING(yyrefri)
       | MISSING(yyanitie) | MISSING(yyradio) | MISSING(yylicua) | MISSING(yyvehi) | MISSING(yytv) | MISSING(yyindisp)) .
   CODE
  input  (0=1)  .
END IF .
EXECUTE .

RECODE yydepen  (SYSMIS=-68.616)  .
```

```
RECODE yyninos  (SYSMIS=-31.452) .
RECODE yynoasi  (SYSMIS=-4.317) .
RECODE yytrab15  (SYSMIS=-10.332) .
RECODE yyhacina  (SYSMIS=32.233) .
RECODE yyesc  (SYSMIS=60.967) .
 ECODE yyocup  (SYSMIS=43.842) .
RECODE yydiscap  (SYSMIS=99.011) .
RECODE yyej  (SYSMIS=82.360) .
RECODE yyestgas  (SYSMIS=77.596) .
RECODE yylicua  (SYSMIS=74.229) .
RECODE yyvehi  (SYSMIS=3.021) .
RECODE yytv  (SYSMIS=83.173) .
RECODE yyanim  (SYSMIS=15.891) .
RECODE yyindisp (sysmis=-17.783).
RECODE yypatron  (SYSMIS=.242) .
RECODE yyenser  (SYSMIS=-16.455) .
RECODE yyanitie (sysmis=-25.229) .
RECODE yyrefri (sysmis= 7.538) .
RECODE yyradio (sysmis=).

COMPUTE yycalif = yydepen + yyninos + yynoasi + yytrab15 + yyhacina +
          yyesc + yyocup + yydiscap + yyej + yyestgas + yylicua + yytv .
EXECUTE .

DISCRIMINANT
  /GROUPS=lpnva(0 1)
  /VARIABLES=yycalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  EQUAL
  /STATISTICS=raw TABLE
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
  RIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
ALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=yycalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=yycalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE yycalif = yycalif + yyvehi + yyindisp + yyanitie + yyrefri + yylava .
EXECUTE .

COMPUTE pobre = 0 .
EXECUTE .
    IF (yycalif < 465.4) .
 ECODE
  pobre  (0=1)  .
END IF .
EXECUTE .
```

```
MEANS
  TABLES=lpnva agua bao depen discap ej1 ej2 ej3 ej4 ej5 ej6 escj1 escj2 escj3
  escj4 estgas hh1 hh2 hh3 hh4 hh5 hh6 ingmen15 ingmes ingmesh ingmigm
  ingmigr inmh15pc lava licua luz  ninos noasi15 ocupj0 ocupj1 ocupj2
  ocupj3_4 ocupj5_9 piso radio refri tierra totpers trab15 tv vehi p65_10 indisp BY
  pobre
  /CELLS MEAN STDDEV COUNT
  /FORMAT= LABELS .

IF (DIS_1=0 & DIS_2=0 & POBRE=0) SECUENCE=1.
IF (DIS_1=0 & DIS_2=0 & POBRE=1) SECUENCE=2.
IF (DIS_1=0 & DIS_2=1 & POBRE=0) SECUENCE=3.
IF (DIS_1=1 & DIS_2=0 & POBRE=0) SECUENCE=4.
IF (DIS_1=0 & DIS_2=1 & POBRE=1) SECUENCE=5.
IF (DIS_1=1 & DIS_2=0 & POBRE=1) SECUENCE=6.
IF (DIS_1=1 & DIS_2=1 & POBRE=0) SECUENCE=7.
IF (DIS_1=1 & DIS_2=1 & POBRE=1) SECUENCE=8.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=0) SECUENCE=9.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=1) SECUENCE=10.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=0) SECUENCE=11.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=1) SECUENCE=12.

FREQUENCIES
    VARIABLES= agua bao  discap ej1 ej2 ej3 ej4 ej5 ej6 escj1 escj2 escj3
               escj4 estgas hh1 hh2 hh3 hh4 hh5 hh6
               lava licua luz  ninos noasi15 ocupj0 ocupj1 ocupj2
               ocupj3_4 ocupj5_9 piso radio refri tierra totpers trab15 tv vehi p65_10 indisp discap lpnva .

FREQUENCIES
  VARIABLES=secuence  pobre  lpnva dis_1 dis_2.

if (yypobre=1 & VEHI=0) yyPOBRE=9.
recode yypobre (9=0).
```

REGIÓN 2. SIERRA
FASE 2
MODELO zz

```
SORT CASES BY
  inmh15pc (A) .

COMPUTE LNIN15PC = LN(INMH15PC+1).
EXECUTE.

IF (LNIN15PC >= 0 & LNIN15PC <= .425) VENT_ING = 1.
IF (LNIN15PC > .414 & LNIN15PC <= .851) VENT_ING = 2.
IF (LNIN15PC > .827 & LNIN15PC <= 1.276) VENT_ING = 3.
IF (LNIN15PC > 1.241 & LNIN15PC <= 1.702) VENT_ING = 4.
IF (LNIN15PC > 1.654 & LNIN15PC <= 2.127) VENT_ING = 5.
IF (LNIN15PC > 2.068 & LNIN15PC <= 2.553) VENT_ING = 6.
IF (LNIN15PC > 2.481 & LNIN15PC <= 2.9785) VENT_ING = 7.
IF (LNIN15PC > 2.895 & LNIN15PC <= 3.404) VENT_ING = 8.
IF (LNIN15PC > 3.308 & LNIN15PC <= 3.829) VENT_ING = 9.
IF (LNIN15PC > 3.722 & LNIN15PC <= 4.255) VENT_ING = 10.
IF (LNIN15PC > 4.135 & LNIN15PC <= 4.68) VENT_ING = 11.
IF (LNIN15PC > 4.549 & LNIN15PC <= 5.106) VENT_ING = 12.
IF (LNIN15PC > 4.962 & LNIN15PC <= 5.531) VENT_ING = 13.
IF (LNIN15PC > 5.376 & LNIN15PC <= 5.957) VENT_ING = 14.
IF (LNIN15PC > 5.789 & LNIN15PC <= 6.382) VENT_ING = 15.
IF (LNIN15PC > 6.203 & LNIN15PC <= 6.808) VENT_ING = 16.
IF (LNIN15PC > 6.616 & LNIN15PC <= 7.233) VENT_ING = 17.
IF (LNIN15PC > 7.030 & LNIN15PC <= 7.659) VENT_ING = 18.
IF (LNIN15PC > 7.443 & LNIN15PC <= 8.084) VENT_ING = 19.
IF (LNIN15PC > 8.51) VENT_ING = 20.
EXECUTE.

IF (PISO1 = 1) PISO_1 = -0.69 .
IF (PISO1 = 2) PISO_1 = 1.47 .
IF (PISO1 = 3) PISO_1 = 0.76 .

IF (PARED1 = 1) PARED_1 = 2.53 .
IF (PARED1 = 2) PARED_1 = -1.68 .
IF (PARED1 = 3) PARED_1 = 1.32 .
IF (PARED1 = 4) PARED_1 = -1.12 .
IF (PARED1 = 5) PARED_1 = 0.47 .
IF (PARED1 = 6) PARED_1 = 0.06 .
IF (PARED1 = 7) PARED_1 = -1.98 .
IF (PARED1 = 8) PARED_1 = 0.29 .
IF (PARED1 = 9) PARED_1 = -2.37 .
IF (PARED1 = 10) PARED_1 = 2.56 .
IF (PARED1 = 11) PARED_1 = 0.07 .
IF (PARED1 = 12) PARED_1 = -2.77 .
IF (PARED1 = 13) PARED_1 = -2.48 .
IF (PARED1 = 14) PARED_1 = 1.57 .

IF (AGUABA1 = 1) AGUABA_1 = 0.68 .
IF (AGUABA1= 2) AGUABA_1 = -3.21 .
IF (AGUABA1 = 3) AGUABA_1 = 0.85 .
IF (AGUABA1 = 4) AGUABA_1 = -0.47 .
IF (AGUABA1 = 5) AGUABA_1 = -2.09 .
IF (AGUABA1 = 6) AGUABA_1 = .85 .
IF (AGUABA1 = 7) AGUABA_1 = -2.24.
IF (AGUABA1 = 8) AGUABA_1 = 4.08 .

IF (OCUPJ = 0) OCUPJ_1 = -0.42 .
IF (OCUPJ = 1) OCUPJ_1 =  1.47.
IF (OCUPJ = 2) OCUPJ_1 = 1.92 .
IF (OCUPJ = 3) OCUPJ_1 = .067 .
IF (OCUPJ = 4) OCUPJ_1 = 1.3 .
IF (OCUPJ = 5) OCUPJ_1 = -1.33 .
IF (OCUPJ = 6) OCUPJ_1 = 0.71 .
IF (OCUPJ = 7) OCUPJ_1 = 1.91 .
IF (OCUPJ = 8) OCUPJ_1 = 0.004 .
IF (OCUPJ = 9) OCUPJ_1 = -2.03 .
```

```
EXECUTE.

DISCRIMINANT
  /GROUPS=lpnva(0 1)
  /VARIABLES=depen ninos noasi1 trab151 hacina esc ocupj_1  discap estgas p08 tv licua hectie1
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS=.42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

COMPUTE animales = 1 .
EXECUTE .
DO IF ((p721 >=  15 & p721 <  99) | (p722 >=  15 & p722 <  99) | (p723 >=  15 & p723 <  99)|
(p731 >=  20 & p731 <  99) | (p732 >=  15 & p732 <  99) | (p733 >=  25 & p733 <  99) | (p734 >=  15 & p734 <  99) |
(p735 >=  25 & p735 <  99) ) .
RECODE
  animales  (1=0)  .
END IF .
EXECUTE .

COMPUTE enseres = 0 .
EXECUTE .
DO IF (lava = 1 & refri = 1 & vehi = 1  & licua = 1 & bao = 1  & agua = 1 & luz = 1 & tv = 1 & animales = 1) .
RECODE
  enseres  (0=1)  .
END IF .
EXECUTE .

COMPUTE patron = 1 .
EXECUTE .
DO IF (p25=4) .
RECODE
  patron  (1=0)  .
 ND IF .
XECUTE .

compute indisp = 0 .
execute.
do if (luz + agua + piso =3) .
recode
     indisp (0=1).
end if.
execute.

compute anitie = 0 .
execute .
do if (animtrab + animcons + tierra=3) .
recode anitie (0=1).
end if .
execute .

compute VIEJITOS = 0 .
execute.
do if ((P08<25 & TOTPERS<5) | (P08>65 & TOTPERS <3)) .
recode
     VIEJITOS (0=1).
end if.
execute.

COMPUTE ZZDEPEN=-26*DEPEN.
COMPUTE ZZNINOS=-18*NINOS.
COMPUTE ZZNOASI=-6*NOASI15.
COMPUTE ZZTRAB15=-9*TRAB15.
COMPUTE ZZHACINA=-6*HACINA.
 OMPUTE ZZESC=6*ESC.
OMPUTE ZZOCUP=30*OCUPJ_1.
COMPUTE ZZP08=.4*P08.
COMPUTE ZZHECTIE=2*HECTIE1.

IF (DISCAP =0) ZZDISCAP = 100.
```

```
IF (DISCAP =1) ZZDISCAP = 94.

IF (estgas =0) ZZestgas = 100.
IF (estgas =1) ZZestgas = 74.

IF (licua =0) ZZlicua = 100.
IF (licua =1) ZZlicua = 68.

IF (tv=0) ZZtv= 100.
IF (tv=1) ZZtv= 77.

if (VEHI=0) ZZVEHI= 100.
IF (VEHI=1) ZZVEHI= 0.

IF (LAVA=0) ZZLAVA= 100.
IF (LAVA=1) ZZLAVA= 0.

if (indisp=0) ZZindisp = 0 .
if (indisp=1) ZZindisp = -100 .

if (anitie=0) ZZanitie=0 .
if (anitie=1) ZZanitie=-100 .

if (refri=0) ZZrefri=100 .
if (refri=1) ZZrefri=0 .

if (viejitos=0) ZZVIEJ = 0 .
if (viejitos=1) ZZVIEJ = -100 .
execute.

FREQUENCIES
  VARIABLES= ZZdepen ZZninos ZZnoasi ZZtrab15 ZZhacina ZZesc ZZocup ZZdiscap
   ZZP08 ZZestgas ZZlicua ZZVEHI ZZLAVA ZZINDISP ZZANITIE ZZREFRI ZZTV ZZHECTIE ZZVIEJ
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

RECODE ZZdepen  (SYSMIS=-68.616) .
RECODE ZZninos  (SYSMIS=-43.549) .
RECODE ZZnoasi  (SYSMIS=-1.992) .
RECODE ZZtrab15  (SYSMIS=-2.906) .
RECODE ZZhacina  (SYSMIS=-28.975) .
RECODE ZZesc  (SYSMIS=20.159) .
RECODE ZZocup  (SYSMIS=-1.45) .
RECODE ZZdiscap  (SYSMIS=99.703) .
RECODE ZZP08  (SYSMIS=17.84) .
RECODE ZZestgas  (SYSMIS=77.595) .
RECODE ZZlicua  (SYSMIS=75.7448) .
RECODE ZZvehi  (SYSMIS=3.02) .
RECODE ZZTV  (SYSMIS=83.1729) .
RECODE ZZLAVA  (SYSMIS=.3946) .
RECODE ZZindisp (sysmis=-17.783).
RECODE ZZanitie (sysmis=-25.229) .
RECODE ZZrefri (sysmis= 7.538) .
RECODE ZZHECTIE (sysmis= 6.39) .
RECODE ZZVIEJ(SYSMIS=-17.78)

COMPUTE ZZcalif = ZZdepen + ZZninos + ZZnoasi + ZZtrab15 + ZZhacina +
  ZZesc + ZZocup + ZZdiscap + ZZP08 + ZZestgas + ZZlicua + ZZtv + ZZHECTIE.
EXECUTE .

DISCRIMINANT
  /GROUPS=lpnva(0 1)
  /VARIABLES=ZZcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  = .42 .58
  /STATISTICS=raw TABLE
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_5 = 0).
VARIABLE LABEL filter_$ 'dis_5 = 0 (FILTER)'.
```

```
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

 REQUENCIES
 VARIABLES=ZZcalif  /FORMAT=NOTABLE
 /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_5 = 1).
VARIABLE LABEL filter_$ 'dis_5 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=ZZcalif  /FORMAT=NOTABLE
 /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE ZZcalif = ZZcalif + ZZvehi + ZZindisp + ZZrefri + ZZLAVA + ZZVIEJ.
EXECUTE .

COMPUTE zzpobre = 0 .
EXECUTE .
DO IF (ZZcalif < 291.5) .
RECODE
 zzpobre  (0=1)  .
END IF .
EXECUTE .

 (zzpobre=1 & VEHI=0) zzPOBRE=9.
recode zzpobre (9=0).
```

REGIÓN 2. SIERRA
FASE 6
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos noasi1 trab151 hacina esc ocupj_1  discap
   estgas ej  tv licua hectie1
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS=.42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN=-26*DEPEN.
COMPUTE AANINOS=-18*NINOS.
COMPUTE AANOASI=-6*NOASI15.
COMPUTE AATRAB15=-9*TRAB15.
COMPUTE AAHACINA=-6*HACINA.
COMPUTE AAESC=6*ESC.
COMPUTE AAOCUPJ=30*OCUPJ_1.
COMPUTE AAEDAD=.4*EJ.
COMPUTE AAHECTIE=2*HECTIE1.

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 94.

IF (estgas =0) AAestgas = 100.
IF (estgas =1) AAestgas = 74.

IF (licua =0) AAlicua = 100.
IF (licua =1) AAlicua = 68.

 F (tv=0) AAtv= 100.
IF (tv=1) AAtv= 77.

EXECUTE .

FREQUENCIES
  VARIABLES= aadepen aaninos aanoasi aatrab15 aahacina aaesc aaocupj aaedad aahectie aadiscap aaestgas aalicua aatv
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aanoasi) | MISSING(aatrab15) | MISSING(aahacina)
       | MISSING(aaesc) | MISSING(aaocupj) | MISSING(aaedad) | MISSING(aahectie) | MISSING(aadiscap)
       | MISSING(aaestgas) | MISSING(aalicua) | MISSING (aatv)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aadepen  (SYSMIS = -55.6389)  .
RECODE aaninos  (SYSMIS = -32.3077)  .
RECODE aanoasi  (SYSMIS = -2.3590)  .
RECODE aatrab15  (SYSMIS = -1.3077)  .
RECODE aahacina  (SYSMIS = -24.7045)  .
RECODE aaesc  (SYSMIS = 15.8462)  .
RECODE aaocupj  (SYSMIS = 13.6560)  .
RECODE aaedad  (SYSMIS = 16.0187)  .
RECODE aahectie  (SYSMIS =1.6923)  .
RECODE aadiscap  (SYSMIS = 99.2564)  .
RECODE aaestgas  (SYSMIS = 74.4502)  .
  ECODE aalicua  (SYSMIS = 70.4935)  .
RECODE aatv  (SYSMIS = 78.3000)  .

EXECUTE .

COMPUTE aacalif = aadepen + aaninos + aanoasi + aatrab15 + aahacina + aaesc + aaocupj + aaedad + aahectie
```

```
          + aadiscap + aaestgas + aalicua + aatv .

EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
   /ARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((EJ < 25 & TOTPER < 5) | (EJ > 65 & EJ < 98 & TOTPER < 3)) VIEJITOS = -100 .

COMPUTE AACALIF1 = AACALIF + VIEJITOS .
EXECUTE.
IF (agua1=1  & luz=1  & piso= 1) AACALIF1=AACALIF1-100 .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1 < 324.45) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES= lp98 aapobre  .
```

REGIÓN 2. SIERRA
FASE 6
MODELO bb

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos noasi1 trab151 hacina esc ocupj_1
   estgas ej  tv licua
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS=.41 .59
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

COMPUTE BBDEPEN=-42*DEPEN.
COMPUTE BBNINOS=-9*NINOS.
COMPUTE BBNOASI=-23*NOASI1.
COMPUTE BBTRAB15=-1*TRAB151.
COMPUTE BBHACINA=-11*HACINA.
COMPUTE BBESC=6*ESC.
COMPUTE BBOCUPJ=-8*OCUPJ_1.
COMPUTE BBEDAD=1*EJ.

IF (estgas =0) BBestgas = 100.
IF (estgas =1) BBestgas = 95.

IF (licua =0) BBlicua = 100.
IF (licua =1) BBlicua = 88.

IF (tv=0) BBtv= 100.
IF (tv=1) BBtv= 82.

EXECUTE .

FREQUENCIES
  VARIABLES= BBdepen BBninos BBnoasi BBtrab15 BBhacina BBesc BBocupj BBedad
   BBestgas BBlicua BBtv
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE BBinput = 0 .
EXECUTE .
DO IF (MISSING(BBdepen) | MISSING(BBninos) | MISSING (BBnoasi)
  | MISSING(BBtrab15) | MISSING(BBhacina)| MISSING(BBesc) | MISSING(BBocupj)
  | MISSING(BBedad) | MISSING(BBestgas) | MISSING(BBlicua) | MISSING (BBtv)) .
RECODE
  BBinput  (0=1)  .
END IF .
EXECUTE .

RECODE BBdepen  (SYSMIS = -107.49)  .
RECODE BBninos  (SYSMIS = -14.71)  .
RECODE BBnoasi  (SYSMIS = -3.47)  .
RECODE BBtrab15  (SYSMIS = -0.06)  .
RECODE BBhacina  (SYSMIS = -42.26)  .
RECODE BBesc  (SYSMIS = 21.30)  .
RECODE BBocupj  (SYSMIS = 0.94)  .
RECODE BBedad  (SYSMIS = 44.23)  .
RECODE BBestgas  (SYSMIS = 96.26)  .
RECODE BBlicua  (SYSMIS = 92.96)  .
RECODE BBtv  (SYSMIS = 91.67)  .

EXECUTE .

  COMPUTE BBcalif = BBdepen + BBninos + BBnoasi + BBtrab15 +
                    BBhacina + BBesc + BBocupj + BBedad + BBestgas + BBlicua + BBtv .

EXECUTE .

DISCRIMINANT
```

```
  /GROUPS=LP98(0 1)
  /VARIABLES=BBcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .41 .59
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_3 = 0).
VARIABLE LABEL filter_$ 'dis_3 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=BBcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_3 = 1).
VARIABLE LABEL filter_$ 'dis_3 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=BBcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
 SE ALL.
_XECUTE .

COMPUTE VIEJITOS = 0 .
IF ((EJ < 25 & TOTPER < 5) | (EJ > 65 & EJ < 98 & TOTPER < 3)) VIEJITOS = -100 .

COMPUTE BBCALIF1 = BBCALIF + VIEJITOS .
EXECUTE.
IF (agua1=1  & luz=1  & piso= 1) BBCALIF1=BBCALIF1-100 .
EXECUTE .

COMPUTE BBpobre = 0 .
EXECUTE .
DO IF (BBcalif1 < 236) .
RECODE
  BBpobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES= lp98 BBpobre  .

IF(AAPOBRE=0 & BBPOBRE=1) NVO_POB=1 .
RECODE NVO_POB (SYSMIS=0) .
EXECUTE .

IF ((ULT_NIV=4 | ULT_NIV=6 | ULT_NIV=7) & SEG_SOC=2) MAESTRO=1 .

DO IF (MAESTRO=1) .
RECODE
 NVO_POB (1=0) .
  ID IF .
_XECUTE .

CROSSTABS
  /TABLES=nvo_pob  BY entidad
  /FORMAT= AVALUE TABLES
```

/CELLS= COUNT .

```
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .41 .59
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
  SE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((EJ < 25 & TOTPER < 5) | (EJ > 65 & EJ < 98 & TOTPER < 3)) VIEJITOS = -100 .

COMPUTE AACALIF1 = AACALIF + VIEJITOS .
EXECUTE.

IF (agua1=1  & luz=1  & piso= 1) AACALIF1=AACALIF1-100 .
EXECUTE .

COMPUTE AApobre = 0 .
EXECUTE .
DO IF (AAcalif1 < 248.3) .
RECODE
  AApobre  (0=1)  .
END IF .
EXECUTE .

IF ((ULT_NIV=4 | ULT_NIV=6 | ULT_NIV=7) & SEG_SOC=2) MAESTRO=1 .

DO IF (MAESTRO=1) .
RECODE
 AAPOBRE (1=0) .
END IF .
EXECUTE .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
  ECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

DO IF (ELIMIN = 1) .
RECODE
  AAPOBRE  (1 = 0)  .
END IF .
```

```
EXECUTE .

FREQUENCIES
  VARIABLES=aapobre lp98 .
```

REGIÓN 2. SIERRA
FASE 8
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos noasi1 trab151 hacina esc ocupj_1 estgas ej tv licua
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS=.41 .59
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-42*DEPEN.
COMPUTE AANINOS=-9*NINOS.
COMPUTE AANOASI=-23*NOASI1.
COMPUTE AATRAB15=-1*TRAB151.
COMPUTE AAHACINA=-11*HACINA.
COMPUTE AAESC=6*ESC.
COMPUTE AAOCUPJ=-8*OCUPJ_1.
COMPUTE AAEDAD=1*EJ.

IF (estgas =0) AAestgas = 100.
IF (estgas =1) AAestgas = 95.

IF (licua =0) AAlicua = 100.
IF (licua =1) AAlicua = 88.

IF (tv=0) AAtv= 100.
IF (tv=1) AAtv= 82.

EXECUTE .

FREQUENCIES
  VARIABLES= AAdepen AAninos AAnoasi AAtrab15 AAhacina AAesc AAocupj AAedad AAestgas AAlicua AAtv
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE AAinput = 0 .
EXECUTE .
DO IF (MISSING(AAdepen) | MISSING(AAninos) | MISSING (AAnoasi)
        | MISSING(AAtrab15) | MISSING(AAhacina)| MISSING(AAesc) | MISSING(AAocupj)
        | MISSING(AAedad) | MISSING(AAestgas) | MISSING(AAlicua) | MISSING (AAtv)) .

RECODE
  AAinput (0=1) .
END IF .
EXECUTE .

RECODE AAdepen (SYSMIS = -107.49) .
RECODE AAninos (SYSMIS = -14.71) .
RECODE AAnoasi (SYSMIS = -3.47) .
RECODE AAtrab15 (SYSMIS = -0.06) .
RECODE AAhacina (SYSMIS = -42.26) .
RECODE AAesc (SYSMIS = 21.30) .
RECODE AAocupj (SYSMIS = 0.94) .
RECODE AAedad (SYSMIS = 44.23) .
RECODE AAestgas (SYSMIS = 96.26) .
RECODE AAlicua (SYSMIS = 92.96) .
RECODE AAtv (SYSMIS = 91.67) .
EXECUTE .

COMPUTE AAcalif = AAdepen + AAninos + AAnoasi + AAtrab15 + AAhacina
                  + AAesc + AAocupj + AAedad + AAestgas + AAlicua + AAtv .
EXECUTE .

DISCRIMINANT
```

```
**********PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos noasi1 trab151 hacina esc ocupj_1  discap  piso_1
  radio tv licua estgas vehi hectie1 ej
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=RAW TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

GET
  FILE='f:\fase8\punteo\REG_3\REG3J_1.sav'.
EXECUTE .

***Calificación

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-35*DEPEN.
COMPUTE AANINOS=-11*NINOS .
COMPUTE AANA15=-18*NOASI1.
COMPUTE AAT15=-14*TRAB151 .
COMPUTE AAHACINA=-2*HACINA .
COMPUTE AAESC=6*ESC .
COMPUTE AAOCUP=23*OCUPJ_1 .
COMPUTE AAPISO=11*PISO_1 .
COMPUTE AAHECTI=2*HECTIE1 .
COMPUTE AAEDAD=1*ej .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 87 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=94 .

if (TV=0) AATV = 100.
IF (TV=1) AATV =79  .

IF (LICUA=0) AALICUA= 100.
IF (LICUA=1) AALICUA=77 .


IF (ESTGAS=0) AAESTGAS=100 .
IF (ESTGAS=1) AAESTGAS=70 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=68 .

EXECUTE.

FREQUENCIES
  VARIABLES= AADEPEN AANINOS AANA15 AAT15 AAHACINA AAESC  AAOCUP AAPISO  AAHECTI
          AAEDAD  AADISCAP  AARADIO AATV  AALICUA   AAESTGAS  AAVEHI
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANA15)
| MISSING(AAT15) | MISSING(AAHACINA)  | MISSING(AAESC)
 |  MISSING(AAOCUP) | MISSING(AAPISO) | missing(AAHECTI) | missing(AAEDAD) |
     missing(AADISCAP) | missing(AARADIO) | MISSING(AATV) |  MISSING(AALICUA) |
    missing(AAESTGAS) | missing(AAVEHI) ) .
RECODE
  aainput  (0=1)  .
```

```
END IF .
EXECUTE .


RECODE  AADEPEN (SYSMIS=-93.8018) .
RECODE  AANINOS (SYSMIS=-19.6289) .
RECODE  AANA15 (SYSMIS=-3.1208).
RECODE  AAT15 (SYSMIS=-.9345).
RECODE  AAHACINA (SYSMIS=-7.4503).
RECODE  AAESC (SYSMIS=17.3331).
RECODE  AAOCUP (SYSMIS=-.6885) .
RECODE  AAPISO (SYSMIS=.4844).
RECODE  AAHECTI (SYSMIS=4.7667) .
RECODE  AAEDAD (SYSMIS=45.2543).
RECODE  AADISCAP (SYSMIS=99.4712) .
RECODE  AARADIO (SYSMIS=97.4780) .
RECODE  AATV (SYSMIS=88.72996).
RECODE  AALICUA (SYSMIS=85.0691).
RECODE  AAESTGAS (SYSMIS=79.3060) .
RECODE  AAVEHI (SYSMIS=69.8375) .


COMPUTE AAcalif = AADEPEN + AANINOS + AANA15 + AAT15 + AAHACINA + AAESC + AAOCUP + AAPISO +
          AAHECTI + AAEDAD +  AADISCAP + AARADIO + AATV + AALICUA   +  AAESTGAS + AAVEHI .
EXECUTE .

****

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS =.42  .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

***checar el número del discriminante

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


**********FILTROS DE SEGUNDA FASE
```

```
IF ( (ej<25 & TOTPER<5) | (ej>64 & totper<3) ) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .

COMPUTE AACALIF=AACALIF + viejitos .

COMPUTE AApobre = 0 .
EXECUTE .
DO IF (AAcalif< 555.13) .
RECODE
AApobre  (0=1)  .
END IF .

DO IF (vehi = 0 & aapobre = 1) .
RECODE
 aapobre  (1=0)  .
END IF .
EXECUTE .

*****************************************************************
****Filtros para eliminar pobres no válidos de fase 8****
*****************************************************************

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) AAPOBRE = 0 .

EXECUTE .

**********************

FREQUENCIES
  VARIABLES= lp99 AAPOBRE elimin.


*/*/*/* para obtener el fopo

COMPUTE fecha = 991013 .
COMPUTE FOPO =26 .
EXECUTE.


SAVE OUTFILE='f:\fase8\punteo\REG_3\REG3J_26.sav'
  /COMPRESSED.

AGGREGATE
 /OUTFILE='f:\fase8\punteo\REG_3\AGGR.SAV'
 /BREAK=entidad mpio local folio
 /aapobr_1 = MEAN(aapobre).

GET
 FILE='f:\fase8\punteo\REG_3\Aggr.sav'.
EXECUTE .

RENAME VARIABLES
        aapobr_1 = aapobre .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='f:\fase8\punteo\ENTREGAS\9910130\Fopo3_26.dbf'
 /TYPE=DB4 /MAP /REPLA.
```

```
**********para obtener  el LOCS

GET
  FILE='F:\Fase8\Punteo\Reg_3\reg3j_26.sav'.
EXECUTE .

COMPUTE  X = 1 .
IF (AAPOBRE = 1) FOLPOB = 1.
IF (AAPOBRE = 1) PERPOB = TOTPER .
RECODE FOLPOB PERPOB (SYSMIS = 0) .
EXECUTE.

SAVE OUTFILE='f:\fase8\punteo\REG_3\REG3J_26.sav'
  /COMPRESSED.

AGGREGATE
  /OUTFILE='f:\fase8\punteo\reg_3\locs3_26.sav'
  /BREAK=entidad mpio local
  /hoglocal = SUM(x) /totper_1 = SUM(totpers) /hogpobre = SUM(folpob) /perpob_1 =
  SUM(perpob) /region_1 = FIRST(region) /fecha_1 = FIRST(fecha) / fopo_1 = FIRST(fopo) .

GET
  FILE='f:\fase8\punteo\reg_3\locs3_26.sav'.
EXECUTE .

RENAME VARIABLES
        region_1 = region / fecha_1 = fecha / fopo_1 = fopo .

SAVE TRANSLATE OUTFILE='f:\fase8\PUNTEO\locals\991013\locs3_26.dbf '
   /TYPE=DB4
   /COMPRESSED.
```

```
**********PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3

*/*/* CON EL MODELO BB

***Nuevo modelo

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=depen ninos noasi1 trab151 hacina esc ocupj_1  discap  piso_1
 radio tv licua estgas vehi hectie1 ej
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=RAW TABLE crossvalid
 /CLASSIFY=NONMISSING POOLED .

GET
 FILE='e:\4_5y6fas\punteo\REG_3\REG3J_9.sav'.
EXECUTE .

COMPUTE bbDEPEN=-34*DEPEN.
COMPUTE bbNINOS=-17*NINOS .
COMPUTE bbNA15=-7*NOASI1.
COMPUTE bbT15=-33*TRAB151 .
COMPUTE bbHACINA=-3*HACINA .
COMPUTE bbESC=7*ESC .
COMPUTE bbOCUP=2*OCUPJ_1 .
COMPUTE bbPISO=7*PISO_1 .
COMPUTE bbHECTI=1*HECTIE1 .
COMPUTE bbEDAD=1*ej .

IF (DISCAP =0) bbDISCAP = 100.
IF (DISCAP =1) bbDISCAP = 71 .

IF (RADIO=0) bbRADIO=100 .
IF (RADIO=1) bbRADIO=87 .

if (TV=0) bbTV = 100.
IF (TV=1) bbTV =83  .

IF (LICUA=0) bbLICUA= 100.
IF (LICUA=1) bbLICUA=75 .

IF (ESTGAS=0) bbESTGAS=100 .
IF (ESTGAS=1) bbESTGAS=93 .

IF (VEHI=0) bbVEHI=100 .
IF (VEHI=1) bbVEHI=59 .
EXECUTE.

FREQUENCIES
  VARIABLES= bbDEPEN bbNINOS bbNA15 bbT15 bbHACINA bbESC  bbOCUP bbPISO  bbHECTI
          bbEDAD  bbDISCAP  bbRADIO bbTV  bbLICUA   bbESTGAS   bbVEHI
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE bbinput = 0 .
EXECUTE .
DO IF ( MISSING(bbDEPEN) | MISSING(bbNINOS) | MISSING(bbNA15)
 | MISSING(bbT15) | MISSING(bbHACINA)  | MISSING(bbESC)
  |  MISSING(bbOCUP) | MISSING(bbPISO) | missing(bbHECTI) | missing(bbEDAD) |
      missing(bbDISCAP) | missing(bbRADIO) | MISSING(bbTV) |  MISSING(bbLICUA) |
     missing(bbESTGAS) | missing(bbVEHI) ) .
RECODE
  bbinput  (0=1)  .
END IF .
EXECUTE .

RECODE  bbDEPEN (SYSMIS=-92.8553) .
```

```
RECODE  bbNINOS (SYSMIS=-27.6437) .
RECODE  bbNA15 (SYSMIS=-.8629).
RECODE  bbT15 (SYSMIS=-1.5476).
RECODE  bbHACINA (SYSMIS=-9.2162).
RECODE  bbESC (SYSMIS=26.9878).
RECODE  bbOCUP (SYSMIS=.7894) .
RECODE  bbPISO (SYSMIS=.4339).
RECODE  bbHECTI (SYSMIS=3.0758) .
RECODE  bbEDAD (SYSMIS=45.4000).
RECODE  bbDISCAP (SYSMIS=98.8230) .
RECODE  bbRADIO (SYSMIS=95.7839) .
RECODE  bbTV (SYSMIS=93.4224).
RECODE  bbLICUA (SYSMIS=88.3280).
RECODE  bbESTGAS (SYSMIS=96.9168) .
RECODE  bbVEHI (SYSMIS=63.5471) .


COMPUTE bbcalif = bbDEPEN + bbNINOS + bbNA15 + bbT15 + bbHACINA + bbESC + bbOCUP + bbPISO +
        bbHECTI + bbEDAD +  bbDISCAP + bbRADIO + bbTV + bbLICUA   +  bbESTGAS + bbVEHI .
EXECUTE .

****

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES=bbcalif
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS =.41  .59
 /STATISTICS=raw TABLE crossvalid
 /CLASSIFY=NONMISSING POOLED .

***checar el número del discriminante

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=bbcalif  /FORMAT=NOTABLE
 /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=bbcalif  /FORMAT=NOTABLE
 /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

**********

IF ((ult_niv=4 | ult_niv = 6 | ult_niv = 7) & seg_soc = 2) maestro = 1 .
recode maestro (SYSMIS=0)

COMPUTE bbpobre = 0 .
EXECUTE .
```

```
DO IF (bbcalif< 543.515) .
RECODE
  bbpobre  (0=1)  .
END IF .

DO IF (bbpobre = 1 &  maestro = 1) .
RECODE
  BBpobre  (1=0)  .
END IF .
EXECUTE .

IF (aapobre = 0 & bbpobre = 1) nvo_pob = 1 .
RECODE nvo_pob (SYSMIS=0) .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 bbpobre bbpobre  .
```

```
**********FILTROS DE SEGUNDA FASE

IF ( (ej<25 & TOTPER<5) | (ej>64 & totper<3) ) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .
execute .

COMPUTE bbCALIF=bbCALIF + viejitos .

COMPUTE bbpobre = 0 .
EXECUTE .
DO IF (bbcalif< 507.1) .
RECODE
bbpobre  (0=1)  .
END IF .

DO IF (vehi = 0 & bbpobre = 1) .
RECODE
  bbpobre  (1=0)  .
END IF .
EXECUTE .

FREQUENCIES
   VARIABLES= lp98 bbPOBRE.


COMPUTE fecha = 181298 .
COMPUTE FOPO =20.
EXECUTE.

SAVE OUTFILE='e:\4_5y6fas\punteo\REG_3\REG3J16.sav'
   /COMPRESSED.

AGGREGATE
  /OUTFILE='e:\4_5y6fas\punteo\REG_3\AGGR.SAV'
  /BREAK=entidad mpio local folio
  /bbpobr_1 = MEAN(bbpobre).
```

```
GET
  FILE='e:\4_5y6fas\punteo\REG_3\Aggr.sav'.
EXECUTE .

RENAME VARIABLES
        bbpobr_1 = bbpobre .

FILTER OFF.
USE ALL.
SELECT IF(bbpobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='e:\4_5y6fas\punteo\ENTREGAS\981218\Fopo3_20.dbf'
  /TYPE=DB4 /MAP /REPLA.
```

```
**********PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3

/*/*/*/ CON EL MODELO AA  */*/*/*/*/*

***Nuevo modelo

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=depen ninos noasi1 trab151 hacina esc ocupj_1  discap  piso_1
 radio tv licua estgas vehi hectie1 ej
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=RAW TABLE crossvalid
 /CLASSIFY=NONMISSING POOLED .


GET
 FILE='e:\4_5y6fas\punteo\REG_3\REG3J_9.sav'.
EXECUTE .

COMPUTE AADEPEN=-35*DEPEN.
COMPUTE AANINOS=-11*NINOS .
COMPUTE AANA15=-18*NOASI1.
COMPUTE AAT15=-14*TRAB151 .
COMPUTE AAHACINA=-2*HACINA .
COMPUTE AAESC=6*ESC .
COMPUTE AAOCUP=23*OCUPJ_1 .
COMPUTE AAPISO=11*PISO_1 .
COMPUTE AAHECTI=2*HECTIE1 .
COMPUTE AAEDAD=1*ej .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 87 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=94 .

if (TV=0) AATV = 100.
IF (TV=1) AATV =79  .

IF (LICUA=0) AALICUA= 100.
IF (LICUA=1) AALICUA=77 .


IF (ESTGAS=0) AAESTGAS=100 .
IF (ESTGAS=1) AAESTGAS=70 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=68 .

EXECUTE.

FREQUENCIES
 VARIABLES= AADEPEN AANINOS AANA15 AAT15 AAHACINA AAESC  AAOCUP AAPISO  AAHECTI
        AAEDAD  AADISCAP  AARADIO AATV  AALICUA   AAESTGAS   AAVEHI
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANA15)
 | MISSING(AAT15) | MISSING(AAHACINA)  | MISSING(AAESC)
  |  MISSING(AAOCUP) | MISSING(AAPISO) | missing(AAHECTI) | missing(AAEDAD) |
     missing(AADISCAP) | missing(AARADIO) | MISSING(AATV) |  MISSING(AALICUA) |
    missing(AAESTGAS) | missing(AAVEHI) ) .
RECODE
 aainput  (0=1)  .
END IF .
```

```
EXECUTE .

RECODE  AADEPEN (SYSMIS=-108.6458) .
RECODE  AANINOS (SYSMIS=-20.5159) .
RECODE  AANA15 (SYSMIS=-2.1905).
RECODE  AAT15 (SYSMIS=-.5556).
RECODE  AAHACINA (SYSMIS=-5.9055).
RECODE  AAESC (SYSMIS=26.0000).
RECODE  AAOCUP (SYSMIS=-56.7666) .
RECODE  AAPISO (SYSMIS=-2.19813).
RECODE  AAHECTI (SYSMIS=.0001) .
RECODE  AAEDAD (SYSMIS=45.0800).
RECODE  AADISCAP (SYSMIS=99.2778) .
RECODE  AARADIO (SYSMIS=97.9524) .
RECODE  AATV (SYSMIS=96.1667).
RECODE  AALICUA (SYSMIS=93.0635).
RECODE  AAESTGAS (SYSMIS=96.4286) .
RECODE  AAVEHI (SYSMIS=73.8413) .


COMPUTE AAcalif = AADEPEN + AANINOS + AANA15 + AAT15 + AAHACINA + AAESC + AAOCUP + AAPISO +
        AAHECTI + AAEDAD +  AADISCAP + AARADIO + AATV + AALICUA   +  AAESTGAS + AAVEHI .
EXECUTE .

****

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS =.42  .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

***checar el número del discriminante

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

**********FILTROS

IF ( (ej<25 & TOTPER<5) | (ej>64 & totper<3) ) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .
```

```
execute .

COMPUTE AACALIF=AACALIF + viejitos .

COMPUTE AApobre = 0 .
EXECUTE .
DO IF (AAcalif< 507.1) .
RECODE
AApobre  (0=1)  .
END IF .

DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
END IF .
EXECUTE .

FREQUENCIES
   VARIABLES= lp98 AAPOBRE.
```

```
***PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3

***MODELO BB DE LA FASE 3

DISCRIMINANT
  GROUPS=lp98(0 1)
 /VARIABLES=depen ninos noasi1 hacina esc bao_1 piso_1 hectie1 discap
 radio tv licua estgas
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=RAW TABLE crossvalid
 /CLASSIFY=NONMISSING POOLED .

COMPUTE BBDEPEN=-33*DEPEN.
COMPUTE BBNINOS=-19*NINOS .
COMPUTE BBNOASI=-33*NOASI1.
COMPUTE BBHACINA=-3*HACINA .
COMPUTE BBESC=5*ESC .
COMPUTE BBBAO=8*BAO_1 .
COMPUTE BBPISO=10*PISO_1 .
COMPUTE BBHECTIE=2*HECTIE1 .

IF (DISCAP =0) BBDISCAP = 100.
IF (DISCAP =1) BBDISCAP = 78 .

IF (RADIO=0) BBRADIO=100 .
IF (RADIO=1) BBRADIO=91 .

if (TV=0) BBTV = 100.
IF (TV=1) BBTV =81  .

IF (LICUA=0) BBLICUA= 100.
IF (LICUA=1) BBLICUA=85 .

IF (ESTGAS=0) BBESTGAS=100 .
IF (ESTGAS=1) BBESTGAS=69 .

   (VEHI=0) BBVEHI=100 .
   (VEHI=1) BBVEHI=68 .

EXECUTE.

FREQUENCIES
  VARIABLES= BBDEPEN BBNINOS BBNOASI BBHACINA BBESC  BBBAO BBPISO  BBHECTIE
        BBDISCAP  BBRADIO BBTV  BBLICUA   BBESTGAS
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .


COMPUTE BBinput = 0 .
EXECUTE .
DO IF ( MISSING(BBDEPEN) | MISSING(BBNINOS) | MISSING(BBNOASI)
  | MISSING(BBHACINA)  | MISSING(BBESC)
  |  MISSING(BBBAO) | MISSING(BBPISO) | missing(BBHECTIE) |
     missing(BBDISCAP) | missing(BBRADIO) | MISSING(BBTV) |  MISSING(BBLICUA) |
    missing(BBESTGAS) ) .
RECODE
  BBinput  (0=1)  .
END IF .
EXECUTE .


RECODE  BBDEPEN (SYSMIS=-66.032) .
RECODE  BBNINOS (SYSMIS=-19.884) .
RECODE  BBNOASI(SYSMIS=-2.526).
RECODE  BBHACINA (SYSMIS=-9.319).
RECODE  BBESC (SYSMIS=14.012).
RECODE  BBBAO (SYSMIS=.95).
RECODE  BBPISO (SYSMIS=1.398).
RECODE  BBHECTIE (SYSMIS=8.348) .
RECODE  BBDISCAP (SYSMIS=98.209).
RECODE  BBRADIO (SYSMIS=96.756) .
RECODE  BBTV (SYSMIS=93.814).
RECODE  BBLICUA (SYSMIS=91.802).
RECODE  BBESTGAS (SYSMIS=83.418) .
RECODE  BBVEHI (SYSMIS=68.86) .
```

```
COMPUTE AAcalif = AADEPEN + AANINOS + AANOASI + AAHACINA + AAESC + AABAO + AAPISO +
          AAHECTIE +  AADISCAP + AARADIO + AATV + AALICUA   +
           AAESTGAS .
EXECUTE .

****

 ,ISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES=AAcalif
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS =.42  .58
 /STATISTICS=raw TABLE crossvalid
 /CLASSIFY=NONMISSING POOLED .

***checar el número del discriminante

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  'STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


*************FILTROS DE SEGUNDA FASE

IF ( (ej<25 & TOTPER<5) | (ej>64 & totper<3) ) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .


            ***********FILTRO INDISP2********


IF ((agua1 ~= 1 & piso1 ~= 1)) indisp2=0 .
RECODE indisp2 (SYSMIS=-100) .
EXECUTE .


COMPUTE AACALIF=AACALIF + viejitos + indisp2 .
EXECUTE .

COMPUTE AApobre = 0 .
EXECUTE .
DO IF (AAcalif< 338.34) .
RECODE
AApobre  (0=1)  .
END IF .
EXECUTE .

DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
  ID IF .
EXECUTE .

FREQUENCIES
  VARIABLES= lp98 AAPOBRE.
```

```
*/*/*/ PUNTAJES DE LA REGION 3
*/*/* FASE 2
*/*/* PRIMER MODELO, YY

COMPUTE animales = 1 .
EXECUTE .
 O IF ((p721 >=  15 & p721 <  99) | (p722 >=  15 & p722 <  99) | (p723 >=  15 & p723 <  99)|
  731 >=  20 & p731 <  99) | (p732 >=  15 & p732 <  99) | (p733 >=  25 & p733 <  99) | (p734 >=  15 & p734 <  99) |
(p735 >=  25 & p735 <  99) ) .
RECODE
 animales  (1=0)  .
END IF .
EXECUTE .

COMPUTE enseres = 0 .
EXECUTE .
DO IF (lava = 1 & refri = 1 & vehi = 1& licua = 1
      & bao = 1 & estgas=1 & agua = 1 & luz = 1
       & tv = 1 & tierra = 1 & animales = 1) .
RECODE
 enseres  (0=1)  .
END IF .
EXECUTE .

COMPUTE patron = 1 .
EXECUTE .
DO IF (p25=4) .
RECODE
 patron  (1=0)  .
END IF .
EXECUTE .

COMPUTE YYDEPEN=-30*DEPEN.
COMPUTE YYNINOS=-6*NINOS.
COMPUTE YYNOASI=-2*NOASI15.
COMPUTE YYTRAB15=-48*TRAB15.

IF ( HH1 = 1) YYHACINA=100.
IF ( HH2 = 1) YYHACINA=52.
IF ( HH3 = 1) YYHACINA=44.
   ( HH4 = 1) YYHACINA=42.
   ( HH5 = 1) YYHACINA=41.
IF ( HH6 = 1 ) YYHACINA=40.


IF ( ESCJ1 = 1) YYESC= 62.
IF ( ESCJ2 = 1) YYESC= 65.
IF ( ESCJ3 = 1) YYESC= 69.
IF ( ESCJ4 = 1) YYESC= 100.

IF (OCUPJ0 = 1) YYOCUP= 86.
IF (OCUPJ1 = 1) YYOCUP= 84.
IF (OCUPJ2 = 1) YYOCUP= 92.
IF (OCUPJ3_4 = 1) YYOCUP = 100.
IF (OCUPJ5_9 = 1) YYOCUP = 88.

IF (DISCAP = 0) YYDISCAP= 100.
IF (DISCAP = 1) YYDISCAP= 93.

IF (PISO = 0) YYPISO= 100.
IF (PISO = 1) YYPISO= 75.

IF (EJ1 =1) YYEJ= 89.
IF (EJ2 =1) YYEJ= 90.
IF (EJ3 =1) YYEJ= 91.
IF (EJ4 =1) YYEJ= 96.
IF (EJ5 =1) YYEJ= 100.
IF (EJ6 =1) YYEJ= 94.


IF (RADIO =0) YYRADIO = 100.
IF (RADIO =1) YYRADIO = 86.

IF (LICUA =0) YYLICUA = 100.
IF (LICUA =1) YYLICUA = 72.

IF (TV=0) YYTV= 100.
IF (TV=1) YYTV= 74.

IF (AGUA=0) YYAGUA= 100.
IF (AGUA=1) YYAGUA= 95.
```

```
IF (VEHI=0) YYVEHI= 100.
IF (VEHI=1) YYVEHI= 0.

IF (REFRI=0) YYREFRI= 100.
IF (REFRI=1) YYREFRI= 0.

  (ANIMALES=0) YYANIM= 100.
IF (ANIMALES=1) YYANIM= 0.

IF (TIERRA=0) YYTIERRA= 100.
IF (TIERRA=1) YYTIERRA= 0.

IF (LAVA=0) YYLAVA= 100.
IF (LAVA=1) YYLAVA= 0.

IF (PATRON=0) YYPATRON= 100.
IF (PATRON=1) YYPATRON= 0.

IF (ENSERES=0) YYENSER= 0.
IF (ENSERES=1) YYENSER= -100.


FREQUENCIES
  VARIABLES= yydepen yyninos yynoasi yytrab15 yyhacina yyesc yyocup yydiscap
  yypiso yyej yyradio yylicua yytv yyagua yyvehi yyrefri yyanim yytierra yylava yypatron yyenser
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .


COMPUTE input = 0 .
EXECUTE .
DO IF (MISSING(yydepen) | MISSING(yyninos) | MISSING(yynoasi) | MISSING(yytrab15)
  | MISSING(yyhacina) | MISSING(yyesc)  | MISSING(yyocup)
  | MISSING(yydiscap) | MISSING(yypiso) | MISSING(yyej) | MISSING(yyradio) |
  MISSING(yylicua) | MISSING(yytv) | MISSING(yyagua) | MISSING(yyvehi)
   | MISSING(yyrefri)| MISSING(yyanim)| MISSING(yytierra)| MISSING(yylava)|
   MISSING(yypatron)| MISSING(yyenser) ) .
RECODE
  input  (0=1)  .
   ND IF .
 XECUTE .

RECODE yydepen  (SYSMIS=-79.393) .
RECODE yyninos  (SYSMIS=-12.131) .
RECODE yynoasi  (SYSMIS=-.546) .
RECODE yytrab15  (SYSMIS=-8.179) .
RECODE yyhacina  (SYSMIS=47.882) .
RECODE yyesc  (SYSMIS=66.395) .
RECODE yyocup  (SYSMIS=88.613) .
RECODE yydiscap  (SYSMIS=99.630) .
RECODE yypiso  (SYSMIS=80.915) .
RECODE yyej  (SYSMIS=94.328) .
RECODE yyradio  (SYSMIS=93.547) .
RECODE yylicua  (SYSMIS=77.183) .
RECODE yytv  (SYSMIS=82.356) .
RECODE yyagua  (SYSMIS=96.650) .
RECODE yyvehi  (SYSMIS=5.780) .
RECODE yyrefri  (SYSMIS=5.968) .
RECODE yyanim  (SYSMIS=4.883) .
RECODE yytierra  (SYSMIS=1.074) .
RECODE yylava  (SYSMIS=1.063) .
RECODE yypatron  (SYSMIS=.806) .
RECODE yyenser  (SYSMIS=-25.064) .


COMPUTE yycalif = yydepen + yyninos + yynoasi + yytrab15 + yyhacina +
  yyesc + yyocup + yydiscap + yypiso + yyej + yyradio + yylicua + yytv
  + yyagua .
EXECUTE .

DISCRIMINANT
  /GROUPS=lpnva(0 1)
  /VARIABLES=yycalif
   ANALYSIS ALL
   SAVE=CLASS
  /PRIORS  EQUAL
  /STATISTICS=TABLE
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
```

```
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

 .REQUENCIES
  VARIABLES=yycalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=yycalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE yycalif = yycalif + yyvehi + yyrefri + yyanim + yytierra + yylava + yyenser  .
EXECUTE .

COMPUTE pobre = 0 .
EXECUTE .
DO IF (yycalif < 759.5) .
RECODE
  pobre  (0=1)  .
END IF .
EXECUTE .


MEANS
   ABLES=agua bao depen discap ej1 ej2 ej3 ej4 ej5 ej6 escj1 escj2 escj3
  escj4 estgas hh1 hh2 hh3 hh4 hh5 hh6 ingmen15 ingmes ingmesh ingmigm
  ingmigr inmh15pc lava licua luz mu15a49 ninos noasi15 ocupj0 ocupj1 ocupj2
  ocupj3_4 ocupj5_9 piso radio refri tierra totpers trab15 tv vehi vhs  BY
  pobre
  /CELLS MEAN STDDEV COUNT
  /FORMAT= LABELS .

IF (DIS_1=0 & DIS_2=0 & POBRE=0) SECUENCE=1.
IF (DIS_1=0 & DIS_2=0 & POBRE=1) SECUENCE=2.
IF (DIS_1=0 & DIS_2=1 & POBRE=0) SECUENCE=3.
IF (DIS_1=1 & DIS_2=0 & POBRE=0) SECUENCE=4.
IF (DIS_1=0 & DIS_2=1 & POBRE=1) SECUENCE=5.
IF (DIS_1=1 & DIS_2=0 & POBRE=1) SECUENCE=6.
IF (DIS_1=1 & DIS_2=1 & POBRE=0) SECUENCE=7.
IF (DIS_1=1 & DIS_2=1 & POBRE=1) SECUENCE=8.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=0) SECUENCE=9.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=1) SECUENCE=10.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=0) SECUENCE=11.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=1) SECUENCE=12.

FREQUENCIES
  VARIABLES=secuence  .
```

```
**********PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3

*/*/*/ MODELO AA DE LA FASE  3

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos noasi1 trab151 hacina esc ocupj_1  discap  piso_1
   adio tv licua estgas vehi hectie1 ej
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=RAW TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

*/*/* se calculan los puntajes

COMPUTE AADEPEN=-35*DEPEN.
COMPUTE AANINOS=-11*NINOS .
COMPUTE AANA15=-18*NOASI1.
COMPUTE AAT15=-14*TRAB151 .
COMPUTE AAHACINA=-2*HACINA .
COMPUTE AAESC=6*ESC .
COMPUTE AAOCUP=23*OCUPJ_1 .
COMPUTE AAPISO=11*PISO_1 .
COMPUTE AAHECTI=2*HECTIE1 .
COMPUTE AAEDAD=1*ej .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 87 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=94 .

if (TV=0) AATV = 100.
IF (TV=1) AATV =79  .

IF (LICUA=0) AALICUA= 100.
IF (LICUA=1) AALICUA=77 .


   (ESTGAS=0) AAESTGAS=100 .
   (ESTGAS=1) AAESTGAS=70 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=68 .

EXECUTE.


FREQUENCIES
  VARIABLES= AADEPEN AANINOS AANA15 AAT15 AAHACINA AAESC  AAOCUP AAPISO  AAHECTI
          AAEDAD   AADISCAP  AARADIO AATV  AALICUA    AAESTGAS   AAVEHI
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .


COMPUTE aainput = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANA15)
 | MISSING(AAT15) | MISSING(AAHACINA)  | MISSING(AAESC)
  |  MISSING(AAOCUP) | MISSING(AAPISO) | missing(AAHECTI) | missing(AAEDAD) |
      missing(AADISCAP) | missing(AARADIO) | MISSING(AATV) |  MISSING(AALICUA) |
     missing(AAESTGAS) | missing(AAVEHI) ) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .


RECODE  AADEPEN (SYSMIS=-100.69) .
RECODE  AANINOS (SYSMIS=-20.17) .
RECODE  AANA15 (SYSMIS=-3.048).
RECODE  AAT15 (SYSMIS=-7.66).
RECODE  AAHACINA (SYSMIS=-8.01).
RECODE  AAESC (SYSMIS=16.74).
RECODE  AAOCUP (SYSMIS=.27).
RECODE  AAPISO (SYSMIS=-.179).
RECODE  AAHECTI (SYSMIS=5.03) .
RECODE  AAEDAD (SYSMIS=45.14).
RECODE  AADISCAP (SYSMIS=99.5).
RECODE  AARADIO (SYSMIS=97.08) .
```

```
RECODE  AATV (SYSMIS=85.48).
RECODE  AALICUA (SYSMIS=83.82).
RECODE  AAESTGAS (SYSMIS=75.93) .
RECODE  AAVEHI (SYSMIS=68.86) .


 OMPUTE AAcalif = AADEPEN + AANINOS + AANA15 + AAT15 + AAHACINA + AAESC + AAOCUP + AAPISO +
        AAHECTI + AAEDAD +  AADISCAP + AARADIO + AATV + AALICUA   +
        AAESTGAS + AAVEHI .
EXECUTE .

***
DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS =.42  .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

***checar el número del discriminante

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
  'LTER BY filter_$.
  XECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

*************FILTROS DE SEGUNDA FASE

IF ( (ej<25 & TOTPER<5) | (ej>64 & totper<3) ) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .

COMPUTE AACALIF1=AACALIF + viejitos .
EXECUTE .

COMPUTE AApobre = 0 .
EXECUTE .
DO IF (AAcalif1< 507.1) .
RECODE
AApobre  (0=1)  .
END IF .
EXECUTE .

DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES= lp98 AAPOBRE.
```

```
*/*/*/ PUNTAJE DE LA REGION 3
*/*/*/ FASE 1
*/*/*/  MODELO  AA

* LINEA DE POBREZA

 code ingmesh ingmen15(99999=sysmis) .

compute inmh15pc=(ingmesh-ingmen15)/totpers.

if (sysmis(ingmesh) | sysmis(ingmen15))inmh15pc=999.
recode inmh15pc (999=sysmis).

compute lpNVA=0.
if (inmh15pc <= 286.06) lpNVA=1.
If (sysmis(ingmesh))lpNVA=99.
recode lpNVA (99=sysmis).

* INDICE DE DEPENDENCIA

IF (PERCEP~=0) depen= (totpers-percep)/percep.
IF (PERCEP=0) DEPEN= TOTPERS.

* DISCAPACITADOS

RENAME VARIABLES  (P431=DISCAP) .

*HACINAMIENTO

RECODE P61 (99=SYSMIS).
compute hacina= totpers/p61.

IF (hacina <= 1) hh1 = 1 .
RECODE  hh1  (MISSING=0)  .
IF (hacina >1 & hacina<=2) hh2 = 1 .
RECODE  hh2  (MISSING=0)  .
IF (hacina >2 & hacina<=3) hh3 = 1 .
RECODE  hh3  (MISSING=0)  .
IF (hacina >3 & hacina<=4) hh4 = 1 .
RECODE  hh4  (MISSING=0)  .
   (hacina >4 & hacina<=5) hh5 = 1 .
RECODE  hh5  (MISSING=0)  .
IF (hacina >5 ) hh6 = 1 .
RECODE  hh6  (MISSING=0)  .

IF (SYSMIS(hacina)) hh1=99.
IF (SYSMIS(hacina)) hh2=99.
IF (SYSMIS(hacina)) hh3=99.
IF (SYSMIS(hacina)) hh4=99.
IF (SYSMIS(hacina)) hh5=99.
IF (SYSMIS(hacina)) hh6=99.

RECODE  hh1 hh2 hh3 hh4 hh5 hh6  (99=SYSMIS) .

* ESCOLARIDAD DEL JEFE

compute esc=escjefe .
if (esccony > escjefe & esccony <99) esc= esccony.

IF (ESC=0) ESCJ1 = 1 .
RECODE  ESCJ1  (MISSING=0)  .
IF (ESC>=1 & ESC<=5) ESCJ2 = 1 .
RECODE  ESCJ2  (MISSING=0)  .
IF (ESC=6) ESCJ3 = 1 .
RECODE  ESCJ3  (MISSING=0)  .
IF (ESC>=7) ESCJ4 = 1 .
RECODE  ESCJ4  (MISSING=0)  .
recode esc (99= sysmis).

IF (SYSMIS(Esc)) EscJ1=99.
IF (SYSMIS(Esc)) EscJ2=99.
IF (SYSMIS(Esc)) EscJ3=99.
IF (SYSMIS(Esc)) EscJ4=99.

  (ESCJ1=1) ESCJ=1 .
   (ESCJ2=1) ESCJ=2 .
IF (ESCJ3=1) ESCJ=3 .
IF (ESCJ4=1) ESCJ=4 .

RECODE EscJ1 EscJ2 EscJ3 EscJ4  (99=SYSMIS).
```

```
* OCUPACIÓN DEL JEFE

COMPUTE TRAB=0.
IF (P23>=1 & p23<=3 | P24>=1 & p24<=5) trab=1 .
IF ((P23 >=8 | SYSMIS(P23))& (P24 >=8 | SYSMIS(P24))) TRAB=9.
recode trab (9= sysmis).

 ecode p27 (99=88).
recode  P27 (88=sysmis)  .
compute ocupj= p27.

if (trab = 0 ) ocupj=0.
IF (ocUPJ = 0) OCUPJ0 = 1 .
RECODE  OCUPJ0  (MISSING=0)  .
IF (ocUPJ = 1) OCUPJ1 = 1 .
RECODE  OCUPJ1  (MISSING=0)  .
IF (OCUPJ = 2) OCUPJ2 = 1 .
RECODE  OCUPJ2  (MISSING=0)  .
IF (OCUPJ = 3) OCUPJ3 = 1 .
RECODE  OCUPJ3  (MISSING=0)  .
IF (OCUPJ = 4) OCUPJ4 = 1 .
RECODE  OCUPJ4  (MISSING=0)  .
IF (OCUPJ = 5) OCUPJ5 = 1 .
RECODE  OCUPJ5 (MISSING=0)  .
IF (OCUPJ = 6) OCUPJ6 = 1 .
RECODE  OCUPJ6  (MISSING=0)  .
IF (OCUPJ = 7) OCUPJ7 = 1 .
RECODE  OCUPJ7  (MISSING=0)  .
IF (OCUPJ = 8) OCUPJ8 = 1 .
RECODE  OCUPJ8  (MISSING=0)  .

IF (SYSMIS(OCUPJ)) OCUPJ0=99.
IF (SYSMIS(OCUPJ)) OCUPJ1=99.
IF (SYSMIS(OCUPJ)) OCUPJ2=99.
IF (SYSMIS(OCUPJ)) OCUPJ3=99.
IF (SYSMIS(OCUPJ)) OCUPJ4=99.
IF (SYSMIS(OCUPJ)) OCUPJ5=99.
IF (SYSMIS(OCUPJ)) OCUPJ6=99.
IF (SYSMIS(OCUPJ)) OCUPJ7=99.
IF (SYSMIS(OCUPJ)) OCUPJ8=99.

.ECODE  OCUPJ0  OCUPJ1 OCUPJ2 OCUPJ3 OCUPJ4
     OCUPJ5 OCUPJ6 OCUPJ7 OCUPJ8 OCUPJ0  (99=SYSMIS) .

*EDAD DEL JEFE

compute EJ = p08 .

DO IF (P09<15 | P09>98) .
RECODE EJ (ELSE=SYSMIS) .
END IF .

IF (EJ = 1) EJ1 = 1 .
RECODE  EJ1  (MISSING=0)  .
IF (EJ = 2) EJ2 = 1 .
RECODE  EJ2  (MISSING=0)  .
IF (EJ = 3) EJ3 = 1 .
RECODE  EJ3  (MISSING=0)  .
IF (EJ = 4) EJ4 = 1 .
RECODE  EJ4  (MISSING=0)  .
IF (EJ = 5) EJ5 = 1 .
RECODE  EJ5 (MISSING=0)  .
IF (EJ = 6) EJ6 = 1 .
RECODE  EJ6 (MISSING=0)  .

IF (SYSMIS(EJ)) EJ1=99.
IF (SYSMIS(EJ)) EJ2=99.
IF (SYSMIS(EJ)) EJ3=99.
IF (SYSMIS(EJ)) EJ4=99.
IF (SYSMIS(EJ)) EJ5=99.
IF (SYSMIS(EJ)) EJ6=99.

RECODE EJ1 EJ2 EJ3 EJ4 EJ5 EJ6 (99=SYSMIS).

  RECODIFICACION Y NOMBRE DE VARIABLES

RENAME VARIABLES (P57=AGUA) (P59=PISO)(P432=BAO) (P64_09=LAVA) (P64_05=REFRI) (P64_06=ESTGAS)
          (P64_12=VHS) (P64_15=TELEF) (NINTRAB=TRAB15) (NOASIS=NOASI15).

RECODE AGUA PISO BAO LAVA REFRI ESTGAS VHS TELEF  TRAB15 NOASI15 (9=SYSMIS) .
```

```
* VEHICULO = AUTO O CAMION O CAMIONETA

compute vehi=p64_01.
if (p64_01 = 0 | p64_02 = 0) vehi=0.

RECODE VEHI (9=SYSMIS).

 ompute ocupj056=ocupj0  + ocupj5 + ocupj6.

**********************************
FREQUENCIES VARIABLES= depen ninos trab15 NOASI15
       escj1 escj2 escj3
  ocupj0 ocupj1 ocupj2 ocupj3
 ej2 ej3 ej4 ej5 ej6
  piso  refri bao
  vehi lava vhs telef.

DISCRIMINANT
 /GROUPS=lpnva(0 1)
 /VARIABLES=  depen ninos
  hh2 hh3 hh4 hh5 hh6 discap trab15 noasi15
   escj1 escj2 escj3
      ocupj056 ocupj1  ocupj3
  ej2 ej3 ej4 ej5 ej1
   agua
   lava  refri estgas  vehi
 /ANALYSIS ALL
 /PRIORS  EQUAL
/STATISTICS= raw TABLE
/CLASSIFY=NONMISSING POOLED  .

*****************************************CALIFICACIONES
**reg5

IF (DEPEN >= 0 ) yyDEPEN = DEPEN * -30 .

IF (ninos >= 0 ) yyNInos = ninos * -7 .

IF (discap = 1 ) yydiscap = 82 .
DO IF (discap = 0 ) .
  ECODE
 yydiscap  (MISSING=100)  .
END IF .

IF (trab15 >= 0 ) yytrab = trab15 * -38 .

IF (noasi15 >= 0 ) yynoasi = noasi15 * -5 .

IF (hh1 = 1 ) yyhh1 = 100.
DO IF (hh2=1 ) .
RECODE
 yyhh1  (MISSING=47)  .
END IF .
DO IF (hh3=1 ) .
RECODE
 yyhh1  (MISSING=45)  .
END IF .
DO IF (hh4=1 ) .
RECODE
 yyhh1  (MISSING=43)  .
END IF .
DO IF (hh5=1 ) .
RECODE
 yyhh1  (MISSING=42)  .
END IF .
DO IF (hh1=0 & hh2=0 & hh3=0 & hh4=0 & hh5=0) .
RECODE
 yyhh1  (MISSING=41)  .
END IF .

IF (ESCJ1=1 ) yyeduc = 57 .
DO IF (ESCJ2 = 1 ) .
RECODE
 yyeduc  (MISSING=62)  .
  ND IF .
  O IF (ESCJ3= 1 ) .
RECODE
 yyeduc  (MISSING=64)  .
END IF .
DO IF (ESCJ1=0 & ESCJ2=0 & ESCJ3=0 ) .
RECODE
```

```
 yyeduc  (MISSING=100)  .
END IF .

IF (OCUPJ056=1 ) yyOCUPJ=52 .
DO IF (OCUPJ1=1 ) .
RECODE
 /yOCUPJ  (MISSING=53)  .
 .ND IF .

DO IF (OCUPJ3=1 ) .
RECODE
 yyOCUPJ  (MISSING=58)  .
END IF .
DO IF (OCUPJ056=0 & ocupj1=0 & ocupj3=0) .
RECODE
 yyOCUPJ  (MISSING=100)  .
END IF .


IF (EJ1=1 ) yyEJ = 73 .
DO IF (EJ2 = 1 ) .
RECODE
 yyEJ  (MISSING=75)  .
END IF .
DO IF (EJ3 = 1 ) .
RECODE
 yyEJ  (MISSING=82)  .
END IF .
DO IF (EJ4 = 1 ) .
RECODE
 yyEJ  (MISSING=88)  .
END IF .
DO IF (EJ5 = 1) .
RECODE
 yyEJ  (MISSING=100)  .
END IF .

DO IF (EJ6 = 1) .
RECODE
 yyEJ  (MISSING=97)  .
  \D IF .


IF (agua = 1 ) yyagua = 88 .
DO IF (agua = 0 ) .
RECODE
 yyagua  (MISSING=100)  .
END IF .


IF (lava = 1 ) yylava = 56 .
DO IF (lava = 0 ) .
RECODE
 yylava  (MISSING=100)  .
END IF .

IF (refri = 1 ) yyrefri = 66 .
DO IF (refri = 0 ) .
RECODE
 yyrefri  (MISSING=100)  .
END IF .


IF (estgas = 1 ) yyestgas = 70 .
DO IF (estgas = 0 ) .
RECODE
 yyestgas  (MISSING=100)  .
END IF .

IF (vehi = 1 ) yyvehi = 73 .
DO IF (vehi = 0 ) .
RECODE
 yyvehi  (MISSING=100)  .
  \D IF .


FREQUENCIES
 VARIABLES=yyhh1 yyninos yyOCUPJ yyvehi yylava yyEJ yyEDUC yyDEPEN yyrefri yydiscap yyestgas yyaguA yynoasi yytrab .

FREQUENCIES
```

```
VARIABLES=hh1 hh2 hh3 hh4 hh5 hh6 ninos OCUPJ vehi lava EJ1 ej2 ej3 ej4 ej5 ej6 Escj refri discap estgas aguA noasi15 trab15 .

COMPUTE yycalif = yydepen+yyninos+yydiscap+yytrab+yynoasi+yyhh1+yyeduc+yyocupj+yyej+yyagua+yylava+yyrefri+yyestgas+yyvehi
.

*****input medias, luego reemplazar yycalif y dis_1

COMPUTE INPUT=0 .

DO if (sysmis(yyDEPEN)) .
recode yyDEPEN (missing=-73.24) .
recode INPUT (else= 1) .
end if .

DO if (sysmis(yyNINOS)) .
recode yyNINOS (missing=-5.43) .
recode INPUT (else= 1) .
end if .

DO if (sysmis(yytrab)) .
recode yytrab (missing=-6.67) .
recode INPUT (else= 1) .
end if .

do if (sysmis(YYNOASI)) .
recode YYNOASI (missing=-0.53) .
recode input (else=1) .
end if .

do if (sysmis(YYHH1)) .
recode YYHH1 (missing=52) .
recode input (else=1) .
end if .

do if (sysmis(YYLAVA)) .
recode YYLAVA (missing=56.77) .
recode input (else=1) .
end if .

    if (sysmis(YYOCUPJ)) .
recode YYOCUPJ (missing=58.49) .
recode input (else=1) .
end if .

do if (sysmis(YYEDUC)) .
recode YYEDUC (missing=65.42) .
recode input (else=1) .
end if .

do if (sysmis(YYREFRI)) .
recode YYREFRI (missing=65.59) .
recode input (else=1) .
end if .

do if (sysmis(YYVEHI)) .
recode YYVEHI (missing=54.61) .
recode input (else=1) .
end if .

do if (sysmis(YYESTGAS)) .
recode YYESTGAS (missing=62.25) .
recode input (else=1) .
end if .

do if (sysmis(YYEJ)) .
recode YYEJ (missing=92.75) .
recode input (else=1) .
end if .

do if (sysmis(YYAGUA)) .
recode YYAGUA (missing=92.87) .
recode input (else=1) .
end if .

    if (sysmis(YYDISCAP)) .
recode YYDISCAP (missing=99.5) .
recode input (else=1) .
end if .
```

```
if (sysmis(yycalif)) yycalif = yydepen+yyninos+yydiscap+yytrab+yynoasi+yyhh1+yyeduc+yyocupj+yyej+yyagua+
        yylava+yyrefri+yyestgas+yyvehi .

if (yycalif<=672.6) pobre=1 .

do if (yycalif>672.6) .
code pobre (missing=0) .
end if .

RENAME VARIABLES (YYCALIF=CALIF) .
```

```
*/*/* PUNTAJE DE LA REGION 3
*/*/* FASE 1
*/*/*  MODELO  BB

**********PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3 PUNTAJE PARA LA REGION 3

   Nuevo modelo

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=depen ninos noasi1 trab151 hacina esc ocupj_1  discap  piso_1
 radio tv licua estgas vehi hectie1 ej
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=RAW TABLE crossvalid
 /CLASSIFY=NONMISSING POOLED .


COMPUTE AADEPEN=-35*DEPEN.
COMPUTE AANINOS=-11*NINOS .
COMPUTE AANA15=-18*NOASI1.
COMPUTE AAT15=-14*TRAB151 .
COMPUTE AAHACINA=-2*HACINA .
COMPUTE AAESC=6*ESC .
COMPUTE AAOCUP=23*OCUPJ_1 .
COMPUTE AAPISO=11*PISO_1 .
COMPUTE AAHECTI=2*HECTIE1 .
COMPUTE AAEDAD=1*ej1 .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 87 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=94 .

if (TV=0) AATV = 100.
IF (TV=1) AATV =79  .

IF (LICUA=0) AALICUA= 100.
   (LICUA=1) AALICUA=77 .


IF (ESTGAS=0) AAESTGAS=100 .
IF (ESTGAS=1) AAESTGAS=70 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=68 .

EXECUTE.

FREQUENCIES
 VARIABLES= AADEPEN AANINOS AANA15 AAT15 AAHACINA AAESC  AAOCUP AAPISO  AAHECTI
        AAEDAD  AADISCAP  AARADIO AATV  AALICUA   AAESTGAS  AAVEHI
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANA15)
 | MISSING(AAT15) | MISSING(AAHACINA)  | MISSING(AAESC)
  | MISSING(AAOCUP) | MISSING(AAPISO) | missing(AAHECTI) | missing(AAEDAD) |
     missing(AADISCAP) | missing(AARADIO) | MISSING(AATV) |  MISSING(AALICUA) |
    missing(AAESTGAS) | missing(AAVEHI) ) .
RECODE
 aainput  (0=1)  .
END IF .
EXECUTE .

RECODE  AADEPEN (SYSMIS=-83.17) .
RECODE  AANINOS (SYSMIS=-20.02) .
RECODE  AANA15 (SYSMIS=-1.50).
RECODE  AAT15 (SYSMIS=-1.15).
RECODE  AAHACINA (SYSMIS=-7.58).
  ECODE  AAESC (SYSMIS=18.47).
  CODE  AAOCUP (SYSMIS=.07).
RECODE  AAPISO (SYSMIS=0.26).
RECODE  AAHECTI (SYSMIS=11.28) .
RECODE  AAEDAD (SYSMIS=45.16).
RECODE  AADISCAP (SYSMIS=99.40).
RECODE  AARADIO (SYSMIS=94.99) .
```

```
RECODE  AATV (SYSMIS=87.31).
RECODE  AALICUA (SYSMIS=77.07).
RECODE  AAESTGAS (SYSMIS=77.93) .
RECODE  AAVEHI (SYSMIS=70.28) .

COMPUTE AAcalif = AADEPEN + AANINOS + AANA15 + AAT15 + AAHACINA + AAESC + AAOCUP + AAPISO +
          AAHECTI + AAEDAD +  AADISCAP + AARADIO + AATV + AALICUA   +
           AAESTGAS + AAVEHI .
EXECUTE .

****

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS =.42  .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

***checar el número del discriminante

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
  LTER BY filter_$.
_XECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

**********FILTROS DE SEGUNDA FASE

IF ( (ej<25 & TOTPERs<5) | (ej>64 & totpers<3) ) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .


COMPUTE AACALIF1=AACALIF + viejitos .
EXECUTE .

COMPUTE AApobre = 0 .
DO IF (AAcalif1< 507.1) .
RECODE
AApobre  (0=1)  .
END IF .
EXECUTE .

DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
END IF .
EXECUTE .


 REQUENCIES
  /ARIABLES=AAPOBRE LPNVA .
```

Región 6. Montaña
Fase 2
Modelo yy

El modelo necesita reconstruirse

Región 6. Montaña
Fase 2
Modelo yy

```
IF (DEPEN >= 0 ) xzDEPEN = DEPEN * -17 .

IF (ninos >= 0 ) xzNInos = ninos * -12 .

IF (trab15 >= 0 ) xztrab = trab15 * -23 .

IF (noasi15 >= 0 ) xznoasi = noasi15 * -3 .

IF (hh1 = 1 ) xzhh1 = 100.
DO IF (hh2=1 ) .
RECODE
  xzhh1  (MISSING=78)  .
END IF .
DO IF (hh3=1 ) .
RECODE
  xzhh1  (MISSING=66)  .
END IF .
DO IF (hh4=1 ) .
RECODE
  xzhh1  (MISSING=62)  .
END IF .
DO IF (hh5=1 ) .
RECODE
  xzhh1  (MISSING=60)  .
END IF .
DO IF (hh1=0 & hh2=0 & hh3=0 & hh4=0 & hh5=0) .
RECODE
  xzhh1  (MISSING=58)  .
END IF .


IF (ESCJ1=1 ) xzeduc = 45 .
  O IF (ESCJ2 = 1 ) .
RECODE
  xzeduc  (MISSING=48)  .
END IF .
DO IF (ESCJ3= 1 ) .
RECODE
  xzeduc  (MISSING=55)  .
END IF .
DO IF (ESCJ1=0 & ESCJ2=0 & ESCJ3=0 ) .
RECODE
  xzeduc  (MISSING=100)  .
END IF .

if (ocupj0= 1) xzocupj=65.
if (ocupj1=1 ) xzocupj=64.
if (ocupj2=1 ) xzocupj=74.
if (ocupj3_4=1 ) xzocupj=100.
if (ocupj5_9=1 ) xzocupj=54.


IF (EJ1=1 ) xzEJ = 81 .
DO IF (EJ2 = 1 ) .
RECODE
  xzEJ  (MISSING=82)  .
END IF .
DO IF (EJ3 = 1 ) .
RECODE
  xzEJ  (MISSING=86)  .
END IF .
DO IF (EJ4 = 1 ) .
RECODE
  xzEJ  (MISSING=91)  .
  ND IF .
 O IF (EJ5 = 1) .
RECODE
  xzEJ  (MISSING=100)  .
END IF .

DO IF (EJ6 = 1) .
```

```
RECODE
  xzEJ  (MISSING=89)  .
END IF .


IF (agua = 1 ) xzagua = 89 .
DO IF (agua = 0 ) .
RECODE
 xzagua  (MISSING=100)  .
END IF .


IF (piso = 1 ) xzpiso = 75 .
DO IF (piso = 0 ) .
RECODE
  xzpiso  (MISSING=100)  .
END IF .



IF (radio = 1 ) xzradio = 89 .
DO IF (radio = 0 ) .
RECODE
  xzradio (MISSING=100)  .
END IF .


IF (licua = 1 ) xzlicua = 63 .
DO IF (licua = 0 ) .
RECODE
  xzlicua (MISSING=100)  .
END IF .

IF (tv = 1 ) xztv = 76 .
DO IF (tv= 0 ) .
RECODE
  xztv (MISSING=100)  .
END IF .

IF (discap = 1 ) xzdiscap= 93 .
DO IF (discap= 0 ) .
RECODE
  xzdiscap (MISSING=100)  .
END IF .




FREQUENCIES
  VARIABLES=yyhh1 yyninos yyOCUPJ yypiso yylicua yyEJ yyEDUC
   yyDEPEN  yydiscap yytv yynoasi yytrab .

FREQUENCIES
  VARIABLES=licua discap radio aguA refri tv tierra lava estgas .

DESCRIPTIVES
  VARIABLES=yyhh1 yyninos yyOCUPJ yypiso yylicua yyEJ yyEDUC yynoasi
          yyDEPEN  yydiscap yytv  yyradio yytrab yyagua
  /FORMAT=LABELS NOINDEX
  /STATISTICS=MEAN STDDEV MIN MAX
  /SORT=MEAN (A) .


DESCRIPTIVES
  VARIABLES=hacina ninos esc noasi15 trab15
          DEPEN
  /FORMAT=LABELS NOINDEX
  /STATISTICS=MEAN STDDEV MIN MAX
  /SORT=MEAN (A) .



*******input medias, luego reemplazar yycalif y dis_1

COMPUTE INPUT=0 .
```

```
DO if (sysmis(xzDEPEN)) .
recode xzDEPEN (missing=-36.22) .
recode INPUT (else= 1) .
end if .

DO if (sysmis(xzNINOS)) .
recode xzNINOS (missing=-24.65) .
recode INPUT (else= 1) .
end if .

DO if (sysmis(xztrab)) .
recode xztrab (missing=-6.96) .
recode INPUT (else= 1) .
end if .

do if (sysmis(xzNOASI)) .
recode xzNOASI (missing=-0.53) .
recode input (else=1) .
end if .

do if (sysmis(xzHH1)) .
recode xzHH1 (missing=67.01) .
recode input (else=1) .
end if .

do if (sysmis(xzdiscap)) .
recode xzdiscap (missing=99.53) .
recode input (else=1) .
end if .

do if (sysmis(xzOCUPJ)) .
recode xzOCUPJ (missing=69.03) .
recode input (else=1) .
end if .

do if (sysmis(xzEDUC)) .
recode xzEDUC (missing=52.01) .
code input (else=1) .
nd if .

do if (sysmis(xzEJ)) .
recode xzEJ (missing=89.72) .
recode input (else=1) .
end if .


do if (sysmis(xztv)) .
recode xztv(missing=82.37) .
recode input (else=1) .
end if .

do if (sysmis(xzlicua)) .
recode xzlicua (missing=69.69) .
recode input (else=1) .
end if .

do if (sysmis(xzpiso)) .
recode xzpiso (missing=81.82) .
recode input (else=1) .
end if .

do if (sysmis(xzradio)) .
recode xzradio (missing=92.96) .
recode input (else=1) .
end if .


do if (sysmis(xzagua)) .
recode xzagua(missing=93.17) .
code input (else=1) .
nd if .



COMPUTE xzcalif = xzdepen+xzninos+xzdiscap+xztrab+xznoasi+xzhh1+xzeduc+xzocupj+xzej
        +xzlicua+xzradio+xztv +xzpiso + xzagua .
```

Región 6. Montaña
Fase 2
Modelo aa

```
SET MXMEMORY = 200000 .
 XECUTE .

DISCRIMINANT
 /GROUPS=lp98 (0 1)
 /VARIABLES= depen  ninos  NOASI1  TRAB151  hacina  esc  ocupj_1  piso_1 ej
 discap licua tv refri  lava vehi pared_1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  = .42 .58
 /STATISTICS=RAW TABLE
 /CLASSIFY=NONMISSING POOLED .


COMPUTE AADEPEN=-18*DEPEN.

COMPUTE AANINOS=-19*NINOS .

COMPUTE AANOASI =-2*NOASI1 .

COMPUTE AATRAB15=-45*TRAB151 .

COMPUTE AAHACINA=-1*HACINA .

COMPUTE AAESC=14*ESC .

COMPUTE AAOCUP=41*OCUPJ_1 .

COMPUTE AAPISO=9*PISO_1 .

COMPUTE AAEDAD=1*EJ .

_OMPUTE AAPARED=17*PARED_1 .


IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 90 .

IF (LICUA=0) AALICUA= 100.
IF (LICUA=1) AALICUA=66 .

if (TV=0) AATV = 100.
IF (TV=1) AATV = 76 .


IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=66 .

IF (LAVA=0) AALAVA=100 .
IF (LAVA=1) AALAVA=67 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=61 .

EXECUTE.

COMPUTE input = 0 .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANOASI)
 | MISSING(AATRAB15) | MISSING(AAHACINA)  | MISSING(AAESC)
  |  MISSING(AAOCUP) | MISSING(AAPISO) | missing(AAEDAD) |
     missing(AAPARED) |  missing(AADISCAP) | MISSING(AALICUA) |
    MISSING(AATV) |  missing(AAREFRI) | missing(AALAVA) | missing(AAVEHI) ) .
  ECODE
  input  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
```

```
  VARIABLES= aadepen aaninos aanoasi aatrab15 aahacina aaesc aaocup aapiso aaedad aapared aadiscap aalicua
        aatv aarefri aalava aavehi
  /STATISTICS=MEAN .

RECODE  AADEPEN (SYSMIS=-48.66).
 ECODE  AANINOS (SYSMIS=-34.19).
.ECODE  AANOASI (SYSMIS=-.30).
RECODE  AATRAB15 (SYSMIS=-2.32).
RECODE  AAHACINA (SYSMIS=-4.00).
RECODE  AAESC (SYSMIS=43.71).
RECODE  AAOCUP (SYSMIS=0.15).
RECODE  AAPISO (SYSMIS=.07).
RECODE  AAEDAD (SYSMIS=47.12).
RECODE  AAPARED (SYSMIS=15.72) .
RECODE  AADISCAP (SYSMIS=99.45).
RECODE  AALICUA (SYSMIS=80.74).
RECODE  AATV (SYSMIS=88.32).
RECODE  AAREFRI (SYSMIS=76.26) .
RECODE  AALAVA (SYSMIS=68.67) .
RECODE  AAVEHI (SYSMIS=62.88) .


COMPUTE AAcalif = AADEPEN + AANINOS + AANOASI + AATRAB15 + AAHACINA + AAESC + AAOCUP + AAPISO +
        AAEDAD +  AAPARED + AADISCAP + AALICUA + AATV  +
    AAREFRI + AALAVA + AAVEHI .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS=.48 .52
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

.SE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.

***Filtro de viejitos

   ( (ej<25 & TOTPERS <5) | (ej>64 & totpers<3) ) viejitos=-100 .
.ECODE  viejitos (SYSMIS=0) .


COMPUTE AACALIF=AACALIF + viejitos .
EXECUTE .
```

```
***La línea de corte

COMPUTE aapobre = 0 .
EXECUTE .
  O IF (aacalif< 502.38) .
.ECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI=0) aapobre = 0.
EXECUTE.

FREQUENCIES
  VARIABLES=lpnva pobre AAPOBRE  .

COMPUTE FECHA = 300698 .

COMPUTE FOPO = 3 .

EXECUTE.


SAVE OUTFILE='e:\PUNTEO\REG_6\reg6j_3.sav'
  /COMPRESSED.



AGGREGATE
 /OUTFILE='E:\punteo\REG_6\AGGR.SAV'
 /BREAK=entidad mpio local folio
 /aapobr_1 = MEAN(aapobre).

GET
 ILE='E:\punteo\REG_6\Aggr.sav'.
XECUTE .

RENAME VARIABLES
        aapobr_1 = aapobre .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\punteo\REG_6\fopo6_10.dbf'
 /TYPE=DB4 /MAP /REPLA.



******filtros para recuperar pobres


IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = - 100 .
IF (RADIO = 1 & ESTGAS = 1 & LICUA = 1) COSINA = - 100 .
RECODE INDISPEN COSINA (SYSMIS = 0) .
```

***** discriminante puntaje vs lpe

```
DISCRIMINANT
 /GROUPS=lpnva(0 1)
 /VARIABLES= xzcalif
    /ANALYSIS ALL
 /PRIORS  EQUAL
/save class
/STATISTICS= raw TABLE
/CLASSIFY=NONMISSING POOLED  .
```

****** encontrar punto de corte

```
EXAMINE
 VARIABLES=xzcalif BY dis_2
 /PLOT NONE
 /STATISTICS DESCRIPTIVES
 /CINTERVAL 95
 /MISSING LISTWISE
 /NOTOTAL.


if (xzcalif<=748) pobrex=1 .

do if (xzcalif>748) .
recode pobrex (missing=0) .
end if .


*** variables extras

if ( agua = 1 & piso = 1 & luz=1 & bao=1) indisp=1.
recode indisp (sysmis=0).

if (indisp=1) yyindisp=-100.
recode yyindisp (sysmis=0).

if (vehi = 0 ) yyvehi=100.
recode yyvehi (sysmis=0).



compute yycalif = yycalif + yyindisp + yyvehi  .


if (xzcalif<=752) pobrez=1 .

do if (xzcalif>752) .
recode pobrez (missing=0) .
end if .

******* quitar pobres con vehiculos

if (pobre =1  & vehi=0) pobre=9.




compute x=1.

*********
```

Región 6. Montaña
Fase 3

```
SET MXMEMORY = 200000 .
.XECUTE

DISCRIMINANT
 /GROUPS=lp98 (0 1)
 /VARIABLES= depen  ninos  NOASI1  TRAB151  hacina  esc  ocupj_1  piso_1 ej
 discap licua  tv  refri  lava  vehi  pared_1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  = .42 .58
 /STATISTICS=RAW TABLE
 /CLASSIFY=NONMISSING POOLED .


COMPUTE AADEPEN=-18*DEPEN.

COMPUTE AANINOS=-19*NINOS .

COMPUTE AANOASI =-2*NOASI1 .

COMPUTE AATRAB15=-45*TRAB151 .

COMPUTE AAHACINA=-1*HACINA .

COMPUTE AAESC=14*ESC .

COMPUTE AAOCUP=41*OCUPJ_1 .

COMPUTE AAPISO=9*PISO_1 .

COMPUTE AAEDAD=1*EJ .

COMPUTE AAPARED=17*PARED_1 .


IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 90 .

IF (LICUA=0) AALICUA= 100.
IF (LICUA=1) AALICUA=66 .

if (TV=0) AATV = 100.
IF (TV=1) AATV = 76 .


IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=66 .

IF (LAVA=0) AALAVA=100 .
IF (LAVA=1) AALAVA=67 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=61 .

EXECUTE.

COMPUTE input = 0 .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANOASI)
 | MISSING(AATRAB15) | MISSING(AAHACINA)  | MISSING(AAESC)
  |  MISSING(AAOCUP) | MISSING(AAPISO) | missing(AAEDAD) |
     missing(AAPARED) |  missing(AADISCAP) | MISSING(AALICUA) |
    MISSING(AATV) |  missing(AAREFRI) | missing(AALAVA) | missing(AAVEHI) ) .
.ECODE
 input  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
```

```
  VARIABLES= aadepen aaninos aanoasi aatrab15 aahacina aaesc aaocup aapiso aaedad aapared aadiscap aalicua
        aatv aarefri aalava aavehi
  /STATISTICS=MEAN .

RECODE  AADEPEN (SYSMIS=-48.66).
RECODE  AANINOS (SYSMIS=-34.19).
RECODE  AANOASI (SYSMIS=-.30).
RECODE  AATRAB15 (SYSMIS=-2.32).
RECODE  AAHACINA (SYSMIS=-4.00).
RECODE  AAESC (SYSMIS=43.71).
RECODE  AAOCUP (SYSMIS=0.15).
RECODE  AAPISO (SYSMIS=.07).
RECODE  AAEDAD (SYSMIS=47.12).
RECODE  AAPARED (SYSMIS=15.72) .
RECODE  AADISCAP (SYSMIS=99.45).
RECODE  AALICUA (SYSMIS=80.74).
RECODE  AATV (SYSMIS=88.32).
RECODE  AAREFRI (SYSMIS=76.26) .
RECODE  AALAVA (SYSMIS=68.67) .
RECODE  AAVEHI (SYSMIS=62.88) .


COMPUTE AAcalif = AADEPEN + AANINOS + AANOASI + AATRAB15 + AAHACINA + AAESC + AAOCUP + AAPISO +
        AAEDAD +  AAPARED + AADISCAP + AALICUA + AATV  +
    AAREFRI + AALAVA + AAVEHI .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS=.48 .52
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.

***filtros

 F ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .

IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = - 100 .
IF (RADIO = 1 & ESTGAS = 1 & LICUA = 1) COSINA = - 100 .

RECODE VIEJITOS INDISPEN COSINA (SYSMIS=0) .
```

```
COMPUTE AACALIF = AACALIF + VIEJITOS + INDISPEN + COSINA .

EXECUTE.

  **La línea de corte

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif< 502.38) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI=0) aapobre = 0.
EXECUTE.

FREQUENCIES
   VARIABLES=AAPOBRE LP98 .

COMPUTE FECHA = 300698 .

COMPUTE FOPO = 3 .

EXECUTE.


SAVE OUTFILE='e:\PUNTEO\REG_6\reg6j_3.sav'
   /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\punteo\REG_6\AGGR.SAV'
  /BREAK=entidad mpio local folio
  /aapobr_1 = MEAN(aapobre).

GET
  FILE='E:\punteo\REG_6\Aggr.sav'.
EXECUTE .

RENAME VARIABLES
         aapobr_1 = aapobre .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\punteo\REG_6\fopo6_10.dbf'
  /TYPE=DB4 /MAP /REPLA.


******filtros para recuperar pobres

IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = - 100 .
IF (RADIO = 1 & ESTGAS = 1 & LICUA = 1) COSINA = - 100 .
RECODE INDISPEN COSINA (SYSMIS = 0) .
```

Región 6. Montaña
Fase 6
Modelo aa

```
 ET MXMEMORY = 200000 .
EXECUTE .

DISCRIMINANT
 /GROUPS=lp98 (0 1)
 /VARIABLES= depen  ninos  NOASI1  TRAB151  hacina  esc  ocupj_1  piso_1  ej
 discap licua  tv  refri  lava  vehi  pared_1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  = .42 .58
 /STATISTICS=RAW TABLE
 /CLASSIFY=NONMISSING POOLED .


COMPUTE AADEPEN=-18*DEPEN.

COMPUTE AANINOS=-19*NINOS .

COMPUTE AANOASI =-2*NOASI1 .

COMPUTE AATRAB15=-45*TRAB151 .

COMPUTE AAHACINA=-1*HACINA .

COMPUTE AAESC=14*ESC .

COMPUTE AAOCUP=41*OCUPJ_1 .

COMPUTE AAPISO=9*PISO_1 .

 OMPUTE AAEDAD=1*EJ .

COMPUTE AAPARED=17*PARED_1 .


IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 90 .

IF (LICUA=0) AALICUA= 100.
IF (LICUA=1) AALICUA=66 .

if (TV=0) AATV = 100.
IF (TV=1) AATV = 76 .


IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=66 .

IF (LAVA=0) AALAVA=100 .
IF (LAVA=1) AALAVA=67 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=61 .

EXECUTE.

COMPUTE input = 0 .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANOASI)
 | MISSING(AATRAB15) | MISSING(AAHACINA)  | MISSING(AAESC)
  |  MISSING(AAOCUP) | MISSING(AAPISO) | missing(AAEDAD) |
     missing(AAPARED) |  missing(AADISCAP) | MISSING(AALICUA) |
    MISSING(AATV) |  missing(AAREFRI) | missing(AALAVA) | missing(AAVEHI) ) .
RECODE
 input  (0=1)  .
END IF .
EXECUTE .
```

```
FREQUENCIES
  VARIABLES= aadepen aaninos aanoasi aatrab15 aahacina aaesc aaocup aapiso aaedad aapared aadiscap aalicua
        aatv aarefri aalava aavehi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

RECODE  AADEPEN (SYSMIS=-21.46).
RECODE  AANINOS (SYSMIS=-15.70).
RECODE  AANOASI (SYSMIS=-0.01).
RECODE  AATRAB15 (SYSMIS=-2.28).
RECODE  AAHACINA (SYSMIS=-2.87).
RECODE  AAESC (SYSMIS=45.65).
RECODE  AAOCUP (SYSMIS=-11.89).
RECODE  AAPISO (SYSMIS=-5.67).
RECODE  AAEDAD (SYSMIS=44.13).
RECODE  AAPARED (SYSMIS=-1.90) .
RECODE  AADISCAP (SYSMIS=99.57).
RECODE  AALICUA (SYSMIS=70.93).
RECODE  AATV (SYSMIS=79.13).
RECODE  AAREFRI (SYSMIS=66.00) .
RECODE  AALAVA (SYSMIS=67.00) .
RECODE  AAVEHI (SYSMIS=61.00) .


COMPUTE aacalif = AADEPEN + AANINOS + AANOASI + AATRAB15 + AAHACINA + AAESC + AAOCUP + AAPISO +
        AAEDAD +  AAPARED + AADISCAP + AALICUA + AATV  +
        AAREFRI + AALAVA + AAVEHI .
EXECUTE .

***filtros

IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .
RECODE VIEJITOS (SYSMIS=0) .

COMPUTE aacalif1 = aacalif + VIEJITOS .

EXECUTE.

***La línea de corte

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 502.38) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI=0) aapobre = 0.
EXECUTE.

FREQUENCIES
  VARIABLES= LP98 aapobre .

COMPUTE FECHA = 981216 .

COMPUTE FOPO = 18 .

EXECUTE.

SAVE OUTFILE='E:\4_5Y6fas\punteo\REG_6\reg6j_18.sav'
  /COMPRESSED.


AGGREGATE
  /OUTFILE='E:\4_5Y6fas\punteo\REG_6\AGGR.SAV'
  /BREAK=entidad mpio local folio
  /aapobre = FIRST(aapobre).

GET
  FILE='E:\4_5Y6fas\punteo\REG_6\Aggr.sav'.
EXECUTE .
```

```
FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\4_5Y6fas\punteo\REG_6\fopo6_18.dbf'
  /TYPE=DB4 /MAP /REPLA.


***LOCS

***crear archivo de control

GET
  FILE='E:\4_5y6fas\PUNTEO\REG_6\reg6j_18.sav'.
EXECUTE .

IF (aapobre = 1) FOLPOB = 1.
IF (aapobre = 1) PERPOB = TOTPER .
RECODE FOLPOB PERPOB (SYSMIS = 0) .

COMPUTE X = 1 .

EXECUTE.

SAVE OUTFILE='E:\4_5y6fas\punteo\REG_6\reg6j_18.sav'
   /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\4_5y6fas\punteo\reg_6\locs6_18.sav'
  /BREAK=entidad mpio local
  /hoglocal = SUM(x) /totper_1 = SUM(totper) /hogpobre = SUM(folpob) /perpob_1 =
  SUM(perpob) /region = FIRST(region) /fecha = FIRST(fecha) / fopo = FIRST(fopo) .

  ET
  FILE='E:\4_5y6fas\punteo\reg_6\locs6_18.sav'.
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\4_5y6fas\PUNTEO\LOCALS\981216\locs6_18.dbf '
    /TYPE=DB4
    /COMPRESSED.

***filtros para recuperar pobres

IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = - 100 .
IF (RADIO = 1 & ESTGAS = 1 & LICUA = 1) COSINA = - 100 .
RECODE INDISPEN COSINA (SYSMIS = 0) .
```

Región 6. Montaña
Fase 6
Modelo bb

```
SET MXMEMORY = 200000 .
 XECUTE .

DISCRIMINANT
 /GROUPS=lp98 (0 1)
 /VARIABLES= depen  ninos  NOASI1  TRAB151  hacina  esc  ocupj_1  piso_1 ej
 discap licua  refri  lava  vehi  pared_1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  = .41 .59
 /STATISTICS=RAW TABLE
 /CLASSIFY=NONMISSING POOLED .


COMPUTE bbDEPEN=-29*DEPEN.

COMPUTE bbNINOS=-23*NINOS .

COMPUTE bbNOASI =-27*NOASI1 .

COMPUTE bbTRAB15=-30*TRAB151 .

COMPUTE bbHACINA=-1*HACINA .

COMPUTE bbESC=9*ESC .

COMPUTE bbOCUP=-37*OCUPJ_1 .

COMPUTE bbPISO=9*PISO_1 .

COMPUTE bbEDAD=1*EJ .

COMPUTE bbPARED=6*PARED_1 .


IF (DISCAP =0) bbDISCAP = 100.
IF (DISCAP =1) bbDISCAP = 69 .

IF (LICUA=0) bbLICUA= 100.
IF (LICUA=1) bbLICUA=81 .

IF (REFRI=0) bbREFRI=100 .
IF (REFRI=1) bbREFRI=91 .

IF (LAVA=0) bbLAVA=100 .
IF (LAVA=1) bbLAVA=59 .

IF (VEHI=0) bbVEHI=100 .
IF (VEHI=1) bbVEHI=56 .

EXECUTE.

COMPUTE input = 0 .
DO IF ( MISSING(bbDEPEN) | MISSING(bbNINOS) | MISSING(bbNOASI)
 | MISSING(bbTRAB15) | MISSING(bbHACINA)  | MISSING(bbESC)
  |  MISSING(bbOCUP) | MISSING(bbPISO) | missing(bbEDAD) |
     missing(bbPARED) |  missing(bbDISCAP) | MISSING(bbLICUA) |
     missing(bbREFRI) | missing(bbLAVA) | missing(bbVEHI) ) .
RECODE
 input  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
 VARIABLES= bbdepen bbninos bbnoasi bbtrab15 bbhacina bbesc bbocup bbpiso bbedad bbpared bbdiscap bblicua
        bbrefri bblava bbvehi
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .
```

```
RECODE  bbDEPEN (SYSMIS=-86.67).
RECODE  bbNINOS (SYSMIS=-41.25).
RECODE  bbNOASI (SYSMIS=-3.91).
RECODE  bbTRAB15 (SYSMIS=-1.51).
 ECODE  bbHACINA (SYSMIS=-3.91).
RECODE  bbESC (SYSMIS=26.81).
RECODE  bbOCUP (SYSMIS=10.53).
RECODE  bbPISO (SYSMIS=.11).
RECODE  bbEDAD (SYSMIS=44.13).
RECODE  bbPARED (SYSMIS=-.4189) .
RECODE  bbDISCAP (SYSMIS=98.25).
RECODE  bbLICUA (SYSMIS=89.22).
RECODE  bbREFRI (SYSMIS=93.38) .
RECODE  bbLAVA (SYSMIS=59.91) .
RECODE  bbVEHI (SYSMIS=58.50) .


COMPUTE bbcalif = bbDEPEN + bbNINOS + bbNOASI + bbTRAB15 + bbHACINA + bbESC + bbOCUP + bbPISO +
        bbEDAD +  bbPARED + bbDISCAP + bbLICUA + bbREFRI + bbLAVA + bbVEHI .
EXECUTE .

***filtros


DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES=bbcalif
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS =.41  .59
 /STATISTICS=raw TABLE crossvalid
 /CLASSIFY=NONMISSING POOLED .

***checar el número del discriminante

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1= 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=bbcalif  /FORMAT=NOTABLE
 /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=bbcalif  /FORMAT=NOTABLE
 /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

**********

 ((ult_niv=4 | ult_niv = 6 | ult_niv = 7) & seg_soc = 2) maestro = 1 .
recode maestro (SYSMIS=0) .

COMPUTE bbpobre = 0 .
EXECUTE .
DO IF (bbcalif< 420.33) .
```

```
RECODE
  bbpobre  (0=1)  .
END IF .

DO IF (bbpobre = 1 &  maestro = 1) .
RECODE
  BBpobre  (1=0)  .
END IF .
EXECUTE .

IF (aapobre = 0 & bbpobre = 1) nvo_pob = 1 .
RECODE nvo_pob (SYSMIS=0) .
EXECUTE .

CROSSTABS
  /TABLES=entidad  BY nvo_pob
  /FORMAT= AVALUE TABLES
  /CELLS= COUNT .
```

Región 6. Montaña
Fase 8
Modelo aa

```
SET MXMEMORY = 200000 .
EXECUTE .

DISCRIMINANT
 /GROUPS=lp98 (0 1)
 /VARIABLES= depen  ninos  NOASI1  TRAB151  hacina  esc  ocupj_1  piso_1 ej
 discap licua tv refri  lava vehi pared_1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  = .42 .58
 /STATISTICS=RAW TABLE
 /CLASSIFY=NONMISSING POOLED .


***Calificación

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-18*DEPEN.

COMPUTE AANINOS=-19*NINOS .

COMPUTE AANOASI =-2*NOASI1 .

COMPUTE AATRAB15=-45*TRAB151 .

COMPUTE AAHACINA=-1*HACINA .

COMPUTE AAESC=14*ESC .

COMPUTE AAOCUP=41*OCUPJ_1 .

COMPUTE AAPISO=9*PISO_1 .

COMPUTE AAEDAD=1*EJ .

COMPUTE AAPARED=17*PARED_1 .


IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 90 .

IF (LICUA=0) AALICUA= 100.
IF (LICUA=1) AALICUA=66 .

if (TV=0) AATV = 100.
IF (TV=1) AATV = 76 .


IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=66 .

IF (LAVA=0) AALAVA=100 .
IF (LAVA=1) AALAVA=67 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=61 .

EXECUTE.

COMPUTE input = 0 .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AANOASI)
 | MISSING(AATRAB15) | MISSING(AAHACINA)  | MISSING(AAESC)
  |  MISSING(AAOCUP) | MISSING(AAPISO) | missing(AAEDAD) |
     missing(AAPARED) |  missing(AADISCAP) | MISSING(AALICUA) |
    MISSING(AATV) |  missing(AAREFRI) | missing(AALAVA) | missing(AAVEHI) ) .
RECODE
```

```
  input  (0=1)  .
 END IF .
 EXECUTE .

 FREQUENCIES
  VARIABLES= aadepen aaninos aanoasi aatrab15 aahacina aaesc aaocup aapiso aaedad aapared aadiscap aalicua
        aatv aarefri aalava aavehi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

 RECODE  AADEPEN (SYSMIS=-45.52).
 RECODE  AANINOS (SYSMIS=-31.25).
 RECODE  AANOASI (SYSMIS=-0.33) .
 RECODE  AATRAB15 (SYSMIS=-3.17).
 RECODE  AAHACINA (SYSMIS=-3.77).
 RECODE  AAESC (SYSMIS=54.11).
 RECODE  AAOCUP (SYSMIS=-7.32).
 RECODE  AAPISO (SYSMIS=-.03).
 RECODE  AAEDAD (SYSMIS=47.57).
 RECODE  AAPARED (SYSMIS=4.36) .
 RECODE  AADISCAP (SYSMIS=99.44).
 RECODE  AALICUA (SYSMIS=81.56).
 RECODE  AATV (SYSMIS=89.13).
 RECODE  AAREFRI (SYSMIS=77.03) .
 RECODE  AALAVA (SYSMIS=68.84) .
 RECODE  AAVEHI (SYSMIS=63.27) .

 COMPUTE AAcalif = AADEPEN + AANINOS + AANOASI + AATRAB15 + AAHACINA + AAESC + AAOCUP + AAPISO +
        AAEDAD +  AAPARED + AADISCAP + AALICUA + AATV  +
     AAREFRI + AALAVA + AAVEHI .
 EXECUTE .

 ***discriminante con la línea de pobreza

 DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvlid
  /CLASSIFY=NONMISSING POOLED .

 USE ALL.
 COMPUTE filter_$=(dis_1 = 0).
 VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
 VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
 FORMAT filter_$ (f1.0).
 FILTER BY filter_$.
 EXECUTE .

 FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

 USE ALL.
 COMPUTE filter_$=(dis_1 = 1).
 VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
 VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
 FORMAT filter_$ (f1.0).
 FILTER BY filter_$.
 EXECUTE .

 FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

 FILTER OFF.
 USE ALL.
 EXECUTE .
```

```
***filtros

IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .
  ECODE VIEJITOS (SYSMIS=0) .

IF ((ult_niv=4 | ult_niv = 6 | ult_niv = 7) & seg_soc = 2) maestro = 1 .
recode maestro (SYSMIS=0) .

COMPUTE AACALIF1 = AACALIF + VIEJITOS .

EXECUTE.

***La línea de corte

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 566.515) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI=0) aapobre = 0.

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) AAPOBRE = 0 .

 XECUTE .

FREQUENCIES
   VARIABLES= LP98 AAPOBRE elimin .

COMPUTE FECHA = 990920 .

COMPUTE FOPO = 25 .

EXECUTE.

SORT CASES BY
  entidad (A) mpio (A) local (A) folio (A) .

SAVE OUTFILE='e:\fase8\punteo\REG_6\reg6j_25.sav'
   /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\fase8\punteo\REG_6\AGGR.SAV'
  /BREAK=entidad mpio local folio
  /aapobre = FIRST(aapobre).

GET
  FILE='E:\fase8\punteo\REG_6\Aggr.sav'.
EXECUTE .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

  \VE TRANSLATE OUTFILE='E:\fase8\PUNTEO\entregas\990920\fopo6_25.dbf '
   /TYPE=DB4
   /COMPRESSED.

***LOCS
```

```
***crear archivo de control

GET
  FILE='E:\fase8\PUNTEO\REG_6\reg6j_25.sav'.
EXECUTE .

IF (aapobre = 1) FOLPOB = 1.
IF (aapobre = 1) PERPOB = TOTPER .
RECODE FOLPOB PERPOB (SYSMIS = 0) .

COMPUTE X = 1 .

EXECUTE.

SAVE OUTFILE='E:\fase8\punteo\REG_6\reg6j_25.sav'
  /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\fase8\punteo\reg_6\locs6_25.sav'
  /BREAK=entidad mpio local
  /hoglocal = SUM(x) /totper_1 = SUM(totper) /hogpobre = SUM(folpob) /perpob_1 =
  SUM(perpob) /region = FIRST(region) /fecha = FIRST(fecha) / fopo = FIRST(fopo) .

GET
  FILE='E:\fase8\punteo\reg_6\locs6_25.sav'.
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\fase8\PUNTEO\LOCALS\990920\locs6_25.dbf '
    /TYPE=DB4
    /COMPRESSED.


***Para verificar hogares analizados y hogares beneficiarios

DESCRIPTIVES
  VARIABLES=hoglocal hogpobre
  /STATISTICS=SUM .

***Para verificar la información de jefes

GET
  FILE='E:\fase8\PUNTEO\REG_6\reg6j_25.sav'.
EXECUTE .

FREQUENCIES
  VARIABLES=peryjef
  /ORDER  ANALYSIS .

***Para verificar la información de personas

GET
  FILE='E:\fase8\PUNTEO\REG_6\reg6p_25.sav'.
EXECUTE .

RENAME VARIABLES
        ent_fed = entidad / munici = mpio / locali = local .

SORT CASES BY
  entidad (A) mpio (A) local (A) folio (A) .

MATCH FILES /FILE=*
 /TABLE='E:\Fase8\Punteo\Reg_6\REG6j_25.sav'
 /RENAME (aacalif aacalif1 aadepen aadiscap aaedad aaesc aahacina aalava
  aalicua aaninos aanoasi aaocup aapared aapiso aarefri aatrab15 aatv aavehi
  adm_gas_ agua1 agua_1 agua_ter agua_viv aguaba1 aguaba_1 anim1 anim2 anim3
  anim4 anim5 anim6 anim7 anim8 animales apo_ing_ asi_esc ate_med_ auto_pro
  bao bao1 bao_1 bao_agua bueyes burros caballos cal_agua camion_p cerdos
  chivos con_inac con_tra conejos conyuge cuan_mur d_r depen dias_tra dif_hog
  disc_ani disc_ens discap edad edo_civ ej ej_1ertr elimin emigro es_ayuda
  es_ciega es_falta es_menta es_muda es_sorda esc estgas fam_bien fam_entr
  fecha folpob fopo gallinas hacina hect_rie hect_tem hectie1 ido_esc ing_hog
  inm15_1 inmh15pc inmp_1 input itmh itmh15 itmh15pe itmh15tp itmh_tpe
```

```
  itmhtper lava leche leer_esc leng_esp leng_mas lengua licua lnin15pc lp98
  luz maestro med_nin_ mot_no_t mu15a49 muro na8a17 nin0a1 nin2a5 nin5a15
  nin6a7 nin8a15 nin_sol ninos no8a17 noasi1 noasi15
 num_dias num_hec num_hog ocupj ocupj1 ocupj_1 pared1 pared_1 per_ayud
  per_cieg per_falt per_ment per_muda per_muri per_ocup per_sord percep perpob
  peryjef piso piso1 piso_1 predios prod_cul radio refri region reses result
  seg_mas seg_soc seguro sexo sit_viv taller techo tierra tit_lech tit_tort
  tocadisc tom_dec_ ton_cos1 ton_cos2 ton_cos3 tortilla tot_anim tot_cuar
  tot_per totper totpers trab trab15 trab151 trab_tem ttem_din ttem_lug
  ttem_mas ttem_mdi ttem_mes tv ult_gra ult_niv v111 v112 v40 v42 v44 v46 v66
  v67 v96 v97 vehi ventila ver_ing_ veritrab vhs viejitos x = d0 d1 d2 d3 d4
  d5 d6 d7 d8 d9 d10 d11 d12 d13 d14 d15 d16 d17 d18 d19 d20 d21 d22 d23 d24
  d25 d26 d27 d28 d29 d30 d31 d32 d33 d34 d35 d36 d37 d38 d39 d40 d41 d42 d43
  d44 d45 d46 d47 d48 d49 d50 d51 d52 d53 d54 d55 d56 d57 d58 d59 d60 d61 d62
  d63 d64 d65 d66 d67 d68 d69 d70 d71 d72 d73 d74 d75 d76 d77 d78 d79 d80 d81
  d82 d83 d84 d85 d86 d87 d88 d89 d90 d91 d92 d93 d94 d95 d96 d97 d98 d99 d100
  d101 d102 d103 d104 d105 d106
 d107 d108 d109 d110 d111 d112 d113 d114 d115 d116 d117 d118 d119 d120 d121
  d122 d123 d124 d125 d126 d127 d128 d129 d130 d131 d132 d133 d134 d135 d136
  d137 d138 d139 d140 d141 d142 d143 d144 d145 d146 d147 d148 d149 d150 d151
  d152 d153 d154 d155 d156 d157 d158 d159 d160 d161 d162 d163 d164 d165 d166
  d167 d168 d169 d170 d171 d172 d173 d174 d175 d176 d177 d178 d179 d180 d181
  d182 d183 d184 d185 d186 d187 d188 d189 d190 d191 d192 d193 d194 d195 d196
  d197 d198 d199 d200 d201)
 /BY entidad mpio local folio
 /DROP= d0 d1 d2 d3 d4 d5 d6 d7 d8 d9 d10 d11 d12 d13 d14 d15 d16 d17 d18 d19
  d20 d21 d22 d23 d24 d25 d26 d27 d28 d29 d30 d31 d32 d33 d34 d35 d36 d37 d38
  d39 d40 d41 d42 d43 d44 d45 d46 d47 d48 d49 d50 d51 d52 d53 d54 d55 d56 d57
  d58 d59 d60 d61 d62 d63 d64 d65 d66 d67 d68 d69 d70 d71 d72 d73 d74 d75 d76
  d77 d78 d79 d80 d81 d82 d83 d84 d85 d86 d87 d88 d89 d90 d91 d92 d93 d94 d95
  d96 d97 d98 d99 d100 d101 d102 d103 d104 d105 d106 d107 d108 d109 d110 d111
  d112 d113 d114 d115 d116 d117 d118
 d119 d120 d121 d122 d123 d124 d125 d126 d127 d128 d129 d130 d131 d132 d133
  d134 d135 d136 d137 d138 d139 d140 d141 d142 d143 d144 d145 d146 d147 d148
  d149 d150 d151 d152 d153 d154 d155 d156 d157 d158 d159 d160 d161 d162 d163
  d164 d165 d166 d167 d168 d169 d170 d171 d172 d173 d174 d175 d176 d177 d178
  d179 d180 d181 d182 d183 d184 d185 d186 d187 d188 d189 d190 d191 d192 d193
  d194 d195 d196 d197 d198 d199 d200 d201.
EXECUTE.

FREQUENCIES
  VARIABLES=AAPOBRE .

***

SAVE OUTFILE='e:\fase8\punteo\REG_6\reg6p_25.sav'
  /COMPRESSED.
```

```
*/*/*/*/        PUNTAJES REGION 8        */*/*/*/*/
*/*/*/                FASE 8                */*/*/*/*/
*/*/*/              UNICO MODELO        */*/*/*/*/

DISCRIMINANT
  /GROUPS=lp98(0 1)
  'VARIABLES=hacina depen ninos ocupj_1 esc mu15a49 trab151 noasi1
                vhs refri vehi lava licua radio estgas tv discap
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42  .58
  /STATISTICS=RAW TABLE  crossvalid
  /CLASSIFY=NONMISSING POOLED .

*** Puntajes Región 8

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AAHACINA=-2*HACINA.
COMPUTE AADEPEN=-46*DEPEN .
COMPUTE AANINOS=-25*NINOS.
COMPUTE AAOCUPJ=-42*OCUPJ_1 .
COMPUTE AAESC=52*ESC .
COMPUTE AAMU15A=10*MU15A49 .
COMPUTE AATRAB=-57*TRAB151 .
COMPUTE AANOASI=-14*NOASI1 .

IF (VHS =0) AAVHS = 100.
IF (VHS =1) AAVHS = 75 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=85 .

if (VEHI=0) AAVEHI = 100.
IF (VEHI=1) AAVEHI =86  .

IF (LAVA=0) AALAVA= 100.
IF (LAVA=1) AALAVA=84 .

   (LICUA =0) AALICUA = 100.
   (LICUA =1) AALICUA = 90 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=94 .

if (ESTGAS=0) AAESTGAS = 100.
IF (ESTGAS=1) AAESTGAS =84  .

IF (TV=0) AATV= 100.
IF (TV=1) AATV=89 .

IF (DISCAP=0) AADISCAP= 100.
IF (DISCAP=1) AADISCAP=80 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= AAHACINA AADEPEN AANINOS AAOCUPJ AAESC AAMU15A AATRAB AANOASI
              AAVHS AAREFRI AAVEHI AALAVA AALICUA AARADIO AAESTGAS AATV AADISCAP
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AAHACINA) | MISSING(AADEPEN) | MISSING(AANINOS)| MISSING(AAOCUPJ) | MISSING(AAESC)
   | MISSING(AAMU15A) | MISSING(AATRAB)  | MISSING(AANOASI)| MISSING(AAVHS) | MISSING(AAREFRI)
   | MISSING(AAVEHI) |  missing(AALAVA)  |  missing(AALICUA) | MISSING(AARADIO) |  MISSING(AAESTGAS)
   | MISSING(AATV) | MISSING(AADISCAP)) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .


***se recodifican los valores perdidos con las medias de las variables

RECODE  AAHACINA (SYSMIS=-5.2940) .
RECODE  AADEPEN (SYSMIS=-103.3956) .
```

```
RECODE  AANINOS (SYSMIS=-37.5886).
RECODE  AAOCUPJ (SYSMIS=2.3241).
RECODE  AAESC (SYSMIS= 185.9680).
RECODE  AAMU15A (SYSMIS=11.2713).
RECODE  AATRAB (SYSMIS=-2.8789).
RECODE  AANOASI (SYSMIS=-1.7226).
 ECODE  AAVHS  (SYSMIS=77.4495) .
 ECODE  AAREFRI (SYSMIS=90.8807).
RECODE  AAVEHI (SYSMIS=89.8533).
RECODE  AALAVA (SYSMIS=87.9514) .
RECODE  AALICUA (SYSMIS=95.0303) .
RECODE  AARADIO (SYSMIS=98.1872).
RECODE  AAESTGAS (SYSMIS=95.7242).
RECODE  AATV (SYSMIS=96.5379).
RECODE  AADISCAP (SYSMIS=98.4042).


COMPUTE AAcalif = AAHACINA + AADEPEN + AANINOS + AAOCUPJ + AAESC + AAMU15A + AATRAB + AANOASI +
        AAVHS + AAREFRI + AAVEHI + AALAVA + AALICUA + AARADIO + AAESTGAS + AATV + AADISCAP  .
EXECUTE .

*** SOLO PARA EL PUNTO DE CORTE **

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42  .58
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

  'EQUENCIES
  /ARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2= 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

******DETERMINADA LA LINEA DE CORTE SEOBTIENEN LOS POBRES

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .

*********1000.2

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 1070.67) .
 ECODE
   obre  (0=1)  .
ND IF .
EXECUTE .

*******Filtro de seguridad social y última pregunta del cuestionario
```

```
IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .
IF (ELIMIN = 1) AAPOBRE = 0 .
EXECUTE .

equencies
variables=aapobre lp98 .
```

```
*/*/*/ PUNTAJE DE LA REGION 8 FASE 4 A 6

***Discriminante con modelo nuevo

DISCRIMINANT
  /GROUPS=lp98(0 1)
  VARIABLES=hacina depen ninos ocupj_1 esc mu15a49 trab151 noasi1
            vhs refri vehi lava licua radio estgas tv discap
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42  .58
  /STATISTICS=RAW TABLE  crossvalid
  /CLASSIFY=NONMISSING POOLED .

*** Puntajes Región 8

COMPUTE AAHACINA=-2*HACINA.
COMPUTE AADEPEN=-46*DEPEN .
COMPUTE AANINOS=-25*NINOS.
COMPUTE AAOCUPJ=-42*OCUPJ_1 .
COMPUTE AAESC=52*ESC .
COMPUTE AAMU15A=10*MU15A49 .
COMPUTE AATRAB=-57*TRAB151 .
COMPUTE AANOASI=-14*NOASI1 .

IF (VHS =0) AAVHS = 100.
IF (VHS =1) AAVHS = 75 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=85 .

if (VEHI=0) AAVEHI = 100.
IF (VEHI=1) AAVEHI =86  .

IF (LAVA=0) AALAVA= 100.
IF (LAVA=1) AALAVA=84 .

IF (LICUA =0) AALICUA = 100.
IF (LICUA =1) AALICUA = 90 .

   (RADIO=0) AARADIO=100 .
.. (RADIO=1) AARADIO=94 .

if (ESTGAS=0) AAESTGAS = 100.
IF (ESTGAS=1) AAESTGAS =84  .

IF (TV=0) AATV= 100.
IF (TV=1) AATV=89 .

IF (DISCAP=0) AADISCAP= 100.
IF (DISCAP=1) AADISCAP=80 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= AAHACINA AADEPEN AANINOS AAOCUPJ AAESC AAMU15A AATRAB AANOASI
             AAVHS AAREFRI AAVEHI AALAVA AALICUA AARADIO AAESTGAS AATV AADISCAP
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AAHACINA) | MISSING(AADEPEN) | MISSING(AANINOS)| MISSING(AAOCUPJ) | MISSING(AAESC)
   | MISSING(AAMU15A) | MISSING(AATRAB)  | MISSING(AANOASI)| MISSING(AAVHS) | MISSING(AAREFRI)
   | MISSING(AAVEHI) |  missing(AALAVA)  |  missing(AALICUA) | MISSING(AARADIO) |  MISSING(AAESTGAS)
   | MISSING(AATV) | MISSING(AADISCAP)) .
RECODE
  input (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

    CODE  AAHACINA (SYSMIS=-4.6654) .
RECODE  AADEPEN (SYSMIS=-110.6081) .
RECODE  AANINOS (SYSMIS=-26.6556).
RECODE  AAOCUPJ (SYSMIS=16.5914).
RECODE  AAESC (SYSMIS=222.1192).
RECODE  AAMU15A (SYSMIS=10.9934).
```

```
RECODE  AATRAB (SYSMIS=-0.3460).
RECODE  AANOASI (SYSMIS=-0.7278).
RECODE  AAVHS  (SYSMIS=77.6490) .
RECODE  AAREFRI (SYSMIS=91.2583).
RECODE  AAVEHI (SYSMIS=89.6159).
RECODE  AALAVA (SYSMIS=87.7086) .
  ECODE  AALICUA (SYSMIS=96.4238) .
.ECODE  AARADIO (SYSMIS=98.5298).
RECODE  AAESTGAS (SYSMIS=96.3974).
RECODE  AATV (SYSMIS=97.7417).
RECODE  AADISCAP (SYSMIS=98.9404).

COMPUTE AAcalif = AAHACINA + AADEPEN + AANINOS + AAOCUPJ + AAESC + AAMU15A + AATRAB + AANOASI +
          AAVHS + AAREFRI + AAVEHI + AALAVA + AALICUA + AARADIO + AAESTGAS + AATV + AADISCAP  .
EXECUTE .

***no**

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42  .58
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

'ISE ALL.
   )MPUTE filter_$=(dis_2= 1).
.ARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

**********se determina la línea de corte y se obtienen los pobres

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 987.84) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

frequencies
'ariables=aapobre lp98 .
```

```
*/*/*/  PUNTAJE DE LA REGION 8,  FASE 3 */*/*/


DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=hacina depen ninos ocupj_1 esc mu15a49 trab151 noasi1
                vhs refri vehi lava licua radio estgas tv discap
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42  .58
  /STATISTICS=RAW TABLE  crossvalid
  /CLASSIFY=NONMISSING POOLED .

*** Puntajes Región 8

COMPUTE AAHACINA=-2*HACINA.
COMPUTE AADEPEN=-46*DEPEN .
COMPUTE AANINOS=-25*NINOS.
COMPUTE AAOCUPJ=-42*OCUPJ_1 .
COMPUTE AAESC=52*ESC .
COMPUTE AAMU15A=10*MU15A49 .
COMPUTE AATRAB=-57*TRAB151 .
COMPUTE AANOASI=-14*NOASI1 .

IF (VHS =0) AAVHS = 100.
IF (VHS =1) AAVHS = 75 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=85 .

if (VEHI=0) AAVEHI = 100.
IF (VEHI=1) AAVEHI =86  .

IF (LAVA=0) AALAVA= 100.
IF (LAVA=1) AALAVA=84 .

IF (LICUA =0) AALICUA = 100.
IF (LICUA =1) AALICUA = 90 .

IF (RADIO=0) AARADIO=100 .
   (RADIO=1) AARADIO=94 .

if (ESTGAS=0) AAESTGAS = 100.
IF (ESTGAS=1) AAESTGAS =84  .

IF (TV=0) AATV= 100.
IF (TV=1) AATV=89 .

IF (DISCAP=0) AADISCAP= 100.
IF (DISCAP=1) AADISCAP=80 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= AAHACINA AADEPEN AANINOS AAOCUPJ AAESC AAMU15A AATRAB AANOASI
                AAVHS AAREFRI AAVEHI AALAVA AALICUA AARADIO AAESTGAS AATV AADISCAP
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .


COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AAHACINA) | MISSING(AADEPEN) | MISSING(AANINOS)| MISSING(AAOCUPJ) | MISSING(AAESC)
   | MISSING(AAMU15A) | MISSING(AATRAB)  | MISSING(AANOASI)| MISSING(AAVHS) | MISSING(AAREFRI)
   | MISSING(AAVEHI) |  missing(AALAVA)  |  missing(AALICUA) | MISSING(AARADIO) |  MISSING(AAESTGAS)
   | MISSING(AATV) | MISSING(AADISCAP)) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

  ECODE  AAHACINA (SYSMIS=-5.23) .
 ECODE  AADEPEN (SYSMIS=-109.8) .
RECODE  AANINOS (SYSMIS=-42.72).
RECODE  AAOCUPJ (SYSMIS=12).
RECODE  AAESC (SYSMIS=166.49).
RECODE  AAMU15A (SYSMIS=10.08).
```

```
RECODE  AATRAB (SYSMIS=-4.13).
RECODE  AANOASI (SYSMIS=-1.74).
RECODE  AAVHS  (SYSMIS=76.42) .
RECODE  AAREFRI (SYSMIS=89.46).
RECODE  AAVEHI (SYSMIS=88.45).
RECODE  AALAVA (SYSMIS=87.61) .
 CODE  AALICUA (SYSMIS=95.46) .
 CODE  AARADIO (SYSMIS=95.63) .
RECODE  AAESTGAS (SYSMIS=94.22).
RECODE  AATV (SYSMIS=96.07).
RECODE  AADISCAP (SYSMIS=98.22).

COMPUTE AAcalif = AAHACINA + AADEPEN + AANINOS + AAOCUPJ + AAESC + AAMU15A + AATRAB + AANOASI +
        AAVHS + AAREFRI + AAVEHI + AALAVA + AALICUA + AARADIO + AAESTGAS + AATV + AADISCAP  .
EXECUTE .


DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES=AAcalif
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42  .58
 /STATISTICS=raw TABLE  CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=AAcalif /FORMAT=NOTABLE
 /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1= 1).
   RIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
  ALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=AAcalif /FORMAT=NOTABLE
 /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

***se determina la línea de corte y se obtienen los pobres

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
 recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .

**********1000.2

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 987.84) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

frequencies
  riables=aapobre lp98 .

****** Recodificación por vehículo EN LA REGION 8 SE TIENEN POBRES CON VEHICULO

DO IF (vehi = 0 & aapobre = 1) .
RECODE
 aapobre  (1=0)  .
```

```
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 aapobre  .
```

```
*/*/*/ PUNTAJES DE LA REGION 8
*/*/* FASE 2
*/*/* SEGUNDO MODELO  AA

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=hacina depen ninos ocupj_1 esc mu15a49 trab151 noasi1
             vhs refri vehi lava licua radio estgas tv discap
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42  .58
  /STATISTICS=RAW TABLE  crossvalid
  /CLASSIFY=NONMISSING POOLED .

*** Puntajes Región 8

COMPUTE AAHACINA=-2*HACINA.
COMPUTE AADEPEN=-46*DEPEN .
COMPUTE AANINOS=-25*NINOS.
COMPUTE AAOCUPJ=-42*OCUPJ_1 .
COMPUTE AAESC=52*ESC .
COMPUTE AAMU15A=10*MU15A49 .
COMPUTE AATRAB=-57*TRAB151 .
COMPUTE AANOASI=-14*NOASI1 .

IF (VHS =0) AAVHS = 100.
IF (VHS =1) AAVHS = 75 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=85 .

if (VEHI=0) AAVEHI = 100.
IF (VEHI=1) AAVEHI =86  .

IF (LAVA=0) AALAVA= 100.
IF (LAVA=1) AALAVA=84 .

IF (LICUA =0) AALICUA = 100.
IF (LICUA =1) AALICUA = 90 .

  (RADIO=0) AARADIO=100 .
  (RADIO=1) AARADIO=94 .

if (ESTGAS=0) AAESTGAS = 100.
IF (ESTGAS=1) AAESTGAS =84  .

IF (TV=0) AATV= 100.
IF (TV=1) AATV=89 .

IF (DISCAP=0) AADISCAP= 100.
IF (DISCAP=1) AADISCAP=80 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= AAHACINA AADEPEN AANINOS AAOCUPJ AAESC AAMU15A AATRAB AANOASI
             AAVHS AAREFRI AAVEHI AALAVA AALICUA AARADIO AAESTGAS AATV AADISCAP
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .


COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AAHACINA) | MISSING(AADEPEN) | MISSING(AANINOS)| MISSING(AAOCUPJ) | MISSING(AAESC)
   | MISSING(AAMU15A) | MISSING(AATRAB)  | MISSING(AANOASI)| MISSING(AAVHS) | MISSING(AAREFRI)
   | MISSING(AAVEHI) |  missing(AALAVA)  |  missing(AALICUA) | MISSING(AARADIO) |  MISSING(AAESTGAS)
   | MISSING(AATV) | MISSING(AADISCAP)) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE  AAHACINA (SYSMIS=-5.23) .
RECODE  AADEPEN (SYSMIS=-109.8) .
RECODE  AANINOS (SYSMIS=-42.72).
RECODE  AAOCUPJ (SYSMIS=12).
RECODE  AAESC (SYSMIS=166.49).
```

```
RECODE  AAMU15A (SYSMIS=10.08).
RECODE  AATRAB (SYSMIS=-4.13).
RECODE  AANOASI (SYSMIS=-1.74).
RECODE  AAVHS  (SYSMIS=76.42) .
RECODE  AAREFRI (SYSMIS=89.46).
RECODE  AAVEHI (SYSMIS=88.45).
RECODE  AALAVA (SYSMIS=87.61) .
RECODE  AALICUA (SYSMIS=95.46) .
RECODE  AARADIO (SYSMIS=95.63) .
RECODE  AAESTGAS (SYSMIS=94.22).
RECODE  AATV (SYSMIS=96.07).
RECODE  AADISCAP (SYSMIS=98.22).

COMPUTE AAcalif = AAHACINA + AADEPEN + AANINOS + AAOCUPJ + AAESC + AAMU15A + AATRAB + AANOASI +
          AAVHS + AAREFRI + AAVEHI + AALAVA + AALICUA + AARADIO + AAESTGAS + AATV + AADISCAP  .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42  .58
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1= 1).
  ARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
  ALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

***se determina la linea de corte y se obtienen los pobres

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .

**********1000.2

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 987.84) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

frequencies
  riables=aapobre lp98 .

   **** Recodificación por vehículo EN LA REGION 8 SE TIENEN POBRES CON VEHICULO

DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
```

```
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 aapobre  .
```

```
*/*/*/ PUNTAJES DE LA REGION 8
*/*/* FASE 2
*/*/*  MODELO  YY

IF (DEPEN >= 0 ) yyDEPEN = DEPEN * -63 .
IF (ninos >= 0 ) yyNInos = ninos * -4 .
   (trab15 >= 0 ) yytrab = trab15 * -92 .
   (noasi15 >= 0 ) yynoasi = noasi15 * -16 .

IF (hh1 = 1 ) yyhh1 = 100.
DO IF (hh2=1 ) .
RECODE
 yyhh1  (MISSING=84)  .
END IF .
DO IF (hh3=1 ) .
RECODE
 yyhh1  (MISSING=72)  .
END IF .
DO IF (hh4=1 ) .
RECODE
 yyhh1  (MISSING=63)  .
END IF .
DO IF (hh5=1 ) .
RECODE
 yyhh1  (MISSING=56)  .
END IF .
DO IF (hh1=0 & hh2=0 & hh3=0 & hh4=0 & hh5=0) .
RECODE
 yyhh1  (MISSING=51)  .
END IF .


IF (ESCJ1=1 ) yyeduc = 61 .
DO IF (ESCJ2 = 1 ) .
RECODE
 yyeduc  (MISSING=67)  .
END IF .
DO IF (ESCJ3= 1 ) .
RECODE
 yyeduc  (MISSING=73)  .
   ID IF .
_O IF (ESCJ1=0 & ESCJ2=0 & ESCJ3=0 ) .
RECODE
 yyeduc  (MISSING=100)  .
END IF .

if (ocupj0= 1) yyocupj=56.
if (ocupj1=1 ) yyocupj=58.
if (ocupj2=1 ) yyocupj=70.
if (ocupj3_4=1 ) yyocupj=100.
if (ocupj5_9=1 ) yyocupj=62.

IF (EJ1=1 ) yyEJ = 78 .
DO IF (EJ2 = 1 ) .
RECODE
 yyEJ  (MISSING=70)  .
END IF .
DO IF (EJ3 = 1 ) .
RECODE
 yyEJ  (MISSING=73)  .
END IF .
DO IF (EJ4 = 1 ) .
RECODE
 yyEJ  (MISSING=82)  .
END IF .
DO IF (EJ5 = 1) .
RECODE
 yyEJ  (MISSING=100)  .
END IF .

DO IF (EJ6 = 1) .
RECODE
 yyEJ  (MISSING=79)  .
END IF .

   (bao = 1 ) yybao = 95 .
DO IF (bao = 0 ) .
RECODE
 yybao  (MISSING=100)  .
END IF .
```

```
IF (piso = 1 ) yypiso = 84 .
DO IF (piso = 0 ) .
RECODE
  yypiso  (MISSING=100)  .
END IF .

   (radio = 1 ) yyradio = 88 .
 O IF (radio = 0 ) .
RECODE
  yyradio (MISSING=100)  .
END IF .

IF (licua = 1 ) yylicua = 87 .
DO IF (licua = 0 ) .
RECODE
  yylicua (MISSING=100)  .
END IF .

IF (tv = 1 ) yytv = 84 .
DO IF (tv= 0 ) .
RECODE
  yytv (MISSING=100)  .
END IF .

IF (discap = 1 ) yydiscap= 78 .
DO IF (discap= 0 ) .
RECODE
  yydiscap (MISSING=100)  .
END IF .

IF (tierra = 1 ) yytierra= 88 .
DO IF (tierra= 0 ) .
RECODE
  yytierra (MISSING=100)  .
END IF .

FREQUENCIES
  VARIABLES=yyhh1 yyninos yyOCUPJ yypiso yylicua yyEJ yyEDUC
   yyDEPEN  yydiscap yytv yynoasi yytrab .

  REQUENCIES
  VARIABLES=licua discap radio bao tv tierra hh1 hh2 hh3 hh4 hh5 hh6 .

DESCRIPTIVES
  VARIABLES=yyhh1 yyninos yyOCUPJ yypiso yylicua yyEJ yyEDUC yynoasi
        yyDEPEN  yydiscap yytv  yyradio yytrab yybao
  /FORMAT=LABELS NOINDEX
  /STATISTICS=MEAN STDDEV MIN MAX
  /SORT=MEAN (A) .

DESCRIPTIVES
  VARIABLES=hacina ninos esc noasi15 trab15
        DEPEN
  /FORMAT=LABELS NOINDEX
  /STATISTICS=MEAN STDDEV MIN MAX
  /SORT=MEAN (A) .

*******input medias, luego reemplazar yycalif y dis_1

COMPUTE INPUT=0 .

DO if (sysmis(yyDEPEN)) .
recode yyDEPEN (missing=-146.23) .
recode INPUT (else= 1) .
end if .

DO if (sysmis(yyNINOS)) .
recode yyNINOS (missing=-4.95) .
recode INPUT (else= 1) .
end if .

DO if (sysmis(yytrab)) .
recode yytrab (missing=-4.88) .
recode INPUT (else= 1) .
nd if .

do if (sysmis(YYNOASI)) .
recode YYNOASI (missing=-2.19) .
recode input (else=1) .
end if .
```

```
do if (sysmis(YYHH1)) .
recode YYHH1 (missing=80.03) .
recode input (else=1) .
end if .

do if (sysmis(YYdiscap)) .
 code YYdiscap (missing=98.56) .
 code input (else=1) .
end if .

do if (sysmis(YYOCUPJ)) .
recode YYOCUPJ (missing=63.31) .
recode input (else=1) .
end if .

do if (sysmis(YYEDUC)) .
recode YYEDUC (missing=75.75) .
recode input (else=1) .
end if .

do if (sysmis(YYEJ)) .
recode YYEJ (missing=81.93) .
recode input (else=1) .
end if .


do if (sysmis(YYtv)) .
recode YYtv(missing=95.92) .
recode input (else=1) .
end if .

do if (sysmis(YYlicua)) .
recode YYlicua (missing=94.6) .
recode input (else=1) .
end if .

do if (sysmis(YYpiso)) .
recode YYpiso (missing=96.64) .
recode input (else=1) .
end if .

do if (sysmis(YYradio)) .
recode YYradio (missing=96.13) .
recode input (else=1) .
end if .

do if (sysmis(YYbao)) .
recode YYbao(missing=95.71) .
recode input (else=1) .
end if .

do if (sysmis(YYtierra)) .
recode YYtierra(missing=90.57) .
recode input (else=1) .
end if .

*** variables extras

if ( piso=1 | agua =1 | luz=1) indisp=1.
recode indisp (sysmis = 0).

if ( refri=1 & estgas=1 & vehi=1 & licua=1 & tv=1 ) enser=1.
recode enser (sysmis=0).

if ( indisp=1 ) yyindisp= -100.
recode yyindisp (sysmis=0).

if ( enser = 1) yyenser= -100.
recode yyenser (sysmis =0).

COMPUTE yycalif = yydepen+yyninos+yydiscap+yytrab+yynoasi+yyhh1+yyeduc+yyocupj+yyej
          +yylicua+yyradio+yytv +yypiso + yybao + yytierra +yyindisp + yyenser.

***** discriminante puntaje vs lpe

 CRIMINANT
/GROUPS=lpnva(0 1)
/VARIABLES= yycalif
  /ANALYSIS ALL
/PRIORS  EQUAL
/save class
```

```
 /STATISTICS= raw TABLE
 /CLASSIFY=NONMISSING POOLED .

****** encontrar punto de corte

EXAMINE
  VARIABLES=yycalif BY dis_1
  /PLOT NONE
  /STATISTICS DESCRIPTIVES
  /CINTERVAL 95
  /MISSING LISTWISE
  /NOTOTAL.

if (yycalif<=819) pobre=1 .

do if (yycalif>819) .
recode pobre (missing=0) .
end if .

compute x=1.
```

```
*/*/*/ PUNTAJE DE LA REGION 3
*/*/*/ FASE 1
*/*/*/  MODELO  YY

* LINEA DE POBREZA

   code ingmesh ingmen15(99999=sysmis) .

compute inmh15pc=(ingmesh-ingmen15)/totpers.

if (sysmis(ingmesh) | sysmis(ingmen15))inmh15pc=999.
recode inmh15pc (999=sysmis).

compute lpNVA=0.
if (inmh15pc <= 286.06) lpNVA=1.
If (sysmis(ingmesh))lpNVA=99.
recode lpNVA (99=sysmis).

* INDICE DE DEPENDENCIA

IF (PERCEP~=0) depen= (totpers-percep)/percep.
IF (PERCEP=0) DEPEN= TOTPERS.

* DISCAPACITADOS

RENAME VARIABLES  (P431=DISCAP) .

*HACINAMIENTO

RECODE P61 (99=SYSMIS).
compute hacina= totpers/p61.

IF (hacina <= 1) hh1 = 1 .
RECODE  hh1  (MISSING=0)  .
IF (hacina >1 & hacina<=2) hh2 = 1 .
RECODE  hh2  (MISSING=0)  .
IF (hacina >2 & hacina<=3) hh3 = 1 .
RECODE  hh3  (MISSING=0)  .
IF (hacina >3 & hacina<=4) hh4 = 1 .
RECODE  hh4  (MISSING=0)  .
   (hacina >4 & hacina<=5) hh5 = 1 .
..ECODE  hh5  (MISSING=0)  .
IF (hacina >5 ) hh6 = 1 .
RECODE  hh6  (MISSING=0)  .

IF (SYSMIS(hacina)) hh1=99.
IF (SYSMIS(hacina)) hh2=99.
IF (SYSMIS(hacina)) hh3=99.
IF (SYSMIS(hacina)) hh4=99.
IF (SYSMIS(hacina)) hh5=99.
IF (SYSMIS(hacina)) hh6=99.

RECODE  hh1 hh2 hh3 hh4 hh5 hh6  (99=SYSMIS) .

* ESCOLARIDAD DEL JEFE

compute esc=escjefe .
if (esccony > escjefe & esccony <99) esc= esccony.

IF (ESC=0) ESCJ1 = 1 .
RECODE  ESCJ1  (MISSING=0)  .
IF (ESC>=1 & ESC<=5) ESCJ2 = 1 .
RECODE  ESCJ2  (MISSING=0)  .
IF (ESC=6) ESCJ3 = 1 .
RECODE  ESCJ3  (MISSING=0)  .
IF (ESC>=7) ESCJ4 = 1 .
RECODE  ESCJ4  (MISSING=0)  .
recode esc (99= sysmis).

IF (SYSMIS(Esc)) EscJ1=99.
IF (SYSMIS(Esc)) EscJ2=99.
IF (SYSMIS(Esc)) EscJ3=99.
IF (SYSMIS(Esc)) EscJ4=99.

IF (ESCJ1=1) ESCJ=1 .
   (ESCJ2=1) ESCJ=2 .
IF (ESCJ3=1) ESCJ=3 .
IF (ESCJ4=1) ESCJ=4 .

RECODE EscJ1 EscJ2 EscJ3 EscJ4  (99=SYSMIS).
```

```
* OCUPACIÓN DEL JEFE

COMPUTE TRAB=0.
IF (P23>=1 & p23<=3 | P24>=1 & p24<=5) trab=1 .
IF ((P23 >=8 | SYSMIS(P23))& (P24 >=8 | SYSMIS(P24))) TRAB=9.
recode trab (9= sysmis).

  code p27 (99=88).
recode  P27 (88=sysmis)  .
compute ocupj= p27.

if (trab = 0 ) ocupj=0.
IF (ocUPJ = 0) OCUPJ0 = 1 .
RECODE  OCUPJ0  (MISSING=0)  .
IF (ocUPJ = 1) OCUPJ1 = 1 .
RECODE  OCUPJ1  (MISSING=0)  .
IF (OCUPJ = 2) OCUPJ2 = 1 .
RECODE  OCUPJ2  (MISSING=0)  .
IF (OCUPJ = 3) OCUPJ3 = 1 .
RECODE  OCUPJ3  (MISSING=0)  .
IF (OCUPJ = 4) OCUPJ4 = 1 .
RECODE  OCUPJ4  (MISSING=0)  .
IF (OCUPJ = 5) OCUPJ5 = 1 .
RECODE  OCUPJ5 (MISSING=0)  .
IF (OCUPJ = 6) OCUPJ6 = 1 .
RECODE  OCUPJ6  (MISSING=0)  .
IF (OCUPJ = 7) OCUPJ7 = 1 .
RECODE  OCUPJ7  (MISSING=0)  .
IF (OCUPJ = 8) OCUPJ8 = 1 .
RECODE  OCUPJ8  (MISSING=0)  .

IF (SYSMIS(OCUPJ)) OCUPJ0=99.
IF (SYSMIS(OCUPJ)) OCUPJ1=99.
IF (SYSMIS(OCUPJ)) OCUPJ2=99.
IF (SYSMIS(OCUPJ)) OCUPJ3=99.
IF (SYSMIS(OCUPJ)) OCUPJ4=99.
IF (SYSMIS(OCUPJ)) OCUPJ5=99.
IF (SYSMIS(OCUPJ)) OCUPJ6=99.
IF (SYSMIS(OCUPJ)) OCUPJ7=99.
IF (SYSMIS(OCUPJ)) OCUPJ8=99.

.ECODE  OCUPJ0  OCUPJ1 OCUPJ2 OCUPJ3 OCUPJ4
     OCUPJ5 OCUPJ6 OCUPJ7 OCUPJ8 OCUPJ0  (99=SYSMIS) .

*EDAD DEL JEFE

compute EJ = p08 .

DO IF (P09<15 | P09>98) .
RECODE EJ (ELSE=SYSMIS) .
END IF .

IF (EJ = 1) EJ1 = 1 .
RECODE  EJ1  (MISSING=0)  .
IF (EJ = 2) EJ2 = 1 .
RECODE  EJ2  (MISSING=0)  .
IF (EJ = 3) EJ3 = 1 .
RECODE  EJ3  (MISSING=0)  .
IF (EJ = 4) EJ4 = 1 .
RECODE  EJ4  (MISSING=0)  .
IF (EJ = 5) EJ5 = 1 .
RECODE  EJ5 (MISSING=0)  .
IF (EJ = 6) EJ6 = 1 .
RECODE  EJ6 (MISSING=0)  .

IF (SYSMIS(EJ)) EJ1=99.
IF (SYSMIS(EJ)) EJ2=99.
IF (SYSMIS(EJ)) EJ3=99.
IF (SYSMIS(EJ)) EJ4=99.
IF (SYSMIS(EJ)) EJ5=99.
IF (SYSMIS(EJ)) EJ6=99.

RECODE EJ1 EJ2 EJ3 EJ4 EJ5 EJ6 (99=SYSMIS).


  RECODIFICACION Y NOMBRE DE VARIABLES

RENAME VARIABLES (P57=AGUA) (P59=PISO)(P432=BAO) (P64_09=LAVA) (P64_05=REFRI) (P64_06=ESTGAS)
          (P64_12=VHS) (P64_15=TELEF) (NINTRAB=TRAB15) (NOASIS=NOASI15).

RECODE AGUA PISO BAO LAVA REFRI ESTGAS VHS TELEF  TRAB15 NOASI15 (9=SYSMIS) .
```

```
* VEHICULO = AUTO O CAMION O CAMIONETA

compute vehi=p64_01.
if (p64_01 = 0 | p64_02 = 0) vehi=0.


  ECODE VEHI (9=SYSMIS).

compute ocupj056=ocupj0  + ocupj5 + ocupj6.

**********************************
FREQUENCIES VARIABLES= depen ninos trab15 NOASI15
       escj1 escj2 escj3
  ocupj0 ocupj1 ocupj2 ocupj3
 ej2 ej3 ej4 ej5 ej6
  piso  refri bao
  vehi lava vhs telef.

DISCRIMINANT
  /GROUPS=lpnva(0 1)
  /VARIABLES=  depen ninos
   hh2 hh3 hh4 hh5 hh6 discap trab15 noasi15
    escj1 escj2 escj3
       ocupj056 ocupj1  ocupj3
   ej2 ej3 ej4 ej5 ej1
    agua
    lava  refri estgas  vehi
  /ANALYSIS ALL
  /PRIORS  EQUAL
 /STATISTICS= raw TABLE
 /CLASSIFY=NONMISSING POOLED  .

****************************************CALIFICACIONES
**reg5

IF (DEPEN >= 0 ) yyDEPEN = DEPEN * -45 .

IF (trab15 >= 0 ) yytrab = trab15 * -73 .

    (noasi15 >= 0 ) yynoasi = noasi15 * -3 .


IF (ESCJ1=1 ) yyeduc = 61 .
DO IF (ESCJ2 = 1 ) .
RECODE
  yyeduc  (MISSING=63)  .
END IF .
DO IF (ESCJ3= 1 ) .
RECODE
  yyeduc  (MISSING=67)  .
END IF .
DO IF (ESCJ1=0 & ESCJ2=0 & ESCJ3=0 ) .
RECODE
  yyeduc  (MISSING=100)  .
END IF .


IF (OCUPJ056=1 ) yyOCUPJ=54 .
DO IF (OCUPJ1=1 ) .
RECODE
  yyOCUPJ  (MISSING=58)  .
END IF .

DO IF (OCUPJ3=1 ) .
RECODE
  yyOCUPJ  (MISSING=70)  .
END IF .
DO IF (OCUPJ056=0 & ocupj1=0 & ocupj3=0) .
RECODE
  yyOCUPJ  (MISSING=100)  .
END IF .


IF (EJ1=1 ) yyEJ = 88 .
    IF (EJ2 = 1 ) .
RECODE
  yyEJ  (MISSING=54)  .
END IF .
DO IF (EJ3 = 1 ) .
RECODE
```

```
  yyEJ  (MISSING=56)  .
END IF .
DO IF (EJ4 = 1 ) .
RECODE
  yyEJ  (MISSING=71)  .
END IF .
   ) IF (EJ5 = 1) .
  ECODE
  yyEJ  (MISSING=100)  .
END IF .

DO IF (EJ6 = 1) .
RECODE
  yyEJ  (MISSING=72)  .
END IF .


IF (tv = 1 ) yytv = 84 .
DO IF (tv = 0 ) .
RECODE
  yyagua  (MISSING=100)  .
END IF .


IF (lava = 1 ) yylava = 84 .
DO IF (lava = 0 ) .
RECODE
  yylava  (MISSING=100)  .
END IF .

IF (refri = 1 ) yyrefri = 66 .
DO IF (refri = 0 ) .
RECODE
  yyrefri  (MISSING=100)  .
END IF .


IF (vehi = 1 ) yyvehi = 66 .
DO IF (vehi = 0 ) .
RECODE
   yvehi  (MISSING=100)  .
_ND IF .

*******input medias, luego reemplazar yycalif y dis_1

COMPUTE INPUT=0 .

DO if (sysmis(yyDEPEN)) .
recode yyDEPEN (missing=-73.24) .
recode INPUT (else= 1) .
end if .

DO if (sysmis(yytrab)) .
recode yytrab (missing=-6.67) .
recode INPUT (else= 1) .
end if .

do if (sysmis(YYLAVA)) .
recode YYLAVA (missing=56.77) .
recode input (else=1) .
end if .

do if (sysmis(YYOCUPJ)) .
recode YYOCUPJ (missing=58.49) .
recode input (else=1) .
end if .

do if (sysmis(YYEDUC)) .
recode YYEDUC (missing=65.42) .
recode input (else=1) .
end if .

do if (sysmis(YYREFRI)) .
recode YYREFRI (missing=65.59) .
  code input (else=1) .
  d if .

do if (sysmis(YYtv)) .
recode YYtv (missing=65.59) .
recode input (else=1) .
end if .
```

```
do if (sysmis(YYVEHI)) .
recode YYVEHI (missing=54.61) .
recode input (else=1) .
end if .

   if (sysmis(YYEJ)) .
  code YYEJ (missing=92.75) .
recode input (else=1) .
end if .

yycalif = yydepen+yytrab+yyeduc+yyocupj+yyej+yytv+
          yylava+yyrefri+yyvehi .

if (yycalif<=447.5) pobre=1 .

do if (yycalif>447.5) .
recode pobre (missing=0) .
end if .

RENAME VARIABLES (YYCALIF=CALIF) .

SAVE TRANSLATE OUTFILE='C:\NUEVA\REG5NVA\REG5cali.DBF'
 /TYPE=DB4
 /KEEP=FOLIO ENTIDAD MPIO LOCAL REGION mu15a49 nin0a2 nin3a5 nio6a9 nia6a9 no10a12 na10a12
     no13a16 na13a16 DEPEN NINOS DISCAP TRAB15 NOASI15 HH1 HH2 HH3 HH4 HH5 HH6
     ESCJ1 ESCJ2 ESCJ3 ESCJ4 OCUPJ056 OCUPJ1 OCUPJ2 OCUPJ3 EJ1 EJ2 EJ3 EJ4 EJ5 EJ6 AGUA LAVA
     REFRI ESTGAS VEHI yydepen yyninos yydiscap yytrab yynoasi yyhh1 yyeduc yyocupj
     yyej yyagua yylava yyrefri yyestgas yyvehi CALIF INPUT POBRE .
```

```
*/*/*/ PUNTAJE DE LA REGION 8
*/*/*/ FASE 1
*/*/*/ MODELO  AA

***Discriminante con modelo nuevo

 !SCRIMINANT
  GROUPS=lp98(0 1)
 /VARIABLES=hacina depen ninos ocupj_1 esc mu15a49 trab151 noasi1
            vhs refri vehi lava licua radio estgas tv discap
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42  .58
 /STATISTICS=RAW TABLE  crossvalid
 /CLASSIFY=NONMISSING POOLED .

*** Puntajes Región 8

COMPUTE AAHACINA=-2*HACINA.
COMPUTE AADEPEN=-46*DEPEN .
COMPUTE AANINOS=-25*NINOS.
COMPUTE AAOCUPJ=-42*OCUPJ_1 .
COMPUTE AAESC=52*ESC .
COMPUTE AAMU15A=10*MU15A49 .
COMPUTE AATRAB=-57*TRAB151 .
COMPUTE AANOASI=-14*NOASI1 .

IF (VHS =0) AAVHS = 100.
IF (VHS =1) AAVHS = 75 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=85 .

if (VEHI=0) AAVEHI = 100.
IF (VEHI=1) AAVEHI =86  .

IF (LAVA=0) AALAVA= 100.
IF (LAVA=1) AALAVA=84 .

IF (LICUA =0) AALICUA = 100.
   (LICUA =1) AALICUA = 90 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=94 .

if (ESTGAS=0) AAESTGAS = 100.
IF (ESTGAS=1) AAESTGAS =84  .

IF (TV=0) AATV= 100.
IF (TV=1) AATV=89 .

IF (DISCAP=0) AADISCAP= 100.
IF (DISCAP=1) AADISCAP=80 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
 VARIABLES= AAHACINA AADEPEN AANINOS AAOCUPJ AAESC AAMU15A AATRAB AANOASI
            AAVHS AAREFRI AAVEHI AALAVA AALICUA AARADIO AAESTGAS AATV AADISCAP
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AAHACINA) | MISSING(AADEPEN) | MISSING(AANINOS)| MISSING(AAOCUPJ) | MISSING(AAESC)
  | MISSING(AAMU15A) | MISSING(AATRAB)  | MISSING(AANOASI)| MISSING(AAVHS) | MISSING(AAREFRI)
  | MISSING(AAVEHI) |  missing(AALAVA)  |  missing(AALICUA) | MISSING(AARADIO) |  MISSING(AAESTGAS)
  | MISSING(AATV) | MISSING(AADISCAP)) .
RECODE
 input  (0=1)  .
END IF .
EXECUTE .

   se recodifican los valores perdidos con las medias de las variables

RECODE  AAHACINA (SYSMIS=-5.23) .
RECODE  AADEPEN (SYSMIS=-109.8) .
RECODE  AANINOS (SYSMIS=-42.72).
RECODE  AAOCUPJ (SYSMIS=12).
```

```
RECODE  AAESC (SYSMIS=166.49).
RECODE  AAMU15A (SYSMIS=10.08).
RECODE  AATRAB (SYSMIS=-4.13).
RECODE  AANOASI (SYSMIS=-1.74).
RECODE  AAVHS  (SYSMIS=76.42) .
RECODE  AAREFRI (SYSMIS=89.46).
   CODE  AAVEHI (SYSMIS=88.45).
  ECODE  AALAVA (SYSMIS=87.61) .
RECODE  AALICUA (SYSMIS=95.46) .
RECODE  AARADIO (SYSMIS=95.63) .
RECODE  AAESTGAS (SYSMIS=94.22).
RECODE  AATV (SYSMIS=96.07).
RECODE  AADISCAP (SYSMIS=98.22).

COMPUTE AAcalif = AAHACINA + AADEPEN + AANINOS + AAOCUPJ + AAESC + AAMU15A + AATRAB + AANOASI +
          AAVHS + AAREFRI + AAVEHI + AALAVA + AALICUA + AARADIO + AAESTGAS + AATV + AADISCAP  .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42  .58
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
   OMPUTE filter_$=(dis_1= 1).
 ARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

***se determina la línea de corte y se obtienen los pobres

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .

*****************1000.2

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 987.84) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

  quencies
    iables=aapobre lp98 .

***** Recodificación por vehículo EN LA REGION 8 SE TIENEN POBRES CON VEHICULO

DO IF (vehi = 0 & aapobre = 1) .
RECODE
```

```
  aapobre  (1=0) .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 aapobre  .
```

Región 9. Campeche Rural
Fase 1
Modelo yy

```
* LINEA DE POBREZA

.ecode ingmesh ingmen15(99999=sysmis) .

compute inmh15pc=(ingmesh-ingmen15)/totpers.

if (sysmis(ingmesh) | sysmis(ingmen15))inmh15pc=999.
recode inmh15pc (999=sysmis).

compute lpNVA=0.
if (inmh15pc <= 286.06) lpNVA=1.
If (sysmis(ingmesh))lpNVA=99.
recode lpNVA (99=sysmis).

* INDICE DE DEPENDENCIA

IF (PERCEP~=0) depen= (totpers-percep)/percep.
IF (PERCEP=0) DEPEN= TOTPERS.

* DISCAPACITADOS

RENAME VARIABLES  (P431=DISCAP) .


*HACINAMIENTO

RECODE P61 (99=SYSMIS).
compute hacina= totpers/p61.

IF (hacina <= 1) hh1 = 1 .
RECODE  hh1  (MISSING=0)  .
 (hacina >1 & hacina<=2) hh2 = 1 .
.ECODE  hh2  (MISSING=0)  .
IF (hacina >2 & hacina<=3) hh3 = 1 .
RECODE  hh3  (MISSING=0)  .
IF (hacina >3 & hacina<=4) hh4 = 1 .
RECODE  hh4  (MISSING=0)  .
IF (hacina >4 & hacina<=5) hh5 = 1 .
RECODE  hh5  (MISSING=0)  .
IF (hacina >5 ) hh6 = 1 .
RECODE  hh6  (MISSING=0)  .

IF (SYSMIS(hacina)) hh1=99.
IF (SYSMIS(hacina)) hh2=99.
IF (SYSMIS(hacina)) hh3=99.
IF (SYSMIS(hacina)) hh4=99.
IF (SYSMIS(hacina)) hh5=99.
IF (SYSMIS(hacina)) hh6=99.

RECODE  hh1 hh2 hh3 hh4 hh5 hh6  (99=SYSMIS) .

* ESCOLARIDAD DEL JEFE

compute esc=escjefe .
if (esccony > escjefe & esccony <99) esc= esccony.

IF (ESC=0) ESCJ1 = 1 .
RECODE  ESCJ1  (MISSING=0)  .
IF (ESC>=1 & ESC<=5) ESCJ2 = 1 .
RECODE  ESCJ2  (MISSING=0)  .
IF (ESC=6) ESCJ3 = 1 .
RECODE  ESCJ3  (MISSING=0)  .
   (ESC>=7) ESCJ4 = 1 .
RECODE  ESCJ4  (MISSING=0)  .
recode esc (99= sysmis).

IF (SYSMIS(Esc)) EscJ1=99.
IF (SYSMIS(Esc)) EscJ2=99.
```

```
IF (SYSMIS(Esc)) EscJ3=99.
IF (SYSMIS(Esc)) EscJ4=99.

IF (ESCJ1=1) ESCJ=1 .
IF (ESCJ2=1) ESCJ=2 .
IF (ESCJ3=1) ESCJ=3 .
IF (ESCJ4=1) ESCJ=4 .

RECODE EscJ1 EscJ2 EscJ3 EscJ4  (99=SYSMIS).

* OCUPACIÓN DEL JEFE

COMPUTE TRAB=0.
IF (P23>=1 & p23<=3 | P24>=1 & p24<=5) trab=1 .
IF ((P23 >=8 | SYSMIS(P23))& (P24 >=8 | SYSMIS(P24))) TRAB=9.
recode trab (9= sysmis).

recode p27 (99=88).
recode  P27 (88=sysmis)  .
compute ocupj= p27.

if (trab = 0 ) ocupj=0.
IF (ocUPJ = 0) OCUPJ0 = 1 .
RECODE  OCUPJ0  (MISSING=0)  .
IF (ocUPJ = 1) OCUPJ1 = 1 .
RECODE  OCUPJ1  (MISSING=0)  .
IF (OCUPJ = 2) OCUPJ2 = 1 .
RECODE  OCUPJ2  (MISSING=0)  .
IF (OCUPJ = 3) OCUPJ3 = 1 .
RECODE  OCUPJ3  (MISSING=0)  .
IF (OCUPJ = 4) OCUPJ4 = 1 .
RECODE  OCUPJ4  (MISSING=0)  .
IF (OCUPJ = 5) OCUPJ5 = 1 .
RECODE  OCUPJ5 (MISSING=0)  .
IF (OCUPJ = 6) OCUPJ6 = 1 .
RECODE  OCUPJ6  (MISSING=0)  .
IF (OCUPJ = 7) OCUPJ7 = 1 .
RECODE  OCUPJ7  (MISSING=0)  .
IF (OCUPJ = 8) OCUPJ8 = 1 .
RECODE  OCUPJ8  (MISSING=0)  .



IF (SYSMIS(OCUPJ)) OCUPJ0=99.
IF (SYSMIS(OCUPJ)) OCUPJ1=99.
IF (SYSMIS(OCUPJ)) OCUPJ2=99.
IF (SYSMIS(OCUPJ)) OCUPJ3=99.
IF (SYSMIS(OCUPJ)) OCUPJ4=99.
IF (SYSMIS(OCUPJ)) OCUPJ5=99.
IF (SYSMIS(OCUPJ)) OCUPJ6=99.
IF (SYSMIS(OCUPJ)) OCUPJ7=99.
IF (SYSMIS(OCUPJ)) OCUPJ8=99.


RECODE  OCUPJ0  OCUPJ1 OCUPJ2 OCUPJ3 OCUPJ4
     OCUPJ5 OCUPJ6 OCUPJ7 OCUPJ8 OCUPJ0  (99=SYSMIS) .


*EDAD DEL JEFE

compute EJ = p08 .

DO IF (P09<15 | P09>98) .
RECODE EJ (ELSE=SYSMIS) .
END IF .

IF (EJ = 1) EJ1 = 1 .
RECODE  EJ1  (MISSING=0)  .
IF (EJ = 2) EJ2 = 1 .
RECODE  EJ2  (MISSING=0)  .
IF (EJ = 3) EJ3 = 1 .
RECODE  EJ3  (MISSING=0)  .
```

```
IF (EJ = 4) EJ4 = 1 .
RECODE  EJ4  (MISSING=0)  .
IF (EJ = 5) EJ5 = 1 .
RECODE  EJ5 (MISSING=0)  .
IF (EJ = 6) EJ6 = 1 .
 ECODE  EJ6 (MISSING=0)  .

IF (SYSMIS(EJ)) EJ1=99.
IF (SYSMIS(EJ)) EJ2=99.
IF (SYSMIS(EJ)) EJ3=99.
IF (SYSMIS(EJ)) EJ4=99.
IF (SYSMIS(EJ)) EJ5=99.
IF (SYSMIS(EJ)) EJ6=99.

RECODE EJ1 EJ2 EJ3 EJ4 EJ5 EJ6 (99=SYSMIS).


* RECODIFICACION Y NOMBRE DE VARIABLES

RENAME VARIABLES (P57=AGUA) (P59=PISO)(P432=BAO) (P64_09=LAVA) (P64_05=REFRI) (P64_06=ESTGAS)
            (P64_12=VHS) (P64_15=TELEF) (NINTRAB=TRAB15) (NOASIS=NOASI15).

RECODE AGUA PISO BAO LAVA REFRI ESTGAS VHS TELEF  TRAB15 NOASI15 (9=SYSMIS) .

* VEHICULO = AUTO O CAMION O CAMIONETA

compute vehi=p64_01.
if (p64_01 = 0 | p64_02 = 0) vehi=0.


RECODE VEHI (9=SYSMIS).

compute ocupj056=ocupj0  + ocupj5 + ocupj6.

**********************************


FREQUENCIES VARIABLES= depen ninos trab15 NOASI15
       escj1 escj2 escj3
  ocupj0 ocupj1 ocupj2 ocupj3
 ej2 ej3 ej4 ej5 ej6
  piso  refri bao
 vehi lava vhs telef.

DISCRIMINANT
 /GROUPS=lpnva(0 1)
 /VARIABLES=  depen ninos
  hh2 hh3 hh4 hh5 hh6 discap trab15 noasi15
   escj1 escj2 escj3
      ocupj056 ocupj1  ocupj3
  ej2 ej3 ej4 ej5 ej1
   agua
   lava  refri estgas  vehi
 /ANALYSIS ALL
 /PRIORS  EQUAL
/STATISTICS= raw TABLE
/CLASSIFY=NONMISSING POOLED  .

**************************************CALIFICACIONES
**reg5

IF (DEPEN >= 0 ) yyDEPEN = DEPEN * -37 .

IF (ninos >= 0 ) yyNInos = ninos * -4 .

IF (discap = 1 ) yydiscap = 75 .
 O IF (discap = 0 ) .
ECODE
 yydiscap  (MISSING=100)  .
END IF .

IF (trab15 >= 0 ) yytrab = trab15 * -63 .
```

```
IF (noasi15 >= 0 ) yynoasi = noasi15 * -2 .

IF (hh1 = 1 ) yyhh1 = 100.
DO IF (hh2=1 ) .
 ECODE
 yyhh1  (MISSING=50)  .
END IF .
DO IF (hh3=1 ) .
RECODE
 yyhh1  (MISSING=47)  .
END IF .
DO IF (hh4=1 ) .
RECODE
 yyhh1  (MISSING=43)  .
END IF .
DO IF (hh5=1 ) .
RECODE
 yyhh1  (MISSING=40)  .
END IF .
DO IF (hh1=0 & hh2=0 & hh3=0 & hh4=0 & hh5=0) .
RECODE
 yyhh1  (MISSING=39)  .
END IF .


IF (ESCJ1=1 ) yyeduc = 79 .
DO IF (ESCJ2 = 1 ) .
RECODE
 yyeduc  (MISSING=82)  .
END IF .
DO IF (ESCJ3= 1 ) .
RECODE
 yyeduc  (MISSING=85)  .
END IF .
 O IF (ESCJ1=0 & ESCJ2=0 & ESCJ3=0 ) .
ECODE
 yyeduc  (MISSING=100)  .
END IF .


IF (OCUPJ056=1 ) yyOCUPJ=44 .
DO IF (OCUPJ1=1 ) .
RECODE
 yyOCUPJ  (MISSING=47)  .
END IF .

DO IF (OCUPJ3=1 ) .
RECODE
 yyOCUPJ  (MISSING=52)  .
END IF .
DO IF (OCUPJ056=0 & ocupj1=0 & ocupj3=0) .
RECODE
 yyOCUPJ  (MISSING=100)  .
END IF .


IF (EJ1=1 ) yyEJ = 70 .
DO IF (EJ2 = 1 ) .
RECODE
 yyEJ  (MISSING=84)  .
END IF .
DO IF (EJ3 = 1 ) .
RECODE
 yyEJ  (MISSING=86)  .
END IF .
 O IF (EJ4 = 1 ) .
ECODE
 yyEJ  (MISSING=88)  .
END IF .
DO IF (EJ5 = 1) .
RECODE
```

```
 yyEJ  (MISSING=100)  .
END IF .

DO IF (EJ6 = 1) .
RECODE
 yyEJ  (MISSING=79)  .
END IF .


IF (agua = 1 ) yyagua = 88 .
DO IF (agua = 0 ) .
RECODE
 yyagua  (MISSING=100)  .
END IF .


IF (lava = 1 ) yylava = 81 .
DO IF (lava = 0 ) .
RECODE
 yylava  (MISSING=100)  .
END IF .

IF (refri = 1 ) yyrefri = 92 .
DO IF (refri = 0 ) .
RECODE
 yyrefri  (MISSING=100)  .
END IF .


IF (estgas = 1 ) yyestgas = 82 .
DO IF (estgas = 0 ) .
RECODE
 yyestgas  (MISSING=100)  .
END IF .


IF (vehi = 1 ) yyvehi = 78 .
DO IF (vehi = 0 ) .
RECODE
 yyvehi  (MISSING=100)  .
END IF .


FREQUENCIES
 VARIABLES=yyhh1 yyninos yyOCUPJ yyvehi yylava yyEJ yyEDUC yyDEPEN yyrefri yydiscap yyestgas yyaguA yynoasi yytrab .

FREQUENCIES
 VARIABLES=hh1 hh2 hh3 hh4 hh5 hh6 ninos OCUPJ vehi lava EJ1 ej2 ej3 ej4 ej5 ej6 Escj refri discap estgas aguA noasi15 trab15
.


COMPUTE yycalif =
yydepen+yyninos+yydiscap+yytrab+yynoasi+yyhh1+yyeduc+yyocupj+yyej+yyagua+yylava+yyrefri+yyestgas+yyvehi .

*******input medias, luego reemplazar yycalif y dis_1

COMPUTE INPUT=0 .

DO if (sysmis(yyDEPEN)) .
recode yyDEPEN (missing=-73.24) .
recode INPUT (else= 1) .
end if .

DO if (sysmis(yyNINOS)) .
recode yyNINOS (missing=-5.43) .
recode INPUT (else= 1) .
 id if .

DO if (sysmis(yytrab)) .
recode yytrab (missing=-6.67) .
recode INPUT (else= 1) .
end if .
```

```
do if (sysmis(YYNOASI)) .
recode YYNOASI (missing=-0.53) .
recode input (else=1) .
end if .

do if (sysmis(YYHH1)) .
recode YYHH1 (missing=52) .
recode input (else=1) .
end if .

do if (sysmis(YYLAVA)) .
recode YYLAVA (missing=56.77) .
recode input (else=1) .
end if .

do if (sysmis(YYOCUPJ)) .
recode YYOCUPJ (missing=58.49) .
recode input (else=1) .
end if .

do if (sysmis(YYEDUC)) .
recode YYEDUC (missing=65.42) .
recode input (else=1) .
end if .

do if (sysmis(YYREFRI)) .
recode YYREFRI (missing=65.59) .
recode input (else=1) .
end if .

do if (sysmis(YYVEHI)) .
recode YYVEHI (missing=54.61) .
recode input (else=1) .
end if .

do if (sysmis(YYESTGAS)) .
recode YYESTGAS (missing=62.25) .
recode input (else=1) .
end if .

do if (sysmis(YYEJ)) .
recode YYEJ (missing=92.75) .
recode input (else=1) .
end if .

do if (sysmis(YYAGUA)) .
recode YYAGUA (missing=92.87) .
recode input (else=1) .
end if .

do if (sysmis(YYDISCAP)) .
recode YYDISCAP (missing=99.5) .
recode input (else=1) .
end if .


if (sysmis(yycalif)) yycalif = yydepen+yyninos+yydiscap+yytrab+yynoasi+yyhh1+yyeduc+yyocupj+yyej+yyagua+
            yylava+yyrefri+yyestgas+yyvehi .

if (yycalif<=738) pobre=1 .

do if (yycalif>738) .
recode pobre (missing=0) .
end if .

RENAME VARIABLES (YYCALIF=CALIF) .
```

Región 9. Campeche Rural
Fase 1
Modelo aa

```
  **puntajes región 9

***discriminante con modelo nuevo

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos noasi1  trab151 hacina esc  ej piso_1 aguaba_1 discap estgas
  ventila lengua vehi
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .



COMPUTE AADEPEN=-28*DEPEN .
COMPUTE AANINOS=-24*NINOS .
COMPUTE AANOASI1=-32*NOASI1 .
COMPUTE AATRAB15 = -52*TRAB151 .
COMPUTE AAHACINA = -10*HACINA .
COMPUTE AAESC = 6*ESC .
COMPUTE AAEJ = 2*EJ .
COMPUTE AAPISO = 7*PISO_1 .
COMPUTE AAAGUAB = 4*AGUABA_1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 91 .

IF (ESTGAS = 0) AAESTGAS = 100 .
 (ESTGAS = 1) AAESTGAS = 62 .

IF (LENGUA = 0) AALENGUA = 100 .
IF (LENGUA = 1) AALENGUA = 93 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 68 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aanoasi1 aatrab15 aahacina aaesc
  aaej aapiso aaaguab aadiscap aaestgas aalengua aavehi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING(aanoasi1) | MISSING (aatrab15)
  | MISSING(aahacina) | MISSING(aaesc)  | MISSING (aaej)
  | MISSING(aapiso) |MISSING(aaaguab) | MISSING(aadiscap) |
  MISSING(aaestgas) |MISSING(aalengua) | MISSING(aavehi)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

  ECODE aadepen  (SYSMIS=-72.14)  .
RECODE aaninos  (SYSMIS=-37.31)  .
RECODE aanoasi1  (SYSMIS=-2.17)  .
RECODE aatrab15  (SYSMIS=-2.09)  .
RECODE aahacina  (SYSMIS=-36.85)  .
RECODE aaesc  (SYSMIS=25.32)  .
```

```
RECODE aaej  (SYSMIS=7.93)  .
RECODE aapiso  (SYSMIS=-2.66)  .
RECODE aaaguab  (SYSMIS=0.01)  .
RECODE aadiscap  (SYSMIS=99.72)  .
RECODE aaestgas  (SYSMIS=74.49)  .
 ECODE aalengua  (SYSMIS=99.07)  .
.ECODE aavehi  (SYSMIS=70.42)  .



***se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aanoasi1+ aatrab15 + aahacina +
  aaesc +  aaej + aapiso + aaaguab + aadiscap + aaestgas + aalengua + aavehi + 93.21 .
EXECUTE .

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=MEAN STDDEV UNIVF BOXM RAW CORR COV GCOV TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2= 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

 REQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


****Filtro

if ((ej<25 & TOTPERS<5) | (ej>65 & TOTPERS <3))  viejitos=-100 .
recode viejitos (sysmis=0) .
execute .

COMPUTE AAcalif= AAcalif + viejitos .
EXECUTE .


***se determina la línea de corte y se obtienen los pobres

COMPUTE aapobre = 0 .
EXECUTE .
```

```
DO IF (aacalif < 451.69) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .


IF (VEHI = 0) AAPOBRE = 0 .
EXECUTE .



FREQUENCIES
   VARIABLES=AAPOBRE LPNVA .

COMPUTE FECHA = 70898 .

COMPUTE FOPO = 9 .

COMPUTE NVOPOB = 0 .
IF (POBRE = 0 & AAPOBRE = 1) NVOPOB = 1.

EXECUTE.

SAVE OUTFILE='K:\SEGUIMIE\BASES\PRIMFASE\REGIONES\Reg9j.sav'
   /COMPRESSED.

AGGREGATE
  /OUTFILE='K:\SEGUIMIE\BASES\PRIMFASE\REGIONES\AGGR9.sav'
  /BREAK=entidad mpio local folio
  /aapobr_1 = MEAN(nvopob).

GET
  FILE='K:\SEGUIMIE\BASES\PRIMFASE\REGIONES\AGGR9.sav'.
EXECUTE .

RENAME VARIABLES
         aapobr_1 = aapobre .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='K:\SEGUIMIE\BASES\PRIMFASE\REGIONES\fopo9_e.dbf'
   /TYPE=DB4 /MAP /REPLA.
```

Región 9. Campeche Rural
Fase 2
Modelo yy

```
DISCRIMINANT
 /GROUPS=lpnva(0 1)
 /VARIABLES= depen ninos noasi15 trab15 hh2 hh3 hh4 hh5 hh6
 escj1 escj2 escj3 ocupj1 ocupj2 ocupj3_4 ocupj5_9 ej2 ej3 ej4 ej5 ej6
 p65_10 tierra discap estgas  radio
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  EQUAL
 /STATISTICS=RAW TABLE
 /CLASSIFY=NONMISSING POOLED .


COMPUTE animales = 1 .
EXECUTE .
DO IF ((p721 >=  15 & p721 <  99) | (p722 >=  15 & p722 <  99) | (p723 >=  15 & p723 <  99)|
(p731 >=  20 & p731 <  99) | (p732 >=  15 & p732 <  99) | (p733 >=  25 & p733 <  99) | (p734 >=  15 & p734 <  99) |
(p735 >=  25 & p735 <  99) ) .
RECODE
 animales  (1=0)  .
END IF .
EXECUTE .

COMPUTE enseres = 0 .
EXECUTE .
DO IF (lava = 1 & refri = 1 & vehi = 1  & licua = 1
      & bao = 1  & agua = 1 & luz = 1
       & tv = 1  & animales = 1) .
RECODE
 enseres  (0=1)  .
END IF .
EXECUTE .

COMPUTE patron = 1 .
EXECUTE .
DO IF (p25=4) .
RECODE
 patron  (1=0)  .
END IF .
EXECUTE .


COMPUTE YYDEPEN=-24*DEPEN.

COMPUTE YYNINOS=-15*NINOS.

COMPUTE YYNOASI=-6*NOASI15.

COMPUTE YYTRAB15=-24*TRAB15.

IF ( HH1 = 1) YYHACINA=100.
IF ( HH2 = 1) YYHACINA=44.
IF ( HH3 = 1) YYHACINA=36.
IF ( HH4 = 1) YYHACINA=34.
IF ( HH5 = 1) YYHACINA=31.
IF ( HH6 = 1 ) YYHACINA=29.



IF ( ESCJ1 = 1) YYESC= 75.
IF ( ESCJ2 = 1) YYESC= 80.
IF ( ESCJ3 = 1) YYESC= 85.
IF ( ESCJ4 = 1) YYESC= 100.

IF (OCUPJ0 = 1) YYOCUP= 65.
IF (OCUPJ1 = 1) YYOCUP= 79.
IF (OCUPJ2 = 1) YYOCUP= 82.
IF (OCUPJ3_4 = 1) YYOCUP = 100.
IF (OCUPJ5_9 = 1) YYOCUP = 74.
```

```
IF (DISCAP = 0) YYDISCAP= 100.
IF (DISCAP = 1) YYDISCAP= 85.

IF (estgas = 0) YYestgas= 100.
IF (estgas = 1) YYestgas= 74.

IF (EJ1 =1) YYEJ= 70.
IF (EJ2 =1) YYEJ= 80.
IF (EJ3 =1) YYEJ= 85.
IF (EJ4 =1) YYEJ= 90.
IF (EJ5 =1) YYEJ= 100.
IF (EJ6 =1) YYEJ= 91.


IF (RADIO =0) YYRADIO = 100.
IF (RADIO =1) YYRADIO = 85.

IF (p65_10 =0) YYventi = 100.
IF (p65_10 =1) YYventi = 80.

IF (tierra=0) YYtierra= 100.
IF (tierra=1) YYtierra= 39.



IF (VEHI=0) YYVEHI= 100.
IF (VEHI=1) YYVEHI= 0.

IF (REFRI=0) YYREFRI= 100.
IF (REFRI=1) YYREFRI= 0.

IF (ANIMALES=0) YYANIM= 100.
IF (ANIMALES=1) YYANIM= 0.



IF (LAVA=0) YYLAVA= 100.
IF (LAVA=1) YYLAVA= 0.

IF (PATRON=0) YYPATRON= 100.
IF (PATRON=1) YYPATRON= 0.

IF (ENSERES=0) YYENSER= 0.
IF (ENSERES=1) YYENSER= -100.



FREQUENCIES
  VARIABLES= yydepen yyninos yynoasi yytrab15 yyhacina yyesc yyocup yydiscap
   yyej yyradio yyestgas yytierra  yyventi yyvehi yyrefri yyanim  yylava yypatron yyenser
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .



COMPUTE input = 0 .
EXECUTE .
DO IF (MISSING(yydepen) | MISSING(yyninos) | MISSING(yynoasi) | MISSING(yytrab15)
  | MISSING(yyhacina) | MISSING(yyesc)  | MISSING(yyocup)
  | MISSING(yydiscap) | MISSING(yyej) | MISSING(yyradio) |
  MISSING(yyestgas) | MISSING(yytierra) | MISSING(yyventi) | MISSING(yyvehi)
   | MISSING(yyrefri)| MISSING(yyanim)| MISSING(yylava)|
   MISSING(yypatron)| MISSING(yyenser) ) .
  ECODE
  input  (0=1)  .
END IF .
EXECUTE .
```

```
RECODE yydepen  (SYSMIS=-48.815) .
RECODE yyninos  (SYSMIS=-29.830) .
RECODE yynoasi  (SYSMIS=-1.237) .
 ECODE yytrab15  (SYSMIS=-4.659) .
.ECODE yyhacina  (SYSMIS=39.418) .
RECODE yyesc  (SYSMIS=82.760) .
RECODE yyocup  (SYSMIS=91.175) .
RECODE yydiscap  (SYSMIS=99.468) .
RECODE yyej  (SYSMIS=87.667) .
RECODE yyradio  (SYSMIS=90.886) .
RECODE yyestgas  (SYSMIS=76.801) .
RECODE yytierra  (SYSMIS=39.364) .
RECODE yyventi  (SYSMIS=83.474) .
RECODE yyvehi  (SYSMIS=5.010) .
RECODE yyrefri  (SYSMIS=11.313) .
RECODE yyanim  (SYSMIS=14.524) .

RECODE yylava  (SYSMIS=5.309) .
RECODE yypatron  (SYSMIS=.149) .
RECODE yyenser  (SYSMIS=-12.556) .


COMPUTE yycalif = yydepen + yyninos + yynoasi + yytrab15 + yyhacina +
  yyesc + yyocup + yydiscap + yyej + yyradio + yyestgas + yytierra
  + yyventi .
EXECUTE .

DISCRIMINANT
  /GROUPS=lpnva(0 1)
  /VARIABLES=yycalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  EQUAL
  /STATISTICS=TABLE
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=yycalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=yycalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

  OMPUTE pobrea = 0 .
execute.
do IF (yycalif < 631.5) .
RECODE
    pobrea (0=1).
end if.
```

```
execute.

compute indisp = 0 .
execute.
do if (luz + agua + piso =3) .
 recode
    indisp (0=1).
end if.
execute.

if (indisp=0) yyindisp = 0 .
if (indisp=1) yyindisp = -50 .


COMPUTE yycalif = yycalif + yyvehi + yyindisp.
EXECUTE .

COMPUTE pobre = 0 .
EXECUTE .
DO IF (yycalif < 631.5) .
RECODE
  pobre  (0=1)  .
END IF .
EXECUTE .

if (pobre=1 & VEHI=0) POBRE=9.
recode (9=sysmis).

MEANS
  TABLES=lpnva agua bao depen discap ej1 ej2 ej3 ej4 ej5 ej6 escj1 escj2 escj3
  escj4 estgas hh1 hh2 hh3 hh4 hh5 hh6 ingmen15 ingmes ingmesh ingmigm
  ingmigr inmh15pc lava licua luz mu15a49 ninos noasi15 ocupj0 ocupj1 ocupj2
  ocupj3_4 ocupj5_9 piso radio refri tierra totpers trab15 tv vehi vhs p65_10 indisp BY
  pobre
  /CELLS MEAN STDDEV COUNT
  /FORMAT= LABELS .

IF (DIS_1=0 & DIS_2=0 & POBRE=0) SECUENCE=1.
IF (DIS_1=0 & DIS_2=0 & POBRE=1) SECUENCE=2.
IF (DIS_1=0 & DIS_2=1 & POBRE=0) SECUENCE=3.
IF (DIS_1=1 & DIS_2=0 & POBRE=0) SECUENCE=4.
IF (DIS_1=0 & DIS_2=1 & POBRE=1) SECUENCE=5.
IF (DIS_1=1 & DIS_2=0 & POBRE=1) SECUENCE=6.
IF (DIS_1=1 & DIS_2=1 & POBRE=0) SECUENCE=7.
IF (DIS_1=1 & DIS_2=1 & POBRE=1) SECUENCE=8.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=0) SECUENCE=9.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=1) SECUENCE=10.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=0) SECUENCE=11.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=1) SECUENCE=12.

FREQUENCIES
  VARIABLES=secuence  pobre pobrea lpnva.
if (pobre=1 & VEHI=0) POBRE=9.
recode (9=sysmis)
```

Región 9. Campeche Rural
Fase 2
Modelo aa

```
***puntajes región 9

COMPUTE AADEPEN=-28*DEPEN .
COMPUTE AANINOS=-24*NINOS .
COMPUTE AANOASI1=-32*NOASI1 .
COMPUTE AATRAB15 = -52*TRAB151 .
COMPUTE AAHACINA = -10*HACINA .
COMPUTE AAESC = 6*ESC .
COMPUTE AAEJ = 2*P08 .
COMPUTE AAPISO = 7*PISO_1 .
COMPUTE AAAGUAB = 4*AGUABA_1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 91 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 62 .

IF (P65_10 = 0) AAVENTIL = 100 .
IF (P65_10 = 1) AAVENTIL =89 .

IF (LENGUA = 0) AALENGUA = 100 .
IF (LENGUA = 1) AALENGUA = 93 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 68 .


EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aanoasi1 aatrab15 aahacina aaesc
  aaej aapiso aaaguab aadiscap aaestgas aaventil aalengua aavehi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING(aanoasi1) | MISSING (aatrab15)
  | MISSING(aahacina) | MISSING(aaesc)  | MISSING (aaej)
  | MISSING(aapiso) |MISSING(aaaguab) | MISSING(aadiscap) |
  MISSING(aaestgas) |MISSING(aaventil) |MISSING(aalengua) | MISSING(aavehi)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS=-59.3905)  .
RECODE aaninos  (SYSMIS=-48.5351)  .
RECODE aanoasi1  (SYSMIS=-2.8228)  .
RECODE aatrab15  (SYSMIS=-4.3438)  .
RECODE aahacina  (SYSMIS=-43.6509)  .
RECODE aaesc  (SYSMIS=23.9647)  .
RECODE aaej  (SYSMIS=83.1209)  .
RECODE aapiso  (SYSMIS=-3.4698)  .
RECODE aaaguab  (SYSMIS=-.2928)  .
RECODE aadiscap  (SYSMIS=99.6726)  .
RECODE aaestgas  (SYSMIS=66.2926)  .
  RECODE aaventil  (SYSMIS=90.8028)  .
RECODE aalengua  (SYSMIS=99.9769)  .
RECODE aavehi  (SYSMIS=69.4494)  .

***se hace la calificación
```

```
COMPUTE aacalif = aadepen + aaninos + aanoasi1+ aatrab15 + aahacina +
  aaesc +  aaej + aapiso + aaaguab + aadiscap + aaestgas + aaventil +
  + aalengua + aavehi .
EXECUTE .

  **discriminante con modelo nuevo

DISCRIMINANT
  /GROUPS=lpnva(0 1)
  /VARIABLES=depen ninos noasi1  trab151 hacina esc  p08 piso_1 aguaba_1 discap estgas
  p65_10 lengua vehi
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LPNVA(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_4 = 0).
VARIABLE LABEL filter_$ 'dis_4 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

  REQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_4 = 1).
VARIABLE LABEL filter_$ 'dis_4 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


***se determina la línea de corte y se obtienen los pobres


COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif < 435.435) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .
```

Región 9. Campeche Rural
Fase 3

```
***puntajes región 9

 **discriminante con modelo nuevo

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=depen ninos noasi1  trab151 hacina esc  ej piso_1 aguaba_1 discap estgas
 ventila lengua vehi
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  .42 .58
 /STATISTICS=RAW TABLE
 /CLASSIFY=NONMISSING POOLED .



COMPUTE AADEPEN=-28*DEPEN .
COMPUTE AANINOS=-24*NINOS .
COMPUTE AANOASI1=-32*NOASI1 .
COMPUTE AATRAB15 = -52*TRAB151 .
COMPUTE AAHACINA = -10*HACINA .
COMPUTE AAESC = 6*ESC .
COMPUTE AAEJ = 2*EJ .
COMPUTE AAPISO = 7*PISO_1 .
COMPUTE AAAGUAB = 4*AGUABA_1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 91 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 62 .

IF (ventila = 0) AAVENTIL = 100 .
IF (ventila = 1) AAVENTIL =89 .

IF (LENGUA = 0) AALENGUA = 100 .
IF (LENGUA = 1) AALENGUA = 93 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 68 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
 VARIABLES= aadepen aaninos aanoasi1 aatrab15 aahacina aaesc
 aaej aapiso aaaguab aadiscap aaestgas aaventil aalengua aavehi
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING(aanoasi1) | MISSING (aatrab15)
 | MISSING(aahacina) | MISSING(aaesc)  | MISSING (aaej)
 | MISSING(aapiso) |MISSING(aaaguab) | MISSING(aadiscap) |
 MISSING(aaestgas) |MISSING(aaventil) |MISSING(aalengua) | MISSING(aavehi)) .
RECODE
 aainput  (0=1)  .
END IF .
EXECUTE .

 **se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS=-63.5951)  .
RECODE aaninos  (SYSMIS=-41.3394)  .
RECODE aanoasi1  (SYSMIS=-3.4331)  .
RECODE aatrab15  (SYSMIS=-1.6538)  .
```

```
RECODE aahacina  (SYSMIS=-34.1375) .
RECODE aaesc  (SYSMIS=22.0596) .
RECODE aaej  (SYSMIS=86.2110) .
RECODE aapiso  (SYSMIS=-0.4529) .
RECODE aaaguab  (SYSMIS=-1.7642) .
 ECODE aadiscap  (SYSMIS=99.7936) .
.ECODE aaestgas  (SYSMIS=70.9771) .
RECODE aaventil  (SYSMIS=91.6239) .
RECODE aalengua  (SYSMIS=99.7592) .
RECODE aavehi  (SYSMIS=69.6881) .



***se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aanoasi1+ aatrab15 + aahacina +
  aaesc +  aaej + aapiso + aaaguab + aadiscap + aaestgas + aaventil +
  + aalengua + aavehi .
EXECUTE .

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=MEAN STDDEV UNIVF BOXM RAW CORR COV GCOV TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2= 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
 ORMAT filter_$ (f1.0).
 ILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


if ((ej<25 & TOTPER<5) | (ej>65 & TOTPER <3))  viejitos=-100 .
recode viejitos (sysmis=0) .
execute .

  (luz=1 & agua1=1 & piso=1) indisp=-100 .
ecode indisp (sysmis=0) .
execute .


COMPUTE AAcalif1= AAcalif + viejitos + indisp.
```

```
EXECUTE .


***se determina la línea de corte y se obtienen los pobres


COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1 < 451.69) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
   VARIABLES=AAPOBRE  lp98 .
```

Región 9. Campeche Rural
Fase 6

```
***puntajes región 9

  **discriminante con modelo nuevo

COMPUTE AADEPEN=-28*DEPEN .
COMPUTE AANINOS=-24*NINOS .
COMPUTE AANOASI1=-32*NOASI1 .
COMPUTE AATRAB15 = -52*TRAB151 .
COMPUTE AAHACINA = -10*HACINA .
COMPUTE AAESC = 6*ESC .
COMPUTE AAEJ = 2*EJ .
COMPUTE AAPISO = 7*PISO_1 .
COMPUTE AAAGUAB = 4*AGUABA_1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 91 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 62 .

IF (ventila = 0) AAVENTIL = 100 .
IF (ventila = 1) AAVENTIL =89 .

IF (LENGUA = 0) AALENGUA = 100 .
IF (LENGUA = 1) AALENGUA = 93 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 68 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

. REQUENCIES
  VARIABLES= aadepen aaninos aanoasi1 aatrab15 aahacina aaesc
  aaej aapiso aaaguab aadiscap aaestgas aaventil aalengua aavehi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING(aanoasi1) | MISSING (aatrab15)
  | MISSING(aahacina) | MISSING(aaesc)  | MISSING (aaej)
  | MISSING(aapiso) |MISSING(aaaguab) | MISSING(aadiscap) |
  MISSING(aaestgas) |MISSING(aaventil) |MISSING(aalengua) | MISSING(aavehi)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS=-57.5078)  .
RECODE aaninos  (SYSMIS=-24.5632)  .
RECODE aanoasi1  (SYSMIS=-1.6265)  .
RECODE aatrab15  (SYSMIS=-0.5898)  .
RECODE aahacina  (SYSMIS=-28.1148)  .
RECODE aaesc  (SYSMIS=29.5668)  .
RECODE aaej  (SYSMIS=94.6449)  .
RECODE aapiso  (SYSMIS=3.0430)  .
RECODE aaaguab  (SYSMIS=-1.0336)  .
RECODE aadiscap  (SYSMIS=99.3827)  .
RECODE aaestgas  (SYSMIS=88.3870)  .
  ECODE aaventil  (SYSMIS=94.8083)  .
RECODE aalengua  (SYSMIS=99.2405)  .
RECODE aavehi  (SYSMIS=72.9365)  .
```

```
***se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aanoasi1+ aatrab15 + aahacina +
  aaesc +  aaej + aapiso + aaaguab + aadiscap + aaestgas + aaventil +
  + aalengua + aavehi .
 XECUTE .

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=MEAN STDDEV UNIVF BOXM RAW CORR COV GCOV TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2= 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
 ORMAT filter_$ (f1.0).
 ILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


if ((ej<25 & TOTPER<5) | (ej>65 & TOTPER <3))  viejitos=-100 .
recode viejitos (sysmis=0) .
execute .

COMPUTE AAcalif1= AAcalif + viejitos.
EXECUTE .



***se determina la línea de corte y se obtienen los pobres


COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1 < 451.69) .
RECODE
  aapobre  (0=1)  .
  ID IF .
 XECUTE .

FREQUENCIES
   VARIABLES=AAPOBRE  lp98 .
```

Región 9. Campeche Rural
Fase 8

```
***discriminante con modelo nuevo

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-28*DEPEN .
COMPUTE AANINOS=-24*NINOS .
COMPUTE AANOASI1=-32*NOASI1 .
COMPUTE AATRAB15 = -52*TRAB151 .
COMPUTE AAHACINA = -10*HACINA .
COMPUTE AAESC = 6*ESC .
COMPUTE AAEJ = 2*EJ .
COMPUTE AAPISO = 7*PISO_1 .
COMPUTE AAAGUAB = 4*AGUABA_1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 91 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 62 .

IF (ventila = 0) AAVENTIL = 100 .
IF (ventila = 1) AAVENTIL =89 .

IF (LENGUA = 0) AALENGUA = 100 .
IF (LENGUA = 1) AALENGUA = 93 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 68 .

EXECUTE.

  **calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aanoasi1 aatrab15 aahacina aaesc
  aaej aapiso aaaguab aadiscap aaestgas aaventil aalengua aavehi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING(aanoasi1) | MISSING (aatrab15)
  | MISSING(aahacina) | MISSING(aaesc)  | MISSING (aaej)
  | MISSING(aapiso) |MISSING(aaaguab) | MISSING(aadiscap) |
  MISSING(aaestgas) |MISSING(aaventil) |MISSING(aalengua) | MISSING(aavehi)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS= -65.8584)  .
RECODE aaninos  (SYSMIS= -37.1289)  .
RECODE aanoasi1  (SYSMIS= -3.4924)  .
RECODE aatrab15  (SYSMIS= -1.6596)  .
RECODE aahacina  (SYSMIS= -36.1220)  .
RECODE aaesc  (SYSMIS= 24.0880)  .
RECODE aaej  (SYSMIS= 86.6519)  .
RECODE aapiso  (SYSMIS= -1.0672)  .
RECODE aaaguab  (SYSMIS= -0.1238)  .
RECODE aadiscap  (SYSMIS= 99.6615)  .
RECODE aaestgas  (SYSMIS= 76.0973)  .
RECODE aaventil  (SYSMIS= 93.1577)  .
RECODE aalengua  (SYSMIS= 99.2871)  .
RECODE aavehi  (SYSMIS= 70.0482)  .
```

```
***se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aanoasi1+ aatrab15 + aahacina +
  aaesc +  aaej + aapiso + aaaguab + aadiscap + aaestgas + aaventil +
  + aalengua + aavehi .
EXECUTE .

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=MEAN STDDEV UNIVF BOXM RAW CORR COV GCOV TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1= 0).
VARIABLE LABEL filter_$ 'dis_1= 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
  ALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
. ORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


if ((ej<25 & TOTPER<5) | (ej>65 & TOTPER <3))  viejitos=-100 .
recode viejitos (sysmis=0) .
execute .

COMPUTE AAcalif1= AAcalif + viejitos.
EXECUTE .


***se determina la línea de corte y se obtienen los pobres

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1 < 428.6) .
RECODE
  aapobre  (0=1)  .
END IF .
  (ECUTE .


*******Filtro de seguridad social y última pregunta del cuestionario

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
```

```
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) AAPOBRE = 0 .

EXECUTE .

FREQUENCIES
  VARIABLES=AAPOBRE lp98 ELIMIN .
```

Región 10. Costa
Fase 3

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=DEPEN   trab151  EJ  esc  bao_1  piso_1
                discap  licua  ventila  radio  refri     vehi  vhs
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42  .58
 /STATISTICS=MEAN STDDEV UNIVF BOXM RAW CORR GCOV TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .


****Puntaje

COMPUTE AADEPEN=-53*DEPEN.
COMPUTE AATRAB15=-100*TRAB151 .
COMPUTE AAEDAD=1*EJ .
COMPUTE AAESC=6*ESC .
COMPUTE AABAO=10*BAO_1 .
COMPUTE AAPISO=14*PISO_1 .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP =73  .

IF (LICUA=0) AALICUA=100 .
IF (LICUA=1) AALICUA=80 .

IF (VENTILA=0) AAVENT=100 .
IF (VENTILA=1) AAVENT=71 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=89 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=85 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=77 .

IF (VHS=0) AAVHS=100 .
IF (VHS=1) AAVHS=77 .

FREQUENCIES
 VARIABLES= AADEPEN  AATRAB15  AAEDAD  AAESC  AABAO  AAPISO
          AADISCAP  AALICUA  AAVENT  AARADIO  AAREFRI    AAVEHI  AAVHS
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .


COMPUTE aainput = 0 .
DO IF ( MISSING(AADEPEN)  | MISSING(AATRAB15) | MISSING(AAEDAD)  | MISSING(AAESC)
  |  MISSING(AABAO) | MISSING(AAPISO) |
     missing(AADISCAP) | missing(AALICUA) | missing(AAVENT) |  missing(AARADIO) | missing(AAREFRI) |
     missing(AAVEHI) | missing(AAVHS)  ) .
RECODE aainput  (0=1)  .
END IF .
EXECUTE .


RECODE  AADEPEN (SYSMIS=-137.08) .
RECODE  AATRAB15 (SYSMIS=-2.71) .
RECODE  AAEDAD (SYSMIS=46.88).
RECODE  AAESC (SYSMIS=23.40) .
RECODE  AABAO (SYSMIS=-1.30) .
RECODE  AAPISO (SYSMIS=-3.64).
RECODE  AADISCAP (SYSMIS=98.94).
RECODE  AALICUA (SYSMIS=89.37) .
RECODE  AAVENT (SYSMIS=79.34) .
RECODE  AARADIO (SYSMIS=95.56).
```

```
RECODE  AAREFRI (SYSMIS=90.49) .
RECODE  AAVEHI (SYSMIS=78.17) .
RECODE  AAVHS (SYSMIS=78.62) .

COMPUTE AAcalif =  AADEPEN + AATRAB15 + AAEDAD  + AAESC + AABAO +  AAPISO  +
           AADISCAP + AALICUA  + AAVENT + AARADIO + AAREFRI   +  AAVEHI + AAVHS  .
_XECUTE .

****Calificación

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
 ALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
 ORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.

EXECUTE .

****Filtro

IF ((TOTPER<=4  & EJ<=24) | (TOTPER<=2  & EJ>=65)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .

COMPUTE AACALIF=AACALIF  + viejitos .

EXECUTE .

***línea de corte

COMPUTE AApobre = 0 .
DO IF (AAcalif< 589.37) .
RECODE AApobre (0=1)  .
END IF .

  (VEHI = 0) AAPOBRE = 0 .
EXECUTE.

FREQUENCIES
  VARIABLES=LP98 AAPOBRE .
```

```
COMPUTE FECHA = 300698 .

COMPUTE FOPO = 3 .

 XECUTE.

SAVE OUTFILE='E:\punteo\REG_10\reg10j_3.sav'
  /COMPRESSED.

AGGREGATE
 /OUTFILE='E:\punteo\REG_10\AGGR.SAV'
 /BREAK=entidad mpio local folio
 /aapobr_1 = MEAN(aapobre).

GET
 FILE='E:\punteo\REG_10\Aggr.sav'.
EXECUTE .

RENAME VARIABLES
        aapobr_1 = aapobre .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\punteo\REG_10\fopo10_3.dbf'
 /TYPE=DB4 /MAP /REPLA.



************************************
**** RECUPERACION DE POBRES  15-ago-'98  *********
************************************************************


*** Se recuperan con el filtro de indispensabe


IF (piso1=1 & aguaba1=1& luz=1) indisp = -100 .
RECODE indisp (sysmis=0) .

COMPUTE bbCALIF=aaCALIF + indisp .
EXECUTE .

COMPUTE bbpobre = 0 .
EXECUTE .
DO IF (bbcalif< 589.37) .
RECODE
   bbpobre  (0=1)  .
END IF .

DO IF (vehi = 0 & bbpobre = 1) .
RECODE
 bbpobre  (1=0)  .
END IF .
EXECUTE .

IF ( aapobre=0 & bbpobre=1) fapobre = 1 .
RECODE fapobre (sysmis=0) .
EXECUTE .



**********************************
 '*******  Se incrementa la linea de corte *******

COMPUTE ccpobre = 0 .
EXECUTE .
DO IF (bbcalif< 648.6) .
RECODE
```

```
   ccpobre  (0=1)  .
END IF .

DO IF (vehi = 0 & ccpobre = 1) .
RECODE
  ccpobre  (1=0)  .
END IF .
EXECUTE .

IF (aapobre=0 & fapobre=0 & ccpobre=1) fbpobre = 1 .
RECODE fbpobre (sysmis=0) .
EXECUTE .


COMPUTE ffpobre = fapobre + fbpobre.
RECODE ffpobre (sysmis=0).

COMPUTE pobre = aapobre + fapobre + fbpobre .
recode pobre (sysmis=0) .

FREQUENCIES
  VARIABLES= pobre .



*** El FOPO de los pobres recuperados  ******


AGGREGATE
  /OUTFILE='E:\punteo\REG_27\aggr1.SAV'
  /BREAK=entidad mpio local folio
  /pobre_1 = MEAN(ffpobre).

GET
  FILE='E:\punteo\REG_27\Aggr1.sav'.
  XECUTE .

RENAME VARIABLES
        pobre_1 = ffpobre .

FILTER OFF.
USE ALL.
SELECT IF(ffpobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\punteo\REG_27\fopo27_3e.dbf'
  /TYPE=DB4 /MAP /REPLA.
```

Región 10. Costa
Fase 6
Modelo aa

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=DEPEN   trab151  EJ  esc  bao_1  piso_1
                discap  licua  ventila  radio  refri     vehi  vhs
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .41  .59
 /STATISTICS=MEAN STDDEV UNIVF BOXM RAW CORR GCOV TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .


**************************************
***********PUNTAJE ********************
**************************************


COMPUTE bbDEPEN=-41*DEPEN.
COMPUTE bbTRAB15=-75*TRAB151 .
COMPUTE bbEDAD=1*EJ .
COMPUTE bbESC=6*ESC .
COMPUTE bbBAO=8*BAO_1 .
COMPUTE bbPISO=2*PISO_1 .

IF (DISCAP =0) bbDISCAP = 100.
IF (DISCAP =1) bbDISCAP =67  .

IF (LICUA=0) bbLICUA=100 .
IF (LICUA=1) bbLICUA=89 .

IF (VENTILA=0) bbVENT=100 .
IF (VENTILA=1) bbVENT=72 .

IF (RADIO=0) bbRADIO=100 .
IF (RADIO=1) bbRADIO=86.

IF (REFRI=0) bbREFRI=100 .
IF (REFRI=1) bbREFRI=81 .

IF (VEHI=0) bbVEHI=100 .
IF (VEHI=1) bbVEHI=58 .

IF (VHS=0) bbVHS=100 .
IF (VHS=1) bbVHS=63 .

FREQUENCIES
 VARIABLES= bbDEPEN  bbTRAB15  bbEDAD  bbESC  bbBAO  bbPISO
          bbDISCAP  bbLICUA  bbVENT  bbRADIO  bbREFRI    bbVEHI  bbVHS
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .


COMPUTE bbinput = 0 .
DO IF ( MISSING(bbDEPEN)  | MISSING(bbTRAB15) | MISSING(bbEDAD)  | MISSING(bbESC)
  |  MISSING(bbBAO) | MISSING(bbPISO) |
     missing(bbDISCAP) | missing(bbLICUA) | missing(bbVENT) |  missing(bbRADIO) | missing(bbREFRI) |
     missing(bbVEHI) | missing(bbVHS)  ) .
RECODE bbinput  (0=1)  .
END IF .
EXECUTE .


RECODE  bbDEPEN (SYSMIS=-114.4589) .
 ECODE  bbTRAB15 (SYSMIS=-1.6518) .
RECODE  bbEDAD (SYSMIS=45.3378).
RECODE  bbESC (SYSMIS=21.8997) .
RECODE  bbBAO (SYSMIS=.1384) .
RECODE  bbPISO (SYSMIS=-.002).
RECODE  bbDISCAP (SYSMIS=98.3028).
```

```
RECODE  bbLICUA (SYSMIS=93.0787) .
RECODE  bbVENT (SYSMIS=80.4509) .
RECODE  bbRADIO (SYSMIS=92.3275).
RECODE  bbREFRI (SYSMIS=86.8312) .
RECODE  bbVEHI (SYSMIS=59.6883) .
 ECODE  bbVHS (SYSMIS=64.5378) .

COMPUTE bbcalif =  bbDEPEN + bbTRAB15 + bbEDAD  + bbESC + bbBAO +  bbPISO  +
          bbDISCAP + bbLICUA  + bbVENT + bbRADIO + bbREFRI   +  bbVEHI + bbVHS  .
EXECUTE .


***discriminante con la línea de pobreza

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES=bbcalif
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  = .41 .59
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

***checar el número del último discriminante

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=bbcalif
 /FORMAT=NOTABLE
 /STATISTICS=MINIMUM .

**********************

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=bbcalif
 /FORMAT=NOTABLE
 /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

***Calificación

IF ((ult_niv=4 | ult_niv = 6 | ult_niv = 7) & seg_soc = 2) maestro = 1 .
recode maestro (SYSMIS=0)

COMPUTE bbpobre = 0 .
EXECUTE .
DO IF (bbcalif< 586.96) .
RECODE
 bbpobre  (0=1)  .
END IF .

DO IF (bbpobre = 1 &  maestro = 1) .
RECODE
 BBpobre  (1=0)  .
```

```
END IF .
EXECUTE .

IF (aapobre = 0 & bbpobre = 1) nvo_pob = 1 .
RECODE nvo_pob (SYSMIS=0) .
 XECUTE .

CROSSTABS
 /TABLES=entidad  BY nvo_pob
 /FORMAT= AVALUE TABLES
 /CELLS= COUNT .




FREQUENCIES
 VARIABLES=lp98 bbpobre .

**********

COMPUTE FECHA1 =060199 .
COMPUTE FOPOB = 1.
EXECUTE.

SAVE OUTFILE='g:\4_5y6fas\punteo\REG_3\reg3j.sav'
  /COMPRESSED.

* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *


AGGREGATE
 /OUTFILE='g:\4_5y6fas\punteo\REG_3\AGGR.SAV'
 /BREAK=entidad mpio local folio
 /nvo_po_1 = MEAN(nvo_pob).

GET
 FILE='g:\4_5y6fas\punteo\REG_3\Aggr.sav'.
EXECUTE .

RENAME VARIABLES
        nvo_po_1 = nvo_pob .

FILTER OFF.
USE ALL.
SELECT IF(nvo_pob = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='g:\4_5y6fas\punteo\reg_3\fopo3_1e.dbf'
 /keep = entidad mpio local folio nvo_pob
 /TYPE=DB4 /MAP /REPLA.




***Filtro

IF ((TOTPER<=4  & EJ<=24) | (TOTPER<=2  & EJ>=65)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .

COMPUTE bbCALIF1=bbCALIF  + viejitos .

EXECUTE .

 **línea de corte

COMPUTE bbpobre = 0 .
DO IF (bbcalif1< 589.37) .
RECODE bbpobre (0=1)  .
END IF .
```

```
IF (VEHI = 0) bbPOBRE = 0 .
EXECUTE.

FREQUENCIES
  VARIABLES=LP98 bbPOBRE .


COMPUTE FECHA = 981216 .

COMPUTE FOPO = 18 .

EXECUTE.
SAVE OUTFILE='E:\4_5y6fas\punteo\REG_10\reg10j20.sav'
  /COMPRESSED.


AGGREGATE
 /OUTFILE='E:\4_5y6fas\punteo\REG_10\AGGR.SAV'
 /BREAK=entidad mpio local folio
 /bbpobr_1 = MEAN(bbpobre).

GET
 FILE='E:\4_5y6fas\punteo\REG_10\Aggr.sav'.
EXECUTE .

RENAME VARIABLES
        bbpobr_1 = bbpobre .

FILTER OFF.
USE ALL.
SELECT IF(bbpobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\4_5y6fas\punteo\REG_10\fopo10_18.dbf'
 'TYPE=DB4 /MAP /REPLA.


***LOCS

***crear archivo de control

GET
 FILE='E:\4_5y6fas\PUNTEO\REG_10\reg10j_18.sav'.
EXECUTE .

IF (bbpobre = 1) FOLPOB = 1.
IF (bbpobre = 1) PERPOB = TOTPER .
RECODE FOLPOB PERPOB (SYSMIS = 0) .

COMPUTE X = 1 .

EXECUTE.

SAVE OUTFILE='E:\4_5y6fas\punteo\REG_10\reg10j_18.sav'
  /COMPRESSED.

AGGREGATE
 /OUTFILE='E:\4_5y6fas\punteo\reg_10\locs10_18.sav'
 /BREAK=entidad mpio local
 /hoglocal = SUM(x) /totper_1 = SUM(totper) /hogpobre = SUM(folpob) /perpob_1 =
 SUM(perpob) /region = FIRST(region) /fecha = FIRST(fecha) / fopo = FIRST(fopo) .

GET
 FILE='E:\4_5y6fas\punteo\reg_10\locs10_18.sav'.
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\4_5y6fas\PUNTEO\LOCALS\981216\locs10_18.dbf '
   /TYPE=DB4
   /COMPRESSED.
```

Región 10. Costa
Fase 6
Modelo bb

```
 ISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=DEPEN   trab151  EJ  esc  bao_1  piso_1
              discap  licua  ventila  radio  refri     vehi  vhs
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42  .58
 /STATISTICS=MEAN STDDEV UNIVF BOXM RAW CORR GCOV TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .


************************************************************
***********PUNTAJE ***************************************
************************************************************


COMPUTE AADEPEN=-53*DEPEN.
COMPUTE AATRAB15=-100*TRAB151 .
COMPUTE AAEDAD=1*EJ .
COMPUTE AAESC=6*ESC .
COMPUTE AABAO=10*BAO_1 .
COMPUTE AAPISO=14*PISO_1 .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP =73  .

IF (LICUA=0) AALICUA=100 .
IF (LICUA=1) AALICUA=80 .

IF (VENTILA=0) AAVENT=100 .
 (VENTILA=1) AAVENT=71 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=89 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=85 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=77 .

IF (VHS=0) AAVHS=100 .
IF (VHS=1) AAVHS=77 .

FREQUENCIES
 VARIABLES= AADEPEN  AATRAB15  AAEDAD  AAESC  AABAO  AAPISO
          AADISCAP  AALICUA  AAVENT  AARADIO  AAREFRI    AAVEHI  AAVHS
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .


COMPUTE aainput = 0 .
DO IF ( MISSING(AADEPEN)  | MISSING(AATRAB15) | MISSING(AAEDAD)  | MISSING(AAESC)
  |  MISSING(AABAO) | MISSING(AAPISO) |
     missing(AADISCAP) | missing(AALICUA) | missing(AAVENT) |  missing(AARADIO) | missing(AAREFRI) |
     missing(AAVEHI) | missing(AAVHS)  ) .
RECODE aainput  (0=1)  .
END IF .
EXECUTE .


 ECODE  AADEPEN (SYSMIS=-186.65) .
RECODE  AATRAB15 (SYSMIS=0) .
RECODE  AAEDAD (SYSMIS=40.37).
RECODE  AAESC (SYSMIS=18.03) .
RECODE  AABAO (SYSMIS=-2.06) .
RECODE  AAPISO (SYSMIS=-1.84).
```

```
RECODE  AADISCAP (SYSMIS=98.38).
RECODE  AALICUA (SYSMIS=86.78) .
RECODE  AAVENT (SYSMIS=71.80) .
RECODE  AARADIO (SYSMIS=92.31).
RECODE  AAREFRI (SYSMIS=87.05) .
 ECODE  AAVEHI (SYSMIS=77.75) .
.ECODE  AAVHS (SYSMIS=77.00) .

COMPUTE AAcalif =  AADEPEN + AATRAB15 + AAEDAD  + AAESC + AABAO +  AAPISO  +
          AADISCAP + AALICUA  + AAVENT + AARADIO + AAREFRI  +  AAVEHI + AAVHS  .
EXECUTE .


***Calificación

***Filtro

IF ((TOTPER<=4  & EJ<=24) | (TOTPER<=2  & EJ>=65)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .

COMPUTE AACALIF1=AACALIF  + viejitos .

EXECUTE .

***línea de corte

COMPUTE AApobre = 0 .
DO IF (AAcalif1< 589.37) .
RECODE AApobre (0=1)  .
END IF .

IF (VEHI = 0) AAPOBRE = 0 .
EXECUTE.

FREQUENCIES
  VARIABLES=LP98 AAPOBRE .


COMPUTE FECHA = 981216 .

COMPUTE FOPO = 18 .

EXECUTE.
SAVE OUTFILE='E:\fase8\punteo\REG_10\reg10j20.sav'
  /COMPRESSED.


AGGREGATE
 /OUTFILE='E:\fase8\punteo\REG_10\AGGR.SAV'
 /BREAK=entidad mpio local folio
 /aapobr_1 = MEAN(aapobre).

GET
 FILE='E:\fase8\punteo\REG_10\Aggr.sav'.
EXECUTE .

RENAME VARIABLES
        aapobr_1 = aapobre .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\fase8\punteo\REG_10\fopo10_18.dbf'
 /TYPE=DB4 /MAP /REPLA.


***LOCS

***crear archivo de control
```

```
GET
  FILE='E:\fase8\PUNTEO\REG_10\reg10j_18.sav'.
EXECUTE .

IF (aapobre = 1) FOLPOB = 1.
 F (aapobre = 1) PERPOB = TOTPER .
RECODE FOLPOB PERPOB (SYSMIS = 0) .

COMPUTE X = 1 .

EXECUTE.

SAVE OUTFILE='E:\fase8\punteo\REG_10\reg10j_18.sav'
   /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\fase8\punteo\reg_10\locs10_18.sav'
  /BREAK=entidad mpio local
  /hoglocal = SUM(x) /totper_1 = SUM(totper) /hogpobre = SUM(folpob) /perpob_1 =
  SUM(perpob) /region = FIRST(region) /fecha = FIRST(fecha) / fopo = FIRST(fopo) .

GET
  FILE='E:\fase8\punteo\reg_10\locs10_18.sav'.
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\fase8\PUNTEO\LOCALS\981216\locs10_18.dbf '
    /TYPE=DB4
    /COMPRESSED.









************************************
**** RECUPERACION DE POBRES  15-ago-'98  *********
************************************************************


*** Se recuperan con el filtro de indispensabe


IF (piso1=1 & aguaba1=1& luz=1) indisp = -100 .
RECODE indisp (sysmis=0) .

COMPUTE bbCALIF=aaCALIF + indisp .
EXECUTE .

COMPUTE bbpobre = 0 .
EXECUTE .
DO IF (bbcalif< 589.37) .
RECODE
    bbpobre  (0=1)  .
  ND IF .

DO IF (vehi = 0 & bbpobre = 1) .
RECODE
  bbpobre  (1=0)  .
END IF .
```

```
EXECUTE .

IF ( aapobre=0 & bbpobre=1) fapobre = 1 .
RECODE fapobre (sysmis=0) .
EXECUTE .



**********************************
*********  Se incrementa la linea de corte *******

COMPUTE ccpobre = 0 .
EXECUTE .
DO IF (bbcalif< 648.6) .
RECODE
   ccpobre  (0=1)  .
END IF .

DO IF (vehi = 0 & ccpobre = 1) .
RECODE
 ccpobre  (1=0)  .
END IF .
EXECUTE .

IF (aapobre=0 & fapobre=0 & ccpobre=1) fbpobre = 1 .
RECODE fbpobre (sysmis=0) .
EXECUTE .


COMPUTE ffpobre = fapobre + fbpobre.
RECODE ffpobre (sysmis=0).

COMPUTE pobre = aapobre + fapobre + fbpobre .
recode pobre (sysmis=0) .

 REQUENCIES
  VARIABLES= pobre .
```

Región 10. Costa
Fase 8

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=DEPEN   trab151   EJ  esc  bao_1  piso_1
                discap  licua   ventila  radio  refri      vehi  vhs
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42  .58
 /STATISTICS=MEAN STDDEV UNIVF BOXM RAW CORR GCOV TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .


************************************************************
**********PUNTAJE ************************************
************************************************************


***Calificación

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-53*DEPEN.
COMPUTE AATRAB15=-100*TRAB151 .
COMPUTE AAEDAD=1*EJ .
COMPUTE AAESC=6*ESC .
COMPUTE AABAO=10*BAO_1 .
COMPUTE AAPISO=14*PISO_1 .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP =73  .

 F (LICUA=0) AALICUA=100 .
.F (LICUA=1) AALICUA=80 .

IF (VENTILA=0) AAVENT=100 .
IF (VENTILA=1) AAVENT=71 .

IF (RADIO=0) AARADIO=100 .
IF (RADIO=1) AARADIO=89 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=85 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=77 .

IF (VHS=0) AAVHS=100 .
IF (VHS=1) AAVHS=77 .

FREQUENCIES
 VARIABLES= AADEPEN  AATRAB15  AAEDAD  AAESC  AABAO  AAPISO
          AADISCAP  AALICUA  AAVENT  AARADIO  AAREFRI     AAVEHI  AAVHS
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .


COMPUTE aainput = 0 .
DO IF ( MISSING(AADEPEN)  | MISSING(AATRAB15) | MISSING(AAEDAD)  | MISSING(AAESC)
  |  MISSING(AABAO) | MISSING(AAPISO) |
     missing(AADISCAP) | missing(AALICUA) | missing(AAVENT) |  missing(AARADIO) | missing(AAREFRI) |
     missing(AAVEHI) | missing(AAVHS)  ) .
RECODE aainput  (0=1)  .
 ND IF .
EXECUTE .


RECODE  AADEPEN (SYSMIS=-129.53) .
RECODE  AATRAB15 (SYSMIS=-3.29) .
```

```
RECODE  AAEDAD (SYSMIS=47.01).
RECODE  AAESC (SYSMIS=24.03) .
RECODE  AABAO (SYSMIS=-.78) .
RECODE  AAPISO (SYSMIS=-1.4582).
RECODE  AADISCAP (SYSMIS=98.87).
 ECODE  AALICUA (SYSMIS=89.90) .
.ECODE  AAVENT (SYSMIS=81.94) .
RECODE  AARADIO (SYSMIS=95.44).
RECODE  AAREFRI (SYSMIS=90.93) .
RECODE  AAVEHI (SYSMIS=78.35) .
RECODE  AAVHS (SYSMIS=79.05) .

COMPUTE AAcalif =  AADEPEN + AATRAB15 + AAEDAD  + AAESC + AABAO +  AAPISO  +
            AADISCAP + AALICUA  + AAVENT + AARADIO + AAREFRI   +  AAVEHI + AAVHS  .
EXECUTE .


**********************************

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

***checar el número del último discriminante

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
 LTER BY filter_$.
XECUTE .

FREQUENCIES             `
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

**********************

***Calificación

***Filtro

   ((TOTPER<=4  & EJ<=24) | (TOTPER<=2  & EJ>=65)) viejitos=-100 .
ECODE  viejitos (SYSMIS=0) .

IF ((ult_niv=4 | ult_niv = 6 | ult_niv = 7) & seg_soc = 2) maestro = 1 .
recode maestro (SYSMIS=0)
```

```
COMPUTE AACALIF1=AACALIF  + viejitos .

EXECUTE .

***línea de corte

COMPUTE AApobre = 0 .
DO IF (AAcalif1< 596) .
RECODE AApobre (0=1)  .
END IF .


IF (VEHI = 0) AAPOBRE = 0 .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) AAPOBRE = 0 .

EXECUTE .

FREQUENCIES
  VARIABLES=LP98 AAPOBRE ELIMIN.


COMPUTE FECHA = 990920 .

COMPUTE FOPO =25 .

EXECUTE.

 ORT CASES BY
 entidad (A) mpio (A) local (A) folio (A) .

SAVE OUTFILE='e:\fase8\punteo\REG_10\reg10j_25.sav'
  /COMPRESSED.

********** para crear el fopo

AGGREGATE
 /OUTFILE='E:\fase8\punteo\REG_10\AGGR.SAV'
 /BREAK=entidad mpio local folio
 /aapobre = FIRST(aapobre).

GET
 FILE='E:\fase8\punteo\REG_10\Aggr.sav'.
EXECUTE .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\fase8\PUNTEO\entregas\990920\fopo10_25.dbf '
   /TYPE=DB4
   /COMPRESSED.

***LOCS

***crear archivo de control

GET
 FILE='E:\fase8\PUNTEO\REG_10\reg10j_25.sav'.
EXECUTE .

IF (aapobre = 1) FOLPOB = 1.
IF (aapobre = 1) PERPOB = TOTPER .
RECODE FOLPOB PERPOB (SYSMIS = 0) .
```

```
COMPUTE X = 1 .

EXECUTE.

 AVE OUTFILE='E:\fase8\punteo\REG_10\reg10j_25.sav'
  /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\fase8\punteo\reg_10\locs10_25.sav'
  /BREAK=entidad mpio local
  /hoglocal = SUM(x) /totper_1 = SUM(totper) /hogpobre = SUM(folpob) /perpob_1 =
  SUM(perpob) /region = FIRST(region) /fecha = FIRST(fecha) / fopo = FIRST(fopo) .

GET
  FILE='E:\fase8\punteo\reg_10\locs10_25.sav'.
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\fase8\PUNTEO\LOCALS\990920\locs10_25.dbf '
    /TYPE=DB4
    /COMPRESSED.



***Para verificar hogares analizados y hogares beneficiarios

DESCRIPTIVES
  VARIABLES=hoglocal hogpobre
  /STATISTICS=SUM .

***Para verificar la información de jefes

GET
  FILE='E:\fase8\PUNTEO\REG_10\reg10j_25.sav'.
EXECUTE .

. REQUENCIES
  VARIABLES=peryjef
  /ORDER  ANALYSIS .

***Para verificar la información de personas

GET
  FILE='E:\fase8\PUNTEO\REG_10\reg10p_25.sav'.
EXECUTE .

RENAME VARIABLES
          ent_fed = entidad / munici = mpio / locali = local .

SORT CASES BY
  entidad (A) mpio (A) local (A) folio (A) .

MATCH FILES /FILE=*
 /TABLE='E:\Fase8\Punteo\Reg_10\REG10j_25.sav'
 /RENAME (aabao aacalif aacalif1 aadepen aadiscap aaedad aaesc aainput
  aalicua aapiso aaradio aarefri aatrab15 aavehi aavent aavhs adm_gas_ agua1
  agua_1 agua_ter agua_viv aguaba1 aguaba_1 anim1 anim2 anim3 anim4 anim5
  anim6 anim7 anim8 animales apo_ing_ asi_esc ate_med_ auto_pro bao bao1 bao_1
  bao_agua bueyes burros caballos cal_agua camion_p cerdos chivos con_inac
  con_tra conejos conyuge cuan_mur d_r depen dias_tra dif_hog disc_ani
  disc_ens discap edad edo_civ ej ej_1ertr elimin emigro es_ayuda es_ciega
  es_falta es_menta es_muda es_sorda esc estgas fam_bien fam_entr fecha folpob
  fopo gallinas hacina hect_rie hect_tem hectie1 ido_esc ing_hog inm15_1
  inmh15pc inmp_1 itmh itmh15 itmh15pe itmh15tp itmh_tpe itmhtper lava leche
  leer_esc leng_esp leng_mas lengua licua lnin15pc lp98 luz maestro med_nin_
  mot_no_t mu15a49 muro na8a17 nin0a1 nin2a5 nin5a15 nin6a7 nin8a15 nin_sol
  ninos no8a17 noasi1 noasi15 num_dias num_hec
 num_hog ocupj ocupj1 ocupj_1 pared1 pared_1 per_ayud per_cieg per_falt
  per_ment per_muda per_muri per_ocup per_sord percep perpob peryjef piso
  piso1 piso_1 predios prod_cul radio refri region reses result seg_mas
  seg_soc seguro sexo sit_viv taller techo tierra tit_lech tit_tort tocadisc
  tom_dec_ ton_cos1 ton_cos2 ton_cos3 tortilla tot_anim tot_cuar totper
```

```
  totper totpers trab trab15 trab151 trab_tem ttem_din ttem_lug ttem_mas
  ttem_mdi ttem_mes tv ult_gra ult_niv v111 v112 v40 v42 v44 v46 v66 v67 v96
  v97 vehi ventila ver_ing_ veritrab vhs viejitos x = d0 d1 d2 d3 d4 d5 d6 d7
  d8 d9 d10 d11 d12 d13 d14 d15 d16 d17 d18 d19 d20 d21 d22 d23 d24 d25 d26
  d27 d28 d29 d30 d31 d32 d33 d34 d35 d36 d37 d38 d39 d40 d41 d42 d43 d44 d45
  d46 d47 d48 d49 d50 d51 d52 d53 d54 d55 d56 d57 d58 d59 d60 d61 d62 d63 d64
  d65 d66 d67 d68 d69 d70 d71 d72 d73 d74 d75 d76 d77 d78 d79 d80 d81 d82 d83
  d84 d85 d86 d87 d88 d89 d90 d91 d92 d93 d94 d95 d96 d97 d98 d99 d100 d101
  d102 d103 d104 d105 d106 d107 d108 d109
 d110 d111 d112 d113 d114 d115 d116 d117 d118 d119 d120 d121 d122 d123 d124
  d125 d126 d127 d128 d129 d130 d131 d132 d133 d134 d135 d136 d137 d138 d139
  d140 d141 d142 d143 d144 d145 d146 d147 d148 d149 d150 d151 d152 d153 d154
  d155 d156 d157 d158 d159 d160 d161 d162 d163 d164 d165 d166 d167 d168 d169
  d170 d171 d172 d173 d174 d175 d176 d177 d178 d179 d180 d181 d182 d183 d184
  d185 d186 d187 d188 d189 d190 d191 d192 d193 d194 d195 d196 d197 d198)
 /BY entidad mpio local folio
 /DROP= d0 d1 d2 d3 d4 d5 d6 d7 d8 d9 d10 d11 d12 d13 d14 d15 d16 d17 d18 d19
  d20 d21 d22 d23 d24 d25 d26 d27 d28 d29 d30 d31 d32 d33 d34 d35 d36 d37 d38
  d39 d40 d41 d42 d43 d44 d45 d46 d47 d48 d49 d50 d51 d52 d53 d54 d55 d56 d57
  d58 d59 d60 d61 d62 d63 d64 d65 d66 d67 d68 d69 d70 d71 d72 d73 d74 d75 d76
  d77 d78 d79 d80 d81 d82 d83 d84 d85 d86 d87 d88 d89 d90 d91 d92 d93 d94 d95
  d96 d97 d98 d99 d100 d101 d102 d103 d104 d105 d106 d107 d108 d109 d110 d111
  d112 d113 d114 d115 d116 d117 d118 d119 d120 d121 d122 d123 d124
d125 d126 d127 d128 d129 d130 d131 d132 d133 d134 d135 d136 d137 d138 d139
  d140 d141 d142 d143 d144 d145 d146 d147 d148 d149 d150 d151 d152 d153 d154
  d155 d156 d157 d158 d159 d160 d161 d162 d163 d164 d165 d166 d167 d168 d169
  d170 d171 d172 d173 d174 d175 d176 d177 d178 d179 d180 d181 d182 d183 d184
  d185 d186 d187 d188 d189 d190 d191 d192 d193 d194 d195 d196 d197 d198.
EXECUTE.

FREQUENCIES
   VARIABLES=AAPOBRE .


***

SAVE OUTFILE='e:\fase8\punteo\REG_10\reg10p_25.sav'
   /COMPRESSED.
```

REGIÓN 12. HUASTECA
FASE 2
MODELO yy

```
  OMPUTE animales = 1 .
EXECUTE .
DO IF ((p721 >=  15 & p721 <  99) | (p722 >=  15 & p722 <  99) | (p723 >=  15 & p723 <  99)|
(p731 >=  20 & p731 <  99) | (p732 >=  15 & p732 <  99) | (p733 >=  25 & p733 <  99) | (p734 >=  15 & p734 <  99) |
(p735 >=  25 & p735 <  99) ) .
RECODE
  animales  (1=0)  .
END IF .
EXECUTE .

COMPUTE enseres = 0 .
EXECUTE .
DO IF (estgas = 1 & radio = 1 & luz = 1
       & tv = 1) .
RECODE
  enseres  (0=1)  .
END IF .
EXECUTE .

COMPUTE patron = 1 .
EXECUTE .
DO IF (p25=4) .
RECODE
  patron  (1=0)  .
END IF .
EXECUTE .

IF (AGUA=0) YYAGUA= 100.
IF (AGUA=1) YYAGUA= 80.

  OMPUTE YYDEPEN=-36*DEPEN.

IF (EJ1 =1) YYEJ= 85.
IF (EJ2 =1) YYEJ= 99.
IF (EJ3 =1) YYEJ= 100.
IF (EJ4 =1) YYEJ= 74.
IF (EJ5 =1) YYEJ= 70.
IF (EJ6 =1) YYEJ= 71.

IF ( ESCJ1 = 1) YYESC= 67.
IF ( ESCJ2 = 1) YYESC= 97.
IF ( ESCJ3 = 1) YYESC= 99.
IF ( ESCJ4 = 1) YYESC= 100.

IF ( HH1 = 1) YYHACINA=100.
IF ( HH2 = 1) YYHACINA=55.
IF ( HH3 = 1) YYHACINA=55.
IF ( HH4 = 1) YYHACINA=58.
IF ( HH5 = 1) YYHACINA=53.
IF ( HH6 = 1 ) YYHACINA=68.

IF (LICUA =0) YYLICUA = 100.
IF (LICUA =1) YYLICUA = 68.

COMPUTE YYNINOS=-1*NINOS.

IF (OCUPJ0 = 1) YYOCUP= 86.
IF (OCUPJ1 = 1) YYOCUP= 84.
IF (OCUPJ2 = 1) YYOCUP= 92.
IF (OCUPJ3_4 = 1) YYOCUP = 100.
IF (OCUPJ5_9 = 1) YYOCUP = 88.

IF (PISO = 0) YYPISO= 100.
IF (PISO = 1) YYPISO= 63.

COMPUTE YYTRAB15=-40*TRAB15
```

```
IF (DISCAP = 0) YYDISCAP= 100.
IF (DISCAP = 1) YYDISCAP= 85.

IF (VEHI=0) YYVEHI= 100.
IF (VEHI=1) YYVEHI= 0.

IF (REFRI=0) YYREFRI= 100.
IF (REFRI=1) YYREFRI= 0.

IF (ANIMALES=0) YYANIM= 100.
IF (ANIMALES=1) YYANIM= 0.

IF (TIERRA=0) YYTIERRA= 100.
IF (TIERRA=1) YYTIERRA= 0.

IF (LAVA=0) YYLAVA= 100.
IF (LAVA=1) YYLAVA= 0.

IF (PATRON=0) YYPATRON= 100.
IF (PATRON=1) YYPATRON= 0.

IF (ENSERES=0) YYENSER= 0.
IF (ENSERES=1) YYENSER= -100.

FREQUENCIES
  VARIABLES= yyagua yydepen yyej yyesc yyhacina yylicua yyninos yyocup
             yypiso yytrab15 yydiscap yyvehi yyrefri yyanim yytierra yylava yypatron yyenser
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF (MISSING(yyagua) | MISSING(yydepen) | MISSING(yyej) | MISSING(yyesc) | MISSING(yyhacina)
      | MISSING(yylicua)  | MISSING(yyninos) | MISSING(yyocup) | MISSING(yypiso) | MISSING(yytrab15)
      | MISSING(yydiscap) | MISSING(yyvehi) | MISSING(yyrefri)| MISSING(yyanim)| MISSING(yytierra)| MISSING(yylava)
      | MISSING(yypatron)| MISSING(yyenser) ) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .

RECODE yyagua  (SYSMIS=   89.148 ) .
RECODE yydepen  (SYSMIS=  -98.163 ) .
RECODE yyej  (SYSMIS=   76.506 ) .
RECODE yyesc  (SYSMIS=   93.483 ) .
RECODE yyhacina  (SYSMIS=   62.111 ) .
RECODE yylicua  (SYSMIS=   77.374 ) .
RECODE yyninos  (SYSMIS=   -1.824 ) .
RECODE yyocup  (SYSMIS=   87.541 ) .
RECODE yypiso  (SYSMIS=   82.141 ) .
RECODE yytrab15  (SYSMIS=   -5.527 ) .
RECODE yydiscap  (SYSMIS=   98.784 ) .
RECODE yyvehi  (SYSMIS=   -13.818 ) .
RECODE yyrefri  (SYSMIS=   16.076 ) .
RECODE yyanim  (SYSMIS=   13.542 ) .
RECODE yytierra  (SYSMIS=    5.021 ) .
RECODE yylava  (SYSMIS=   13.232 ) .
RECODE yypatron  (SYSMIS=     .691 ) .
RECODE yyenser  (SYSMIS=  -13.818) .

COMPUTE yycalif = yyagua + yydepen + yyej + yyesc + yyhacina + yylicua +
                  yyninos + yyocup + yypiso + yytrab15 + yydiscap .
EXECUTE .

DISCRIMINANT
  /GROUPS=lpnva(0 1)
   VARIABLES=yycalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  EQUAL
  /STATISTICS=TABLE
```

```
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
'ALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
 ORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=yycalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=yycalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE yycalif = yycalif + yyenser  + yytierra.
EXECUTE .

COMPUTE pobre = 0 .
EXECUTE .
O IF (yycalif < 572.5) .
 CODE
  pobre  (0=1)  .
END IF .
EXECUTE .

MEANS
  TABLES=agua bao depen discap ej1 ej2 ej3 ej4 ej5 ej6 escj1 escj2 escj3
  escj4 estgas hh1 hh2 hh3 hh4 hh5 hh6 ingmen15 ingmes ingmesh ingmigm
  ingmigr inmh15pc lava licua luz mu15a49 ninos noasi15 ocupj0 ocupj1 ocupj2
  ocupj3_4 ocupj5_9 piso radio refri tierra totpers trab15 tv vehi vhs  BY
  pobre
  /CELLS MEAN STDDEV COUNT
  /FORMAT= LABELS .

IF (DIS_1=0 & DIS_2=0 & POBRE=0) SECUENCE=1.
IF (DIS_1=0 & DIS_2=0 & POBRE=1) SECUENCE=2.
IF (DIS_1=0 & DIS_2=1 & POBRE=0) SECUENCE=3.
IF (DIS_1=1 & DIS_2=0 & POBRE=0) SECUENCE=4.
IF (DIS_1=0 & DIS_2=1 & POBRE=1) SECUENCE=5.
IF (DIS_1=1 & DIS_2=0 & POBRE=1) SECUENCE=6.
IF (DIS_1=1 & DIS_2=1 & POBRE=0) SECUENCE=7.
IF (DIS_1=1 & DIS_2=1 & POBRE=1) SECUENCE=8.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=0) SECUENCE=9.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=1) SECUENCE=10.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=0) SECUENCE=11.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=1) SECUENCE=12.
```

REGIÓN 12. HUASTECA
FASE 2
MODELO aa

```
 OMPUTE AADEPEN=-42*DEPEN .
COMPUTE AANINOS=-3*NINOS .
COMPUTE AATRAB15 = -124*TRAB151 .
COMPUTE AAHACINA = -6*HACINA .
COMPUTE AAESC = 8*ESC .
COMPUTE AAHECTIE = 2*HECTIE1

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 79 .

IF (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 96 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 67 .

IF (ESTGAS=0) AAESTGAS= 100 .
IF (ESTGAS=1) AAESTGAS= 84 .

IF (P65_10=0) AAVENTIL= 100 .
IF (P65_10=1) AAVENTIL= 56 .

EXECUTE.

FREQUENCIES
  VARIABLES= aadepen aaninos  aatrab15 aahacina aaesc  aahectie
   aadiscap aaradio aatv  aaestgas  aaventil
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

  OMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) |  MISSING (aatrab15) | MISSING(aahacina) | MISSING(aaesc)
       | MISSING(aahectie) | MISSING(aadiscap) | MISSING(aaradio) | MISSING(aatv) | MISSING(aaestgas) | MISSING(aaventil)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aadepen  (SYSMIS=-114.5239)  .
RECODE aaninos  (SYSMIS=-5.4708)  .
RECODE aatrab15  (SYSMIS=-7.6870)  .
RECODE aahacina  (SYSMIS=-19.0873)  .
RECODE aaesc  (SYSMIS= 28.5526)  .
RECODE aahectie  (SYSMIS= 8.1953)  .
RECODE aadiscap  (SYSMIS= 98.2976)  .
RECODE aaradio  (SYSMIS=98.6826)  .
RECODE aatv  (SYSMIS=86.5021)  .
RECODE aaestgas  (SYSMIS= 90.9751)  .
RECODE aaventil  (SYSMIS= 63.5799)  .

COMPUTE aacalif = aadepen + aaninos + aatrab15 + aahacina + aaesc + aahectie + aadiscap + aaradio
                  + aatv + aaestgas + aaventil.
EXECUTE .

DISCRIMINANT
  /GROUPS=lpnva(0 1)
  /VARIABLES=depen ninos  trab151  hacina esc discap radio tv
   estgas p65_10 hectie1
  /ANALYSIS ALL
  'SAVE=CLASS
   PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

DISCRIMINANT
```

```
  /GROUPS=LPNVA(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_4 = 0).
VARIABLE LABEL filter_$ 'dis_4 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_4 = 1).
VARIABLE LABEL filter_$ 'dis_4 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
 'SE ALL.
  ECUTE .

IF ( (ej<25 & TOTPERS <5) | (ej>64 & totpers<3) ) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .

COMPUTE aaCALIF1=aaCALIF + viejitos .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1 < 383.75) .
RECODE
  zzpobre  (0=1)  .
END IF .
EXECUTE .

DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lpnva pobre aapobre  .
```

REGIÓN 12. HUASTECA
FASE 2
Modelo aa

No aplica el modelo para 13 hogares.

REGIÓN 12. HUASTECA
FASE 3
MODELO aa

```
 ISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=depen ninos  trab151  hacina esc discap radio tv estgas ventila hectie1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  .42 .58
 /STATISTICS=RAW TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN=-42*DEPEN .
COMPUTE AANINOS=-3*NINOS .
COMPUTE AATRAB15 = -124*TRAB151 .
COMPUTE AAHACINA = -6*HACINA .
COMPUTE AAESC = 8*ESC .
COMPUTE AAHECTIE = 2*HECTIE1

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 79 .

IF (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 96 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 67 .

IF (ESTGAS=0) AAESTGAS= 100 .
IF (ESTGAS=1) AAESTGAS= 84 .

IF (VENTILA= 0) AAVENTIL= 100 .
IF (VENTILA= 1) AAVENTIL= 56 .

EXECUTE.

FREQUENCIES
 VARIABLES= aadepen aaninos aatrab15 aahacina aaesc aahectie aadiscap aaradio aatv aaestgas aaventil
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) |  MISSING (aatrab15) | MISSING(aahacina) | MISSING(aaesc)
      | MISSING(aahectie) | MISSING(aadiscap) | MISSING(aaradio) | MISSING(aatv) | MISSING(aaestgas) | MISSING(aaventil)) .
RECODE
 aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aadepen  (SYSMIS = -92.0369)  .
RECODE aaninos  (SYSMIS = -4.7133)  .
RECODE aatrab15  (SYSMIS = -2.6451)  .
RECODE aahacina  (SYSMIS = -18.8364)  .
RECODE aaesc  (SYSMIS = 28.6415)  .
RECODE aahectie  (SYSMIS = 5.8139)  .
RECODE aadiscap  (SYSMIS = 98.9357)  .
RECODE aaradio  (SYSMIS = 98.7818)  .
RECODE aatv  (SYSMIS = 86.6798)  .
RECODE aaestgas  (SYSMIS = 91.5273)  .
RECODE aaventil  (SYSMIS = 72.6082)  .

COMPUTE aacalif = aadepen + aaninos + aatrab15 + aahacina + aaesc
                + aahectie + aadiscap + aaradio + aatv + aaestgas + aaventil.
  ECUTE .

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES=aacalif
```

```
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2= 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = - 100 .
IF (RADIO = 1 & ESTGAS = 1 & LICUA = 1) COCINA = - 100 .
RECODE INDISPEN COCINA  (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos + indispen + cocina .
EXECUTE .

COMPUTE AApobre = 0 .
EXECUTE .
DO IF (AAcalif1< 400.5) .
RECODE
AApobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 aapobre  .
```

REGIÓN 12. HUASTECA
FASE 3
Modelo aa

No se aplicó filtro de VIEJITOS.

REGIÓN 12. HUASTECA
FASE 6
MODELO aa

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=depen ninos  trab151  hacina esc discap radio tv estgas ventila hectie1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  .42 .58
 /STATISTICS=RAW TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN=-42*DEPEN .
COMPUTE AANINOS=-3*NINOS .
COMPUTE AATRAB15 = -124*TRAB151 .
COMPUTE AAHACINA = -6*HACINA .
COMPUTE AAESC = 8*ESC .
COMPUTE AAHECTIE = 2*HECTIE1

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 79 .

IF (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 96 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 67 .

IF (ESTGAS=0) AAESTGAS= 100 .
IF (ESTGAS=1) AAESTGAS= 84 .

'F (VENTILA= 0) AAVENTIL= 100 .
.F (VENTILA= 1) AAVENTIL= 56 .

EXECUTE.

FREQUENCIES
 VARIABLES= aadepen aaninos  aatrab15 aahacina aaesc  aahectie
  aadiscap aaradio aatv  aaestgas  aaventil
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) |  MISSING (aatrab15) | MISSING(aahacina) | MISSING(aaesc)
      | MISSING(aahectie) | MISSING(aadiscap) | MISSING(aaradio) | MISSING(aatv) | MISSING(aaestgas) | MISSING(aaventil)) .
RECODE
 aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aadepen  (SYSMIS = -92.0369)  .
RECODE aaninos  (SYSMIS = -4.7133)  .
RECODE aatrab15  (SYSMIS = -2.6451)  .
RECODE aahacina  (SYSMIS = -18.8364)  .
RECODE aaesc  (SYSMIS = 28.6415)  .
RECODE aahectie  (SYSMIS = 5.8139)  .
RECODE aadiscap  (SYSMIS = 98.9357)  .
RECODE aaradio  (SYSMIS = 98.7818)  .
RECODE aatv  (SYSMIS = 86.6798)  .
RECODE aaestgas  (SYSMIS = 91.5273)  .
RECODE aaventil  (SYSMIS = 72.6082)  .

_OMPUTE aacalif = aadepen + aaninos + aatrab15 + aahacina + aaesc + aahectie + aadiscap + aaradio
                  + aatv + aaestgas + aaventil.
EXECUTE .

DISCRIMINANT
 /GROUPS=LP98(0 1)
```

```
 /VARIABLES=aacalif
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=AAcalif  /FORMAT=NOTABLE
 /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2= 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=AAcalif  /FORMAT=NOTABLE
 /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

 ((EJ<= 24 & tot_per <= 4) | (EJ >= 65 & tot_per <= 2)) viejitos = -100.
 recode viejitos (SYSMIS = 0) .
IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = - 100 .
IF (RADIO = 1 & ESTGAS = 1 & LICUA = 1) COCINA = - 100 .
RECODE INDISPEN COCINA  (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos + indispen + cocina .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 400.5) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
 VARIABLES=lp98 aapobre  .
```

REGIÓN 12. HUASTECA
FASE 8
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos  trab151  hacina esc discap radio tv estgas ventila hectie1
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-42*DEPEN .
COMPUTE AANINOS=-3*NINOS .
COMPUTE AATRAB15 = -124*TRAB151 .
COMPUTE AAHACINA = -6*HACINA .
COMPUTE AAESC = 8*ESC .
COMPUTE AAHECTIE = 2*HECTIE1

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 79 .

IF (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 96 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 67 .

IF (ESTGAS=0) AAESTGAS= 100 .
 (ESTGAS=1) AAESTGAS= 84 .

IF (VENTILA= 0) AAVENTIL= 100 .
IF (VENTILA= 1) AAVENTIL= 56 .

EXECUTE.

FREQUENCIES
  VARIABLES= aadepen aaninos aatrab15 aahacina aaesc aahectie aadiscap aaradio aatv aaestgas aaventil
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) |  MISSING (aatrab15) | MISSING(aahacina) | MISSING(aaesc)
       | MISSING(aahectie) | MISSING(aadiscap) | MISSING(aaradio) | MISSING(aatv) | MISSING(aaestgas)
       | MISSING(aaventil)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aadepen  (SYSMIS = -95.2553)  .
RECODE aaninos  (SYSMIS = -4.7500)  .
RECODE aatrab15  (SYSMIS = -3.4488)  .
RECODE aahacina  (SYSMIS = -17.8581)  .
RECODE aaesc  (SYSMIS = 25.9664)  .
RECODE aahectie  (SYSMIS = 6.2492)  .
RECODE aadiscap  (SYSMIS = 98.7557)  .
RECODE aaradio  (SYSMIS = 98.7911)  .
RECODE aatv  (SYSMIS = 88.2480)  .
 ECODE aaestgas  (SYSMIS = 91.8743)  .
ECODE aaventil  (SYSMIS = 71.8945)  .

COMPUTE aacalif = aadepen + aaninos + aatrab15 + aahacina + aaesc + aahectie + aadiscap + aaradio  + aatv
                  + aaestgas + aaventil.
EXECUTE .
```

```
DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1= 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
  SE ALL.
EXECUTE .

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = -100 .
IF (RADIO = 1 & ESTGAS = 1 & LICUA = 1) COCINA = -100 .
RECODE INDISPEN COCINA  (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos + indispen + cocina .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 458.75) .
RECODE
zzpobre  (0=1)  .
END IF .
EXECUTE .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .
IF (ELIMIN = 1) zzPOBRE = 0 .
EXECUTE .

FREQUENCIES
  VARIABLES = aapobre lp98.
```

REGIÓN 12. HUASTECA
FASE 8
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos  trab151  hacina esc discap radio tv estgas ventila hectie1
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-42*DEPEN .
COMPUTE AANINOS=-3*NINOS .
COMPUTE AATRAB15 = -124*TRAB151 .
COMPUTE AAHACINA = -6*HACINA .
COMPUTE AAESC = 8*ESC .
COMPUTE AAHECTIE = 2*HECTIE1

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 79 .

IF (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 96 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 67 .

IF (ESTGAS=0) AAESTGAS= 100 .
 (ESTGAS=1) AAESTGAS= 84 .

IF (VENTILA= 0) AAVENTIL= 100 .
IF (VENTILA= 1) AAVENTIL= 56 .

EXECUTE.

FREQUENCIES
  VARIABLES= aadepen aaninos aatrab15 aahacina aaesc aahectie aadiscap aaradio aatv aaestgas aaventil
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) |  MISSING (aatrab15) | MISSING(aahacina) | MISSING(aaesc)
       | MISSING(aahectie) | MISSING(aadiscap) | MISSING(aaradio) | MISSING(aatv) | MISSING(aaestgas)
       | MISSING(aaventil)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aadepen  (SYSMIS = -95.2553)  .
RECODE aaninos  (SYSMIS = -4.7500)  .
RECODE aatrab15  (SYSMIS = -3.4488)  .
RECODE aahacina  (SYSMIS = -17.8581)  .
RECODE aaesc  (SYSMIS = 25.9664)  .
RECODE aahectie  (SYSMIS = 6.2492)  .
RECODE aadiscap  (SYSMIS = 98.7557)  .
RECODE aaradio  (SYSMIS = 98.7911)  .
RECODE aatv  (SYSMIS = 88.2480)  .
 ECODE aaestgas  (SYSMIS = 91.8743)  .
RECODE aaventil  (SYSMIS = 71.8945)  .

COMPUTE aacalif = aadepen + aaninos + aatrab15 + aahacina + aaesc + aahectie + aadiscap + aaradio  + aatv
                  + aaestgas + aaventil.
EXECUTE .
```

```
DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1= 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = -100 .
IF (RADIO = 1 & ESTGAS = 1 & LICUA = 1) COCINA = -100 .
RECODE INDISPEN COCINA  (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos + indispen + cocina .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif1< 458.75) .
RECODE
zzpobre  (0=1)  .
END IF .
EXECUTE .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .
IF (ELIMIN = 1) zzPOBRE = 0 .
EXECUTE .

FREQUENCIES
  VARIABLES = aapobre lp98.
```

Región 13. Mixteca - Costa - Chatina
Fase 3

***discriminante con modelo nuevo

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
 /VARIABLES= depen ninos ocupj_1 esc piso_1 ej aguaba_1 trab151 noasi1 pared_1
  refri vehi estgas tv
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .
```

***puntajes región 13

```
COMPUTE AADEPEN = -31*DEPEN .
COMPUTE AANINOS = -17*NINOS .
COMPUTE AAOCUPJ = -35*OCUPJ_1 .
COMPUTE AAESC = 4*ESC .
COMPUTE AAPISO = 11*PISO_1 .
COMPUTE AAEDAD = 1*EJ .
COMPUTE AAAGUABA = 13*AGUABA_1 .
COMPUTE AATRAB = -31*TRAB151 .
COMPUTE AANOASI = -26*NOASI1 .
COMPUTE AAPARED = 11* PARED_1 .

IF (REFRI = 0) AAREFRI = 100 .
IF (REFRI = 1) AAREFRI = 76 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 55 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 76 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 76 .

EXECUTE.
```

***calcular las medias de las variables para imputar a valores perdidos

```
FREQUENCIES
  VARIABLES= aadepen aaninos aaocupj aaesc aapiso aaedad aaaguaba aatrab aanoasi aapared
  aarefri aavehi aaestgas aatv
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aaocupj)| MISSING (aaesc)| MISSING (aapiso)
  | MISSING(aaedad) | MISSING(aaaguaba)  | MISSING (aatrab) | MISSING(aanoasi)  | MISSING (aapared)
  | MISSING(aarefri)  | MISSING (aavehi)| MISSING(aaestgas) |MISSING(aatv)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .
```

***se recodifican los valores perdidos con las medias de las variables

```
RECODE aadepen  (SYSMIS = -116.2500)  .
  ECODE aaninos  (SYSMIS = -40.0714)  .
RECODE aaocupj (SYSMIS = -3.2750)  .
RECODE aaesc  (SYSMIS = 4.5714)  .
RECODE aapiso  (SYSMIS = -5.8850)  .
RECODE aaedad  (SYSMIS = 47.2857)  .
RECODE aaaguaba  (SYSMIS = 15.5800)  .
```

```
RECODE aatrab  (SYSMIS = -9.7798)  .
RECODE aanoasi  (SYSMIS = -7.8929)  .
RECODE aapared  (SYSMIS = -1.9957)  .
RECODE aarefri  (SYSMIS = 76.0000)  .
RECODE aavehi  (SYSMIS = 55.0000)  .
 ECODE aaestgas  (SYSMIS = 76.0000)  .
.ECODE aatv  (SYSMIS = 76.0000)  .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos +  aaocupj + aaesc + aapiso + aaedad +
  aaaguaba +  aatrab + aanoasi + aapared + aarefri + aavehi + aaestgas + aatv .
EXECUTE .


***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


***se determina la línea de corte y se obtienen los pobres


IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .


COMPUTE aapobre= 0 .
EXECUTE .
DO IF (aacalif1< 291.03) .
RECODE
```

```
  aapobre  (0=1)  .
END IF .
EXECUTE .


  ***** Recodificación por vehículo

DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
END IF .
EXECUTE .



FREQUENCIES
  VARIABLES=lp98 aapobre  .
```

Región 13 Fase 3

En esta fase la región 13 contenía localidades del estado de Puebla y de Oaxaca, posteriormente, se separó la parte correspondiente al estado de Puebla formándose la región 44.

Los totales presentados corresponden únicamente a lo analizado en el estado de Oaxaca.

Región 13. Mixteca - Costa - Chatina
Fase 6
Modelo aa

***discriminante con modelo nuevo

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
 /VARIABLES= depen ninos ocupj_1 esc piso_1 ej aguaba_1 trab151 noasi1 pared_1
  refri vehi estgas tv
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .
```

***puntajes región 13

```
COMPUTE AADEPEN = -31*DEPEN .
COMPUTE AANINOS = -17*NINOS .
COMPUTE AAOCUPJ = -35*OCUPJ_1 .
COMPUTE AAESC = 4*ESC .
COMPUTE AAPISO = 11*PISO_1 .
COMPUTE AAEDAD = 1*EJ .
COMPUTE AAAGUABA = 13*AGUABA_1 .
COMPUTE AATRAB = -31*TRAB151 .
COMPUTE AANOASI = -26*NOASI1 .
COMPUTE AAPARED = 11* PARED_1 .

IF (REFRI = 0) AAREFRI = 100 .
IF (REFRI = 1) AAREFRI = 76 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 55 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 76 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 76 .

EXECUTE.
```

***calcular las medias de las variables para imputar a valores perdidos

```
FREQUENCIES
  VARIABLES= aadepen aaninos aaocupj aaesc aapiso aaedad aaaguaba aatrab aanoasi aapared
  aarefri aavehi aaestgas aatv
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aaocupj)| MISSING (aaesc)| MISSING (aapiso)
  | MISSING(aaedad) | MISSING(aaaguaba)  | MISSING (aatrab) | MISSING(aanoasi)  | MISSING (aapared)
  | MISSING(aarefri)  | MISSING (aavehi)| MISSING(aaestgas) |MISSING(aatv)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .
```

***se recodifican los valores perdidos con las medias de las variables

```
RECODE aadepen  (SYSMIS = -85.4368)  .
RECODE aaninos  (SYSMIS = -26.8268)  .
RECODE aaocupj (SYSMIS = 0.2294)  .
RECODE aaesc  (SYSMIS = 14.7402)  .
RECODE aapiso  (SYSMIS = 0.03216)  .
RECODE aaedad  (SYSMIS = 45.9395)  .
RECODE aaaguaba  (SYSMIS = 0.01265)  .
```

```
RECODE aatrab  (SYSMIS = -1.1176)  .
RECODE aanoasi  (SYSMIS = -3.3519)  .
RECODE aapared  (SYSMIS = 0.0932)  .
RECODE aarefri  (SYSMIS = 80.7750)  .
RECODE aavehi  (SYSMIS = 57.4354)  .
 ECODE aaestgas  (SYSMIS = 84.5393)  .
.ECODE aatv  (SYSMIS = 87.7776)  .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos +  aaocupj + aaesc + aapiso + aaedad +
  aaaguaba +  aatrab + aanoasi + aapared + aarefri + aavehi + aaestgas + aatv .
EXECUTE .


***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


***se determina la línea de corte y se obtienen los pobres


IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .


COMPUTE AAPOBRE= 0 .
EXECUTE .
DO IF (aacalif1< 291.03) .
RECODE
```

```
  AAPOBRE  (0=1)  .
END IF .
EXECUTE .


  ***** Recodificación por vehículo

DO IF (vehi = 0 & AAPOBRE = 1) .
RECODE
  AAPOBRE  (1=0)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 AAPOBRE  .
```

Región 13. Mixteca - Costa - Chatina
Fase 6
Modelo bb

```
  **discriminante con modelo nuevo

DISCRIMINANT
  /GROUPS=lp98(0 1)
 /VARIABLES= depen ninos ocupj_1 esc piso_1 ej aguaba_1 trab151 noasi1 pared_1
  refri vehi estgas tv
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .41 .59
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .


***puntajes región 13

COMPUTE bbDEPEN = -31*DEPEN .
COMPUTE bbNINOS = -20*NINOS .
COMPUTE bbOCUPJ = -41*OCUPJ_1 .
COMPUTE bbESC = 8*ESC .
COMPUTE bbPISO = -2*PISO_1 .
COMPUTE bbEDAD = -1*EJ .
COMPUTE bbAGUABA = 16*AGUABA_1 .
COMPUTE bbTRAB = -41*TRAB151 .
COMPUTE bbNOASI = -29*NOASI1 .
COMPUTE bbPARED = -30* PARED_1 .

IF (REFRI = 0) bbREFRI = 100 .
IF (REFRI = 1) bbREFRI = 86 .

IF (VEHI = 0) bbVEHI = 100 .
  (VEHI = 1) bbVEHI = 71 .

IF (ESTGAS = 0) bbESTGAS = 100 .
IF (ESTGAS = 1) bbESTGAS = 78 .

IF (TV = 0) bbTV = 100 .
IF (TV = 1) bbTV = 79 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= bbdepen bbninos bbocupj bbesc bbpiso bbedad bbaguaba bbtrab bbnoasi bbpared
  bbrefri bbvehi bbestgas bbtv
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE bbinput = 0 .
EXECUTE .
DO IF (MISSING(bbdepen) | MISSING(bbninos) | MISSING (bbocupj)| MISSING (bbesc)| MISSING (bbpiso)
  | MISSING(bbedad) | MISSING(bbaguaba)  | MISSING (bbtrab) | MISSING(bbnoasi)  | MISSING (bbpared)
  | MISSING(bbrefri)  | MISSING (bbvehi)| MISSING(bbestgas) |MISSING(bbtv)) .
RECODE
  bbinput  (0=1)  .
END IF .
EXECUTE .


***se recodifican los valores perdidos con las medias de las variables

  ECODE bbdepen  (SYSMIS = -85.1868)  .
RECODE bbninos  (SYSMIS = -31.4122)  .
RECODE bbocupj (SYSMIS = 0.1526)  .
RECODE bbesc  (SYSMIS = 29.5263)  .
RECODE bbpiso  (SYSMIS = -0.0105)  .
RECODE bbedad  (SYSMIS = -45.9325)  .
```

```
RECODE bbaguaba  (SYSMIS = -0.0034437)  .
RECODE bbtrab  (SYSMIS = -1.4704)  .
RECODE bbnoasi  (SYSMIS = -3.7344)  .
RECODE bbpared  (SYSMIS = 0.2032)  .
RECODE bbrefri  (SYSMIS = 88.7829)  .
 ECODE bbvehi  (SYSMIS = 72.5740)  .
.ECODE bbestgas  (SYSMIS = 85.8486)  .
RECODE bbtv  (SYSMIS = 89.3207)  .

***se hace la calificación

COMPUTE bbcalif = bbdepen + bbninos +  bbocupj + bbesc + bbpiso + bbedad +
  bbaguaba +  bbtrab + bbnoasi + bbpared + bbrefri + bbvehi + bbestgas + bbtv .
EXECUTE .


***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=bbcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .41 .59
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

 REQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


***se determina la línea de corte y se obtienen los pobres


IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE bbcalif1 = bbcalif + viejitos .
  XECUTE .


COMPUTE bbpobre= 0 .
EXECUTE .
DO IF (bbcalif1< 258.02) .
```

```
RECODE
  bbpobre (0=1) .
END IF .
EXECUTE .


  ***** Recodificación por vehículo

DO IF (vehi = 0 & bbpobre = 1) .
RECODE
  bbpobre (1=0) .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 bbpobre .
```

Región 13. Mixteca - Costa - Chatina
Fase 8

```
***discriminante con modelo nuevo

DISCRIMINANT
  /GROUPS=lp98(0 1)
 /VARIABLES= depen ninos ocupj_1 esc piso_1 ej aguaba_1 trab151 noasi1 pared_1
  refri vehi estgas tv
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .


***puntajes región 13

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN = -31*DEPEN .
COMPUTE AANINOS = -17*NINOS .
COMPUTE AAOCUPJ = -35*OCUPJ_1 .
COMPUTE AAESC = 4*ESC .
COMPUTE AAPISO = 11*PISO_1 .
COMPUTE AAEDAD = 1*EJ .
COMPUTE AAAGUABA = 13*AGUABA_1 .
COMPUTE AATRAB = -31*TRAB151 .
COMPUTE AANOASI = -26*NOASI1 .
COMPUTE AAPARED = 11* PARED_1 .

IF (REFRI = 0) AAREFRI = 100 .
IF (REFRI = 1) AAREFRI = 76 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 55 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 76 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 76 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aaocupj aaesc aapiso aaedad aaaguaba aatrab aanoasi aapared
  aarefri aavehi aaestgas aatv
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aaocupj)| MISSING (aaesc)| MISSING (aapiso)
  | MISSING(aaedad) | MISSING(aaaguaba)  | MISSING (aatrab) | MISSING(aanoasi)  | MISSING (aapared)
  | MISSING(aarefri)  | MISSING (aavehi)| MISSING(aaestgas) |MISSING(aatv)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .


***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS = -86.3830)  .
RECODE aaninos  (SYSMIS = -32.2052)  .
RECODE aaocupj (SYSMIS = -0.1957)  .
RECODE aaesc  (SYSMIS = 11.3084)  .
```

```
RECODE aapiso  (SYSMIS = -0.1677)  .
RECODE aaedad  (SYSMIS = 46.5358)  .
RECODE aaaguaba  (SYSMIS = 0.2089)  .
RECODE aatrab  (SYSMIS = -3.1996)  .
RECODE aanoasi  (SYSMIS = -3.9132)  .
 ECODE aapared  (SYSMIS = 0.02622)  .
RECODE aarefri  (SYSMIS = 78.0951)  .
RECODE aavehi  (SYSMIS = 56.5298)  .
RECODE aaestgas  (SYSMIS = 78.7379)  .
RECODE aatv  (SYSMIS = 80.7853)  .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos +  aaocupj + aaesc + aapiso + aaedad +
  aaaguaba +  aatrab + aanoasi + aapared + aarefri + aavehi + aaestgas + aatv .
EXECUTE .


***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
 XECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


***se determina la línea de corte y se obtienen los pobres


IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .


COMPUTE aapobre= 0 .
```

```
EXECUTE .
DO IF (aacalif1< 347.385) .
RECODE
  aapobre  (0=1)  .
END IF .
  XECUTE .


****** Recodificación por vehículo

DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
END IF .
EXECUTE .


*******Filtro de seguridad social y última pregunta del cuestionario


IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) AAPOBRE = 0 .

EXECUTE .

FREQUENCIES
  VARIABLES=lp98 aapobre  .
```

Región 13 Fase 8

En esta región se calificaron 563 folios en la región 41, debido a que la clave del municipio estaba. El error se descubrió cuando se llegó a las localidades a incorporar a las familias.

Dado que ya se había impreso la papelería y el proceso de incorporación estaba ya muy avanzado, se optó por llevar los resultados de la calificación de estos folios a la región 13, y para indicar que habían sido calificados con el modelo de la región 41 se creó la variable reg_cal que tiene el valor de la región en que fueron calificados.

REGIÓN 15. NORTE - SELVA
FASE 2
MODELO yy

```
COMPUTE animales = 1 .
EXECUTE .
DO IF ((p721 >=  15 & p721 <  99) | (p722 >=  15 & p722 <  99) | (p723 >=  15 & p723 <  99)|
(p731 >=  20 & p731 <  99) | (p732 >=  15 & p732 <  99) | (p733 >=  25 & p733 <  99) | (p734 >=  15 & p734 <  99) |
(p735 >=  25 & p735 <  99) ) .
RECODE
 animales  (1=0)  .
END IF .
EXECUTE .

COMPUTE enseres = 0 .
EXECUTE .
DO IF (lava = 1 & refri = 1 & vehi = 1 & licua = 1 & agua = 1 & luz = 1
      & bao = 1 & estgas=1
       & tierra = 1 ) .
RECODE
 enseres  (0=1)  .
END IF .
EXECUTE .

COMPUTE patron = 1 .
EXECUTE .
DO IF (p25=4) .
RECODE
 patron  (1=0)  .
END IF .
EXECUTE .

COMPUTE YYDEPEN=-17*DEPEN.
COMPUTE YYNINOS=-5*NINOS.
COMPUTE YYNOASI=-4*NOASI15.
COMPUTE YYTRAB15=-34*TRAB15.

IF ( HH1 = 1) YYHACINA=100.
IF ( HH2 = 1) YYHACINA=35.
IF ( HH3 = 1) YYHACINA=29.
IF ( HH4 = 1) YYHACINA=28.
IF ( HH5 = 1) YYHACINA=27.
IF ( HH6 = 1 ) YYHACINA=26.

IF ( ESCJ1 = 1) YYESC= 52.
IF ( ESCJ2 = 1) YYESC= 53.
IF ( ESCJ3 = 1) YYESC= 57.
IF ( ESCJ4 = 1) YYESC= 100.

IF (OCUPJ0 = 1) YYOCUP= 77.
IF (OCUPJ1 = 1) YYOCUP= 81.
IF (OCUPJ2 = 1) YYOCUP= 84.
IF (OCUPJ3_4 = 1) YYOCUP = 100.
IF (OCUPJ5_9 = 1) YYOCUP = 75.

IF (DISCAP = 0) YYDISCAP= 100.
IF (DISCAP = 1) YYDISCAP= 80.

IF (PISO = 0) YYPISO= 100.
IF (PISO = 1) YYPISO= 73.

IF (EJ1 =1) YYEJ= 48.
IF (EJ2 =1) YYEJ= 53.
IF (EJ3 =1) YYEJ= 62.
IF (EJ4 =1) YYEJ= 82.
IF (EJ5 =1) YYEJ= 100.
IF (EJ6 =1) YYEJ= 84.

IF (RADIO =0) YYRADIO = 100.
IF (RADIO =1) YYRADIO = 91.
```

```
IF (LICUA =0) YYLICUA = 100.
IF (LICUA =1) YYLICUA = 66.

'F (VEHI=0) YYVEHI= 100.
.F (VEHI=1) YYVEHI= 0.

IF (REFRI=0) YYREFRI= 100.
IF (REFRI=1) YYREFRI= 0.

IF (ANIMALES=0) YYANIM= 100.
IF (ANIMALES=1) YYANIM= 0.

IF (TIERRA=0) YYTIERRA= 100.
IF (TIERRA=1) YYTIERRA= 0.

IF (LAVA=0) YYLAVA= 100.
IF (LAVA=1) YYLAVA= 0.

IF (PATRON=0) YYPATRON= 100.
IF (PATRON=1) YYPATRON= 0.

IF (ENSERES=0) YYENSER= 0.
IF (ENSERES=1) YYENSER= -100.

FREQUENCIES
  VARIABLES= yydepen yyninos yynoasi yytrab15 yyhacina yyesc yyocup yydiscap
             yyej yyradio yylicua yypiso  yyvehi yyrefri yyanim yytierra yylava yypatron yyenser
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF (MISSING(yydepen) | MISSING(yyninos) | MISSING(yynoasi) | MISSING(yytrab15)
       | MISSING(yyhacina) | MISSING(yyesc)  | MISSING(yyocup) | MISSING(yydiscap) | MISSING(yyej)
       | MISSING(yyradio) | MISSING(yylicua) | MISSING(yypiso)  | MISSING(yyvehi) | MISSING(yyrefri)
       | MISSING(yyanim)| MISSING(yytierra)| MISSING(yylava) | MISSING(yypatron)| MISSING(yyenser) ) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .

RECODE yydepen  (SYSMIS=-54.712)  .
RECODE yyninos  (SYSMIS=-11.168)  .
RECODE yynoasi  (SYSMIS=-.804)  .
RECODE yytrab15  (SYSMIS=-5.308)  .
RECODE yyhacina  (SYSMIS=31.650)  .
RECODE yyesc  (SYSMIS=56.640)  .
RECODE yyocup  (SYSMIS=84.945)  .
RECODE yydiscap  (SYSMIS=99.173)  .
RECODE yyej  (SYSMIS=73.331)  .
RECODE yyradio  (SYSMIS=95.406)  .
RECODE yylicua  (SYSMIS=67.875)  .
RECODE yypiso  (SYSMIS=78.175)  .
RECODE yyvehi  (SYSMIS=1.919)  .
RECODE yyrefri  (SYSMIS=5.357)  .
RECODE yyanim  (SYSMIS=21.868)  .
RECODE yytierra  (SYSMIS=.588)  .
RECODE yylava  (SYSMIS=.476)  .
RECODE yypatron  (SYSMIS=.373)  .
RECODE yyenser  (SYSMIS=-17.113)  .

COMPUTE yycalif = yydepen + yyninos + yynoasi + yytrab15 + yyhacina +
          yyesc + yyocup + yydiscap  + yyej + yyradio + yylicua + yypiso.
EXECUTE .

)ISCRIMINANT
  /GROUPS=lpnva(0 1)
  /VARIABLES=yycalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  EQUAL
```

```
  /STATISTICS=TABLE
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=yycalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=yycalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE yycalif1 = yycalif + yyvehi + yyrefri +  yyenser + yytierra + yylava .
EXECUTE .

COMPUTE yypobre = 0 .
EXECUTE .
DO IF (yycalif1 < 545.45) .
RECODE
  yypobre  (0=1)  .
END IF .
EXECUTE .



MEANS
  TABLES=agua bao depen discap ej1 ej2 ej3 ej4 ej5 ej6 escj1 escj2 escj3
  escj4 estgas hh1 hh2 hh3 hh4 hh5 hh6 ingmen15 ingmes ingmesh ingmigm
  ingmigr inmh15pc lava licua luz mu15a49 ninos noasi15 ocupj0 ocupj1 ocupj2
  ocupj3_4 ocupj5_9 piso radio refri tierra totpers trab15 tv vehi vhs  BY
  pobre
  /CELLS MEAN STDDEV COUNT
  /FORMAT= LABELS .

IF (DIS_1=0 & DIS_2=0 & POBRE=0) SECUENCE=1.
IF (DIS_1=0 & DIS_2=0 & POBRE=1) SECUENCE=2.
IF (DIS_1=0 & DIS_2=1 & POBRE=0) SECUENCE=3.
IF (DIS_1=1 & DIS_2=0 & POBRE=0) SECUENCE=4.
IF (DIS_1=0 & DIS_2=1 & POBRE=1) SECUENCE=5.
IF (DIS_1=1 & DIS_2=0 & POBRE=1) SECUENCE=6.
IF (DIS_1=1 & DIS_2=1 & POBRE=0) SECUENCE=7.
IF (DIS_1=1 & DIS_2=1 & POBRE=1) SECUENCE=8.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=0) SECUENCE=9.
IF (SYSMIS(DIS_1) & DIS_2=0 & POBRE=1) SECUENCE=10.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=0) SECUENCE=11.
IF (SYSMIS(DIS_1) & DIS_2=1 & POBRE=1) SECUENCE=12.

 REQUENCIES
  VARIABLES=secuence  .

FREQUENCIES
  VARIABLES=dis_1 dis_2 pobre lpnva .
```

```
IF (vehi=0 & yypobre=1) yypobre=9.
RECODE yypobre (9=0).
```

REGIÓN 15. NORTE - SELVA
FASE 2
MODELO aa

```
DISCRIMINANT
 /GROUPS=lpnva(0 1)
  /VARIABLES=depen ninos  TRAB151  hacina  esc  ocupj_1  discap  piso_1
 ej lava vehi estgas  licua refri  aguaba_1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS =  .42 .58
 /STATISTICS=RAW TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN=-16*DEPEN.
COMPUTE AANINOS=-7*NINOS .
COMPUTE AATRAB15=-68*trab151.
COMPUTE AAHACINA=-7*HACINA .
COMPUTE AAESC=14*ESC .
COMPUTE AAOCUPJ=37*OCUPJ_1 .
COMPUTE AAPISO=20*PISO_1 .
COMPUTE AAEDAD=1*EJ .
COMPUTE AAAGUABA = 9*AGUABA_1 .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 83 .

IF (LAVA =0) AALAVA = 100.
IF (LAVA =1) AALAVA = 48 .

IF (VEHI =0) AAVEHI = 100.
IF (VEHI =1) AAVEHI = 43 .

IF (ESTGAS=0) AAESTGAS = 100.
IF (ESTGAS=1) AAESTGAS = 50 .

IF (LICUA=0) AALICUA= 100.
IF (LICUA=1) AALICUA=73 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=55 .

FREQUENCIES
 VARIABLES= AADEPEN AANINOS AATRAB15 AAHACINA AAESC  AAOCUPJ AAPISO
            AAEDAD AAAGUABA AADISCAP AALAVA AAVEHI AAESTGAS AALICUA AAREFRI
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AATRAB15) | MISSING(AAHACINA) | MISSING(AAESC)
      | MISSING(AAOCUPJ) | MISSING(AAPISO) | MISSING(AAEDAD) | MISSING(AAAGUABA) | MISSING(AADISCAP)
      | MISSING(AALAVA) | MISSING(AAVEHI) | MISSING(AAESTGAS) | MISSING(AALICUA) | MISSING(AAREFRI) ) .
RECODE
 input  (0=1)  .
END IF .
EXECUTE .

RECODE  AADEPEN (SYSMIS=-50.99).
RECODE  AANINOS (SYSMIS=-15.24).
RECODE  AATRAB15 (SYSMIS=-7.71).
RECODE  AAHACINA (SYSMIS=-31.95).
RECODE  AAESC (SYSMIS=41.49).
RECODE  AAOCUPJ (SYSMIS=-.06).
RECODE  AAPISO (SYSMIS=.20).
RECODE  AAEDAD (SYSMIS=40.14).
RECODE  AAAGUABA (SYSMIS=.02) .
RECODE  AADISCAP (SYSMIS=99.28).
RECODE  AALAVA (SYSMIS=48.19) .
RECODE  AAVEHI (SYSMIS=43.96) .
```

```
RECODE  AAESTGAS (SYSMIS=52.52).
RECODE  AALICUA (SYSMIS=74.41).
RECODE  AAREFRI (SYSMIS=57.14) .

COMPUTE aacalif = AADEPEN + AANINOS + TRAB15 + AAHACINA + AAESC + AAOCUPJ + AAPISO + AAEDAD +
                  AAAGUABA + AADISCAP + AALAVA  + AAVEHI + AAESTGAS + AALICUA + AAREFRI  .
EXECUTE .

DISCRIMINANT
  /GROUPS=LPNVA(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_4 = 0).
VARIABLE LABEL filter_$ 'dis_4 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_4 = 1).
VARIABLE LABEL filter_$ 'dis_4 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((P08 < 25 & TOTPERS < 5) | (P08 > 65 & P08 < 98 & TOTPERS < 3)) VIEJITOS = -100 .

COMPUTE AACALIF1 = AACALIF + VIEJITOS .
EXECUTE.

COMPUTE aapobre = 0 .
DO IF (aacalif1< 428.24) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) AAPOBRE = 0.
EXECUTE.

FREQUENCIES
   VARIABLES=AAPOBRE POBRE .
```

REGIÓN 15. NORTE - SELVA
FASE 6
MODELO aa

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos TRAB151 hacina esc ocupj_1 discap piso_1 ej lava vehi estgas licua refri aguaba_1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS =  .42 .58
 /STATISTICS=RAW TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN=-16*DEPEN.
COMPUTE AANINOS=-7*NINOS .
COMPUTE AATRAB15=-68*trab151.
COMPUTE AAHACINA=-7*HACINA .
COMPUTE AAESC=14*ESC .
COMPUTE AAOCUPJ=37*OCUPJ_1 .
COMPUTE AAPISO=20*PISO_1 .
COMPUTE AAEDAD=1*EJ .
COMPUTE AAAGUABA = 9*AGUABA_1 .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 83 .

IF (LAVA =0) AALAVA = 100.
IF (LAVA =1) AALAVA = 48 .

IF (VEHI =0) AAVEHI = 100.
IF (VEHI =1) AAVEHI = 43 .

IF (ESTGAS=0) AAESTGAS = 100.
IF (ESTGAS=1) AAESTGAS = 50 .

IF (LICUA=0) AALICUA= 100.
IF (LICUA=1) AALICUA=73 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=55 .

FREQUENCIES
 VARIABLES= AADEPEN AANINOS AATRAB15 AAHACINA AAESC  AAOCUPJ AAPISO
            AAEDAD AAAGUABA  AADISCAP AALAVA AAVEHI AAESTGAS AALICUA AAREFRI
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AATRAB15) | MISSING(AAHACINA) | MISSING(AAESC)
      | MISSING(AAOCUPJ) | MISSING(AAPISO) | MISSING(AAEDAD) | MISSING(AAAGUABA) | MISSING(AADISCAP)
      | MISSING(AALAVA) | MISSING(AAVEHI) | MISSING(AAESTGAS) | MISSING(AALICUA) | MISSING(AAREFRI) ) .
RECODE
 input  (0=1)  .
END IF .
EXECUTE .

RECODE  AADEPEN (SYSMIS=-52.39).
RECODE  AANINOS (SYSMIS=-14.26).
RECODE  AATRAB15 (SYSMIS=-3.14).
RECODE  AAHACINA (SYSMIS= -30.49).
RECODE  AAESC (SYSMIS=23.04).
RECODE  AAOCUPJ (SYSMIS=9.88).
RECODE  AAPISO (SYSMIS=1.97).
RECODE  AAEDAD (SYSMIS=41.45).
RECODE  AAAGUABA (SYSMIS=1.44) .
RECODE  AADISCAP (SYSMIS=99.26).
RECODE  AALAVA (SYSMIS=49.77) .
RECODE  AAVEHI (SYSMIS=44.24) .
RECODE  AAESTGAS (SYSMIS=55.58).
```

```
RECODE  AALICUA (SYSMIS=77.26).
RECODE  AAREFRI (SYSMIS=60.24) .


COMPUTE AAcalif = AADEPEN + AANINOS + TRAB15 + AAHACINA + AAESC + AAOCUPJ + AAPISO +
        AAEDAD + AAAGUABA + AADISCAP + AALAVA  + AAVEHI + AAESTGAS + AALICUA + AAREFRI  .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOT_PER < 5) | (ej > 65 & ej < 98 & TOT_PER < 3)) VIEJITOS = -100 .

COMPUTE AACALIF1 = AACALIF + VIEJITOS .
EXECUTE.

IF (agua1=1  & luz=1  & piso= 1) AACALIF1=AACALIF1-100 .
EXECUTE .

COMPUTE aapobre = 0 .
DO IF (AAcalif< 428.24) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) aapobre = 0.
EXECUTE.

FREQUENCIES
  VARIABLES= lp98 aapobre  .
```

REGIÓN 15. NORTE - SELVA
FASE 6
MODELO bb

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos  TRAB151  hacina  esc  ocupj_1  discap  piso_1
              ej lava vehi estgas  licua refri  aguaba_1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS =  .41 .59
 /STATISTICS=RAW TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE bbDEPEN=-7*DEPEN.
COMPUTE bbNINOS=-28*NINOS .
COMPUTE bbTRAB15=-32*trab151.
COMPUTE bbHACINA=-7*HACINA .
COMPUTE bbESC=13*ESC .
COMPUTE bbOCUPJ=4*OCUPJ_1 .
COMPUTE bbPISO=11*PISO_1 .
COMPUTE bbEDAD=1*EJ .
COMPUTE bbAGUABA = -15*AGUABA_1 .

IF (DISCAP =0) bbDISCAP = 100.
IF (DISCAP =1) bbDISCAP = 74 .

IF (LAVA =0) bbLAVA = 100.
IF (LAVA =1) bbLAVA = 63 .

IF (VEHI =0) bbVEHI = 100.
IF (VEHI =1) bbVEHI = 30 .

IF (ESTGAS=0) bbESTGAS = 100.
IF (ESTGAS=1) bbESTGAS = 67 .

IF (LICUA=0) bbLICUA= 100.
IF (LICUA=1) bbLICUA=99 .

IF (REFRI=0) bbREFRI=100 .
IF (REFRI=1) bbREFRI=70 .


FREQUENCIES
 VARIABLES= bbDEPEN bbNINOS bbTRAB15 bbHACINA bbESC bbOCUPJ bbPISO
            bbEDAD bbAGUABA bbDISCAP bbLAVA bbVEHI bbESTGAS bbLICUA bbREFRI
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .


COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(bbDEPEN) | MISSING(bbNINOS) | MISSING(bbTRAB15) | MISSING(bbHACINA) | MISSING(bbESC)
      | MISSING(bbOCUPJ) | MISSING(bbPISO) | MISSING(bbEDAD) | MISSING(bbAGUABA) | MISSING(bbDISCAP)
      | MISSING(bbLAVA) | MISSING(bbVEHI) | MISSING(bbESTGAS) | MISSING(bbLICUA) | MISSING(bbREFRI)) .
RECODE
 input  (0=1)  .
END IF .
EXECUTE .

RECODE  bbDEPEN (SYSMIS=-20.5147).
RECODE  bbNINOS (SYSMIS=-55.2664).
RECODE  bbTRAB15 (SYSMIS=-1.6591).
RECODE  bbHACINA (SYSMIS= -30.2501).
RECODE  bbESC (SYSMIS=34.5158).
RECODE  bbOCUPJ (SYSMIS=0.03518).
RECODE  bbPISO (SYSMIS=0.2511).
RECODE  bbEDAD (SYSMIS=41.5455).
RECODE  bbAGUABA (SYSMIS=-0.2801) .
RECODE  bbDISCAP (SYSMIS=98.9514).
```

```
RECODE  bbLAVA (SYSMIS=63.8368) .
RECODE  bbVEHI (SYSMIS=31.2565) .
RECODE  bbESTGAS (SYSMIS=70.8742).
RECODE  bbLICUA (SYSMIS=99.1370).
RECODE  bbREFRI (SYSMIS=73.2419) .

COMPUTE bbcalif = bbDEPEN + bbNINOS + TRAB15 + bbHACINA + bbESC + bbOCUPJ + bbPISO + bbEDAD
                + bbAGUABA + bbDISCAP + bbLAVA  + bbVEHI + bbESTGAS + bbLICUA + bbREFRI  .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=bbcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .41 .59
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOT_PER < 5) | (ej > 65 & ej < 98 & TOT_PER < 3)) VIEJITOS = -100 .

COMPUTE bbCALIF1 = bbCALIF + VIEJITOS .
EXECUTE.

IF (agua1=1  & luz=1  & piso= 1) bbCALIF1=bbCALIF1-100 .
EXECUTE .

COMPUTE bbpobre = 0 .
DO IF (bbcalif1< 483.08) .
RECODE
bbpobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) bbpobre = 0.
EXECUTE.

DO IF (aapobre = 1) .
RECODE
  bbpobre  (1=0)  .
END IF .
EXECUTE .
```

```
FREQUENCIES
  VARIABLES= lp98 BBpobre  .
```

REGIÓN 15. NORTE - SELVA
FASE 8
MODELO aa

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos TRAB151 hacina esc ocupj_1 discap piso_1 ej lava vehi estgas licua refri aguaba_1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS =  .42 .58
 /STATISTICS=RAW TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN=-16*DEPEN.
COMPUTE AANINOS=-7*NINOS .
COMPUTE AATRAB15=-68*trab151.
COMPUTE AAHACINA=-7*HACINA .
COMPUTE AAESC=14*ESC .
COMPUTE AAOCUPJ=37*OCUPJ_1 .
COMPUTE AAPISO=20*PISO_1 .
COMPUTE AAEDAD=1*EJ .
COMPUTE AAAGUABA = 9*AGUABA_1 .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 83 .

IF (LAVA =0) AALAVA = 100.
IF (LAVA =1) AALAVA = 48 .

IF (VEHI =0) AAVEHI = 100.
IF (VEHI =1) AAVEHI = 43 .

IF (ESTGAS=0) AAESTGAS = 100.
IF (ESTGAS=1) AAESTGAS = 50 .

IF (LICUA=0) AALICUA= 100.
IF (LICUA=1) AALICUA=73 .

IF (REFRI=0) AAREFRI=100 .
IF (REFRI=1) AAREFRI=55 .

FREQUENCIES
 VARIABLES= AADEPEN AANINOS AATRAB15 AAHACINA AAESC  AAOCUPJ AAPISO
            AAEDAD AAAGUABA  AADISCAP AALAVA AAVEHI AAESTGAS AALICUA AAREFRI
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AATRAB15) | MISSING(AAHACINA) | MISSING(AAESC)
      | MISSING(AAOCUPJ) | MISSING(AAPISO) | MISSING(AAEDAD) | MISSING(AAAGUABA) | MISSING(AADISCAP)
      | MISSING(AALAVA) | MISSING(AAVEHI) | MISSING(AAESTGAS) | MISSING(AALICUA) | MISSING(AAREFRI) ) .
RECODE
 input  (0=1)  .
END IF .
EXECUTE .

RECODE  AADEPEN (SYSMIS=-52.39).
RECODE  AANINOS (SYSMIS=-14.26).
RECODE  AATRAB15 (SYSMIS=-3.14).
RECODE  AAHACINA (SYSMIS= -30.49).
RECODE  AAESC (SYSMIS=23.04).
RECODE  AAOCUPJ (SYSMIS=9.88).
RECODE  AAPISO (SYSMIS=1.97).
RECODE  AAEDAD (SYSMIS=41.45).
RECODE  AAAGUABA (SYSMIS=1.44) .
RECODE  AADISCAP (SYSMIS=99.26).
RECODE  AALAVA (SYSMIS=49.77) .
RECODE  AAVEHI (SYSMIS=44.24) .
RECODE  AAESTGAS (SYSMIS=55.58).
```

```
RECODE  AALICUA (SYSMIS=77.26).
RECODE  AAREFRI (SYSMIS=60.24) .


COMPUTE AAcalif = AADEPEN + AANINOS + TRAB15 + AAHACINA + AAESC + AAOCUPJ + AAPISO +
        AAEDAD + AAAGUABA + AADISCAP + AALAVA  + AAVEHI + AAESTGAS + AALICUA + AAREFRI  .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
  XECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOT_PER < 5) | (ej > 65 & ej < 98 & TOT_PER < 3)) VIEJITOS = -100 .

COMPUTE AACALIF1 = AACALIF + VIEJITOS .
EXECUTE.

IF (agua1=1  & luz=1  & piso= 1) AACALIF1=AACALIF1-100 .
EXECUTE .

COMPUTE aapobre = 0 .
DO IF (AAcalif< 487.36) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) aapobre = 0.
IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
  ECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .
IF (ELIMIN = 1) AAPOBRE = 0 .
EXECUTE.

FREQUENCIES
  VARIABLES= lp98 aapobre  .
```

Región 16. Pochutla
Fase 8

```
***discriminante con modelo nuevo

DISCRIMINANT
  /GROUPS=lp98(0 1)
 /VARIABLES= lengua esc discap trab151 noasi1 vehi hacina
  depen ninos luz licua refri tv
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

***puntajes región 16

***Calificación

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AAESC = 7.86*ESC .
COMPUTE AATRAB = -33.075*TRAB151 .
COMPUTE AANOASI = -13.867*NOASI1 .
COMPUTE AAHACINA = -5.021*HACINA .
COMPUTE AADEPEN = -18.058*DEPEN .
COMPUTE AANINOS = -15.86*NINOS .


IF (LENGUA = 0) AALENGUA = 100 .
IF (LENGUA = 1) AALENGUA = 96 .

IF (DISCAP = 0) AADISCAP = 100 .
  (DISCAP = 1) AADISCAP = 66 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 39 .

IF (LUZ = 0) AALUZ = 100 .
IF (LUZ = 1) AALUZ = 75 .

IF (LICUA = 0) AALICUA = 100 .
IF (LICUA = 1) AALICUA = 47 .

IF (REFRI = 0) AAREFRI = 100 .
IF (REFRI = 1) AAREFRI = 59 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 100 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aaesc aatrab aanoasi aahacina aadepen aaninos aalengua aadiscap aavehi
  aaluz aalicua aarefri aatv
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aaesc) | MISSING(aatrab) | MISSING (aanoasi)| MISSING (aahacina)| MISSING (aadepen)
  | MISSING(aaninos) | MISSING(aalengua)  | MISSING (aadiscap) | MISSING(aavehi)  | MISSING (aaluz)
    MISSING(aalicua)  | MISSING (aarefri)| MISSING(aatv)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .
```

```
***se recodifican los valores perdidos con las medias de las variables

RECODE aaesc  (SYSMIS = 29.3643)  .
RECODE aatrab  (SYSMIS = -1.478)  .
 ECODE aanoasi (SYSMIS = -2.108)  .
.ECODE aahacina  (SYSMIS = -21.2908)  .
RECODE aadepen  (SYSMIS = -51.127)  .
RECODE aaninos  (SYSMIS = -28.4765)  .
RECODE aalengua  (SYSMIS = 96.6119)  .
RECODE aadiscap  (SYSMIS = 98.467)  .
RECODE aavehi  (SYSMIS = 41.0628)  .
RECODE aaluz  (SYSMIS =93.7399 )  .
RECODE aalicua  (SYSMIS = 59.7399)  .
RECODE aarefri  (SYSMIS = 62.2351)  .
RECODE aatv  (SYSMIS = 100)  .

***se hace la calificación

COMPUTE aacalif = aaesc + aatrab +  aanoasi + aahacina + aadepen + aaninos +
  aalengua +  aadiscap + aavehi + aaluz + aalicua + aarefri + aatv .
EXECUTE .


***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

  SE ALL.
.OMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


 **se determina la línea de corte y se obtienen los pobres

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .
```

```
COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .


COMPUTE aapobre= 0 .
 XECUTE .
JO IF (aacalif1< 522.72) .
RECODE
 aapobre (0=1) .
END IF .
EXECUTE .


****** Recodificación por vehículo

DO IF (vehi = 0 & aapobre = 1) .
RECODE
 aapobre (1=0) .
END IF .
EXECUTE .


*******Filtro de seguridad social y última pregunta del cuestionario


IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) AAPOBRE = 0 .

EXECUTE .

. REQUENCIES
 VARIABLES=lp98 aapobre ELIMIN .
```

REGIÓN 28. ALTIPLANO
FASE 2
Modelo yy
Modelo aa

Los modelos son incorrectos. Las bases presentan valores perdidos en las variables.

REGIÓN 28. ALTIPLANO
FASE 3
MODELO aa

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES= depen ninos vhs ocupj_1 vehi lava piso_1 mu15a49 aguaba_1 trab151 estgas hectie1 discap
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  .42 .58
 /STATISTICS=RAW TABLE
 /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN = -30*DEPEN .
COMPUTE AANINOS = -31*NINOS .
COMPUTE AAOCUPJ = -24*OCUPJ_1 .
COMPUTE AAPISO = 11*PISO_1 .
COMPUTE AAMU15A = -13*MU15A49 .
COMPUTE AAAGUABA = 12*AGUABA_1 .
COMPUTE AATRAB = -48*TRAB151 .
COMPUTE AAHECTIE = 2*HECTIE1 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 1) AAVHS = 58 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 82 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 64 .

IF (ESTGAS = 0) AAESTGAS= 100 .
IF (ESTGAS = 1) AAESTGAS = 78

   (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 70

EXECUTE.

FREQUENCIES
 VARIABLES= aadepen aaninos aaocupj aapiso aamu15a aaaguaba aatrab aahectie
            aavhs aavehi aalava aaestgas aadiscap
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING(aaocupj)| MISSING(aapiso) | MISSING(aamu15a)
      | MISSING (aaaguaba) | MISSING(aatrab) | MISSING (aahectie)| MISSING(aavhs) | MISSING(aavehi)
      | MISSING(aalava)  | MISSING(aaestgas) | MISSING(aadiscap)) .
RECODE
 aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aadepen  (SYSMIS = -70.9908) .
RECODE aaninos  (SYSMIS = -50.0667) .
RECODE aaocupj  (SYSMIS = 2.9610) .
RECODE aapiso  (SYSMIS = -3.2240) .
RECODE aamu15a  (SYSMIS = -15.1862) .
RECODE aaaguaba  (SYSMIS = -1.1773) .
RECODE aatrab  (SYSMIS = -1.8725) .
RECODE aahectie  (SYSMIS = 11.2473) .
RECODE aavhs  (SYSMIS = 63.1277) .
   CODE aavehi  (SYSMIS = 86.8590) .
   CODE aalava  (SYSMIS = 72.3638) .
RECODE aaestgas  (SYSMIS = 91.7228) .
RECODE aadiscap (SYSMIS = 98.0387) .

COMPUTE zzcalif = aadepen + aaninos + aaocupj + aapiso + aamu15a + aaaguaba + aatrab + aahectie + aavhs
```

```
                + aavehi + aalava + aaestgas +  aadiscap .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .
IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = - 100 .
RECODE INDISPEN (SYSMIS = 0) .

COMPUTE zzCALIF1 = zzCALIF + VIEJITO .
EXECUTE.

COMPUTE zzpobre = 0 .
DO IF (zzcalif1 < 330.615) .
RECODE
  zzpobre  (0=1)  .
END IF .
EXECUTE .

DO IF (vehi = 0 & zzpobre = 1) .
RECODE
  zzpobre  (1=0)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 aapobre  .
```

REGIÓN 28. ALTIPLANO
FASE 3
MODELO bb

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
 /VARIABLES= hacina depen ninos ocupj_1 piso_1 mu15a49 trab151 hectie1 agua_1
              vhs refri vehi lava radio estgas discap
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

COMPUTE bbHACINA = -5*HACINA .
COMPUTE bbDEPEN = -32*DEPEN .
COMPUTE bbNINOS = -28*NINOS .
COMPUTE bbOCUPJ = -24*OCUPJ_1 .
COMPUTE bbPISO = 11*PISO_1 .
COMPUTE bbMU15A = -11*MU15A49 .
COMPUTE bbTRAB = -33*TRAB151 .
COMPUTE bbHECTIE = 3*HECTIE1 .
COMPUTE bbAGUA = 6*AGUA_1 .

IF (VHS = 0) bbVHS = 100 .
IF (VHS = 1) bbVHS = 62 .

IF (REFRI = 0) bbREFRI = 100 .
IF (REFRI = 1) bbREFRI = 88 .

IF (VEHI = 0) bbVEHI = 100 .
IF (VEHI = 1) bbVEHI = 81 .

 F (LAVA = 0) bbLAVA = 100 .
IF (LAVA = 1) bbLAVA = 75 .

IF (RADIO = 0) bbRADIO = 100 .
IF (RADIO = 1) bbRADIO = 88 .

IF (ESTGAS = 0) bbESTGAS= 100 .
IF (ESTGAS = 1) bbESTGAS = 87

IF (DISCAP = 0) bbDISCAP = 100 .
IF (DISCAP = 1) bbDISCAP = 72

EXECUTE.

FREQUENCIES
  VARIABLES= bbhacina bbdepen bbninos bbocupj bbpiso bbmu15a bbtrab bbhectie bbagua
              bbvhs bbrefri bbvehi bblava bbradio bbestgas bbdiscap
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE bbinput = 0 .
EXECUTE .
DO IF (MISSING(bbhacina) | MISSING(bbdepen) | MISSING(bbninos) | MISSING(bbocupj) | MISSING(bbpiso)
  | MISSING(bbmu15a) | MISSING(bbtrab)  | MISSING (bbhectie) | MISSING (bbagua)
  | MISSING(bbvhs) | MISSING(bbrefri)  | MISSING(bbvehi) | MISSING(bblava)
  | MISSING(bbradio) | MISSING(bbestgas) | MISSING(bbdiscap)) .
RECODE
  bbinput  (0=1)  .
END IF .
EXECUTE .

  ECODE bbhacina  (SYSMIS = -13.7644) .
RECODE bbdepen  (SYSMIS = -72.6155) .
RECODE bbninos  (SYSMIS = -45.2907) .
RECODE bbocupj  (SYSMIS = -0.0740) .
RECODE bbpiso  (SYSMIS = 0.03365) .
RECODE bbmu15a  (SYSMIS = -12.6689) .
```

```
RECODE bbtrab  (SYSMIS = -1.2912) .
RECODE bbhectie  (SYSMIS = 13.4777) .
RECODE bbagua  (SYSMIS = -0.0369) .
RECODE bbvhs  (SYSMIS = 64.3574) .
RECODE bbrefri  (SYSMIS = 90.4985) .
RECODE bbvehi  (SYSMIS = 85.2814) .
RECODE bblava  (SYSMIS = 77.9967) .
RECODE bbradio (SYSMIS = 96.4030) .
RECODE bbestgas  (SYSMIS = 94.2435) .
RECODE bbdiscap (SYSMIS = 98.2055) .

COMPUTE bbcalif = bbhacina + bbdepen + bbninos + bbocupj + bbpiso + bbmu15a + bbtrab + bbhectie + bbagua
                  + bbvhs + bbrefri + bbvehi + bblava + bbradio + bbestgas +  bbdiscap .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=bbcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .

IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = - 100 .
RECODE INDISPEN (SYSMIS = 0) .

IF (REFRI = 1 & LAVA = 1 & VEHI = 1 & VHS = 1 & LICUA = 1 & BAO1 = 1 & AGUA1 = 1
   & ESTGAS = 1 & LUZ = 1 & TV = 1) NEC = - 100 .
IF (RADIO = 1 & ESTGAS = 1 & LICUA = 1) COCINA = - 100 .
IF (animales=1) animsf = -25 .
RECODE  COCINA animsf NEC (SYSMIS = 0) .

.XECUTE .

COMPUTE bbcalif1 = bbcalif +  viejitos + indispen + cocina + animsf + NEC .
EXECUTE .

COMPUTE bbpobre = 0 .
```

```
DO IF (bbcalif1 < 527.015) .
RECODE
  bbpobre  (0=1)  .
END IF .
EXECUTE .

DO IF (vehi = 0 & bbpobre = 1) .
RECODE
  bbpobre  (1=0)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 bbpobre  .
```

REGIÓN 28. ALTIPLANO
FASE 6
MODELO aa

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES= hacina depen ninos ocupj_1 piso_1 mu15a49 trab151 hectie1 agua_1
             vhs refri vehi lava radio estgas discap
  /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE AAHACINA = -5*HACINA .
COMPUTE AADEPEN = -32*DEPEN .
COMPUTE AANINOS = -28*NINOS .
COMPUTE AAOCUPJ = -24*OCUPJ_1 .
COMPUTE AAPISO = 11*PISO_1 .
COMPUTE AAMU15A = -11*MU15A49 .
COMPUTE AATRAB = -33*TRAB151 .
COMPUTE AAHECTIE = 3*HECTIE1 .
COMPUTE AAAGUA = 6*AGUA_1 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 1) AAVHS = 62 .

IF (REFRI = 0) AAREFRI = 100 .
IF (REFRI = 1) AAREFRI = 88 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 81 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 75 .

IF (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 88 .

IF (ESTGAS = 0) AAESTGAS= 100 .
IF (ESTGAS = 1) AAESTGAS = 87

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 72

EXECUTE.

FREQUENCIES
  VARIABLES= aahacina aadepen aaninos aaocupj aapiso aamu15a aatrab aahectie aaagua
             aavhs aarefri aavehi aalava aaradio aaestgas aadiscap
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aahacina) | MISSING(aadepen) | MISSING(aaninos) | MISSING(aaocupj) | MISSING(aapiso)
  | MISSING(aamu15a) | MISSING(aatrab)  | MISSING (aahectie) | MISSING (aaagua)
  | MISSING(aavhs) | MISSING(aarefri)  | MISSING(aavehi) | MISSING(aalava)
  | MISSING(aaradio) | MISSING(aaestgas) | MISSING(aadiscap)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aahacina  (SYSMIS = -13.1579) .
RECODE aadepen  (SYSMIS = -80.5613) .
RECODE aaninos  (SYSMIS = -45.6842) .
RECODE aaocupj  (SYSMIS = -18.2400).
RECODE aapiso  (SYSMIS = 2.6168) .
RECODE aamu15a  (SYSMIS = -8.6842) .
```

```
RECODE aatrab  (SYSMIS = 0) .
RECODE aahectie  (SYSMIS = 0) .
RECODE aaagua  (SYSMIS = -3.1200) .
RECODE aavhs  (SYSMIS = 64.0000) .
RECODE aarefri  (SYSMIS = 95.5789) .
RECODE aavehi  (SYSMIS = 85.0000) .
RECODE aalava  (SYSMIS = 85.5623) .
RECODE aaradio (SYSMIS = 98.7368) .
RECODE aaestgas  (SYSMIS = 96.5789) .
RECODE aadiscap (SYSMIS = 97.0526) .

COMPUTE aacalif = aahacina + aadepen + aaninos + aaocupj + aapiso + aamu15a + aatrab + aahectie + aaagua
                  + aavhs + aarefri + aavehi + aalava + aaradio + aaestgas +  aadiscap .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .
RECODE viejitos (SYSMIS=0) .
EXECUTE.

COMPUTE aacalif1=aacalif + viejitos .
execute .

COMPUTE aapobre = 0 .
DO IF (aacalif1 < 527.015) .
RECODE
  aapobre  (0=1)  .
  ND IF .
EXECUTE .

DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
```

```
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES= aapobre lp98  .
```

REGIÓN 28. ALTIPLANO
FASE 3
MODELO bb

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES= hacina depen ninos ocupj_1 piso_1 mu15a49 trab151 hectie1 agua_1
             vhs refri vehi lava radio estgas discap
  /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .41 .59
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

COMPUTE bbHACINA = -5*HACINA .
COMPUTE bbDEPEN = -23*DEPEN .
COMPUTE bbNINOS = -24*NINOS .
COMPUTE bbOCUPJ = 90*OCUPJ_1 .
COMPUTE bbPISO = 8*PISO_1 .
COMPUTE bbMU15A = 8*MU15A49 .
COMPUTE bbTRAB = 8*TRAB151 .
COMPUTE bbHECTIE = 3*HECTIE1 .
COMPUTE bbAGUA = 11*AGUA_1 .

IF (VHS = 0) bbVHS = 100 .
IF (VHS = 1) bbVHS = 69 .

IF (REFRI = 0) bbREFRI = 100 .
IF (REFRI = 1) bbREFRI = 115 .

IF (VEHI = 0) bbVEHI = 100 .
IF (VEHI = 1) bbVEHI = 77 .

 F (LAVA = 0) bbLAVA = 100 .
IF (LAVA = 1) bbLAVA = 85 .

IF (RADIO = 0) bbRADIO = 100 .
IF (RADIO = 1) bbRADIO = 85 .

IF (ESTGAS = 0) bbESTGAS= 100 .
IF (ESTGAS = 1) bbESTGAS = 91.

IF (DISCAP = 0) bbDISCAP = 100 .
IF (DISCAP = 1) bbDISCAP = 81.

EXECUTE.

FREQUENCIES
  VARIABLES= bbhacina bbdepen bbninos bbocupj bbpiso bbmu15a bbtrab bbhectie bbagua
             bbvhs bbrefri bbvehi bblava bbradio bbestgas bbdiscap
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE bbinput = 0 .
EXECUTE .
DO IF (MISSING(bbhacina) | MISSING(bbdepen) | MISSING(bbninos) | MISSING(bbocupj) | MISSING(bbpiso)
  | MISSING(bbmu15a) | MISSING(bbtrab)  | MISSING (bbhectie) | MISSING (bbagua)
  | MISSING(bbvhs) | MISSING(bbrefri)  | MISSING(bbvehi) | MISSING(bblava)
  | MISSING(bbradio) | MISSING(bbestgas) | MISSING(bbdiscap)) .
RECODE
  bbinput  (0=1)  .
END IF .
EXECUTE .

RECODE bbhacina  (SYSMIS = -12.0449) .
RECODE bbdepen  (SYSMIS = -52.8718) .
RECODE bbninos  (SYSMIS = -34.4606) .
RECODE bbocupj  (SYSMIS = 42.1463).
RECODE bbpiso  (SYSMIS = 1.6544) .
RECODE bbmu15a  (SYSMIS = 9.0671) .
```

```
RECODE bbtrab  (SYSMIS = 0.3637) .
RECODE bbhectie  (SYSMIS = 24.3088) .
RECODE bbagua  (SYSMIS = -1.7249) .
RECODE bbvhs  (SYSMIS = 72.9850) .
RECODE bbrefri  (SYSMIS = 108.9380) .
RECODE bbvehi  (SYSMIS = 83.3627) .
RECODE bblava  (SYSMIS = 90.0817) .
RECODE bbradio (SYSMIS = 96.1613) .
RECODE bbestgas  (SYSMIS = 97.8581) .
RECODE bbdiscap (SYSMIS = 98.7515) .

COMPUTE bbcalif = bbhacina + bbdepen + bbninos + bbocupj + bbpiso + bbmu15a + bbtrab + bbhectie + bbagua
                  + bbvhs + bbrefri + bbvehi + bblava + bbradio + bbestgas + bbdiscap .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=bbcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .41 .59
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .
RECODE viejitos (SYSMIS=0) .
EXECUTE.

IF (agua1=1  & luz=1  & piso= 1) indis= -100 .
RECODE indis (SYSMIS=0) .
EXECUTE .

IF (Refri = 1 & ESTGAS = 1 & LICUA = 1) COCINA = - 100 .
RECODE COCINA (SYSMIS = 0) .
execute.

COMPUTE bbcalif1=bbcalif + viejitos + indis + cocina.
execute .

COMPUTE bbpobre = 0 .
DO IF (bbcalif1< 684.03) .
```

```
RECODE
  bbpobre  (0=1)  .
END IF .
EXECUTE .

COMPUTE nvopob = 0 .
DO IF (aapobre = 0 & bbpobre=1) .
RECODE
  nvopob  (0=1)  .
END IF .
EXECUTE .

IF ((ULT_NIV=4 | ULT_NIV=6 | ULT_NIV=7) & SEG_SOC=2) MAESTRO=1 .

DO IF (MAESTRO=1) .
RECODE
 NVOP (1=0) .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES= bbpobre lp98  .
```

REGIÓN 28. HUASTECA
FASE 6
Modelo bb

No aplica el modelo para 18 hogares.

REGIÓN 28. ALTIPLANO
FASE 8
MODELO aa

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES= hacina depen ninos ocupj_1 piso_1 mu15a49 trab151 hectie1 agua_1
              vhs refri vehi lava radio estgas discap
  /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE aaHACINA = -5*HACINA .
COMPUTE aaDEPEN = -32*DEPEN .
COMPUTE aaNINOS = -28*NINOS .
COMPUTE aaOCUPJ = -24*OCUPJ_1 .
COMPUTE aaPISO = 11*PISO_1 .
COMPUTE aaMU15A = -11*MU15A49 .
COMPUTE aaTRAB = -33*TRAB151 .
COMPUTE aaHECTIE = 3*HECTIE1 .
COMPUTE aaAGUA = 6*AGUA_1 .

IF (VHS = 0) aaVHS = 100 .
IF (VHS = 1) aaVHS = 62 .

IF (REFRI = 0) aaREFRI = 100 .
IF (REFRI = 1) aaREFRI = 88 .

 F (VEHI = 0) aaVEHI = 100 .
IF (VEHI = 1) aaVEHI = 81 .

IF (LAVA = 0) aaLAVA = 100 .
IF (LAVA = 1) aaLAVA = 75 .

IF (RADIO = 0) aaRADIO = 100 .
IF (RADIO = 1) aaRADIO = 88 .

IF (ESTGAS = 0) aaESTGAS= 100 .
IF (ESTGAS = 1) aaESTGAS = 87

IF (DISCAP = 0) aaDISCAP = 100 .
IF (DISCAP = 1) aaDISCAP = 72

EXECUTE.

FREQUENCIES
 VARIABLES= aahacina aadepen aaninos aaocupj aapiso aamu15a aatrab aahectie aaagua
            aavhs aarefri aavehi aalava aaradio aaestgas aadiscap
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aahacina) | MISSING(aadepen) | MISSING(aaninos) | MISSING(aaocupj) | MISSING(aapiso)
      | MISSING(aamu15a) | MISSING(aatrab)  | MISSING (aahectie) | MISSING (aaagua)
      | MISSING(aavhs) | MISSING(aarefri)  | MISSING(aavehi) | MISSING(aalava)
      | MISSING(aaradio) | MISSING(aaestgas) | MISSING(aadiscap)) .
RECODE
 aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aahacina  (SYSMIS = -13.7644) .
RECODE aadepen  (SYSMIS = -72.6155) .
RECODE aaninos  (SYSMIS = -45.2907) .
```

```
RECODE aaocupj  (SYSMIS = -0.07400).
RECODE aapiso  (SYSMIS = 0.03365) .
RECODE aamu15a  (SYSMIS = -12.6689) .
RECODE aatrab  (SYSMIS = -1.2912) .
RECODE aahectie  (SYSMIS = 13.4777) .
 ECODE aaagua  (SYSMIS = -0.0369) .
RECODE aavhs  (SYSMIS = 64.3574) .
RECODE aarefri  (SYSMIS = 90.4985) .
RECODE aavehi  (SYSMIS = 85.2814) .
RECODE aalava  (SYSMIS = 77.9967) .
RECODE aaradio (SYSMIS = 96.4030) .
RECODE aaestgas  (SYSMIS = 94.2435) .
RECODE aadiscap (SYSMIS = 98.2055) .

COMPUTE aacalif = aahacina + aadepen + aaninos + aaocupj + aapiso + aamu15a + aatrab + aahectie + aaagua
                  + aavhs + aarefri + aavehi + aalava + aaradio + aaestgas +  aadiscap .
EXECUTE .

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES=aacalif
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  .42 .58
 /STATISTICS=raw TABLE crossvalid
 /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

 REQUENCIES
 VARIABLES=aacalif
 /FORMAT=NOTABLE
 /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
 VARIABLES=aacalif
 /FORMAT=NOTABLE
 /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .
RECODE viejitos (SYSMIS=0) .
EXECUTE.

COMPUTE aacalif=aacalif + viejitos .
execute .

COMPUTE aapobre = 0 .
 ) IF (aacalif < 588.07) .
RECODE
 aapobre  (0=1)  .
END IF .
EXECUTE .
```

```
DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
END IF .
EXECUTE .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .
IF (ELIMIN = 1) AAPOBRE = 0 .
EXECUTE .

FREQUENCIES
  VARIABLES= aapobre lp98  .
```

```
*****************************************
*********puntajes región 32**************
*****************************************

***Modelo  AA

  `SCRIMINANT
  .GROUPS=LP98(0 1)
  /VARIABLES= depen ninos  trab151  ocupj_1 esc  discap
    piso_1  aguaba_1 pared_1  hectie1 radio estgas  vhs  vehi lava
    cal_agua tocadisc ventila
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .


***Calificación


COMPUTE AADEPEN=-52*DEPEN .
COMPUTE AANINOS=-18*NINOS .
COMPUTE AATRAB15 = -75 * TRAB151 .
COMPUTE AAOCUPJ = 8 * OCUPJ_1 .
COMPUTE AAESC = 3 * ESC .
COMPUTE AAPISO = 2 * PISO1.
COMPUTE AAAGUABA = 3*AGUABA_1 .
COMPUTE AAPARED = -13 * PARED1.
COMPUTE AAHECTIE = 1 * HECTIE1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 78 .

IF (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 93 .

IF (ESTGAS = 0) AAESTGAS = 100.
IF (ESTGAS = 1) AAESTGAS = 81 .

   (VHS = 0) AAVHS = 100 .
IF (VHS = 0) AAVHS = 80 .

IF (VEHI=0) AAVEHI= 100 .
IF (VEHI=1) AAVEHI= 78 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 83 .

IF (CAL_AGUA = 0) AACAL_AG = 100 .
IF (CAL_AGUA = 1) AACAL_AG = 90 .

IF (TOCADISC = 0) AATOCADI = 100 .
IF (TOCADISC = 1) AATOCADI = 83 .

IF (VENTILA = 0) AAVENTI = 100 .
IF (VENTILA = 1) AAVENTI = 85 .

EXECUTE .

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aatrab15 aaocupj aaesc aapiso aaaguaba aapared aahectie aadiscap
        aaradio aaestgas aavhs aavehi aalava aacal_ag aatocadi aaventi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING(aatrab15) | MISSING(aaocupj) | MISSING(aaesc)
  | MISSING(aapiso) | MISSING(aaaguaba) | MISSING(aapared) | MISSING(aahectie) | MISSING(aadiscap) | MISSING(aaradio)
  | MISSING(aaestgas) | MISSING(aavhs) | MISSING(aavehi) | MISSING (aalava) | MISSING(aacal_ag) | MISSING (aatocadi)
  | MISSING(aaventi) ) .
  RECODE
    ainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables
```

```
 | MISSING(aaestgas) | MISSING(aavhs) | MISSING(aavehi) | MISSING (aalava) | MISSING(aacal_ag) | MISSING (aatocadi)
 | MISSING(aaventi) ) .
RECODE
 aainput (0=1) .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen (SYSMIS=-112.63) .
RECODE aaninos (SYSMIS=-21.36) .
RECODE aatrab15 (SYSMIS = -2.37) .
RECODE aaocupj (SYSMIS = 3.74) .
RECODE aaesc (SYSMIS= 10.59) .
RECODE aapiso (SYSMIS = 3.10) .
RECODE aaaguaba (SYSMIS= 1.26) .
RECODE aapared (SYSMIS=-109.57) .
RECODE aahectie (SYSMIS = 22.53) .
RECODE aadiscap (SYSMIS = 98.92) .
RECODE aaradio (SYSMIS=97.97) .
RECODE aaestgas (SYSMIS = 95.73) .
RECODE aavhs (SYSMIS = 80.00) .
RECODE aavehi (SYSMIS=81.15) .
RECODE aalava (SYSMIS=86.29) .
RECODE aacal_ag (SYSMIS = 90.26) .
RECODE aatocadi (SYSMIS=83.74) .
RECODE aaventi (SYSMIS = 94.95) .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aatrab15 + aaocupj + aaesc + aapiso + aaaguaba + aapared + aahectie
                  + aadiscap + aaradio + aaestgas + aavhs + aavehi + aalava + aacal_ag + aatocadi + aaventi .
EXECUTE .

***filtros

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .

COMPUTE AACALIF1 = AACALIF + VIEJITOS .

EXECUTE.

*** línea de corte

COMPUTE aapobre = 0 .
DO IF (aacalif1 < 609.01) .
RECODE
 aapobre (0=1) .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES = lp98 AAPOBRE .
```

```
*****************************************
*********puntajes región 32*************
*****************************************

***Modelo AA

  'SCRIMINANT
  GROUPS=LP98(0 1)
 /VARIABLES= depen ninos  trab151  ocupj_1 esc  discap
   piso_1  aguaba_1 pared_1  hectie1 radio estgas  vhs  vehi lava
   cal_agua tocadisc ventila
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .


***Calificación

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-52*DEPEN .
COMPUTE AANINOS=-18*NINOS .
COMPUTE AATRAB15 = -75 * TRAB151 .
COMPUTE AAOCUPJ = 8 * OCUPJ_1 .
COMPUTE AAESC = 3 * ESC .
COMPUTE AAPISO = 2 * PISO1.
COMPUTE AAAGUABA = 3*AGUABA_1 .
COMPUTE AAPARED = -13 * PARED1.
COMPUTE AAHECTIE = 1 * HECTIE1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 78 .

IF (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 93 .

IF (ESTGAS = 0) AAESTGAS = 100.
   (ESTGAS = 1) AAESTGAS = 81 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 0) AAVHS = 80 .

IF (VEHI=0) AAVEHI= 100 .
IF (VEHI=1) AAVEHI= 78 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 83 .

IF (CAL_AGUA = 0) AACAL_AG = 100 .
IF (CAL_AGUA = 1) AACAL_AG = 90 .

IF (TOCADISC = 0) AATOCADI = 100 .
IF (TOCADISC = 1) AATOCADI = 83 .

IF (VENTILA = 0) AAVENTI = 100 .
IF (VENTILA = 1) AAVENTI = 85 .

EXECUTE .

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aatrab15 aaocupj aaesc aapiso aaaguaba aapared aahectie aadiscap
          aaradio aaestgas aavhs aavehi aalava aacal_ag aatocadi aaventi
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING(aatrab15) | MISSING(aaocupj) | MISSING(aaesc)
  | MISSING(aapiso) | MISSING(aaaguaba) | MISSING(aapared) | MISSING(aahectie) | MISSING(aadiscap) | MISSING(aaradio)
  | MISSING(aaestgas) | MISSING(aavhs) | MISSING(aavehi) | MISSING (aalava) | MISSING(aacal_ag) | MISSING (aatocadi)
  | MISSING(aaventi) ) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .
```

```
COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING(aatrab15) | MISSING(aaocupj) | MISSING(aaesc)
  | MISSING(aapiso) | MISSING(aaaguaba) | MISSING(aapared) | MISSING(aahectie) | MISSING(aadiscap) | MISSING(aaradio)
  | MISSING(aaestgas) | MISSING(aavhs) | MISSING(aavehi) | MISSING (aalava) | MISSING(aacal_ag) | MISSING (aatocadi)
  | MISSING(aaventi) ) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS=-105.77)  .
RECODE aaninos  (SYSMIS=-21.24)  .
RECODE aatrab15 (SYSMIS = -2.05) .
RECODE aaocupj (SYSMIS = 0.10) .
RECODE aaesc  (SYSMIS= 11.24)  .
RECODE aapiso (SYSMIS = 3.38) .
RECODE aaaguaba  (SYSMIS= 0.03)  .
RECODE aapared (SYSMIS=-125.74)  .
RECODE aahectie (SYSMIS = 7.14) .
RECODE aadiscap (SYSMIS = 98.79) .
RECODE aaradio  (SYSMIS=97.55)  .
RECODE aaestgas (SYSMIS = 93.25) .
RECODE aavhs (SYSMIS = 80.00) .
RECODE aavehi  (SYSMIS=83.21)  .
RECODE aalava  (SYSMIS=87.52)  .
RECODE aacal_ag (SYSMIS = 90.35) .
RECODE aatocadi  (SYSMIS=84.41)  .
RECODE aaventi (SYSMIS = 93.76) .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aatrab15 + aaocupj + aaesc + aapiso + aaaguaba + aapared + aahectie
                  + aadiscap + aaradio + aaestgas + aavhs + aavehi + aalava + aacal_ag + aatocadi + aaventi .

EXECUTE .


***se calcula la línea de corte y se obtienen los pobres
***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .48  .52
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .


USE ALL.
COMPUTE filter_$=(dis_1= 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
```

```
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

***filtros

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .

COMPUTE AACALIF1 = AACALIF + VIEJITOS  .

EXECUTE.


***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

COMPUTE aapobre = 0 .
DO IF (aacalif1 < 605.50) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) AAPOBRE = 0 .

EXECUTE .

FREQUENCIES
   VARIABLES = lp98 AAPOBRE ELIMIN.

COMPUTE fecha = 990702 .
COMPUTE FOPO = 12 .
EXECUTE.

SORT CASES BY
  entidad (A) mpio (A) local (A) folio (A) .

SAVE OUTFILE='e:\Fase8\PUNTEO\REG_32\reg32j_12.sav'
   /COMPRESSED.


AGGREGATE
  /OUTFILE='E:\Fase8\punteo\REG_32\AGGR.SAV'
  /BREAK=entidad mpio local folio
  /aapobre = FIRST(aapobre).

GET
  FILE='E:\Fase8\punteo\REG_32\Aggr.sav'.
EXECUTE .

FILTER OFF.
```

```
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\Fase8\punteo\entregas\990702\fopo32_12.dbf'
  /TYPE=DB4 /MAP /REPLA.



***LOCS

***crear archivo de control

GET
  FILE='E:\Fase8\PUNTEO\REG_32\reg32j_12.sav'.
EXECUTE .

IF (aapobre = 1) FOLPOB = 1.
IF (aapobre = 1) PERPOB = TOTPER .
RECODE FOLPOB PERPOB (SYSMIS = 0) .

COMPUTE X = 1 .

EXECUTE.

SAVE OUTFILE='E:\Fase8\punteo\REG_32\reg32j_12.sav'
   /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\Fase8\punteo\reg_32\locs32_12.sav'
  /BREAK=entidad mpio local
  /hoglocal = SUM(x) /totper_1 = SUM(totper) /hogpobre = SUM(folpob) /perpob_1 =
  SUM(perpob) /region = FIRST(region) /fecha = FIRST(fecha) / fopo = FIRST(fopo) .

GET
  FILE='E:\Fase8\punteo\reg_32\locs32_12.sav'.
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\Fase8\PUNTEO\LOCALS\990702\locs32_12.dbf '
    /TYPE=DB4
    /COMPRESSED.


*******************************************************************************
***Para verificar hogares analizados y hogares beneficiarios*****
*******************************************************************************

DESCRIPTIVES
  VARIABLES=hoglocal hogpobre
  /STATISTICS=SUM .

***Para verificar la información de jefes

GET
  FILE='E:\fase8\PUNTEO\REG_32\reg32j_12.sav'.
EXECUTE .

FREQUENCIES
  VARIABLES=peryjef
  /ORDER  ANALYSIS .

***Para verificar la información de personas

GET
  FILE='E:\fase8\PUNTEO\REG_32\reg32p_12.sav'.
EXECUTE .

RENAME VARIABLES
          ent_fed = entidad / munici = mpio / locali = local .
```

```
SORT CASES BY
  entidad (A) mpio (A) local (A) folio (A) .

MATCH FILES /FILE=*
 /TABLE='E:\Fase8\Punteo\Reg_32\reg32j_12.sav'
 /RENAME (aaaguaba aacal_ag aacalif aacalif1 aadepen aadiscap aaesc aaestgas
  aahectie aainput aalava aaninos aaocupj aapared aapiso aaradio aatocadi
  aatrab15 aavehi aaventi aavhs adm_gas_ agua1 agua_1 agua_ter agua_viv
  aguaba1 aguaba_1 anim1 anim2 anim3 anim4 anim5 anim6 anim7 anim8 animales
  apo_ing_ asi_esc ate_med_ auto_pro bao bao1 bao_1 bao_agua bueyes burros
  caballos cal_agua camion_p cerdos chivos con_inac con_tra conejos conyuge
  cuan_mur d_r depen dias_tra dif_hog disc_ani disc_ens discap edad edo_civ ej
  ej_1ertr elimin emigro es_ayuda es_ciega es_falta es_menta es_muda es_sorda
  esc estgas fam_bien fam_entr fecha folpob fopo gallinas hacina hect_rie
  hect_tem hectie1 ido_esc ing_hog inm15_1 inmh15pc inmp_1 itmh itmh15
  itmh15pe itmh15tp itmh_tpe itmhtper lava leche leer_esc leng_esp leng_mas
  lengua licua lnin15pc lp98 luz med_nin_ mot_no_t mu15a49 muro na8a17 nin0a1
  nin2a5 nin5a15 nin6a7 nin8a15 nin_sol ninos
 no8a17 noasi1 noasi15 num_dias num_hec num_hog ocupj ocupj1 ocupj_1 pared1
  pared_1 per_ayud per_cieg per_falt per_ment per_muda per_muri per_ocup
  per_sord percep perpob peryjef piso piso1 piso_1 predios prod_cul radio
  refri region reses result seg_mas seg_soc seguro sexo sit_viv taller techo
  tierra tit_lech tit_tort tocadisc tom_dec_ ton_cos1 ton_cos2 ton_cos3
  tortilla tot_anim tot_cuar tot_per totper totpers trab trab15 trab151
  trab_tem ttem_din ttem_lug ttem_mas ttem_mdi ttem_mes tv ult_gra ult_niv
  v111 v112 v40 v42 v44 v46 v66 v67 v96 v97 vehi ventila ver_ing_ veritrab vhs
  viejitos x = d0 d1 d2 d3 d4 d5 d6 d7 d8 d9 d10 d11 d12 d13 d14 d15 d16 d17
  d18 d19 d20 d21 d22 d23 d24 d25 d26 d27 d28 d29 d30 d31 d32 d33 d34 d35 d36
  d37 d38 d39 d40 d41 d42 d43 d44 d45 d46 d47 d48 d49 d50 d51 d52 d53 d54 d55
  d56 d57 d58 d59 d60 d61 d62 d63 d64 d65 d66 d67 d68 d69 d70 d71 d72 d73 d74
  d75 d76 d77 d78 d79 d80 d81 d82 d83 d84 d85 d86 d87 d88 d89 d90 d91 d92 d93
  d94 d95 d96 d97 d98 d99 d100 d101
 d102 d103 d104 d105 d106 d107 d108 d109 d110 d111 d112 d113 d114 d115 d116
  d117 d118 d119 d120 d121 d122 d123 d124 d125 d126 d127 d128 d129 d130 d131
  d132 d133 d134 d135 d136 d137 d138 d139 d140 d141 d142 d143 d144 d145 d146
  d147 d148 d149 d150 d151 d152 d153 d154 d155 d156 d157 d158 d159 d160 d161
  d162 d163 d164 d165 d166 d167 d168 d169 d170 d171 d172 d173 d174 d175 d176
  d177 d178 d179 d180 d181 d182 d183 d184 d185 d186 d187 d188 d189 d190 d191
  d192 d193 d194 d195 d196 d197 d198 d199 d200 d201 d202)
 /BY entidad mpio local folio
 /DROP= d0 d1 d2 d3 d4 d5 d6 d7 d8 d9 d10 d11 d12 d13 d14 d15 d16 d17 d18 d19
  d20 d21 d22 d23 d24 d25 d26 d27 d28 d29 d30 d31 d32 d33 d34 d35 d36 d37 d38
  d39 d40 d41 d42 d43 d44 d45 d46 d47 d48 d49 d50 d51 d52 d53 d54 d55 d56 d57
  d58 d59 d60 d61 d62 d63 d64 d65 d66 d67 d68 d69 d70 d71 d72 d73 d74 d75 d76
  d77 d78 d79 d80 d81 d82 d83 d84 d85 d86 d87 d88 d89 d90 d91 d92 d93 d94 d95
  d96 d97 d98 d99 d100 d101 d102 d103 d104 d105 d106 d107 d108 d109 d110 d111
  d112
 d113 d114 d115 d116 d117 d118 d119 d120 d121 d122 d123 d124 d125 d126 d127
  d128 d129 d130 d131 d132 d133 d134 d135 d136 d137 d138 d139 d140 d141 d142
  d143 d144 d145 d146 d147 d148 d149 d150 d151 d152 d153 d154 d155 d156 d157
  d158 d159 d160 d161 d162 d163 d164 d165 d166 d167 d168 d169 d170 d171 d172
  d173 d174 d175 d176 d177 d178 d179 d180 d181 d182 d183 d184 d185 d186 d187
  d188 d189 d190 d191 d192 d193 d194 d195 d196 d197 d198 d199 d200 d201 d202.
EXECUTE.

FREQUENCIES
  VARIABLES=AAPOBRE .

***

SAVE OUTFILE='e:\fase8\punteo\REG_32\reg32p_12.sav'
  /COMPRESSED.
```

```
*****************************************
*********puntajes región 32*************
*****************************************

***Modelo BB

   SCRIMINANT
   GROUPS=LP98(0 1)
  /VARIABLES= depen ninos   trab151  ocupj_1 esc  discap
    piso_1  pared_1   hectie1 radio estgas    vehi
     tocadisc ventila
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .


***Calificación

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE BBDEPEN=-37*DEPEN .
COMPUTE BBNINOS=-42*NINOS .
COMPUTE BBTRAB15 = -107 * TRAB151 .
COMPUTE BBOCUPJ = 27 * OCUPJ_1 .
COMPUTE BBESC = 10 * ESC .
COMPUTE BBPISO = 84 * PISO1.
COMPUTE BBPARED = -9 * PARED1.
COMPUTE BBHECTIE = 2 * HECTIE1 .

IF (DISCAP = 0) BBDISCAP = 100 .
IF (DISCAP = 1) BBDISCAP = 60 .

IF (RADIO = 0) BBRADIO = 100 .
IF (RADIO = 1) BBRADIO = 87 .

IF (ESTGAS = 0) BBESTGAS = 100.
IF (ESTGAS = 1) BBESTGAS = 58 .

IF (VEHI=0) BBVEHI= 100 .
IF (VEHI=1) BBVEHI= 79 .

IF (TOCADISC = 0) BBTOCADI = 100 .
IF (TOCADISC = 1) BBTOCADI = 83 .

IF (VENTILA = 0) BBVENTI = 100 .
IF (VENTILA = 1) BBVENTI = 75 .

EXECUTE .

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= bbdepen bbninos bbtrab15 bbocupj bbesc bbpiso bbpared bbhectie bbdiscap
          bbradio bbestgas bbvehi bbtocadi bbventi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE bbinput = 0 .
EXECUTE .
DO IF (MISSING(bbdepen) | MISSING(bbninos) | MISSING(bbtrab15) | MISSING(bbocupj) | MISSING(bbesc)
  | MISSING(bbpiso) | MISSING(bbpared) | MISSING(bbhectie) | MISSING(bbdiscap) | MISSING(bbradio)
  | MISSING(bbestgas) | MISSING(bbvehi) | MISSING (bbtocadi)
  | MISSING(bbventi) ) .
RECODE
  bbinput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE bbdepen  (SYSMIS=-86.77)  .
  ECODE bbninos  (SYSMIS=-42.69)  .
  ECODE bbtrab15 (SYSMIS = -2.18) .
RECODE bbocupj (SYSMIS = 18.67) .
RECODE bbesc  (SYSMIS= 35.50)  .
RECODE bbpiso (SYSMIS = 118.08) .
RECODE bbpared (SYSMIS=-68.62)  .
RECODE bbhectie (SYSMIS = 30.44) .
```

```
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE bbdepen  (SYSMIS=-86.77) .
RECODE bbninos  (SYSMIS=-42.69) .
RECODE bbtrab15 (SYSMIS = -2.18) .
RECODE bbocupj (SYSMIS = 18.67) .
RECODE bbesc  (SYSMIS= 35.50) .
RECODE bbpiso (SYSMIS = 118.08) .
RECODE bbpared (SYSMIS=-68.62) .
RECODE bbhectie (SYSMIS = 30.44) .
RECODE bbdiscap (SYSMIS = 98.59) .
RECODE bbradio  (SYSMIS=92.17) .
RECODE bbestgas (SYSMIS = 72.50) .
RECODE bbvehi  (SYSMIS=80.86) .
RECODE bbtocadi  (SYSMIS=83.41) .
RECODE bbventi (SYSMIS = 79.73) .

***se hace la calificación

COMPUTE bbcalif = bbdepen + bbninos + bbtrab15 + bbocupj + bbesc + bbpiso + bbpared + bbhectie
                  + bbdiscap + bbradio + bbestgas + bbvehi + bbtocadi + bbventi .

EXECUTE .


***se calcula la línea de corte y se obtienen los pobres
***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=bbcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42  .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .


USE ALL.
COMPUTE filter_$=(dis_1= 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .
```

```
***filtros

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .

COMPUTE BBCALIF1 = BBCALIF + VIEJITOS  .

EXECUTE.


***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

COMPUTE bbpobre = 0 .
DO IF (bbcalif1 < 564.31) .
RECODE
  bbpobre  (0=1)  .
END IF .
EXECUTE .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & BBPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) BBPOBRE = 0 .

COMPUTE POBRE = BBPOBRE .

EXECUTE .

FREQUENCIES
   VARIABLES = lp98 BBPOBRE ELIMIN POBRE.

COMPUTE fecha = 991013 .
COMPUTE FOPO = 26 .
EXECUTE.

SORT CASES BY
  entidad (A) mpio (A) local (A) folio (A) .

SAVE OUTFILE='e:\Fase8\PUNTEO\REG_32\reg32j_26.sav'
   /COMPRESSED.


AGGREGATE
  /OUTFILE='E:\Fase8\punteo\REG_32\AGGR.SAV'
  /BREAK=entidad mpio local folio
  /bbpobre = FIRST(bbpobre).

GET
  FILE='E:\Fase8\punteo\REG_32\Aggr.sav'.
EXECUTE .

FILTER OFF.
USE ALL.
SELECT IF(bbpobre = 1).
EXECUTE .

RENAME VARIABLES
   bbpobre = aapobre.

SAVE TRANSLATE OUTFILE='E:\Fase8\punteo\entregas\991013\fopo32_26.dbf'
  /TYPE=DB4 /MAP /REPLA.
```

```
***LOCS

***crear archivo de control

GET
  FILE='E:\Fase8\PUNTEO\REG_32\reg32j_26.sav'.
EXECUTE .

IF (bbpobre = 1) FOLPOB = 1.
IF (bbpobre = 1) PERPOB = TOTPER .
RECODE FOLPOB PERPOB (SYSMIS = 0) .

COMPUTE X = 1 .

EXECUTE.

SAVE OUTFILE='E:\Fase8\punteo\REG_32\reg32j_26.sav'
  /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\Fase8\punteo\reg_32\locs32_26.sav'
  /BREAK=entidad mpio local
  /hoglocal = SUM(x) /totper_1 = SUM(totper) /hogpobre = SUM(folpob) /perpob_1 =
  SUM(perpob) /region = FIRST(region) /fecha = FIRST(fecha) / fopo = FIRST(fopo) .

GET
  FILE='E:\Fase8\punteo\reg_32\locs32_26.sav'.
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\Fase8\PUNTEO\LOCALS\991013\locs32_26.dbf '
    /TYPE=DB4
    /COMPRESSED.


*****************************************************************************
***Para verificar hogares analizados y hogares beneficiarios*****
*****************************************************************************

DESCRIPTIVES
  VARIABLES=hoglocal hogpobre
  /STATISTICS=SUM .

***Para verificar la información de jefes

GET
  FILE='E:\fase8\PUNTEO\REG_32\reg32j_26.sav'.
EXECUTE .

FREQUENCIES
  VARIABLES=peryjef
  /ORDER  ANALYSIS .

***Para verificar la información de personas

GET
  FILE='E:\fase8\PUNTEO\REG_32\reg32p_26.sav'.
EXECUTE .

RENAME VARIABLES
      -     ent_fed = entidad / munici = mpio / locali = local .

SORT CASES BY
  entidad (A) mpio (A) local (A) folio (A) .


MATCH FILES /FILE=*
 /TABLE='E:\Fase8\Punteo\Reg_32\reg32j_26.sav'
 /RENAME (adm_gas_ agua1 agua_1 agua_ter agua_viv aguaba1 aguaba_1 anim1
  anim2 anim3 anim4 anim5 anim6 anim7 anim8 animales apo_ing_ asi_esc ate_med_
```

```
 auto_pro bao bao1 bao_1 bao_agua bbcalif bbcalif1 bbdepen bbdiscap bbesc
 bbestgas bbhectie bbinput bbninos bbocupj bbpared bbpiso bbradio bbtocadi
 bbtrab15 bbvehi bbventi bueyes burros caballos cal_agua camion_p cerdos
 chivos con_inac con_tra conejos conyuge cuan_mur d_r depen dias_tra dif_hog
 disc_ani disc_ens discap edad edo_civ ej ej_1ertr elimin emigro es_ayuda
 es_ciega es_falta es_menta es_muda es_sorda esc estgas fam_bien fam_entr
 fecha folpob fopo gallinas hacina hect_rie hect_tem hectie1 ido_esc ing_hog
 inm15_1 inmh15pc inmp_1 itmh itmh15 itmh15pe itmh15tp itmh_tpe itmhtper lava
 leche leer_esc leng_esp leng_mas lengua licua lnin15pc lp98 luz med_nin_
 mot_no_t mu15a49 muro na8a17 nin0a1 nin2a5 nin5a15 nin6a7 nin8a15 nin_sol
 ninos no8a17 noasi1 noasi15 num_dias
num_hec num_hog ocupj ocupj1 ocupj_1 pared1 pared_1 per_ayud per_cieg
 per_falt per_ment per_muda per_muri per_ocup per_sord percep perpob peryjef
 piso piso1 piso_1 predios prod_cul radio refri region reses result seg_mas
 seg_soc seguro sexo sit_viv taller techo tierra tit_lech tit_tort tocadisc
 tom_dec_ ton_cos1 ton_cos2 ton_cos3 tortilla tot_anim tot_cuar tot_per
 totper totpers trab trab15 trab151 trab_tem ttem_din ttem_lug ttem_mas
 ttem_mdi ttem_mes tv ult_gra ult_niv v111 v112 v40 v42 v44 v46 v66 v67 v96
 v97 vehi ventila ver_ing_ veritrab vhs viejitos x = d0 d1 d2 d3 d4 d5 d6 d7
 d8 d9 d10 d11 d12 d13 d14 d15 d16 d17 d18 d19 d20 d21 d22 d23 d24 d25 d26
 d27 d28 d29 d30 d31 d32 d33 d34 d35 d36 d37 d38 d39 d40 d41 d42 d43 d44 d45
 d46 d47 d48 d49 d50 d51 d52 d53 d54 d55 d56 d57 d58 d59 d60 d61 d62 d63 d64
 d65 d66 d67 d68 d69 d70 d71 d72 d73 d74 d75 d76 d77 d78 d79 d80 d81 d82 d83
 d84 d85 d86 d87 d88 d89 d90 d91 d92 d93 d94 d95 d96 d97 d98 d99 d100 d101
 d102 d103 d104 d105 d106 d107
d108 d109 d110 d111 d112 d113 d114 d115 d116 d117 d118 d119 d120 d121 d122
 d123 d124 d125 d126 d127 d128 d129 d130 d131 d132 d133 d134 d135 d136 d137
 d138 d139 d140 d141 d142 d143 d144 d145 d146 d147 d148 d149 d150 d151 d152
 d153 d154 d155 d156 d157 d158 d159 d160 d161 d162 d163 d164 d165 d166 d167
 d168 d169 d170 d171 d172 d173 d174 d175 d176 d177 d178 d179 d180 d181 d182
 d183 d184 d185 d186 d187 d188 d189 d190 d191 d192 d193 d194 d195 d196 d197
 d198)
 /BY entidad mpio local folio
 /DROP= d0 d1 d2 d3 d4 d5 d6 d7 d8 d9 d10 d11 d12 d13 d14 d15 d16 d17 d18 d19
  d20 d21 d22 d23 d24 d25 d26 d27 d28 d29 d30 d31 d32 d33 d34 d35 d36 d37 d38
  d39 d40 d41 d42 d43 d44 d45 d46 d47 d48 d49 d50 d51 d52 d53 d54 d55 d56 d57
  d58 d59 d60 d61 d62 d63 d64 d65 d66 d67 d68 d69 d70 d71 d72 d73 d74 d75 d76
  d77 d78 d79 d80 d81 d82 d83 d84 d85 d86 d87 d88 d89 d90 d91 d92 d93 d94 d95
  d96 d97 d98 d99 d100 d101 d102 d103 d104 d105 d106 d107 d108 d109 d110 d111
  d112 d113 d114 d115 d116 d117 d118 d119 d120 d121 d122
d123 d124 d125 d126 d127 d128 d129 d130 d131 d132 d133 d134 d135 d136 d137
  d138 d139 d140 d141 d142 d143 d144 d145 d146 d147 d148 d149 d150 d151 d152
  d153 d154 d155 d156 d157 d158 d159 d160 d161 d162 d163 d164 d165 d166 d167
  d168 d169 d170 d171 d172 d173 d174 d175 d176 d177 d178 d179 d180 d181 d182
  d183 d184 d185 d186 d187 d188 d189 d190 d191 d192 d193 d194 d195 d196 d197
  d198.
EXECUTE.

FREQUENCIES
   VARIABLES=BBPOBRE .


***

SAVE OUTFILE='e:\fase8\punteo\REG_32\reg32p_26.sav'
   /COMPRESSED.
```

```
*/*/*/*/*   FASE 3
*/*/*        PUNTAJES DE LA REGION 32
*/*/*/       MODELO AA

***método de STEPWISE

 `ISCRIMINANT
  GROUPS=lp98(0 1)
 /VARIABLES=hacina depen ninos  noasi1 trab151  ocupj_1 ej esc  lengua discap
   piso_1 bao_1 agua_1 aguaba_1 pared_1 luz  hectie1 radio estgas tv vhs refri vehi lava licua
   cal_agua tocadisc ventila
 /ANALYSIS ALL
 /SAVE=CLASS
  /METHOD=WILKS
  /FIN= 3.84
  /FOUT= 2.71
 /PRIORS  .42 .58
 /HISTORY
 /STATISTICS=BOXM RAW TABLE
 /CLASSIFY=NONMISSING POOLED .

***Modelo

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES= depen ninos   trab151  ocupj_1 esc  discap
   piso_1  aguaba_1 pared_1   hectie1 radio estgas  vhs  vehi lava
   cal_agua tocadisc ventila
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

***Calificación

COMPUTE AADEPEN=-52*DEPEN .
COMPUTE AANINOS=-18*NINOS .
COMPUTE AATRAB15 = -75 * TRAB151 .
COMPUTE AAOCUPJ = 8 * OCUPJ_1 .
  OMPUTE AAESC = 3 * ESC .
COMPUTE AAPISO = 2 * PISO1.
COMPUTE AAAGUABA = 3*AGUABA_1 .
COMPUTE AAPARED = -13 * PARED1.
COMPUTE AAHECTIE = 1 * HECTIE1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 78 .

IF (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 93 .

IF (ESTGAS = 0) AAESTGAS = 100.
IF (ESTGAS = 1) AAESTGAS = 81 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 0) AAVHS = 80 .

IF (VEHI=0) AAVEHI= 100 .
IF (VEHI=1) AAVEHI= 78 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 83 .

IF (CAL_AGUA = 0) AACAL_AG = 100 .
IF (CAL_AGUA = 1) AACAL_AG = 90 .

IF (TOCADISC = 0) AATOCADI = 100 .
IF (TOCADISC = 1) AATOCADI = 83 .

IF (VENTILA = 0) AAVENTI = 100 .
IF (VENTILA = 1) AAVENTI = 85 .

EXECUTE .

   calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
 VARIABLES= aadepen aaninos aatrab15 aaocupj aaesc aapiso aaaguaba aapared aahectie aadiscap
        aaradio aaestgas aavhs aavehi aalava aacal_ag aatocadi aaventi
 /FORMAT=NOTABLE
```

```
  /STATISTICS=MEAN .

 COMPUTE aainput = 0 .
 EXECUTE .
 DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING(aatrab15) | MISSING(aaocupj) | MISSING(aaesc)
   | MISSING(aapiso) | MISSING(aaaguaba) | MISSING(aapared) | MISSING(aahectie) | MISSING(aadiscap) | MISSING(aaradio)
   | MISSING(aaestgas) | MISSING(aavhs) | MISSING(aavehi) | MISSING (aalava) | MISSING(aacal_ag) | MISSING (aatocadi)
   MISSING(aaventi) ) .
 RECODE
   aainput  (0=1)  .
 END IF .
 EXECUTE .

 ***se recodifican los valores perdidos con las medias de las variables

 RECODE aadepen  (SYSMIS=-107.63)  .
 RECODE aaninos  (SYSMIS=-21.31)  .
 RECODE aatrab15 (SYSMIS = -2.66) .
 RECODE aaocupj (SYSMIS = 0.02) .
 RECODE aaesc  (SYSMIS= 10.76)  .
 RECODE aapiso (SYSMIS = 3.41) .
 RECODE aaaguaba  (SYSMIS= -0.03)  .
 RECODE aapared (SYSMIS=-128.32)  .
 RECODE aahectie (SYSMIS = 4.37) .
 RECODE aadiscap (SYSMIS = 98.64) .
 RECODE aaradio  (SYSMIS=97.39)  .
 RECODE aaestgas (SYSMIS = 92.99) .
 RECODE aavhs (SYSMIS = 80.00) .
 RECODE aavehi  (SYSMIS=81.98)  .
 RECODE aalava  (SYSMIS=86.98)  .
 RECODE aacal_ag (SYSMIS = 90.37) .
 RECODE aatocadi  (SYSMIS=84.48)  .
 RECODE aaventi (SYSMIS = 93.16) .

 ***se hace la calificación

 COMPUTE aacalif = aadepen + aaninos + aatrab15 + aaocupj + aaesc + aapiso + aaaguaba + aapared + aahectie
                   + aadiscap + aaradio + aaestgas + aavhs + aavehi + aalava + aacal_ag + aatocadi + aaventi .
 EXECUTE .

    se calcula la línea de corte y se obtienen los pobres

 ***discriminante con la línea de pobreza

 DISCRIMINANT
   /GROUPS=LP98(0 1)
   /VARIABLES=aacalif
   /ANALYSIS ALL
   /SAVE=CLASS
   /PRIORS = .42 .58
   /STATISTICS=raw TABLE CROSSVALID
   /CLASSIFY=NONMISSING POOLED .

 ****se checa el último discriminante

 USE ALL.
 COMPUTE filter_$=(dis_1 = 0).
 VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
 VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
 FORMAT filter_$ (f1.0).
 FILTER BY filter_$.
 EXECUTE .

 FREQUENCIES
   VARIABLES=aacalif
   /FORMAT=NOTABLE
   /STATISTICS=MINIMUM .

 USE ALL.
 COMPUTE filter_$=(dis_1 = 1).
 VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
 VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
 FORMAT filter_$ (f1.0).
 FILTER BY filter_$.
    ECUTE .

 FREQUENCIES
   VARIABLES=aacalif
   /FORMAT=NOTABLE
   /STATISTICS= MAXIMUM .
```

```
FILTER OFF.
USE ALL.

EXECUTE .

***filtros

  OMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .
IF (BAO1 = 1 & AGUA1 = 1 & PISO1 = 1) INDISPEN = - 100 .
RECODE INDISPEN (SYSMIS = 0) .
COMPUTE AACALIF = AACALIF + VIEJITOS + indispen .
EXECUTE.

***se checa el mínimo y el máximo y se toma el punto intermedio como linea de corte

COMPUTE aapobre = 0 .
DO IF (aacalif < 609.01) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES = lp98 AAPOBRE .

COMPUTE fecha = 170898 .

COMPUTE FOPO = 10.

EXECUTE.

SAVE OUTFILE='e:\PUNTEO\REG_32\reg32j10.sav'
  /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\punteo\REG_32\AGGR.SAV'
  /BREAK=entidad mpio local folio
  /aapobr_1 = MEAN(aapobre).

  ET
 FILE='E:\punteo\REG_32\Aggr.sav'.
EXECUTE .

RENAME VARIABLES
        aapobr_1 = aapobre .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\punteo\REG_32\fopo32_10.dbf'
  /TYPE=DB4 /MAP /REPLA.
```

```
SAVE OUTFILE='E:\Fase8\punteo\REG_34\REG34J_25.sav'
  /COMPRESSED.

*****************************************************************************************************
*************************************con el archivo de personas**************************************
*****************************************************************************************************
***se llama el archivo regp_#.dbf en la región que se va a trabajar y guardar con extensión .sav


GET FILE='E:\Fase8\punteo\calificar\990920\personas.sav' .
  EXECUTE .

FILTER OFF.
USE ALL.
SELECT IF(region = 34).
EXECUTE .

SAVE OUTFILE='E:\Fase8\punteo\REG_34\REG34P_25.sav'
  /COMPRESSED.

*************RECODIFICACION DE VALORES EXTRAÑOS EN LA DECLARACION DEL INGRESO

RECODE  MONTO (98888=SYSMIS) (99999=SYSMIS)  (88888=SYSMIS) (9999=SYSMIS) (9888=SYSMIS)
(8888=SYSMIS) (999=SYSMIS) (94444=SYSMIS) (9898=SYSMIS)  (88889=SYSMIS)  .
RECODE MON_ING_ (98888=SYSMIS) (99999=SYSMIS) (88888=SYSMIS) (88885=SYSMIS) (9999=SYSMIS) (9888=SYSMIS)
(8888=SYSMIS) (999=SYSMIS) (996=SYSMIS) (908=SYSMIS) (904=SYSMIS) (99=SYSMIS) (89=SYSMIS) (9=SYSMIS)
(8=SYSMIS)  .
RECODE V37 (98888=SYSMIS) (99999=SYSMIS) (900000=SYSMIS) (88888=SYSMIS)  (8888=SYSMIS)  (9999=SYSMIS)
(999=SYSMIS)  (999=SYSMIS)  (99=SYSMIS)  (89=SYSMIS)  (9=SYSMIS)  (8=SYSMIS)    .
RECODE PERIODO (8=SYSMIS) (9=SYSMIS) .
RECODE PER_ING_ (8=SYSMIS) (9=SYSMIS) .
RECODE V38 (8=SYSMIS) (9=SYSMIS) .

**********************INGRESO MENSUAL PERSONAL SIN DISTINCION DE EDAD

IF (PERIODO=1) INTRA=25*MONTO .
IF (PERIODO=2) INTRA=4*MONTO .
IF (PERIODO=3) INTRA=2*MONTO .
IF (PERIODO=4) INTRA=MONTO .
IF (PERIODO=5) INTRA=MONTO/12 .
IF (PERIODO=0) INTRA=0 .

IF (PER_ING_=1) OIN1=25*MON_ING_ .
IF (PER_ING_=2) OIN1=4*MON_ING_ .
IF (PER_ING_=3) OIN1=2*MON_ING_ .
IF (PER_ING_=4) OIN1=MON_ING_ .
IF (PER_ING_=5) OIN1=MON_ING_/12 .
IF (PER_ING_=0) OIN1=0 .

IF (V38=1) OIN2=25*V37 .
IF (V38=2) OIN2=4*V37 .
IF (V38=3) OIN2=2*V37 .
IF (V38=4) OIN2=V37 .
IF (V38=5) OIN2=V37/12 .
IF (V38=0) OIN2=0 .

COMPUTE INMP = INTRA + OIN1 + OIN2 .

IF (SYSMIS(INTRA) &  OIN1>= 0 &  OIN2>= 0) INMP = OIN1 + OIN2 .
IF (SYSMIS(OIN1) & INTRA>=0 & OIN2>=0) INMP = INTRA + OIN2 .
IF (SYSMIS(OIN2) & INTRA>=0 & OIN1>=0) INMP = INTRA + OIN1 .
IF (SYSMIS(INTRA) & SYSMIS(OIN1) & OIN2>=0) INMP=OIN2 .
IF (SYSMIS(INTRA) & SYSMIS(OIN2) & OIN1>=0) INMP=OIN1 .
IF (SYSMIS(OIN1) & SYSMIS(OIN2) & INTRA>=0) INMP=INTRA .
IF (SYSMIS(INTRA) & (INGRE_A = 11 |  SYSMIS(MON_ING_) | SYSMIS(PER_ING_))) INMP = 99999 .
RECODE INMP (99999=SYSMIS) .

**********************INGRESO MENSUAL PERSONAL PARA NIÑOS ENTRE 8 Y 15 AÑOS
```

```
COMPUTE EDAD2 = EDAD .

IF (EDAD2>=8 & EDAD2<=15) EDAD815=1 .
RECODE EDAD815 (SYSMIS=0) .

IF (EDAD815=1) INM15=INMP .
RECODE INM15 (SYSMIS=0) .

EXECUTE .

*******INGRESO MESUAL DEL HOGAR. INGRESO MENSUAL QUE APORTAN AL HOGAR LOS MENORES DE 15 AÑOS

RENAME VARIABLES
        ent_fed = entidad / munici = mpio / locali = local .

compute pyj =1.

AGGREGATE
 /OUTFILE='e:\Fase8\punteo\REG_34\agrreg34.SAV'
 /BREAK=entidad mpio local folio
 /INMP_1 = SUM(INMP) /INM15_1 = SUM(INM15) / peryjef = first(pyj) .

**************************************************************************************************
**********************************con el archivo de hogares**************************************
**************************************************************************************************

***pegar INMP_1 y INM15 del archivo de personas

GET
 FILE='e:\Fase8\punteo\REG_34\REG34J_25.sav'.
EXECUTE .

SORT CASES BY
 entidad (A) mpio (A) local (A) folio (A) .

MATCH FILES /FILE=*
 /TABLE='e:\Fase8\punteo\REG_34\agrreg34.sav'
 /BY entidad mpio local folio.
EXECUTE.

SAVE OUTFILE='e:\Fase8\punteo\REG_34\REG34J_25.sav'
  /COMPRESSED.

COMPUTE INMH15PC = (INMP_1 - INM15_1) / TOTPERS .

***calcular ventiles de ingreso
***calcular el logarítmo natural del ingreso per cápita

SORT CASES BY
 inmh15pc (A) .

COMPUTE LNIN15PC = LN(INMH15PC+1).

EXECUTE.

***imputación de valores obtenidos en SAS para el análisis de discriminante

**********  PESOS DE LA REGION 34

IF(PISO1=     1     )     PISO_1=     -0.764  .
IF(PISO1=     2     )     PISO_1=     1.057   .
IF(PISO1=     3     )     PISO_1=     2.074   .
IF(PARED1=    1     )     PARED_1=    -0.610  .
IF(PARED1=    2     )     PARED_1=    0.792   .
IF(PARED1=    3     )     PARED_1=    -0.876  .
IF(PARED1=    4     )     PARED_1=    -0.761  .
IF(PARED1=    5     )     PARED_1=    -0.831  .
IF(PARED1=    6     )     PARED_1=    0.450   .
IF(PARED1=    7     )     PARED_1=    -0.773  .
```

```
IF(PARED1=     8      )      PARED_1=     -0.233  .
IF(PARED1=     9      )      PARED_1=     -3.938  .
IF(PARED1=     10     )      PARED_1=     0.539   .
IF(PARED1=     11     )      PARED_1=     -0.069  .
IF(PARED1=     12     )      PARED_1=     -0.007  .
IF(PARED1=     13     )      PARED_1=     11.624  .
IF(AGUABA1=    1      )      AGUABA_1=    -0.033  .
IF(AGUABA1=    2      )      AGUABA_1=    -0.866  .
IF(AGUABA1=    3      )      AGUABA_1=    -0.095  .
IF(AGUABA1=    4      )      AGUABA_1=    0.934   .
IF(AGUABA1=    5      )      AGUABA_1=    -0.177  .
IF(AGUABA1=    6      )      AGUABA_1=    1.280   .
IF(AGUABA1=    7      )      AGUABA_1=    2.116   .
IF(AGUABA1=    8      )      AGUABA_1=    3.233   .
IF(OCUPJ1=     0      )      OCUPJ_1=     0.299   .
IF(OCUPJ1=     1      )      OCUPJ_1=     -0.939  .
IF(OCUPJ1=     2      )      OCUPJ_1=     0.850   .
IF(OCUPJ1=     3      )      OCUPJ_1=     0.622   .
IF(OCUPJ1=     4      )      OCUPJ_1=     -0.299  .
IF(OCUPJ1=     5      )      OCUPJ_1=     2.056   .
IF(OCUPJ1=     6      )      OCUPJ_1=     0.876   .
IF(OCUPJ1=     7      )      OCUPJ_1=     -1.623  .
IF(OCUPJ1=     8      )      OCUPJ_1=     1.879   .
IF(OCUPJ1=     9      )      OCUPJ_1=     1.560   .
IF(AGUA1=      1      )      AGUA_1=      0.321   .
IF(AGUA1=      2      )      AGUA_1=      -0.658  .
IF(AGUA1=      3      )      AGUA_1=      2.386   .
IF(BAO1=       1      )      BAO_1= -0.578  .
IF(BAO1=       2      )      BAO_1= 0.294   .
IF(BAO1=       3      )      BAO_1= 2.963   .

EXECUTE.

***cálculo de medias para verificar tendencias

IF (INMH15PC <= 409.3) LP98 = 1 .
IF (INMH15PC > 409.3) LP98 = 0 .

EXECUTE.

SAVE OUTFILE='e:\Fase8\punteo\REG_34\REG34J_25.sav'
  /COMPRESSED.


MEANS
  TABLES=lp98  BY piso1 pared1 aguaba1 ocupj agua1 bao1
  /CELLS MEAN  .


***análisis de discriminante

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=depen ninos  trab151 hacina esc   discap  piso_1
  radio tv licua aguaba_1  estgas vehi
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  = .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .
```

```
*************************************************************************************************
**********Programa para calcular los hogares beneficiarios de la OCTAVA FASE del programa**********
*************************************************************************************************

        *****                    DE LA REGION 34                    *****

*************************************************************************************************
*************************************con el archivo de hogares*************************************
*************************************************************************************************

***se llama el archivo regj_#.dbf en la región que se va a trabajar y guardar con extensión .sav


GET FILE='E:\Fase8\punteo\calificar\990920\jefes.sav' .
  EXECUTE .

FILTER OFF.
USE ALL.
SELECT IF(region = 34).
EXECUTE .

SAVE OUTFILE='E:\Fase8\punteo\REG_34\REG34J_25.sav'
  /COMPRESSED.

****Se cambian las variables: edad,dias_tra,num_hec,caballos,burros,bueyes,chivos,reses,gallinas,cerdos,conejos,totpers

COMPUTE EJ = edad .
COMPUTE NUM_DIAS = dias_tra .
COMPUTE ANIM1 = caballos .
COMPUTE ANIM2 = burros .
COMPUTE ANIM3 = bueyes .
COMPUTE ANIM4 = chivos .
COMPUTE ANIM5 = reses .
COMPUTE ANIM6 = gallinas .
COMPUTE ANIM7 = cerdos .
COMPUTE ANIM8 = conejos .
COMPUTE TOTPER = totpers .

***Recodificación del nombre de algunas variables

RENAME VARIABLES
  ent_fed = entidad / munici = mpio / locali = local / res_entr = result
 / habla_di = lengua / hab_dia_ = leng_mas / habla_es = leng_esp
 / ver_con_ = veritrab / pos_ocu = ocupj / seg_soc_ = seg_mas
 / per_ocu = per_ocup / edad_pri = ej_1ertr / v30 = ttem_mas / lug_trab = ttem_lug
 / mes_trab = ttem_mes / din_env = ttem_din / din_env_ = ttem_mdi / piso_viv = piso
 / tech_viv = techo  / muro_viv = muro / exc_viv = bao / exc_agua = bao_agua / luz_ele = luz
 / licuador = licua / est_gas = estgas / televis = tv / videocas = vhs / tierr_ag = tierra
 / cu_ti_ag = predios / luz_ele = luz / lavadora = lava .

***Recodificación de variables

RECODE num_hog  result  tot_per  sexo  lengua  leng_mas  leng_esp
 leer_esc  ido_esc  ult_gra  ult_niv  asi_esc  con_tra  veritrab  con_inac
 ocupj  seg_soc mot_no_t ej_1ertr  trab_tem  ttem_mas  ttem_lug
 edo_civ  conyuge  nin_sol  tortilla tit_tort  leche  tit_lech  es_ciega
 es_muda  es_sorda  es_menta  es_falta es_ayuda  emigro  sit_viv  piso
 techo  muro  tot_cuar  agua_ter agua_viv  bao  bao_agua  tierra
 totper (0=SYSMIS) .

DO IF (tierra = 2 | tierra = 9) .
RECODE
  num_hec hect_rie hect_tem (0=SYSMIS)  .
END IF .
EXECUTE .

RECODE sexo lengua (2=0) (9=sysmis) .

RECODE licua refri estgas cal_agua radio tocadisc tv vhs lava ventila animales luz (1=0) (9=sysmis).
```

```
RECODE licua refri estgas cal_agua radio tocadisc tv vhs lava ventila animales luz (2=1) .

EXECUTE.

***Creación de algunas variables

COMPUTE HECTIE1 = NUM_HEC .

IF (CON_TRA <= 3 | VERITRAB <= 5) TRAB = 1 .
IF (CON_TRA = 4 | VERITRAB = 6) TRAB = 0 .

IF (AUTO_PRO = 1 | CAMION_P = 1) VEHI = 0 .
IF (AUTO_PRO = 2 & CAMION_P = 2) VEHI = 1 .

IF (NIN5A15 > 0) NOASI1 = NOASI15 / NIN5A15.

IF (NIN8A15 > 0) TRAB151 = TRAB15 / NIN8A15.

IF (ULT_NIV = 2) ESC = ULT_GRA .
IF (ULT_NIV = 3) ESC = 6 + ULT_GRA .
IF (ULT_NIV = 4) ESC = 9 + ULT_GRA .
IF (ULT_NIV = 5) ESC = 9 + ULT_GRA .
IF (ULT_NIV = 6) ESC = 12 + ULT_GRA .
IF (ULT_NIV = 7) ESC = 16 + ULT_GRA .

RECODE noasi1 trab151 esc (SYSMIS = 0) .
EXECUTE.

COMPUTE DISCAP = 0 .
IF (ES_CIEGA = 1 | ES_MUDA = 1 | ES_SORDA = 1 | ES_MENTA = 1 | ES_FALTA = 1 | ES_AYUDA = 1) DISCAP = 1 .

RECODE EJ (98=SYSMIS) .
RECODE EJ (99=SYSMIS) .

RECODE ANIM1 ANIM2 ANIM3 ANIM4 ANIM5 ANIM6 ANIM7 ANIM8 (99=0) .
RECODE ANIM1 ANIM2 ANIM3 ANIM4 ANIM5 ANIM6 ANIM7 ANIM8 (SYSMIS=0) .

COMPUTE TOT_ANIM = ANIM1 * 150 + ANIM2 * 100 + ANIM3 * 225 + ANIM4 * 150 + ANIM5 * 400
                + ANIM6 + ANIM7 * 150 + ANIM8 * 2.5 .

IF (AGUA_TER = 2 & BAO = 2) AGUABA1 = 1.
IF (AGUA_TER = 1 & AGUA_VIV = 2 & BAO = 2) AGUABA1 = 2.
IF (AGUA_VIV = 1 & BAO = 2) AGUABA1 = 3.
IF (AGUA_TER = 2 & BAO = 1 & BAO_AGUA = 2) AGUABA1 = 4.
IF(AGUA_TER = 1 & BAO = 1 & BAO_AGUA = 2) AGUABA1 = 5.
IF (AGUA_VIV = 1 & BAO = 1 & BAO_AGUA = 2) AGUABA1 =6.
IF (AGUA_TER =1 & AGUA_VIV = 2 & BAO_AGUA = 1) AGUABA1 = 7.
IF (AGUA_VIV = 1 & BAO_AGUA = 1) AGUABA1 = 8.

COMPUTE PISO1 = PISO .
RECODE PISO1 (9=SYSMIS) .

COMPUTE PARED1 = MURO .
RECODE PARED1 (99=SYSMIS) .

IF (CON_TRA = 4 | VERITRAB = 6) OCUPJ = 0 .
COMPUTE OCUPJ1 = OCUPJ .
RECODE OCUPJ1 (99=SYSMIS) .

IF (AGUA_TER = 2) AGUA1 = 1.
IF (AGUA_TER = 1 & AGUA_VIV = 2) AGUA1 = 2.
IF (AGUA_VIV = 1) AGUA1 = 3.

IF (BAO = 2) BAO1 = 1.
IF (BAO = 1 & BAO_AGUA = 2) BAO1 = 2.
IF (BAO_AGUA = 1) BAO1 = 3.

EXECUTE.
```

```
*** PUNTAJES DE LA REGION  34, FASE 8
*/*/ MODELO AA

DISCRIMINANT
  /GROUPS=lp98(0 1)
   /VARIABLES=depen ninos trab151 esc piso_1 aguaba_1
         lava  estgas vhs discap ventila
   ANALYSIS ALL
   /PRIORS =  .42 .58
  /STATISTICS=RAW TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

************************************

***Calificación

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-29*DEPEN .
COMPUTE AANINOS=-29*NINOS .
COMPUTE AATRAB15 = -74*TRAB151 .
COMPUTE AAESC = 3*ESC .
COMPUTE AAPISO = 7*PISO_1 .
COMPUTE AAAGUABA = 10*AGUABA_1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP =72 .

IF (LAVA=0) AALAVA= 100 .
IF (LAVA=1) AALAVA= 89 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 69 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 1) AAVHS = 68 .

IF (VENTILA = 0) AAVENTIL = 100 .
IF (VENTILA = 1) AAVENTIL = 73 .

 XECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aatrab15  aaesc
  aapiso aaaguaba aalava aaestgas aavhs aadiscap aaventil
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aatrab15)
  |  MISSING(aaesc)  | MISSING (aapiso) | MISSING (aaaguaba)
  | MISSING(aalava) | MISSING(aaestgas) |
  MISSING(aavhs) | MISSING(aadiscap) | MISSING(aaventil)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS=-71.69) .
RECODE aaninos  (SYSMIS=-47.56)  .
RECODE aatrab15  (SYSMIS=-2.22) .
RECODE aaesc  (SYSMIS=8.44)  .
RECODE aapiso  (SYSMIS=0.08) .
RECODE aaaguaba  (SYSMIS=-0.0003) .
RECODE aalava  (SYSMIS=90.09)  .
RECODE aaestgas  (SYSMIS=82.45) .
RECODE aavhs  (SYSMIS=69.98)  .
RECODE aadiscap  (SYSMIS=98.09) .
RECODE aaventil  (SYSMIS=75.47)  .

  *se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aatrab15 + aaesc +
  aapiso +  aaaguaba + aalava + aaestgas + aavhs + aadiscap
  + aaventil .
```

```
EXECUTE .

***discriminante con la linea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
  SE ALL.
  XECUTE .

***filtros

IF ((EJ < 25 & TOTPER < 5) | (EJ > 65 & EJ < 98 & TOTPER < 3)) VIEJITOS = -100 .
RECODE viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE AACALIF = AACALIF  + viejitos .
EXECUTE.

***se determina la linea de corte y se obtienen los pobres

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif < 374.50) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) AAPOBRE = 0.

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) AAPOBRE = 0 .

EXECUTE .

  EQUENCIES
  VARIABLES= LP98 AAPOBRE ELIMIN.
```

```
*/*/* PUNTAJES DE LA REGION 34
*/*/* FASE 4 A 6
*/*/* MODELO AA

DISCRIMINANT
  /GROUPS=lp98(0 1)
   /VARIABLES=depen ninos trab151 esc piso_1 aguaba_1
         lava  estgas vhs discap ventila
  /ANALYSIS ALL
   /PRIORS =  .42 .58
  /STATISTICS=RAW TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

************************************

GET
  FILE='h:\4_5y6fas\punteo\reg_34\reg34j_8.sav'.
EXECUTE .

COMPUTE AADEPEN=-29*DEPEN .
COMPUTE AANINOS=-29*NINOS .
COMPUTE AATRAB15 = -74*TRAB151 .
COMPUTE AAESC = 3*ESC .
COMPUTE AAPISO = 7*PISO_1 .
COMPUTE AAAGUABA = 10*AGUABA_1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP =72 .

IF (LAVA=0) AALAVA= 100 .
IF (LAVA=1) AALAVA= 89 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 69 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 1) AAVHS = 68 .

IF (VENTILA = 0) AAVENTIL = 100 .
IF (VENTILA = 1) AAVENTIL = 73 .

 XECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aatrab15  aaesc
  aapiso aaaguaba aalava aaestgas aavhs aadiscap aaventil
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aatrab15)
  |  MISSING(aaesc)  | MISSING (aapiso) | MISSING (aaaguaba)
  | MISSING(aalava) | MISSING(aaestgas) |
  MISSING(aavhs) | MISSING(aadiscap) | MISSING(aaventil)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS=-74.6002) .
RECODE aaninos  (SYSMIS=-36.3813)  .
RECODE aatrab15  (SYSMIS=-2.6599) .
RECODE aaesc  (SYSMIS=10.2887)  .
RECODE aapiso  (SYSMIS=-.8214) .
RECODE aaaguaba  (SYSMIS=-2.5881) .
RECODE aalava  (SYSMIS=91.0958)  .
RECODE aaestgas  (SYSMIS=93.6690) .
RECODE aavhs  (SYSMIS=72.9728)  .
RECODE aadiscap  (SYSMIS=98.8169) .
RECODE aaventil  (SYSMIS=76.6707)  .

 *se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aatrab15 + aaesc +
  aapiso +  aaaguaba + aalava + aaestgas + aavhs + aadiscap
  + aaventil .
```

```
EXECUTE .

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
   ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE
  /CLASSIFY=NONMISSING POOLED .


USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

  'LTER OFF.
  SE ALL.
EXECUTE .

***filtros

IF ((EJ < 25 & TOTPER < 5) | (EJ > 65 & EJ < 98 & TOTPER < 3)) VIEJITOS = -100 .
RECODE viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE AACALIF = AACALIF  + viejitos .
EXECUTE.

***se determina la línea de corte y se obtienen los pobres

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif < 352.435) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) AAPOBRE = 0.
EXECUTE.

FREQUENCIES
  VARIABLES= lp98 aapobre  .
```

```
*/*/* PUNTAJES DE LA REGION 34
*/*/* FASE 4 A 6
*/*/* MODELO BB

DISCRIMINANT
  /GROUPS=lp98(0 1)
   /VARIABLES=depen ninos trab151 esc
         lava  vhs discap ventila
  /ANALYSIS ALL
   /PRIORS =  .41 .59
  /STATISTICS=RAW TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

****PUNTAJES

COMPUTE BBDEPEN=-36*DEPEN .
COMPUTE BBNINOS=-29*NINOS .
COMPUTE BBTRAB15 = -53*TRAB151 .
COMPUTE BBESC = 9*ESC .

IF (DISCAP = 0) BBDISCAP = 100 .
IF (DISCAP = 1) BBDISCAP =56 .

IF (LAVA=0) BBLAVA= 100 .
IF (LAVA=1) BBLAVA= 85 .

IF (VHS = 0) BBVHS = 100 .
IF (VHS = 1) BBVHS = 98 .

IF (VENTILA = 0) BBVENTIL = 100 .
IF (VENTILA = 1) BBVENTIL = 71 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= BBdepen BBninos BBtrab15  BBesc
  BBlava BBvhs BBdiscap BBventil
  /FORMAT=NOTABLE
   STATISTICS=MEAN .

COMPUTE BBinput = 0 .
EXECUTE .
DO IF (MISSING(BBdepen) | MISSING(BBninos) | MISSING (BBtrab15)
  | MISSING(BBesc)  | MISSING(BBlava) |
  MISSING(BBvhs) | MISSING(BBdiscap) | MISSING(BBventil)) .
RECODE
  BBinput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE BBdepen  (SYSMIS=-89.82) .
RECODE BBninos  (SYSMIS=-37.68)  .
RECODE BBtrab15  (SYSMIS=-1.51) .
RECODE BBesc  (SYSMIS=30.91)  .
RECODE BBlava  (SYSMIS=88.40)  .
RECODE BBvhs  (SYSMIS=98.26)  .
RECODE BBdiscap  (SYSMIS=97.33) .
RECODE BBventil  (SYSMIS=78.10)  .

***se hace la calificación

COMPUTE BBcalif = BBdepen + BBninos + BBtrab15 + BBesc +
  BBlava+ BBvhs + BBdiscap
  + BBventil .
EXECUTE .

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
   /VARIABLES=BBcalif
    ANALYSIS ALL
   /SAVE=CLASS
  /PRIORS = .41 .59
  /STATISTICS=raw TABLE
  /CLASSIFY=NONMISSING POOLED .
```

```
USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
 'LTER BY filter_$.
  (ECUTE .

FREQUENCIES
  VARIABLES=BBcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=BBcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


***filtros

IF ((EJ < 25 & TOTPER < 5) | (EJ > 65 & EJ < 98 & TOTPER < 3)) VIEJITOS = -100 .
RECODE viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE BBCALIF = BBCALIF  + viejitos .
EXECUTE.

  'se determina la linea de corte y se obtienen los pobres

COMPUTE BBpobre = 0 .
EXECUTE .
DO IF (BBcalif < 315.75) .
RECODE
  BBpobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) BBPOBRE = 0.
EXECUTE.

FREQUENCIES
  VARIABLES= lp98 BBpobre  .
```

```
*** PUNTAJES DE LA REGION 34
*/*/*/ FASE 3
*/*/*/ MODELO AA

DISCRIMINANT
  /GROUPS=lp98(0 1)
   /VARIABLES=depen ninos trab151 esc piso_1 aguaba_1
         lava  estgas vhs discap ventila
  /ANALYSIS ALL
   /PRIORS =  .42 .58
  /STATISTICS=RAW TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN=-29*DEPEN .
COMPUTE AANINOS=-29*NINOS .
COMPUTE AATRAB15 = -74*TRAB151 .
COMPUTE AAESC = 3*ESC .
COMPUTE AAPISO = 7*PISO_1 .
COMPUTE AAAGUABA = 10*AGUABA_1 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP =72 .

IF (LAVA=0) AALAVA= 100 .
IF (LAVA=1) AALAVA= 89 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 69 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 1) AAVHS = 68 .

IF (VENTILA = 0) AAVENTIL = 100 .
IF (VENTILA = 1) AAVENTIL = 73 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
   'ARIABLES= aadepen aaninos aatrab15  aaesc
  aapiso aaaguaba aalava aaestgas aavhs aadiscap aaventil
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aatrab15)
  |  MISSING(aaesc)  | MISSING (aapiso) | MISSING (aaaguaba)
  | MISSING(aalava) | MISSING(aaestgas) |
  MISSING(aavhs) | MISSING(aadiscap) | MISSING(aaventil)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS=-71.5010)  .
RECODE aaninos  (SYSMIS=-47.4363)  .
RECODE aatrab15  (SYSMIS=-2.2118) .
RECODE aaesc  (SYSMIS=8.4146)  .
RECODE aapiso  (SYSMIS=.07719 ) .
RECODE aaaguaba  (SYSMIS=.0004)  .
RECODE aalava  (SYSMIS=90.1205)  .
RECODE aaestgas  (SYSMIS=82.4966) .
RECODE aavhs  (SYSMIS=70.0637)  .
RECODE aadiscap  (SYSMIS=.980931) .
RECODE aaventil  (SYSMIS=75.5390)  .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aatrab15 + aaesc +
  aapiso +  aaaguaba + aalava + aaestgas + aavhs + aadiscap
  + aaventil .
    ECUTE .

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
```

```
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE
  /CLASSIFY=NONMISSING POOLED .


USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

***filtros

   ((EJ < 25 & TOTPER < 5) | (EJ > 65 & EJ < 98 & TOTPER < 3)) VIEJITOS = -100 .
IF (estgas = 1 & licua=1) cocina = -100 .
IF ( tv = 1 & radio = 1 )  entret  = -100 .

RECODE viejitos cocina  entret (SYSMIS = 0) .

EXECUTE .

COMPUTE AACALIF = AACALIF  + viejitos + cocina + entret .
EXECUTE.

***se determina la línea de corte y se obtienen los pobres

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (aacalif < 352.435) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) AAPOBRE = 0.
EXECUTE.

FREQUENCIES
  VARIABLES= lp98 aapobre  .
```

Región 39. Frontera Sur
Fase 3

```
***puntajes región 39

 **método de STEPWISE

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=hacina depen ninos  noasi1 trab151  ocupj_1 ej esc  lengua discap
   piso_1 bao_1 agua_1 aguaba_1 pared_1 luz  hectie1 radio estgas tv vhs refri vehi lava licua
   cal_agua tocadisc ventila
 /ANALYSIS ALL
 /SAVE=CLASS
  /METHOD=WILKS
  /FIN= 3.84
  /FOUT= 2.71
 /PRIORS  .42 .58
 /HISTORY
 /STATISTICS=BOXM RAW TABLE
 /CLASSIFY=NONMISSING POOLED .


REGRESSION
 /MISSING LISTWISE
 /STATISTICS COEFF OUTS R ANOVA
 /CRITERIA=PIN(.05) POUT(.10)
 /NOORIGIN
 /DEPENDENT lp98
 /METHOD=ENTER hacina depen ninos  noasi1 trab151  ocupj_1 ej esc  lengua discap
   piso_1 bao_1 agua_1 aguaba_1 pared_1 luz  hectie1 radio estgas tv vhs refri vehi lava licua
   cal_agua tocadisc ventila
 /SAVE PRED .


 **Modelo

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES= hacina depen ninos  noasi1 trab151 esc
   bao_1 agua_1 pared_1 estgas vhs refri vehi lava
   tocadisc
    /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .


***Calificación

COMPUTE AAHACINA = -9 * HACINA .
COMPUTE AADEPEN=-28*DEPEN .
COMPUTE AANINOS=-16*NINOS .
COMPUTE AANOASI = -73 * NOASI1 .
COMPUTE AATRAB15 = -45 * TRAB15 .
COMPUTE AAESC = 2 * ESC .
COMPUTE AABAO = -7 * BAO_1 .
COMPUTE AAAGUA = -22 * AGUA_1.
COMPUTE AAPARED = -40 * PARED_1 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 79 .

IF (VHS = 0) AAVHS = 100 .
 (VHS = 1) AAVHS = 65 .

IF (REFRI = 0) AAREFRI = 100 .
IF (REFRI = 1) AAREFRI = 69 .

IF (VEHI=0) AAVEHI= 100 .
```

```
IF (VEHI=1) AAVEHI= 50 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 78 .

IF (TOCADISC = 0) AATOCADI = 100 .
IF (TOCADISC = 1) AATOCADI = 65 .

EXECUTE .

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aahacina aadepen aaninos aanoasi aatrab15 aaesc aabao
   aaagua aapared aaestgas aavhs aarefri aavehi aalava aatocadi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
DO IF (MISSING(aahacina) |MISSING(aadepen) | MISSING(aaninos) | MISSING(aanoasi) | MISSING(aatrab15)
  | MISSING(aaesc) | MISSING(aabao) | MISSING(aaagua) | MISSING(aapared)
  | MISSING(aaestgas) |MISSING(aavhs) | MISSING (aarefri) | MISSING(aavehi) | MISSING (aalava) | MISSING (aatocadi)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aahacina (SYSMIS = -44.39) .
RECODE aadepen  (SYSMIS=-62.43)  .
RECODE aaninos  (SYSMIS=-36.76)  .
RECODE aanoasi (SYSMIS = -13.08) .
RECODE aatrab15 (SYSMIS = -3.65) .
RECODE aaesc  (SYSMIS=3.73)  .
RECODE aabao (SYSMIS = -3.72) .
RECODE aaagua (SYSMIS=14.23)  .
RECODE aapared (SYSMIS=-22.17)  .
RECODE aaestgas  (SYSMIS=84.11)  .
RECODE aavhs  (SYSMIS=65.00)  .
RECODE aarefri (SYSMIS = 76.54) .
RECODE aavehi (SYSMIS=51.35)  .
RECODE aalava (SYSMIS=78.00)  .
RECODE aatocadi (SYSMIS = 65.95) .

***se hace la calificación

COMPUTE aacalif = aahacina + aadepen + aaninos + aanoasi + aatrab15 + aaesc + aabao + aaagua +
        aapared + aaestgas + aavhs + aarefri + aavehi + aalava + aatocadi .

EXECUTE .

***se calcula la línea de corte y se obtienen los pobres

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .


  ***se checa el último discriminante

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
```

```
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


***filtros

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .


COMPUTE AACALIF = AACALIF + VIEJITOS .

  XECUTE.

***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

COMPUTE aapobre = 0 .
DO IF (aacalif < 263.10) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) AAPOBRE = 0 .
EXECUTE.

FREQUENCIES
   VARIABLES = lp98 AAPOBRE .


COMPUTE FECHA = 60898 .

COMPUTE FOPO = 9 .

EXECUTE.

SAVE OUTFILE='E:\punteo\REG_39\reg39j_9.sav'
   /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\punteo\REG_39\AGGR.SAV'
  /BREAK=entidad mpio local folio
  /aapobr_1 = MEAN(aapobre).

GET
  FILE='E:\punteo\REG_39\Aggr.sav'.
EXECUTE .

RENAME VARIABLES
```

```
        aapobr_1 = aapobre .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\punteo\REG_39\fopo39_9.dbf'
  /TYPE=DB4 /MAP /REPLA.
```

Región 39. Frontera Sur
Fase 6

```
***puntajes región 39

 **método de STEPWISE

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=hacina depen ninos  noasi1 trab151  ocupj_1 ej esc  lengua discap
   piso_1 bao_1 agua_1 aguaba_1 pared_1 luz  hectie1 radio estgas tv vhs refri vehi lava licua
   cal_agua tocadisc ventila
 /ANALYSIS ALL
 /SAVE=CLASS
  /METHOD=WILKS
  /FIN= 3.84
  /FOUT= 2.71
 /PRIORS  .42 .58
 /HISTORY
 /STATISTICS=BOXM RAW TABLE
 /CLASSIFY=NONMISSING POOLED .


REGRESSION
 /MISSING LISTWISE
 /STATISTICS COEFF OUTS R ANOVA
 /CRITERIA=PIN(.05) POUT(.10)
 /NOORIGIN
 /DEPENDENT lp98
 /METHOD=ENTER hacina depen ninos  noasi1 trab151  ocupj_1 ej esc  lengua discap
   piso_1 bao_1 agua_1 aguaba_1 pared_1 luz  hectie1 radio estgas tv vhs refri vehi lava licua
   cal_agua tocadisc ventila
 /SAVE PRED .


 **Modelo

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES= hacina depen ninos  noasi1 trab151 esc
   bao_1 agua_1 pared_1 estgas vhs refri vehi lava
   tocadisc
     /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .


***Calificación

COMPUTE AAHACINA = -9 * HACINA .
COMPUTE AADEPEN=-28*DEPEN .
COMPUTE AANINOS=-16*NINOS .
COMPUTE AANOASI = -73 * NOASI1 .
COMPUTE AATRAB15 = -45 * TRAB15 .
COMPUTE AAESC = 2 * ESC .
COMPUTE AABAO = -7 * BAO_1 .
COMPUTE AAAGUA = -22 * AGUA_1.
COMPUTE AAPARED = -40 * PARED_1 .

IF (ESTGAS = 0) AAESTGAS = 100 .
IF (ESTGAS = 1) AAESTGAS = 79 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 1) AAVHS = 65 .

IF (REFRI = 0) AAREFRI = 100 .
IF (REFRI = 1) AAREFRI = 69 .

IF (VEHI=0) AAVEHI= 100 .
IF (VEHI=1) AAVEHI= 50 .
```

```
IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 78 .

IF (TOCADISC = 0) AATOCADI = 100 .
F (TOCADISC = 1) AATOCADI = 65 .

EXECUTE .

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aahacina aadepen aaninos aanoasi aatrab15 aaesc aabao
   aaagua aapared aaestgas aavhs aarefri aavehi aalava aatocadi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
DO IF (MISSING(aahacina) |MISSING(aadepen) | MISSING(aaninos) | MISSING(aanoasi) | MISSING(aatrab15)
  | MISSING(aaesc) | MISSING(aabao) | MISSING(aaagua) | MISSING(aapared)
  | MISSING(aaestgas) |MISSING(aavhs) | MISSING (aarefri) | MISSING(aavehi) | MISSING (aalava) | MISSING (aatocadi)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aahacina (SYSMIS = -26.0098) .
RECODE aadepen  (SYSMIS=-61.4208)  .
RECODE aaninos  (SYSMIS=-20.0802)  .
RECODE aanoasi (SYSMIS = -6.3239) .
RECODE aatrab15 (SYSMIS = -5.0287) .
RECODE aaesc  (SYSMIS=7.7421)  .
RECODE aabao (SYSMIS = -9.4625) .
`ECODE aaagua (SYSMIS=-15.9826)  .
RECODE aapared (SYSMIS=-70.4653)  .
RECODE aaestgas  (SYSMIS=86.6034)  .
RECODE aavhs  (SYSMIS=66.0116)  .
RECODE aarefri (SYSMIS = 80.0460) .
RECODE aavehi (SYSMIS=50.4335)  .
RECODE aalava (SYSMIS=80.9164)  .
RECODE aatocadi (SYSMIS = 66.4203) .

***se hace la calificación

COMPUTE aacalif = aahacina + aadepen + aaninos + aanoasi + aatrab15 + aaesc + aabao + aaagua +
        aapared + aaestgas + aavhs + aarefri + aavehi + aalava + aatocadi .

EXECUTE .


***filtro de viejitos

if ((EJ<=24 & totper<=4) | (EJ>=65 & totper<=2)) viejitos = -100 .
RECODE viejitos (sysmis=0) .

compute aacalif1 = aacalif + viejitos .

EXECUTE.

***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

COMPUTE aapobre = 0 .
DO IF (aacalif1 < 263.10) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) AAPOBRE = 0 .
EXECUTE.
```

```
FREQUENCIES
  VARIABLES = lp98 AAPOBRE .


COMPUTE FECHA = 981216 .

COMPUTE FOPO =18 .

EXECUTE.

SAVE OUTFILE='g:\4_5Y6fas\punteo\REG_39\reg39j_18.sav'
  /COMPRESSED.

AGGREGATE
 /OUTFILE='E:\4_5Y6fas\punteo\REG_39\AGGR.SAV'
 /BREAK=entidad mpio local folio
 /aapobre = FIRST(aapobre).

GET
 FILE='g:\4_5Y6fas\punteo\REG_39\Aggr.sav'.
EXECUTE .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='g:\4_5Y6fas\punteo\REG_39\fopo39_18.dbf'
 /TYPE=DB4 /MAP /REPLA.


***LOCS

***crear archivo de control

GET
 FILE='g:\4_5y6fas\PUNTEO\REG_39\reg39j_18.sav'.
EXECUTE .

IF (aapobre = 1) FOLPOB = 1.
IF (aapobre = 1) PERPOB = TOTPER .
RECODE FOLPOB PERPOB (SYSMIS = 0) .

COMPUTE X = 1 .

EXECUTE.

SAVE OUTFILE='g:\4_5y6fas\punteo\REG_39\reg39j_18.sav'
  /COMPRESSED.

AGGREGATE
 /OUTFILE='g:\4_5y6fas\punteo\reg_39\locs39_18.sav'
 /BREAK=entidad mpio local
 /hoglocal = SUM(x) /totper_1 = SUM(totper) /hogpobre = SUM(folpob) /perpob_1 =
 SUM(perpob) /region = FIRST(region) /fecha = FIRST(fecha) / fopo = FIRST(fopo) .

GET
 FILE='g:\4_5y6fas\punteo\reg_39\locs39_18.sav'.
EXECUTE .

SAVE TRANSLATE OUTFILE='g:\4_5y6fas\PUNTEO\LOCALS\981216\locs39_18.dbf '
   /TYPE=DB4
   /COMPRESSED.
```

Región 39. Frontera Sur
Fase 8

```
***puntajes región 39

**método de STEPWISE

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=hacina depen ninos  noasi1 trab151  ocupj_1 ej esc  lengua discap
   piso_1 bao_1 agua_1 aguaba_1 pared_1 luz  hectie1 radio estgas tv vhs refri vehi lava licua
   cal_agua tocadisc ventila
 /ANALYSIS ALL
 /SAVE=CLASS
  /METHOD=WILKS
  /FIN= 3.84
  /FOUT= 2.71
 /PRIORS  .42 .58
 /HISTORY
 /STATISTICS=BOXM RAW TABLE
 /CLASSIFY=NONMISSING POOLED .


REGRESSION
 /MISSING LISTWISE
 /STATISTICS COEFF OUTS R ANOVA
 /CRITERIA=PIN(.05) POUT(.10)
 /NOORIGIN
 /DEPENDENT lp98
 /METHOD=ENTER hacina depen ninos  noasi1 trab151  ocupj_1 ej esc  lengua discap
   piso_1 bao_1 agua_1 aguaba_1 pared_1 luz  hectie1 radio estgas tv vhs refri vehi lava licua
   cal_agua tocadisc ventila
 /SAVE PRED .


**Modelo

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES= hacina depen ninos  noasi1 trab151 esc
   bao_1 agua_1 pared_1 estgas vhs refri vehi lava
   tocadisc
    /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .


***Calificación

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AAHACINA = -9 * HACINA .
COMPUTE AADEPEN=-28*DEPEN .
COMPUTE AANINOS=-16*NINOS .
COMPUTE AANOASI = -73 * NOASI1 .
COMPUTE AATRAB15 = -45 * TRAB15 .
COMPUTE AAESC = 2 * ESC .
COMPUTE AABAO = -7 * BAO_1 .
COMPUTE AAAGUA = -22 * AGUA_1.
COMPUTE AAPARED = -40 * PARED_1 .

IF (ESTGAS = 0) AAESTGAS = 100 .
 (ESTGAS = 1) AAESTGAS = 79 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 1) AAVHS = 65 .

IF (REFRI = 0) AAREFRI = 100 .
```

```
IF (REFRI = 1) AAREFRI = 69 .

IF (VEHI=0) AAVEHI= 100 .
IF (VEHI=1) AAVEHI= 50 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 78 .

IF (TOCADISC = 0) AATOCADI = 100 .
IF (TOCADISC = 1) AATOCADI = 65 .

EXECUTE .

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aahacina aadepen aaninos aanoasi aatrab15 aaesc aabao
   aaagua aapared aaestgas aavhs aarefri aavehi aalava aatocadi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
DO IF (MISSING(aahacina) |MISSING(aadepen) | MISSING(aaninos) | MISSING(aanoasi) | MISSING(aatrab15)
  | MISSING(aaesc) | MISSING(aabao) | MISSING(aaagua) | MISSING(aapared)
  | MISSING(aaestgas) |MISSING(aavhs) | MISSING (aarefri) | MISSING(aavehi) | MISSING (aalava) | MISSING (aatocadi)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aahacina (SYSMIS = -34.96) .
RECODE aadepen  (SYSMIS=-74.01)  .
RECODE aaninos  (SYSMIS=-27.34)  .
RECODE aanoasi (SYSMIS = -9.60) .
RECODE aatrab15 (SYSMIS = -3.94) .
RECODE aaesc  (SYSMIS=6.49)  .
RECODE aabao (SYSMIS = 1.81) .
RECODE aaagua (SYSMIS=-6.04)  .
RECODE aapared (SYSMIS=-62.45)  .
RECODE aaestgas  (SYSMIS=83.56)  .
RECODE aavhs  (SYSMIS=65.59)  .
RECODE aarefri (SYSMIS = 76.24) .
RECODE aavehi (SYSMIS=51.83)  .
RECODE aalava (SYSMIS=79.75)  .
RECODE aatocadi (SYSMIS = 66.61) .

***se hace la calificación

COMPUTE aacalif = aahacina + aadepen + aaninos + aanoasi + aatrab15 + aaesc + aabao + aaagua +
          aapared + aaestgas + aavhs + aarefri + aavehi + aalava + aatocadi .

EXECUTE .


***Se determina el punto de corte
***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .48  .52
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .


USE ALL.
COMPUTE filter_$=(dis_1= 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
```

```
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


***filtro de viejitos

if ((EJ<=24 & totper<=4) | (EJ>=65 & totper<=2)) viejitos = -100 .
RECODE viejitos (sysmis=0) .

compute aacalif1 = aacalif + viejitos .

EXECUTE.

***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

COMPUTE aapobre = 0 .
DO IF (aacalif1 < 259.48) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

IF (VEHI = 0) AAPOBRE = 0 .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) AAPOBRE = 0 .

EXECUTE .

FREQUENCIES
   VARIABLES= LP98 AAPOBRE ELIMIN.

COMPUTE FECHA = 990920 .

COMPUTE FOPO = 25 .

  EXECUTE.

SORT CASES BY
  entidad (A) mpio (A) local (A) folio (A) .

SAVE OUTFILE='e:\fase8\punteo\REG_39\reg39j_25.sav'
```

```
  /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\fase8\punteo\REG_39\AGGR.SAV'
  /BREAK=entidad mpio local folio
  /aapobre = FIRST(aapobre).

GET
  FILE='E:\fase8\punteo\REG_39\Aggr.sav'.
EXECUTE .

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\fase8\PUNTEO\entregas\990920\fopo39_25.dbf '
    /TYPE=DB4
    /COMPRESSED.

***LOCS

***crear archivo de control

GET
  FILE='E:\fase8\PUNTEO\REG_39\reg39j_25.sav'.
EXECUTE .

IF (aapobre = 1) FOLPOB = 1.
IF (aapobre = 1) PERPOB = TOTPER .
RECODE FOLPOB PERPOB (SYSMIS = 0) .

COMPUTE X = 1 .

EXECUTE.

SAVE OUTFILE='E:\fase8\punteo\REG_39\reg39j_25.sav'
  /COMPRESSED.

AGGREGATE
  /OUTFILE='E:\fase8\punteo\reg_39\locs39_25.sav'
  /BREAK=entidad mpio local
  /hoglocal = SUM(x) /totper_1 = SUM(totper) /hogpobre = SUM(folpob) /perpob_1 =
  SUM(perpob) /region = FIRST(region) /fecha = FIRST(fecha) / fopo = FIRST(fopo) .

GET
  FILE='E:\fase8\punteo\reg_39\locs39_25.sav'.
EXECUTE .

SAVE TRANSLATE OUTFILE='E:\fase8\PUNTEO\LOCALS\990920\locs39_25.dbf '
    /TYPE=DB4
    /COMPRESSED.


***Para verificar hogares analizados y hogares beneficiarios

DESCRIPTIVES
  VARIABLES=hoglocal hogpobre
  /STATISTICS=SUM .

***Para verificar la información de jefes

GET
  FILE='E:\fase8\PUNTEO\REG_39\reg39j_25.sav'.
EXECUTE .

  FREQUENCIES
  VARIABLES=peryjef
  /ORDER  ANALYSIS .

***Para verificar la información de personas
```

```
GET
  FILE='E:\fase8\PUNTEO\REG_39\reg39p_25.sav'.
EXECUTE .

RENAME VARIABLES
        ent_fed = entidad / munici = mpio / locali = local .

SORT CASES BY
  entidad (A) mpio (A) local (A) folio (A) .

MATCH FILES /FILE=*
 /TABLE='E:\Fase8\Punteo\Reg_39\REG39j_25.sav'
 /RENAME (aaagua aabao aacalif aacalif1 aadepen aaesc aaestgas aahacina
  aainput aalava aaninos aanoasi aapared aarefri aatocadi aatrab15 aavehi
  aavhs adm_gas_ agua1 agua_1 agua_ter agua_viv aguaba1 aguaba_1 anim1 anim2
  anim3 anim4 anim5 anim6 anim7 anim8 animales apo_ing_ asi_esc ate_med_
  auto_pro bao bao1 bao_1 bao_agua bueyes burros caballos cal_agua camion_p
  cerdos chivos con_inac con_tra conejos conyuge cuan_mur d_r depen dias_tra
  dif_hog disc_ani disc_ens discap edad edo_civ ej ej_1ertr elimin emigro
  es_ayuda es_ciega es_falta es_menta es_muda es_sorda esc estgas fam_bien
  fam_entr fecha folpob fopo gallinas hacina hect_rie hect_tem hectie1 ido_esc
  ing_hog inm15_1 inmh15pc inmp_1 itmh itmh15 itmh15pe itmh15tp itmh_tpe
  itmhtper lava leche leer_esc leng_esp leng_mas lengua licua lnin15pc lp98
  luz med_nin_ mot_no_t mu15a49 muro na8a17 nin0a1 nin2a5 nin5a15 nin6a7
  nin8a15 nin_sol ninos no8a17 noasi1 noasi15 num_dias
 num_hec num_hog ocupj ocupj1 ocupj_1 pared1 pared_1 per_ayud per_cieg
  per_falt per_ment per_muda per_muri per_ocup per_sord percep perpob peryjef
  piso piso1 piso_1 predios prod_cul radio refri region reses result seg_mas
  seg_soc seguro sexo sit_viv taller techo tierra tit_lech tit_tort tocadisc
  tom_dec_ ton_cos1 ton_cos2 ton_cos3 tortilla tot_anim tot_cuar tot_per
  totper totpers trab trab15 trab151 trab_tem ttem_din ttem_lug ttem_mas
  ttem_mdi ttem_mes tv ult_gra ult_niv v111 v112 v40 v42 v44 v46 v66 v67 v96
  v97 vehi ventila ver_ing_ veritrab vhs viejitos x = d0 d1 d2 d3 d4 d5 d6 d7
  d8 d9 d10 d11 d12 d13 d14 d15 d16 d17 d18 d19 d20 d21 d22 d23 d24 d25 d26
  d27 d28 d29 d30 d31 d32 d33 d34 d35 d36 d37 d38 d39 d40 d41 d42 d43 d44 d45
  d46 d47 d48 d49 d50 d51 d52 d53 d54 d55 d56 d57 d58 d59 d60 d61 d62 d63 d64
  d65 d66 d67 d68 d69 d70 d71 d72 d73 d74 d75 d76 d77 d78 d79 d80 d81 d82 d83
  d84 d85 d86 d87 d88 d89 d90 d91 d92 d93 d94 d95 d96 d97 d98 d99 d100 d101
  d102 d103 d104 d105 d106 d107
 d108 d109 d110 d111 d112 d113 d114 d115 d116 d117 d118 d119 d120 d121 d122
  d123 d124 d125 d126 d127 d128 d129 d130 d131 d132 d133 d134 d135 d136 d137
  d138 d139 d140 d141 d142 d143 d144 d145 d146 d147 d148 d149 d150 d151 d152
  d153 d154 d155 d156 d157 d158 d159 d160 d161 d162 d163 d164 d165 d166 d167
  d168 d169 d170 d171 d172 d173 d174 d175 d176 d177 d178 d179 d180 d181 d182
  d183 d184 d185 d186 d187 d188 d189 d190 d191 d192 d193 d194 d195 d196 d197
  d198 d199)
 /BY entidad mpio local folio
 /DROP= d0 d1 d2 d3 d4 d5 d6 d7 d8 d9 d10 d11 d12 d13 d14 d15 d16 d17 d18 d19
  d20 d21 d22 d23 d24 d25 d26 d27 d28 d29 d30 d31 d32 d33 d34 d35 d36 d37 d38
  d39 d40 d41 d42 d43 d44 d45 d46 d47 d48 d49 d50 d51 d52 d53 d54 d55 d56 d57
  d58 d59 d60 d61 d62 d63 d64 d65 d66 d67 d68 d69 d70 d71 d72 d73 d74 d75 d76
  d77 d78 d79 d80 d81 d82 d83 d84 d85 d86 d87 d88 d89 d90 d91 d92 d93 d94 d95
  d96 d97 d98 d99 d100 d101 d102 d103 d104 d105 d106 d107 d108 d109 d110 d111
  d112 d113 d114 d115 d116 d117 d118 d119 d120 d121
d122 d123 d124 d125 d126 d127 d128 d129 d130 d131 d132 d133 d134 d135 d136
  d137 d138 d139 d140 d141 d142 d143 d144 d145 d146 d147 d148 d149 d150 d151
  d152 d153 d154 d155 d156 d157 d158 d159 d160 d161 d162 d163 d164 d165 d166
  d167 d168 d169 d170 d171 d172 d173 d174 d175 d176 d177 d178 d179 d180 d181
  d182 d183 d184 d185 d186 d187 d188 d189 d190 d191 d192 d193 d194 d195 d196
  d197 d198 d199.
EXECUTE.

FREQUENCIES
   VARIABLES=AAPOBRE .
```

Región 40. Centro - Sierra - Chotalpan - Costa
Fase 3

```
***puntajes región 40

 **método de STEPWISE

FREQUENCIES
 VARIABLES=hacina depen ninos  noasi1 trab151  ocupj_1 ej esc  lengua discap
  piso_1 bao_1 agua_1 aguaba_1 pared_1 luz  hectie1 radio estgas tv vhs refri vehi lava licua
  cal_agua tocadisc ventila
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=hacina depen ninos  noasi1 trab151  ocupj_1 ej esc  lengua discap
  piso_1 bao_1 agua_1 aguaba_1 pared_1 luz  hectie1 radio estgas tv vhs refri vehi lava licua
  cal_agua tocadisc ventila
 /ANALYSIS ALL
 /SAVE=CLASS
  /METHOD=WILKS
  /FIN= 3.84
  /FOUT= 2.71
 /PRIORS  .42 .58
 /HISTORY
 /STATISTICS=BOXM RAW TABLE
 /CLASSIFY=NONMISSING POOLED .


REGRESSION
 /MISSING LISTWISE
 /STATISTICS COEFF OUTS R ANOVA
 /CRITERIA=PIN(.05) POUT(.10)
 /NOORIGIN
 /DEPENDENT lp98
 /METHOD=ENTER hacina depen ninos  noasi1 trab151  ocupj_1 ej esc  lengua discap
  piso_1 bao_1 agua_1 aguaba_1 pared_1 luz  hectie1 radio estgas tv vhs refri vehi lava licua
  cal_agua tocadisc ventila
 /SAVE PRED .



***Modelo

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES= depen ninos  noasi1 esc
  agua_1  estgas vhs refri vehi lava discap
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .


***Calificación


COMPUTE AADEPEN=-25*DEPEN .
COMPUTE AANINOS=-26*NINOS .
COMPUTE AANOASI=-33*NOASI1 .
COMPUTE AAESC=8*ESC .
COMPUTE AAAGUA=12*AGUA_1 .

IF (DISCAP=0) AADISCAP = 100 .
  (DISCAP=1) AADISCAP = 86 .

IF (ESTGAS=0) AAESTGAS = 100 .
IF (ESTGAS=1) AAESTGAS = 63 .

IF (VHS=0) AAVHS= 100 .
```

```
IF (VHS=1) AAVHS= 56 .

IF (REFRI=0) AAREFRI= 100 .
IF (REFRI=1) AAREFRI= 79 .

IF (VEHI=0) AAVEHI= 100 .
IF (VEHI=1) AAVEHI= 66 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 67 .


EXECUTE .

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aanoasi aaesc
   aaagua aadiscap aaestgas aavhs aarefri aavehi aalava
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos)  | MISSING(aanoasi)  | MISSING(aaesc)
  | MISSING(aaagua) | MISSING(aadiscap)  | MISSING(aaestgas)  | MISSING(aavhs)  | MISSING(aarefri) | MISSING (aavehi) |
MISSING (aalava)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS=-66.74)  .
RECODE aaninos  (SYSMIS=-45.17)  .
RECODE aanoasi (SYSMIS=-4.01) .
RECODE aaesc  (SYSMIS=32.58)  .
RECODE aaagua  (SYSMIS=-.18)  .
RECODE aadiscap (SYSMIS=99.32) .
RECODE aaestgas  (SYSMIS=73.15)  .
RECODE aavhs  (SYSMIS=56.73)  .
RECODE aarefri (SYSMIS=83.96) .
RECODE aavehi  (SYSMIS=66.72)  .
RECODE aalava  (SYSMIS=69.07)  .

EXECUTE .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aanoasi + aaesc + aaagua + aadiscap
  + aaestgas + aavhs + aarefri + aavehi + aalava  .

EXECUTE .

***se calcula la línea de corte y se obtienen los pobres

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .


****se checa el último discriminante (lp98 vs aacalif)

USE ALL.
```

```
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
XECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

***filtros

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .


 OMPUTE AACALIF = AACALIF + VIEJITOS .

EXECUTE.

***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

COMPUTE aapobre = 0 .
DO IF (aacalif < 412.10) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
   VARIABLES=LP98 AAPOBRE .

USE ALL.
COMPUTE filter_$=(aapobre = 1).
VARIABLE LABEL filter_$ 'aapobre = 1 (FILTRO)'.
VALUE LABELS filter_$  0 'No seleccionado' 1 'Seleccionado'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=vehi  .

FILTER OFF.
USE ALL.
EXECUTE .

  O IF (AApobre = 1 &  vehi = 0) .
RECODE
  AApobre  (1=0)  .
END IF .
EXECUTE .
```

```
FREQUENCIES
   VARIABLES=AAPOBRE .

COMPUTE fecha=150798.
EXECUTE.

SAVE OUTFILE='H:\punteo\REG_40\reg40j_6.sav'
   /COMPRESSED.

***archivo de entrega:   fopo#_1.dbf

FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='H:\punteo\REG_40\fopo40_6.dbf'
  /keep = entidad mpio local folio aapobre
  /TYPE=DB4 /MAP /REPLA.

SAVE TRANSLATE OUTFILE='H:\entregas\980717\fopo40_6.dbf'
  /keep = entidad mpio local folio aapobre
  /TYPE=DB4 /MAP /REPLA.

GET TRANSLATE
  FILE='H:\punteo\REG_40\fopo40_6.dbf'
  /TYPE=DBF /MAP .
EXECUTE .
```

Región 40. Centro - Sierra - Chotalpan - Costa
Fase 8

```
***puntajes región 40

***Modelo

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES= depen ninos  noasi1 esc
    agua_1  estgas vhs refri vehi lava discap
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .


***Calificación

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-25*DEPEN .
COMPUTE AANINOS=-26*NINOS .
COMPUTE AANOASI=-33*NOASI1 .
COMPUTE AAESC=8*ESC .
COMPUTE AAAGUA=12*AGUA_1 .

IF (DISCAP=0) AADISCAP = 100 .
IF (DISCAP=1) AADISCAP = 86 .

IF (ESTGAS=0) AAESTGAS = 100 .
IF (ESTGAS=1) AAESTGAS = 63 .

IF (VHS=0) AAVHS= 100 .
IF (VHS=1) AAVHS= 56 .

IF (REFRI=0) AAREFRI= 100 .
IF (REFRI=1) AAREFRI= 79 .

IF (VEHI=0) AAVEHI= 100 .
IF (VEHI=1) AAVEHI= 66 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 67 .


EXECUTE .

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aanoasi aaesc
   aaagua aadiscap aaestgas aavhs aarefri aavehi aalava
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos)  | MISSING(aanoasi)  | MISSING(aaesc)
  | MISSING(aaagua) | MISSING(aadiscap)  | MISSING(aaestgas)  | MISSING(aavhs)  | MISSING(aarefri) | MISSING (aavehi) |
MISSING (aalava)) .
RECODE
  aainput  (0=1)  .
  ID IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS=-67.62)  .
```

```
RECODE aaninos  (SYSMIS=-46.60) .
RECODE aanoasi (SYSMIS=-4.50) .
RECODE aaesc  (SYSMIS=31.67) .
RECODE aaagua  (SYSMIS=-.60) .
RECODE aadiscap (SYSMIS=99.30) .
RECODE aaestgas  (SYSMIS=73.71) .
RECODE aavhs  (SYSMIS=56.83) .
RECODE aarefri (SYSMIS=83.98) .
RECODE aavehi  (SYSMIS=66.87) .
RECODE aalava  (SYSMIS=69.20) .

EXECUTE .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aanoasi + aaesc + aaagua + aadiscap
  + aaestgas + aavhs + aarefri + aavehi + aalava  .

EXECUTE .

***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42  .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


***filtros

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .

COMPUTE AACALIF = AACALIF + VIEJITOS .

EXECUTE.
```

```
COMPUTE aapobre = 0 .
DO IF (aacalif < 437.5) .
RECODE
  aapobre  (0=1)  .
END IF .
  XECUTE .

DO IF (AApobre = 1 &  vehi = 0) .
RECODE
  AApobre  (1=0)  .
END IF .
EXECUTE .


****Filtros para eliminar pobres no válidos de fase 8****


IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

DO IF (ELIMIN = 1) .
RECODE
  AAPOBRE  (1 = 0)  .
END IF .

EXECUTE .

FREQUENCIES
  VARIABLES=lp98 aapobre
  /ORDER  ANALYSIS .

  \VE OUTFILE='e:\fase8\punteo\REG_40\reg40j_$$.sav'
  /COMPRESSED.
```

Región 40. Centro - Sierra - Chotalpan - Costa
Fase 6
Modelo aa

```
***puntajes región 40

***Modelo

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES= depen ninos  noasi1 esc
    agua_1  estgas vhs refri vehi lava discap
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .



***Calificación


COMPUTE AADEPEN=-25*DEPEN .
COMPUTE AANINOS=-26*NINOS .
COMPUTE AANOASI=-33*NOASI1 .
COMPUTE AAESC=8*ESC .
COMPUTE AAAGUA=12*AGUA_1 .

IF (DISCAP=0) AADISCAP = 100 .
IF (DISCAP=1) AADISCAP = 86 .

IF (ESTGAS=0) AAESTGAS = 100 .
IF (ESTGAS=1) AAESTGAS = 63 .

  (VHS=0) AAVHS= 100 .
IF (VHS=1) AAVHS= 56 .

IF (REFRI=0) AAREFRI= 100 .
IF (REFRI=1) AAREFRI= 79 .

IF (VEHI=0) AAVEHI= 100 .
IF (VEHI=1) AAVEHI= 66 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 67 .


EXECUTE .

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aanoasi aaesc
   aaagua aadiscap aaestgas aavhs aarefri aavehi aalava
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos)  | MISSING(aanoasi)  | MISSING(aaesc)
  | MISSING(aaagua) | MISSING(aadiscap)  | MISSING(aaestgas)  | MISSING(aavhs)  | MISSING(aarefri) | MISSING (aavehi) |
MISSING (aalava)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS=-65.51)  .
RECODE aaninos  (SYSMIS=-38.62)  .
```

```
RECODE aanoasi (SYSMIS=-2.91) .
RECODE aaesc  (SYSMIS=35.20)  .
RECODE aaagua  (SYSMIS=-2.81)  .
RECODE aadiscap (SYSMIS=99.26) .
RECODE aaestgas  (SYSMIS=79.71)  .
RECODE aavhs  (SYSMIS=57.30)  .
RECODE aarefri (SYSMIS=86.01) .
RECODE aavehi  (SYSMIS=67.35)  .
RECODE aalava  (SYSMIS=71.36)  .

EXECUTE .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos + aanoasi + aaesc + aaagua + aadiscap
  + aaestgas + aavhs + aarefri + aavehi + aalava  .

EXECUTE .

***filtros

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .

COMPUTE AACALIF = AACALIF + VIEJITOS .

EXECUTE.


COMPUTE aapobre = 0 .
DO IF (aacalif < 412.10) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

DO IF (AApobre = 1 &  vehi = 0) .
RECODE
  AApobre  (1=0)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=LP98 AAPOBRE .

COMPUTE fecha=161298.
EXECUTE.


SAVE OUTFILE='H:\4_5y6fas\punteo\REG_40\reg40j_18.sav'
  /COMPRESSED.

**********archivo de entrega:   fopo#_1.dbf**********


FILTER OFF.
USE ALL.
SELECT IF(aapobre = 1).
EXECUTE .

SAVE TRANSLATE OUTFILE='H:\4_5y6fas\punteo\REG_40\fopo40_18.dbf'
  /keep = entidad mpio local folio aapobre
  /TYPE=DB4 /MAP /REPLA.

SAVE TRANSLATE OUTFILE='H:\4_5y6fas\punteo\entregas\981216\fopo40_18.dbf'
  /keep = entidad mpio local folio aapobre
  /TYPE=DB4 /MAP /REPLA.
```

Región 40. Centro - Sierra - Chotalpan - Costa
Fase 6
Modelo bb

```
 **puntajes región 40

***Modelo

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES= depen ninos  noasi1 esc
    agua_1  estgas vhs refri vehi lava discap
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .41 .59
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .



***Calificación


COMPUTE BBDEPEN=-13*DEPEN .
COMPUTE BBNINOS=-32*NINOS .
COMPUTE BBNOASI=-22*NOASI1 .
COMPUTE BBESC=13*ESC .
COMPUTE BBAGUA=1*AGUA_1 .

IF (DISCAP=0) BBDISCAP = 100 .
IF (DISCAP=1) BBDISCAP = 70 .

IF (ESTGAS=0) BBESTGAS = 100 .
  (ESTGAS=1) BBESTGAS = 68 .

IF (VHS=0) BBVHS= 100 .
IF (VHS=1) BBVHS= 56 .

IF (REFRI=0) BBREFRI= 100 .
IF (REFRI=1) BBREFRI= 74 .

IF (VEHI=0) BBVEHI= 100 .
IF (VEHI=1) BBVEHI= 55 .

IF (LAVA = 0) BBLAVA = 100 .
IF (LAVA = 1) BBLAVA = 56 .


EXECUTE .

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= BBdepen BBninos BBnoasi BBesc
   BBagua BBdiscap BBestgas BBvhs BBrefri BBvehi BBlava
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE BBinput = 0 .
EXECUTE .
DO IF (MISSING(BBdepen) | MISSING(BBninos)  | MISSING(BBnoasi)  | MISSING(BBesc)
  | MISSING(BBagua) | MISSING(BBdiscap)  | MISSING(BBestgas)  | MISSING(BBvhs)  | MISSING(BBrefri) | MISSING (BBvehi) |
MISSING (BBlava)) .
RECODE
  BBinput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables
```

```
RECODE BBdepen  (SYSMIS=-34.95) .
RECODE BBninos  (SYSMIS=-50.04) .
RECODE BBnoasi (SYSMIS=-2.36) .
RECODE BBesc  (SYSMIS=57.92) .
RECODE BBagua  (SYSMIS=-0.23) .
 ECODE BBdiscap (SYSMIS=98.41) .
.ECODE BBestgas  (SYSMIS=80.53) .
RECODE BBvhs  (SYSMIS=57.41) .
RECODE BBrefri (SYSMIS=81.86) .
RECODE BBvehi  (SYSMIS=56.79) .
RECODE BBlava  (SYSMIS=60.84) .

EXECUTE .

***se hace la calificación

COMPUTE BBcalif = BBdepen + BBninos + BBnoasi + BBesc + BBagua + BBdiscap
  + BBestgas + BBvhs + BBrefri + BBvehi + BBlava  .

EXECUTE .

***se checa el mínimo y el máximo y se toma el punto intermedio como línea de corte

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=BBcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .41  .59
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_4 = 0).
VARIABLE LABEL filter_$ 'dis_4 = 0 (FILTER)'.
 ALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
. ORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=BBcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_4 = 1).
VARIABLE LABEL filter_$ 'dis_4 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=BBcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .



***filtros

COMPUTE VIEJITOS = 0 .
IF ((ej < 25 & TOTPER < 5) | (ej > 65 & ej < 98 & TOTPER < 3)) VIEJITOS = -100 .

COMPUTE BBCALIF = BBCALIF + VIEJITOS .
```

```
EXECUTE.


COMPUTE BBpobre = 0 .
DO IF (BBcalif < 465) .
 ΞCODE
 BBpobre  (0=1)  .
END IF .
EXECUTE .

DO IF (BBpobre = 1 &  vehi = 0) .
RECODE
 BBpobre  (1=0)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=LP98 BBPOBRE .


IF(AAPOBRE=0 & BBPOBRE=1) NVO_POB=1 .
RECODE NVO_POB (SYSMIS=0) .
EXECUTE .


IF ((ULT_NIV=4 | ULT_NIV=6 | ULT_NIV=7) & SEG_SOC=2) MAESTRO=1 .

DO IF (MAESTRO=1) .
RECODE
 NVO_POB (1=0) .
END IF .
EXECUTE .


CROSSTABS
 /TABLES=nvo_pob  BY entidad
 /FORMAT= AVALUE TABLES
 /CELLS= COUNT .


SAVE OUTFILE='F:\4_5y6fas\punteo\REG_40\reg40j.sav'
  /COMPRESSED.
```

REGIÓN 43. NORTE (JALISCO)
FASE 3
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
 /VARIABLES= depen ninos vhs ocupj_1 vehi esc lava piso_1 mu15a49 radio aguaba_1 noasi1 hectie1 tv pared_1
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN = -23*DEPEN .
COMPUTE AANINOS = -35*NINOS .
COMPUTE AAOCUPJ = -47*OCUPJ_1 .
COMPUTE AAESC = 6*ESC .
COMPUTE AAPISO = -6*PISO_1 .
COMPUTE AAMU15A = 8*MU15A49 .
COMPUTE AAAGUABA = 8*AGUABA_1 .
COMPUTE AANOASI = -20*NOASI1 .
COMPUTE AAHECTIE = 1*HECTIE1 .
COMPUTE AAPARED = -11*PARED_1 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 1) AAVHS = 81 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 82 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 84 .

.F (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 89 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 89 .

EXECUTE.

FREQUENCIES
  VARIABLES= aadepen aaninos aaocupj aaesc aapiso aamu15a aaaguaba aanoasi aahectie
             aapared aavhs aavehi aalava aaradio aatv
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aaocupj)| MISSING (aaesc)| MISSING (aapiso)
       | MISSING(aamu15a) | MISSING(aaaguaba)  | MISSING (aanoasi) | MISSING(aahectie)  | MISSING (aapared)
       | MISSING(aavhs)  | MISSING (aavehi)|  MISSING(aalava)  | MISSING (aaradio)| MISSING(aatv)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aadepen  (SYSMIS = -57.3291)  .
RECODE aaninos  (SYSMIS = -62.1968)  .
RECODE aaocupj (SYSMIS = 0.01825)  .
RECODE aaesc  (SYSMIS = 16.5989)  .
RECODE aapiso  (SYSMIS = 0.1956)  .
RECODE aamu15a  (SYSMIS = 10.0563)  .
RECODE aaaguaba  (SYSMIS = -0.0112)  .
RECODE aanoasi  (SYSMIS = -3.4393)  .
RECODE aahectie  (SYSMIS = 3.3632)  .
RECODE aapared  (SYSMIS = 0.2469)  .
RECODE aavhs  (SYSMIS = 83.4402)  .
RECODE aavehi  (SYSMIS = 88.5120)  .
RECODE aalava  (SYSMIS = 87.8340)  .
```

```
RECODE aaradio  (SYSMIS = 97.6805)  .
RECODE aatv  (SYSMIS = 97.5456)  .

COMPUTE aacalif = aadepen + aaninos + aaocupj + aaesc + aapiso + aamu15a + aaaguaba + aanoasi + aahectie
                  + aapared + aavhs +  aavehi + aalava + aaradio + aatv  .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
IF (vehi = 0 & estgas = 0 & vhs = 0 & lava = 0 & refri = 0) enseres = 100 .
RECODE enseres  (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos + enseres.
EXECUTE .

COMPUTE aapobre= 0 .
EXECUTE .
DO IF (aacalif1< 409.34) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 aapobre  .
```

REGIÓN 43. NORTE (JALISCO)
FASE 6
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
 /VARIABLES= depen ninos vhs ocupj_1  esc lava piso_1 mu15a49 radio aguaba_1 noasi1  pared_1
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .41 .59
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN = -23*DEPEN .
COMPUTE AANINOS = -35*NINOS .
COMPUTE AAOCUPJ = -47*OCUPJ_1 .
COMPUTE AAESC = 6*ESC .
COMPUTE AAPISO = -6*PISO_1 .
COMPUTE AAMU15A = 8*MU15A49 .
COMPUTE AAAGUABA = 8*AGUABA_1 .
COMPUTE AANOASI = -20*NOASI1 .
COMPUTE AAHECTIE = 1*HECTIE1 .
COMPUTE AAPARED = -11*PARED_1 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 1) AAVHS = 81 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 82 .

IF (LAVA = 0) AALAVA = 100 .
IF (LAVA = 1) AALAVA = 84 .

F (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 89 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 89 .

EXECUTE.

FREQUENCIES
  VARIABLES= aadepen aaninos aaocupj aaesc aapiso aamu15a aaaguaba aanoasi aahectie
              aapared aavhs aavehi aalava aaradio aatv
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aaocupj)| MISSING (aaesc)| MISSING (aapiso)
       | MISSING(aamu15a) | MISSING(aaaguaba)  | MISSING (aanoasi) | MISSING(aahectie) | MISSING (aapared)
       | MISSING(aavhs)  | MISSING (aavehi)|  MISSING(aalava)  | MISSING (aaradio)| MISSING(aatv)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aadepen  (SYSMIS = -41.8929)  .
RECODE aaninos  (SYSMIS = -67.5000)  .
RECODE aaocupj (SYSMIS =-37.6000)  .
RECODE aaesc  (SYSMIS = 21.4286)  .
RECODE aapiso  (SYSMIS = 2.1214)  .
RECODE aamu15a  (SYSMIS = 8.5714)  .
RECODE aaaguaba  (SYSMIS = 8.9840)  .
  ECODE aanoasi  (SYSMIS = -4.4286)  .
RECODE aahectie  (SYSMIS =6.5011)  .
RECODE aapared  (SYSMIS = 2.7579)  .
RECODE aavhs  (SYSMIS = 85.0714)  .
RECODE aavehi  (SYSMIS = 83.2857)  .
RECODE aalava  (SYSMIS = 85.1429)  .
```

```
RECODE aaradio  (SYSMIS = 96.8571)  .
RECODE aatv  (SYSMIS = 96.8571)  .

COMPUTE aacalif = aadepen + aaninos + aaocupj + aaesc + aapiso + aamu15a + aaaguaba + aanoasi + aahectie
                  + aapared + aavhs +  aavehi + aalava + aaradio + aatv  .
 XECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
 XECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .

COMPUTE aapobre= 0 .
EXECUTE .
DO IF (aacalif1< 409.34) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 aapobre  .
```

REGIÓN 43. NORTE (JALISCO)
FASE 6
MODELO bb

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
/VARIABLES= depen ninos vhs ocupj_1  esc lava piso_1 mu15a49 radio aguaba_1 noasi1  pared_1
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS  .41 .59
 /STATISTICS=RAW TABLE
 /CLASSIFY=NONMISSING POOLED .

COMPUTE bbDEPEN = -36*DEPEN .
COMPUTE bbNINOS = -20*NINOS .
COMPUTE bbOCUPJ = -98*OCUPJ_1 .
COMPUTE bbESC = 6*ESC .
COMPUTE bbPISO = -21*PISO_1 .
COMPUTE bbMU15A = 7*MU15A49 .
COMPUTE bbAGUABA = -4*AGUABA_1 .
COMPUTE bbNOASI = -14*NOASI1 .
COMPUTE bbPARED = -5*PARED_1 .

IF (VHS = 0) bbVHS = 100 .
IF (VHS = 1) bbVHS = 90 .

IF (LAVA = 0) bbLAVA = 100 .
IF (LAVA = 1) bbLAVA = 88.

IF (RADIO = 0) bbRADIO = 100 .
IF (RADIO = 1) bbRADIO = 98.

EXECUTE.

FREQUENCIES
 VARIABLES= bbdepen bbninos bbocupj bbesc bbpiso bbmu15a bbaguaba bbnoasi
            bbpared bbvhs bblava bbradio
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE bbinput = 0 .
EXECUTE .
DO IF (MISSING(bbdepen) | MISSING(bbninos) | MISSING (bbocupj)| MISSING (bbesc)
      | MISSING (bbpiso) | MISSING(bbmu15a) | MISSING(bbaguaba) | MISSING (bbnoasi)
      | MISSING (bbpared) | MISSING(bbvhs) |  MISSING(bblava)  | MISSING (bbradio)) .
RECODE
 bbinput  (0=1)  .
END IF .
EXECUTE .

RECODE bbdepen  (SYSMIS = -100.1224)  .
RECODE bbninos  (SYSMIS = -30.7774)  .
RECODE bbocupj (SYSMIS =28.0132)  .
RECODE bbesc  (SYSMIS = 16.5849)  .
RECODE bbpiso  (SYSMIS = 4.5644)  .
RECODE bbmu15a  (SYSMIS = 8.7170)  .
RECODE bbaguaba  (SYSMIS = -2.6348)  .
RECODE bbnoasi  (SYSMIS = -1.7060) .
RECODE bbpared  (SYSMIS = 1.2599)  .
RECODE bbvhs  (SYSMIS = 92.0755)  .
RECODE bblava  (SYSMIS = 92.6415)  .
RECODE bbradio  (SYSMIS = 99.6952)  .

COMPUTE bbcalif = bbdepen + bbninos + bbocupj + bbesc + bbpiso + bbmu15a + bbaguaba + bbnoasi
                  + bbpared + bbvhs +  bblava + bbradio .
EXECUTE .

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES=bbcalif
```

```
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE bbcalif = bbcalif + viejitos .
EXECUTE .

COMPUTE bbpobre= 0 .
EXECUTE .
DO IF (bbcalif< 247.20) .
RECODE
  bbpobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 bbpobre  .

IF(AAPOBRE=0 & BBPOBRE=1) NVO_POB=1 .
RECODE NVO_POB (SYSMIS=0) .
EXECUTE .

IF ((ULT_NIV=4 | ULT_NIV=6 | ULT_NIV=7) & SEG_SOC=2) MAESTRO=1 .

DO IF (MAESTRO=1) .
RECODE
 NVO_POB (1=0) .
END IF .
EXECUTE .
```

REGIÓN 43. NORTE (JALISCO)
FASE 6
Modelo bb

Entrega 25 no se aplicó filtro de MAESTRO.

REGIÓN 43. NORTE (JALISCO)
FASE 8
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
 /VARIABLES= depen ninos vhs ocupj_1  esc lava piso_1 mu15a49 radio aguaba_1 noasi1  pared_1
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE aaDEPEN = -36*DEPEN .
COMPUTE aaNINOS = -20*NINOS .
COMPUTE aaOCUPJ = -98*OCUPJ_1 .
COMPUTE aaESC = 6*ESC .
COMPUTE aaPISO = -21*PISO_1 .
COMPUTE aaMU15A = 7*MU15A49 .
COMPUTE aaAGUABA = -4*AGUABA_1 .
COMPUTE aaNOASI = -14*NOASI1 .
COMPUTE aaPARED = -5*PARED_1 .

IF (VHS = 0) aaVHS = 100 .
IF (VHS = 1) aaVHS = 90 .

IF (LAVA = 0) aaLAVA = 100 .
IF (LAVA = 1) aaLAVA = 88.

IF (RADIO = 0) aaRADIO = 100 .
 (RADIO = 1) aaRADIO = 98.

EXECUTE.

FREQUENCIES
  VARIABLES= aadepen aaninos aaocupj aaesc aapiso aamu15a aaaguaba aanoasi aapared aavhs aalava aaradio
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aaocupj)| MISSING (aaesc)| MISSING (aapiso)
       | MISSING(aamu15a) | MISSING(aaaguaba)  | MISSING (aanoasi) | MISSING (aapared)
       | MISSING(aavhs) |  MISSING(aalava)  | MISSING (aaradio)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

RECODE aadepen  (SYSMIS = -57.3272)  .
RECODE aaninos  (SYSMIS = -62.1965)  .
RECODE aaocupj (SYSMIS = 0.01699)  .
RECODE aaesc  (SYSMIS = 16.5995)  .
RECODE aapiso  (SYSMIS = 0.1960)  .
RECODE aamu15a  (SYSMIS = 10.0557)  .
RECODE aaaguaba  (SYSMIS = -0.011088)  .
RECODE aanoasi  (SYSMIS = -3.4390) .
RECODE aapared  (SYSMIS = 0.2473)  .
RECODE aavhs  (SYSMIS = 83.4403)  .
RECODE aalava  (SYSMIS = 87.8342)  .
RECODE aaradio  (SYSMIS = 97.6808)  .

COMPUTE aacalif = aadepen + aaninos + aaocupj + aaesc + aapiso + aamu15a + aaaguaba + aanoasi +
                  aapared + aavhs +  aalava + aaradio .
EXECUTE .

DISCRIMINANT
```

```
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif1 + viejitos .
EXECUTE .

COMPUTE aapobre= 0 .
EXECUTE .
DO IF (aacalif1< 255.65) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .
IF (ELIMIN = 1) AAPOBRE = 0 .
EXECUTE .

FREQUENCIES
  VARIABLES=lp98 aapobre  .
```

```
*/*/*PUNTAJE DE LA REGION 41
*/*/*  FASE 8
*/*/ MODELO AA

DISCRIMINANT
  /GROUPS=lp98(0 1)
   /VARIABLES= depen ninos vhs refri ocupj_1 vehi lengua mu15a49 radio trab151 estgas noasi1  hectie1 tv pared_1  discap agua_1
   /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

***puntajes

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE aaDEPEN = -38*DEPEN .
COMPUTE aaNINOS = -16*NINOS .
COMPUTE aaOCUPJ = 24*OCUPJ_1 .
COMPUTE aaMU15A = -3*MU15A49 .
COMPUTE aaTRAB = -48*TRAB151 .
COMPUTE aaNOASI = -22*NOASI1 .
COMPUTE aaHECTIE = 26*HECTIE1 .
COMPUTE aaPARED = -7*PARED_1 .
COMPUTE aaAGUA = 10*AGUA_1 .

IF (VHS = 0) aaVHS = 100 .
IF (VHS = 1) aaVHS = 72 .

IF (REFRI = 0) aaREFRI = 100 .
IF (REFRI = 1) aaREFRI = 88 .

IF (VEHI = 0) aaVEHI = 100 .
IF (VEHI = 1) aaVEHI = 70 .

IF (LENGUA = 0) aaLENGUA = 100 .
IF (LENGUA = 1) aaLENGUA = 82 .

   (RADIO = 0) aaRADIO = 100 .
   (RADIO = 1) aaRADIO = 81 .

IF (ESTGAS = 0) aaESTGAS = 100 .
IF (ESTGAS = 1) aaESTGAS = 89 .

IF (TV = 0) aaTV = 100 .
IF (TV = 1) aaTV = 90 .

IF (DISCAP = 0) aaDISCAP = 100 .
IF (DISCAP = 1) aaDISCAP = 72 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= aadepen aaninos aaocupj aamu15a aatrab aanoasi aahectie aapared aaagua
  aavhs aarefri aavehi aalengua aaradio aaestgas aatv aadiscap
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aaocupj)| MISSING (aamu15a)| MISSING (aatrab)
  | MISSING(aanoasi) | MISSING(aahectie)  | MISSING (aapared) | MISSING(aaagua)  | MISSING (aavhs)
  | MISSING(aarefri)  | MISSING (aavehi)|  MISSING(aalengua)  | MISSING (aaradio)| MISSING(aaestgas) |MISSING(aatv)
|MISSING(aadiscap)) .
RECODE
  aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

    CODE aadepen  (SYSMIS = -103.0711)  .
RECODE aaninos  (SYSMIS = -27.5873)  .
RECODE aaocupj (SYSMIS = 0.2528)  .
RECODE aamu15a  (SYSMIS = -3.4045)  .
RECODE aatrab  (SYSMIS = -3.6698)  .
RECODE aanoasi  (SYSMIS = -3.2987)  .
```

```
RECODE aahectie  (SYSMIS = 47.4134) .
RECODE aapared  (SYSMIS = -0.6674) .
RECODE aaagua  (SYSMIS = -0.4117) .
RECODE aavhs  (SYSMIS = 75.7085) .
RECODE aarefri  (SYSMIS = 91.1713) .
RECODE aavehi  (SYSMIS = 72.8078) .
RECODE aalengua  (SYSMIS = 97.6956) .
RECODE aaradio  (SYSMIS = 95.1461) .
RECODE aaestgas  (SYSMIS = 93.9760) .
RECODE aatv  (SYSMIS = 96.7148) .
RECODE aadiscap  (SYSMIS = 98.7448) .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos +  aaocupj + aamu15a + aatrab + aanoasi + aahectie + aapared + aaagua +
  aavhs + aarefri + aavehi + aalengua + aaradio + aaestgas + aatv + aadiscap .
EXECUTE .

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
   STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

***se determin
a la línea de corte y se obtienen los pobres

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .

COMPUTE aapobre= 0 .
EXECUTE .
DO IF (aacalif1< 778.235) .
RECODE
  aapobre  (0=1)  .
END IF .
   EXECUTE .

****** Recodificación por vehículo

DO IF (vehi = 0 & aapobre = 1) .
RECODE
```

```
 aapobre  (1=0)  .
END IF .
EXECUTE .

*******Filtro de seguridad social y última pregunta del cuestionario

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
   (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .
IF (ELIMIN = 1) AAPOBRE = 0 .
EXECUTE .

FREQUENCIES
  VARIABLES= aapobre lp98  .
```

```
*** PUNTAJES DE L A REGION 44
*/*/ FASE 4A 6
 */*/ MODELO AA

DISCRIMINANT
 /GROUPS=lp98(0 1)
  /ARIABLES= depen ninos vhs refri ocupj_1 vehi lengua mu15a49 radio trab151 estgas noasi1  hectie1 tv pared_1  discap agua_1
  .NALYSIS ALL
 /SAVE=CLASS
 /PRIORS  .42 .58
 /STATISTICS=RAW TABLE
 /CLASSIFY=NONMISSING POOLED .

***puntajes

COMPUTE AADEPEN = -38*DEPEN .
COMPUTE AANINOS = -16*NINOS .
COMPUTE AAOCUPJ = 24*OCUPJ_1 .
COMPUTE AAMU15A = -3*MU15A49 .
COMPUTE AATRAB = -48*TRAB151 .
COMPUTE AANOASI = -22*NOASI1 .
COMPUTE AAHECTIE = 26*HECTIE1 .
COMPUTE AAPARED = -7*PARED_1 .
COMPUTE AAAGUA = 10*AGUA_1 .

IF (VHS = 0) AAVHS = 100 .
IF (VHS = 1) AAVHS = 72 .

IF (REFRI = 0) AAREFRI = 100 .
IF (REFRI = 1) AAREFRI = 88 .

IF (VEHI = 0) AAVEHI = 100 .
IF (VEHI = 1) AAVEHI = 70 .

IF (LENGUA = 0) AALENGUA = 100 .
IF (LENGUA = 1) AALENGUA = 82 .

IF (RADIO = 0) AARADIO = 100 .
IF (RADIO = 1) AARADIO = 81 .

   (ESTGAS = 0) AAESTGAS = 100 .
.. (ESTGAS = 1) AAESTGAS = 89 .

IF (TV = 0) AATV = 100 .
IF (TV = 1) AATV = 90 .

IF (DISCAP = 0) AADISCAP = 100 .
IF (DISCAP = 1) AADISCAP = 72 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
 VARIABLES= aadepen aaninos aaocupj aamu15a aatrab aanoasi aahectie aapared aaagua
 aavhs aarefri aavehi aalengua aaradio aaestgas aatv aadiscap
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE aainput = 0 .
EXECUTE .
DO IF (MISSING(aadepen) | MISSING(aaninos) | MISSING (aaocupj)| MISSING (aamu15a)| MISSING (aatrab)
  | MISSING(aanoasi) | MISSING(aahectie)  | MISSING (aapared) | MISSING(aaagua)  | MISSING (aavhs)
  | MISSING(aarefri)  | MISSING (aavehi)|  MISSING(aalengua)  | MISSING (aaradio)| MISSING(aaestgas) |MISSING(aatv)
|MISSING(aadiscap)) .
RECODE
 aainput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE aadepen  (SYSMIS = -106.69)  .
RECODE aaninos  (SYSMIS = -23.86)  .
RECODE aaocupj (SYSMIS = 25.84)  .
  CODE aamu15a  (SYSMIS = -3.1)  .
RECODE aatrab  (SYSMIS = -1.96)  .
RECODE aanoasi  (SYSMIS = -3.06)  .
RECODE aahectie  (SYSMIS = 66.69)  .
RECODE aapared  (SYSMIS = 2.4)  .
RECODE aaagua  (SYSMIS = -5.18)  .
```

```
RECODE aavhs  (SYSMIS = 74.82)  .
RECODE aarefri  (SYSMIS = 93.35)  .
RECODE aavehi  (SYSMIS = 73.86)  .
RECODE aalengua  (SYSMIS = 99.25)  .
RECODE aaradio  (SYSMIS = 95.63)  .
RECODE aaestgas  (SYSMIS = 94.48)  .
RECODE aatv  (SYSMIS = 96.48)  .
RECODE aadiscap  (SYSMIS = 98.04)  .

***se hace la calificación

COMPUTE aacalif = aadepen + aaninos +  aaocupj + aamu15a + aatrab + aanoasi + aahectie + aapared + aaagua +
  aavhs + aarefri + aavehi + aalengua + aaradio + aaestgas + aatv + aadiscap .
EXECUTE .

**discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=aacalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .42 .58
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=aacalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

***se determin
a la línea de corte y se obtienen los pobres

IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE aacalif1 = aacalif + viejitos .
EXECUTE .

COMPUTE aapobre= 0 .
EXECUTE .
DO IF (aacalif1< 712.095) .
RECODE
  aapobre  (0=1)  .
END IF .
EXECUTE .

***** Recodificación por vehículo

DO IF (vehi = 0 & aapobre = 1) .
RECODE
  aapobre  (1=0)  .
END IF .
EXECUTE .
```

```
FREQUENCIES
  VARIABLES= aapobre lp98  .
```

```
*** PUNTAJES DE L A REGION 44
*/*/ FASE 4A 6
 */*/ MODELO BB

DISCRIMINANT
  /GROUPS=lp98(0 1)
 /VARIABLES= depen ninos vhs refri ocupj_1 vehi lengua mu15a49 radio trab151 estgas noasi1  hectie1 tv pared_1  discap agua_1
   ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .41 .59
  /STATISTICS=RAW TABLE
  /CLASSIFY=NONMISSING POOLED .

***puntajes

COMPUTE bbDEPEN = -34*DEPEN .
COMPUTE bbNINOS = -15*NINOS .
COMPUTE bbOCUPJ = 74*OCUPJ_1 .
COMPUTE bbMU15A = -1*MU15A49 .
COMPUTE bbTRAB = -11*TRAB151 .
COMPUTE bbNOASI = -33*NOASI1 .
COMPUTE bbHECTIE = 4*HECTIE1 .
COMPUTE bbPARED = -19*PARED_1 .
COMPUTE bbAGUA = -20*AGUA_1 .

IF (VHS = 0) bbVHS = 100 .
IF (VHS = 1) bbVHS = 79 .

IF (REFRI = 0) bbREFRI = 100 .
IF (REFRI = 1) bbREFRI = 75 .

IF (VEHI = 0) bbVEHI = 100 .
IF (VEHI = 1) bbVEHI = 65 .

IF (LENGUA = 0) bbLENGUA = 100 .
IF (LENGUA = 1) bbLENGUA = 114 .

IF (RADIO = 0) bbRADIO = 100 .
IF (RADIO = 1) bbRADIO = 102 .

   (ESTGAS = 0) bbESTGAS = 100 .
   (ESTGAS = 1) bbESTGAS = 93 .

IF (TV = 0) bbTV = 100 .
IF (TV = 1) bbTV = 87 .

IF (DISCAP = 0) bbDISCAP = 100 .
IF (DISCAP = 1) bbDISCAP = 83 .

EXECUTE.

***calcular las medias de las variables para imputar a valores perdidos

FREQUENCIES
  VARIABLES= bbdepen bbninos bbocupj bbmu15a bbtrab bbnoasi bbhectie bbpared bbagua
  bbvhs bbrefri bbvehi bblengua bbradio bbestgas bbtv bbdiscap
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE bbinput = 0 .
EXECUTE .
DO IF (MISSING(bbdepen) | MISSING(bbninos) | MISSING (bbocupj)| MISSING (bbmu15a)| MISSING (bbtrab)
  | MISSING(bbnoasi) | MISSING(bbhectie)  | MISSING (bbpared) | MISSING(bbagua)  | MISSING (bbvhs)
  | MISSING(bbrefri)  | MISSING (bbvehi)|  MISSING(bblengua)  | MISSING (bbradio)| MISSING(bbestgas) |MISSING(bbtv)
|MISSING(bbdiscap)) .
RECODE
  bbinput  (0=1)  .
END IF .
EXECUTE .

***se recodifican los valores perdidos con las medias de las variables

RECODE bbdepen  (SYSMIS = -86.9838)  .
RECODE bbninos  (SYSMIS = -21.8781)  .
RECODE bbocupj (SYSMIS = 28.1384)  .
   ECODE bbmu15a  (SYSMIS = -1.0531)  .
  ECODE bbtrab  (SYSMIS = -0.4706)  .
RECODE bbnoasi  (SYSMIS = -3.9140)  .
RECODE bbhectie  (SYSMIS = 11.7069)  .
RECODE bbpared  (SYSMIS = 8.4596)  .
RECODE bbagua  (SYSMIS = 2.3238)  .
```

```
RECODE bbvhs  (SYSMIS = 81.6262)  .
RECODE bbrefri  (SYSMIS = 82.7835)  .
RECODE bbvehi  (SYSMIS = 68.5981)  .
RECODE bblengua  (SYSMIS = 101.4647)  .
RECODE bbradio  (SYSMIS = 100.6142)  .
RECODE bbestgas  (SYSMIS = 96.7998)  .
  ECODE bbtv  (SYSMIS = 95.3602)  .
  ECODE bbdiscap  (SYSMIS = 99.0889)  .

***se hace la calificación

COMPUTE bbcalif = bbdepen + bbninos +  bbocupj + bbmu15a + bbtrab + bbnoasi + bbhectie + bbpared + bbagua +
  bbvhs + bbrefri + bbvehi + bblengua + bbradio + bbestgas + bbtv + bbdiscap .
EXECUTE .

***discriminante con la línea de pobreza

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=bbcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS  .41 .59
  /STATISTICS=raw TABLE crossvalid
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
  OMPUTE filter_$=(dis_2 = 1).
 ARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=bbcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .


***se determin
a la línea de corte y se obtienen los pobres


IF ((EJ<= 24 & totper <= 4) | (EJ >= 65 & totper <= 2)) viejitos = -100.
  recode viejitos (SYSMIS = 0) .
EXECUTE .

COMPUTE bbcalif1 = bbcalif + viejitos .
EXECUTE .

COMPUTE BBpobre= 0 .
EXECUTE .
DO IF (bbcalif1< 723.005) .
RECODE
  BBpobre  (0=1)  .
END IF .
 XECUTE .

 **** Recodificación por vehículo

DO IF (vehi = 0 & BBpobre = 1) .
RECODE
  BBpobre  (1=0)  .
```

```
END IF .
EXECUTE .

DO IF (aapobre = 1) .
RECODE
  bbpobre  (1=0)  .
    'D IF .
    .ECUTE .

FREQUENCIES
  VARIABLES= bbpobre lp98  .
```

REGIÓN 45. VALLE DE SAN QUINTIN
FASE 6
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=  ninos mu15a49  depen  trab151 ej
  piso_1  ocupj_1  discap esc
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS=0.42 0.58
  /STATISTICS=RAW
  /HISTORY
  /CLASSIFY=NONMISSING POOLED .

COMPUTE AANINOS=-32*NINOS .
COMPUTE AAMU1549=31*MU15A49.
COMPUTE AADEPEN=-43*DEPEN.
COMPUTE AAT15=-89*TRAB151 .
COMPUTE AAEDAD=-1*ej .
COMPUTE AAPISO=15*PISO_1 .
COMPUTE AAOCUP=-56*OCUPJ_1 .
COMPUTE AAESC=5*ESC .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 52 .

FREQUENCIES
  VARIABLES= AANINOS AAMU1549 AADEPEN AAT15 AAEDAD AAPISO AAOCUP AAESC AADISCAP
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AANINOS) | MISSING(AAMU1549) |  MISSING(AADEPEN) | MISSING(AAT15)
      | MISSING(AAEDAD) | MISSING(AAPISO)   |  MISSING(AAOCUP) | MISSING(AAESC) | MISSING(AADISCAP)  ) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .

RECODE  AANINOS (SYSMIS=-53.02) .
RECODE  AAmu1549 (SYSMIS=33).
RECODE  AADEPEN (SYSMIS=-86.38) .
RECODE  AAT15 (SYSMIS=-7.78).
RECODE  AAEDAD (SYSMIS=-39.45).
RECODE  AAPISO (SYSMIS=-7.21).
RECODE  AAOCUP (SYSMIS=50.61).
RECODE  AAESC (SYSMIS=20.67).
RECODE  AADISCAP (SYSMIS=98.87).

COMPUTE AAcalif = AADEPEN + AANINOS + AAmu1549 + AAT15 + AAESC + AAOCUP + AAEDAD + AAPISO + AADISCAP.
EXECUTE .

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

'ISE ALL.
.OMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .
```

```
FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

 JSE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((TOT_PER<=4  & ej<=24) | (TOT_PER<=2  & ej >= 65) & missing(seg_soc)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .
EXECUTE .

COMPUTE AACALIF1=AACALIF  + viejitos .
EXECUTE .

IF (agua1=1  & luz=1  & piso= 1) AACALIF1=AACALIF1-100 .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (AAcalif1<25.1) .
RECODE
  apobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES= lp98 aapobre  .
```

REGIÓN 45. VALLE DE SAN QUINTIN
FASE 8
MODELO aa

```
DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=  ninos mu15a49  depen  trab151 ej
 piso_1  ocupj_1  discap esc
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS=0.42 0.58
 /STATISTICS=RAW
 /HISTORY
 /CLASSIFY=NONMISSING POOLED .

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AANINOS=-32*NINOS .
COMPUTE AAMU1549=31*MU15A49.
COMPUTE AADEPEN=-43*DEPEN.
COMPUTE AAT15=-89*TRAB151 .
COMPUTE AAEDAD=-1*ej .
COMPUTE AAPISO=15*PISO_1 .
COMPUTE AAOCUP=-56*OCUPJ_1 .
COMPUTE AAESC=5*ESC .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 52 .

FREQUENCIES
 VARIABLES=  AANINOS AAMU1549 AADEPEN AAT15 AAEDAD AAPISO AAOCUP AAESC AADISCAP
 /FORMAT=NOTABLE
 'STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF (MISSING(AANINOS) | MISSING(AAMU1549) | MISSING(AADEPEN) | MISSING(AAT15)
      | MISSING(AAEDAD) | MISSING(AAPISO) | MISSING(AAOCUP) | MISSING(AAESC) | MISSING(AADISCAP)) .
RECODE
 input  (0=1)  .
END IF .
EXECUTE .

RECODE  AANINOS (SYSMIS= -52.8854) .
RECODE  AAmu1549 (SYSMIS=32.8754).
RECODE  AADEPEN (SYSMIS= -86.5160) .
RECODE  AAT15 (SYSMIS= -7.7545).
RECODE  AAEDAD (SYSMIS= -39.4895).
RECODE  AAPISO (SYSMIS= -7.2765).
RECODE  AAOCUP (SYSMIS= 50.5193).
RECODE  AAESC (SYSMIS= 20.6726).
RECODE  AADISCAP (SYSMIS= 98.8555).

COMPUTE AAcalif = AADEPEN + AANINOS + AAmu1549 + AAT15 + AAESC + AAOCUP + AAEDAD + AAPISO + AADISCAP  .
EXECUTE .

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=AAcalif
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS = .42 .58
 /STATISTICS=raw TABLE  CROSSVALID
  CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
```

```
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((TOT_PER<=4  & ej<=24) | (TOT_PER<=2  & ej >= 65) & missing(seg_soc)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .
EXECUTE .

COMPUTE AACALIF1=AACALIF + viejitos .
EXECUTE .

IF (agua1=1  & luz=1  & piso= 1) AACALIF1=AACALIF1-100 .
EXECUTE .

COMPUTE aapobre = 0 .
 XECUTE .
DO IF (AAcalif1<7.4) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .
IF (ELIMIN = 1) AAPOBRE = 0 .
EXECUTE .

FREQUENCIES
  VARIABLES= aapobre lp98 elimin .
```

REGIÓN 45. VALLE DE SAN QUINTIN
FASE 8
MODELO bb

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=  ninos mu15a49  depen  trab151 ej
  piso_1  ocupj_1  discap esc
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS=0.42 0.58
  /STATISTICS=RAW
  /HISTORY
  /CLASSIFY=NONMISSING POOLED .

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AANINOS=-32*NINOS .
COMPUTE AAMU1549=31*MU15A49.
COMPUTE AADEPEN=-43*DEPEN.
COMPUTE AAT15=-89*TRAB151 .
COMPUTE AAEDAD=-1*ej .
COMPUTE AAPISO=15*PISO_1 .
COMPUTE AAOCUP=-56*OCUPJ_1 .
COMPUTE AAESC=5*ESC .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 52 .

FREQUENCIES
  VARIABLES= AANINOS AAMU1549 AADEPEN AAT15 AAEDAD AAPISO AAOCUP AAESC AADISCAP
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF (MISSING(AANINOS) | MISSING(AAMU1549) |  MISSING(AADEPEN)  | MISSING(AAT15)
      | MISSING(AAEDAD) | MISSING(AAPISO) | MISSING(AAOCUP) | MISSING(AAESC) | MISSING(AADISCAP)) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .

RECODE  AANINOS (SYSMIS= -52.8854) .
RECODE  AAmu1549 (SYSMIS=32.8754).
RECODE  AADEPEN (SYSMIS= -86.5160) .
RECODE  AAT15 (SYSMIS= -7.7545).
RECODE  AAEDAD (SYSMIS= -39.4895).
RECODE  AAPISO (SYSMIS= -7.2765).
RECODE  AAOCUP (SYSMIS= 50.5193).
RECODE  AAESC (SYSMIS= 20.6726).
RECODE  AADISCAP (SYSMIS= 98.8555).

COMPUTE AAcalif = AADEPEN + AANINOS + AAmu1549 + AAT15 + AAESC + AAOCUP +  AAEDAD + AAPISO + AADISCAP.
EXECUTE .

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
```

```
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((TOT_PER<=4  & ej<=24) | (TOT_PER<=2  & ej >= 65) & missing(seg_soc)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .
EXECUTE .

COMPUTE AACALIF1=AACALIF + viejitos .
EXECUTE .

IF (agua1=1  & luz=1  & piso= 1) AACALIF1=AACALIF1-100 .
EXECUTE .

COMPUTE bbpobre = 0 .
 XECUTE .
JO IF (AAcalif1<7.4) .
RECODE
bbpobre  (0=1)  .
END IF .
EXECUTE .

IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF (FAM_BIEN = 1 & BBPOBRE = 1) ELIMIN_2 = 1 .
RECODE FAM_BIEN ELIMIN_2 (SYSMIS = 0) .
IF (ELIMIN_2 = 1) BBPOBRE = 0 .
EXECUTE .

FREQUENCIES
  VARIABLES= BBpobre lp98 elimin_2 .
```

REGIÓN 46. BAJA CALIFORNIA SUR
FASE 6
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES= ventila ninos mu15a49 vehi depen  ej noasi1 trab151 discap esc
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS=0.42 0.58
  /STATISTICS=RAW TABLE
  /HISTORY
  /CLASSIFY=NONMISSING POOLED .

COMPUTE AADEPEN=-41*DEPEN.
COMPUTE AANINOS=-37*NINOS .
COMPUTE AANA15=-91*NOASI1.
COMPUTE AAmu1549=39*mu15a49 .
COMPUTE AAT15=-153*TRAB151 .
COMPUTE AAESC=7*ESC .
COMPUTE AAEDAD=-3*ej .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 71 .

IF (VENTILA=0) AAVENTIL=100 .
IF (VENTILA=1) AAVENTIL=63 .

IF (ESTGAS=0) AAESTGAS=100 .
IF (ESTGAS=1) AAESTGAS=52 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=52 .

FREQUENCIES
  VARIABLES= AADEPEN AANINOS AAMU1549 AANA15 AAT15 AAESC AAEDAD AAVENTIL AADISCAP AAVEHI
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AAMU1549) | MISSING(AANA15) | MISSING(AAT15)
      | MISSING(AAESC) | MISSING(AAEDAD) | MISSING(AAVENTIL) | MISSING(AADISCAP) | MISSING(AAVEHI) ) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .

RECODE  AADEPEN (SYSMIS=-79.66) .
RECODE  AANINOS (SYSMIS=-40.48) .
RECODE  AAMU1549 (SYSMIS=40.59) .
RECODE  AANA15 (SYSMIS=-5.8).
RECODE  AAT15 (SYSMIS=-3.12).
RECODE  AAESC (SYSMIS=37.32).
RECODE  AAEDAD (SYSMIS=-137.84).
RECODE  AAVENTIL (SYSMIS=93.79).
RECODE  AADISCAP (SYSMIS=95.79) .
RECODE  AAVEHI (SYSMIS=79.02) .

COMPUTE AAcalif = AADEPEN + AANINOS + AAMU1549 + AANA15 + AAT15 +AAESC + AAEDAD + AAVENTIL
                  + AADISCAP +  AAVEHI .
EXECUTE .

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE  CROSSVALID
```

```
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_2 = 0).
VARIABLE LABEL filter_$ 'dis_2 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_2 = 1).
VARIABLE LABEL filter_$ 'dis_2 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((TOT_PER<=4  & ej<=24) | (TOT_PER<=2  & ej >= 65) & SYSMIS(SEG_SOC)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .
EXECUTE .

COMPUTE AACALIF1=AACALIF  + viejitos .
EXECUTE .

IF (agua1=1  & luz=1  & piso= 1) AACALIF1=AACALIF1-100 .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (AAcalif1< 111) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

FREQUENCIES
  VARIABLES= LP98 aapobre  .
```

REGIÓN 46. BAJA CALIFORNIA SUR
FASE 8
MODELO aa

```
DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES= ventila ninos mu15a49 vehi depen  ej noasi1 trab151 discap esc
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS=0.42 0.58
  /STATISTICS=RAW TABLE
  /HISTORY
  /CLASSIFY=NONMISSING POOLED .

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE AADEPEN=-41*DEPEN.
COMPUTE AANINOS=-37*NINOS .
COMPUTE AANA15=-91*NOASI1.
COMPUTE AAmu1549=39*mu15a49 .
COMPUTE AAT15=-153*TRAB151 .
COMPUTE AAESC=7*ESC .
COMPUTE AAEDAD=-3*ej .

IF (DISCAP =0) AADISCAP = 100.
IF (DISCAP =1) AADISCAP = 71 .

IF (VENTILA=0) AAVENTIL=100 .
IF (VENTILA=1) AAVENTIL=63 .

IF (ESTGAS=0) AAESTGAS=100 .
IF (ESTGAS=1) AAESTGAS=52 .

IF (VEHI=0) AAVEHI=100 .
IF (VEHI=1) AAVEHI=52 .

FREQUENCIES
  VARIABLES= AADEPEN AANINOS AAMU1549 AANA15 AAT15 AAESC AAEDAD AAVENTIL AADISCAP AAVEHI
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AANINOS) | MISSING(AAMU1549) | MISSING(AANA15) | MISSING(AAT15)
      | MISSING(AAESC) | MISSING(AAEDAD) | MISSING(AAVENTIL) | MISSING(AADISCAP) | MISSING(AAVEHI) ) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .

RECODE  AADEPEN (SYSMIS=-85.38) .
RECODE  AANINOS (SYSMIS=-42.91) .
RECODE  AAMU1549 (SYSMIS=41.89) .
RECODE  AANA15 (SYSMIS=-5.70).
RECODE  AAT15 (SYSMIS=-2.87).
RECODE  AAESC (SYSMIS=36.83).
RECODE  AAEDAD (SYSMIS=-136.02).
RECODE  AAVENTIL (SYSMIS=90.28).
RECODE  AADISCAP (SYSMIS=96.16) .
RECODE  AAVEHI (SYSMIS=77.65) .

COMPUTE AAcalif = AADEPEN + AANINOS +AAMU1549 + AANA15 + AAT15 +AAESC +  AAEDAD + AAVENTIL
                  + AADISCAP + AAVEHI .
  EXECUTE .

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
```

```
  /SAVE=CLASS
  /PRIORS = .42 .58
  /STATISTICS=raw TABLE  CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

'JSE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
VARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

IF ((TOT_PER<=4  & ej<=24) | (TOT_PER<=2  & ej >= 65) & SYSMIS(SEG_SOC)) viejitos=-100 .
RECODE  viejitos (SYSMIS=0) .
EXECUTE .

COMPUTE AACALIF1=AACALIF + viejitos .
EXECUTE .

IF (agua1=1  & luz=1  & piso= 1) AACALIF1=AACALIF1-100 .
EXECUTE .

COMPUTE aapobre = 0 .
EXECUTE .
DO IF (AAcalif1< 77.5) .
RECODE
aapobre  (0=1)  .
END IF .
EXECUTE .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .
IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .
RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .
IF (ELIMIN = 1) AAPOBRE = 0 .
EXECUTE .

FREQUENCIES
  VARIABLES= aapobre  LP98 .
```

```
*/*/* PUNTAJES DE LA REGION 47
*/*/* FASE 8
*/*/* MODELO AA

IF (seg_soc <= 1 & seg_soc <= 5) seg_soc1 = 0 .
EXECUTE .
RECODE
 seg_soc1 (SYSMIS=1) .
EXECUTE .

FREQUENCIES
 VARIABLES=depen trab151  seg_soc1 ninos vehi
 /FORMAT=NOTABLE
 /STATISTICS=MEAN .

DISCRIMINANT
 /GROUPS=lp98(0 1)
 /VARIABLES=depen trab151 seg_soc1 ninos vehi
 /ANALYSIS ALL
 /PRIORS  EQUAL
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

***Calificación

IF (PERCEP = 0) DEPEN = 99 .
RECODE DEPEN (99 = SYSMIS) .

COMPUTE aadepen = -32*DEPEN .
COMPUTE aatrab15 = -249*TRAB151 .
COMPUTE aaninos = -29*NINOS .

IF (seg_soc1 = 0) aasegsoc = 100 .
IF (seg_soc1 = 1) aasegsoc = 52.38 .

IF (vehi = 0) aavehi = 100 .
IF (vehi = 1) aavehi = 50.15 .

FREQUENCIES
 VARIABLES= AADEPEN AATRAB15 AANINOS AASEGSOC  AAVEHI
  FORMAT=NOTABLE
 /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
DO IF ( MISSING(AADEPEN) | MISSING(AATRAB15) | MISSING(AANINOS) |
  missing(AASEGSOC) | missing(AAVEHI)) .
RECODE
 input  (0=1)  .
END IF .
EXECUTE .

************************************************************

RECODE  AADEPEN (SYSMIS=-62.28) .
RECODE  AATRAB15 (SYSMIS=-9.29) .
RECODE  AANINOS (SYSMIS=-35.54) .
RECODE  AASEGSOC (SYSMIS=68.25) .
RECODE  AAVEHI (SYSMIS=71.96) .

COMPUTE AAcalif = AADEPEN + AATRAB15 + AANINOS + AASEGSOC + AAVEHI .
EXECUTE .

DISCRIMINANT
 /GROUPS=LP98(0 1)
 /VARIABLES=AAcalif
 /ANALYSIS ALL
 /SAVE=CLASS
 /PRIORS EQUAL
 /STATISTICS=raw TABLE CROSSVALID
 /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
  LUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
```

```
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
COMPUTE filter_$=(dis_1 = 1).
 'ARIABLE LABEL filter_$ 'dis_1 = 1 (FILTER)'.
  ALUE LABELS filter_$ 0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

FREQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS= MAXIMUM .

FILTER OFF.
USE ALL.
EXECUTE .

compute VIEJITOS = 0 .
execute.
do if (((EJ<25 & TOTPER<5) | (EJ>65 & TOTPER <3)) & (SEG_SOC1 = 1)) .
recode
    VIEJITOS (0=1).
end if.
execute.

IF (VIEJITOS = 1) AAVIEJ = -100 .
RECODE AAVIEJ (SYSMIS = 0) .
EXECUTE .

COMPUTE AAcalif = AAcalif + AAVIEJ.
EXECUTE .


COMPUTE AApobre = 0 .
EXECUTE .
DO IF (AAcalif < 23.69) .
  CODE
 .pobre  (0=1)  .
END IF .
EXECUTE .

IF (SEG_SOC > 0 & SEG_SOC < 6) SEGURO = 1 .
IF (FAM_ENTR >= 1 & FAM_ENTR <= 7) FAM_BIEN = 1 .

IF ((SEGURO = 1 | FAM_BIEN = 1) & AAPOBRE = 1) ELIMIN = 1 .

RECODE SEGURO FAM_BIEN ELIMIN (SYSMIS = 0) .

IF (ELIMIN = 1) AAPOBRE = 0 .

EXECUTE .

FREQUENCIES
  VARIABLES=LP98 AAPOBRE .
```

```
*/*/*/ PUNTAJES DE LA REGION 47
*/*/  FASE 4 A 6
*/*/*  MODELO  AA

IF (seg_soc <= 1 & seg_soc <= 5) seg_soc1 = 0 .
EXECUTE .
 'ECODE
 ;eg_soc1 (SYSMIS=1) .
EXECUTE .

FREQUENCIES
  VARIABLES=depen trab151  seg_soc1 ninos vehi
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

DISCRIMINANT
  /GROUPS=lp98(0 1)
  /VARIABLES=depen trab151 seg_soc1 ninos vehi
  /ANALYSIS ALL
  /PRIORS  EQUAL
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

COMPUTE aadepen = -32*DEPEN .
COMPUTE aatrab15 = -249*TRAB151 .
COMPUTE aaninos = -29*NINOS .

IF (seg_soc1 = 0) aasegsoc = 100 .
IF (seg_soc1 = 1) aasegsoc = 52.38 .

IF (vehi = 0) aavehi = 100 .
IF (vehi = 1) aavehi = 50.15 .

FREQUENCIES
  VARIABLES= AADEPEN AATRAB15 AANINOS AASEGSOC  AAVEHI
  /FORMAT=NOTABLE
  /STATISTICS=MEAN .

COMPUTE input = 0 .
EXECUTE .
  ) IF ( MISSING(AADEPEN) | MISSING(AATRAB15) | MISSING(AANINOS) |
  missing(AASEGSOC) | missing(AAVEHI)) .
RECODE
  input  (0=1)  .
END IF .
EXECUTE .

************************************************************

RECODE  AADEPEN (SYSMIS=-62.27) .
RECODE  AATRAB15 (SYSMIS=-9.29) .
RECODE  AANINOS (SYSMIS=-35.54) .
RECODE  AASEGSOC (SYSMIS=68.25) .
RECODE  AAVEHI (SYSMIS=71.96) .

COMPUTE AAcalif = AADEPEN + AATRAB15 + AANINOS + AASEGSOC + AAVEHI .
EXECUTE .

DISCRIMINANT
  /GROUPS=LP98(0 1)
  /VARIABLES=AAcalif
  /ANALYSIS ALL
  /SAVE=CLASS
  /PRIORS EQUAL
  /STATISTICS=raw TABLE CROSSVALID
  /CLASSIFY=NONMISSING POOLED .

USE ALL.
COMPUTE filter_$=(dis_1 = 0).
VARIABLE LABEL filter_$ 'dis_1 = 0 (FILTER)'.
VALUE LABELS filter_$  0 'Not Selected' 1 'Selected'.
FORMAT filter_$ (f1.0).
FILTER BY filter_$.
EXECUTE .

    EQUENCIES
  VARIABLES=AAcalif
  /FORMAT=NOTABLE
  /STATISTICS=MINIMUM .

USE ALL.
```