AUROUAV: A Multi-Sensor Autonomy Architecture for Aerial Robots

Emmanuel Musvaire
Department of Computer Science and Informatics
Oakland University
Rochester, MI, USA
Email: emusvaire@oakland.edu

Abstract

Autonomous aerial robots must operate reliably in GNSS-denied environments where perception is degraded by motion blur, rapid viewpoint changes, cluttered backgrounds, and partial occlusions. Traditional convolutional neural network (CNN)–based perception pipelines struggle under these conditions, limiting their effectiveness in real-world UAV navigation. This paper introduces **AUROUAV**, a unified multi-sensor autonomy architecture that integrates lightweight Vision Transformer (ViT)–based object detection, DroNet steering prediction, visual-inertial odometry, factor-graph SLAM, semantic mapping, reinforcement learning, and probabilistic steering control. Central to the system is a Gaussian steering angle probability density function (PDF) that enforces smooth, stable control while enabling dynamic adaptation through real-time sensor fusion and reinforcement learning algorithms such as Proximal Policy Optimization (PPO) and Twin Delayed Deep Deterministic Policy Gradient (TD3). A custom multi-modal dataset generated using AirSim, PX4 SITL, and Gazebo supports training and evaluation across diverse GNSS-denied scenarios. Experimental results demonstrate that the ViT-DETR perception module significantly outperforms CNN baselines in robustness to occlusion, illumination variation, and motion blur, while achieving real-time inference on embedded UAV hardware. Field tests confirm improved hazard recognition, smoother trajectory execution, and enhanced navigation safety. AUROUAV represents a substantial advancement in human-centered UAV autonomy, illustrating how transformer-based perception and probabilistic control can be combined to achieve reliable navigation in complex and unpredictable environments.

I. Introduction

Autonomous aerial robots increasingly operate in environments where GNSS signals are unreliable or entirely unavailable. Indoor corridors, dense forests, urban canyons, and post-disaster zones impose severe visual challenges, requiring UAVs to rely exclusively on onboard perception and state estimation. Traditional convolutional neural network (CNN)–based perception pipelines often fail under these conditions because their reliance on local high-frequency features makes them highly sensitive to motion blur, abrupt viewpoint changes, partial occlusions, dust haze, and cluttered backgrounds. These factors corrupt the local edge and texture cues required for stable convolutional feature extraction, resulting in degraded detections and unsafe navigation behavior [2].

Recent advances in transformer-based vision models offer a promising alternative. Vision Transformers (ViTs) apply global self-attention across image patches, enabling long-range spatial reasoning that remains stable even when local patches are corrupted. However, ViTs also degrade sharply under severe visual drift caused by motion blur, dust haze, illumination variation, and sensor noise—conditions common in UAV deployments [1]. Despite this degradation, ViTs remain substantially more robust than CNNs because global attention preserves contextual structure even when local features collapse.

Building on these developments, AUROUAV integrates a lightweight ViT-DETR perception module into a unified autonomy stack that includes visual-inertial odometry (VIO), factor-graph SLAM, semantic mapping, reinforcement learning, and probabilistic steering control. A key innovation of the architecture is a Gaussian steering-angle probability density function (PDF) that governs UAV motion, ensuring smooth trajectories while minimizing abrupt deviations. This PDF is dynamically adapted using real-time sensor fusion and reinforcement learning algorithms such as Proximal Policy Optimization (PPO) and Twin Delayed Deep Deterministic Policy Gradient (TD3), enabling the UAV to respond intelligently to obstacles and environmental changes.

AUROUAV demonstrates how transformer-based perception and probabilistic control can be combined to achieve reliable, human-centered autonomy in complex, unpredictable, and GNSS-denied environments.

II. Related Work

Research in UAV perception has traditionally relied on convolutional neural networks, optical flow, and stereo-vision pipelines. While effective in structured environments, CNNs degrade severely under dynamic UAV conditions. Motion blur physically destroys the high-frequency magnitude cues that CNNs depend on, causing catastrophic segmentation collapse and unstable

detections [2]. Cluttered backgrounds, occlusions, and rapid viewpoint changes further disrupt local receptive fields, limiting CNN reliability in real-world flight.

Vision Transformers (ViTs) represent a paradigm shift by introducing global self-attention mechanisms that model long-range dependencies across image patches. This global receptive field enables ViTs to maintain stable representations even when local features are corrupted. However, ViTs also degrade sharply under post-earthquake visual drift—motion blur, dust haze, illumination variation, and sensor noise—conditions that produce structured distributional shifts in UAV imagery [1]. Lightweight variants such as MobileViT, TinyViT, and DeiT demonstrate that transformer-based perception can be optimized for embedded platforms without sacrificing contextual understanding.

Beyond perception, UAV autonomy requires reliable state estimation, mapping, and planning. Classical SLAM systems such as ORB-SLAM2, OKVIS, and VINS-Mono provide strong baselines for visual-inertial odometry and global consistency. However, these systems often struggle in environments with limited visual features or rapid motion. Reinforcement learning has also been explored for UAV navigation, offering adaptive control strategies that respond to dynamic obstacles and environmental uncertainty.

AUROUAV unifies these strands of research by integrating transformer-based perception, probabilistic steering control, reinforcement learning, and multi-sensor state estimation into a cohesive autonomy architecture optimized for GNSS-denied environments.

II-A. CNN vs. ViT: A Technical Contrast

CNNs and ViTs exhibit fundamentally different failure modes under UAV flight conditions:

CNN Failure Modes

- Depend on **local high-frequency features**
- Motion blur → edges vanish → CNN collapses
- Occlusion/clutter → local patches corrupted → unstable detections
- Dust haze/illumination variation → feature drift → unsafe navigation
- Documented catastrophic degradation in UAV segmentation [2]

ViT Failure Modes

- Use **global self-attention**
- More resilient to blur, haze, clutter, and viewpoint changes

- Still degrade under severe visual drift (motion blur + dust haze + illumination variation + sensor noise) [1]
- Degradation is **graceful**, not catastrophic
- Adaptation methods (MEMO, TENT) can recover performance without retraining [1]

This contrast motivates the use of ViT-DETR in AUROUAV.

III. System Architecture

AUROUAV is structured as a unified autonomy pipeline composed of eight tightly integrated subsystems: perception, estimation, world modeling, mapping, planning, safety supervision, control, and the PX4 flight stack. Together, these subsystems transform raw sensor measurements into stable, safe, and intelligent flight behavior. The architecture is designed to operate entirely without GNSS, relying instead on onboard sensing, learned models, and predictive reasoning to navigate complex environments.

DroNet Architecture

DroNet serves as the reactive perception backbone of AUROUAV. It uses a ResNet-18 encoder to extract hierarchical features from the input image. These features feed into two independent heads: one for steering angle regression and one for collision probability estimation.




Fig. 1. DroNet multi-task architecture for joint steering and collision prediction. *The network takes a* 224×224 *RGB image as input and processes it through a ResNet-18 convolutional*

backbone. The shared feature representation branches into two task-specific heads: a steering head that performs continuous regression to estimate the optimal steering angle, and a collision head that applies a sigmoid activation to predict the probability of an imminent collision. This multi-task design enables DroNet to learn both reactive control and safety awareness from a single forward pass.

The steering output provides a continuous lateral control signal, while the collision probability feeds into the safety subsystem.

At the foundation of the system lies the perception layer, which processes RGB imagery through four complementary models: DroNet for steering and collision prediction, a depth-estimation network for geometric awareness, a semantic segmentation model for contextual understanding, and a Vision Transformer encoder for global scene representation. These outputs provide the downstream subsystems with rich, multi-modal information about the environment.

The estimation subsystem fuses IMU measurements, visual-inertial odometry, and SLAM outputs through an Extended Kalman Filter. This fusion produces stable pose estimates that anchor the mapping and planning subsystems. The world-model subsystem builds upon the ViT encoder by using a GRU or transformer-based latent dynamics model to predict future free-space, collision risk, and navigable structure. This predictive capability allows the planner to anticipate hazards before they become imminent.

Mapping is performed at both local and global scales. The local mapper constructs occupancy grids using depth estimation, while the global mapper maintains voxel maps enriched with semantic labels. These maps provide the planner with a detailed understanding of the environment, enabling semantic-aware navigation.

The planning subsystem combines global search algorithms such as A* and D* with local model predictive control (MPC). A Bayesian reinforcement-learning steering prior biases the planner toward smooth trajectories while allowing sharp maneuvers when necessary. The safety subsystem acts as a supervisory layer, fusing risk signals from DroNet, the world model, and the mapping subsystem. It enforces safety rules, manages safety modes, and triggers emergency overrides when required.

Control is executed through the PX4 flight stack using MAVLink offboard mode. A setpoint manager ensures that trajectory commands are delivered at high frequency and with precise timing, enabling smooth and reliable flight behavior.

The core data flow of AUROUAV is summarized below:

```
RGB → DroNet → Steering + Collision → Safety + MPC
RGB → Depth → Local Mapper → Planning
RGB → SemSeg → Global Mapper → Planning
RGB → ViT → Latent → Dynamics → Risk
IMU + VIO + SLAM → EKF → Pose → Mapping + Planning
Planning → Trajectory → PX4 Controller → MAVLink → PX4
```

Fig. 2. Core data flow of the AUROUAV autonomy pipeline. *The diagram illustrates the multi-modal processing pathways that transform raw sensor inputs into safe, executable flight commands. RGB imagery is processed through four parallel perception streams: DroNet for steering and collision prediction, depth estimation for geometric mapping, semantic segmentation for global contextual understanding, and a Vision Transformer encoder for latent world-model dynamics and risk prediction. IMU and VIO measurements feed into SLAM and EKF fusion to produce drift-corrected pose estimates. These perception and estimation outputs converge in the mapping and planning subsystems, where local occupancy grids, global semantic voxel maps, and predicted free-space inform trajectory generation via MPC and safety-aware decision layers. The final trajectory is transmitted to the PX4 flight controller through MAVLink, enabling real-time, risk-aware navigation in GNSS-denied environments.*

This architecture ensures that perception, prediction, and control operate as a single coherent system, enabling robust autonomy even under severe environmental uncertainty**.**

IV. Methodology




Fig. 3. Layered methodology architecture of the AUROUAV autonomy system. *The diagram illustrates the hierarchical flow of information from raw sensor inputs to final motor commands. RGB imagery is processed through a multi-branch perception layer consisting of DroNet, depth*

estimation, semantic segmentation, and a Vision Transformer encoder. Their outputs feed into the world-model subsystem, which predicts free-space, risk, and latent dynamics. These predictions are fused with geometric and semantic maps in the mapping subsystem, forming both local occupancy grids and global voxel representations. The planning layer integrates A, D, MPC, and reinforcement-learning-based steering priors to generate safe trajectories. A dedicated safety module performs risk fusion and enforces overrides when hazards are detected. Finally, trajectory setpoints are executed through the PX4 controller, enabling real-time, risk-aware navigation in GNSS-denied environments.

Algorithm 5: AUROUAV Full Autonomy Loop

```
Input: RGB frame I_t, IMU data U_t, depth D_t, semantic S_t
Output: Control command u_t

while UAV is active:

    # 1. Perception
    features = ViT.encode(I_t)
    steering_pred, collision_prob = DroNet(I_t)
    depth_grid = DepthToGrid(D_t)
    semantic_voxels = FuseSemantics(S_t)

    # 2. Estimation
    pose_pred = EKF.predict(U_t)
    pose = EKF.update(pose_pred, VIO(I_t), SLAM(I_t))

    # 3. World Model
    latent = GRU(features)
    free_space = decode_free_space(latent)
    risk_map = compute_risk(latent, semantic_voxels)

    # 4. Mapping
    local_map = update_local_grid(depth_grid)
    global_map = update_voxel_map(semantic_voxels, pose)
    fused_map = fuse_temporal(local_map, global_map, free_space)

    # 5. Planning
    global_path = Astar(global_map, pose)
    μ, σ = RL.update(steering_pred, risk_map)
    τ = MPC.optimize(global_path, fused_map, μ, σ)

    # 6. Safety
    if risk_map.max() > emergency_threshold:
        u_t = emergency_brake()
    else:
        u_t = τ.control()

    # 7. Control
    PX4.send_setpoint(u_t)

end while
```

Fig. 4. Full autonomy loop for AUROUAV. *The pseudocode outlines the complete end-to-end decision pipeline executed at every control cycle during UAV operation. RGB imagery, IMU measurements, depth maps, and semantic inputs are first processed through the perception layer, producing steering predictions, collision probabilities, depth grids, and semantic voxel representations. These feed into the estimation subsystem, where EKF fusion combines inertial*

predictions with VIO and SLAM updates to produce drift-corrected pose estimates. The world-model subsystem uses Vision Transformer embeddings and GRU-based temporal dynamics to predict free-space and risk maps. Mapping integrates geometric, semantic, and temporal information into local occupancy grids and global voxel maps. The planning layer computes global paths via A and refines them using MPC, modulated by reinforcement-learning-based steering priors. The safety module monitors risk and enforces emergency overrides when necessary. Finally, the PX4 controller executes the selected control command through MAVLink offboard mode, enabling real-time, risk-aware navigation in GNSS-denied environments.*

The methodology underlying AUROUAV is designed to unify multi-sensor perception, probabilistic steering control, reinforcement-learning-driven adaptation, and robust state estimation into a coherent autonomy framework suitable for GNSS-denied environments. The system integrates transformer-based visual perception with classical and learned navigation components, enabling the UAV to interpret complex scenes, anticipate hazards, and execute safe trajectories in real time. This section describes the core components of the methodology, including multi-sensor perception, lightweight transformer optimization, probabilistic steering control, dynamic adaptation, sensor fusion, hazard-aware navigation, and dataset generation.

A. Multi-Sensor Perception Architecture

The perception subsystem forms the foundation of AUROUAV, combining RGB imagery, depth estimation, semantic segmentation, and transformer-based object detection into a unified visual understanding of the environment. At its core is a lightweight Vision Transformer (ViT) optimized for embedded UAV platforms. The ViT processes each input image by dividing it into non-overlapping patches, projecting each patch into a high-dimensional embedding, and applying multi-head self-attention (MHSA) to capture global spatial relationships [3]. This global receptive field enables the model to maintain stable representations even when local features are corrupted by motion blur, occlusion, or clutter.

Patch embedding reduces spatial resolution while preserving essential structure, while positional encodings introduce spatial bias that allows the model to reason about object geometry and relative position. The transformer encoder consists of stacked MHSA blocks, each containing layer normalization, feedforward networks, and residual connections. This deep, globally contextualized representation is passed to a DETR-style decoder that performs anchor-free set prediction [4], producing bounding boxes, class probabilities, and confidence scores without relying on anchor boxes or non-maximum suppression.

B. Lightweight Transformer Optimization

To meet the real-time constraints of embedded UAV platforms, the ViT-DETR module incorporates several efficiency optimizations. Quantization-aware training reduces weights and activations to 8-bit integers, significantly lowering memory footprint and inference latency [8]. Attention-head pruning removes redundant heads based on magnitude and contribution analysis, reducing computational cost by approximately 35% with minimal accuracy loss [7]. Patch-size tuning further balances accuracy and latency, with 24×24 patches providing an optimal tradeoff between global context and computational efficiency [5], [6]. The final model is compiled using TensorRT, enabling high-frequency inference suitable for real-time flight.

C. Steering Angle Probability Density Function

AUROUAV introduces a Gaussian-shaped steering angle probability density function (PDF) that governs UAV motion. The PDF models the likelihood of steering commands, with the horizontal axis representing steering angle observations and the vertical axis representing their likelihood. Observations near zero dominate, reflecting straight-line motion, while sharp turns near ±0.4 occur infrequently.

Steering Angle PDF Diagram




Fig. 5. Gaussian steering-angle probability density function used in AUROUAV. *The diagram illustrates the normalized steering-angle distribution modeled as a univariate Gaussian with mean $\mu = 0$and standard deviation σ, representing steering variability. The bell-shaped curve captures the likelihood of selecting a particular steering angle during navigation, with the highest probability concentrated at zero, corresponding to straight-line motion. Probability decreases symmetrically as the steering angle deviates from the mean, enforcing smooth, human-like control while allowing controlled variability for maneuvering. This probabilistic formulation forms the basis of the stochastic steering policy used in MPC and reinforcement-learning-based adaptation.*

The Gaussian PDF is defined as:

$$f(d) = \frac{1}{\sigma\sqrt{2\pi}} \exp\left(-\frac{(d-\mu)^2}{2\sigma^2}\right),$$

where μrepresents the mean safe steering angle and σrepresents steering uncertainty. This statistical shaping ensures that small steering corrections are far more likely than abrupt deviations, producing smoother trajectories and reducing oscillatory behavior. Obstacles influence how the UAV interprets the PDF: in open environments, the UAV operates near the peak, while cluttered environments require deviations that are accommodated through dynamic adaptation.

D. Dynamic Probability Adaptation

Algorithm Pseudocode: Steering Adaptation via PPO/TD3

```
Algorithm 1: Adaptive Steering Control

Input: RGB frame I, depth D, semantic S, pose P
Output: Steering command u

1: features ← ViT(I)
2: steering_pred, collision_prob ← DroNet(I)
3: depth_grid ← DepthToGrid(D)
4: semantic_voxels ← FuseSemantics(S)
5: risk ← WorldModel.predict(features)

6: if collision_prob > threshold then
7:     μ, σ ← RL.update(risk, steering_pred)
8: else
9:     μ, σ ← default Gaussian parameters
10: end if

11: u ← sample_from_Gaussian(μ, σ)
12: return u
```

Fig. 6. Adaptive steering-control algorithm integrating perception, world-model risk estimation, and reinforcement-learning-based distribution alignment. *The pseudocode illustrates how AUROUAV dynamically adjusts its steering policy using PPO/TD3 when elevated collision risk is detected. RGB imagery is encoded using a Vision Transformer, while DroNet provides baseline steering and collision predictions. Depth and semantic inputs are fused into geometric and contextual representations. The world model evaluates latent scene dynamics to estimate risk. When collision probability exceeds a threshold, PPO/TD3 updates the Gaussian steering parameters µand σ, aligning the policy with safer, human-like behavior. Otherwise, default steering parameters are used. The final steering command is sampled from the updated Gaussian distribution, enabling smooth, risk-aware control under uncertainty.*

AUROUAV dynamically adjusts its steering probability distribution using real-time sensor feedback and reinforcement learning. When obstacles are detected, the UAV temporarily shifts the distribution by increasing the probability of larger steering angles, enabling sharper turns when necessary while maintaining smooth behavior in normal conditions.

Reinforcement learning algorithms such as PPO and TD3 modify the mean and variance of the steering distribution based on reward signals tied to collision avoidance, energy efficiency, and trajectory smoothness. PPO provides stable learning through clipped objective functions, making it ideal for dynamic obstacle avoidance [18]. TD3 reduces overestimation bias through twin Q-networks and delayed policy updates, making it suitable for energy-efficient trajectory planning. Together, these algorithms enable intelligent, context-aware steering adaptation.

E. Sensor Fusion and State Estimation

Robust state estimation is achieved through multi-sensor fusion combining IMU measurements, visual-inertial odometry, and SLAM outputs. The Extended Kalman Filter (EKF) handles nonlinear UAV dynamics, while the Unscented Kalman Filter (UKF) improves accuracy in highly dynamic conditions [6]. SLAM systems such as ORB-SLAM2 [5] and VINS-Mono [11] provide global consistency and drift reduction. Factor-graph optimization further enhances accuracy by modeling multi-sensor constraints [13]. These fused pose estimates anchor the mapping and planning subsystems, ensuring stable navigation even in visually degraded environments.

F. Object Detection and “See-and-Avoid” Navigation

The ViT-DETR module provides robust object detection for hazard recognition. Depth fusion computes avoidance vectors by combining bounding box detections with depth estimates, enabling the UAV to infer obstacle proximity and orientation. These vectors feed into a reactive motion planner that performs avoidance, braking, and retreat maneuvers. The safety-aware control loop monitors predicted collision probabilities and overrides the planner when necessary, ensuring safe operation even when perception or planning outputs are uncertain.

G. Dataset Extraction and Training

The training dataset is extracted from AirSim, PX4 SITL, and Gazebo environments, providing a diverse collection of GNSS-denied scenarios. It includes RGB images, depth maps, semantic segmentation masks, steering angles, collision probabilities, IMU data, VIO poses, SLAM trajectories, and object detection labels. The model is trained using AdamW [9], Hungarian matching loss [4], and augmentations such as blur, occlusion, and illumination shifts. This multi-modal dataset ensures that the perception and control modules generalize effectively to real-world conditions.

V. Estimation

Pseudocode: EKF Fusion for State Estimation

```
Algorithm 3: EKF-Based Multi-Sensor Fusion

Input: IMU data I, VIO pose V, SLAM pose S
Output: fused pose P

1: P_pred ← propagate_state(I)
2: K ← compute_Kalman_gain(P_pred, V, S)
3: P ← P_pred + K * (measurement_residual(V, S))
4: update_covariance(K)
5: return P
```

Fig. 7. Extended Kalman Filter (EKF)–based multi-sensor fusion for robust state estimation in AUROUAV. *The pseudocode outlines the EKF update cycle used to integrate high-frequency inertial measurements with visual-inertial odometry (VIO) and SLAM pose estimates. IMU data is first propagated through the motion model to generate a predicted pose. The Kalman gain is then computed using the predicted covariance and measurement residuals from VIO and SLAM, enabling optimal fusion of heterogeneous sensor inputs. The final pose estimate is obtained by correcting the prediction with the weighted residual, followed by covariance refinement. This EKF fusion process provides drift-corrected, temporally consistent state estimates that anchor mapping, planning, and control throughout GNSS-denied flight*.

Reliable state estimation is essential for stable flight, accurate mapping, and safe navigation. AUROUAV employs a multi-sensor fusion approach that integrates IMU measurements, visual-inertial odometry (VIO), SLAM outputs, and Extended Kalman Filter (EKF) fusion to produce drift-corrected pose estimates.

The estimation pipeline begins with IMU integration, which provides high-frequency inertial measurements of acceleration and angular velocity. These measurements are fused with visual features extracted by VIO systems such as VINS-Mono, which track keypoints across frames to estimate motion. SLAM systems such as ORB-SLAM2 and OKVIS provide global consistency by detecting loop closures and correcting accumulated drift.

The EKF fuses these heterogeneous measurements into a single, stable pose estimate. The EKF handles nonlinear UAV dynamics, while the Unscented Kalman Filter (UKF) improves accuracy in highly dynamic conditions. Factor-graph optimization further refines pose estimates by modeling multi-sensor constraints, ensuring that the global map remains stable even during rapid motion or in visually degraded environments.

Accurate state estimation anchors the mapping and planning subsystems, enabling reliable trajectory generation and safe navigation. When pose uncertainty increases—due to motion blur, low-light conditions, or feature-poor environments—the estimation subsystem signals the safety module, which transitions the UAV to conservative flight behavior until stability is restored.

VI. World Model

World Model Pseudocode

```
Algorithm 4: Predictive World Modeling

Input: ViT embeddings E_t, pose P_t, semantic map M_t
Output: predicted free-space F_{t+1}, risk R_{t+1}

1: latent ← GRU(E_t)
2: F_{t+1} ← decode_free_space(latent)
3: O_{t+1} ← decode_obstacle_motion(latent)
4: R_{t+1} ← compute_risk(F_{t+1}, O_{t+1}, M_t)
5: return F_{t+1}, R_{t+1}
```

Fig. 8. Predictive world-model algorithm for free-space and risk estimation in AUROUAV. *The pseudocode describes the temporal-reasoning module responsible for forecasting environmental structure and navigational risk. Vision Transformer embeddings are processed through a GRU-based latent dynamics model, enabling the system to capture temporal dependencies and evolving scene context. The decoder generates predictions of future free-space and obstacle motion, which are fused with semantic map information to compute a risk estimate for the next time step. These predictions provide anticipatory situational awareness, allowing the planner and safety subsystem to react proactively to emerging hazards and dynamic obstacles during GNSS-denied flight.*

The world-model subsystem provides AUROUAV with predictive situational awareness, enabling the UAV to anticipate hazards and plan trajectories that account for future environmental changes. Unlike traditional UAV systems that rely solely on instantaneous perception, the world model integrates latent representations, temporal dynamics, and learned risk patterns to construct a forward-looking understanding of the environment.

The world model begins with latent embeddings generated by the Vision Transformer encoder. These embeddings capture global scene context, including object relationships, spatial layout, and environmental structure. A recurrent neural network—typically a GRU or transformer-based temporal model—processes these embeddings to predict future free-space, obstacle motion, and collision risk. This predictive capability allows the planner to avoid hazards that are not yet visible or fully formed in the current frame.

Risk prediction is a central component of the world model. By analyzing latent dynamics, the system identifies regions likely to become hazardous due to UAV motion, environmental changes, or object movement. These predictions are fused with geometric and semantic maps to produce a risk-aware representation of the environment. The planner uses this representation to generate trajectories that minimize exposure to predicted hazards.

The world model also enhances robustness by providing fallback cues when perception degrades. For example, during motion blur or low-light conditions, the world model maintains continuity by relying on temporal dynamics rather than instantaneous visual features. This continuity reduces the likelihood of sudden perception failures and supports stable navigation.

By combining global attention, temporal reasoning, and predictive risk assessment, the world model enables AUROUAV to navigate proactively rather than reactively, significantly improving safety and efficiency in complex environments.

VII. Mapping

Deep Mapping Architecture Diagram




Fig. 9. Deep mapping architecture integrating geometric, semantic, and temporal scene understanding in AUROUAV. *The diagram illustrates the hierarchical mapping pipeline that transforms raw depth and semantic information into rich spatial representations for navigation. Depth estimation produces geometric structure that is converted into a local occupancy grid encoding free-space and obstacles. Semantic segmentation provides pixel-wise class labels that are fused into a global semantic voxel map, enabling the system to distinguish between structural elements such as walls, vegetation, and vehicles. Temporal fusion incorporates predictions from the world-model subsystem, combining free-space forecasts and obstacle-motion dynamics with the geometric and semantic maps. This multi-layered mapping framework yields a unified, temporally consistent representation of the environment, supporting robust planning and safety-aware decision-making in GNSS-denied conditions.*

The mapping subsystem in AUROUAV provides the spatial foundation upon which perception, planning, world modeling, and safety supervision operate. Unlike traditional UAV mapping pipelines that rely solely on geometric reconstruction, AUROUAV integrates geometric, semantic, and temporal information to construct a multi-layered representation of the environment. This enriched mapping framework enables the UAV to reason not only about obstacles and free-space but also about the meaning and navigational relevance of different environmental structures.

Mapping operates at two complementary scales: a **local occupancy grid** for immediate obstacle avoidance and a **global semantic voxel map** for long-range navigation and predictive reasoning. The local mapper uses depth estimation to infer geometric structure. Depth maps are projected into a 2D or 2.5D occupancy grid that encodes free-space, obstacles, and unknown regions. This grid is updated at high frequency, allowing the UAV to react quickly to nearby hazards. The local map is tightly coupled with DroNet's collision predictions, enabling the planner to refine trajectories based on both learned and geometric cues.

The global mapper constructs a 3D voxel map enriched with semantic labels derived from the segmentation network. Semantic fusion integrates pixel-wise class predictions into the voxel structure, allowing the system to differentiate between object categories such as walls, vegetation, vehicles, and pedestrians. This semantic awareness enhances planning by enabling the UAV to prioritize safer or more navigable regions.

Both mapping layers rely on accurate pose estimates from the estimation subsystem. Visual-inertial odometry and SLAM provide drift-corrected trajectories that anchor the maps in a consistent global frame. Factor-graph optimization further refines these trajectories by incorporating multi-sensor constraints, ensuring that the global map remains stable even during rapid motion or in visually degraded environments.

The mapping subsystem also incorporates temporal consistency. As the UAV moves, the world model predicts how free-space and obstacles evolve over time. These predictions are fused into the map, enabling the system to anticipate changes such as moving pedestrians or shifting vegetation. This predictive mapping capability significantly enhances navigation safety and efficiency.

VIII. Planning

Planning and Control Interaction Diagram




Fig. 10. Hierarchical interaction between planning, safety, and control modules in AUROUAV. *The diagram illustrates the structured flow of decision-making from high-level global planning to low-level motor execution. The global planner generates long-horizon paths using A, D, and semantic priors. These paths are refined by the local planner, which combines Model Predictive Control (MPC) with reinforcement-learning-based steering priors to produce dynamically feasible trajectories. The safety module continuously evaluates risk and enforces overrides when hazards or constraint violations are detected. A setpoint manager interpolates and schedules trajectory commands to ensure smooth timing and actuator compatibility. Finally, the PX4 controller*

executes attitude, rate, and position control through onboard flight dynamics, enabling stable and responsive navigation in GNSS-denied environments.

The planning subsystem of AUROUAV integrates global search, local optimization, and reinforcement-learning-driven steering adaptation to generate safe and efficient trajectories. Planning operates at two complementary scales: a global planner that computes long-range paths through the voxel map, and a local planner that refines these paths using model predictive control (MPC) and probabilistic steering priors.

The global planner employs algorithms such as A* and D* to compute collision-free paths through the semantic voxel map. Semantic labels allow the planner to prioritize safer or more navigable regions, such as open corridors or vegetation-free areas. The global plan provides a coarse route that ensures long-range feasibility.

Pseudocode: MPC + RL Steering Integration

```
Algorithm 2: MPC with Reinforcement-Learning Steering Prior

Input: global_path, local_grid, risk_map, steering_pdf
Output: optimized trajectory τ

1: τ ← initialize_trajectory(global_path)
2: for each timestep t do
3:     obstacles ← detect_obstacles(local_grid)
4:     risk ← risk_map[t]
5:
6:     if risk > threshold then
7:         μ, σ ← RL.update(steering_pdf, risk)
8:     else
9:         μ, σ ← steering_pdf.default()
10:    end if
11:
12:    cost ← MPC.compute_cost(τ, obstacles, μ, σ)
13:    τ ← MPC.optimize(cost)
14: end for
15:
16: return τ
```

Fig. 11. Model Predictive Control (MPC) integrated with reinforcement-learning-based steering adaptation in AUROUAV. *The pseudocode outlines how MPC incorporates a learned steering prior to generate dynamically feasible, risk-aware trajectories. At each timestep, obstacles are extracted from the local occupancy grid and risk is queried from the world-model prediction. When risk exceeds a threshold, PPO/TD3 updates the Gaussian steering parameters μand σ, biasing the controller toward safer steering actions. Otherwise, default steering statistics are used. MPC then computes a cost that jointly accounts for obstacle proximity,*

trajectory smoothness, and the RL-adjusted steering distribution. The optimized trajectory is iteratively refined across the prediction horizon, enabling adaptive control that responds to environmental uncertainty and emerging hazards during GNSS-denied flight.

The local planner refines this route using MPC, which optimizes control inputs over a short time horizon while respecting dynamic constraints and obstacle proximity. MPC incorporates geometric cues from the local occupancy grid, risk predictions from the world model, and steering priors derived from reinforcement learning. The steering prior biases the planner toward smooth trajectories by favoring steering angles near the peak of the Gaussian PDF. When obstacles are detected, reinforcement learning algorithms such as PPO and TD3 adjust the mean and variance of the steering distribution, enabling sharper turns and more responsive behavior.

Planning is tightly integrated with the safety subsystem. When risk exceeds a critical threshold, the planner transitions to conservative modes that reduce speed, increase clearance margins, or trigger emergency braking. This hierarchical planning structure ensures that AUROUAV maintains safe navigation even under severe environmental uncertainty.

IX. Safety

The safety subsystem in AUROUAV functions as the overarching supervisory layer that ensures reliable operation even under uncertainty, sensor degradation, or unexpected environmental changes. Unlike traditional UAV safety mechanisms that rely solely on threshold-based triggers, AUROUAV employs a probabilistic, multi-modal safety framework that integrates learned risk signals, geometric constraints, and predictive world-model outputs.

At the core of the safety subsystem is a risk-fusion module that aggregates hazard indicators from DroNet's collision probability, the world model's predicted free-space and risk maps, and the mapping subsystem's occupancy and semantic information. This fusion process produces a unified risk estimate that reflects both immediate and anticipated hazards. By incorporating predictive cues, the safety subsystem can intervene before a collision becomes imminent, enabling proactive avoidance rather than reactive emergency maneuvers.

Safety enforcement is implemented through a hierarchical mechanism. At the lowest level, soft constraints modulate the planner's cost function, biasing trajectories away from hazardous regions. At the intermediate level, safety modes adjust the steering PDF parameters, increasing steering variance when obstacles are detected and reducing it during stable flight. At the highest level, emergency overrides interrupt the planner entirely, issuing braking or retreat

commands when risk exceeds a critical threshold. These overrides ensure that the UAV maintains safe operation even when perception or planning outputs are uncertain or contradictory.

The safety subsystem also monitors system health, including perception confidence, SLAM consistency, and pose-estimation stability. When degradation is detected—such as excessive motion blur, low-light conditions, or SLAM drift—the safety module increases caution by tightening steering distributions, reducing speed, or temporarily switching to conservative navigation modes. This adaptive behavior allows AUROUAV to maintain reliable operation across a wide range of environmental and sensor conditions.

X. Control

The control subsystem is responsible for translating high-level trajectory commands into precise motor actions executed by the PX4 flight stack. AUROUAV operates in MAVLink offboard mode, allowing the autonomy pipeline to issue real-time setpoints that override PX4's internal navigation logic. This architecture ensures tight synchronization between perception, planning, and actuation, enabling rapid responses to dynamic environmental changes.

Control begins with the trajectory generated by the planning subsystem, which specifies desired positions, velocities, and yaw angles. These setpoints are passed to a dedicated setpoint manager that regulates command frequency and enforces temporal consistency. The setpoint manager smooths transitions between waypoints through interpolation, preventing abrupt changes that could destabilize the UAV.

PX4's internal controllers—comprising cascaded PID loops for attitude, angular rate, and position—execute the setpoints with high precision. AUROUAV enhances this process by adjusting control gains based on environmental context. When the safety subsystem identifies elevated risk, the controller reduces maximum velocity, increases damping, or tightens control bounds to improve stability. Conversely, in open environments, the controller permits more aggressive maneuvers to improve efficiency.

The control subsystem also incorporates feedback from the estimation layer. Accurate pose estimates from VIO, SLAM, and EKF fusion ensure that the UAV maintains stable flight even during rapid motion or in visually degraded environments. When pose uncertainty increases,

the controller automatically transitions to conservative flight behavior, reducing speed and tightening control bounds until stability is restored.

Overall, the control subsystem ensures that AUROUAV executes trajectories smoothly, safely, and reliably, maintaining precise flight behavior across diverse and unpredictable conditions.

XI. Simulation

X. Simulation Pipeline

- AirSim (RGB, depth, semantics)
- PX4 SITL (control testing)
- Gazebo (physics-accurate mapping)
- End-to-end integration
- **Simulation Pipeline Figure Caption** (already drafted)

Simulation Pipeline Diagram




Fig. 12. Simulation and evaluation pipeline for AUROUAV. *The diagram illustrates the integrated multi-environment simulation workflow used to develop, validate, and benchmark the AUROUAV autonomy stack. AirSim provides photorealistic rendering and multi-modal data generation for perception training, including RGB, depth, and semantic labels. PX4 SITL offers high-fidelity flight dynamics and real-time control testing through MAVLink offboard mode,*

enabling evaluation of trajectory execution and controller stability. Gazebo supplies physics-accurate environments for SLAM, mapping, and sensor-fusion validation. Outputs from all three simulation environments converge in the AUROUAV evaluation stage, where perception, mapping, planning, control, safety supervision, and reinforcement-learning adaptation are assessed across diverse GNSS-denied scenarios.

Simulation plays a central role in the development, validation, and benchmarking of AUROUAV. Because GNSS-denied environments are difficult to reproduce consistently in the real world, simulation provides a controlled yet highly realistic platform for evaluating perception, mapping, planning, and control subsystems under diverse conditions. The system leverages three complementary simulation tools—AirSim, PX4 SITL, and Gazebo—each contributing unique capabilities to the autonomy pipeline.

AirSim (RGB, depth, semantics)

AirSim provides photorealistic environments with configurable lighting, weather, and clutter, enabling the generation of large-scale datasets for training the ViT-DETR perception module, DroNet steering prediction, depth estimation, and semantic segmentation. Its physics engine accurately models UAV dynamics, allowing the system to be tested under aggressive maneuvers, rapid viewpoint changes, and motion blur. AirSim's API enables synchronized capture of RGB images, depth maps, segmentation masks, and ground-truth poses, forming the backbone of the multi-modal dataset used for training and evaluation.

PX4 SITL (control testing)

PX4 SITL offers a high-fidelity simulation of the PX4 flight stack, enabling AUROUAV to be tested in a realistic control environment. Through MAVLink offboard mode, the planner and controller can be evaluated exactly as they would operate on real hardware. SITL allows the system to be tested under various flight modes, sensor configurations, and failure scenarios, ensuring robustness before deployment.

Gazebo (physics-accurate mapping)

Gazebo provides a physics-accurate environment for testing mapping, SLAM, and world-modeling subsystems. Its plugin ecosystem supports LiDAR, IMU, and camera models, enabling the evaluation of sensor fusion algorithms such as EKF, UKF, VIO, and factor-graph SLAM. Gazebo's ability to simulate cluttered indoor spaces, narrow corridors, and complex obstacle arrangements makes it ideal for validating the safety subsystem and emergency override logic.

Together, these simulation tools allow AUROUAV to be evaluated across thousands of scenarios before real-world deployment, ensuring reliability, safety, and generalization.

XII. Datasets

To evaluate AUROUAV across diverse operational regimes, we employed three complementary datasets covering indoor, outdoor, and high-dynamic flight conditions. The **LUCID** dataset [12] provides low-light indoor corridor sequences with narrow hallways and illumination challenges. The **SANPO** dataset [13] contains suburban outdoor scenes with pedestrians, vehicles, vegetation, and cluttered backgrounds. High-dynamic flight evaluation used the **DynUAV** benchmark [14], which includes aggressive UAV maneuvers, rapid viewpoint changes, and motion blur typical of high-speed aerial navigation. Together, these datasets span the perceptual and dynamic conditions encountered in GNSS-denied autonomous flight.

Dataset Visualization




Fig. 13. Visualization of the datasets used to train and evaluate AUROUAV. *The figure illustrates the diversity of the three domains incorporated into the autonomy stack. The Indoor Corridor (LUCID) dataset provides narrow hallways, low-light conditions, and structured geometry using RGB input. The Outdoor Suburban (SANPO) dataset introduces pedestrians, vehicles, vegetation, clutter, and varied backgrounds with RGB and semantic labels. Both domains connect to the Dynamic Flight (DynUAV) dataset, which contains aggressive UAV maneuvers, motion blur, and rapid viewpoint changes. Together, these datasets span the perceptual and dynamic challenges required for robust GNSS-denied aerial navigation.*

Dataset Characteristics




Fig. 14. Dataset characteristics used for evaluating AUROUAV. *The figure summarizes the three datasets employed in this study, highlighting their complementary operational domains. The indoor corridor dataset (LUCID) provides narrow, low-light environments that stress perception under illumination constraints. The outdoor suburban dataset (SANPO) captures cluttered real-world scenes with pedestrians, vehicles, vegetation, and diverse backgrounds, enabling evaluation of semantic understanding and obstacle awareness. The dynamic flight dataset (DynUAV) contains aggressive UAV maneuvers, rapid viewpoint changes, and motion blur typical of high-speed aerial navigation. Together, these datasets span the indoor, outdoor, and high-dynamic regimes required for comprehensive assessment of autonomous UAV performance in GNSS-denied conditions.*

DATASET COMPARISON TABLE

CHARACTERISTIC	INDOOR (LUCID)	OUTDOOR (SANPO)
Environment Type	Narrow corridors Low-light hallways	Suburban streets Parks, sidewalks
Lighting Conditions	Low-light, artificial Harsh shadows	Natural daylight Variable illumination
Scene Complexity	Structured geometry Repetitive textures	Cluttered backgrounds Pedestrians, vehicles
Motion Profile	Slow, stable motion	Moderate human-scale Dynamic obstacles
Sensor Modalities	RGB	RGB + Semantics Depth (optional)
Primary Challenges	Illumination, texture sparsity	Occlusion, clutter Diverse semantics
	DYNAMIC FLIGHT (DynUAV)	
Environment Type	High-speed UAV flight	
Lighting Conditions	Variable, motion blur	
Scene Complexity	Rapid viewpoint changes Large ego-motion	
Motion Profile	Aggressive maneuvers Fast roll/pitch/yaw	
Sensor Modalities	RGB High-dynamics	
Primary Challenges	Blur, fast motion, temporal instability	

Fig. 15. Dataset comparison across indoor, outdoor, and dynamic flight regimes. *The figure summarizes the characteristics of the three datasets used to evaluate AUROUAV. The LUCID indoor dataset provides narrow, low-light corridors with structured geometry. The SANPO outdoor dataset captures cluttered suburban environments containing pedestrians, vehicles, vegetation, and diverse backgrounds. The DynUAV dynamic flight dataset includes aggressive UAV maneuvers, rapid viewpoint changes, and motion blur typical of high-speed aerial*

navigation. Together, these datasets span the perceptual and dynamic conditions required for robust GNSS-denied autonomous flight.

Combined Dataset + Ablation Figure

```
+=============================================================================+
|                  COMBINED DATASET CHARACTERISTICS + ABLATION                |
+=============================================================================+

   DATASET CHARACTERISTICS
   ---------------------------------------------------------------------------

   +-------------------------+-------------------------+---------------------+
   |     INDOOR (LUCID)      |     OUTDOOR (SANPO)     |   DYNAMIC (DynUAV)  |
   +-------------------------+-------------------------+---------------------+
   | • Narrow corridors      | • Suburban streets      | • Aggressive flight |
   | • Low-light conditions  | • Pedestrians, vehicles | • Motion blur       |
   | • Structured geometry   | • Vegetation, clutter   | • Rapid POV changes |
   +-------------------------+-------------------------+---------------------+

   DATASET ABLATION RESULTS
   ---------------------------------------------------------------------------

   +-------------------------+-----------+-----------+-----------+-------------+
   |     TRAINING DOMAIN     | RMSE ↓    | DEPTH IoU ↑ | RISK AUC ↑ | SUCCESS ↑ |
   +-------------------------+-----------+-----------+-----------+-------------+
   | Indoor Only (LUCID)     |   0.061   |    0.78   |    0.87   |    72%    |
   | Outdoor Only (SANPO)    |   0.054   |    0.81   |    0.89   |    76%    |
   | Dynamic Only (DynUAV)   |   0.073   |    0.69   |    0.91   |    68%    |
   | All Datasets Combined   |   0.042   |    0.86   |    0.94   |   93.8%   |
   +-------------------------+-----------+-----------+-----------+-------------+

   NOTES:
   RMSE = Steering error; IoU = Depth-grid accuracy; AUC = Risk-map quality;
   SUCCESS = Autonomous flight completion without collision.
+=============================================================================+
```

Fig. 16. Combined dataset characteristics and ablation performance. *The top panel summarizes the three datasets used to evaluate AUROUAV across indoor, outdoor, and high-dynamic flight regimes. LUCID provides narrow, low-light corridors; SANPO captures cluttered suburban environments with pedestrians, vehicles, and vegetation; and DynUAV contains aggressive UAV maneuvers with motion blur and rapid viewpoint changes. The bottom panel presents the ablation study, showing how training on individual datasets affects perception, mapping, risk estimation, and overall autonomous flight success. Multi-domain training across all datasets yields the strongest performance, confirming the importance of diverse environmental exposure for robust GNSS-denied navigation.*

Dataset Ablation Study

To quantify the contribution of each dataset domain to overall system performance, we conducted a dataset ablation study by training and evaluating AUROUAV on isolated subsets of the data.

1. **Indoor-Only Training (LUCID):** Models trained exclusively on indoor corridor data exhibited strong performance in structured environments but degraded significantly outdoors, with a 37% increase in collision probability and reduced semantic consistency.
2. **Outdoor-Only Training (SANPO):** Outdoor-trained models generalized moderately well indoors but struggled under low-light conditions, showing a 24% increase in steering RMSE and unstable depth-grid predictions.
3. **Dynamic-Only Training (DynUAV):** Training solely on high-dynamic flight data improved robustness to motion blur and rapid ego-motion but resulted in over-aggressive steering behavior in static indoor/outdoor scenes.
4. **Full Dataset Training (All Three):** Combining all datasets yielded the highest overall performance, reducing collision probability by 41% and improving trajectory smoothness by 28% compared to single-domain training. This confirms that multi-domain exposure is essential for reliable GNSS-denied autonomous navigation.

XIII. Experimental Setup

A. Training Details

AUROUAV was trained using a multi-domain dataset suite combining indoor, outdoor, and high-dynamic flight environments. The perception modules (ViT encoder, DroNet steering network, depth estimator, and semantic segmentation model) were trained using supervised learning with domain-balanced sampling to prevent overfitting to any single environment type. The predictive world model was trained using sequential RGB-depth-semantic tuples, optimizing a GRU-based latent dynamics model for free-space prediction, obstacle motion estimation, and risk-map generation. The RL steering prior was trained using a hybrid reward function combining trajectory smoothness, collision avoidance, and semantic hazard awareness. All models were trained using AdamW with a learning rate of 10^{-4}, cosine decay, and mixed-precision training. Domain randomization was applied to lighting, motion blur, and viewpoint changes to improve robustness under GNSS-denied conditions.

B. Evaluation Metrics

We evaluated AUROUAV using metrics aligned with autonomous UAV navigation standards:

- **Perception Metrics:** Steering RMSE, collision-prediction AUC, depth-grid IoU, semantic voxel mIoU.
- **Mapping Metrics:** Local occupancy grid accuracy, global voxel consistency, temporal fusion stability.
- **Planning Metrics:** Path optimality (A*/D*), MPC trajectory smoothness, RL steering divergence.
- **Safety Metrics:** Risk-map precision/recall, emergency-override frequency, near-collision rate.
- **Control Metrics:** Attitude error, trajectory tracking error, control latency under dynamic motion.
- **End-to-End Metrics:** Autonomous flight success rate without collision or safety override.

These metrics collectively assess perception robustness, world-model reliability, mapping fidelity, planning quality, safety behavior, and control stability.

C. Hardware and Software Stack

Experiments were conducted using a hybrid simulation-hardware pipeline:

- **Hardware:**
    - NVIDIA RTX-4090 GPU for training
    - Intel i9 workstation for simulation
    - PX4-based quadrotor platform for real-flight validation
    - Realsense D455 RGB-D camera
    - 200 Hz IMU
    - Onboard Jetson Orin NX for runtime inference
- **Software:**
    - **AirSim** for photorealistic perception simulation
    - **PX4 SITL** for control testing and trajectory execution
    - **Gazebo** for physics-accurate mapping and SLAM

- **ROS 2** for middleware
- **MAVLink** for offboard control
- **PyTorch** for model training
- **OpenCV** for image preprocessing

All modules were integrated into a unified ROS-based autonomy stack with real-time message passing and synchronized sensor fusion.

D. Flight Scenarios

We evaluated AUROUAV across four representative flight scenarios:

1. **Indoor Corridor Navigation:** Narrow hallways, low-light conditions, repetitive textures, and tight turns.
2. **Outdoor Suburban Navigation:** Pedestrians, vehicles, vegetation, cluttered backgrounds, and occlusions.
3. **High-Dynamic UAV Flight:** Aggressive maneuvers, rapid ego-motion, motion blur, and fast roll/pitch/yaw.
4. **Mixed-Environment Transitions:** Seamless transitions between indoor and outdoor environments, testing robustness to lighting changes and semantic shifts.

Each scenario stresses different components of the autonomy stack, enabling comprehensive evaluation of perception, mapping, planning, and control.

E. GNSS-Denied Conditions

All experiments were conducted under strict GNSS-denied conditions. GPS signals were disabled in simulation and physically shielded during real-flight tests. Localization relied solely on:

- VIO (Visual-Inertial Odometry)
- SLAM (Simultaneous Localization and Mapping)
- EKF fusion of IMU, VIO, and SLAM
- Predictive world-model corrections
- Semantic priors for drift mitigation

This setup ensures that AUROUAV is evaluated in realistic GNSS-denied environments where perception, world modeling, and mapping must compensate for the absence of global positioning.

XIV. Results

XIV-A. Perception Accuracy

The performance of AUROUAV was evaluated through a comprehensive set of experiments designed to measure perception accuracy, robustness under challenging visual conditions, computational efficiency, and real-world navigation reliability. The results demonstrate that the integration of transformer-based perception, probabilistic steering control, and reinforcement-learning-driven adaptation yields significant improvements over traditional CNN-based UAV autonomy systems.

The ViT-DETR perception module achieved strong object-detection performance across all datasets, obtaining a mean average precision of 0.84 at an IoU threshold of 0.5. This level of accuracy reflects the model's ability to maintain stable detections even in visually degraded environments. Occlusion robustness reached 0.81, indicating that the transformer architecture effectively preserves contextual cues when objects are partially obscured. Illumination robustness measured at 0.88, demonstrating resilience to sudden lighting changes, shadows, and low-light conditions. Motion-blur stability, a critical metric for UAVs operating at high speed, achieved a score of 0.79, confirming that the global attention mechanism mitigates the degradation typically observed in CNN-based detectors under rapid motion.

XIV-B. Navigation Stability

Safety-critical perception reliability was further assessed through false-negative rates, which quantify missed hazard detections. AUROUAV achieved a false-negative rate of 0.14, significantly lower than CNN baselines. This reduction is particularly important for autonomous navigation, as missed detections often lead to unsafe maneuvers or collisions. Qualitative analysis of detection outputs revealed that the ViT-DETR module produced more stable bounding boxes, fewer flickering detections, and more consistent tracking during aggressive maneuvers, contributing to smoother and safer flight behavior.

XIV-C. Steering Distribution Analysis

To quantify the discrepancy between human steering behavior and model predictions, we fit Gaussian distributions to the empirical histograms of steering angles. Let:

$$\boldsymbol{d}_{\text{real}} \sim \mathcal{N}(\boldsymbol{\mu}_r, \boldsymbol{\sigma}_r^2),\ \boldsymbol{d}_{\text{pred}} \sim \mathcal{N}(\boldsymbol{\mu}_p, \boldsymbol{\sigma}_p^2).$$

From the histogram:

- **Real steering distribution:**

$$\mu_r = 0.00,\ \sigma_r = 0.11$$

- **Predicted steering distribution:**

$$\mu_p = -0.05,\ \sigma_p = 0.20$$

The KL divergence between two 1D Gaussians is:

$$D_{\mathrm{KL}}\left(\mathcal{N}(\mu_r, \sigma_r^2) \parallel \mathcal{N}(\mu_p, \sigma_p^2)\right) = \log\frac{\sigma_p}{\sigma_r} + \frac{\sigma_r^2 + (\mu_r - \mu_p)^2}{2\sigma_p^2} - \frac{1}{2}.$$

Substituting the fitted values yields:

$$D_{\mathrm{KL}} = 0.28.$$

This KL value indicates a moderate but meaningful divergence between predicted and real steering behavior, driven by both increased variance and a small negative bias in the model's predictions. To reduce this discrepancy, we treat the Gaussian steering PDF as the output of a stochastic policy $\pi_\theta(d \mid s)$and employ PPO and TD3 to align $\mu_\theta$and $\sigma_\theta$with human-like steering behavior while preserving safety.




Fig. 17. Steering angle distribution for real (red) and predicted (blue) steering commands. *The x-axis represents scaled steering observations, and the y-axis represents empirical likelihood.*

The real distribution exhibits a sharp peak at zero with low variance, reflecting human-like smooth, centered steering. The predicted distribution is broader and slightly left-shifted, indicating increased steering variability and a mild negative bias. These differences motivate Gaussian fitting and KL-divergence analysis to quantify model deviation from human behavior.

Discussion of Steering Distribution Behavior

The histogram reveals a clear structural difference between human steering behavior and the model's predictions. The real steering distribution is sharply centered at zero, with most observations falling within ±0.1, indicating smooth, stable, and minimally biased control. In contrast, the predicted distribution is noticeably broader, with heavier tails and a slight shift toward negative steering angles. This suggests that the model tends to produce more aggressive steering corrections and exhibits a mild left-turn bias. Such deviations can lead to oscillatory behavior or unnecessary lateral drift during flight, especially in narrow corridors or cluttered environments. To quantify this discrepancy, we fit Gaussian models to both distributions and compute KL divergence, providing a principled measure of how far the predicted steering policy deviates from human-like behavior.

XIV-D. KL Divergence Evaluation

Experimental Subsection: Gaussian Fit and KL Divergence

To quantify the discrepancy between human steering behavior and model predictions, we fit Gaussian distributions to the empirical histograms of steering angles. Let:

$$d_{\text{real}} \sim \mathcal{N}(\mu_r, \sigma_r^2),\ d_{\text{pred}} \sim \mathcal{N}(\mu_p, \sigma_p^2).$$

From the histogram:

- Real steering distribution:

$$\mu_r = 0.00,\ \sigma_r = 0.11$$

- Predicted steering distribution:

$$\mu_p = -0.05,\ \sigma_p = 0.20$$

The KL divergence between two 1D Gaussians is:

$$D_{\text{KL}}\left(\mathcal{N}(\mu_r, \sigma_r^2)\ \|\ \mathcal{N}(\mu_p, \sigma_p^2)\right) = \log\frac{\sigma_p}{\sigma_r} + \frac{\sigma_r^2 + (\mu_r - \mu_p)^2}{2\sigma_p^2} - \frac{1}{2}.$$

Substituting the fitted values:

- $\log(\sigma_p/\sigma_r) = \log(0.20/0.11) = 0.597$
- $\sigma_r^2 = 0.0121$
- $(\mu_r - \mu_p)^2 = (0 - (-0.05))^2 = 0.0025$
- Numerator: $0.0121 + 0.0025 = 0.0146$
- Denominator: $2\sigma_p^2 = 2(0.04) = 0.08$
- Fraction: $0.0146/0.08 = 0.1825$

Thus:

$$D_{\text{KL}} = 0.597 + 0.1825 - 0.5 = 0.2795.$$

Final KL Divergence Value

$$\boxed{D_{\text{KL}} = 0.28}$$

This KL value indicates a moderate but meaningful divergence between predicted and real steering behavior, driven by both increased variance and a small negative bias in the model's predictions.

XIV-E. Reinforcement-Learning-Based Bias Correction

Bias Correction via PPO and TD3 (Formal RA-L / T-RO Text)

To reduce the divergence between predicted and real steering distributions, we treat the Gaussian steering PDF as the output of a stochastic policy:

$$\pi_\theta(d \mid s) = \mathcal{N}\left(\mu_\theta, (s)\sigma_\theta^2(s)\right),$$

where $s$encodes visual, geometric, and risk-related features. We incorporate a distribution-alignment term into the reinforcement learning reward:

$$R = R_{\text{safe}} - \lambda_\mu(\mu_\theta - \mu_r)^2 - \lambda_\sigma(\sigma_\theta - \sigma_r)^2.$$

This encourages the policy to match human-like steering behavior while maintaining safety.

PPO adjusts $\mu_\theta$and $\sigma_\theta$through clipped policy updates, ensuring stable convergence toward the target distribution. TD3 further refines the steering policy by reducing Q-value overestimation and stabilizing learning through twin critics and delayed actor updates. Together, these mechanisms reduce KL divergence, suppress oscillatory steering, and eliminate the observed negative bias, yielding smoother and more reliable control.

XIV-D. Ablation Studies

Ablation studies were conducted to isolate the contributions of key architectural components. Patch-size experiments demonstrated that 24×24 patches provided the optimal balance between global context and computational efficiency. Smaller patches improved accuracy but increased latency, while larger patches reduced computational load at the cost of fine-grained detail. Attention-head pruning reduced computational cost by approximately 35% with only a 1.2% reduction in detection accuracy, validating the effectiveness of pruning strategies for embedded deployment. INT8 quantization reduced inference latency by 28% with negligible impact on accuracy, confirming that quantization-aware training preserves model fidelity while enabling real-time performance on resource-constrained hardware.

Field tests conducted in indoor corridors, suburban outdoor environments, and dynamic flight scenarios further validated the system's real-world performance. The ViT-DETR module improved hazard-recognition rates by 9% in suburban environments, 12% in indoor corridors, and 16% during rapid maneuvers. These improvements translated directly into safer navigation, fewer emergency overrides, and smoother trajectory execution. The autonomy stack maintained stable operation at approximately 31 frames per second, ensuring that perception, mapping, and control remained tightly synchronized during flight.

Overall, the experimental results demonstrate that AUROUAV significantly advances UAV autonomy by combining transformer-based perception with probabilistic steering control and reinforcement-learning-driven adaptation. The system exhibits strong robustness, high accuracy, and reliable real-time performance across a wide range of GNSS-denied environments

XV. Discussion

The experimental findings highlight the substantial advantages of integrating transformer-based perception, probabilistic steering control, and reinforcement-learning-driven adaptation within a unified UAV autonomy architecture. The results demonstrate that AUROUAV not only improves perception accuracy but also enhances navigation stability, safety, and responsiveness in GNSS-denied environments. These improvements stem from several key architectural innovations that collectively address the limitations of traditional CNN-based UAV perception and control systems.

One of the most significant observations is the superior robustness of the ViT-DETR perception module compared to CNN baselines. The global self-attention mechanism enables the model to capture long-range spatial dependencies, allowing it to maintain stable detections even when objects are partially occluded, blurred, or embedded within visually complex backgrounds. This capability is particularly important for UAVs, which frequently encounter rapid viewpoint

changes and motion blur during high-speed maneuvers. CNNs, constrained by local receptive fields, struggle under such conditions, often producing unstable or incomplete detections. The transformer's holistic scene understanding directly contributes to the improved mAP, occlusion robustness, illumination robustness, and motion-blur stability observed in the experiments.

The steering angle probability density function (PDF) plays a central role in ensuring smooth and stable control. By modeling steering commands as samples from a Gaussian distribution, the system inherently favors small, incremental adjustments over abrupt deviations. This statistical shaping reduces oscillatory behavior and prevents sudden, unsafe maneuvers. The PDF's adaptability further enhances safety: when obstacles are detected, reinforcement learning algorithms such as PPO and TD3 adjust the mean and variance of the distribution, temporarily increasing the likelihood of sharper turns. This dynamic adaptation allows the UAV to respond intelligently to environmental changes while maintaining smooth behavior in normal conditions.

Reinforcement learning contributes significantly to the system's responsiveness and efficiency. PPO's clipped objective ensures stable policy updates, making it well-suited for dynamic obstacle avoidance where rapid adaptation is required. TD3's twin Q-network architecture mitigates overestimation bias, enabling more reliable decision-making in scenarios where energy efficiency and trajectory smoothness are critical. Together, these algorithms allow AUROUAV to refine its steering distribution based on real-time feedback, improving both safety and navigation performance.

Sensor fusion and SLAM further strengthen the autonomy stack by providing accurate and stable state estimation. The combination of IMU measurements, VIO, SLAM, and EKF fusion ensures that the UAV maintains a consistent understanding of its position and orientation, even in environments with poor visual features or rapid motion. This reliable pose estimation is essential for mapping and planning, as it anchors the global voxel map and local occupancy grids used to generate safe trajectories. The integration of semantic segmentation into the mapping subsystem enhances environmental understanding, enabling the planner to differentiate between navigable and hazardous regions.

Deployment considerations also play a crucial role in the system's practicality. Embedded GPUs and NPUs impose strict computational constraints, making optimizations such as quantization, pruning, and patch-size tuning essential. The experimental results confirm that these optimizations preserve accuracy while enabling real-time inference, demonstrating that transformer-based perception can be deployed effectively on resource-constrained UAV platforms. The stability of the ViT-DETR module, combined with DroNet's reactive steering and the world-model's predictive capabilities, reduces false negatives and enhances safety around humans and dynamic obstacles.

Overall, the discussion reveals that AUROUAV successfully addresses the challenges of UAV autonomy in GNSS-denied environments by combining advanced perception, predictive reasoning, and adaptive control. The system's architecture demonstrates how modern transformer models, probabilistic control frameworks, and reinforcement learning can be integrated to achieve reliable, human-centered navigation in complex and unpredictable settings.

XVI. Evaluation

A. Perception Evaluation

AUROUAV demonstrates strong perception robustness across indoor, outdoor, and dynamic flight regimes. Steering RMSE remained low across all datasets, with indoor sequences achieving **0.042 rad**, outdoor suburban scenes **0.067 rad**, and dynamic flight **0.083 rad** due to motion blur and rapid viewpoint changes. Collision prediction AUC exceeded **0.91** across all domains, confirming reliable hazard awareness. Depth-grid IoU remained above **86%** indoors and **82%** outdoors, decreasing to **71%** under high-dynamic motion. Semantic voxel mIoU reached **82.3%** outdoors, reflecting strong semantic fusion in cluttered environments.

Steering RMSE Across Datasets




Fig. 18. Steering RMSE across indoor, outdoor, and dynamic flight environments. *The figure compares steering prediction accuracy for AUROUAV under three operational regimes. Indoor sequences (LUCID) yield the lowest RMSE due to structured geometry and stable lighting. Outdoor suburban scenes (SANPO) introduce clutter and semantic diversity, increasing RMSE. Dynamic UAV flight (DynUAV) produces the highest RMSE as rapid ego-motion and motion blur challenge temporal consistency. Lower RMSE indicates more accurate steering predictions and improved trajectory stability.*

B. Mapping and World-Model Evaluation

Local occupancy grid accuracy exceeded **89%** indoors and **84%** outdoors. Global semantic voxel consistency remained high, with drift increasing only slightly during dynamic flight. Free-space

prediction accuracy reached **87%**, and risk-map precision/recall exceeded **0.90**, demonstrating effective anticipation of obstacles and dynamic hazards.

Mapping Accuracy




Fig. 19. Mapping accuracy across indoor, outdoor, and dynamic flight environments. *The figure compares the accuracy of AUROUAV's mapping subsystem under three operational regimes. Indoor sequences (LUCID) achieve the highest accuracy at 89% due to structured geometry and stable lighting. Outdoor suburban scenes (SANPO) reduce accuracy to 84% as clutter, vegetation, and occlusions introduce semantic ambiguity. Dynamic UAV flight (DynUAV) yields the lowest accuracy at 78%, reflecting the challenges posed by rapid ego-motion, motion blur, and fast viewpoint changes. These results highlight the importance of multi-domain training for reliable mapping in GNSS-denied conditions.*

C. Planning and Control Evaluation

Trajectory smoothness improved by **28%** when integrating RL steering priors. MPC curvature variance decreased significantly, especially in dynamic flight. Path optimality remained within **6%** of A* and D* baselines. Control stability metrics showed attitude error below **3.1°** and trajectory tracking error under **0.18 m**, even during aggressive maneuvers.

RL Steering Prior Impact



Fig. 20. Impact of the RL steering prior on trajectory smoothness. *The figure compares trajectory smoothness with and without the reinforcement-learning steering prior. Without the prior, MPC produces a baseline level of curvature variation. When the RL prior is applied, trajectory smoothness improves by 28%, demonstrating the effectiveness of learned steering distributions in reducing oscillations, stabilizing local planning, and improving overall flight comfort—especially under dynamic motion and cluttered environments.*

D. Safety Evaluation

Risk-aware overrides occurred in **7.4%** of outdoor runs and **12.1%** of dynamic runs. Near-collision rate remained below **1.3%** across all datasets. End-to-end autonomous flight success rate reached **93.8%**, demonstrating strong reliability in GNSS-denied conditions.

E. Discussion

Results confirm that AUROUAV maintains robust perception, mapping, planning, and control across diverse environments. Indoor performance benefits from structured geometry, while outdoor scenes challenge semantic consistency. Dynamic flight stresses temporal fusion and control stability due to motion blur and rapid ego-motion. RL steering priors significantly improve trajectory smoothness and hazard avoidance. Multi-domain dataset exposure is essential for generalization, validating the importance of combining indoor, outdoor, and dynamic flight data.

XVII. Limitations

Despite its strong performance, AUROUAV has several limitations:

1. Sensitivity to Extreme Visual Drift

Although ViT-DETR is more robust than CNNs, it still degrades sharply under severe motion blur, dust haze, and illumination variation, consistent with findings in UAV disaster imagery [1].

2. Computational Constraints on Embedded Hardware

Transformer-based perception, even in lightweight variants, remains more computationally demanding than CNNs. Real-time inference on embedded UAV hardware requires aggressive optimization, quantization, and pruning.

3. Dependence on Multi-Sensor Fusion

The Gaussian steering PDF relies on stable VIO, SLAM, and IMU fusion. In environments with extremely poor visual features (e.g., smoke, fog, darkness), state estimation may drift.

4. Limited Generalization to Unseen Disaster Conditions

The multi-modal dataset used for training covers diverse GNSS-denied scenarios, but real-world disasters may introduce novel visual drift patterns not captured in simulation.

5. RL Steering Prior Requires Careful Tuning

PPO and TD3 adaptation must be carefully constrained to avoid over-aggressive steering variance updates that could destabilize MPC.

These limitations motivate future work in adaptive perception, robust SLAM, and lightweight transformer architectures.

XVIII. Future Work

Although AUROUAV demonstrates strong performance across a wide range of GNSS-denied environments, several promising avenues remain open for future research and development. One of the most compelling directions involves expanding the perception subsystem beyond RGB imagery. Integrating multimodal Vision Transformers that fuse RGB with thermal, infrared, or event-camera data could significantly enhance perception in visually degraded conditions such as smoke, fog, nighttime flight, or high-dynamic-range environments. These modalities would allow the autonomy stack to maintain reliable hazard detection even when traditional cameras fail.

Another important direction lies in hybridizing CNN and transformer architectures. While ViTs excel at capturing global context, CNNs remain highly efficient for extracting fine-grained local features. A hybrid CNN-ViT backbone could combine these strengths, yielding a perception model that is both computationally efficient and robust to occlusion, motion blur, and clutter. Such architectures may be particularly beneficial for micro-UAVs with strict power and compute limitations.

Further improvements can be achieved by exploring efficient attention mechanisms. Linear attention, sparse attention, and low-rank approximations have shown promise in reducing the computational burden of self-attention without sacrificing global context. Incorporating these mechanisms could enable larger transformer models to run on embedded GPUs or NPUs, expanding the capabilities of AUROUAV on smaller platforms.

The integration of transformer-based SLAM represents another frontier. While AUROUAV currently relies on classical SLAM pipelines such as ORB-SLAM2, OKVIS, and VINS-Mono, emerging research suggests that transformers can unify feature extraction, data association, and pose estimation within a single learned model. A transformer-based SLAM system could provide more robust global consistency, especially in environments with repetitive textures or limited visual features.

Finally, transformer-based flight-control policies offer a path toward more adaptive and human-like navigation. By learning control policies directly from latent world-model representations, UAVs could anticipate future hazards, adjust their trajectories proactively, and exhibit smoother, more natural flight behavior. Such policies could also enable higher-level reasoning, allowing UAVs to navigate complex environments with minimal human supervision.

Together, these future directions highlight the potential for AUROUAV to evolve into an even more capable and intelligent autonomy framework, pushing the boundaries of UAV navigation in challenging and unpredictable environments.

XIX. Conclusion

AUROUAV presents a unified autonomy architecture that integrates transformer-based perception, probabilistic steering control, reinforcement learning, sensor fusion, and SLAM into a cohesive system capable of operating reliably in GNSS-denied environments. The lightweight ViT-DETR perception module provides robust object detection under motion blur, occlusion, and illumination variation, outperforming traditional CNN-based detectors and demonstrating the advantages of global self-attention for UAV perception.

The introduction of a Gaussian steering angle probability density function ensures smooth and stable control, while dynamic probability adaptation enables responsive navigation in cluttered environments. Reinforcement learning algorithms such as PPO and TD3 allow the system to adjust its steering distribution intelligently based on real-time feedback, improving both safety and efficiency. The integration of VIO, SLAM, and EKF fusion ensures accurate state estimation, anchoring the mapping and planning subsystems and enabling reliable trajectory generation even under uncertainty.

Field tests and simulation experiments confirm that AUROUAV improves hazard recognition, reduces false negatives, and enhances navigation stability across a wide range of environments. The system maintains real-time performance on embedded hardware, demonstrating that transformer-based perception and predictive control can be deployed effectively on resource-constrained UAV platforms.

Overall, AUROUAV represents a significant advancement in UAV autonomy, illustrating how modern transformer architectures, probabilistic control frameworks, and reinforcement learning can be combined to achieve reliable, human-centered navigation in complex and unpredictable settings. The architecture lays a strong foundation for future research, opening the door to multimodal perception, hybrid transformer-CNN models, transformer-based SLAM, and learned flight-control policies that will further expand the capabilities of autonomous aerial robots.

XX References

[1] A. K. Mishra, S. K. Singh, and A. K. Singh, “Robust Vision Transformer Adaptation for UAV Imagery,” *Frontiers in Artificial Intelligence*, vol. 3, 2026.

[2] A. K. Mishra, S. K. Singh, and A. K. Singh, “Rank-Aware Quantile Activation for Motion-Robust Crop Segmentation in UAV Imagery,” *arXiv preprint arXiv:2606.01118*, 2026.

[3] A. Dosovitskiy, L. Beyer, A. Kolesnikov, et al., “An Image is Worth 16×16 Words: Transformers for Image Recognition at Scale,” *ICLR*, 2021.

[4] N. Carion, F. Massa, G. Synnaeve, et al., “End-to-End Object Detection with Transformers,” *CVPR*, 2020.

[5] S. Mehta and M. Rastegari, “MobileViT: Light-weight, General-purpose, and Mobile-friendly Vision Transformer,” *arXiv:2110.02178*, 2021.

[6] B. Wu, H. Fan, Y. Zhang, et al., “TinyViT: Fast Pretraining Distillation for Small Vision Transformers,” *ECCV*, 2022.

[7] H. Touvron, M. Cord, A. Sablayrolles, et al., “Training Data-Efficient Image Transformers (DeiT),” *ICLR*, 2021.

[8] R. Mur-Artal and J. D. Tardós, “ORB-SLAM2: An Open-Source SLAM System for Monocular, Stereo, and RGB-D Cameras,” *IEEE Transactions on Robotics*, vol. 33, no. 5, pp. 1255–1262, 2017.

[9] S. Leutenegger, S. Lynen, M. Bosse, et al., “Keyframe-based Visual-Inertial Odometry using Nonlinear Optimization,” *Robotics: Science and Systems (RSS)*, 2015.

[10] T. Qin, P. Li, and S. Shen, “VINS-Mono: A Robust and Versatile Monocular Visual-Inertial State Estimator,” *IEEE Transactions on Robotics*, vol. 34, no. 4, pp. 1004–1020, 2018.

[11] J. Schulman, F. Wolski, P. Dhariwal, et al., “Proximal Policy Optimization Algorithms,” *arXiv:1707.06347*, 2017.

[12] S. Fujimoto, H. Hoof, and D. Meger, “Addressing Function Approximation Error in Actor-Critic Methods,” *ICML*, 2018.

[13] A. Loquercio, A. I. Maqueda, C. R. del Blanco, and D. Scaramuzza, “DroNet: Learning to Fly by Driving,” *IEEE Robotics and Automation Letters*, vol. 3, no. 2, pp. 1088–1095, 2018.

[14] S. Shah, D. Dey, C. Lovett, and A. Kapoor, “AirSim: High-Fidelity Visual and Physical Simulation for Autonomous Vehicles,” *Field and Service Robotics (FSR)*, 2017.

[15] L. Meier, D. Honegger, and M. Pollefeys, “PX4: A Node-Based Architecture for Autonomous UAVs,” *ICRA*, 2015.

[16] N. Koenig and A. Howard, “Design and Use Paradigms for Gazebo, an Open-Source Multi-Robot Simulator,” *IROS*, 2004.