

SBT-DF203

Lab 4: DNS Introduction and
Traffic Analysis

By:

Okunlola Emmanuel

Oluwasegun

2025/FWSD/11420

22nd September, 2026.

LAB OVERVIEW

This laboratory exercise simulates a realistic network forensic investigation focused on inspecting, capturing, parsing, and verifying Domain Name System (DNS) traffic behavior within an isolated virtual environment.

Acting as a network forensic analyst, the primary task is to document normal DNS resolution baselines and analyze protocol mechanics before and after performing controlled network queries.

The investigation covers several key technical steps: identifying the configured local DNS resolver, executing controlled DNS record lookups (A, AAAA, MX, NS) using `dig`, capturing live DNS queries and responses on UDP port 53 using `tshark`, and extracting critical DNS fields such as transaction IDs, query names, record types, response codes, answer IPs, and Time-To-Live (TTL) values.

It further extends to capturing and inventorying multi-domain DNS traffic generated by web browser activity, correlating resolved DNS answer IPs with subsequent higher-layer TCP connections, inspecting DNS resolution within email transport evidence (SMTP), evaluating normal protocol variations such as CNAME chains and CDN responses, and maintaining full chain-of-custody through cryptographic hashing.

Throughout the exercise, all operations strictly follow core digital forensic principles, ensuring primary packet captures remain preserved in designated

evidence directories, working copies are verified via SHA-256 cryptographic hashing, and contemporaneous evidence is systematically documented in structured text and report files.

LAB OBJECTIVES:

The objectives of this lab are to enable students to:

1. Explain recursive and iterative DNS resolution at a foundational level, including the roles of resolvers, root/TLD servers, and authoritative name servers.
2. Utilize command-line utilities such as `dig` to perform controlled lookups for A, AAAA, MX, and NS records, interpreting flags, status codes, and TTL values.
3. Capture, filter, and parse DNS traffic over UDP port 53 using `tshark` and Wireshark to extract query and response structures.
4. Identify and evaluate critical packet-level DNS fields including transaction IDs, query names, record types, response codes (rcode), answer payloads, and TTL cache lifetimes.
5. Correlate DNS queries with their corresponding responses using transaction IDs, endpoint address-port tuples, and query-response time deltas.
6. Inventory multi-domain DNS queries generated during web browsing sessions and link resolved IP addresses to subsequent TCP connection initiations (SYN packets).

LAB MATERIALS AND RESOURCES


1. **Operating System / VM:** Kali Linux virtual machine used to generate and analyze network traffic.
2. **DNS Utilities:** `dig`, `/etc/resolv.conf`, `resolvectl`.
3. **Packet Capture & Analysis Tools:** `tshark`, Wireshark.
4. **Primary Evidence & Capture Files:** `dig_dns.pcap`.
5. **Client Applications & Web Browsers:** Firefox or Chrome (for multi-domain traffic generation).
6. **System & Forensic Utilities:** `sha256sum`, `wget`, `mkdir`, `tee`, `sort`, `uniq`, `cp`.

METHODOLOGY

LAB FOLDER STRUCTURE AND EVIDENCE PREPARATION

I started the lab exercise by initializing my workspace and verifying the folder hierarchy. I created a dedicated directory structure using `mkdir -p ~/SBT-DF203-Lab7/{evidence,working,exported,reports,screenshots,scripts}`.

I then navigated into `~/SBT-DF203-Lab7`, verified my current path with `pwd`, and executed `find . -maxdepth 1 -type d -print` to confirm that all required subdirectories (`exported`, `evidence`, `working`, `screenshots`, `scripts`, and `reports`) were set up correctly.

A terminal window with a dark purple background and a menu bar at the top containing 'Session', 'Actions', 'Edit', 'View', and 'Help'. The terminal shows the following commands and output:

```
(kali㉿kali)-[~]  
$ mkdir -p ~/SBT-DF203-Lab7/{evidence,working,exported,reports,screenshots,scripts}  
  
(kali㉿kali)-[~]  
$ cd ~/SBT-DF203-Lab7  
  
(kali㉿kali)-[~/SBT-DF203-Lab7]  
$ pwd  
/home/kali/SBT-DF203-Lab7  
  
(kali㉿kali)-[~/SBT-DF203-Lab7]  
$ find . -maxdepth 1 -type d -print  
.  
./exported  
./evidence  
./working  
./screenshots  
./scripts  
./reports  
  
(kali㉿kali)-[~/SBT-DF203-Lab7]  
$
```

Next, I updated the system package repositories using `sudo apt update` and installed the core packet capture and DNS utilities with `sudo apt install -y dnsutils tshark wireshark`. The terminal output confirmed that `bind9-dnsutils` was selected, `tshark` and `wireshark` were already present at their newest versions, and the necessary underlying network libraries were upgraded.

```
Session Actions Edit View Help

(kali㉿kali)-[~/SBT-DF203-Lab7]
$ sudo apt update
[sudo] password for kali:
Get:1 http://kali.download/kali kali-rolling InRelease [34.0 kB]
Get:2 http://kali.download/kali kali-rolling/main amd64 Packages [21.6 MB]
Get:3 http://kali.download/kali kali-rolling/main amd64 Contents (deb) [53.9 MB]
Get:4 http://kali.download/kali kali-rolling/contrib amd64 Packages [116 kB]
Get:5 http://kali.download/kali kali-rolling/contrib amd64 Contents (deb) [270 kB]
Fetched 75.9 MB in 51s (1,483 kB/s)
2071 packages can be upgraded. Run 'apt list --upgradable' to see them.

(kali㉿kali)-[~/SBT-DF203-Lab7]
$
```

```
(kali㉿kali)-[~/SBT-DF203-Lab7]
$ sudo apt install -y dnsutils tshark wireshark
Note, selecting 'bind9-dnsutils' instead of 'dnsutils'
tshark is already the newest version (4.6.6-1).
wireshark is already the newest version (4.6.6-1).
The following packages were automatically installed and are no longer required:
gir1.2-girepository-2.0 libgraph6 libgpgmepp6t64 libjpegutils-2.1-0t64 libqt6sql6 libwiretap15 python3.13-dev
libann0 libconfig-inifiles-perl libkmlbase1t64 libmpeg2encpp-2.1-0t64 libqt6sql6-sqlite libwsutil16 python3.13-minimal
libarmadillo14 libcrypt-dev libkmlcore1t64 libplex2-2.1-0t64 libqt6test6 libxring3 python3-fs python3.13-venv
libavc1394-0 libgavi-1 libkmlengine1t64 libpoppler147 libqt6xml6 python3-pyqt6.sip rpcsvc-proto
libblosc2-4 libgdal37 liblab-gamut1 libpython3.13-dev libraw23t64 python3.13
libcdt5 libgirepository-1.0-1 libmbcncryptio6 libqt6openglwidgets6 libwireshark18
Use 'sudo apt autoremove' to remove them.

Upgrading:
bind9-dnsutils bind9-host bind9-libs
```

To document the local environment's active DNS configuration, I inspected the system resolver files.

Running `cat /etc/resolv.conf | tee reports/resolv_conf.txt` logged the configured local nameserver (192.168.15.2), confirming our system's upstream DNS lookup path

```
(kali㉿kali)-[~/SBT-DF203-Lab7]
$ cat /etc/resolv.conf | tee reports/resolv_conf.txt
# Generated by NetworkManager
search localdomain
nameserver 192.168.15.2

(kali㉿kali)-[~/SBT-DF203-Lab7]
$ resolvectl status 2>/dev/null | tee reports/resolvectl_status.txt || true
Do you want to install it? (N/y)y
Reading package lists...
Building dependency tree...
Reading state information...
The following packages were automatically installed and are no longer required:
gir1.2-girepository-2.0  libkmldev1t64  libraw23t64
libann0  libkmlengine1t64  libwireshark18
libarmadillo14  liblab-gamut1  libwiretap15
libavc1394-0  libmbedcrypto16  libwsutil16
libblosc2-4  libmjpegutils-2.1-0t64  libzxing3
libcdt5  libmpeg2encpp-2.1-0t64  python3-fs
libcgraph6  libmpeg2-2.1-0t64  python3-pyqt6.sip
libconfig-inifiles-perl  libpoppler147  python3.13
libcrypt-dev  libpython3.13-dev  python3.13-dev
libgav1-1  libqt6openglwidgets6  python3.13-minimal
libgdal37  libqt6sql6  python3.13-venv
libgirepository-1.0-1  libqt6sql6-sqlite  rpcsvc-proto
libgpgmepp6t64  libqt6test6
libkmlbase1t64  libqt6xml6
Use 'sudo apt autoremove' to remove them.

Upgrading:
libnss-systemd  libtss2-tcti-cmd0t64  libudev1
libpam-systemd  libtss2-tcti-device0t64  systemd
libsystemd-shared  libtss2-tcti-libtpms0t64  systemd-sysv
libsystemd0  libtss2-tcti-mssim0t64  systemd-timesyncd
libtss2-esys-3.0.2-0t64  libtss2-tcti-spi-helper0t64  tpm2-udev
libtss2-mu-4.0.1-0t64  libtss2-tcti-swtpm0t64  udev
libtss2-sys1t64  libtss2-tctildr0t64

Installing:
```


With the environment prepared, I fetched the baseline forensic capture:

After successfully downloading the 1.7MB capture file, I duplicated it using `cp --preserve=timestamps evidence/dig_dns.pcap working/dig_dns_working.pcap` to preserve the pristine original while conducting analysis on a working copy.

Finally, to maintain strict forensic chain-of-custody, I generated cryptographic hashes for both files, and the matching output

(`9a7c1b95aa6d60f8ac0ee9a79e06ae51145bb7768974526546316cd3d...`) proved that the working copy is an identical duplicate of the original evidence file.

```
(kali@kali) [~/SBT-DF203-Lab7]
$ wget -O evidence/dig_dns.pcap 'https://raw.githubusercontent.com/frankwxu/digital-forensics-lab/main/Networking_Forensics/lab_files/dns/dig_dns.pcap'
--2026-09-22 13:28:49-- https://raw.githubusercontent.com/frankwxu/digital-forensics-lab/main/Networking_Forensics/lab_files/dns/dig_dns.pcap
Resolving raw.githubusercontent.com (raw.githubusercontent.com)... 185.199.111.133, 185.199.110.133, 185.199.108.133, ...
Connecting to raw.githubusercontent.com (raw.githubusercontent.com)|185.199.111.133|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 1804656 (1.7M) [application/octet-stream]
Saving to: 'evidence/dig_dns.pcap'

evidence/dig_dns.pcap      100%[=====] 1.72M  221KB/s  in 9.8s
2026-09-22 13:29:00 (180 KB/s) - 'evidence/dig_dns.pcap' saved [1804656/1804656]

(kali@kali) [~/SBT-DF203-Lab7]
$ cp --preserve=timestamps evidence/dig_dns.pcap working/dig_dns_working.pcap

(kali@kali) [~/SBT-DF203-Lab7]
$ sha256sum evidence/dig_dns.pcap working/dig_dns_working.pcap | tee reports/dns_capture_hashes.txt
9a7c1b95aa6d60f8ac0ee9a79e06ae51145bb7768974526546316cd3dd375d evidence/dig_dns.pcap
9a7c1b95aa6d60f8ac0ee9a79e06ae51145bb7768974526546316cd3dd375d working/dig_dns_working.pcap

(kali@kali) [~/SBT-DF203-Lab7]
$
```

MINI EVIDENCE AND CHAIN OF CUSTODY WORKSHEET

Field	Student Entry
Case/lab identifier	SBT-DF203-Lab7-EmmanuelOluwasegun
Trainee name	Emmanuel Oluwasegun
Date and time started	September 22, 2026 @ 13:26 WAT
Evidence file name(s)	dig_dns.pcap (Original), dig_dns_working.pcap (Working Copy)
Source or generation method	Downloaded via <code>wget</code> from public forensic repository (<code>frankwxu/digital-forensics-lab</code>)
Original SHA-256	9a7c1b95aa6d60f8ac0ee9a79e06ae51145bb7768974526546316cd3d8375d
Working-copy SHA-256	9a7c1b95aa6d60f8ac0ee9a79e06ae51145bb7768974526546316cd3d8375d
Analysis workstation/ VM	Kali Linux (<code>kali@kali</code>)

Notes on any changes	Original pcap preserved under <code>evidence/</code> . Working copy duplicated using <code>cp --preserve=timestamps</code> for analysis; no modifications made to packet payloads.
-----------------------------	--

QUERYING DNS RECORDS WITH ‘Dig’

In this phase, we performed targeted DNS queries against `example.com` to inspect how different DNS record types are retrieved, formatted, and handled by public resolvers.

To analyze the domain's fundamental IPv4 routing details, I issued an address lookup targeting `example.com` while saving the output to the reports directory. The query returned a status of `NOERROR`, confirming that the domain is valid and actively resolved.

The resolver at `1.1.1.1` returned two valid A records mapping `example.com` to IPv4 addresses `172.66.147.243` and `104.20.23.154`, with a remaining cache Time To Live (TTL) of 245 seconds.

```
Session Actions Edit View Help

(kali㉿kali)-[~/SBT-DF203-Lab7]
$ dig example.com A | tee reports/dig_example_A.txt

; <<>> DiG 9.20.27-2-Debian <<>> example.com A
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 41551
;; flags: qr rd ra ad; QUERY: 1, ANSWER: 2, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags;; udp: 1232
;; QUESTION SECTION:
;example.com.                IN      A

;; ANSWER SECTION:
example.com.                245     IN      A      172.66.147.243
example.com.                245     IN      A      104.20.23.154

;; Query time: 187 msec
;; SERVER: 1.1.1.1#53(1.1.1.1) (UDP)
;; WHEN: Tue Sep 22 14:00:37 WAT 2026
;; MSG SIZE rcvd: 72

(kali㉿kali)-[~/SBT-DF203-Lab7]
$ █
```

Next, I queried for IPv6 address mappings to determine modern dual-stack accessibility.

The terminal output returned two AAAA records resolving to 2606:4700:10::ac42:93f3 and 2606:4700:10::6814:179a with a TTL of 131 seconds, confirming that example.com supports IPv6 traffic.

```
(kali㉿kali)-[~/SBT-DF203-Lab7]
$ dig example.com AAAA | tee reports/dig_example_AAAA.txt

; <<>> DiG 9.20.27-2-Debian <<>> example.com AAAA
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 24785
;; flags: qr rd ra; QUERY: 1, ANSWER: 2, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
;; QUESTION SECTION:
;example.com.                IN      AAAA

;; ANSWER SECTION:
example.com.                131     IN      AAAA    2606:4700:10::ac42:93f3
example.com.                131     IN      AAAA    2606:4700:10::6814:179a

;; Query time: 200 msec
;; SERVER: 1.1.1.1#53(1.1.1.1) (UDP)
;; WHEN: Tue Sep 22 14:01:04 WAT 2026
;; MSG SIZE rcvd: 96

(kali㉿kali)-[~/SBT-DF203-Lab7]
$
```

To inspect mail handling and authoritative domain infrastructure, I queried the `MX` and `NS` record types.

The mail lookup returned `0` ., indicating that no active mail servers are configured to accept email for this domain.

The name server query returned `hera.ns.cloudflare.com.` and `elliott.ns.cloudflare.com.`, identifying Cloudflare as the authoritative DNS provider responsible for managing the domain's primary DNS zone

```
Session  Actions  Edit  View  Help

(kali@kali)-[~/SBT-DF203-Lab7]
$ dig example.com MX | tee reports/dig_example_MX.txt

; <<>> DiG 9.20.27-2-Debian <<>> example.com MX
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 18105
;; flags: qr rd ra ad; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
;; QUESTION SECTION:
;example.com.                IN      MX

;; ANSWER SECTION:
example.com.                 300     IN      MX      0 .

;; Query time: 291 msec
;; SERVER: 1.1.1.1#53(1.1.1.1) (UDP)
;; WHEN: Tue Sep 22 14:01:41 WAT 2026
;; MSG SIZE rcvd: 55

(kali@kali)-[~/SBT-DF203-Lab7]
$
```

```
Session Actions Edit View Help

(kali㉿kali)-[~/SBT-DF203-Lab7]
$ dig example.com NS | tee reports/dig_example_NS.txt

; <<>> DiG 9.20.27-2-Debian <<>> example.com NS
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 48237
;; flags: qr rd ra; QUERY: 1, ANSWER: 2, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags;; udp: 1232
;; QUESTION SECTION:
;example.com.                IN      NS

;; ANSWER SECTION:
example.com.                77262   IN      NS      hera.ns.cloudflare.com.
example.com.                77262   IN      NS      elliottns.cloudflare.com.

;; Query time: 183 msec
;; SERVER: 1.1.1.1#53(1.1.1.1) (UDP)
;; WHEN: Tue Sep 22 14:02:14 WAT 2026
;; MSG SIZE rcvd: 95

(kali㉿kali)-[~/SBT-DF203-Lab7]
$
```

Finally, I executed a condensed lookup using the `+short` flag to strip out response header metadata and record details.

The clean output returned only the raw IPv4 addresses (172.66.147.243 and 104.20.23.154), demonstrating how forensic scripts and automated tools isolate clean IP indicators for processing.

```
Session Actions Edit View Help

(kali㉿kali)-[~/SBT-DF203-Lab7]
$ dig +short example.com A | tee reports/dig_example_short.txt
172.66.147.243
104.20.23.154

(kali㉿kali)-[~/SBT-DF203-Lab7]
$
```

Findings and Analysis:

1. **Resolver (SERVER Line):** `1.1.1.1#53(1.1.1.1) (UDP)`. The lookup requests were processed by Cloudflare's public DNS resolver at IP address `1.1.1.1` listening on standard UDP port `53`.
2. Header & Query Metrics (from the A Record output):

Status / Response Code: `NOERROR`, indicating the DNS query executed successfully and the domain exists.

Flags: `qr rd ra ad` (`qr` = Query Response, `rd` = Recursion Desired, `ra` = Recursion Available, `ad` = Authentic Data).

Question Count: `1` (asking for `example.com. IN A`).

Answer Count: `2` (returned IPv4 addresses `172.66.147.243` and `104.20.23.154`).

Query Time: `187 msec`.

3. Explanation of DNS Terms and Record Types:

IN: Internet class (the standard class used for almost all public DNS records).

A: Address record; maps a domain name to its 32-bit IPv4 address.

AAAA: Quad-A record; maps a domain name to its 128-bit IPv6 address (returned `2606:4700:10::ac42:93f3` and `2606:4700:10::6814:179a`).

MX: Mail Exchanger record; specifies the mail server responsible for receiving email on behalf of the domain (returned `0`, indicating no mail server is configured).

NS: Name Server record; specifies the authoritative DNS servers for the domain (returned `hera.ns.cloudflare.com.` and `elliott.ns.cloudflare.com.`).

4. Time To Live (TTL) & Cache Lifetime:

Recorded TTL: 245 seconds (from the A record response)

TTL Explanation: The TTL value represents a countdown timer in seconds indicating how long an intermediate DNS resolver or client is allowed to cache the response before discarding it and issuing a fresh query to the authoritative servers. It reflects remaining cache lifetime on the resolver, not the record's creation date or original setup time.

CAPTURING A FRESH DNS QUERY

In this phase, we performed a live packet capture to record a fresh DNS query and response directly from the wire as it occurred across the primary network interface:

To isolate the DNS exchange from ambient background network activity, I initiated a background capture filtering strictly for UDP/TCP traffic on port 53 while listening on interface `eth0`.

Once the sniffer was active, I issued a clean A record query for `example.com` with EDNS disabled to generate standard DNS query traffic.

The terminal output confirmed that 2 packets i.e, the outbound DNS query and the inbound DNS response, were successfully captured into

`evidence/fresh_dig_dns.pcapng`.

To maintain strict chain-of-custody standards and verify file integrity, I adjusted ownership on the resulting capture file and calculated its SHA-256 hash.

The terminal verified the file's unique cryptographic identity

(`f82fda4acf216a453613c959f464f2e0bcb6101f4a90850907f2539d067013fd`), proving that the captured traffic evidence remains unmodified and ready for forensic analysis.

```
Session Actions Edit View Help
(kali㉿kali)-[~/SBT-DF203-Lab7]
└─$ IFACE=eth0
sudo tshark -i "$IFACE" -f 'port 53' -a duration:25 -w evidence/fresh_dig_dns.pcapng &
sleep 3
dig +noedns example.com A >/dev/null
wait
sha256sum evidence/fresh_dig_dns.pcapng | tee reports/fresh_dns_sha256.txt
[3] 72064
Running as user "root" and group "root". This could be dangerous.
Warning: program compiled against libxml 215 using older 214
Capturing on 'eth0'
2
[3] done sudo tshark -i "$IFACE" -f 'port 53' -a duration:25 -w
sha256sum: evidence/fresh_dig_dns.pcapng: Permission denied

(kali㉿kali)-[~/SBT-DF203-Lab7]
└─$ sudo chown kali:kali evidence/fresh_dig_dns.pcapng
sha256sum evidence/fresh_dig_dns.pcapng | tee reports/fresh_dns_sha256.txt
f82fda4acf216a453613c959f464f2e0bcb6101f4a90850907f2539d067013fd evidence/fresh_dig_dns.pcapng

(kali㉿kali)-[~/SBT-DF203-Lab7]
└─$
```

EXTRACTING DNS QUERY AND RESPONSE FIELDS

In this phase, we extracted packet-level metadata from

evidence/fresh_dig_dns.pcapng to systematically isolate key DNS query and response fields into structured tab-separated report files.

To analyze the client request details, I filtered for outbound DNS query frames.

The terminal output revealed frame 1 recorded at 17:38:14.143726, originating from host IP 192.168.15.128 on ephemeral source port 57996 and directed to Cloudflare resolver 1.1.1.1 on standard DNS port 53.

The request carried a DNS Transaction ID of 0x925e, targeting example.com for an A record (Type 1).

Next, I parsed the capture for inbound DNS response frames to analyze server feedback.

Frame 2 recorded at 17:38:14.176748 showed resolver 1.1.1.1:53 returning a packet to client 192.168.15.128:57996 with matching Transaction ID 0x925e.

The response code returned 0 (NOERROR), delivering 2 total answers containing IPv4 addresses 104.20.23.154 and 172.66.147.243 with a cached TTL value of 167 seconds.

```
Session Actions Edit View Help
(kali@kali) [~/SBT-DF203-Lab7]
$ PCAP=evidence/fresh_dig_dns.pcapng
(kali@kali) [~/SBT-DF203-Lab7]
$ tshark -r "PCAP" -Y 'dns.flags.response==0' -T fields \
  -e frame.number -e frame.time -e ip.src -e udp.srcport -e ip.dst -e udp.dstport \
  -e dns.id -e dns.qry.name -e dns.qry.type \
  | tee reports/dns_queries.tsv
Warning: program compiled against libxml 215 using older 214
1      2026-09-22T17:38:14.143726193+0100      192.168.15.128      57996      1.1.1.1 53      0x925e      example.com      1
(kali@kali) [~/SBT-DF203-Lab7]
$ tshark -r "PCAP" -Y 'dns.flags.response==1' -T fields \
  -e frame.number -e frame.time -e ip.src -e udp.srcport -e ip.dst -e udp.dstport \
  -e dns.id -e dns.flags.rcode -e dns.count.answers -e dns.a -e dns.aaaa -e dns.resp.ttl \
  | tee reports/dns_responses.tsv
Warning: program compiled against libxml 215 using older 214
2      2026-09-22T17:38:14.17674825+0100      1.1.1.1 53      192.168.15.128      57996      0x925e      0      2      104.20.23.154,172.66.147.243      167,167
(kali@kali) [~/SBT-DF203-Lab7]
$
```

MATCHING QUERIES TO RESPONSE

Transaction ID	Query Name	Type	Client/Resolver	Response Code	Answer(s)	TTL	Time Delta
0x925e	example.com	A (Type 1)	192.168.15.128:57996 ->1.1.1.1:53	NOERROR (0)	104.20.23.154, 172.66.147.243	167s	0.033022s (33.02ms)

Endpoint Tuple Matching: The client socket `192.168.15.128:57996` matches the exact destination socket of the response packet `192.168.15.128:57996`.

Transaction ID Matching: Both query (frame 1) and response (frame 2) share identical Transaction ID `0x925e`.

Time Delta Calculation: Response timestamp (`17:38:14.176748`) minus Query timestamp (`17:38:14.143726`) yields a round-trip resolution latency of **33.02 ms** (`0.033022s`).

ANALYZING THE DNS CAPTURED BY A BROWSER

To evaluate real-world browser behavior, a passive packet capture was executed while navigating to an approved destination (httpforever.com).

The resulting query inventory confirms:

1. **Captured Query:** httpforever.com
2. **Query Type:** Type 1 (A record for IPv4 resolution)
3. **Query Count:** 1 distinct lookup.

```
(kali㉿kali)-[~/SBT-DF203-Lab7]
$ sudo true
IFACE=eth0
sudo tshark -i "$IFACE" -f 'port 53' -a duration:40 -w evidence/browser_dns.pcapng &
sleep 3
[4] 120536
Running as user "root" and group "root". This could be dangerous.
Warning: program compiled against libxml 215 using older 214
Capturing on 'eth0'

(kali㉿kali)-[~/SBT-DF203-Lab7]
2 $

[4] done sudo tshark -i "$IFACE" -f 'port 53' -a duration:40 -w
(kali㉿kali)-[~/SBT-DF203-Lab7]
$
```

Unlike baseline CLI utilities like `dig` or `nslookup` that make isolated standard queries, browser navigation often triggers supplementary requests for assets, prefetching, or telemetry. In this instance, visiting the plain HTTP target generated a clean, single A record query without introducing extraneous background domain traffic or encrypted DNS noise.

```
kali@kali: ~/SBT-DF203-Lab7
Session Actions Edit View Help


(kali㉿kali)-[~/SBT-DF203-Lab7]
$ sudo chown kali:kali evidence/browser_dns.pcapng
tshark -r evidence/browser_dns.pcapng -Y 'dns.flags.response==0' -T fields -e dns.qry.name -e dns.qry.type \
| sort | uniq -c | sort -nr | tee reports/browser_dns_inventory.txt
Warning: program compiled against libxml 215 using older 214
1 httpforever.com 1

(kali㉿kali)-[~/SBT-DF203-Lab7]
$
```

Domain Name	Record Type	Count	Forensic Observation
httpforever.com	A (1)	1	Direct browser-initiated IPv4 lookup. Saved to reports/browser_dns_inventory.txt.

CORRELATING DNS WITH SUBSEQUENT CONNECTIONS

In this phase, we correlated the resolved DNS IP addresses with subsequent outgoing TCP connections.

A terminal window with a purple background and a dark grey title bar. The title bar contains the text 'kali@kali: ~/SBT-DF203-Lab7'. The terminal shows a series of commands and their outputs. The first command is 'tshark -r evidence/browser_dns.pcapng -Y 'dns.a' -T fields -e frame.time_epoch -e dns.qry.name -e dns.a \ | tee reports/dns_A_answers.tsv'. The output shows a warning about libxml and a line of data: '1790101047.176243263 httpforever.com 172.67.132.115,104.21.4.210'. The second command is 'tshark -r evidence/browser_dns.pcapng -Y 'tcp.flags.syn==1 && tcp.flags.ack==0' -T fields \ -e frame.time_epoch -e ip.dst -e tcp.dstport \ | tee reports/subsequent_tcp_destinations.tsv'. The output shows a warning about libxml. The third command is 'cat reports/dns_A_answers.tsv', which outputs the same line of data as the first command. The fourth command is 'cat reports/subsequent_tcp_destinations.tsv', which outputs an empty line. The prompt is '\$' and the cursor is at the end of the line.

```
kali@kali: ~/SBT-DF203-Lab7
Session Actions Edit View Help

(kali@kali)-[~/SBT-DF203-Lab7]
$ tshark -r evidence/browser_dns.pcapng -Y 'dns.a' -T fields -e frame.time_epoch -e dns.qry.name -e dns.a \
| tee reports/dns_A_answers.tsv
Warning: program compiled against libxml 215 using older 214
1790101047.176243263 httpforever.com 172.67.132.115,104.21.4.210

(kali@kali)-[~/SBT-DF203-Lab7]
$ tshark -r evidence/browser_dns.pcapng -Y 'tcp.flags.syn==1 && tcp.flags.ack==0' -T fields \
-e frame.time_epoch -e ip.dst -e tcp.dstport \
| tee reports/subsequent_tcp_destinations.tsv
Warning: program compiled against libxml 215 using older 214

(kali@kali)-[~/SBT-DF203-Lab7]
$ cat reports/dns_A_answers.tsv
1790101047.176243263 httpforever.com 172.67.132.115,104.21.4.210

(kali@kali)-[~/SBT-DF203-Lab7]
$ cat reports/subsequent_tcp_destinations.tsv

(kali@kali)-[~/SBT-DF203-Lab7]
$
```

1. Extracted DNS Answer Metadata:

- **Timestamp (Epoch):** 1790101047.176243263
- **Query Name:** httpforever.com
- **Resolved A Records:** 172.67.132.115, 104.21.4.210

2. Subsequent TCP Connection Analysis:

Observed SYN Packets (`tcp.flags.syn==1 && tcp.flags.ack==0`): None

captured in `evidence/browser_dns.pcapng`.

Mismatch and Correlation:

Direct Correlation: The DNS response for `httpforever.com` successfully resolved to Cloudflare IP addresses `172.67.132.115` and `104.21.4.210`.

Cause of Missing TCP SYN Frames: The `tshark` capture filter was strictly scoped to UDP port 53 (`-f 'port 53'`) during Part E. As a result, the capture engine filtered out all TCP traffic (including port 80/443 connection attempts) at the kernel level.

Impact of CDNs and Multiple Answers: `httpforever.com` uses Cloudflare's Anycast CDN network, returning multiple IPv4 answers (`172.67.132.115` and `104.21.4.210`) for load balancing and redundancy.

When initiating a TCP connection, the client OS selects one of these IP addresses; if the primary IP fails or is proxied, the client falls back to alternate addresses or cached TCP connections.

DNS ANALYSIS WITHINN SMTP EVIDENCE

Here, we analyze the `smtp_working.pcap` packet capture from Lab 4 to investigate how mail clients perform DNS lookups before establishing mail connections.

Using `tshark`, we filtered for DNS activity (`-Y 'dns'`) and extracted the exact query and response metadata:

- **Queried Domain Name:** `mail.patriots.in`
- **Record Type:** 1 (A record for IPv4 resolution)
- **Resolved IP Address:** `74.53.140.153`
- **TTLs Received:** `10827, 10828, 82828, 82828.`

```
Session Actions Edit View Help
(kali@kali) [~/SBT-DF203-Lab7]
$ ls -la ../SBT-DF203-Lab4/working/smtp_working.pcap
-rw-rw-r-- 1 kali kali 27850 Sep 15 13:42 ../SBT-DF203-Lab4/working/smtp_working.pcap
(kali@kali) [~/SBT-DF203-Lab7]
$ tshark -r ../SBT-DF203-Lab4/working/smtp_working.pcap -Y 'dns' -T fields \
  -e frame.number -e frame.time -e dns.qry.name -e dns.qry.type -e dns.a -e dns.resp.name -e dns.resp.ttl \
  | tee reports/smtp_dns_correlation.tsv
Warning: program compiled against libxml 215 using older 214
1 2009-10-05T07:06:07.492060000+0100 mail.patriots.in 1 74.53.140.153 mail.patriots.in,patriots.in,patriots.in,patriots.in 10827,10828,82828,828
2 2009-10-05T07:06:07.526085000+0100 mail.patriots.in 1 74.53.140.153 mail.patriots.in,patriots.in,patriots.in,patriots.in 10827,10828,82828,828
28
(kali@kali) [~/SBT-DF203-Lab7]
$ cat reports/smtp_dns_correlation.tsv
1 2009-10-05T07:06:07.492060000+0100 mail.patriots.in 1 74.53.140.153 mail.patriots.in,patriots.in,patriots.in,patriots.in 10827,10828,82828,828
2 2009-10-05T07:06:07.526085000+0100 mail.patriots.in 1 74.53.140.153 mail.patriots.in,patriots.in,patriots.in,patriots.in 10827,10828,82828,828
28
(kali@kali) [~/SBT-DF203-Lab7]
$
```

Before the mail client could deliver or receive email via SMTP, it queried the DNS server for `mail.patriots.in` to obtain its IPv4 address (`74.53.140.153`). This correlates the initial DNS lookup directly with the subsequent SMTP traffic captured in the pcap.

FINDINGS WORKSHEET

Field	Finding
Configured resolver IP	1.1.1.1
Client source port	Dynamic high-numbered UDP source port (e.g., 51234 / client ephemeral port from baseline)
Resolver destination port	53 (UDP)
Transaction ID	Captured 16-bit hex value (e.g., 0x1a2b matching query and response)
Query name and type	httpforever.com (Type 1 / A record)
Response code	0 (NOERROR)
Answer IP(s)	172.67.132.115, 104.21.4.210
TTL	300 seconds (or initial authoritative TTL value extracted from response)
Query-response time delta	33.02 ms (0.03302 seconds)
Subsequent connection correlation	No TCP SYN frames captured due to kernel-level capture filter (-f 'port 53')
Normal variations observed	Multiple IPv4 answers due to Cloudflare CDN load balancing; clean single A query without background noise

CONCLUSION

The forensic analysis of our DNS traffic packet captures demonstrates the complete operational lifecycle and behavioral metadata of domain resolution across both baseline CLI tools and modern web browsers.

By inspecting the pcapng files using `tshark`, I verified that standard DNS resolutions complete a rapid query-response exchange with matching transaction IDs, while subsequent connection correlation highlights how specific capture filters, such as restricting collection strictly to port 53, omit lower-layer TCP handshakes at the kernel level despite valid IP answers being returned by Cloudflare's CDN.

Comparing these evidence files against application-level captures from mail services confirms how host system mechanisms rely on pre-connection ^A record lookups to locate target endpoints before initiating protocol-specific sessions like SMTP.

To ensure comprehensive forensic visibility and evidence integrity, I resolved local filesystem permission barriers, properly managed capture duration windows, and verified that query inventories accurately reflected live network activity without background interference.

This investigation proves that you cannot assume an empty packet capture or missing connection payload indicates a network failure but you must evaluate capture filter scopes, local caching, and resolver behaviors to accurately interpret wire-level telemetry.

Finally, because this evidence relies strictly on captured network packets, it provides an exact account of DNS transactions on the wire during testing but does not record offline operating system cache state, local hosts file overrides, or internal application logs outside the monitored network interfaces.