

Joining tables with dplyr

Emily Malcolm-White

nycflights23 dataset

```
#LOAD PACKAGES
library(tidyverse)

#LOAD DATA
library(nycflights23)
data("flights")
```

nycflights23 contains information about all 435352 flights departing NYC in 2023.



Join dataframes

Matching key variable names

Some airline names might be easy to guess (ie. “UA” is United Airlines), but what airlines have the code “VX”, “HA”, and “B6”? Data on airline codes is provided in a dataset called `airlines`.

```
#data("airlines")
```

We want to have all this information in one data frame instead of two separate data frames.

The variable `carrier` in `flights` match the variable `carrier` in the `airlines` dataset – this is our *key variable*. In this case, they have the same name, but this doesn’t necessarily have to be true.

```
flights_joined <- flights %>%  
  inner_join(airlines, by="carrier")
```

Different key variable names

Say instead you are interested in the destinations of all domestic flights departing NYC in 2013, and you ask yourself questions like: “What cities are these airports in?”, or “Is”ORD” Orlando?”

```
data("airports")
```

In `airports` the airport code is in `faa`, whereas in `flights` the airport codes are in `origin` and `dest`.

```
flights_with_airport_names <- flights %>%  
  inner_join(airports, by = c("dest" = "faa"))
```

Let’s construct the chain of pipe operators `%>%` that computes the number of flights from NYC to each destination, but also includes information about each destination airport:

```
named_dests <- flights %>%  
  group_by(dest) %>%  
  summarize(num_flights = n()) %>%  
  arrange(desc(num_flights)) %>%  
  inner_join(airports, by = c("dest" = "faa")) %>%
```

```

  rename(airport_name = name)
named_dests

```

A tibble: 114 x 9

	dest	num_flights	airport_name	lat	lon	alt	tz	dst	tzone
	<chr>	<int>	<chr>	<dbl>	<dbl>	<dbl>	<dbl>	<chr>	<chr>
1	BOS	19036	General Edward Lawren~	42.4	-71.0	20	-5	A	Amer~
2	ORD	18200	Chicago O'Hare Intern~	42.0	-87.9	672	-6	A	Amer~
3	MCO	17756	Orlando International~	28.4	-81.3	96	-5	A	Amer~
4	ATL	17570	Hartsfield Jackson At~	33.6	-84.4	1026	-5	A	Amer~
5	MIA	16076	Miami International A~	25.8	-80.3	8	-5	A	Amer~
6	LAX	15968	Los Angeles Internati~	33.9	-118.	125	-8	A	Amer~
7	FLL	14239	Fort Lauderdale Holly~	26.1	-80.2	9	-5	A	Amer~
8	CLT	12866	Charlotte Douglas Int~	35.2	-80.9	748	-5	A	Amer~
9	DFW	11675	Dallas Fort Worth Int~	32.9	-97.0	607	-6	A	Amer~
10	SFO	11651	San Francisco Interna~	37.6	-122.	13	-8	A	Amer~

i 104 more rows

Multiple Key variables

In order to join the flights and weather data frames, we need more than one key variable: year, month, day, hour, and origin. This is because the combination of these 5 variables act to uniquely identify each observational unit in the weather data frame: hourly weather recordings at each of the 3 NYC airports.

```

data("weather")

flights_weather_joined <- flights %>%
  inner_join(weather, by = c("year", "month", "day", "hour", "origin"))

```


Why is this useful?

Updating labels:

```


flights %>%
  ggplot(aes(x = carrier, fill = origin)) +
  geom_bar() +
  coord_flip()

```




```
#VS
```

```
flights %>%
  inner_join(airports, by = c("origin" = "faa")) %>%
  rename(origin_airport = name) %>%
  inner_join(airlines, by = c("carrier")) %>%
  rename(carrier_name = name) %>%
  ggplot(mapping = aes(x = carrier_name, fill = origin_airport)) +
    geom_bar() +
    coord_flip()
```



Exploring relationships between variables in separate tables:

```
flights_weather_joined %>%
  filter(dep_delay > 0) %>%
  ggplot(aes(x=temp, y=dep_delay)) +
  geom_point()
```



Different Types of Joins

Common Issues with Joining

- duplicate keys
- lowercase/uppercase
- symbols or whitespace
- Make sure the join fields are the same format.

External Resources

- [R for Data Science, Joins](#)

Combine Data Sets

a		b	
x1	x2	x1	x3
A	1	A	T
B	2	B	F
C	3	D	T

+

=

Mutating Joins

x1	x2	x3
A	1	T
B	2	F
C	3	NA

dplyr::left_join(a, b, by = "x1")

Join matching rows from b to a.

x1	x3	x2
A	T	1
B	F	2
D	T	NA

dplyr::right_join(a, b, by = "x1")

Join matching rows from a to b.

x1	x2	x3
A	1	T
B	2	F

dplyr::inner_join(a, b, by = "x1")

Join data. Retain only rows in both sets.

x1	x2	x3
A	1	T
B	2	F
C	3	NA
D	NA	T

dplyr::full_join(a, b, by = "x1")

Join data. Retain all values, all rows.

Filtering Joins

x1	x2
A	1
B	2

dplyr::semi_join(a, b, by = "x1")

All rows in a that have a match in b.

x1	x2
C	3

dplyr::anti_join(a, b, by = "x1")

All rows in a that do not have a match in b.

Figure 1: Credit: RStudio