To Whom It May Concern



This copy is being provided for courtesy purposes only, and does not give any person or company other than our named client a right to rely on these results.

No warranties, express or implied, including the warranty of due diligence and care mentioned

elsewhere, shall extend to any party other than such named client.

Analysis Report

Report number : 12004/00126406.1/L/20 Composite prep date : 28-09-2020

Main Object : New Jersey Place of sampling : Koole Tankstorage Mineral BV

Report Date : 28-09-2020 Date received : 28-09-2020 Date of issue : 28-09-2020 Date completed : 28-09-2020 Sample object : New Jersey Sample number : 10568416

Sample type : Composite

Sample submitted as : DMA 890 Reddyed

Marked : Barge New Jersey multiple tank composite prepared from running samples ex P2, S2, P3,

S3 after loading from shoretank 806 & 092

Composite (10568416)					
SAMPLE NR	OBJECT	DESCRIPTION	RATIO		
10568359	New Jersey	Barge New Jersey P2 running after loading from shoretank 806 & 092			
10568360	New Jersey	Barge New Jersey S2 running after loading from shoretank 806 & 092			
10568361	New Jersey	Barge New Jersey P3 running after loading from shoretank 806 & 092			
10568362	New Jersey	Barge New Jersey S3 running after loading from shoretank 806 & 092			

NAME	METHOD	UNIT	RESULT
Appearance ¹	Visual	-	Slightly Hazy
Density at 15 °C	ASTM D 4052	kg/L	0.8713
Distillation	ASTM D 86		
Initial boiling point		°C	188.2
5% Recovered		°C	232.1
10% Recovered		°C	255.6
30% Recovered		°C	300.7
50% Recovered		°C	328.2
70% Recovered		°C	347.6
90% Recovered		°C	370.7
95% Recovered		°C	380.4
Final boiling point		°C	386.4
Recovered at 250 °C		vol %	8.6
Recovered at 350 °C		vol %	72.3
FAME content	EN 14078	vol %	<0.05
Filter Blocking Tendency	IP 387		
Filter Blocking Tendency		-	1.03
Initial Pressure		kPa	14
Final Pressure		kPa	25
Volume Filtered		mL	300
Temperature		°C	24
Procedure		-	В
Acid Number	ASTM D 664		
Acid number		mg KOH/g	0.03
Strong acid number		mg KOH/g	nill

All results in this report refer to the sample(s) tested as taken or submitted like specified in this Analysis report. Uncertainties, available on request, apply in the evaluation of the test results. All tests are conducted according to the latest version of the methods, unless another version is specifically indicated. Where available and for convenience purposes, the tested sample has been checked for compliance with supplied specifications, without accepting any liability. In case of dispute or concern, we refer to the interpretation of test results as defined in ASTM D3244, IP 367, ISO 4259 or GOST 33701. This report shall not be partially copied and reproduced without the written permission of the laboratory.

To Whom It May Concern



This copy is being provided for courtesy purposes only, and does not give any person or company other than our named client a right to rely on these results.

No warranties, express or implied, including the warranty of due diligence and care mentioned elsewhere, shall extend to any party other than such named client.

Analysis Report

Main Object : New Jersey Place of sampling : Koole Tankstorage Mineral BV

 Report Date
 : 28-09-2020
 Date received
 : 28-09-2020

 Date of issue
 : 28-09-2020
 Date completed
 : 28-09-2020

 Sample object
 : New Jersey
 Sample number
 : 10568416

Sample type : Composite

Sample submitted as : DMA 890 Reddyed

Marked : Barge New Jersey multiple tank composite prepared from running samples ex P2, S2, P3,

S3 after loading from shoretank 806 & 092

Composite (10568416)						
SAMPLE NR	OBJECT	DESCRIPTION	RATIO			
10568359	New Jersey	Barge New Jersey P2 running after loading from shoretank 806 & 092				
10568360	New Jersey	Barge New Jersey S2 running after loading from shoretank 806 & 092				
10568361	New Jersey	Barge New Jersey P3 running after loading from shoretank 806 & 092				
10568362	New Jersey	Barge New Jersey S3 running after loading from shoretank 806 & 092				

NAME	METHOD	UNIT	RESULT
Water Karl Fischer	ASTM D 6304		
Water Karl Fischer - Procedure A		mg/kg	90
Solvent Yellow	HPLC	mg/L	6
Cloud Point	EN 23015 obs.	°C	+10
Cold Filter Plugging Point	EN 116	°C	+7

Remarks:

1 Some particles present

Signed by: Fatih Eroglu - Sr Account Manager

Issued by: Saybolt Nederland BV

Place and date of issue: Rotterdam-Botlek - 28-09-2020

Print Date: 28-09-2020 12:33

Page 2 of 2

All results in this report refer to the sample(s) tested as taken or submitted like specified in this Analysis report. Uncertainties, available on request, apply in the evaluation of the test results. All tests are conducted according to the latest version of the methods, unless another version is specifically indicated. Where available and for convenience purposes, the tested sample has been checked for compliance with supplied specifications, without accepting any liability. In case of dispute or concern, we refer to the interpretation of test results as defined in ASTM D3244, IP 367, ISO 4259 or GOST 33701. This report shall not be partially copied and reproduced without the written permission of the laboratory.