



Parcel Summary

TRIP: AF21021

	· J							
Transport	Location	Activity	Grade	Quantity	ETA	Supply Contract Window	Inspector	Inspection Requirements
MED BALTIC (9462304)	VOPAK VLD LWH:LUB:4583/ 2235 (Nether- lands)	Load	AP/E CORE 600	850 Met- ric tonnes	05 Feb 2021	n/a	Saybolt	Quality / Quantity / Time log
MED BALTIC (9462304)	VOPAK VLD LWH:LUB:4583/ 2235 (Nether- lands)	Load	EHC 50	1,200 Metric tonnes	05 Feb 2021	n/a	Saybolt	Quality / Quantity / Time log
MED BALTIC (9462304)	VOPAK VLD LWH:LUB:4583/ 2235 (Nether- lands)	Load	AP/E CORE 150	1,500 Metric tonnes	05 Feb 2021	n/a	Saybolt	Quality / Quantity / Time log



Region: EAME Other Reference: B&S EAME LOAD ROTTERDAM TERMINALS - SAYBOLT - 100%

EM ONLY – EMPC **Business Group**: B&S EAME

Operator: CHRISTINE PEIJ

(christine.peij@exxonmobil.com)

Desk: B&S EAME Supply

Mobile: Nomination Type: Marine

Revision Comment: increased C600 to 850mts (was 800)

Documentary Instructions:

Phone:

Please provide an independent cargo inspection service in accordance with the Esso global inspection contract.

LOAD: MED BALTIC (9462304) - VOPAK VLD LWH:LUB:4583 / 2235 (NETHERLANDS)

Inspector: Saybolt

Hub: Europe/Africa/Russia/ME (International

Desk Rotterdam)

ExxonMobil Webservice

Created On: 04 Feb 2021 by

Last Modified: 04 Feb 2021 by

Inspection Status: Accepted

Coordinator: Cora Ligt (intdesk.saynl@corelab.com)

Cora Ligt

Local Office: Saybolt Netherland Rotterdam Chemicals

(saybolt.rotterdam.chemical@corelab.com)
INSPECTION REQUIREMENTS: QUALITY / QUANTITY / TIME LOG

Voyage Parcel External Reference Number: 5261687-10

Grade: AP/E CORE 600

ETA: 05 Feb 2021

ETD:

Start: p/a

Contract Number:
Parcel Ref:
Destination:
Source Location:

Supply Contract Window Start: n/a Source Location: Supply Contract Window End: n/a Supplier: Total Nominated Quantity: 850 Metric tonnes Receiver:

Transport / Voyage Number / Quantity / Tolerance: MED BALTIC (9462304) / 850 Metric Delivery Terms: CFR (Cost and

Freight)

tonnes

Mother Vessel:

Email Quantity Results To:

am.vlaardingen@vopak.com; basestocks@exxonmobil.com; BO-Rot-Terminal@exxonmobil.com; esup.inspection@exxonmobil.com;

Email Quality Results To:

am.vlaardingen@vopak.com; basestocks@exxonmobil.com; BO-Rot-Terminal@exxonmobil.com; esup.inspection@exxonmobil.com;

Load / Discharge Instructions:

For sampling and sealing, below instructions must be followed:

- 1) Invite the owners to witness the sampling of the manifold (arm loading "beginning")/ship tanks
- 2) Jointly seal and label the samples
- 3) Issue the samples document and have it signed by the ship crew showing samples are drawn in the presence of both parties

Attn Inspector: If you cannot draw sample yourself, do accompany and witness the site operators when samples are drawn.

Parcel Comments:

Retain samples for 90 days.

Quality Inspection Instructions:

SET 1

Description: On-shore tank Sample
Sample Location: Other (Specify in Comments)



								RO = Report Only Req. = Required
Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Additional Tests								
Retain sample -90 days	[OTHER] n/a					Yes	No	No lab testing needed - for retain purposes only

SET 2

Description: Loading Arm Sample

Sample Location: Other (Specify in Comments)

Quality Test Comments:

A **loading arm sample** (either at vessel manifold, or if not possible at the onshore point closest to the loading arm), before loading.

RO = Report Only

Reg. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature:Clear & Bright (no haze, no free water, no particulates)
Kinematic Viscosity at 100°C	[ASTM] ASTM D445			mm²/ S		No	Yes	
Odor	[OTHER] OL- FACTORY			None	No abnormal odor. Report if unusual odor.	No	Yes	

SET 3

Description: Loading arm beginning sample **Sample Location:** Other (Specify in Comments)

RO = Report Only

Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Additional Tests								
Retain sample -90 days	[OTHER] n/a					Yes	No	No lab testing needed - for retain purposes only

SET 4

Description: First foot sample **Sample Location:** Vessel First Foot

Quality Test Comments:

A 0.5 to 1-L first foot sample for each compartment to be loaded

*Viscosity for the first compartment loaded with a grade if flushing in between different grades cannot be applied or common lines are used for different categories.

RO = Report Only

Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature:Clear & Bright (no haze, no free water, no particulates)
Kinematic Viscosity at 100°C	[ASTM] ASTM D445			mm²/ S		No	Yes	
Odor	[OTHER] OL- FACTORY			None	No abnormal odor. Report if unusual odor.	No	Yes	

SET 5

Description: Compartment running samples

Sample Location: Ship Tank Individual





Quality Test Comments:

TRIP: AF21021

A 0.5 to 1L compartment running sample after completion of loading

RO = Report Only

Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Additional To	ests							
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature:Clear & Bright (no haze, no free water, no particulates)
Odor	[OTHER] OL- FACTORY			None	Acceptable	No	Yes	No Abnormal odor - Report if unusual odor.

SET 6

Description: Vessel Composite BTT Testing Sample Location: Other (Specify in Comments)

Quality Test Comments:

If all compartment samples are tested OK for appearance and odour, an average of each grade loaded is made from the running samples and divided into four.

The 3 other samples (1L) are labeled and sealed as retain samples. One is kept by the Surveyor, one given to the vessel Officer, one to the EM loading site. One sample (0.5 to 1 L) is analyzed according to the list of Bulk Transfer Tests as indicated in ProMIS requirements.

/I\ Important: The ship's departure is only allowed if the grade composite meets EM ProMIS requirements for Bulk Transfer Tests, or a waiver has been granted.

RO = Report Only

Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature:Clear & Bright (no haze, no free water, no particulates)
Kinematic Viscosity at 100°C	[ASTM] ASTM D445			mm²/ S		No	Yes	
Odor	[OTHER] OL- FACTORY			None	No abnormal odor. Report if unusual odor.	No	Yes	

SET 7

Description: Dead bottom sample Sample Location: Other (Specify in Comments)

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Additional Tests								
Retain sample -90 days	[OTHER] n/a					Yes	No	No lab testing needed - for retain purposes only

Invoice Instructions:

Bill Invoice To	Item to Bill	Split	Contact / Comment
2235 - ExxonMobil Petroleum & Chemical, BV (Legal Entity: 2235 EXXONMOBIL PETROLEUM & CHEMICAL, BV (2235))	Quantity only	100%	
	Test: Retain sam- ple -90 days	100%	
	Slate: B&S EAME Y2 BTT	100%	



Test: Retain sam- ple -90 days	100%	
Slate: B&S EAME Y2 BTT	100%	
Test: Appearance	100%	
Test: Odor	100%	
Slate: B&S EAME Y2 BTT	100%	
Test: Retain sam- ple -90 days	100%	

LOAD: MED BALTIC (9462304) - VOPAK VLD LWH:LUB:4583 / 2235 (NETHERLANDS)

Inspection Status: Accepted Inspector: Saybolt

Hub: Europe/Africa/Russia/ME (International Created On: 04 Feb 2021 by Desk Rotterdam)

ExxonMobil Web-

service Coordinator: Cora Ligt (intdesk.saynl@corelab.com)

Last Modified: 04 Feb 2021 by

Cora Ligt

Local Office: Saybolt Netherland Rotterdam Chemicals (saybolt.rotterdam.chemical@corelab.com)

INSPECTION REQUIREMENTS: QUALITY / QUANTITY / TIME LOG

Voyage Parcel External Reference Number: 5261319-10

Grade: EHC 50 **Contract Number:** Parcel Ref: ETA: 05 Feb 2021 **Destination:** ETD: Supply Contract Window Start: n/a **Source Location:**

Supply Contract Window End: n/a Supplier: Total Nominated Quantity: 1,200 Metric tonnes Receiver:

Delivery Terms: FCA (Free Carrier) Transport / Voyage Number / Quantity / Tolerance: MED BALTIC (9462304) / 1,200 Metric

tonnes

Mother Vessel:

Email Quantity Results To:

am.vlaardingen@vopak.com; basestocks@exxonmobil.com; BO-Rot-Terminal@exxonmobil.com; esup.inspection@exxonmobil.com;

Email Quality Results To:

am.vlaardingen@vopak.com; basestocks@exxonmobil.com; BO-Rot-Terminal@exxonmobil.com; esup.inspection@exxonmobil.com;

Load / Discharge Instructions:

For sampling and sealing, below instructions must be followed:

- 1) Invite the owners to witness the sampling of the manifold (arm loading "beginning")/ship tanks
- 2) Jointly seal and label the samples
- 3) Issue the samples document and have it signed by the ship crew showing samples are drawn in the presence of both parties

Attn Inspector: If you cannot draw sample yourself, do accompany and witness the site operators when samples are drawn.

Parcel Comments:

Retain samples for 90 days.

Quality Inspection Instructions:

SET 1

Description: On-shore tank Sample Sample Location: Other (Specify in Comments)

Quality Test Comments:





A 1-L <u>retain sample</u> of the **on-shore tank**, which is <u>sealed</u> and kept either at the loading site, or by the Surveyor. When the tank has no specific protection device against the ingress of atmospheric humidity, a low level (i.e. tank outlet level) sample is taken and confirmed B&C.

RO = Report Only

Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Additional Tests								
Retain sample -90 days	[OTHER] n/a					Yes	No	NO Analysis

SET 2

Description: Loading Arm Sample

Sample Location: Other (Specify in Comments)

Quality Test Comments:

A **loading arm sample** (either at vessel manifold, or if not possible at the onshore point closest to the loading arm), before loading.

RO = Report Only

Reg. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature: Clear & Bright (no haze, no free water, no particulates)
Kinematic Viscosity at 100°C	[ASTM] ASTM D445			mm²/ s		No	Yes	
Color (Say- bolt)	[ASTM] ASTM D156					No	Yes	
Kinematic Viscosity at 40°C	[ASTM] ASTM D445			mm²/ s		No	Yes	
ASTM Color	[ASTM] ASTM D1500					No	Yes	
Odor	[OTHER] OL- FACTORY			None	No abnormal odor. Report if unusual odor	No	Yes	

SET 3

Description: Loading arm beginning sample **Sample Location:** Other (Specify in Comments)

Quality Test Comments:

A 0.5 to 1-L **loading arm "beginning"** retain sample taken during the loading, preferably when 5 to 15% of the basestock is transferred.

This sample is labeled distinctly from the first one, <u>sealed</u> and stored by the surveyor.

This sample is a key one for investigations in case of a claim and litigation.

RO = Report Only

Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Additional Tests								
Retain sample -90 days	[OTHER] n/a					Yes	No	No Analysis

SET 4

Description: First foot sample **Sample Location:** Vessel First Foot

Quality Test Comments:



A 0.5 to 1-L first foot sample for each compartment to be loaded

*Viscosity for the first compartment loaded with a grade if flushing in between different grades cannot be applied or common lines are used for different categories.

RO = Report Only

Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature: Clear & Bright (no haze, no free water, no particulates)
Kinematic Viscosity at 100°C	[ASTM] ASTM D445			mm²/ S		No	Yes	
Color (Say- bolt)	[ASTM] ASTM D156					No	Yes	
Kinematic Viscosity at 40°C	[ASTM] ASTM D445			mm²/ S		No	Yes	
ASTM Color	[ASTM] ASTM D1500					No	Yes	
Odor	[OTHER] OL- FACTORY			None	No abnormal odor. Report if unusual odor	No	Yes	

SET 5

Description: Compartment running samples

Sample Location: Ship Tank Individual

Quality Test Comments:

A 0.5 to 1L compartment running sample after completion of loading

RO = Report Only

Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Additional To	ests							
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature:Clear & Bright (no haze, no free water, no particulates)
Odor	[OTHER] OL- FACTORY			None	Acceptable	No	Yes	No Abnormal odor - Report if unusual odor.

SET 6

Description: Vessel Composite BTT Testing **Sample Location:** Other (Specify in Comments)

Quality Test Comments:

If all compartment samples are tested OK for appearance and odour, an average of **each grade loaded is made from the running samples** and divided into four.

The 3 other samples (1L) are labeled and <u>sealed as retain</u> samples. One is kept by the Surveyor, one given to the vessel Officer, one to the EM loading site. One sample (0.5 to 1 L) is analyzed according to the list of Bulk Transfer Tests as indicated in ProMIS requirements.

/I\ Important: The ship's departure is only allowed if the grade composite meets EM ProMIS requirements for Bulk Transfer Tests, or a waiver has been granted.

RO = Report Only

Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature: Clear & Bright (no haze, no free water, no particulates)



									RO = Report Only	Req. = Required
Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment		
Kinematic Viscosity at 100°C	[ASTM] ASTM D445			mm²/ S		No	Yes			
Color (Say- bolt)	[ASTM] ASTM D156					No	Yes			
Kinematic Viscosity at 40°C	[ASTM] ASTM D445			mm²/ S		No	Yes			
ASTM Color	[ASTM] ASTM D1500					No	Yes			
Odor	[OTHER] OL- FACTORY			None	No abnormal odor. Report if unusual odor	No	Yes			

SET 7

Description: Dead bottom sample **Sample Location:** Other (Specify in Comments)

Quality Test Comments:

A 0.5 to 1L dead bottom retain sample for each compartment after completion of loading.

RO = Report Only Req. = Required Test Methods Min Max **UOM Typical** R.O. Comment Req. **Additional Tests** Retain sample -90 days [OTHER] n/a Yes No NO Analysis

Invoice Instructions:

Bill Invoice To	Item to Bill	Split	Contact / Comment
4583 ExxonMobil Sales & Supply (Legal Entity: 4583 ExxonMobil Sales & Supply (4583))	Quantity only	100%	
	Test: Retain sample -90 days	100%	
	Slate: B&S EAME Y4 (A&B) BTT	100%	
	Test: Retain sample -90 days	100%	
	Slate: B&S EAME Y4 (A&B) BTT	100%	
	Test: Appearance	100%	
	Test: Odor	100%	
	Slate: B&S EAME Y4 (A&B) BTT	100%	
	Test: Retain sample -90 days	100%	

LOAD: MED BALTIC (9462304) - VOPAK VLD LWH:LUB:4583 / 2235 (NETHERLANDS)

Inspector: Saybolt

Hub: Europe/Africa/Russia/ME (International

Desk Rotterdam)

Inspection Status: Accepted

Created On: 04 Feb 2021 by

ExxonMobil Web-

Cora Ligt

service **Last Modified:** 04 Feb 2021 by

Local Office: Saybolt Netherland Rotterdam Chemicals

Coordinator: Cora Ligt (intdesk.saynl@corelab.com)

(saybolt.rotterdam.chemical@corelab.com)

INSPECTION REQUIREMENTS: QUALITY / QUANTITY / TIME LOG



Voyage Parcel External Reference Number: 5261686-10

Grade: AP/E CORE 150 ETA: 05 Feb 2021 ETD:

ETD: Destination:
Supply Contract Window Start: n/a Source Location:
Supply Contract Window End: n/a Supplier:
Total Nominated Quantity: 1,500 Metric tonnes Receiver:

Transport / Voyage Number / Quantity / Tolerance: MED BALTIC (9462304) / 1,500 Metric Delivery Terms: CFR (Cost and

Freight)

Mother Vessel:

Contract Number:

Parcel Ref:

Email Quantity Results To:

am.vlaardingen@vopak.com; basestocks@exxonmobil.com; BO-Rot-Terminal@exxonmobil.com; esup.inspection@exxonmobil.com;

Email Quality Results To:

am.vlaardingen@vopak.com; basestocks@exxonmobil.com; BO-Rot-Terminal@exxonmobil.com; esup.inspection@exxonmobil.com;

Load / Discharge Instructions:

For sampling and sealing, below instructions must be followed:

- 1) Invite the owners to witness the sampling of the manifold (arm loading "beginning")/ship tanks
- 2) Jointly seal and label the samples
- 3) Issue the samples document and have it signed by the ship crew showing samples are drawn in the presence of both parties

Attn Inspector: If you cannot draw sample yourself, do accompany and witness the site operators when samples are drawn.

Parcel Comments:

Retain samples for 90 days.

Quality Inspection Instructions:

SET 1

Description: On-shore tank Sample **Sample Location:** Other (Specify in Comments)

								RO = Report Only Req. = Required
Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Additional Tests								
Retain sample -90 days	[OTHER] n/a					Yes	No	No lab testing needed - for retain purposes only

SET 2

Description: Loading Arm Sample **Sample Location:** Other (Specify in Comments)

Quality Test Comments:

A **loading arm sample** (either at vessel manifold, or if not possible at the onshore point closest to the loading arm), before loading.

PO - Poport	Only	Pog -	Required
RO = Report	Office	rteq. –	Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature:Clear & Bright (no haze, no free water, no particulates)
Kinematic Viscosity at 100°C	[ASTM] ASTM D445			mm²/ s		No	Yes	



Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment	RO = Report Only	Req. = Required
Odor	[OTHER] OL- FACTORY			None	No abnormal odor. Report if unusual odor.	No	Yes			

SET 3

Description: Loading arm beginning sample **Sample Location:** Other (Specify in Comments)

								RO = Report Only Req. = Required
Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Additional Tests								
Retain sample -90 days	[OTHER] n/a					Yes	No	No lab testing needed - for retain purposes only

SET 4

Description: First foot sample **Sample Location:** Vessel First Foot

Quality Test Comments:

A 0.5 to 1-L first foot sample for each compartment to be loaded

*Viscosity for the first compartment loaded with a grade if flushing in between different grades cannot be applied or common lines are used for different categories.

RO = Report Only Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature:Clear & Bright (no haze, no free water, no particulates)
Kinematic Viscosity at 100°C	[ASTM] ASTM D445			mm²/ S		No	Yes	
Odor	[OTHER] OL- FACTORY			None	No abnormal odor. Report if unusual odor.	No	Yes	

SET 5

Description: Compartment running samples

Sample Location: Ship Tank Individual

Quality Test Comments:

A 0.5 to 1L compartment running sample after completion of loading

								RO = Report Only Req. = Required			
Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment			
Additional Tests											
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature:Clear & Bright (no haze, no free water, no particulates)			
Odor	[OTHER] OL- FACTORY			None	Acceptable	No	Yes	No Abnormal odor - Report if unusual odor.			

SET 6

Description: Vessel Composite BTT Testing **Sample Location:** Other (Specify in Comments)

Quality Test Comments:





TRIP: AF21021

If all compartment samples are tested OK for appearance and odour, an average of each grade loaded is made from the running samples and divided into four.

The 3 other samples (1L) are labeled and sealed as retain samples. One is kept by the Surveyor, one given to the vessel Officer, one to the EM loading site. One sample (0.5 to 1 L) is analyzed according to the list of Bulk Transfer Tests as indicated in ProMIS requirements.

/!\ Important: The ship's departure is only allowed if the grade composite meets EM ProMIS requirements for Bulk Transfer Tests, or a waiver has been granted.

> RO = Report Only Req. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Appearance	[OTHER] Vi- sual				C&B	No	Yes	Appearance at ambient temperature:Clear & Bright (no haze, no free water, no particulates)
Kinematic Viscosity at 100°C	[ASTM] ASTM D445			mm²/ S		No	Yes	
Odor	[OTHER] OL- FACTORY			None	No abnormal odor. Report if unusual odor.	No	Yes	

SET 7

Description: Dead bottom sample Sample Location: Other (Specify in Comments)

> RO = Report Only Reg. = Required

Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment
Additional Tests								
Retain sample -90 days	[OTHER] n/a					Yes	No	No lab testing needed - for retain purposes only

Invoice Instructions:

Bill Invoice To	Item to Bill	Split	Contact / Comment
2235 - ExxonMobil Petroleum & Chemical, BV (Legal Entity: 2235 EXXONMOBIL PETROLEUM & CHEMICAL, BV (2235))	Quantity only	100%	
	Test: Retain sam- ple -90 days	100%	
	Slate: B&S EAME Y2 BTT	100%	
	Test: Retain sam- ple -90 days	100%	
	Slate: B&S EAME Y2 BTT	100%	
	Test: Appearance	100%	
	Test: Odor	100%	
	Slate: B&S EAME Y2 BTT	100%	
	Test: Retain sam- ple -90 days	100%	

NOMINATION COMMENTS

Inspection Appointment:

Load Inspection Checklist Cost Share - 100% EMPC

Inspector to communicate to Operator (Scheduler) if shore line, shore line manifold, or shore tanks not suitable for discharge.

Additional Comments:



Terminals/ Refineries and inspectors to confirm cargo orders and to verify that nominated equipment, cargo, and terminal match are correct for the intended transfer. In the event of ANY discrepancies, please contact scheduler (operator listed above). No transfers shall begin until all discrepancies have been cleared via issuing of new orders.

Framework Agreement Reference:

Activities provided by the Inspection Company under this nomination shall be performed in accordance with ExxonMobil Global Inspection Contract (GIC), effective July 2019 to June 2026, Exhibit C, Schedule E. Please ensure all quality testing is completed at ExxonMobil approved lab unless specified not to. If there are any questions about this, contact the undersigned.

Recipient List:

 $int desk. saynl@corelab.com; saybolt.rotterdam.chemical@corelab.com\\bss.med.scheduling@exxonmobil.com$

REPORT GENERATED 04 FEB 2021