

Region: EAME
Operator: ALEX KETELS (alex.ketels@exxonmobil.com)
Phone:
Mobile:

Other Reference:
Business Group: 4733 - EMAPEU ExxonMobil Asia Pacific Pte. Ltd.
Desk:
Nomination Type: Marine

Documentary Instructions: n/a

LOAD: EMMA (VS00060869) - ROTTERDAM, NL-LIGHTERING (NETHERLANDS)

Inspector: Saybolt
Hub: Europe/Africa/Russia/ME (International Desk Rotterdam)
Coordinator: Cora Ligt (intdesk.saynl@corelab.com)
Local Office: Saybolt Netherlands Rotterdam (Saybolt.Rotterdam.Mineral@corelab.com)

Inspection Status: Accepted
Created On: 17 Sep 2020 by Alex Ketels
Last Modified: 17 Sep 2020 by Cora Ligt

INSPECTION REQUIREMENTS: QUALITY / QUANTITY / TIME LOG

Voyage Parcel External Reference Number: 5028346-10	Contract Number:
Grade: DMA 0.1% DYED	Parcel Ref: 5028330
ETA: 18 Sep 2020	Destination:
ETD:	Source Location:
Supply Contract Window Start: n/a	Supplier:
Supply Contract Window End: n/a	Receiver:
Total Nominated Quantity: 1,000 Metric tonnes	Delivery Terms: FOB (Free On Board)
Transport / Voyage Number / Quantity / Tolerance: EMMA (VS00060869) / 1,000 Metric tonnes	Mother Vessel:

Email Quantity Results To:

marinefuels.benelux@exxonmobil.com; Fuel.Oil.Coordination@exxonmobil.com; PMIVATRADING@exxonmobil.com

Email Quality Results To:

marinefuels.benelux@exxonmobil.com; Fuel.Oil.Coordination@exxonmobil.com;

Load / Discharge Instructions:

Resuesting for quantity and quality.

LOCATION = SHELL KTM

Quality Inspection Instructions:

SET 1

Description:

Sample Location: Barge or Vessel Line Composite Sample

Quality Test Comments:

Also please perform following tests:
 Could not find them in list.

Water by Coulometric ASTM D 6304-07 mg/kg
 Solvent Yellow HPLC mg/L

						RO = Report Only	Req. = Required		
Test	Methods	Min	Max	UOM	Typical	R.O.	Req.	Comment	
Additional Tests									
Density (@15°C)	[ASTM] ASTM D4052			g/cm3		No	No		
5% recovered	[ASTM] ASTM D6352, [ASTM] ASTM D1160			°C		No	No		
Initial Boiling Point	[ASTM] ASTM D86			C		No	No		
Distillation- % Rec'd @ 350C	[ASTM] ASTM D86			Vol %		No	No		

Test	Methods	Min	Max	UOM	Typical	RO = Report Only		Req. = Required		Comment
						R.O.	Req.			
Distillation-% Recd @ 250C	[ASTM] ASTM D86			%		No	No			
Final Boiling Point, degree C	[ASTM] ASTM D86			DegC		No	No			
95% Recovered	[ASTM] ASTM D86			°C		No	No			
90% recovered	[ASTM] ASTM D86			°C		No	No			
70% recovered	[ASTM] ASTM D6352, [ASTM] ASTM D7169			°C		No	No			
50% recovered	[ASTM] ASTM D86			°C		No	No			
30% recovered	[ASTM] ASTM D1160, [ASTM] ASTM D6352			°C		No	No			
10% recovered	[ASTM] ASTM D86			°C		No	No			
FAME	[EN] EN 14078			mg/kg		No	No			
Filter Blocking Tendency	[IP] IP 387			FBT		No	No			
Strong Acid No.	[ASTM] ASTM D664			mgKOH/g		No	No			
Acid Number	[ASTM] ASTM D664			mg KOH/g		No	No			
Cloud Point	[EN] EN 23015			°C		No	No			
CFPP, cold filter plugging point	[EN] EN 116			C		No	No			

Invoice Instructions:

Bill Invoice To	Item to Bill	Split	Contact / Comment
4733 - EMAPEU ExxonMobil Asia Pacific Pte. Ltd. (Legal Entity: 4733 EMAPEU ExxonMobil Asia Pacific Pte. Ltd. (4733))	Quantity only	50%	
	Test: Density (@15°C)	50%	
	Test: 5% recovered	50%	
	Test: Initial Boiling Point	50%	
	Test: Distillation- % Rec'd @ 350C	50%	
	Test: Distillation-% Recd @ 250C	50%	
	Test: Final Boiling Point, degree C	50%	
	Test: 95% Recovered	50%	
	Test: 90% recovered	50%	
	Test: 70% recovered	50%	
	Test: 50% recovered	50%	
	Test: 30% recovered	50%	
	Test: 10% recovered	50%	
	Test: FAME	50%	
	Test: Filter Blocking Tendency	50%	
	Test: Strong Acid No.	50%	
	Test: Acid Number	50%	
	Test: Cloud Point	50%	
	Test: CFPP, cold filter plugging point	50%	
SHELL TRADING ROTTERDAM BV	Quantity only	50%	
	Test: Density (@15°C)	50%	
	Test: 5% recovered	50%	

	Test: Initial Boiling Point	50%	
	Test: Distillation- % Rec'd @ 350C	50%	
	Test: Distillation-% Recd @ 250C	50%	
	Test: Final Boiling Point, degree C	50%	
	Test: 95% Recovered	50%	
	Test: 90% recovered	50%	
	Test: 70% recovered	50%	
	Test: 50% recovered	50%	
	Test: 30% recovered	50%	
	Test: 10% recovered	50%	
	Test: FAME	50%	
	Test: Filter Blocking Tendency	50%	
	Test: Strong Acid No.	50%	
	Test: Acid Number	50%	
	Test: Cloud Point	50%	
	Test: CFPP, cold filter plugging point	50%	

Recipient List:

intdesk.saynl@corelab.com; Saybolt.Rotterdam.Mineral@corelab.com
marinefuels.benelux@exxonmobil.com
supplymovementsebelday12.pmibudapest@exxonmobil.com

REPORT GENERATED 17 SEP 2020