

To Whom It May Concern

This copy is being provided for courtesy purposes only, and does not give any person or company other than our named client a right to rely on these results. No warranties, express or implied, including the warranty of due diligence and care mentioned elsewhere, shall extend to any party other than such named client.



Analysis Report

Report number : 12004/00129672.1/L/21

Main Object : Serenity

Report Date : 22-01-2021

Date of issue : 22-01-2021

Sample object : Serenity

Sample type : Composite

Sample submitted as : EHC 50

Marked : Barge Serenity multiple tank composite prepared from running samples ex C1 , C2 , C3 , C4 , C5 , C6 , C7 , C8 , C9 after loading from Shore tank S582

Composite prep date : 22-01-2021

Place of sampling : Esso Refinery Botlek

Date received : 22-01-2021

Date completed : 22-01-2021

Sample number : 11085246

Composite (11085246)			
SAMPLE NR	OBJECT	DESCRIPTION	RATIO
11084551	Serenity	Barge Serenity C1 running after loading from Shore tank S582	
11084552	Serenity	Barge Serenity C2 running after loading from Shore tank S582	
11084553	Serenity	Barge Serenity C3 running after loading from Shore tank S582	
11084554	Serenity	Barge Serenity C4 running after loading from Shore tank S582	
11084555	Serenity	Barge Serenity C5 running after loading from Shore tank S582	
11084556	Serenity	Barge Serenity C6 running after loading from Shore tank S582	
11084557	Serenity	Barge Serenity C7 running after loading from Shore tank S582	
11084558	Serenity	Barge Serenity C8 running after loading from Shore tank S582	
11084559	Serenity	Barge Serenity C9 running after loading from Shore tank S582	

NAME	METHOD	UNIT	RESULT
Appearance	Visual	-	Clear and Bright
Kinematic Viscosity at 40 °C	ASTM D 445	mm²/s	29.73
Color ASTM	ASTM D 1500	-	L 0.5
Color Saybolt	ASTM D 156	-	+30

Signed by: Corla Lakerveld - Sr Account Manager
Issued by: Saybolt Nederland BV
Place and date of issue: Rotterdam-Botlek - 22-01-2021

All results in this report refer to the sample(s) tested as taken or submitted like specified in this Analysis report. Uncertainties, available on request, apply in the evaluation of the test results. All tests are conducted according to the latest version of the methods, unless another version is specifically indicated. Where available and for convenience purposes, the tested sample has been checked for compliance with supplied specifications, without accepting any liability. In case of dispute or concern, we refer to the interpretation of test results as defined in ASTM D3244, IP 367, ISO 4259 or GOST 33701. This report shall not be partially copied and reproduced without the written permission of the laboratory.