

# GENERAL PHYSICS PH1110

**Nam Le, Dr.**

School of Engineering Physics

Hanoi University of Science and Technology

## 2. THERMODYNAMICS

### 2.3 SECOND LAW OF THERMODYNAMICS

- 1 **STARTING POINTS**
- 2 **POSTULATES OF THE SECOND LAW**
- 3 **HEAT ENGINE**
- 4 **ENTROPY AND STATEMENT OF THE SECOND LAW**
- 5 **CHANGE IN ENTROPY OF AN IDEAL GAS**

## 1. Starting points

## 1. Starting points

- All natural processes obey the first law.

## 1. Starting points

- All natural processes obey the first law. However, there are processes that obey the first law but cannot occur naturally.

## 1. Starting points

- All natural processes obey the first law. However, there are processes that obey the first law but cannot occur naturally.
- The second law deals with these limitations using a new state function, the **entropy**  $S$ .

## 1. Starting points

- All natural processes obey the first law. However, there are processes that obey the first law but cannot occur naturally.
- The second law deals with these limitations using a new state function, the **entropy**  $S$ . It asserts that a natural process runs only in one direction, and is **irreversible**.

## 1. Starting points

- All natural processes obey the first law. However, there are processes that obey the first law but cannot occur naturally.
- The second law deals with these limitations using a new state function, the **entropy**  $S$ . It asserts that a natural process runs only in one direction, and is **irreversible**.
- For example, heat always flows spontaneously from a hotter body to a colder body.



## 1. Starting points

- All natural processes obey the first law. However, there are processes that obey the first law but cannot occur naturally.
- The second law deals with these limitations using a new state function, the **entropy**  $S$ . It asserts that a natural process runs only in one direction, and is **irreversible**.
- For example, heat always flows spontaneously from a hotter body to a colder body. (In order to transfer heat from a colder body to a hotter body, work must be done, or there must be some change in the surrounding environment.)

## 1. Starting points

- All natural processes obey the first law. However, there are processes that obey the first law but cannot occur naturally.
- The second law deals with these limitations using a new state function, the **entropy**  $S$ . It asserts that a natural process runs only in one direction, and is **irreversible**.
- For example, heat always flows spontaneously from a hotter body to a colder body. (In order to transfer heat from a colder body to a hotter body, work must be done, or there must be some change in the surrounding environment.)
- For an **idealized reversible process**,

## 1. Starting points

- All natural processes obey the first law. However, there are processes that obey the first law but cannot occur naturally.
- The second law deals with these limitations using a new state function, the **entropy**  $S$ . It asserts that a natural process runs only in one direction, and is **irreversible**.
- For example, heat always flows spontaneously from a hotter body to a colder body. (In order to transfer heat from a colder body to a hotter body, work must be done, or there must be some change in the surrounding environment.)
- For an **idealized reversible process**, the entropy change obeys an equality and can be calculated.

## 1. Starting points

- All natural processes obey the first law. However, there are processes that obey the first law but cannot occur naturally.
- The second law deals with these limitations using a new state function, the **entropy**  $S$ . It asserts that a natural process runs only in one direction, and is **irreversible**.
- For example, heat always flows spontaneously from a hotter body to a colder body. (In order to transfer heat from a colder body to a hotter body, work must be done, or there must be some change in the surrounding environment.)
- For an **idealized reversible process**, the entropy change obeys an equality and can be calculated. That is why it is important even though it is a hypothetical process.

## 2. THERMODYNAMICS

### 2.3 SECOND LAW OF THERMODYNAMICS

- 1 **STARTING POINTS**
- 2 **POSTULATES OF THE SECOND LAW**
- 3 **HEAT ENGINE**
- 4 **ENTROPY AND STATEMENT OF THE SECOND LAW**
- 5 **CHANGE IN ENTROPY OF AN IDEAL GAS**

## 2. Postulates of the second law

## 2. Postulates of the second law

### ♣ Postulate of Clausius

## 2. Postulates of the second law

### ♣ Postulate of Clausius

A transformation whose only final result is to transfer heat from a body at a given temperature to a body at a higher temperature is impossible.



## 2. Postulates of the second law

### ♣ Postulate of Clausius

A transformation whose only final result is to transfer heat from a body at a given temperature to a body at a higher temperature is impossible.

### ♣ Postulate of Kelvin

## 2. Postulates of the second law

### ♣ Postulate of Clausius

A transformation whose only final result is to transfer heat from a body at a given temperature to a body at a higher temperature is impossible.

### ♣ Postulate of Kelvin

A transformation whose only final result is to transfer into work heat extracted from a source which is at the same temperature throughout is impossible.

## 2. Postulates of the second law

### ♣ Postulate of Clausius

A transformation whose only final result is to transfer heat from a body at a given temperature to a body at a higher temperature is impossible.

### ♣ Postulate of Kelvin

A transformation whose only final result is to transfer into work heat extracted from a source which is at the same temperature throughout is impossible.

- The two postulates were shown to be equivalent by Fermi.

## 2. THERMODYNAMICS

### 2.3 SECOND LAW OF THERMODYNAMICS

- 1 **STARTING POINTS**
- 2 **POSTULATES OF THE SECOND LAW**
- 3 **HEAT ENGINE**
- 4 **ENTROPY AND STATEMENT OF THE SECOND LAW**
- 5 **CHANGE IN ENTROPY OF AN IDEAL GAS**

### 3. Heat engine

### 3. Heat engine

Heat engine is

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy,

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.



### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

♣ A heat engine consists of

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**,

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**,

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.
- It works periodically.

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.
- It works periodically. In each cycle, the working substance takes a heat  $Q_1$  from the heat source,

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.
- It works periodically. In each cycle, the working substance takes a heat  $Q_1$  from the heat source, does a work  $W'$ ,

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.
- It works periodically. In each cycle, the working substance takes a heat  $Q_1$  from the heat source, does a work  $W'$ , and transfers a heat  $Q'_2$  to the colder sink.



### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.
- It works periodically. In each cycle, the working substance takes a heat  $Q_1$  from the heat source, does a work  $W'$ , and transfers a heat  $Q'_2$  to the colder sink.

$$\Delta U = 0$$

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.
- It works periodically. In each cycle, the working substance takes a heat  $Q_1$  from the heat source, does a work  $W'$ , and transfers a heat  $Q'_2$  to the colder sink.

$$\Delta U = 0 \quad \rightarrow \quad 0 + W' + (Q'_2 - Q_1) = 0$$

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.
- It works periodically. In each cycle, the working substance takes a heat  $Q_1$  from the heat source, does a work  $W'$ , and transfers a heat  $Q'_2$  to the colder sink.

$$\Delta U = 0 \quad \rightarrow \quad 0 + W' + (Q'_2 - Q_1) = 0 \quad \rightarrow \quad W' = Q_1 - Q'_2$$

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.

- It works periodically. In each cycle, the working substance takes a heat  $Q_1$  from the heat source, does a work  $W'$ , and transfers a heat  $Q'_2$  to the colder sink.

$$\Delta U = 0 \quad \rightarrow \quad 0 + W' + (Q'_2 - Q_1) = 0 \quad \rightarrow \quad W' = Q_1 - Q'_2$$

- Its efficiency:

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.
- It works periodically. In each cycle, the working substance takes a heat  $Q_1$  from the heat source, does a work  $W'$ , and transfers a heat  $Q'_2$  to the colder sink.

$$\Delta U = 0 \quad \rightarrow \quad 0 + W' + (Q'_2 - Q_1) = 0 \quad \rightarrow \quad W' = Q_1 - Q'_2$$

- Its efficiency:

$$\eta = \frac{W'}{Q_1}$$

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.
- It works periodically. In each cycle, the working substance takes a heat  $Q_1$  from the heat source, does a work  $W'$ , and transfers a heat  $Q'_2$  to the colder sink.

$$\Delta U = 0 \quad \rightarrow \quad 0 + W' + (Q'_2 - Q_1) = 0 \quad \rightarrow \quad W' = Q_1 - Q'_2$$

- Its efficiency:

$$\eta = \frac{W'}{Q_1} = \frac{Q_1 - Q'_2}{Q_1}$$

### 3. Heat engine

Heat engine is a system that converts thermal energy to mechanical energy, which can then be used to do work.

- ♣ A heat engine consists of a **working substance**, a **heat source**, and a **colder sink**.
- It works periodically. In each cycle, the working substance takes a heat  $Q_1$  from the heat source, does a work  $W'$ , and transfers a heat  $Q'_2$  to the colder sink.

$$\Delta U = 0 \quad \rightarrow \quad 0 + W' + (Q'_2 - Q_1) = 0 \quad \rightarrow \quad W' = Q_1 - Q'_2$$

- Its efficiency:

$$\eta = \frac{W'}{Q_1} = \frac{Q_1 - Q'_2}{Q_1} \quad \rightarrow \quad \boxed{\eta = 1 - \frac{Q'_2}{Q_1}}$$

### 3. Heat engine

♣ **Carnot heat engine** (a theoretical engine)



### 3. Heat engine

- ♣ **Carnot heat engine** (a theoretical engine)
  - It operates on the **Carnot cycles**.

### 3. Heat engine

- ♣ **Carnot heat engine** (a theoretical engine)
  - It operates on the **Carnot cycles**. Each cycle consists of two isothermal processes

### 3. Heat engine

♣ **Carnot heat engine** (a theoretical engine)

- It operates on the **Carnot cycles**. Each cycle consists of two isothermal processes and two reversible adiabatic processes.

### 3. Heat engine

♣ **Carnot heat engine** (a theoretical engine)

- It operates on the **Carnot cycles**. Each cycle consists of two isothermal processes and two reversible adiabatic processes. We first consider when the working substance is an ideal gas.

### 3. Heat engine

♣ **Carnot heat engine** (a theoretical engine)

- It operates on the **Carnot cycles**. Each cycle consists of two isothermal processes and two reversible adiabatic processes. We first consider when the working substance is an ideal gas.
  - ▷ Heat  $Q_1$

### 3. Heat engine

#### ♣ **Carnot heat engine** (a theoretical engine)

- It operates on the **Carnot cycles**. Each cycle consists of two isothermal processes and two reversible adiabatic processes. We first consider when the working substance is an ideal gas.
  - ▶ Heat  $Q_1$  is absorbed from the heat source (temperature  $T_1$ ) during the isothermal expansion  $1 \rightarrow 2$ :

### 3. Heat engine

#### ♣ **Carnot heat engine** (a theoretical engine)

- It operates on the **Carnot cycles**. Each cycle consists of two isothermal processes and two reversible adiabatic processes. We first consider when the working substance is an ideal gas.
- ▶ Heat  $Q_1$  is absorbed from the heat source (temperature  $T_1$ ) during the isothermal expansion  $1 \rightarrow 2$ :

$$Q_1 = \frac{m}{\mu} R T_1 \ln \frac{V_2}{V_1}$$

### 3. Heat engine

#### ♣ **Carnot heat engine** (a theoretical engine)

- It operates on the **Carnot cycles**. Each cycle consists of two isothermal processes and two reversible adiabatic processes. We first consider when the working substance is an ideal gas.
- ▶ Heat  $Q_1$  is absorbed from the heat source (temperature  $T_1$ ) during the isothermal expansion  $1 \rightarrow 2$ :

$$Q_1 = \frac{m}{\mu} RT_1 \ln \frac{V_2}{V_1}$$

- ▶ Heat  $Q'_2$  is transferred to the colder sink (temperature  $T_2$ ) during the isothermal compression  $3 \rightarrow 4$ :



### 3. Heat engine

#### ♣ **Carnot heat engine** (a theoretical engine)

- It operates on the **Carnot cycles**. Each cycle consists of two isothermal processes and two reversible adiabatic processes. We first consider when the working substance is an ideal gas.
- Heat  $Q_1$  is absorbed from the heat source (temperature  $T_1$ ) during the isothermal expansion  $1 \rightarrow 2$ :

$$Q_1 = \frac{m}{\mu} RT_1 \ln \frac{V_2}{V_1}$$

- Heat  $Q'_2$  is transferred to the colder sink (temperature  $T_2$ ) during the isothermal compression  $3 \rightarrow 4$ :

$$Q'_2 = \frac{m}{\mu} RT_2 \ln \frac{V_3}{V_4}$$

### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :

### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$

### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$
- ▶ In the adiabatic compression  $4 \rightarrow 1$ :

### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$
- ▶ In the adiabatic compression  $4 \rightarrow 1$ :  $T_1 V_1^{\gamma-1} = T_2 V_4^{\gamma-1}$

### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$
- ▶ In the adiabatic compression  $4 \rightarrow 1$ :  $T_1 V_1^{\gamma-1} = T_2 V_4^{\gamma-1}$

$$Q_1 = \frac{m}{\mu} R T_1 \ln \frac{V_2}{V_1}, \quad Q'_2 = \frac{m}{\mu} R T_2 \ln \frac{V_3}{V_4},$$

### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$
- ▶ In the adiabatic compression  $4 \rightarrow 1$ :  $T_1 V_1^{\gamma-1} = T_2 V_4^{\gamma-1}$

$$Q_1 = \frac{m}{\mu} R T_1 \ln \frac{V_2}{V_1}, \quad Q'_2 = \frac{m}{\mu} R T_2 \ln \frac{V_3}{V_4}, \quad \frac{V_2}{V_1} = \frac{V_3}{V_4}$$

### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$
- ▶ In the adiabatic compression  $4 \rightarrow 1$ :  $T_1 V_1^{\gamma-1} = T_2 V_4^{\gamma-1}$

$$Q_1 = \frac{m}{\mu} R T_1 \ln \frac{V_2}{V_1}, \quad Q'_2 = \frac{m}{\mu} R T_2 \ln \frac{V_3}{V_4}, \quad \frac{V_2}{V_1} = \frac{V_3}{V_4}$$

- Efficiency:



### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$
- ▶ In the adiabatic compression  $4 \rightarrow 1$ :  $T_1 V_1^{\gamma-1} = T_2 V_4^{\gamma-1}$

$$Q_1 = \frac{m}{\mu} R T_1 \ln \frac{V_2}{V_1}, \quad Q'_2 = \frac{m}{\mu} R T_2 \ln \frac{V_3}{V_4}, \quad \frac{V_2}{V_1} = \frac{V_3}{V_4}$$

- Efficiency:  $\eta = 1 - \frac{Q'_2}{Q_1}$

## 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$
- ▶ In the adiabatic compression  $4 \rightarrow 1$ :  $T_1 V_1^{\gamma-1} = T_2 V_4^{\gamma-1}$

$$Q_1 = \frac{m}{\mu} R T_1 \ln \frac{V_2}{V_1}, \quad Q'_2 = \frac{m}{\mu} R T_2 \ln \frac{V_3}{V_4}, \quad \frac{V_2}{V_1} = \frac{V_3}{V_4}$$

- Efficiency:  $\eta = 1 - \frac{Q'_2}{Q_1} \rightarrow \boxed{\eta = 1 - \frac{T_2}{T_1}}$

### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$
- ▶ In the adiabatic compression  $4 \rightarrow 1$ :  $T_1 V_1^{\gamma-1} = T_2 V_4^{\gamma-1}$

$$Q_1 = \frac{m}{\mu} R T_1 \ln \frac{V_2}{V_1}, \quad Q'_2 = \frac{m}{\mu} R T_2 \ln \frac{V_3}{V_4}, \quad \frac{V_2}{V_1} = \frac{V_3}{V_4}$$

- Efficiency:  $\eta = 1 - \frac{Q'_2}{Q_1} \rightarrow \boxed{\eta = 1 - \frac{T_2}{T_1}}$
- So, in the case of an ideal gas,

### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$
- ▶ In the adiabatic compression  $4 \rightarrow 1$ :  $T_1 V_1^{\gamma-1} = T_2 V_4^{\gamma-1}$

$$Q_1 = \frac{m}{\mu} R T_1 \ln \frac{V_2}{V_1}, \quad Q'_2 = \frac{m}{\mu} R T_2 \ln \frac{V_3}{V_4}, \quad \frac{V_2}{V_1} = \frac{V_3}{V_4}$$

- Efficiency:  $\eta = 1 - \frac{Q'_2}{Q_1} \rightarrow \boxed{\eta = 1 - \frac{T_2}{T_1}}$
- So, in the case of an ideal gas, the efficiency of a reversible Carnot cycle depends only on the temperatures of the heat source and the colder sink.

### 3. Heat engine

- ▶ In the adiabatic expansion  $2 \rightarrow 3$ :  $T_1 V_2^{\gamma-1} = T_2 V_3^{\gamma-1}$
- ▶ In the adiabatic compression  $4 \rightarrow 1$ :  $T_1 V_1^{\gamma-1} = T_2 V_4^{\gamma-1}$

$$Q_1 = \frac{m}{\mu} R T_1 \ln \frac{V_2}{V_1}, \quad Q'_2 = \frac{m}{\mu} R T_2 \ln \frac{V_3}{V_4}, \quad \frac{V_2}{V_1} = \frac{V_3}{V_4}$$

- Efficiency:  $\eta = 1 - \frac{Q'_2}{Q_1} \rightarrow \boxed{\eta = 1 - \frac{T_2}{T_1}}$
- So, in the case of an ideal gas, the efficiency of a reversible Carnot cycle depends only on the temperatures of the heat source and the colder sink. However, Carnot stated that this applies for any working substance.

### 3. Heat engine

#### ♣ Carnot's theorem

### 3. Heat engine

#### ♣ Carnot's theorem

The efficiency of a Carnot engine depends solely on the temperatures of the hot and cold reservoirs.

### 3. Heat engine

#### ♣ Carnot's theorem

The efficiency of a Carnot engine depends solely on the temperatures of the hot and cold reservoirs. It is the maximum efficiency any heat engine can obtain.



### 3. Heat engine

#### ♣ Carnot's theorem

The efficiency of a Carnot engine depends solely on the temperatures of the hot and cold reservoirs. It is the maximum efficiency any heat engine can obtain.

- **Proof:**

### 3. Heat engine

#### ♣ Carnot's theorem

The efficiency of a Carnot engine depends solely on the temperatures of the hot and cold reservoirs. It is the maximum efficiency any heat engine can obtain.

- **Proof:** Consider the hybrid engine of any two Carnot engines working between the same hot and cold reservoirs.

### 3. Heat engine

#### ♣ Carnot's theorem

The efficiency of a Carnot engine depends solely on the temperatures of the hot and cold reservoirs. It is the maximum efficiency any heat engine can obtain.

- **Proof:** Consider the hybrid engine of any two Carnot engines working between the same hot and cold reservoirs.

$$\eta_1 = 1 - \frac{Q'_{2a}}{Q_1}, \quad \eta_2 = 1 - \frac{Q'_{2b}}{Q_1}$$

### 3. Heat engine

#### ♣ Carnot's theorem

The efficiency of a Carnot engine depends solely on the temperatures of the hot and cold reservoirs. It is the maximum efficiency any heat engine can obtain.

- **Proof:** Consider the hybrid engine of any two Carnot engines working between the same hot and cold reservoirs.

$$\eta_1 = 1 - \frac{Q'_{2a}}{Q_1}, \quad \eta_2 = 1 - \frac{Q'_{2b}}{Q_1}$$

- According to the postulate of Kelvin,

### 3. Heat engine

#### ♣ Carnot's theorem

The efficiency of a Carnot engine depends solely on the temperatures of the hot and cold reservoirs. It is the maximum efficiency any heat engine can obtain.

- **Proof:** Consider the hybrid engine of any two Carnot engines working between the same hot and cold reservoirs.

$$\eta_1 = 1 - \frac{Q'_{2a}}{Q_1}, \quad \eta_2 = 1 - \frac{Q'_{2b}}{Q_1}$$

- According to the postulate of Kelvin, it is impossible that

$$Q'_{2a} < Q'_{2b} \quad \text{or} \quad Q'_{2a} > Q'_{2b}$$

### 3. Heat engine

#### ♣ Carnot's theorem

The efficiency of a Carnot engine depends solely on the temperatures of the hot and cold reservoirs. It is the maximum efficiency any heat engine can obtain.

- **Proof:** Consider the hybrid engine of any two Carnot engines working between the same hot and cold reservoirs.

$$\eta_1 = 1 - \frac{Q'_{2a}}{Q_1}, \quad \eta_2 = 1 - \frac{Q'_{2b}}{Q_1}$$

- According to the postulate of Kelvin, it is impossible that

$$Q'_{2a} < Q'_{2b} \quad \text{or} \quad Q'_{2a} > Q'_{2b} \quad \Rightarrow \quad Q'_{2a} = Q'_{2b}$$

### 3. Heat engine

#### ♣ Carnot's theorem

The efficiency of a Carnot engine depends solely on the temperatures of the hot and cold reservoirs. It is the maximum efficiency any heat engine can obtain.

- **Proof:** Consider the hybrid engine of any two Carnot engines working between the same hot and cold reservoirs.

$$\eta_1 = 1 - \frac{Q'_{2a}}{Q_1}, \quad \eta_2 = 1 - \frac{Q'_{2b}}{Q_1}$$

- According to the postulate of Kelvin, it is impossible that

$$Q'_{2a} < Q'_{2b} \quad \text{or} \quad Q'_{2a} > Q'_{2b} \quad \Rightarrow \quad Q'_{2a} = Q'_{2b} \quad \Rightarrow \quad \boxed{\eta_1 = \eta_2}$$

## 2. THERMODYNAMICS

### 2.3 SECOND LAW OF THERMODYNAMICS

- 1 STARTING POINTS
- 2 POSTULATES OF THE SECOND LAW
- 3 HEAT ENGINE
- 4 ENTROPY AND STATEMENT OF THE SECOND LAW
- 5 CHANGE IN ENTROPY OF AN IDEAL GAS



## 4. Entropy and statement of the second law

## 4. Entropy and statement of the second law

The entropy  $S$  of a system is defined by

## 4. Entropy and statement of the second law

The entropy  $S$  of a system is defined by

$$dS = \frac{\delta Q}{T} \quad - \quad \text{in a reversible process}$$

## 4. Entropy and statement of the second law

The entropy  $S$  of a system is defined by

$$dS = \frac{\delta Q}{T} \quad - \quad \text{in a reversible process}$$

- For an irreversible process:

## 4. Entropy and statement of the second law

The entropy  $S$  of a system is defined by

$$dS = \frac{\delta Q}{T} \quad - \quad \text{in a reversible process}$$

- For an irreversible process:

$$\frac{\delta Q}{T} < dS$$

## 4. Entropy and statement of the second law

The entropy  $S$  of a system is defined by

$$dS = \frac{\delta Q}{T} \quad - \quad \text{in a reversible process}$$

- For an irreversible process:

$$\frac{\delta Q}{T} < dS$$

- Entropy is a state function:

## 4. Entropy and statement of the second law

The entropy  $S$  of a system is defined by

$$dS = \frac{\delta Q}{T} \quad - \quad \text{in a reversible process}$$

- For an irreversible process:

$$\frac{\delta Q}{T} < dS$$

- Entropy is a state function:

$$\Delta S \equiv S_2 - S_1 = \int_1^2 dS$$

## 4. Entropy and statement of the second law

The entropy  $S$  of a system is defined by

$$dS = \frac{\delta Q}{T} \quad - \quad \text{in a reversible process}$$

- For an irreversible process:

$$\frac{\delta Q}{T} < dS$$

- Entropy is a state function:

$$\Delta S \equiv S_2 - S_1 = \int_1^2 dS$$

- Entropy of a system is equal to the sum of entropies of all of its subsystems.



## 4. Entropy and statement of the second law

- According to the Carnot's theorem:

## 4. Entropy and statement of the second law

- According to the Carnot's theorem:

$$1 - \frac{Q'_2}{Q_1} \leq 1 - \frac{T_2}{T_1}$$

## 4. Entropy and statement of the second law

- According to the Carnot's theorem:

$$1 - \frac{Q'_2}{Q_1} \leq 1 - \frac{T_2}{T_1} \quad \rightarrow \quad \frac{Q_1}{T_1} \leq \frac{Q'_2}{T_2}$$

## 4. Entropy and statement of the second law

- According to the Carnot's theorem:

$$1 - \frac{Q'_2}{Q_1} \leq 1 - \frac{T_2}{T_1} \quad \rightarrow \quad \frac{Q_1}{T_1} \leq \frac{Q'_2}{T_2} \quad \rightarrow \quad \boxed{\frac{Q_1}{T_1} + \frac{Q_2}{T_2} \leq 0}$$

## 4. Entropy and statement of the second law

- According to the Carnot's theorem:

$$1 - \frac{Q'_2}{Q_1} \leq 1 - \frac{T_2}{T_1} \quad \rightarrow \quad \frac{Q_1}{T_1} \leq \frac{Q'_2}{T_2} \quad \rightarrow \quad \boxed{\frac{Q_1}{T_1} + \frac{Q_2}{T_2} \leq 0}$$

- For a cycle of  $n$  isothermal processes in alternate between  $n$  adiabatic processes:

## 4. Entropy and statement of the second law

- According to the Carnot's theorem:

$$1 - \frac{Q_2'}{Q_1} \leq 1 - \frac{T_2}{T_1} \quad \rightarrow \quad \frac{Q_1}{T_1} \leq \frac{Q_2'}{T_2} \quad \rightarrow \quad \boxed{\frac{Q_1}{T_1} + \frac{Q_2}{T_2} \leq 0}$$

- For a cycle of  $n$  isothermal processes in alternate between  $n$  adiabatic processes:

$$\frac{Q_1}{T_1} + \frac{Q_2}{T_2} + \dots + \frac{Q_n}{T_n} \leq 0$$

## 4. Entropy and statement of the second law

- According to the Carnot's theorem:

$$1 - \frac{Q_2'}{Q_1} \leq 1 - \frac{T_2}{T_1} \quad \rightarrow \quad \frac{Q_1}{T_1} \leq \frac{Q_2'}{T_2} \quad \rightarrow \quad \boxed{\frac{Q_1}{T_1} + \frac{Q_2}{T_2} \leq 0}$$

- For a cycle of  $n$  isothermal processes in alternate between  $n$  adiabatic processes:

$$\frac{Q_1}{T_1} + \frac{Q_2}{T_2} + \dots + \frac{Q_n}{T_n} \leq 0 \quad \text{or} \quad \boxed{\sum_{i=1}^n \frac{Q_i}{T_i} \leq 0}$$

## 4. Entropy and statement of the second law

- According to the Carnot's theorem:

$$1 - \frac{Q'_2}{Q_1} \leq 1 - \frac{T_2}{T_1} \quad \rightarrow \quad \frac{Q_1}{T_1} \leq \frac{Q'_2}{T_2} \quad \rightarrow \quad \boxed{\frac{Q_1}{T_1} + \frac{Q_2}{T_2} \leq 0}$$

- For a cycle of  $n$  isothermal processes in alternate between  $n$  adiabatic processes:

$$\frac{Q_1}{T_1} + \frac{Q_2}{T_2} + \dots + \frac{Q_n}{T_n} \leq 0 \quad \text{or} \quad \boxed{\sum_{i=1}^n \frac{Q_i}{T_i} \leq 0}$$

- An arbitrary cycle corresponds to the case of  $n \rightarrow \infty$ :



## 4. Entropy and statement of the second law

- According to the Carnot's theorem:

$$1 - \frac{Q'_2}{Q_1} \leq 1 - \frac{T_2}{T_1} \quad \rightarrow \quad \frac{Q_1}{T_1} \leq \frac{Q'_2}{T_2} \quad \rightarrow \quad \boxed{\frac{Q_1}{T_1} + \frac{Q_2}{T_2} \leq 0}$$

- For a cycle of  $n$  isothermal processes in alternate between  $n$  adiabatic processes:

$$\frac{Q_1}{T_1} + \frac{Q_2}{T_2} + \dots + \frac{Q_n}{T_n} \leq 0 \quad \text{or} \quad \boxed{\sum_{i=1}^n \frac{Q_i}{T_i} \leq 0}$$

- An arbitrary cycle corresponds to the case of  $n \rightarrow \infty$ :

$$\boxed{\oint_{1a2b1} \frac{\delta Q}{T} \leq 0}$$

## 4. Entropy and statement of the second law

- According to the Carnot's theorem:

$$1 - \frac{Q_2'}{Q_1} \leq 1 - \frac{T_2}{T_1} \quad \rightarrow \quad \frac{Q_1}{T_1} \leq \frac{Q_2'}{T_2} \quad \rightarrow \quad \boxed{\frac{Q_1}{T_1} + \frac{Q_2}{T_2} \leq 0}$$

- For a cycle of  $n$  isothermal processes in alternate between  $n$  adiabatic processes:

$$\frac{Q_1}{T_1} + \frac{Q_2}{T_2} + \dots + \frac{Q_n}{T_n} \leq 0 \quad \text{or} \quad \boxed{\sum_{i=1}^n \frac{Q_i}{T_i} \leq 0}$$

- An arbitrary cycle corresponds to the case of  $n \rightarrow \infty$ :

$$\boxed{\oint_{1a2b1} \frac{\delta Q}{T} \leq 0} \quad \left\{ \begin{array}{l} \text{'equal' for reversible cycles} \\ \text{'less than' for irreversible cycles} \end{array} \right.$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T}$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS + \int_{\widehat{2b1}} dS$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS}$$



## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS} \quad (\text{path independent/state function})$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS} \quad (\text{path independent/state function})$$

- If the cycle is irreversible in the  $\widehat{1a2}$  process

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS} \quad (\text{path independent/state function})$$

- If the cycle is irreversible in the  $\widehat{1a2}$  process and is reversible in the  $\widehat{2b1}$  process:

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS} \quad (\text{path independent/state function})$$

- If the cycle is irreversible in the  $\widehat{1a2}$  process and is reversible in the  $\widehat{2b1}$  process:

$$0 > \oint_{\widehat{1a2b1}} \frac{\delta Q}{T}$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS} \quad (\text{path independent/state function})$$

- If the cycle is irreversible in the  $\widehat{1a2}$  process and is reversible in the  $\widehat{2b1}$  process:

$$0 > \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \frac{\delta Q}{T} + \int_{\widehat{2b1}} \frac{\delta Q}{T}$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS} \quad (\text{path independent/state function})$$

- If the cycle is irreversible in the  $\widehat{1a2}$  process and is reversible in the  $\widehat{2b1}$  process:

$$0 > \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \frac{\delta Q}{T} + \int_{\widehat{2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \frac{\delta Q}{T} + \int_{\widehat{2b1}} dS$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS} \quad (\text{path independent/state function})$$

- If the cycle is irreversible in the  $\widehat{1a2}$  process and is reversible in the  $\widehat{2b1}$  process:

$$0 > \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \frac{\delta Q}{T} + \int_{\widehat{2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \frac{\delta Q}{T} - \int_{\widehat{1b2}} dS$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS} \quad (\text{path independent/state function})$$

- If the cycle is irreversible in the  $\widehat{1a2}$  process and is reversible in the  $\widehat{2b1}$  process:

$$0 > \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \frac{\delta Q}{T} + \int_{\widehat{2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \frac{\delta Q}{T} - \int_{\widehat{1a2}} dS$$



## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS} \quad (\text{path independent/state function})$$

- If the cycle is irreversible in the  $\widehat{1a2}$  process and is reversible in the  $\widehat{2b1}$  process:

$$0 > \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \frac{\delta Q}{T} + \int_{\widehat{2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \left( \frac{\delta Q}{T} - dS \right)$$

## 4. Entropy and statement of the second law

- Consider a reversible cycle  $\widehat{1a2b1}$ :

$$0 = \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \oint_{\widehat{1a2b1}} dS = \int_{\widehat{1a2}} dS - \int_{\widehat{1b2}} dS$$

$$\boxed{\int_{\widehat{1a2}} dS = \int_{\widehat{1b2}} dS} \quad (\text{path independent/state function})$$

- If the cycle is irreversible in the  $\widehat{1a2}$  process and is reversible in the  $\widehat{2b1}$  process:

$$0 > \oint_{\widehat{1a2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \frac{\delta Q}{T} + \int_{\widehat{2b1}} \frac{\delta Q}{T} = \int_{\widehat{1a2}} \left( \frac{\delta Q}{T} - dS \right)$$

- So, for an irreversible process:

$$\boxed{\frac{\delta Q}{T} < dS}$$

## 4. Entropy and statement of the second law

### ♣ Summary

## 4. Entropy and statement of the second law

### ♣ Summary

$$\frac{\delta Q}{T} \leq dS$$

## 4. Entropy and statement of the second law

### ♣ Summary

$$\boxed{\frac{\delta Q}{T} \leq dS} \quad \left\{ \begin{array}{l} \text{'equal' for reversible processes;} \\ \text{'less than' for irreversible processes} \end{array} \right.$$

## 4. Entropy and statement of the second law

### ♣ Summary

$$\boxed{\frac{\delta Q}{T} \leq dS} \quad \left\{ \begin{array}{l} \text{'equal' for reversible processes;} \\ \text{'less than' for irreversible processes} \end{array} \right.$$

- For an isolated system:

## 4. Entropy and statement of the second law

### ♣ Summary

$$\boxed{\frac{\delta Q}{T} \leq dS} \quad \left\{ \begin{array}{l} \text{'equal' for reversible processes;} \\ \text{'less than' for irreversible processes} \end{array} \right.$$

- For an isolated system:  $\boxed{dS \geq 0}$

## 4. Entropy and statement of the second law

### ♣ Summary

$$\boxed{\frac{\delta Q}{T} \leq dS} \quad \left\{ \begin{array}{l} \text{'equal' for reversible processes;} \\ \text{'less than' for irreversible processes} \end{array} \right.$$

- For an isolated system:  $\boxed{dS \geq 0}$ 
  - ▶  $dS > 0$  when there are irreversible processes in the system,



## 4. Entropy and statement of the second law

### ♣ Summary

$$\boxed{\frac{\delta Q}{T} \leq dS} \quad \left\{ \begin{array}{l} \text{'equal' for reversible processes;} \\ \text{'less than' for irreversible processes} \end{array} \right.$$

- For an isolated system:  $\boxed{dS \geq 0}$ 
  - ▶  $dS > 0$  when there are irreversible processes in the system, that is when the system is evolving.

## 4. Entropy and statement of the second law

### ♣ Summary

$$\boxed{\frac{\delta Q}{T} \leq dS} \quad \left\{ \begin{array}{l} \text{'equal' for reversible processes;} \\ \text{'less than' for irreversible processes} \end{array} \right.$$

- For an isolated system:  $\boxed{dS \geq 0}$ 
  - ▶  $dS > 0$  when there are irreversible processes in the system, that is when the system is evolving.
  - ▶  $dS = 0$ , or  $S$  reaches its maximum constant value,

## 4. Entropy and statement of the second law

## ♣ Summary

$$\boxed{\frac{\delta Q}{T} \leq dS} \quad \left\{ \begin{array}{l} \text{'equal' for reversible processes;} \\ \text{'less than' for irreversible processes} \end{array} \right.$$

- For an isolated system:  $\boxed{dS \geq 0}$ 
  - ▷  $dS > 0$  when there are irreversible processes in the system, that is when the system is evolving.
  - ▷  $dS = 0$ , or  $S$  reaches its maximum constant value, when all internal processes are reversible,

## 4. Entropy and statement of the second law

### ♣ Summary

$$\boxed{\frac{\delta Q}{T} \leq dS} \quad \left\{ \begin{array}{l} \text{'equal' for reversible processes;} \\ \text{'less than' for irreversible processes} \end{array} \right.$$

- For an isolated system:  $\boxed{dS \geq 0}$ 
  - ▶  $dS > 0$  when there are irreversible processes in the system, that is when the system is evolving.
  - ▶  $dS = 0$ , or  $S$  reaches its maximum constant value, when all internal processes are reversible, that is when the system is at its thermodynamic equilibrium state.

## 4. Entropy and statement of the second law

### ♣ Second law of thermodynamics

## 4. Entropy and statement of the second law

### ♣ Second law of thermodynamics

The total entropy of an isolated system can never decrease over time, and is constant if and only if all processes within the system are reversible.

## 4. Entropy and statement of the second law

### ♣ Second law of thermodynamics

The total entropy of an isolated system can never decrease over time, and is constant if and only if all processes within the system are reversible. Isolated systems spontaneously evolve towards thermodynamic equilibrium, the state with maximum entropy.

## 2. THERMODYNAMICS

### 2.3 SECOND LAW OF THERMODYNAMICS

- 1 STARTING POINTS
- 2 POSTULATES OF THE SECOND LAW
- 3 HEAT ENGINE
- 4 ENTROPY AND STATEMENT OF THE SECOND LAW
- 5 CHANGE IN ENTROPY OF AN IDEAL GAS



## 5. Change in entropy of an ideal gas

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0$$

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0$$

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad S = \text{constant}$$

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad S = \text{constant}$$

- In an isothermal process:

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad S = \text{constant}$$

- In an isothermal process:

$$T = \text{constant}$$

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad \boxed{S = \text{constant}}$$

- In an isothermal process:

$$T = \text{constant} \quad \rightarrow \quad \Delta S = \int_1^2 dS$$



## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad \boxed{S = \text{constant}}$$

- In an isothermal process:

$$T = \text{constant} \quad \rightarrow \quad \Delta S = \int_1^2 dS = \frac{1}{T} \int_{\widehat{12}} \delta Q$$

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad \boxed{S = \text{constant}}$$

- In an isothermal process:

$$T = \text{constant} \quad \rightarrow \quad \Delta S = \int_1^2 dS = \frac{1}{T} \int_{\widehat{12}} \delta Q = \frac{Q}{T}$$

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad \boxed{S = \text{constant}}$$

- In an isothermal process:

$$T = \text{constant} \quad \rightarrow \quad \Delta S = \int_1^2 dS = \frac{1}{T} \int_{\widehat{12}} \delta Q = \frac{Q}{T}$$

- ▶ Heat added to the system in the isothermal process:

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad \boxed{S = \text{constant}}$$

- In an isothermal process:

$$T = \text{constant} \quad \rightarrow \quad \Delta S = \int_1^2 dS = \frac{1}{T} \int_{\widehat{12}} \delta Q = \frac{Q}{T}$$

- ▶ Heat added to the system in the isothermal process:

$$Q = \frac{m}{\mu} RT \ln \frac{V_2}{V_1}$$

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad \boxed{S = \text{constant}}$$

- In an isothermal process:

$$T = \text{constant} \quad \rightarrow \quad \Delta S = \int_1^2 dS = \frac{1}{T} \int_{\widehat{12}} \delta Q = \frac{Q}{T}$$

- ▶ Heat added to the system in the isothermal process:

$$Q = \frac{m}{\mu} RT \ln \frac{V_2}{V_1} = \frac{m}{\mu} RT \ln \frac{p_1}{p_2}$$

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad \boxed{S = \text{constant}}$$

- In an isothermal process:

$$T = \text{constant} \quad \rightarrow \quad \Delta S = \int_1^2 dS = \frac{1}{T} \int_{\widehat{12}} \delta Q = \frac{Q}{T}$$

- Heat added to the system in the isothermal process:

$$Q = \frac{m}{\mu} RT \ln \frac{V_2}{V_1} = \frac{m}{\mu} RT \ln \frac{p_1}{p_2}$$

- Therefore:

## 5. Change in entropy of an ideal gas

- In an adiabatic process:

$$\delta Q = 0 \quad \rightarrow \quad dS = 0 \quad \rightarrow \quad \boxed{S = \text{constant}}$$

- In an isothermal process:

$$T = \text{constant} \quad \rightarrow \quad \Delta S = \int_1^2 dS = \frac{1}{T} \int_{\widehat{12}} \delta Q = \frac{Q}{T}$$

- ▶ Heat added to the system in the isothermal process:

$$Q = \frac{m}{\mu} RT \ln \frac{V_2}{V_1} = \frac{m}{\mu} RT \ln \frac{p_1}{p_2}$$

- ▶ Therefore:

$$\boxed{\Delta S = \frac{m}{\mu} R \ln \frac{V_2}{V_1} = \frac{m}{\mu} R \ln \frac{p_1}{p_2}}$$

## 5. Change in entropy of an ideal gas

- For an arbitrary process:



## 5. Change in entropy of an ideal gas

- For an arbitrary process:

$$\delta Q = dU - \delta W$$

## 5. Change in entropy of an ideal gas

- For an arbitrary process:

$$\delta Q = dU - \delta W = \frac{m}{\mu} \frac{i}{2} R dT + p dV$$

## 5. Change in entropy of an ideal gas

- For an arbitrary process:

$$\delta Q = dU - \delta W = \frac{m}{\mu} \frac{i}{2} R dT + p dV = \frac{m}{\mu} C_V dT + \frac{m}{\mu} R T \frac{dV}{V}$$

## 5. Change in entropy of an ideal gas

- For an arbitrary process:

$$\delta Q = dU - \delta W = \frac{m}{\mu} \frac{i}{2} R dT + p dV = \frac{m}{\mu} C_V dT + \frac{m}{\mu} R T \frac{dV}{V}$$

$$dS = \frac{m}{\mu} C_V \frac{dT}{T} + \frac{m}{\mu} R \frac{dV}{V}$$

## 5. Change in entropy of an ideal gas

- For an arbitrary process:

$$\delta Q = dU - \delta W = \frac{m}{\mu} \frac{i}{2} R dT + p dV = \frac{m}{\mu} C_V dT + \frac{m}{\mu} R T \frac{dV}{V}$$

$$dS = \frac{m}{\mu} C_V \frac{dT}{T} + \frac{m}{\mu} R \frac{dV}{V} \quad \rightarrow \quad \Delta S = \frac{m}{\mu} C_V \ln \frac{T_2}{T_1} + \frac{m}{\mu} R \ln \frac{V_2}{V_1}$$

## 5. Change in entropy of an ideal gas

- For an arbitrary process:

$$\delta Q = dU - \delta W = \frac{m}{\mu} \frac{i}{2} R dT + p dV = \frac{m}{\mu} C_V dT + \frac{m}{\mu} R T \frac{dV}{V}$$

$$dS = \frac{m}{\mu} C_V \frac{dT}{T} + \frac{m}{\mu} R \frac{dV}{V} \quad \rightarrow \quad \Delta S = \frac{m}{\mu} C_V \ln \frac{T_2}{T_1} + \frac{m}{\mu} R \ln \frac{V_2}{V_1}$$

▸ By substituting  $\frac{T_2}{T_1} = \frac{p_2 V_2}{p_1 V_1}$

## 5. Change in entropy of an ideal gas

- For an arbitrary process:

$$\delta Q = dU - \delta W = \frac{m}{\mu} \frac{i}{2} R dT + p dV = \frac{m}{\mu} C_V dT + \frac{m}{\mu} R T \frac{dV}{V}$$

$$dS = \frac{m}{\mu} C_V \frac{dT}{T} + \frac{m}{\mu} R \frac{dV}{V} \quad \rightarrow \quad \boxed{\Delta S = \frac{m}{\mu} C_V \ln \frac{T_2}{T_1} + \frac{m}{\mu} R \ln \frac{V_2}{V_1}}$$

▸ By substituting  $\frac{T_2}{T_1} = \frac{p_2 V_2}{p_1 V_1}$  and  $C_V + R = C_p$ :

## 5. Change in entropy of an ideal gas

- For an arbitrary process:

$$\delta Q = dU - \delta W = \frac{m}{\mu} \frac{i}{2} R dT + p dV = \frac{m}{\mu} C_V dT + \frac{m}{\mu} R T \frac{dV}{V}$$

$$dS = \frac{m}{\mu} C_V \frac{dT}{T} + \frac{m}{\mu} R \frac{dV}{V} \quad \rightarrow \quad \boxed{\Delta S = \frac{m}{\mu} C_V \ln \frac{T_2}{T_1} + \frac{m}{\mu} R \ln \frac{V_2}{V_1}}$$

▷ By substituting  $\frac{T_2}{T_1} = \frac{p_2 V_2}{p_1 V_1}$  and  $C_V + R = C_p$ :

$$\boxed{\Delta S = \frac{m}{\mu} C_V \ln \frac{p_2}{p_1} + \frac{m}{\mu} C_p \ln \frac{V_2}{V_1}}$$