



Imperas Peripheral Model Guide

Model Specific Information for freescale.ovpworld.org / KinetisDMA

Imperas Software Limited

Imperas Buildings, North Weston
Thame, Oxfordshire, OX9 2HA, U.K.
docs@imperas.com.



Author	Imperas Software Limited
Version	20211118.0
Filename	OVP_Peripheral_Specific_Information_KinetisDMA.pdf
Created	31 December 2021
Status	OVP Standard Release

Copyright Notice

Copyright 2021 Imperas Software Limited. All rights reserved. This software and documentation contain information that is the property of Imperas Software Limited. The software and documentation are furnished under a license agreement and may be used or copied only in accordance with the terms of the license agreement. No part of the software and documentation may be reproduced, transmitted, or translated, in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without prior written permission of Imperas Software Limited, or as expressly provided by the license agreement.

Right to Copy Documentation

The license agreement with Imperas permits licensee to make copies of the documentation for its internal use only. Each copy shall include all copyrights, trademarks, service marks, and proprietary rights notices, if any.

Destination Control Statement

All technical data contained in this publication is subject to the export control laws of the United States of America. Disclosure to nationals of other countries contrary to United States law is prohibited. It is the readers responsibility to determine the applicable regulations and to comply with them.

Disclaimer

IMPERAS SOFTWARE LIMITED, AND ITS LICENSORS MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Model Release Status

This model is released as part of OVP releases and is included in OVPworld packages. Please visit OVPworld.org.

Table Of Contents

1.0 Model Specific Information	4
1.1 Description	4
1.2 Limitations	4
1.3 Reference	4
1.4 Licensing	4
1.5 Location	4
2.0 Net Ports	4
3.0 Bus Master Ports	5
3.1 Bus Master Port: MREAD	5
3.2 Bus Master Port: MWRITE	5
4.0 Bus Slave Ports	5
4.1 Bus Slave Port: bport1	5
5.0 Platforms that use this peripheral component	13
6.0 Peripheral components in the library	14
7.0 General Information on Peripheral Models	16
7.1 Background	16
8.0 Building peripherals easily with Imperas iGen	16
9.0 Peripheral model internals	16
10.0 Parts of peripheral models	17
10.1 Configuring the Peripheral Instance with Parameters	17
10.2 Net Ports	17
10.3 Bus master ports	17
10.4 Bus slave ports	17
10.5 Packetnets	17
11.0 More information (documentation) on peripheral models and modeling	17

1.0 Model Specific Information

This document provides usage information for an Imperas OVP peripheral behavioral model.

The document is split into sections providing specific information for this peripheral, including any ports for connecting into a platform, registers, other component parts, and configuration options and general information for peripheral modeling with Imperas OVP.

1.1 Description

Model of the DMA peripheral used on the Freescale Kinetis platform

1.2 Limitations

Provides the base behaviour for the OVP Freescale Kinetis platforms

1.3 Reference

www.freescale.com/Kinetis

1.4 Licensing

Open Source Apache 2.0

1.5 Location

The KinetisDMA peripheral model is located in an Imperas/OVP installation at the VLNV:
[freescale.ovpworld.org / peripheral / KinetisDMA / 1.0](http://freescale.ovpworld.org/peripheral/KinetisDMA/1.0).

2.0 Net Ports

This model has the following net ports:

Table 1. Net Ports

Name	Type	Must Be Connected	Description
Reset	input	F (False)	
eDMARequest	input	F (False)	
eDMADone	output	F (False)	
errorInterrupt	output	F (False)	DMA Error Interrupt port
dmaInterrupt_ch0	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch1	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch2	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch3	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch4	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch5	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch6	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch7	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch8	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch9	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch10	output	F (False)	DMA Done Interrupt

dmaInterrupt_ch11	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch12	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch13	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch14	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch15	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch16	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch17	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch18	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch19	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch20	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch21	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch22	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch23	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch24	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch25	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch26	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch27	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch28	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch29	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch30	output	F (False)	DMA Done Interrupt
dmaInterrupt_ch31	output	F (False)	DMA Done Interrupt

3.0 Bus Master Ports

This model has the following bus master ports:

3.1 Bus Master Port: MREAD

Table 2. MREAD

Name	Address Width (bits)	Description
MREAD	32	DMA Master Read of address space

3.2 Bus Master Port: MWRITE

Table 3. MWRITE

Name	Address Width (bits)	Description
MWRITE	32	DMA Master Write of address space

4.0 Bus Slave Ports

This model has the following bus slave ports:

4.1 Bus Slave Port: bport1

Table 4. Bus Slave Port: bport1

Name	Size (bytes)	Must Be Connected	Description
bport1	0x2000	F (False)	

Table 5. Bus Slave Port: bport1 Registers:

Name	Offset	Width (bits)	Description	R/W	is Volatile
ab_CR	0x0	32	Control Register, offset: 0x0		
ab_ES	0x4	32	Error Status Register, offset: 0x4		
ab_ERQ	0xc	32	Enable Request Register, offset: 0xC		
ab_EEI	0x14	32			
ab_CS_EEI_ERC	0x18	32	Clear/Set EEI, ERC		
ab_DNE_SRT_ERR_INT	0x1c	32	Clear/Set DNE, START, ERR, INT registers		
ab_INT	0x24	32			
ab_ERR	0x2c	32	Error Register, offset: 0x2C		
ab_HRS	0x34	32			
ab_DCHPRI3_0	0x100	32	Channel n Priority Registers 3 to 0		
ab_DCHPRI7_4	0x104	32			
ab_DCHPRI11_8	0x108	32			
ab_DCHPRI15_12	0x10c	32			
ab_DCHPRI19_16	0x110	32			
ab_DCHPRI23_20	0x114	32			
ab_DCHPRI27_24	0x118	32			
ab_DCHPRI31_28	0x11c	32			
TCD0_SADDR	0x1000	32	TCD Source Address		
TCD0_SOFF_ATTR	0x1004	32	TCD Signed Source Address Offset		
TCD0_NBYTES	0x1008	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD0_SLAST	0x100c	32			
TCD0_DADDR	0x1010	32			
TCD0_DOFF_CITER	0x1014	32			
TCD0_DLASTSGA	0x1018	32			
TCD0_CSR_BITER	0x101c	32			
TCD1_SADDR	0x1020	32	TCD Source Address		
TCD1_SOFF_ATTR	0x1024	32	TCD Signed Source Address Offset		
TCD1_NBYTES	0x1028	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD1_SLAST	0x102c	32			
TCD1_DADDR	0x1030	32			
TCD1_DOFF_CITER	0x1034	32			
TCD1_DLASTSGA	0x1038	32			
TCD1_CSR_BITER	0x103c	32			
TCD2_SADDR	0x1040	32	TCD Source Address		
TCD2_SOFF_ATTR	0x1044	32	TCD Signed Source Address Offset		
TCD2_NBYTES	0x1048	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		

TCD2_SLAST	0x104c	32			
TCD2_DADDR	0x1050	32			
TCD2_DOFF_CITER	0x1054	32			
TCD2_DLASTSGA	0x1058	32			
TCD2_CSR_BITER	0x105c	32			
TCD3_SADDR	0x1060	32	TCD Source Address		
TCD3_SOFF_ATTR	0x1064	32	TCD Signed Source Address Offset		
TCD3_NBYTES	0x1068	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD3_SLAST	0x106c	32			
TCD3_DADDR	0x1070	32			
TCD3_DOFF_CITER	0x1074	32			
TCD3_DLASTSGA	0x1078	32			
TCD3_CSR_BITER	0x107c	32			
TCD4_SADDR	0x1080	32	TCD Source Address		
TCD4_SOFF_ATTR	0x1084	32	TCD Signed Source Address Offset		
TCD4_NBYTES	0x1088	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD4_SLAST	0x108c	32			
TCD4_DADDR	0x1090	32			
TCD4_DOFF_CITER	0x1094	32			
TCD4_DLASTSGA	0x1098	32			
TCD4_CSR_BITER	0x109c	32			
TCD5_SADDR	0x10a0	32	TCD Source Address		
TCD5_SOFF_ATTR	0x10a4	32	TCD Signed Source Address Offset		
TCD5_NBYTES	0x10a8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD5_SLAST	0x10ac	32			
TCD5_DADDR	0x10b0	32			
TCD5_DOFF_CITER	0x10b4	32			
TCD5_DLASTSGA	0x10b8	32			
TCD5_CSR_BITER	0x10bc	32			
TCD6_SADDR	0x10c0	32	TCD Source Address		
TCD6_SOFF_ATTR	0x10c4	32	TCD Signed Source Address Offset		
TCD6_NBYTES	0x10c8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD6_SLAST	0x10cc	32			
TCD6_DADDR	0x10d0	32			
TCD6_DOFF_CITER	0x10d4	32			
TCD6_DLASTSGA	0x10d8	32			
TCD6_CSR_BITER	0x10dc	32			
TCD7_SADDR	0x10e0	32	TCD Source Address		
TCD7_SOFF_ATTR	0x10e4	32	TCD Signed Source Address Offset		

TCD7_NBYTES	0x10e8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD7_SLAST	0x10ec	32			
TCD7_DADDR	0x10f0	32			
TCD7_DOFF_CITER	0x10f4	32			
TCD7_DLASTSGA	0x10f8	32			
TCD7_CSR_BITER	0x10fc	32			
TCD8_SADDR	0x1100	32	TCD Source Address		
TCD8_SOFF_ATTR	0x1104	32	TCD Signed Source Address Offset		
TCD8_NBYTES	0x1108	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD8_SLAST	0x110c	32			
TCD8_DADDR	0x1110	32			
TCD8_DOFF_CITER	0x1114	32			
TCD8_DLASTSGA	0x1118	32			
TCD8_CSR_BITER	0x111c	32			
TCD9_SADDR	0x1120	32	TCD Source Address		
TCD9_SOFF_ATTR	0x1124	32	TCD Signed Source Address Offset		
TCD9_NBYTES	0x1128	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD9_SLAST	0x112c	32			
TCD9_DADDR	0x1130	32			
TCD9_DOFF_CITER	0x1134	32			
TCD9_DLASTSGA	0x1138	32			
TCD9_CSR_BITER	0x113c	32			
TCD10_SADDR	0x1140	32	TCD Source Address		
TCD10_SOFF_ATTR	0x1144	32	TCD Signed Source Address Offset		
TCD10_NBYTES	0x1148	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD10_SLAST	0x114c	32			
TCD10_DADDR	0x1150	32			
TCD10_DOFF_CITER	0x1154	32			
TCD10_DLASTSGA	0x1158	32			
TCD10_CSR_BITER	0x115c	32			
TCD11_SADDR	0x1160	32	TCD Source Address		
TCD11_SOFF_ATTR	0x1164	32	TCD Signed Source Address Offset		
TCD11_NBYTES	0x1168	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD11_SLAST	0x116c	32			
TCD11_DADDR	0x1170	32			
TCD11_DOFF_CITER	0x1174	32			
TCD11_DLASTSGA	0x1178	32			
TCD11_CSR_BITER	0x117c	32			

TCD12_SADDR	0x1180	32	TCD Source Address		
TCD12_SOFF_ATTR	0x1184	32	TCD Signed Source Address Offset		
TCD12_NBYTES	0x1188	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD12_SLAST	0x118c	32			
TCD12_DADDR	0x1190	32			
TCD12_DOFF_CITER	0x1194	32			
TCD12_DLASTSGA	0x1198	32			
TCD12_CSR_BITER	0x119c	32			
TCD13_SADDR	0x11a0	32	TCD Source Address		
TCD13_SOFF_ATTR	0x11a4	32	TCD Signed Source Address Offset		
TCD13_NBYTES	0x11a8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD13_SLAST	0x11ac	32			
TCD13_DADDR	0x11b0	32			
TCD13_DOFF_CITER	0x11b4	32			
TCD13_DLASTSGA	0x11b8	32			
TCD13_CSR_BITER	0x11bc	32			
TCD14_SADDR	0x11c0	32	TCD Source Address		
TCD14_SOFF_ATTR	0x11c4	32	TCD Signed Source Address Offset		
TCD14_NBYTES	0x11c8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD14_SLAST	0x11cc	32			
TCD14_DADDR	0x11d0	32			
TCD14_DOFF_CITER	0x11d4	32			
TCD14_DLASTSGA	0x11d8	32			
TCD14_CSR_BITER	0x11dc	32			
TCD15_SADDR	0x11e0	32	TCD Source Address		
TCD15_SOFF_ATTR	0x11e4	32	TCD Signed Source Address Offset		
TCD15_NBYTES	0x11e8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD15_SLAST	0x11ec	32			
TCD15_DADDR	0x11f0	32			
TCD15_DOFF_CITER	0x11f4	32			
TCD15_DLASTSGA	0x11f8	32			
TCD15_CSR_BITER	0x11fc	32			
TCD16_SADDR	0x1200	32	TCD Source Address		
TCD16_SOFF_ATTR	0x1204	32	TCD Signed Source Address Offset		
TCD16_NBYTES	0x1208	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD16_SLAST	0x120c	32			
TCD16_DADDR	0x1210	32			

TCD16_DOFF_CITER	0x1214	32			
TCD16_DLASTSGA	0x1218	32			
TCD16_CSR_BITER	0x121c	32			
TCD17_SADDR	0x1220	32	TCD Source Address		
TCD17_SOFF_ATTR	0x1224	32	TCD Signed Source Address Offset		
TCD17_NBYTES	0x1228	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD17_SLAST	0x122c	32			
TCD17_DADDR	0x1230	32			
TCD17_DOFF_CITER	0x1234	32			
TCD17_DLASTSGA	0x1238	32			
TCD17_CSR_BITER	0x123c	32			
TCD18_SADDR	0x1240	32	TCD Source Address		
TCD18_SOFF_ATTR	0x1244	32	TCD Signed Source Address Offset		
TCD18_NBYTES	0x1248	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD18_SLAST	0x124c	32			
TCD18_DADDR	0x1250	32			
TCD18_DOFF_CITER	0x1254	32			
TCD18_DLASTSGA	0x1258	32			
TCD18_CSR_BITER	0x125c	32			
TCD19_SADDR	0x1260	32	TCD Source Address		
TCD19_SOFF_ATTR	0x1264	32	TCD Signed Source Address Offset		
TCD19_NBYTES	0x1268	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD19_SLAST	0x126c	32			
TCD19_DADDR	0x1270	32			
TCD19_DOFF_CITER	0x1274	32			
TCD19_DLASTSGA	0x1278	32			
TCD19_CSR_BITER	0x127c	32			
TCD20_SADDR	0x1280	32	TCD Source Address		
TCD20_SOFF_ATTR	0x1284	32	TCD Signed Source Address Offset		
TCD20_NBYTES	0x1288	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD20_SLAST	0x128c	32			
TCD20_DADDR	0x1290	32			
TCD20_DOFF_CITER	0x1294	32			
TCD20_DLASTSGA	0x1298	32			
TCD20_CSR_BITER	0x129c	32			
TCD21_SADDR	0x12a0	32	TCD Source Address		
TCD21_SOFF_ATTR	0x12a4	32	TCD Signed Source Address Offset		
TCD21_NBYTES	0x12a8	32	TCD Signed Minor Loop Offset, Minor Loop		

			Disabled		
TCD21_SLAST	0x12ac	32			
TCD21_DADDR	0x12b0	32			
TCD21_DOFF_CITER	0x12b4	32			
TCD21_DLASTSGA	0x12b8	32			
TCD21_CSR_BITER	0x12bc	32			
TCD22_SADDR	0x12c0	32	TCD Source Address		
TCD22_SOFF_ATTR	0x12c4	32	TCD Signed Source Address Offset		
TCD22_NBYTES	0x12c8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD22_SLAST	0x12cc	32			
TCD22_DADDR	0x12d0	32			
TCD22_DOFF_CITER	0x12d4	32			
TCD22_DLASTSGA	0x12d8	32			
TCD22_CSR_BITER	0x12dc	32			
TCD23_SADDR	0x12e0	32	TCD Source Address		
TCD23_SOFF_ATTR	0x12e4	32	TCD Signed Source Address Offset		
TCD23_NBYTES	0x12e8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD23_SLAST	0x12ec	32			
TCD23_DADDR	0x12f0	32			
TCD23_DOFF_CITER	0x12f4	32			
TCD23_DLASTSGA	0x12f8	32			
TCD23_CSR_BITER	0x12fc	32			
TCD24_SADDR	0x1300	32	TCD Source Address		
TCD24_SOFF_ATTR	0x1304	32	TCD Signed Source Address Offset		
TCD24_NBYTES	0x1308	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD24_SLAST	0x130c	32			
TCD24_DADDR	0x1310	32			
TCD24_DOFF_CITER	0x1314	32			
TCD24_DLASTSGA	0x1318	32			
TCD24_CSR_BITER	0x131c	32			
TCD25_SADDR	0x1320	32	TCD Source Address		
TCD25_SOFF_ATTR	0x1324	32	TCD Signed Source Address Offset		
TCD25_NBYTES	0x1328	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD25_SLAST	0x132c	32			
TCD25_DADDR	0x1330	32			
TCD25_DOFF_CITER	0x1334	32			
TCD25_DLASTSGA	0x1338	32			
TCD25_CSR_BITER	0x133c	32			
TCD26_SADDR	0x1340	32	TCD Source Address		

TCD26_SOFF_ATTR	0x1344	32	TCD Signed Source Address Offset		
TCD26_NBYTES	0x1348	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD26_SLAST	0x134c	32			
TCD26_DADDR	0x1350	32			
TCD26_DOFF_CITER	0x1354	32			
TCD26_DLASTSGA	0x1358	32			
TCD26_CSR_BITER	0x135c	32			
TCD27_SADDR	0x1360	32	TCD Source Address		
TCD27_SOFF_ATTR	0x1364	32	TCD Signed Source Address Offset		
TCD27_NBYTES	0x1368	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD27_SLAST	0x136c	32			
TCD27_DADDR	0x1370	32			
TCD27_DOFF_CITER	0x1374	32			
TCD27_DLASTSGA	0x1378	32			
TCD27_CSR_BITER	0x137c	32			
TCD28_SADDR	0x1380	32	TCD Source Address		
TCD28_SOFF_ATTR	0x1384	32	TCD Signed Source Address Offset		
TCD28_NBYTES	0x1388	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD28_SLAST	0x138c	32			
TCD28_DADDR	0x1390	32			
TCD28_DOFF_CITER	0x1394	32			
TCD28_DLASTSGA	0x1398	32			
TCD28_CSR_BITER	0x139c	32			
TCD29_SADDR	0x13a0	32	TCD Source Address		
TCD29_SOFF_ATTR	0x13a4	32	TCD Signed Source Address Offset		
TCD29_NBYTES	0x13a8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD29_SLAST	0x13ac	32			
TCD29_DADDR	0x13b0	32			
TCD29_DOFF_CITER	0x13b4	32			
TCD29_DLASTSGA	0x13b8	32			
TCD29_CSR_BITER	0x13bc	32			
TCD30_SADDR	0x13c0	32	TCD Source Address		
TCD30_SOFF_ATTR	0x13c4	32	TCD Signed Source Address Offset		
TCD30_NBYTES	0x13c8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD30_SLAST	0x13cc	32			
TCD30_DADDR	0x13d0	32			
TCD30_DOFF_CITER	0x13d4	32			

TCD30_DLASTSGA	0x13d8	32			
TCD30_CSR_BITER	0x13dc	32			
TCD31_SADDR	0x13e0	32	TCD Source Address		
TCD31_SOFF_ATTR	0x13e4	32	TCD Signed Source Address Offset		
TCD31_NBYTES	0x13e8	32	TCD Signed Minor Loop Offset, Minor Loop Disabled		
TCD31_SLAST	0x13ec	32			
TCD31_DADDR	0x13f0	32			
TCD31_DOFF_CITER	0x13f4	32			
TCD31_DLASTSGA	0x13f8	32			
TCD31_CSR_BITER	0x13fc	32			

5.0 Platforms that use this peripheral component

Peripheral components can be used in many different platforms, including those developed by Imperas or by other users of OVP. You can use this peripheral in your own platforms.

Table 6. Publicly available platforms using peripheral 'KinetisDMA'

Platform Name	Vendor
FreescaleKinetis60	freescale.ovpworld.org
FreescaleKinetis64	freescale.ovpworld.org

6.0 Peripheral components in the library

Table 7. Publicly available Imperas/OVP peripheral models (227 models)

Peripheral	Peripheral	Peripheral
freescale.ovpworld.org/KinetisDMAC	freescale.ovpworld.org/KinetisDMAMUX	freescale.ovpworld.org/KinetisENET
freescale.ovpworld.org/KinetisEWM	freescale.ovpworld.org/KinetisFB	freescale.ovpworld.org/KinetisFMC
freescale.ovpworld.org/KinetisFTFE	freescale.ovpworld.org/KinetisFTM	freescale.ovpworld.org/KinetisGPIO
freescale.ovpworld.org/KinetisI2C	freescale.ovpworld.org/KinetisI2S	freescale.ovpworld.org/KinetisLLWU
freescale.ovpworld.org/KinetisLPTMR	freescale.ovpworld.org/KinetisMCG	freescale.ovpworld.org/KinetisMPU
freescale.ovpworld.org/KinetisNFC	freescale.ovpworld.org/KinetisOSC	freescale.ovpworld.org/KinetisPDB
freescale.ovpworld.org/KinetisPIT	freescale.ovpworld.org/KinetisPMC	freescale.ovpworld.org/KinetisPORT
freescale.ovpworld.org/KinetisRCM	freescale.ovpworld.org/KinetisRFSYS	freescale.ovpworld.org/KinetisRFVBAT
freescale.ovpworld.org/KinetisRNG	freescale.ovpworld.org/KinetisRTC	freescale.ovpworld.org/KinetisSDHC
freescale.ovpworld.org/KinetisSIM	freescale.ovpworld.org/KinetisSMC	freescale.ovpworld.org/KinetisSPI
freescale.ovpworld.org/KinetisTSI	freescale.ovpworld.org/KinetisUART	freescale.ovpworld.org/KinetisUSB
freescale.ovpworld.org/KinetisUSBDCD	freescale.ovpworld.org/KinetisUSBHS	freescale.ovpworld.org/KinetisVREF
freescale.ovpworld.org/KinetisWDOG	freescale.ovpworld.org/Uart	freescale.ovpworld.org/VybridADC
freescale.ovpworld.org/VybridANADIG	freescale.ovpworld.org/VybridCCM	freescale.ovpworld.org/VybridDMA
freescale.ovpworld.org/VybridGPIO	freescale.ovpworld.org/VybridI2C	freescale.ovpworld.org/VybridLCD
freescale.ovpworld.org/VybridQUADSPI	freescale.ovpworld.org/VybridSDHC	freescale.ovpworld.org/VybridSPI
freescale.ovpworld.org/VybridUART	freescale.ovpworld.org/VybridUSB	imperas.ovpworld.org/frameBuffer
imperas.ovpworld.org/uart	imperas.ovpworld.org/usecCounter	intel.ovpworld.org/82077AA
intel.ovpworld.org/82371EB	intel.ovpworld.org/8253	intel.ovpworld.org/8259A
intel.ovpworld.org/NorFlash48F4400	intel.ovpworld.org/PciIDE	intel.ovpworld.org/PciPM
intel.ovpworld.org/PciUSB	intel.ovpworld.org/Ps2Control	marvell.ovpworld.org/GT6412x
maxim.ovpworld.org/max673x	microsemi.ovpworld.org/CoreUARTapb	mips.ovpworld.org/16450C
mips.ovpworld.org/MaltaFPGA	mips.ovpworld.org/SmartLoaderLinux	motorola.ovpworld.org/MC146818
national.ovpworld.org/16450	national.ovpworld.org/16550	national.ovpworld.org/16550_4bytes
nxp.ovpworld.org/iMX6_Analog	nxp.ovpworld.org/iMX6_CCM	nxp.ovpworld.org/iMX6_GPC
nxp.ovpworld.org/iMX6_GPIO	nxp.ovpworld.org/iMX6_GPT	nxp.ovpworld.org/iMX6_MMDC
nxp.ovpworld.org/iMX6_SDHC	nxp.ovpworld.org/iMX6_SRC	nxp.ovpworld.org/iMX6_UART
nxp.ovpworld.org/iMX6_WDOG	ovpworld.org/Alpha2x16Display	ovpworld.org/DynamicBridge
ovpworld.org/FlashDevice	ovpworld.org/ledRegister	ovpworld.org/SerInt
ovpworld.org/SimpleDma	ovpworld.org/switchRegister	ovpworld.org/temperatureSensor
ovpworld.org/trap	ovpworld.org/trap4K	ovpworld.org/vEthernet_Bridge
ovpworld.org/VirtioBlkMMIO	ovpworld.org/VirtioNetMMIO	philips.ovpworld.org/ISP1761
renesas.ovpworld.org/adc	renesas.ovpworld.org/bcu	renesas.ovpworld.org/brg
renesas.ovpworld.org/can	renesas.ovpworld.org/can	renesas.ovpworld.org/clkgen
renesas.ovpworld.org/crc	renesas.ovpworld.org/csib	renesas.ovpworld.org/csie
renesas.ovpworld.org/dma	renesas.ovpworld.org/intc	renesas.ovpworld.org/memc
renesas.ovpworld.org/rng	renesas.ovpworld.org/taa	renesas.ovpworld.org/tms
renesas.ovpworld.org/tmt	renesas.ovpworld.org/uartc	renesas.ovpworld.org/UPD70F3441Logic
riscv.ovpworld.org/CLINT	riscv.ovpworld.org/PLIC	riscv.ovpworld.org/SmartLoaderRV64Linux
safepower.ovpworld.org/node	safepower.ovpworld.org/NostrumNode	safepower.ovpworld.org/ring_oscillator
safepower.ovpworld.org/TTELNode	sifive.ovpworld.org/artyIO	sifive.ovpworld.org/DDRCTL
sifive.ovpworld.org/gpio	sifive.ovpworld.org/MSEL	sifive.ovpworld.org/PLIC
sifive.ovpworld.org/PRCI	sifive.ovpworld.org/pwm	sifive.ovpworld.org/spi

sifive.ovpworld.org/teststatus	sifive.ovpworld.org/UART	smcsc.ovpworld.org/LAN9118
smcsc.ovpworld.org/LAN91C111	ti.ovpworld.org/tca6416a	ti.ovpworld.org/UartInterface
ti.ovpworld.org/ucd9012a	ti.ovpworld.org/ucd9248	vendor.com/fifo
xilinx.ovpworld.org/axi-gpio	xilinx.ovpworld.org/axi-intc	xilinx.ovpworld.org/axi-pcie
xilinx.ovpworld.org/axi-timer	xilinx.ovpworld.org/logicore-fit	xilinx.ovpworld.org/mdm
xilinx.ovpworld.org/mpmc	xilinx.ovpworld.org/xps-gpio	xilinx.ovpworld.org/xps-iic
xilinx.ovpworld.org/xps-intc	xilinx.ovpworld.org/xps-ll-temac	xilinx.ovpworld.org/xps-mch-emc
xilinx.ovpworld.org/xps-sysace	xilinx.ovpworld.org/xps-timer	xilinx.ovpworld.org/xps-uartlite
xilinx.ovpworld.org/zynq_7000-can	xilinx.ovpworld.org/zynq_7000-ddrc	xilinx.ovpworld.org/zynq_7000-devcfg
xilinx.ovpworld.org/zynq_7000-dmac	xilinx.ovpworld.org/zynq_7000-gpio	xilinx.ovpworld.org/zynq_7000-iic
xilinx.ovpworld.org/zynq_7000-ocm	xilinx.ovpworld.org/zynq_7000-qos301	xilinx.ovpworld.org/zynq_7000-qspi
xilinx.ovpworld.org/zynq_7000-sdio	xilinx.ovpworld.org/zynq_7000-slcr	xilinx.ovpworld.org/zynq_7000-spi
xilinx.ovpworld.org/zynq_7000-swdt	xilinx.ovpworld.org/zynq_7000-ttc	xilinx.ovpworld.org/zynq_7000-tz_GPVsecurity
xilinx.ovpworld.org/zynq_7000-tz_security	xilinx.ovpworld.org/zynq_7000-usb	altera.ovpworld.org/dw-apb-timer
altera.ovpworld.org/dw-apb-uart	altera.ovpworld.org/IntervalTimer32Core	altera.ovpworld.org/IntervalTimer64Core
altera.ovpworld.org/JtagUart	altera.ovpworld.org/PerformanceCounterCore	altera.ovpworld.org/RSTMGR
altera.ovpworld.org/SystemIDCore	altera.ovpworld.org/Uart	amd.ovpworld.org/79C970
andes.ovpworld.org/ATCUART100	andes.ovpworld.org/NCEPLIC100	andes.ovpworld.org/NCEPLMT100
arm.ovpworld.org/AaciPL041	arm.ovpworld.org/CompactFlashRegs	arm.ovpworld.org/CoreModule9x6
arm.ovpworld.org/DebugLedAndDipSwitch	arm.ovpworld.org/DMemCtrlPL341	arm.ovpworld.org/IcpControl
arm.ovpworld.org/IcpCounterTimer	arm.ovpworld.org/IntICP	arm.ovpworld.org/IntICP
arm.ovpworld.org/KbPL050	arm.ovpworld.org/L2CachePL310	arm.ovpworld.org/LcdPL110
arm.ovpworld.org/MmciPL181	arm.ovpworld.org/RtcPL031	arm.ovpworld.org/SerBusDviRegs
arm.ovpworld.org/SmartLoaderArm64Linux	arm.ovpworld.org/SmartLoaderArmLinux	arm.ovpworld.org/SMemCtrlPL354
arm.ovpworld.org/SysCtrlSP810	arm.ovpworld.org/TimerSP804	arm.ovpworld.org/TzpcBP147
arm.ovpworld.org/UartPL011	arm.ovpworld.org/VexpressSysRegs	arm.ovpworld.org/WdtSP805
atmel.ovpworld.org/AdvancedInterruptController	atmel.ovpworld.org/ParallelIOController	atmel.ovpworld.org/PowerSaving
atmel.ovpworld.org/SpecialFunction	atmel.ovpworld.org/TimerCounter	atmel.ovpworld.org/UsartInterface
atmel.ovpworld.org/WatchdogTimer	cadence.ovpworld.org/gem	cadence.ovpworld.org/uart
cirrus.ovpworld.org/GD5446	freescale.ovpworld.org/KinetisADC	freescale.ovpworld.org/KinetisAIPS
freescale.ovpworld.org/KinetisAXBS	freescale.ovpworld.org/KinetisCAN	freescale.ovpworld.org/KinetisCMP
freescale.ovpworld.org/KinetisCMT	freescale.ovpworld.org/KinetisCRC	freescale.ovpworld.org/KinetisDAC
freescale.ovpworld.org/KinetisDDR	freescale.ovpworld.org/KinetisDMA	

7.0 General Information on Peripheral Models

This document provides usage information for an Imperas OVP peripheral behavioral model.

The document is split into sections providing specific information for this peripheral, including any ports for connecting into a platform, registers etc. and configuration options and general information for peripheral modeling with Imperas OVP.

7.1 Background

Imperas OVP simulation technology enables very high performance simulation, debug and analysis of platforms containing multiple processors and peripheral models. The technology is designed to be extensible: you can create new models of processors, peripherals and other platform components using interfaces and libraries defined by OVP.

The peripheral models created using the OVP APIs run on the Peripheral Simulation Engine (PSE).

The model is typically written in C and compiled into an executable for the PSE processor architecture. The model is compiled for speed of execution and to protect IP. It is dynamically loaded by the simulator at run time.

8.0 Building peripherals easily with Imperas iGen

To aid with model creation, Imperas products include iGen, a model generation tool. iGen takes the laborious and error-prone task of constructing the various hardware model and software element files required for a typical model, and automates this process. iGen creates the needed C files. iGen also creates the C++ SystemC TLM2 interface files needed to run peripheral models in SystemC simulations.

iGen takes as input a simple script specification that includes device internals such as registers and memories, port information, component descriptors, and other elements. iGen then builds the C code model files and user editable templates. These include model frameworks with registers, function calls, memory map, and other items. It ensures that all component parts of the model are well-structured using best practices, and are consistent throughout the files, thus eliminating a common source of errors.

More information on iGen can be found: imperas.com/products.

9.0 Peripheral model internals

Each instance of a peripheral model runs on its own virtual machine with an address space large enough for the model. This processor (the PSE) and its memory are separate from any processors, memories and buses in the platform being simulated; they exist only to execute the code of the peripheral model.

Interception of functions defined in the peripheral model allows the use of features of the host system in the

implementation of the behavior of a peripheral. As an example, a real platform might contain a video display device. When simulating this system, it is generally more convenient not to simulate the complete video display device but to use a video package available on the host machine, such as SDL, and to use this to render to the host display. Also models of uarts, ethernet devices and USB components can make use of the host PC resources during simulation, to allow, for example, a simulation to browse the real internet, or the simulation to connect to a real USB device.

10.0 Parts of peripheral models

10.1 Configuring the Peripheral Instance with Parameters

A peripheral can include the behaviour of several configurations. These are controlled when the peripheral is instanced in the platform by setting parameters defined on the peripheral.

10.2 Net Ports

Peripherals may be connected to other peripherals or processors with signal wires (nets). These can be used to act as interrupt signals or used to control behavior between peripherals.

The wires are created in the platform as nets and this net is connected into the peripheral using a net port.

10.3 Bus master ports

A bus master port initiates (and controls the address of) a bus cycle. Bus cycles are generated by behavioral code within the peripheral model.

10.4 Bus slave ports

A peripheral can be defined as having several bus slave ports. The bus slave ports can be split into several address blocks. Each address block be either local memory or memory mapped registers. Both of these can have associated callback functions. A memory mapped register can also be defined as specific read/write access, whether it is volatile, and also whether it is associated with a reset pin and mask. A memory mapped register can also have specific bit fields defined.

10.5 Packetnets

A peripheral can be defined as being connected to packetnet ports. A packetnet is used to model packet based communication such as Ethernet, CAN bus or GSM. A packetnet is created in a platform, then connected to packetnet ports on model instances. A packetnet can have many connections, each able to send or receive packets. A packetnet is used as an efficient method of communication within OVP models.

For more information on modeling with packetnets, please see the peripheral modeling documentation: [OVP_Peripheral_Modeling_Guide.pdf](#), [OVPSim_and_CpuManager_User_Guide.pdf](#) and the example: [\\$IMPERAS_HOME/Examples/Models/Peripherals/packetnet](#).

11.0 More information (documentation) on peripheral models and modeling

More information on modeling and APIs can be found at: OVPworld.org/technology_apis.

Specifics on modeling peripherals can be found: [OVP Peripheral Modeling Guide.pdf](#).

A full list of the currently available OVP documentation is available: [OVPworld.org/documentation](#).

#