Nu Html Checker

This tool is an ongoing experiment in better HTML checking, and its behavior remains subject to change

Showing results for contents of text-input area

Checker Input

Show ☑ source   ☐ outline   ☐ image report   [Options…]

Check by [text input ▾] ☐ css

```
<div class="card-body">
        <form method="POST" action="{{ route('register') }}"
class="login-form" onsubmit="return validateForm()">
            {{ csrf_field() }}

            <div class="mb-3">
                <label for="username" class="form-label">Username</label>
                <input id="username" placeholder="ex: john1234"
type="text" name="username" value="{{ old('username') }}" required autofocus
class="form-control">
                @if ($errors->has('username'))
                    <span class="error">
                        {{ $errors->first('username') }}
                    </span>
                @endif
            </div>
```

[Check]

Use the Message Filtering button below to display options for hiding/showing particular messages, and to see total counts of errors and warnings.

[Message Filtering]   *6 messages hidden by filtering*

---

1. **Error**   **Element** `head` **is missing a required instance of child element** `title`**.**

    [From line 1, column 28; to line 3, column 23](#)

    `de.php -->↵↵@extends('layouts.app')↵↵@sec`

    Content model for element [head](#):

    If the document is [an iframe srcdoc document](#) or if title information is available from a higher-level protocol: Zero or more elements of [metadata content](#), of which no more than one is a [title](#) element and no more than one is a [base](#) element.

    Otherwise: One or more elements of [metadata content](#), of which exactly one is a [title](#) element and no more than one is a [base](#) element.

2. **Warning**   **The** `type` **attribute is unnecessary for JavaScript resources.**

    [From line 7, column 5; to line 7, column 83](#)

```
nt')↵↵        <script type="text/javascript" src="{{ asset('js/password_forms.js')

}}" defer></scri
```

3. **Error** A document must not include more than one `autofocus` attribute.

From line 34, column 29; to line 34, column 163

```
            <input id="name" placeholder="ex: John Bill" type="text" name="name"

value="{{ old('name') }}" required autofocus class="form-control">↵
```

Document checking completed.

Source

```
1.  <!-- register.blade.php -->↵
2.  ↵
3.  @extends('layouts.app')↵
4.  ↵
5.  @section('content')↵
6.  ↵
7.      <script type="text/javascript" src="{{ asset('js/password_forms.js') }}"
    defer></script>↵
8.      <link href="{{ asset('css/register.css') }}" rel="stylesheet">↵
9.      ↵
10.     <div class="container mt-2">↵
11.         <div class="text-center mb-3">↵
12.             <p class="login-section-text" style="color: #006aa7;">↵
13.                 Create an account to get started and enjoy our services.↵
14.             </p>↵
15.         </div>↵
16.         <div class="register-container">↵
17.             <div class="card register-card">↵
18.                 <div class="card-body">↵
19.                     <form method="POST" action="{{ route('register') }}"
    class="login-form" onsubmit="return validateForm()">↵
20.                         {{ csrf_field() }}↵
21.  ↵
22.                         <div class="mb-3">↵
23.                             <label for="username" class="form-
    label">Username</label>↵
24.                             <input id="username" placeholder="ex: john1234"
    type="text" name="username" value="{{ old('username') }}" required autofocus
    class="form-control">↵
25.                             @if ($errors->has('username'))↵
26.                                 <span class="error">↵
27.                                     {{ $errors->first('username') }}↵
28.                                 </span>↵
29.                             @endif↵
30.                         </div>↵
31.  ↵
32.                         <div class="mb-3">↵
33.                             <label for="name" class="form-label">Name</label>↵
34.                             <input id="name" placeholder="ex: John Bill"
    type="text" name="name" value="{{ old('name') }}" required autofocus class="form-
    control">↵
35.                             @if ($errors->has('name'))↵
36.                                 <span class="error">↵
37.                                     {{ $errors->first('name') }}↵
38.                                 </span>↵
```

```
39.                            @endif↵
40.                        </div>↵
41.  ↵
42.                        <div class="mb-3">↵
43.                            <label for="email" class="form-label">E-mail</label>↵
44.                            <input id="email" placeholder="ex: abc123@email.com"
     type="email" name="email" value="{{ old('email') }}" required class="form-
     control">↵
45.                            @if ($errors->has('email'))↵
46.                                <span class="error">↵
47.                                    {{ $errors->first('email') }}↵
48.                                </span>↵
49.                            @endif↵
50.                        </div>↵
51.  ↵
52.                        <div class="mb-3">↵
53.                            <label for="phonenumber" class="form-label">Phone
     Number (optional)</label>↵
54.                            <input id="phonenumber" placeholder="ex: 917918916"
     type="text" name="phonenumber" value="{{ old('phonenumber') }}" class="form-
     control">↵
55.                            @if ($errors->has('phonenumber'))↵
56.                                <span class="error">↵
57.                                    {{ $errors->first('phonenumber') }}↵
58.                                </span>↵
59.                            @endif↵
60.                        </div>↵
61.  ↵
62.                        <div class="mb-3">↵
63.                            <label for="password" class="form-
     label">Password</label>↵
64.                            <input id="password" placeholder="ex: 12345678"
     type="password" name="password" required class="form-control" minlength="8"
     oninput="validatePassword()">↵
65.                            <span id="password-error" class="error"></span>↵
66.                        </div>↵
67.  ↵
68.                        <div class="mb-3">↵
69.                            <label for="password-confirm" class="form-
     label">Confirm Password</label>↵
70.                            <input id="password-confirm" placeholder="ex:
     12345678" type="password" name="password_confirmation" required class="form-
     control" oninput="validatePassword()" onblur="validatePassword()">↵
71.                            <span id="password-confirm-error" class="error">
     </span>↵
72.                        </div>↵
73.  ↵
74.                        <button type="submit" id="submit-button" class="btn btn-
     primary" disabled>↵
75.                            Register↵
76.                        </button>↵
77.  ↵
78.                        <div class="separator text-center">↵
79.                            <hr>↵
80.                            <span id="no-account">Already have an account?
     </span>↵
81.                            <hr>↵
82.                        </div>↵
83.  ↵
84.                        <a class="btn btn-primary btn-register register-button"
     href="{{ route('login') }}">↵
85.                            Login↵
86.                        </a>↵
87.                    </form>↵
88.                </div>↵
89.            </div>↵
90.        </div>↵
```

```
91.        </div>↵
92.  @endsection
```

Used the HTML parser.

Total execution time 20 milliseconds.

[About this checker](#) • [Report an issue](#) • Version: 23.12.19