

IPS**Individual Product Specification**

**Rivet, blind - general purpose, bulbed, protruding head,
mechanically-locked-spindle**

Allfast Fastening Systems – City of Industry

**Published and distributed by :
AIRBUS S.A.S.
ENGINEERING DIRECTORATE
31707 BLAGNAC Cedex
FRANCE**

Contents

- 1 Scope
- 2 Normative references
- 3 Material and manufacturer
- 4 Cross-references
- 5 Material application
- 6 Qualification
- 7 Release
- 8 Specific agreements
- 9 Material safety data sheet

1 Scope

This Individual Product Specification identifies a standard, or standard parts from a manufacturer that has been successfully qualified to the relevant Technical Specification

The Individual Product Specification specifies individual requirements, which describe the specific performance of the standard, as demonstrated by the qualification, and which have to be considered for procurement and use, together with the Technical Specification.

2 Normative references

This Airbus specification incorporates by dated or undated reference provisions from other publications. All normative references cited at the appropriate places in the text are listed hereafter. For dated references, subsequent amendments to or revisions of any these publications apply to this Airbus specification only when incorporated in it by amendment or revision. For undated references, the latest issue of the publication referred to shall be applied.

A1091	Airbus Requirements for the Management of Hazardous Substances
EC n°1272/2008	Regulation on classification, labelling and packaging of substances and mixtures, amending and repealing ¹
EC n°1907/2006	REACH – Registration, Evaluation, Authorization and Restriction of Chemical Substances ¹
AMS5737	Steel, Corrosion and Heat-Resistant, Bars, Wire, Forgings, and Tubing 15Cr - 25.5Ni - 1.2Mo - 2.1Ti - 0.006B - 0.30V Consumable Electrode Melted 1650 °F (899 °C) Solution and Precipitation Heat Treated
NAS 4006	Aluminum coating
NAS1900 Rev 4	Procurement specification –Rivet, blind-General Purpose, bulbed, self-plugging, mechanically locked spindle.
NAS1919 Rev 8	Rivet, blind - general purpose, bulbed, NAS 1900 protruding head, mechanically-locked-spindle
QQ-A-430	Aluminium alloy rod and wire; for rivets and cold heading
QQ-N-281	Nickel-copper alloy bar, rod, plate, sheet, strip, wire, forgings, and structural and special shaped sections
QQ-P-35	Passivation treatments for austenitic, resisting steel (fastening devices), ferritic, and martensitic corrosion resistant steel (fastening devices)
QQ-P-416	Plating, Cadmium (Electrodeposited)

3 Material and manufacturer

3.1 Manufacturer material designation

The trade name of the product is defined as NAS1919.

3.2 Manufacturer

The product is manufactured by: Allfast Fastening Systems

3.3 Manufacturing Plant

Allfast Fastening Systems.
15200 Don Julian Rd.
City of industry. Los Angeles

Cage Code: 53551

¹ Published as European Union Regulation (EC)

4 Cross-references

Table 1 encloses the qualified couples (standard part number / proprietary part number)

Table 1 : Airbus / Manufacturer Part number cross reference

Airbus P/N reference	Allfast P/N Reference
NAS1919B04-xx	AF1919B04-xx
NAS1919B04Sxx	AF1919B04Sxx
NAS1919B04SxxU	AF1919B04SxxU
NAS1919C04-xx	AF1919C04-xx
NAS1919C04Sxx	AF1919C04Sxx
NAS1919C04SxxU	AF1919C04SxxU
NAS1919C04SxxW	AF1919C04SxxW
NAS1919C04SxxAU	AF1919C04SxxAU
NAS1919C04SxxWU	AF1919C04SxxWU
NAS1919M04-xx	AF1919M04-xx
NAS1919M04Sxx	AF1919M04Sxx
NAS1919M04SxxU	AF1919M04SxxU
NAS1919M04SxxW	AF1919M04SxxW
NAS1919M04SxxAU	AF1919M04SxxAU
NAS1919M04SxxWU	AF1919M04SxxWU
NAS1919B05Sxx	AF1919B05Sxx
NAS1919B05SxxU	AF1919B05SxxU
NAS1919C05-xx	AF1919C05-xx
NAS1919C05Sxx	AF1919C05Sxx
NAS1919C05SxxU	AF1919C05SxxU
NAS1919C05SxxW	AF1919C05SxxW
NAS1919C05SxxAU	AF1919C05SxxAU
NAS1919C05SxxWU	AF1919C05SxxWU
NAS1919M05-xx	AF1919M05-xx
NAS1919M05Sxx	AF1919M05Sxx
NAS1919M05SxxU	AF1919M05SxxU
NAS1919M05SxxW	AF1919M05SxxW
NAS1919M05SxxAU	AF1919M05SxxAU
NAS1919M05SxxWU	AF1919M05SxxWU
NAS1919B06-xx	AF1919B06-xx
NAS1919B06Sxx	AF1919B06Sxx
NAS1919B06SxxU	AF1919B06SxxU
NAS1919C06-xx	AF1919C06-xx
NAS1919C06Sxx	AF1919C06Sxx
NAS1919C06SxxU	AF1919C06SxxU
NAS1919C06SxxW	AF1919C06SxxW
NAS1919C06SxxAU	AF1919C06SxxAU
NAS1919C06SxxWU	AF1919C06SxxWU
NAS1919M06-xx	AF1919M06-xx
NAS1919M06Sxx	AF1919M06Sxx
NAS1919M06SxxU	AF1919M06SxxU
NAS1919M06SxxW	AF1919M06SxxW
NAS1919M06SxxAU	AF1919M06SxxAU
NAS1919M06SxxWU	AF1919M06SxxWU

(Continued)

Table 2 : Airbus / Manufacturer Part number cross reference (Concluded)

Airbus P/N reference	Allfast P/N Reference
NAS1919M08-xx	AF1919M08-xx
NAS1919M08Sxx	AF1919M08Sxx
NAS1919M08SxxU	AF1919M08SxxU
NAS1919M08SxxW	AF1919M08SxxW
NAS1919M08SxxAU	AF1919M08SxxAU
NAS1919M08SxxWU	AF1919M08SxxWU

5 Material application

The product shall be used in conjunction with the relevant design documents.

6 Qualification

6.1 Status

6.1.1 Qualification basis

Following specifications have been the basis for qualification:

- Technical Specification: NAS1900
- Supplier drawing part reference: NAS1919

Qualification is linked to a valid approval of the manufacturer according to the actual Airbus Quality Regulations. In case relevant approval should be withdrawn later, also this qualification shall become automatically obsolete.

Changes in the manufacturing drawing must be stated by the manufacturer and shall be subject to written approval of the Qualification Body before first delivery.

6.1.2 Qualification test report

The successful qualification has been documented in the qualification test report:

Reference number: 110108 Issue: 1 Dated 26/04/12

6.2 Manufacturing schedule

Qualified products in this document have been manufactured according to the manufacturing routes submitted from Allfast and included in the annex of the QTR110108 (NAS1900 Sealed Manufacturing Routes).

Changes in the manufacturing schedule which may adversely affect the quality of the product must be stated by the manufacturer and shall be subject to written approval of the Qualification Body before first delivery.

6.3 Special storage condition

Not applicable.

7 Release

Release testing shall be performed in accordance with the relevant specifications of clause 6.1.1 and specific agreements of clause 8 (if applicable).

8 Specific agreements

For Quality Conformance Inspection Tests, NAS1900 specification is applicable.

For acceptable bulb formation, NAS1919 qualified rivets installed in metallic plates must accomplish the following requirements:

- The minimum bearing diameter "A" dimension must accomplish or exceed values indicated in table -2
- Bulb form must be as per figure -1.
Abruptal changes in the external diameter of the bulb as per figure -2 are not acceptable.
Gaps between the structure and bulb that extend up to the fastener's shank, as per figure -3, are not acceptable.

Table 3 : Minimum bearing diameter requirement

Dia. code	Min bearing dia –"A" (mm)
-04	3,48
-05	4,29
-06	5,11
-08	6,76




Figure 1- Acceptable bulb formation




Figure 2- Abrupt change – Not acceptable bulb formation




Figure 3- Gap between bulb-structure reaching fastener's shank – Not acceptable

bulb formation

For quality conformance inspections, besides tests in NAS1900 specification, the manufacturer shall provide 5 cross sections per inspection lot of the blind rivet installed at minimum grip condition. These cross sections must show the min. bearing diameter measured on it.

9 Material safety data sheet

The supplier shall provide information enabling a safe use, according to REACH (EC n°1907/2006) and CLP (EC n°1272/2008) regulations.

In particular, for preparations and for the first delivery, the manufacturer shall provide a safety data sheet appropriate to the country of purchase/use.

For articles, the manufacturer shall provide information according to REACH Article 33, and additionally, safety data sheet shall be provided whenever available.

Site competent environment health and safety authority shall be the final recipient of the documents.

At least, document has to be delivered simultaneously with the product.

Material shall comply with A1091.

The supplier should provide chemical composition of the cured product and propose recycling possibilities (cured/uncured product) whenever relevant.

Confidential

RECORD OF REVISIONS

Issue	Clause modified	Description of modification
1 05/12		New standard
2 08/17	Table 1 6.1.2	NAS1919C04S**W, NAS1919M04S**W, NAS1919C05S**W, NAS1919M05S**W, NAS1919C06S**W, NAS1919M06S**W, NAS1919M08S**W added. Chapter 6.1.2 updated to reflect additions