

RESERVE FACTORS SUMMARY										
STRUCTURAL COMPONENT:						REFERENCE DOCUMENT:				
ZONE	ELEMENT	DRAWING	MATERIAL & TEMPER	LOAD CASE	LOAD TYPE	M A G	APPLIED VALUE	ALLOWABLE VALUE	R.F.	REFERENCE PAGE
				TEMPERAT.						REMARKS
Fusel. Left	Frame: F65 bt'n str's S2 – S3		3.1364N T42	ZCT (1)	T BD	F M	131183 –623	439326 –2088	> 2	Ultimate loads. End A. Outer fibre tension
Fusel. Right	Frame: F65 bt'n str's S37 – S38		3.1364N T42	GV325Z (13)	S TO	F M	8694 0	21735 0	> 2	Web shear.
Fusel. Left	Frame: F66 bt'n str's S15 – S16		3.4364 T7351	ZCT (1)	T BD	F M	154586 –3200	834148 –17267	> 2	Ultimate loads. End B. Outer fibre tension
Fusel. Right	Frame: F66 bt'n str's S27 – S28		3.4364 T7351	ML322Z (35)	T BD	F M	74796 –2314	285241 –8824	> 2	Ultimate loads. End A. Inner fibre tension
LOAD TYPES:				MAGNITUDES:				RESERVE FACTOR:		
T: TENSION C: COMPRESSION S: SHEAR TO: TORSION BD: BENDING BR: BEARING P: PRESSURE				FORCE (F): N MOMENT (M): $N \cdot m$ STRESS (S): N/mm^2 STRAIN (E): $\mu mm/mm$ FLOW (Q): N/mm				$RF = \frac{\text{FAILURE LOADS}}{\text{APPLIED LOADS}}$		