



Optical Music Recognition for Homophonic LilyPond File Generation

Evan Matthews

Executive Summary

abstract goes here...

Department of Computer Science
University of Illinois Urbana-Champaign
United States
May 10th, 2024

Optical Music Recognition for Homophonic LilyPond File Generation

Evan Matthews

ACM Reference Format:

Evan Matthews. 2024. Optical Music Recognition for Homophonic LilyPond File Generation. In . ACM, New York, NY, USA, 4 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

1 INTRODUCTION

1.1 Initial Proposal

TODO: Introduction citations [2? , 3]

In the world of music or audio transcription/arrangement, the complexity of sound and score data has allowed human performance to remain the current state-of-the-art. Several factors contribute to this circumstance: the number of potential audio and score file types, ambiguity on how performance qualities are notated, and overall inconsistencies between recordings and their respective scores. Machine learning models, in turn, have been a crucial step towards reducing these inconsistencies. Their ability to learn the nonlinearities and artistic qualities that otherwise plague audio computation have allowed for noteworthy advancements such as the WaveNet [9]. The remaining issue in the process of sound generation is the amount of data available to train with. Worthwhile audio data remains difficult to collect due to its large size and potential copyright issues. In particular, trying to condition off another medium is incredibly difficult as current datasets lack the correlations necessary to streamline the audio transcription process. Datasets such as MAESTRO [4] are close to ideal results, but some intermediate steps are needed to learn correlations between audio files and musical scores.

With the following conditions in mind, I propose an Image-to-MIDI model to serve a few purposes. First, this model serves to convert image data to relative musical data to a high degree of accuracy. The process of converting MIDI to an image is trivial, but the opposite is a known Optical Music Recognition (OMR) problem in that the correlation is nonexistent. Second, a highly reliable model of this type is capable of serving as an intermediate step in future audio computation endeavors, as the nontrivial nature of OMR is a barrier for reliable model training between scores and other types of audio data. Finally, a conversion of this type allows

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Conference'17, July 2017, Washington, DC, USA

© 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

for more flexible datasets because MIDI can be converted into a number of other audio file types.

1.2 Known Limitations

Given the vast complexity of western music notation and intricacies in notation/time alignment, the proposed model has a pessimistic approach. That is, given a small subset of musical data (*among all notated music*) and some model, results can be expected to only match expected outputs through one or more of: pitch, rhythm, duration, and overall formatting. Existing research in OMR supports these expectations. First, several digital notation systems exist for music, including:

- Standards like *MusicXML*, *Lilypond* and *MIDI*,
- Software-specific formats from *Musescore*, *Sibelius* and *Finale*,
- *KERN* from the Humdrum tool-set [?],
- Mayer, et al.'s *Linearized MusicXML* [6], and
- Contreras, et al.'s untitled "end-to-end OMR" encoding language [2].

Each format provides benefits and drawbacks towards generalized OMR, but combined research efforts have yet to hone in on a particular format. Second, current research continues to limit its effective musical scope: constant genre, time period composed, single vs. multi-line pieces, and single vs. multiple measures, to name a few. These limitations are to be expected as a means of balancing experiment accuracy with the subset of musical notation to be recognized. However, no paper to date has intended to capture a high accuracy while completely generalizing the space of recognizable music.

Finally, the state-of-the-art for machine-learning-based OMR lies in the implementation of Convolutional Recurrent Neural Networks (CRNN). This model type is preferred over CNN for its ability to learn data as order-dependent sequences- a crucial philosophy in parsing and understanding musical scores in general. However, it should be noted that CNNs are still viable for their non-order-dependent musical problems, such as Nugroho and Zahra's work on individual note and duration recognition [7].

1.3 Research Questions

Despite low research expectations, I believe that a few questions can be posed and answered for the purpose of bounding requirements on a larger, all-encompassing Image-to-MIDI model:

- RQ1** What forms of recognition can be expected from a generalized CRNN implementation?
- RQ2** How does Lilypond recognition compare against other standard and custom formats?
- RQ3** What conflicts currently prevent state-of-the-art models from further generalization?

For **RQ1**, I aim to recover noticeable results regarding the CRNN model's ability to generalize sequences of data from scores. Hence, whether or not order-dependent training can pick up on note, rhythm or duration sequences will be crucial to my final analysis. Next, promising results from **RQ1** will be compared against existing research to answer **RQ2**. In particular, the generalized CRNN model's ability to render score data as Lilypond (.ly) files is compared against other notation systems to determine if a more complex Lilypond-based model would be successful. Finally, for **RQ3**, the results of CRNN model training are criticized on what should be generalized or further implemented in order to reliably translate score images into Lilypond data. This research question refers to all-encompassing limitations such as in 1.2 along with experiment-specific limitations.

2 BACKGROUND

2.1 Optical Music Recognition

TODO: OMR background

2.2 Lilypond

Lilypond was chosen for dataset file representation as it maintains accurate translation between digital (MIDI) and visual (image) notation systems [5]. In particular, translation from Lilypond to MIDI is trivial, and Lilypond provides a more intuitive representation of musical information compared to raw bytes of MIDI data. This notation language consists of multiple layers to separate score components:

- **Document level:** components related to page layout and high-level musical details, (number of instruments/tracks, score engraving information).
- **Music level:** components related to low-level musical details, (notes, rhythms, durations, key/time signatures, tempo).

At the document level, aspects of a score that stay mostly or completely constant throughout a piece are indicated by specific, indent-sensitive keywords. For example, the number of voices/instruments and respective number of staves are initialized with the `\Voice` and `\context` commands, while high-level musical information is initialized by commands such as `\time` for time signature, `\key` for key signature, and `\tempo` for performance speed in beats per minute.

At the music level, rhythmic musical symbols are notated according to their pitches and relative time duration. pitches are all characters *a, b, c, d, e, f, g, r*, where *r* is a "rest" meaning no pitch occurs. To ascend or descend in pitch beyond a single musical "octave," the `'` and `,` characters are appended to indicate one or more octave ascendings or descendings, respectively. Pitches are also preceded by a rhythmic value representing its duration in time. These values are typically powers of two, (but can technically be any positive floating-point value), and they dictate how long a pitch is played with respect to the piece's time signature. For example, a score with time signature = 2/4 indicates that each measure has two beats, and each beat is the length of a quarter




Figure 1: Lilypond (.ly) code and rendering

note (hard-coded in the denominator). In this case, the line `"c4 d4"` would represent two quarter (4) notes or a single measure in the provided time signature. Additionally, notes without defined durational values take on the previous note's duration in a line, so a series of equal-duration notes is represented by one durational value. Finally, separations between measures are made with `"| %n"`, marking the end of measure *n*. Figure 1 compares the rendering of a single staff of music with its relative Lilypond notation.¹

3 EXPERIMENT

3.1 CRNN Model

TODO: CRNN model The proposed Image-to-MIDI model is a smaller model referencing Shi, et al.'s pioneering work in the creation of CRNNs [8]. The model itself consists of multiple two-dimensional Convolutional/MaxPooling pairs for the purpose of extracting features from the initial score images. Batch normalization layers are also applied to refine data recovered from the feature extraction. Lastly, features are pushed through two bidirectional LSTM layers- the recurrent layers of the model- for data prediction with respect to "sequences" of the images. In this case, sequences of the image data are the pixel columns of $(595 \times H)$ images, where *H* is the height of the image dependent on the overall "length" of the music.

3.2 Data Specifications

TODO: dataset specifics MIDI data used for this experiment has been narrowed down to strictly two-stave piano "inventions" by Johann Sebastian Bach [1] to maintain rhythmic and compositional uniformity. These works maintain relatively similar quantization schemes (rhythms and durations of notes), are short, and have several clear transcriptions for research, education, and entertainment purposes.

4 RESULTS

TODO: results

5 DISCUSSION

The following section details my analysis with respect to previously discussed research questions.

¹The time signature *C* or "common-time" is another common way of writing 4/4.




Figure 2: CRNN architecture, as modeled by Shi, et al. [8]

5.1 Model Generalization (RQ1)

5.2 Format Comparison (RQ2)

5.3 Model Criticism (RQ3)

6 CONCLUSIONS

TODO: conclusions

REFERENCES

- [1] [n.d.]. Complete Bach Midi Index. <https://www.bachcentral.com/midiindexcomplete.html>
- [2] María Alfaro-Contreras, JoséM. Iñesta, and Jorge Calvo-Zaragoza. 2023. Optical music recognition for homophonic scores with neural networks and synthetic music generation. *International Journal of Multimedia Information Retrieval* 12, 1 (2023), 12. <https://doi.org/10.1007/s13735-023-00278-5>
- [3] Andrea, Paoline, and Amalia Zahra. 2021. Music note position recognition in optical music recognition using convolutional neural network. *International Journal of Arts and Technology* 13, 1 (2021), 45–60. <https://doi.org/10.1504/IJART.2021.115764>
- [4] Curtis Hawthorne, Andriy Stasyuk, Adam Roberts, Ian Simon, Cheng-Zhi Anna Huang, Sander Dieleman, Erich Elsen, Jesse Engel, and Douglas Eck. 2019. Enabling Factorized Piano Music Modeling and Generation with the MAESTRO Dataset. In *International Conference on Learning Representations*. <https://openreview.net/forum?id=r1IYRjC9F7>
- [5] Lilypond 2024. Lilypond music notation for everyone. <https://lilypond.org/doc/v2.25/Documentation/web/index>
- [6] Jiří Mayer, Milan Straka, Jan Hajič jr. au2, and Pavel Pecina. 2024. Practical End-to-End Optical Music Recognition for Pianoform Music. arXiv:2403.13763 [cs.CV]
- [7] Douglas Rakasiwi Nugroho and Amalia Zahra. 2024. Musical Note Position and Duration Recognition Model in Optical Music Recognition Using Convolutional Neural Network. *Journal of Image and Graphics* 12, 1 (Jan 2024), 32–39. <https://doi.org/10.18178/joig.12.1.32-39>
- [8] Baoguang Shi, Xiang Bai, and Cong Yao. 2015. An End-to-End Trainable Neural Network for Image-based Sequence Recognition and Its Application to Scene Text Recognition. arXiv:1507.05717 [cs.CV]



Figure 3: Excerpt of Invention No.4; cropped/prepared rendering of Invention No.8.

349	[9] Aaron van den Oord, Sander Dieleman, Heiga Zen, Karen Si-	Senior, and Koray Kavukcuoglu. 2016. WaveNet: A Generative	407
350	monyman, Oriol Vinyals, Alex Graves, Nal Kalchbrenner, Andrew	Model for Raw Audio. arXiv:1609.03499 [cs.SD]	408
351			409
352			410
353			411
354			412
355			413
356			414
357			415
358			416
359			417
360			418
361			419
362			420
363			421
364			422
365			423
366			424
367			425
368			426
369			427
370			428
371			429
372			430
373			431
374			432
375			433
376			434
377			435
378			436
379			437
380			438
381			439
382			440
383			441
384			442
385			443
386			444
387			445
388			446
389			447
390			448
391			449
392			450
393			451
394			452
395			453
396			454
397			455
398			456
399			457
400			458
401			459
402			460
403			461
404			462
405			463
406			464