# Nothing is happening

3 3

海映月 (ELEA BRIANT)

All Sections

Hello,
I have an issue, when I do the command, nothing is printed.

```
PS C:\Users\Elea Bnant\mp2-CactuSunshin> ./mp2.sh setup
PS C:\Users\Elea Bnant\mp2-CactuSunshin> ./mp2.sh test all
PS C:\Users\Elea Bnant\mp2-CactuSunshin> ./mp2.sh test all
PS C:\Users\Elea Bnant\mp2-CactuSunshin>  ./mp2.sh test all
PS C:\Users\Elea Bnant\mp2-CactuSunshin>  ./mp2.sh test all
PS C:\Users\Elea Bnant\mp2-CactuSunshin> ./mp2.sh update
PS C:\Users\Elea Bnant\mp2-CactuSunshin> ./mp2.sh test all
PS C:\Users\Elea Bnant\mp2-CactuSunshin>
```

I followed the setup instruction closely and did the same. When I did the tests without anything being implemented it did the same things.  Do you know why it is happening ?
I'm on a windows machine, I don't know if it makes any difference.

Search entries or author | Unread | Subscribe

Reply

---

吳述宇 (WU,SHU-YU) (https://cool.ntu.edu.tw/courses/46296/users/186220)

Yesterday

The command will work if u use them on wsl or linux

Reply

---

楊德倫 (TE-LUN YANG) (https://cool.ntu.edu.tw/courses/46296/users/184997)

Yesterday

In mp0, the teaching assistant provided instructions on how to create an xv6 environment. mp2 is based on mp0 and adds the shellscript program provided by the teaching assistant to help us test the results after running programs directly in the container. You might as well confirm whether your WSL is enabled. If so, use the environment creation instructions mentioned by the teaching assistant in the manual (mp2-spec) to confirm whether your mp2 environment (especially the container) is enabled. Perhaps after everything is confirmed, the instructions you use can also display some information.



海映月 (ELEA BRIANT) (https://cool.ntu.edu.tw/courses/46296/users/229908)

Yesterday

With the methods from mp0, i have an issue with make qemu. It's probably because there is no Makefile in xv6. Or should I just replace xv6 by mp2-[My-name]?

```
PS C:\Users\Elea Bnant> cd mp2-CactuSunshin
PS C:\Users\Elea Bnant\mp2-CactuSunshin> docker pull ntuos/mp2
Using default tag: latest
latest: Pulling from ntuos/mp2
Digest: sha256:9e0deb936da7667634dc905f22aa7bb590e4aea819bc957a94f0b1deb0c6d9e1
Status: Image is up to date for ntuos/mp2:latest
docker.io/ntuos/mp2:latest
PS C:\Users\Elea Bnant\mp2-CactuSunshin> docker run -it -v ${PWD}\xv6:/home/os_mp2/xv6 ntuos/mp2
docker: Error response from daemon: failed to create task for container: failed to create shim task: OCI runtime create
failed: runc create failed: unable to start container process: exec: "/sbin/init": stat /sbin/init: no such file or dire
ctory: unknown.
PS C:\Users\Elea Bnant\mp2-CactuSunshin> docker run -it --entrypoint /bin/bash -v ${PWD}\xv6:/home/os_mp2/xv6 ntuos/mp2
root@0f2812ed1029:/# cat /etc/os-release
PRETTY_NAME="Debian GNU/Linux 11 (bullseye)"
NAME="Debian GNU/Linux"
VERSION_ID="11"
VERSION="11 (bullseye)"
VERSION_CODENAME=bullseye
ID=debian
HOME_URL="https://www.debian.org/"
SUPPORT_URL="https://www.debian.org/support"
BUG_REPORT_URL="https://bugs.debian.org/"
root@0f2812ed1029:/# make qemu
make: *** No rule to make target 'qemu'.  Stop.
root@0f2812ed1029:/# cd /home/os_mp2/xv6
root@0f2812ed1029:/home/os_mp2/xv6# make qemu
make: *** No rule to make target 'qemu'.  Stop.
```

Reply