[MP2] ./mp2.sh container start 報錯 (更：已解決)

馬定璿 (MA,TING-XUAN)

All Sections

4

我在輸入 ./mp2.sh container start 後會出現Error response from daemon: container xxx is not running。 docker ps -a 也顯示狀態為exit

```
Container 'mp2' started.
Error response from daemon: container ef0808657dcee5ee78b815a3699ceb6e2667f48c1ac0ee8431c3d777dd5d0919 is not running
root@MSI:/mnt/d/馬定璿/NTU/113-2/OS/mp2/mp2-fxck2# docker ps -a
CONTAINER ID   IMAGE              COMMAND       CREATED         STATUS                       PORTS     NAMES
ef0808657dce   ntuos/mp2          "bash"        2 minutes ago   Exited (0) 2 minutes ago             mp2
acc035f1339a   ntuos/mp2:latest   "/sbin/init"  4 minutes ago   Created                              zen_lamport
8d2744e0f617   ntuos/mp2          "/sbin/init"  5 minutes ago   Created                              objective_brattain
a26d3cddb82a   ntuos/mp1          "bash"        5 days ago      Exited (129) 5 days ago              zen_chatterjee
db645f3937de   ntuos/mp1          "bash"        11 days ago     Exited (129) 11 days ago             boring_bhabha
bf8f51f2793e   ntuos/mp1          "bash"        12 days ago     Exited (129) 12 days ago             infallible_knuth
```

解法 (WSL)：

會出問題似乎是因為mp2.sh的DOCKER_IT_FLAG沒有設定好，如果把if else 全部註解起來似乎就能解決。if else是用來檢測環境的，根據環境設定DOCKER_IT_FLAG，註解起來不確定會不會有其他問題，不過暫時可以解決container error。

```
15  DOCKER_IT_FLAG="-it"
16  #if [ -n "$GITHUB_ACTIONS" ]; then
17  #    DOCKER_IT_FLAG=""
18  #elif [ -n "$TRAVIS" ]; then
19  #    DOCKER_IT_FLAG=""
20  #elif [ -n "$GITLAB_CI" ]; then
21  #    DOCKER_IT_FLAG=""
22  #else
23  #    DOCKER_IT_FLAG=""
24  #fi
```

Search entries or author | Unread | Subscribe

Reply

吳述宇 (WU,SHU-YU) (https://cool.ntu.edu.tw/courses/46296/users/186220)

Mar 23, 2025

卡個

Reply



李怡霈 (LEE I-PEI) (https://cool.ntu.edu.tw/courses/46296/users/220438)

Mar 23, 2025

如果是用Mac的話

mp2.sh要用 https://cool.ntu.edu.tw/courses/46296/discussion_topics/381980 (https://cool.ntu.edu.tw/courses/46296/discussion_topics/381980) 裡面助教留言給的mp2.sh跑才不會有問題

可以先試試看 但如果已經試過是別的問題的話我就不知道了~

Reply



黃建碩 (HUANG, JIAN-SHUO) (https://cool.ntu.edu.tw/courses/46296/users/180833)

Mar 23, 2025

把 docker run 後面的 bash 改成 sleep infinity 就不會 exit 了

Edited by 黃建碩 (HUANG, JIAN-SHUO) (https://cool.ntu.edu.tw/courses/46296/users/180833) on Mar 23 at 3:18pm



楊子慶 (YANG, TZU-CHING) (https://cool.ntu.edu.tw/courses/46296/users/229158)

Mar 24, 2025

感謝同學們的提問與回答。

是的，請使用 https://cool.ntu.edu.tw/courses/46296/discussion_topics/381980 (https://cool.ntu.edu.tw/courses/46296/discussion_topics/381980) 的 mp2.sh，其解決了錯誤的 flag 設定。

Reply