

DIP-SW User Manual

for 1chipMSX, Zemmix Neo, SX-1 and related (Cyclone I series)

OCM-PLD Pack v3.9 by KdL

| DIP-SW | FUNCTION | STATUS | DESCRIPTION |
|--------|------------------|-----------|---|
| 1 | CPU Clock | OFF | Standard mode 3.58MHz |
| | | ON | Custom Speed mode 4.10MHz to 8.06MHz (10.74MHz on system bus) • Press [F12] key to change clock type (3.58MHz >> 5.37MHz >> Custom Speed) • The external clock is set on [Sync to CPU] by default • [Turbo Pana] is 5.37MHz like the original specification • A special hybrid clock [Turbo MegaSD] is enabled by default |
| 2/3 | Video Output | OFF / OFF | Composite / S-Video • 15kHz, 50Hz+60Hz, interlaced video signal |
| | | OFF / ON | RGB w/ Audio Out (a mono signal inside the video cable) • 15kHz, 50Hz+60Hz, interlaced video signal, requires a VGA to SCART cable |
| | | ON / OFF | VGA Mode for LED TV or LED Display • Progressive video signal 31kHz / 50Hz+60Hz with the ability to set the pixel ratio 1:1 at 60Hz |
| | | ON / ON | VGA+ Mode for CRT Monitor (legacy output) (hardware scanlines on Zemmix Neo) • Progressive video signal 31kHz / 50Hz+60Hz / SETSMART -D0 must be executed to force 60Hz |
| 4 | Cartridge Slot-1 | OFF | External Slot-1 • Advised like default |
| | | ON | Internal ESE-MegaSCC+ 1024kB (shared w/ the 2nd half of ESE-MegaSCC+ Slot-2) • External Slot-1 is disabled • Memo: the CMT toggle is [Scroll Lock] key (disabled by default) |
| 5/6 | Cartridge Slot-2 | OFF / OFF | External Slot-2 • Advised like default |
| | | OFF / ON | Internal ESE-MegaRAM ASCII-8K 1024kB • External Slot-2 is disabled |
| | | ON / OFF | Internal ESE-MegaSCC+ 2048kB • External Slot-2 is disabled |
| | | ON / ON | Internal ESE-MegaRAM ASCII-16K 2048kB • External Slot-2 is disabled |
| 7 | Internal Mapper | OFF | Internal 2048kB RAM • Advised like default |
| | | ON | Internal 4096kB RAM |
| 8 | Internal MegaSD | OFF | Disabled |
| | | ON | Enabled • Advised like default |