

AVT EMC 4K MiniCam

High resolution (UHD) Camera
especially for EMC- and test laboratories,
as well as general applications



Fully compatible with different visual inspection
software and MiniCam programs



- ⇒ **4K Camera** for EMC labs and test fields with high interference immunity
- ⇒ different resolutions selectable (640 x 360 up to 3840 x 2160)
- ⇒ **Pan/Tilt/Zoom inside camera** controlled by software
- ⇒ easy to use in hardware and software
- ⇒ high quality vision sensor
- ⇒ USB Video Class (UVC) compliant
- ⇒ data transmission with optical fibers (USB 3.0)
- ⇒ small housing in slim design
- ⇒ high field immunity > 100 V/m

options:

- ⇒ integrated rechargeable battery (5 Ah)
- ⇒ optic lens for different angles
- ⇒ higher interference immunity

MADE IN GERMANY

All options on: www.world-of-emc-equipment.com

Ordering informations

AVT - EMC4K - xxx - x - x

emc hardened
4K MiniCam

focal length
032: 3,2 mm
045: 4,5 mm
068: 6,8 mm
120: 12,0 mm

version
01: version 1

internal battery
-: without battery
A: with battery

Example: AVT-EMC4K-120-01

Technical specifications

Optics

focal length	3,2	4,5	6,8	12,0
focus distance	103°	68°	48°	30°
field of view	70°	42°	28°	17°
optical format, sensor	1/2,5", CMOS Sony IMX317			

Resolutions

small size (below HD)	640x360, 640x480, 800x600, 960x540			
HD-resolutions	1280x720, 1280x 960, 1600x1200, 1920x1080			
2K-resolutions	2048x1536, 2688x1512, 2592x1944			
4K-resolution (UHD)	3840x2160 (Pixel Größe 1,62 µm x 1,62 µm)			
frame rates	30 fps (alle Auflösungen)			

General informations

USB video class compliant	yes, Microsoft WHQL certified		
temperature operating range	-10°C ... 50°C		
length of fiber optic cable	10 m, 20 m, 30 m, 50 m, 70 m, 100 m		
data- and control interface on PC/Laptop	USB 3.0 (plug A)		

Electrical specifications

	min	max
supply voltage (DC, 5 V typ.)	4,85 V	5,25 V
power (camera without battery charging)	0,6 W	2,6 W
current (operation / charging battery / operation and charging)	0,11 / 0,0 / 0,11 A	0,52 / 2,0 / 2,52 A
delivery of power supply / charger / external battery	yes / sold as option / sold as option	

Dimensions

Length of the camera without connectors	126 mm
Width	50 mm
Height (with foot)	50 mm (60 mm)
Weight	370 g

Contact

Errors and changes excepted.

AVT GmbH • Automatisierungs- und Verfahrenstechnik • Am Hammergrund 1 • 98693 Ilmenau • Germany
Tel: +49 (0)3677 6479-56 • Fax: +49 (0)3677 6479-69 • Web: www.avt-ilmenau.de • Mail: info@avt-ilmenau.de

