

chapter-5

July 16, 2025

0.1 Overview

The objective of this data analysis practical is to learn how to visually explore and quantify muscle fatigue from EMG recordings. All of the recordings analyzed below can be found in our GitHub repository (<https://github.com/emckiernan/electrophys/tree/master/EMG/EMGfatigue/data>), or new recordings can be obtained by performing the experimental practical in [Ch. 4: Using EMG to measure muscle fatigue](#). The duration of this practical could vary depending on the programming experience of students and the goals of the class. This practical could be carried out in multiple sessions, especially if students are asked to first record EMGs and then analyze their own recordings. Or, since this is an analysis practical, it could be done asynchronously as an assigned homework. Before carrying out this analysis practical, it is recommended that students first complete the analysis practicals in [Ch. 2: Graphing and visually exploring EMG data](#) and [Ch. 3: Filtering, processing, and analyzing EMG data](#).

0.2 Setting up the notebook

We begin by setting up the Jupyter notebook and importing the Python modules for plotting figures. We include commands to view plots in the notebook, and to create figures with good resolution and large labels.

```
[256]: # command to view figures in Jupyter notebook
      %matplotlib inline

      # import plotting module
      import matplotlib.pyplot as plt

      # commands to create high-resolution figures with large labels
      %config InlineBackend.figure_formats = {'png', 'retina'}
      plt.rcParams['axes.labelsize'] = 18 # fontsize for figure labels
      plt.rcParams['axes.titlesize'] = 20 # fontsize for figure titles
      plt.rcParams['font.size'] = 16 # fontsize for figure numbers
      plt.rcParams['lines.linewidth'] = 1.6 # line width for plotting
```

Next, we import the necessary modules and features to perform extract data, perform analysis, etc.

```
[119]: # import modules
      import math
      import numpy as np
```

```

import os
import pandas as pd
import scipy as sc
from scipy import signal
from scipy.fftpack import fft
from scipy.signal import butter, lfilter, filtfilt
import wave

```

To analyze recordings, we first define a function that will allow us to quickly run the basic data extraction, visualization, and signal processing. This is the same function we defined in the [Ch. 3: Filtering, processing, and analyzing EMG data](#) practical.

```

[120]: def processEMG(file,graph):
    # open .wav file by specifying the path and filename
    record = wave.open(file)
    # extract number of channels, sample rate, data
    numChannels = record.getnchannels() # number of channels
    N = record.getnframes() # number of frames
    sampleRate = record.getframerate() # sampling rate
    # extract data from the .wav file
    dstr = record.readframes(N * numChannels)
    waveData = np.frombuffer(dstr, np.int16)
    # calculate time window
    timeEMG=np.linspace(0, len(waveData)/sampleRate, num=len(waveData))
    # calculate frequency
    freq = 1/np.mean(np.diff(timeEMG))
    # band-pass Butterworth filter at 10-400Hz
    b, a = butter(2, ([10, 400]/(freq/2)), btype = 'bandpass')
    dataf = filtfilt(b, a, waveData)
    # rectify filtered EMG signal
    absSignal = np.absolute(dataf)
    timeAbs=np.linspace(0, len(absSignal)/sampleRate, num=len(absSignal))
    # low-pass Butterworth filter for envelope detection
    lowp = 8
    sfreq = sampleRate
    low_pass = lowp/sfreq
    b, a = sc.signal.butter(4, low_pass, btype='lowpass')
    datafrle = filtfilt(b, a, absSignal)
    # save relevant data in array
    xx={'sampleRate':sampleRate,\
        'waveData':waveData,\
        'timeEMG':timeEMG,\
        'freq':freq,\
        'dataf':dataf,\
        'absSignal':absSignal,\
        'timeAbs':timeAbs,\
        'datafrle':datafrle

```

```

    }
    # plot EMG
    if graph:

        fig, (ax1,ax2,ax3) = plt.subplots(3,1,figsize = (20,15))

        # plot filtered data
        ax1.plot(timeEMG,dataf, 'b')
        ax1.set_title('Raw data', fontsize=20)
        ax1.set_xlim(0,max(timeEMG))
        #ax1.set_ylim(-8000,4000)
        ax1.set_xlabel('time (s)')
        ax1.set_ylabel('voltage ($\mu$V)')

        # plot rectified data with envelope
        ax2.plot(timeAbs,datafrle*3, 'r', linewidth=2.5) # multiply envelope to
↪see data fit
        ax2.plot(timeAbs,absSignal, 'b', alpha=0.4)
        ax2.set_title('Rectified EMG with envelope', fontsize=20)
        ax2.set_xlim(0,max(timeEMG))
        ax2.set_xlabel('time (s)')
        ax2.set_ylabel('voltage ($\mu$V)')

        # plot envelope with potential threshold
        ax3.plot(timeAbs,datafrle, 'b')
        #plt.axhline(y=200, color='k',linewidth=2.0, linestyle='--') #
↪potential threshold
        ax3.set_title('Enveloped EMG', fontsize=20)
        ax3.set_xlim(0,max(timeEMG))
        #ax3.set_ylim(0,1200)
        ax3.set_xlabel('time (s)')

        # spacing between subplots
        plt.tight_layout(pad=3.0)

    return xx

```


0.3 Muscle fatigue over a single trial

As muscles contract, they also fatigue, especially if a significant effort is exerted, or if the contraction is prolonged. There are several ways we can visualize and quantify fatigue.

0.3.1 Changes in EMG signal amplitude with fatigue

The following recording was obtained from the biceps muscle while performing a sustained concentric contraction, i.e. holding a weight with the arm bent at 90 degrees for 50 seconds (contraction starts around $t=5s$ and ends at $t=55s$).

```
[52]: xx=processEMG(file='../data/S3/concentric/S3_EMG_concentric_trial0.wav',graph=1)
```



As we can see in the above recording, the amplitude of the signal decreases as the recording progresses and the muscle presumably fatigues. One way to quantify this is to bin the data and find the maximum amplitude of the signal within each bin. For ease, we first divide the data into 1 second bins.

```
[59]: # calculate number of 1 second bins in the recording; 'floor' to expresses
      ↪ number as integer
nbins = math.floor(len(xx['waveData'])/xx['sampleRate'])
print('The recording has %d bins of 1 second duration.' % (nbins))

# function to create bins, adapted from https://www.python-course.eu/
↪ pandas_python_binning.php
def createBins(lower_bound, width, quantity):
    bins = []
    for low in range(lower_bound, lower_bound + quantity*width + 1, width):
        bins.append((low, low+width))
    return bins

# run function to create bins
```

```
secBins = createBins(0,xx['sampleRate'],nbins)
```


The recording has 61 bins of 1 second duration.

Next, we iterate over the bins, calculating the maximum amplitude for each bin and plot the results.

```
[56]: # calculate max amplitude over the bins
x = secBins
y = xx['absSignal']
maxamps = []

for n in range(0,len(x)):
    maxAmp=y[min(x[n]):max(x[n])].max()
    maxamps.append(maxAmp)

# plot results
plt.figure(figsize=(20,6))
plt.plot(maxamps,'o-')
plt.title('Maximum EMG amplitude')
plt.xlabel('time (s)')
plt.xlim(0,max(xx['timeEMG']))
plt.ylabel(r'voltage ($\mu$V)');
```




The above graph shows that the maximum amplitude decreases slightly as the recording progresses. However, outliers make the trend a less clear than it might be. Instead, we can also iterate over the bins and calculate the mean amplitude to see if that gives us a clearer picture of the decrease due to fatigue.

```
[57]: # calculate mean amplitude over bins
meanamps = []
for n in range(0,len(x)):
    meanAmp=y[min(x[n]):max(x[n])].mean()
    meanamps.append(meanAmp)

# plot results
```

```
plt.figure(figsize=(20,6))
plt.plot(meanamps,'o-')
plt.title('Mean EMG amplitude')
plt.xlabel('time (s)')
plt.xlim(0,max(xx['timeEMG']))
plt.ylabel(r'voltage ( $\mu$ V)');
```



In this case, the trend is much clearer and we can see how the mean amplitude decreases throughout the recording, indicating muscle fatigue. One crude but effective way to calculate the size of the decrease is by taking the difference between the peak mean amplitudes at the beginning (bin 6) and end (bin 54) of the muscle activity.

```
[58]: ampChange = meanamps[6] - meanamps[54]
      print(ampChange)
```


```
3321.231964621004
```

The above calculation shows an over 3,000 microvolt decrease in amplitude over the course of the recording.

We can also calculate the variance over the bins, which shows a similar decrease, also indicating fatigue.

```
[63]: varamps = []
      for n in range(0,len(x)):
          varAmp=y[min(x[n]):max(x[n])].var()
          varamps.append(varAmp)

      # plot results
      plt.figure(figsize=(20,6))
      plt.plot(varamps,'o-')
      plt.title('Variance in EMG amplitude')
      plt.xlabel('time (s)')
      plt.xlim(0,max(xx['timeEMG']));
```



0.4 Changes in EMG frequency with fatigue

Muscle fatigue is also marked by a decrease in the frequency of the EMG signal, which can result from both a decrease in the firing rate of individual motor units and a decrease in the total number of active motor units. For ease of analysis, we first shorten the EMG signal by removing the baseline activity before and after the muscle contraction. In other words, the shortened EMG has only the activity during the contraction.

```
[92]: # shorten EMG to leave only contraction activity; run on filtered_
      ↪ (non-rectified) data
def shortEMG(signal, threshold):
    difSignal = np.diff(signal)
    startind=np.where(difSignal>threshold)[0][0]
    endind=np.where(difSignal[::-1]>threshold)[0][0]
    endind=len(difSignal)-endind
    return(signal[startind:endind])

workdata = shortEMG(xx['dataf'],150)

[93]: # plot results to compare original to shortened EMG
fig, (ax1,ax2) = plt.subplots(2,1,sharex=False,sharey=False,figsize = (20,10))

# plot full EMG
ax1.plot(xx['timeEMG'],xx['dataf'],'b')
ax1.set_title('Full EMG')
ax1.set_ylabel('voltage ( $\mu V$ )')
ax1.set_xlabel('time (s)')
#ax1.set_xlim(0,max(xx['timeEMG']))


# plot shortened EMG
ax2.plot(np.arange(0,len(workdata))/xx['sampleRate'],workdata,'b')
ax2.set_title('Shortened EMG')
ax2.set_ylabel(r'voltage ( $\mu V$ )')
```

```

ax2.set_xlabel('time (s)')
#ax1.set_xlim(0,max(xx['timeEMG']))

# spacing between subplots
plt.tight_layout(pad=3.0)

```



Next, we divide the EMG data into windows and define that as the ‘workdata’ which we will run through the frequency analysis.

```

[94]: def windows(data,npoints,step):
        datapts = np.size(data)
        anchorpts = np.arange(0,datapts-npoints,step)
        noverlap = len(anchorpts)
        ovData = [data[anchorpts[i]:anchorpts[i]+npoints] for i in
        ↪range(0,noverlap)]
        return(ovData)

windowedEMG = windows(workdata,xx['sampleRate'],xx['sampleRate'])

```

Now, we calculate the Power Spectral Density (PSD) using a Fourier transform.

```

[95]: # function for calculating Power Spectral Density (PSD)
# adapted from https://stackoverflow.com/questions/1523814/
# units-of-a-fourier-transform-fft-when-doing-spectral-analysis-of-a-signal/
↪1524535

def PSD(data):
    ps = np.abs(np.fft.fft(data))**2
    timeStep = 1 / xx['sampleRate']
    freqs = np.fft.fftfreq(data.size, timeStep)

```

```

    idx = np.argsort(freqs)
    goodinds = np.where(freqs[idx]>0)[0]
    F = freqs[idx][goodinds]
    P = ps[idx][goodinds]
    return([F,P])

```

```
F,P = PSD(windowedEMG[0])
```

We plot the results, showing the EMG signal in the first bin (bin 0), the PSD for that bin, and the log of the PSD for the same bin.

```

[98]: fig = plt.figure(figsize=(20,15))


# EMG signal
ax = plt.subplot(311)
ax.plot(np.arange(0,xx['sampleRate'])/xx['sampleRate'],windowedEMG[0])
plt.xlabel('Time [s]')
plt.ylabel('Voltage')
plt.title('Bin 0 - Time Domain')

# PSD
ax = plt.subplot(312)
ax.plot(F,P)
plt.xlim(10,400)
plt.xlabel('Frequency (Hz)')
plt.ylabel('Voltage^2')
plt.title('Bin 0 - PSD')

# log PSD
ax = plt.subplot(313)
ax.plot(F,np.log(P))
plt.xlim(10,400)
plt.xlabel('Frequency (Hz)')
plt.ylabel('log(Voltage^2)')
plt.title('Bin 0 - log(PSD)')

plt.tight_layout(pad=3.0)

```



The above plots show the frequency analysis for just the first bin. Now, to examine the effects of fatigue, we can compare the first bin, bin number 10, and the last bin of the recording to see how the PSD changes.

```
[104]: fig = plt.figure(figsize=(12,7))


ax = plt.subplot(111)
ax.plot(PSD(windowedEMG[0])[0],
        PSD(windowedEMG[0])[1],
        label='First Window',alpha=.5)

ax.plot(PSD(windowedEMG[10])[0],
        PSD(windowedEMG[10])[1],
        label='Window 10',alpha=.5)

ax.plot(PSD(windowedEMG[-1])[0],
        PSD(windowedEMG[-1])[1],
        label='Last Window',alpha=.8)

plt.xlim(10,400)
plt.legend()
```

```
plt.xlabel('Frequency (Hz)')
plt.ylabel('log($V^2$)');
```



Using the PSD function, we can also calculate the mean and median power frequencies, which have been shown to change with muscle fatigue.

```
[110]: # mean power frequency
def meanPF(data):
    F,P = PSD(data)
    sumProd = sum([F[i]*P[i] for i in range(0,len(F))])
    sumPower = sum(P)
    meanPower = sumProd/sumPower
    return(round(meanPower,5))
```

```
# median power frequency
def medianPF(data):
    F,P = PSD(data)
    medianPower = sum(P)/2
    return(round(medianPower,5))
```

```
[114]: MNPF = list(map(meanPF,windowedEMG))
MDPF = list(map(medianPF,windowedEMG))

fig, (ax1,ax2) = plt.subplots(2,1,sharex=False,sharey=False,figsize = (20,10))

ax1.plot(MNPF, 'o-')
```


```

ax1.set_title('Mean Power Frequency')
ax1.set_ylabel('MNPF (Hz)')
ax1.set_xlabel('time bin (s)')

ax2.plot(MDPF, 'o-')
ax2.set_title('Median Power Frequency')
plt.ylabel('MDPF (Hz)')
plt.xlabel('time bin (s)')

plt.tight_layout(pad=3.0)

```



Both measures show a decrease as the EMG recording progresses, indicating fatigue. However, the trend is clearer with the Median Power Frequency.

```

[118]: data = xx['absSignal']
f,t,sxx = sc.signal.spectrogram(data,xx['sampleRate'],nperseg=xx['sampleRate'],\
                                scaling='spectrum')

f = f[:401]
sxx = sxx[:401]

fig = plt.figure(figsize=(20,10),dpi=50)
ax1 = plt.subplot(211)
plt.pcolormesh(np.log(sxx),cmap='jet')
plt.xticks([])
plt.ylabel('Frequency [Hz]')
plt.title('Spectrogram - Rectified EMG')


ax2 = plt.subplot(212)
plt.plot(np.arange(0,len(data))/xx['sampleRate'],data,lw=.1)

```

```
plt.ylabel('Voltage ( $\mu$ V)')
plt.xlabel('Time [sec]')
plt.xlim(t[0],t[-1])

# adding an independent axis for the colorbar:
fig.subplots_adjust(right=0.8)
cbar_ax = fig.add_axes([.81, .5, 0.025, 0.4])
plt.colorbar(label='log(Voltage2)',cax=cbar_ax,)

plt.draw()
```



0.5 Muscle fatigue across trials

Muscles also fatigue with repeated contractions. We asked subjects to repeat the above exercise (holding a weight with the arm bent at 90 degrees for 50 seconds) for 10 trials with 60 seconds rest between each trial. Trial 0, analyzed above, is the first trial (i.e. before fatigue through repetition) and trial 9 is the last repetition, i.e. after fatigue.

There are several measures we could use to quantify fatigue. One is the **maximum amplitude** of the EMG signal. If repeated trials fatigue the muscle, then the maximum contraction subjects generate during trial 9 should be less than that generated during trial 0, and we will see a decrease in the maximum amplitude. Second, we can calculate the **root mean square (RMS)** of the signal, which should also decrease with fatigue. Finally, we calculate the **total area** of the envelope signal, i.e. the maximum of the cumulative sum, which should decrease as well.

First, we run our analysis function on trials 0 and 9 for a given subject and graph the two recordings.

```
[121]: # specify files to be analyzed
EMGfiles = ['../data/S3/concentric/S3_EMG_concentric_trial0.wav',
            '../data/S3/concentric/S3_EMG_concentric_trial9.wav']
```

```
[123]: # create an empty array to store data
data = []
# iterate over each recording to analyze and graph
for record in EMGfiles:
    xx=processEMG(record,graph=0)
    data.append(xx)
```

Now, we calculate the maximum amplitude (maxamps), the maximum cumulative sum (maxsums), and RMS (rmss) for trials 0 and 9, and then generate bar graphs to compare each measure before and after fatigue.

```
[124]: # create empty arrays to hold measures
maxsums = []
maxamps = []
rmss = []

# for loop to iterate over recordings
for n in range(len(data)):
    # calculate the maximum amplitude
    maxamp=max(data[n]['absSignal'])
    maxamps.append(maxamp)
    # calculate the cumulative sum
    sumSignal = np.cumsum(data[n]['absSignal'])
    # calculate the max of the cumulative sum, i.e. the total area
    maxsum = max(sumSignal)
    maxsums.append(maxsum)
    # calculate RMS
    rms=np.sqrt(np.mean(data[n]['absSignal']**2))
    rmss.append(rms)
```

```
[125]: # set labels for each bar graph
labels = ('before','after')
y_pos = [0,1]

plt.figure(figsize=(20,7))

# plot and compare maximum amplitudes
plt.subplot(1, 3, 1)
for n in range(len(maxamps)):
    plt.bar(y_pos,maxamps,width=0.5,align='center',color='steelblue',alpha=0.4)
    plt.xticks(y_pos, labels)
    plt.title('Maximum amplitude',fontsize=16)
    plt.ylabel('voltage ( $\mu V$ )')
```


```

# plot and compare RMS
plt.subplot(1, 3, 2)
for n in range(len(rms)):
    plt.bar(y_pos,rms,width=0.5,align='center',color='steelblue',alpha=0.4)
    plt.xticks(y_pos, labels)
    plt.title('RMS',fontsize=16)
    plt.ylabel('RMS')

# plot and compare total area
plt.subplot(1, 3, 3)
for n in range(len(maxsums)):
    plt.bar(y_pos,maxsums,width=0.5,align='center',color='steelblue',alpha=0.4)
    plt.xticks(y_pos, labels)
    plt.title('Total area',fontsize=16)
    plt.ylabel('Cumulative sum')

plt.tight_layout(pad=3.0)

```



We can see that for all three measures, there is a noticeable decrease when we compare the first to the last trial, indicating that the protocol of repeated contractions induced fatigue in the bicep muscle.

If we want to see how each measure changed over the entire protocol, we can run the analysis on all trials and plot the measures as functions of trial number. To do this, we first define functions that will pull all the file names from a given directory and sort the files for batch processing.

```

[155]: # loop over given directory to pull out file names
def loopFiles(path):
    trials=[]
    for filename in os.listdir(path):
        if filename.endswith(".wav"):
            file=os.path.join(path,filename)
            trials.append(file)
    return(trials)

```

```

filelist = loopFiles('../data/S4/concentric/')

# sort files so analysis runs in order from trial 0 to trial 9
def lastchars(x):
    return(x[-5:])

dataset = sorted(filelist, key = lastchars)

# print file names in order
for elem in dataset:
    print(elem)

```

```

../data/S4/concentric/S4_EMG_concentric_trial0.wav
../data/S4/concentric/S4_EMG_concentric_trial1.wav
../data/S4/concentric/S4_EMG_concentric_trial2.wav
../data/S4/concentric/S4_EMG_concentric_trial3.wav
../data/S4/concentric/S4_EMG_concentric_trial4.wav
../data/S4/concentric/S4_EMG_concentric_trial5.wav
../data/S4/concentric/S4_EMG_concentric_trial6.wav
../data/S4/concentric/S4_EMG_concentric_trial7.wav
../data/S4/concentric/S4_EMG_concentric_trial8.wav
../data/S4/concentric/S4_EMG_concentric_trial9.wav

```

```

[169]: def batch(files):
    # create an empty array to store data
    data = []
    # iterate over each recording to analyze and graph
    for record in files:
        xx=processEMG(record,graph=0)
        data.append(xx)

    # create empty arrays to hold measures
    maxsums = []
    maxamps = []
    rmss = []
    # for loop to iterate over recordings
    for n in range(len(data)):
        # calculate the maximum amplitude
        maxamp=max(data[n]['absSignal'])
        maxamps.append(maxamp)
        # calculate the cumulative sum
        sumSignal = np.cumsum(data[n]['absSignal'])
        # calculate the max of the cumulative sum, i.e. the total area
        maxsum = max(sumSignal)
        maxsums.append(maxsum)
        # calculate RMS
        rms=np.sqrt(np.mean(data[n]['absSignal']**2))
        rmss.append(rms)

```

```

# plot and compare measures over all trials
plt.figure(figsize=(20,7))

# plot maximum amplitudes
plt.subplot(1, 3, 1)
plt.plot(maxamps, 'o-')
plt.xticks(np.arange(0, 10, step=1))
plt.xlabel('trial')
plt.title('Maximum amplitude')

# plot RMS
plt.subplot(1, 3, 2)
plt.plot(rmss, 'o-');
plt.xticks(np.arange(0, 10, step=1))
plt.xlabel('trial')
plt.title('RMS')

# plot total area
plt.subplot(1, 3, 3)
plt.plot(maxsums, 'o-')
plt.xticks(np.arange(0, 10, step=1))
plt.xlabel('trial')
plt.title('Total area')

plt.tight_layout(pad=3.0)

return


```

Now we can run analysis on any subject just by changing the directory (S1, S2, etc.)

```

[179]: filelist = loopFiles('../data/S3/concentric/')
dataset = sorted(filelist, key = lastchars)
batch(files=dataset)

```




We can also run frequency analysis on multiple files.

```
[225]: filelist = loopFiles('../data/S3/concentric/')
dataset = sorted(filelist, key = lastchars)

# create an empty array to store data
data = []
# iterate over each recording to analyze and graph
for record in dataset:
    xx=processEMG(record,graph=0)
    data.append(xx)

# create empty array to hold measures
MDFs = []
# for loop to iterate over recordings
for n in range(len(data)):
    ovData = []
    windows(data[n]['dataf'],data[n]['sampleRate'],data[n]['sampleRate'])
    MDF = list(map(medianPF,ovData))
    MDFs.append(MDF)
```

```
[240]: plt.figure(figsize=(20,10))
plt.plot(MDFs[0], 'o-',label='trial 0',alpha=0.4)
plt.plot(MDFs[4], 'o-',label='trial 4',alpha=0.7)
plt.plot(MDFs[9], 'o-',label='trial 9')
plt.xlabel('time (s)')
plt.ylabel(r'voltage ( $\mu V$ )')
plt.xlim(0,60)
plt.legend();
```



```
[254]: # suppress tight layout warning
import warnings
warnings.filterwarnings('ignore')
```

```
[255]: trial0=processEMG(file='../data/S3/concentric/S3_EMG_concentric_trial0.
    ↪wav',graph=0)
trial9=processEMG(file='../data/S3/concentric/S3_EMG_concentric_trial9.
    ↪wav',graph=0)

fig = plt.figure(figsize=(20,10),dpi=100)

data = trial0['absSignal']
f, t, sxx1 = sc.signal.
    ↪spectrogram(data,trial0['sampleRate'],nperseg=trial0['sampleRate'],\
                scaling='spectrum')

f = f[:401]
sxx1 = sxx1[:401]
min_sxx1 = np.min(np.log(sxx1))
max_sxx1 = np.max(np.log(sxx1))

plt.subplot(211)
plt.pcolormesh(np.log(sxx1),cmap='jet',vmin=min_sxx1,vmax=max_sxx1)
plt.ylabel('Frequency [Hz]')
plt.title('Spectrogram - Trial 0')


data = trial9['absSignal']
f, t, sxx = sc.signal.
    ↪spectrogram(data,trial9['sampleRate'],nperseg=trial9['sampleRate'],\
                scaling='spectrum')

f = f[:401]
sxx = sxx[:401]
plt.subplot(212)
plt.pcolormesh(np.log(sxx),cmap='jet',vmin=min_sxx1,vmax=max_sxx1)
plt.ylabel('Frequency [Hz]')
plt.title('Spectrogram - Trial 9')

plt.xlabel('Time[s]')

fig.subplots_adjust(right=0.8)
cbar_ax = fig.add_axes([1.01, .1, 0.035, 0.8])
plt.colorbar(label='log($Voltage^2$)',cax=cbar_ax,)

plt.draw()
plt.tight_layout()
```



From the above figures, we can see that the first spectrogram reaches higher values associated with the power content per frequency (orange area). This can be observed along the whole frequency band (0-400 Hz). The second spectrogram shows a generalized decrease in the power content contributed by frequency. It is possible to quickly compare these graphs by noticing the difference in the overall colors of the spectrogram, with the first one showing tones closer to red (higher power values), while the second one displays an overall yellow color (lower power values).