MSc Human and Biological Robotics

Author:
Edward McLaughlin

Course Co-ordinator:
Prof. Etienne *Burdet*

Human Neuro-Mechanical Control and Learning: Tutorial 2: Kinematics and Redundancy

Imperial College London

Department of Bioengineering

February 7, 2018

1 Question 1

1.1 Part a

Direct Kinematics



Figure 1

In direct kinematics, the Cartesian coordinates of the end-effector are found as a function of joint space angles. The three bar system shown in 1 represents the human arm from should to end-effector (i.e. hand).

Defining:

$$P_S = \begin{bmatrix} X_S \\ Y_S \end{bmatrix} \quad ; \quad P_E = \begin{bmatrix} X_E \\ Y_E \end{bmatrix} \quad ; \quad P_W = \begin{bmatrix} X_W \\ Y_W \end{bmatrix} \quad ; \quad P_{EE} = \begin{bmatrix} X_{EE} \\ Y_{EE} \end{bmatrix} \tag{1}$$

Let the shoulder position represent the origin, i.e.

$$P_S = \begin{bmatrix} X_S \\ Y_S \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \end{bmatrix} \tag{2}$$

.

Therefore,

$$P_E = \begin{bmatrix} X_E \\ Y_E \end{bmatrix} = \begin{bmatrix} l_s \cos(q_S) \\ l_s \sin(q_S) \end{bmatrix} \tag{3}$$

$$P_W = \begin{bmatrix} X_W \\ Y_W \end{bmatrix} = \begin{bmatrix} l_s \cos(q_S) + l_e \cos(q_S + q_E) \\ l_s \sin(q_S) + l_e \sin(q_S + q_E) \end{bmatrix} \tag{4}$$

$$P_{EE} = \begin{bmatrix} X_{EE} \\ Y_{EE} \end{bmatrix} = \begin{bmatrix} l_s \cos(q_S) + l_e \cos(q_S + q_E) + l_w \cos(q_S + q_E + q_W) \\ l_s \sin(q_S) + l_e \sin(q_S + q_E) + l_w \sin(q_S + q_E + q_W) \end{bmatrix} \tag{5}$$

Equation 5 gives the direct kinematics between the shoulder and the end-effector.

Inverse Kinematics

The inverse kinematics of the system can be found either geometrically or through differential kinematics. The former will be dealt with here, the latter will be considered in part 1.2.



Figure 2

Using the cosine rule,

$$a^2 = b^2 + c^2 - 2ab\cos(\alpha) \tag{6}$$

,

it can be shown that

$$X_w^2 + Y_w^2 = l_s^2 + l_e^2 - 2\ l_s\ l_e\ cos(\pi - q_e) \tag{7}$$

$$\& \qquad l_e^2 = X_w^2 + Y_w^2 + l_s^2 - 2\ l_s\ \sqrt{X_w^2 + Y_w^2}\ \ cos(\beta) \tag{8}$$

.

From equations 7-8, q_e and β can be expressed as

$$q_e = cos^{-1}\left(\frac{X_w^2 + Y_w^2 - l_s^2 - l_e^2}{2\ l_s\ l_s}\right) \tag{9}$$

$$\& \quad \beta = cos^{-1}\left(\frac{X_w^2 + Y_w^2 + l_s^2 - l_e^2}{2\ l_s\ \sqrt{X_w^2 + Y_w^2}}\right) \tag{10}$$

.

It can also be shown that

$$\alpha = arctan2\left(\frac{Y_w}{X_w}\right) \tag{11}$$

$$q_s = \alpha - \beta \tag{12}$$

$$= arctan2\left(\frac{Y_w}{X_w}\right) - cos^{-1}\left(\frac{X_w^2 + Y_w^2 + l_s^2 - l_e^2}{2\, l_s\, \sqrt{X_w^2 + Y_w^2}}\right) \tag{13}$$

.

Adding a constraint on the wrist orientation such that $\Theta = q_s + q_e + q_w$, therefore

$$q_w = \Theta - q_s - q_e \tag{14}$$

.

Thus the inverse kinematics have been determined in equations 9, 13 and 14, which relate the angles to desired X and Y position of the wrist. Since the wrist angle is predetermined, these equations also given the desired angles for a given position of the end-effector with an offset of $-l_w cos(\Theta)$ in the x-direction and $l_w sin(\Theta)$ in the y-direction.

1.2 Part b

Differential Kinematics and Joint Space Jacobian

Knowing P_{EE} from part 1.1, the velocity profile, V_{EE} can be calculated as

$$V_{EE} = \frac{dP_{EE}}{dt} = \begin{bmatrix} -l_s sin(q_s)\dot{q}_s - l_e sin(q_s+q_e)(\dot{q}_s+\dot{q}_e) - l_w sin(q_s+q_e+q_w)(\dot{q}_s+\dot{q}_e+\dot{q}_w) \\ l_s cos(q_s)\dot{q}_s + l_e cos(q_s+q_e)(\dot{q}_s+\dot{q}_e) + l_w cos(q_s+q_e+q_w)(\dot{q}_s+\dot{q}_e+\dot{q}_w) \end{bmatrix} \tag{15}$$

$$\begin{bmatrix} V_{XEE} \\ V_{YEE} \end{bmatrix} = J\omega \tag{16}$$

where

$$J = \begin{bmatrix} -l_s sin(q_s) - l_e sin(q_s+q_e) - l_w sin(q_s+q_e+q_w), & -l_w sin(q_s+q_e+q_w) \\ l_s cos(q_s) + l_e cos(q_s+q_e) + l_w cos(q_s+q_e+q_w), & l_w cos(q_s+q_e+q_w) \end{bmatrix} \tag{17}$$

$$\& \quad \omega = \begin{bmatrix} \dot{q}_s \\ \dot{q}_e \\ \dot{q}_w \end{bmatrix} \tag{18}$$

.

In this case, as the jacobian matrix is not square, there is redundancy in the system and thus adding the constrain in equation 14, we can find the inverse of the jacobian in order to implement inverse differential kinematics. In this case,

$$J = \begin{bmatrix} -l_s sin(q_s) - l_e sin(q_s+q_e) - l_w sin(q_s+q_e+q_w), & -l_e sin(q_s+q_e) - l_w sin(q_s+q_e+q_w), & -l_w sin(q_s+q_e+q_w) \\ l_s cos(q_s) + l_e cos(q_s+q_e) + l_w cos(q_s+q_e+q_w), & l_e sin(q_s+q_e) + l_w cos(q_s+q_e+q_w), & l_w cos(q_s+q_e+q_w) \\ 1, & 1, & 1 \end{bmatrix} \tag{19}$$

$$V'_{EE} = \begin{bmatrix} V_{XEE} \\ V_{YEE} \\ \dot{\Theta} \end{bmatrix} \tag{20}$$

Alternatively, when dealing with a non-square jacobian, we can obtain the penrose-moore pseudo inverse, $J^{\dagger}$, such that

$$J^{\dagger} = (J^T J)^{-1} J^T. \tag{21}$$

Muscle Space Jacobian, J_μ

The muscle space Jacobian for the 3 link system including the shoulder, biarticular, elbow and wrist muscles is given as

$$J_\mu = \begin{bmatrix} \rho_{s+}, & 0, & 0 \\ -\rho_{s-}, & 0, & 0 \\ \rho_{bs+}, & \rho_{bs+}, & 0 \\ -\rho_{bs-}, & -\rho_{bs-}, & 0 \\ 0, & \rho_{e+}, & 0 \\ 0, & -\rho_{e-}, & 0 \\ 0, & 0, & \rho_{w+} \\ 0, & 0, & -\rho_{w-} \end{bmatrix} \tag{22}$$

Joint Space Stiffness

The muscle stiffness matrix, K, is given by

$$K = \frac{dJ_\mu^T}{dq} F + J_\mu^T K_x J_\mu \tag{23}$$

Assuming that:

- there is no external forces: $F = 0$;
- Moment arms are all equal: $\rho_{s+} = \rho_{s-} = \rho_{bs+} = \rho_{bs-} = \rho_{e+} = \rho_{e-} = \rho_{w+} = \rho_{w-} = \rho_m$;
- No heteronymous reflexes: stiffness matrix, K_x is diagonal.

equation 23 reduces to

$$K = J_\mu^T K_x J_\mu \tag{24}$$

$$= \rho_m \begin{bmatrix} 1, & 0, & 0 \\ -1, & 0, & 0 \\ 1, & 1, & 0 \\ -1, & -1, & 0 \\ 0, & 1, & 0 \\ 0, & -1, & 0 \\ 0, & 0, & 1 \\ 0, & 0, & -1 \end{bmatrix}^T \begin{bmatrix} K_{s+}, & 0, & 0, & 0, & 0, & 0, & 0, & 0 \\ 0, & K_{s-}, & 0, & 0, & 0, & 0, & 0, & 0 \\ 0, & 0, & K_{b+}, & 0, & 0, & 0, & 0, & 0 \\ 0, & 0, & 0, & K_{b-}, & 0, & 0, & 0, & 0 \\ 0, & 0, & 0, & 0, & K_{e+}, & 0, & 0, & 0 \\ 0, & 0, & 0, & 0, & 0, & K_{e-}, & 0, & 0 \\ 0, & 0, & 0, & 0, & 0, & 0, & K_{w+}, & 0 \\ 0, & 0, & 0, & 0, & 0, & 0, & 0, & K_{w-} \end{bmatrix} \rho_m \begin{bmatrix} 1, & 0, & 0 \\ -1, & 0, & 0 \\ 1, & 1, & 0 \\ -1, & -1, & 0 \\ 0, & 1, & 0 \\ 0, & -1, & 0 \\ 0, & 0, & 1 \\ 0, & 0, & -1 \end{bmatrix} \tag{25}$$

$$= \rho_m^2 \begin{bmatrix} k_s + k_b, & k_b, & 0 \\ k_b, & k_b + k_e, & 0 \\ 0, & 0, & k_w \end{bmatrix} \quad ; \qquad where\ k_s = K_{s+} + K_{s-}\ etc. \tag{26}$$

Equation 26 gives the muscle stiffness matrix.

1.3 Part c

The process for calculating and plotting the position and velocity of the end-effector as well as the joint angles and angular velocities is as follows:

- Define Time parameters
- Define physiological parameters
- Calculate the position and velocity profiles in x and y
- Iteratively calculate the angular speed and hence angles using
  - Evaluate inverse Jacobian based on current angles and moment arms
  - Calculate angular velocity : angularVelocity = inverseJacobian * velocity
  - Calculate angles: Angles = oldAngles + angularVelocity*timestep
- Plot position, velocity, angles and angular velocity.

The plots are shown below. The matlab code is given in the appendix.



Figure 3: Position profile of the end-effector.



Figure 4: Velocity profile of the end-effector.



Figure 5: Angles of system to achieve the desired profile.



Figure 6: Angular velocities of the system to achieve the desired profile.

2 appendix

```
%Time properties
t = 0:0.01:2;
T = 2;
tn = t/T;

%Physiology properties
qs = deg2rad(90);
qe = deg2rad(130);
qw = deg2rad(90);
Q(:,1)= [qs;...
         qe;...
         qw];
ls = 0.3;
le = 0.3;
lw = 0.15;

%Position profile as given in the question
x_tn = 0.1289*tn.^3.*(6*tn.^2-15*tn+10)-0.1334;
y_tn = 0.7355*tn.^3.*(6*tn.^2-15*tn+10)-0.0077;

%Velocity profile found by derivative of position w.r.t t
Vx = 0.1289*(30*tn.^4-60*tn.^3+30*tn.^2)/T;
Vy = 0.7355*(30*tn.^4-60*tn.^3+30*tn.^2)/T;

for i = 1:length(t)
    %Evaluate inverse jacobian
    JinvLoop = updateJinv(ls, le, lw, Q(1,i), Q(2,i), Q(3,i));

    %Calculate maximum value in jacobian - mainly for debugging
    %singularities
    MaxJ(i) = max(max(JinvLoop));

    %Calculate angular speed
    omega(:,i) = JinvLoop*[Vx(i); Vy(i)];

    %Calculate new angles
    Q(:,i+1) = Q(:,i) + omega(:,i)*0.01;
end
```