

# Software Development (cs2500)

## Lecture 57: Special Topics in Concurrency

M. R. C. van Dongen

5 March, 2014

# Outline

## Outline

Deadlock

Shared Mutable Data

Excessive  
Synchronisation

The Executor Framework

Concurrency Utilities

Lazy Initialisation

For Friday

Acknowledgements

Bibliography

References

About this Document

- Revisit *deadlock*.
- Accessing shared synchronised data.
- Avoiding excessive synchronisation.
- The *Executor Framework*.
- Concurrency utilities.
- Lazy initialisation.
- Deadlock based on on line Java documentation.
- The rest is based on [Bloch 2008].

- Deadlock occurs when:
  - Two or more threads each own a shared resource;
  - Each thread requires a resource from some other thread;
  - No thread is willing to release their resource.
- When deadlock occurs, no thread can proceed.
  - The program cannot terminate.
- A synchronized block/method is a shared object (resource).
- Therefore, executing them may also cause deadlock.

# Enter Alphonse and Gaston



# Example (Continued)

## Java

```
public class Friend {
    private final String name;

    public Friend( final String name ) {
        this.name = name;
    }

    public synchronized void bow( final Friend bower ) {
        System.out.println( bower.name
                           + " has bowed to "
                           + this.name );

        pause( );
        bower.bowBack( this );
    }

    public synchronized void bowBack( final Friend bower ) {
        System.out.println( this.name
                           + " has bowed back to "
                           + bower.name );
    }
}
```

# Example (Continued)

## Java

```
final Friend alphonse = new Friend( "Alphonse" );
final Friend gaston = new Friend( "Gaston" );

new Thread( new Runnable( ) {
    @Override public void run( ) {
        alphonse.bow( gaston );
    } } ).start( );

new Thread( new Runnable( ) {
    @Override public void run( ) {
        gaston.bow( alphonse );
    } } ).start( );
```

# Accessing Shared Mutable Data

- synchronized guarantees exclusive monitor access.
- Best view it as a lock.
- Lets you deal with shared data.

# Atomic Reading and Writing

- Java guarantees that all read & write operations are *atomic*,
  - Except for *double* or *long*.
- Sometimes used to implement synchronized-free “locking.”
- In short, this *doesn't work*.



# How Long before this Terminates?

## Don't Try This at Home

```
import java.util.concurrent.TimeUnit;

public class StopThread {
    private static boolean stopRequested;

    public static void main( String[] args )
        throws InterruptedException {
        final Thread thread = new Thread( new Runnable( ) {
            @Override
            public void run( ) {
                int i = 0;
                while (!stopRequested) {
                    i++;
                }
            }
        } );
        thread.start( );

        TimeUnit.SECONDS.sleep( 1 );
        stopRequested = true;
    }
}
```

Outline

Deadlock

Shared Mutable Data

Excessive  
Synchronisation

The Executor Framework

Concurrency Utilities

Lazy Initialisation

For Friday

Acknowledgements

Bibliography

References

About this Document

## Software Development

## Outline

## Deadlock

## Shared Mutable Data

### Excessive Synchronisation

## The Executor Framework

## Concurrency Utilities

## Lazy Initialisation

For Friday

## Acknowledgements

## Bibliography

## References

## About this Document

```
while (!stopRequested) {
    i++;
}
```

```
if (!stopRequested) {
    while (true) {
        i++;
    }
}
```

# Fixing the Problem

## Java

```
private static boolean stopRequested;

private static synchronized void requestStop( ) {
    stopRequested = true;
}

private static synchronized boolean stopRequested( ) {
    return stopRequested;
}

public static void main( String[] args )
    throws InterruptedException {
    final Thread thread = new Thread( new Runnable( ) {
        @Override
        public void run( ) {
            int i = 0;
            while ( !stopRequested( ) ) {
                i++;
            }
        }
    } );
    thread.start( );
    TimeUnit.SECONDS.sleep( 1 );
    requestStop( );
}
```

# The volatile Keyword

Makes sure Reads Read the Last Write

## Java

```
private static volatile boolean stopRequested;

public static void main( String[] args )
    throws InterruptedException {
    final Thread thread = new Thread( new Runnable( ) {
        @Override
        public void run( ) {
            int i = 0;
            while ( !stopRequested ) {
                i++;
            }
        }
    } );
    thread.start( );
    TimeUnit.SECONDS.sleep( 1 );
    stopRequested = true;
}
```

Software Development

M. R. C. van Dongen

Outline

Deadlock

Shared Mutable Data

Excessive  
Synchronisation

The Executor Framework

Concurrency Utilities

Lazy Initialisation

For Friday

Acknowledgements

Bibliography

References

About this Document

# No Mutual Exclusion;

## Don't Try This at Home

```
private static volatile int nextSerialNumber = 0;

public static int generateSerialNumber( ) {
    return nextSerialNumber++;
}
```

# No Mutual Exclusion; No Atomicity

## Don't Try This at Home

```
private static volatile int nextSerialNumber = 0;

public static int generateSerialNumber( ) {
    return nextSerialNumber++;
}
```

## Don't Try This at Home

```
public static int generateSerialNumber( ) {
    final int current = nextSerialNumber;
    nextSerialNumber = current + 1;
    return current;
}
```

# Sharing Mutable Data

- ❑ Confine mutable data to a single thread.
- ❑ Make one thread responsible for updating the values.
  - 1 Values are shared using object references.
  - 2 The thread prepares the data.
  - 3 Thread synchronises only when it shares object references.
  - 4 Client threads use getters without synchronisation.
- ❑ Such objects are called *effectively immutable*.
- ❑ Sharing effectively immutable objects is called *safe publication*.
- ❑ Implementation techniques:
  - ❑ Store the reference as class attribute at class construction time.
  - ❑ Store it in a `volatile` attribute.
  - ❑ Store it in a `final` variable.
  - ❑ Store it in a variable with internally locked getters and setters.
  - ❑ Store it in a concurrent collection.

# Synchronisation Takes Time

- Synchronisation takes time.
- Be careful when sharing synchronized variables.
- Delay caused by weak/malicious client delays all threads.
- Do not call client methods in synchronized blocks/methods.



# Alien Methods

- A method is called *alien* if it is designed to be overridden.
- **Avoid alien method calls in synchronized blocks.**

# Calling an Alien Method

## Don't Try This at Home

```
public ObservableSet<E> extends ForwardingSet<E> {
    public ObservableSet( Set<E> set ) { super( set ); }

    private final List<SetObserver<E>> observers
        = new ArrayList<SetObserver<E>>( );

    public void addObserver( SetObserver<E> observer ) {
        synchronized(observers) { observers.add( observer ); }
    }

    public boolean removeObserver( SetObserver<E> observer ) {
        synchronized(observers) { return observers.remove( observer ); }
    }

    private void notifyElementAdded( E element ) {
        synchronized(observers) {
            for( SetObserver<E> observer : observers ) {
                observer.update( this, element );
            }
        }
    }

    ...
}
```

# Calling an Alien Method : Where is It?

## Don't Try This at Home

```
public ObservableSet<E> extends ForwardingSet<E> {
    public ObservableSet( Set<E> set ) { super( set ); }

    private final List<SetObserver<E>> observers
        = new ArrayList<SetObserver<E>>( );

    public void addObserver( SetObserver<E> observer ) {
        synchronized(observers) { observers.add( observer ); }
    }

    public boolean removeObserver( SetObserver<E> observer ) {
        synchronized(observers) { return observers.remove( observer ); }
    }

    private void notifyElementAdded( E element ) {
        synchronized(observers) {
            for( SetObserver<E> observer : observers ) {
                observer.update( this, element );
            }
        }
    }

    ...
}
```

Outline

Deadlock

Shared Mutable Data

Excessive  
Synchronisation

The Executor Framework

Concurrency Utilities

Lazy Initialisation

For Friday

Acknowledgements

Bibliography

References

About this Document

# Calling an Alien Method

## Don't Try This at Home

```
public ObservableSet<E> extends ForwardingSet<E> {
    public ObservableSet( Set<E> set ) { super( set ); }

    private final List<SetObserver<E>> observers
        = new ArrayList<SetObserver<E>>( );

    public void addObserver( SetObserver<E> observer ) {
        synchronized(observers) { observers.add( observer ); }
    }

    public boolean removeObserver( SetObserver<E> observer ) {
        synchronized(observers) { return observers.remove( observer ); }
    }

    private void notifyElementAdded( E element ) {
        synchronized(observers) {
            for( SetObserver<E> observer : observers ) {
                observer.update( this, element );
            }
        }
    }

    ...
}
```

# Calling an Alien Method in a synchronized Block

Software Development

M. R. C. van Dongen

## Don't Try This at Home

```
public ObservableSet<E> extends ForwardingSet<E> {
    public ObservableSet( Set<E> set ) { super( set ); }

    private final List<SetObserver<E>> observers
        = new ArrayList<SetObserver<E>>( );

    public void addObserver( SetObserver<E> observer ) {
        synchronized(observers) { observers.add( observer ); }
    }

    public boolean removeObserver( SetObserver<E> observer ) {
        synchronized(observers) { return observers.remove( observer ); }
    }

    private void notifyElementAdded( E element ) {
        synchronized(observers) {
            for( SetObserver<E> observer : observers ) {
                observer.update( this, element );
            }
        }
    }

    ...
}
```

Outline

Deadlock

Shared Mutable Data

Excessive  
Synchronisation

The Executor Framework

Concurrency Utilities

Lazy Initialisation

For Friday

Acknowledgements

Bibliography

References

About this Document

## Don't Try This at Home

```
final ObservableSet<Integer> set = new ObservableSet<>( );

set.addObserver( new SetObserver<Integer>( ) {
    @Override
    public void update( ObservableSet<Integer> s, Integer e ) {
        ...
        if ((condition)) {
            s.removeObserver( this );
        }
        ...
    }
} );
```

## Don't Try This at Home

```
set.addObserver( new SetObserver<Integer>( ) {
    @Override
    public void update( ObservableSet<Integer> set, Integer e ) {
        final SetObserver<Integer> observer = this;
        final Thread thread = new Thread( new Runnable( ) {
            @Override public void run( ) {
                ...
                set.remove( observer );
                ...
            }
        } );
        thread.start( );
    } } );

synchronized(set) {
    for (SetObserver<Integer> observer : set) {
        set.add( 666 );
    }
}
```

# Solving the Problem

## Java

```
private void notifyElementAdded( E element ) {  
    final List<SetObserver<E>> copy = null;  
    synchronized(observers) {  
        copy = new ArrayList<SetObserver<E>>( observers );  
    }  
    for (SetObserver<E> observer : copy) {  
        observer.update( this, element );  
    }  
}
```



# java.util.concurrent to the Rescue

## Java

```
private final List<SetObserver<E>> observers
    = new CopyOnWriteArrayList<SetObserver<E>>( );

public void addObserver( SetObserver<E> observer ) {
    observers.add( observer );
}

public boolean removeObserver( SetObserver<E> observer ) {
    observers.remove( observer );
}

public void notifyElementAdded( E element ) {
    for (SetObserver<E> observer : observers) {
        observers.add( observer );
    }
}
```

# Final Thoughts

- An alien method call outside a synchronized block is an *open call*.
  - Open calls avoid (certain) synchronisation errors.
  - They increase concurrency.
- As a rule, minimise the time spent in synchronised blocks.

- Using `wait` and `notify` is difficult.
- An *executor* creates, manages, and terminates tasks.
- An executor also provides synchronisation primitives.
- `ExecutorService` provides tools for creating executors.

# Using Executors

**Creation** You create the executor as follows.

## Java

```
final ExecutorService executor  
    = ExecutorService.singleThreadExecutor( );
```

**Execution** To start a worker thread, you offer the executor a task.

## Java

```
executor.execute( runnable );
```

**Joining** You can join with all tasks.

## Java

```
executor.awaitTermination( );
```

**Termination** You can shut down the executor.

## Java

```
executor.shutdown( );
```

# Thread Pools

- Another executor service is a *thread pool*.
- This is an executor service that manages multiple threads.
  - Offering tasks for execution works as usual.
  - However, the service is now multi-threaded.
  - You can control the minimum number of threads;
  - You can control the maximum number of threads;
  - You can request a fixed number of threads.

# Concurrent Collections

- Using normal collections requires locking.
- Poses serious problems: deadlock.
- *Concurrent collections* provides solution with concurrent
  - List,
  - Queue, and
  - Map implementations.
- Concurrent collections lock themselves:
  - External locking? **No thanks.**
  - External locking slows down.
- Concurrent collections are in `java.util.concurrent`.

# Synchronizers

- A *synchronizer* coordinates thread synchronisation.
- They synchronise with `await( )` and `countDown( )`.

`CountDownLatch` Non-reusable synchronizer.

`Semaphore` A semaphore object.

`CyclicBarrier` Cyclic version of `CountDownLatch`.

# Example

- ❑ We use an executor to create 3 tasks.
- ❑ Each task carries out a computation.
- ❑ The tasks start by reporting they're ready.
- ❑ A task may start its computation when all tasks are ready.
- ❑ The main thread waits until all tasks are done.

## Java

```
final ExecutorService executor = Executors.newCachedThreadPool( );
final int nthreads = 3;
final CountDownLatch ready = new CountDownLatch( nthreads );
final CountDownLatch start = new CountDownLatch( 1 );
final CountDownLatch done = new CountDownLatch( nthreads );
```



# Example (Continued)

## Worker Thread

### Java

```
final Runnable task = new Runnable( ) {
    @Override public void run( ) {
        ready.countDown( ); // report presence
        try {
            start.await( ); // wait till all tasks have reported presence
            computation( ); // carry out main computation
        } catch (InterruptedException e) {
            // Omitted
        } finally {
            done.countDown( ); // report task completed
        }
    }
};
```

# Example (Continued)

Main Thread

## Java

```
for (int number = 0; number != nthreads; number++) {
    executor.execute( task );
}
try {
    ready.await( );    // wait till all tasks are ready
    start.countDown( ); // let tasks start computation
    done.await( );     // wait till all tasks are done
} catch (InterruptedException e) {
    // Omitted
} finally {
    executor.shutdownNow( );
}
```

Software Development

M. R. C. van Dongen

Outline

Deadlock

Shared Mutable Data

Excessive  
Synchronisation

The Executor Framework

Concurrency Utilities

Concurrent Collections

Synchronizers

Lazy Initialisation

For Friday

Acknowledgements

Bibliography

References

About this Document

# Introduction

- An expression is *strict* when it's evaluated when it's defined.
- It is *lazy* when it's evaluated when it's needed.
- Lets you implement “infinite data structures.”
- Lazy language: Haskell.
- Useful when computations are expensive or not always needed.

# Simulating Lazy Evaluation

- Lazy evaluation can be simulated.
- Simply postpone the computation until it's needed.
  - Use the Command pattern.
- Trigger the initialisation at a later stage.
- Also possible to trigger just one initialisation.

# Initialising Read-Only Class Attributes

WrapperClass only Created when value is Needed

## Java

```
private static class WrapperClass {  
    private static final <type> value = computation( );  
}  
  
private static <type> getValue( ) {  
    return WrapperClass.value;  
}
```

Software Development

M. R. C. van Dongen

Outline

Deadlock

Shared Mutable Data

Excessive  
Synchronisation

The Executor Framework

Concurrency Utilities

Lazy Initialisation

Class Attributes

Instance Attributes

For Friday

Acknowledgements

Bibliography

References

About this Document

# Initialising Read-Only Class Attributes

JVM will Optimise Byte Code after

## Initialisation

### Java

```
private static class WrapperClass {  
    private static final <type> value = computation( );  
}  
  
private static <type> getValue( ) {  
    return WrapperClass.value;  
}
```

Software Development

M. R. C. van Dongen

Outline

Deadlock

Shared Mutable Data

Excessive  
Synchronisation

The Executor Framework

Concurrency Utilities

Lazy Initialisation

Class Attributes

Instance Attributes

For Friday

Acknowledgements

Bibliography

References

About this Document

# Initialising Read-Only Instance Attributes

## Java

```
private volatile <type> attribute = null;

public <type> getValue( ) {
    <type> value = attribute;
    if (value == null) {
        synchronized(this) {
            value = attribute;
            if (value == null) {
                attribute = value = computation( );
            }
        }
    }
    return value;
}
```

# For Friday

- Study the lecture notes.



# Acknowledgements

Software Development

M. R. C. van Dongen

Outline

Deadlock

Shared Mutable Data

Excessive  
Synchronisation

The Executor Framework

Concurrency Utilities

Lazy Initialisation

For Friday

Acknowledgements

Bibliography

References

About this Document

- This lecture is based on [Bloch 2008, Items 66, 67, 69, and 71].

## Software Development

## Outline

## Deadlock

## Shared Mutable Data

### Excessive Synchronisation

## The Executor Framework

## Concurrency Utilities

## Lazy Initialisation


For Friday

## Acknowledgements

## Bibliography

## References

## About this Document



# About this Document

- This document was created with pdf $\text{\LaTeX}$ atex.
- The  $\text{\LaTeX}$  document class is beamer.

Software Development

M. R. C. van Dongen

Outline

Deadlock

Shared Mutable Data

Excessive  
Synchronisation

The Executor Framework

Concurrency Utilities

Lazy Initialisation

For Friday

Acknowledgements

Bibliography

References

About this Document