

Software Development (cs2500)

Lecture 27: Recursion

M. R. C. van Dongen

November 25, 2013

Outline

Recursion

Factorial Computation

Fibonacci Numbers

Towers of Hanoi

Binary Search

Quicksort

For Wednesday

Acknowledgements

About this Document

- We study recursion:
 - Methods that call themselves;
 - Definitions that are defined in terms of themselves.
- We start with some easy/recreative applications:
 - We study a recursive method for computing factorials.
 - We study the recursive breeding habits of rabbits.
 - We study the famous towers of hanoi.
- We end with some practical real-world applications:
 - Binary search;
 - Quicksort.

Recursion

Outline

Recursion

Definition

Examples

Pitfalls

Factorial Computation

Fibonacci Numbers

Towers of Hanoi

Binary Search

Quicksort

For Wednesday

Acknowledgements

About this Document

- Many concepts in computer science and mathematics are defined or computed *recursively*, i.e. using *recursion*.
- The idea is to define a complicated concept in terms of itself.

Recursion: Base Case

Base Case: Simple computation.

- We don't have to call the method itself.

Recursive Computation: Complicated computation involving:

- Simple computations.
- Lower order computation(s).

Recursion: Recursive Computation

Base Case: Simple computation.

- We don't have to call the method itself.

Recursive Computation: Complicated computation involving:

- Simple computations.
- Lower order computation(s).

Recursive Algorithm: Dictionary Search

Dictionary Contains all Possible Words: One Word per Page

To *search* for the word given n pages do the following:

- If there's only one page ($n = 1$): We've found the word.
- Otherwise ($n > 1$):
 - Find the page in the "middle."
 - Read the word on the middle page.
 - If that word is our word: We've found the word.
 - If our word is smaller: *search* to the left.
 - Otherwise: *search* to the right.

Outline

Recursion

Definition

Examples

Pitfalls

Factorial Computation

Fibonacci Numbers

Towers of Hanoi

Binary Search

Quicksort

For Wednesday

Acknowledgements

About this Document

Recursive Picture

Outline

Recursion

Definition

Examples

Pitfalls

Factorial Computation

Fibonacci Numbers

Towers of Hanoi


Binary Search

Quicksort

For Wednesday

Acknowledgements

About this Document



Recursive Picture



Outline

Recursion

Definition

Examples

Pitfalls

Factorial Computation

Fibonacci Numbers

Towers of Hanoi

Binary Search

Quicksort

For Wednesday

Acknowledgements

About this Document

- Recursive computations involve themselves.
- If we're not careful we may get an infinite chain of computations.
- For example, we may be
 - Computing what's on Box 1 with Box 2 on it, which involves
 - Computing what's on Box 2 with Box 3 on it, which involves
 - Computing what's on Box 3 with Box 4 on it, which involves
 -
- Each recursive computation should eventually terminate.
- This only happens if they all reach some base case condition.
 - (The base conditions may be different.)

Controlling the Size

Guaranteeing Termination

- Each computation should have a *size*: a non-negative integer.
- The size should depend on one or several method parameters.
- Base-case computations have small fixed sizes.
- Recursive sub-computations should get smaller and smaller.
- Using an induction argument this guarantees termination.

How does this Work?

Dictionary Search Revisited

- Let's call the top computation C_0 .
- Let C_1 be the recursive computation of C_0 ,
- Let C_2 be the recursive computation of C_1 , and so on.
- Finally, let S_i be the size of C_i .
 - By nature of the algorithm we have $S_i > S_{i+1}$.
- Let's assume an infinite chain of computations C_0, C_1, C_2, \dots
- Then we have an infinite chain of *integers* $S_0 > S_1 > S_2 > \dots$.
- But this is impossible since $S_i \geq 0$, for all i .

Computing Factorials

- Let n be a positive integer.
- The *factorial* of n , denoted $n!$, is defined as follows:

$$n! = 1 \times 2 \times \cdots \times (n-1) \times n.$$

- Using the product notation we may write this as follows:

$$n! = \prod_{i=1}^n i.$$

Computing Factorials: An Iterative Solution

Software Development

M. R. C. van Dongen

Outline

Recursion

Factorial Computation

Fibonacci Numbers

Towers of Hanoi

Binary Search

Quicksort

For Wednesday

Acknowledgements

About this Document

Java

```
public static int factorial( int n ) {  
    int product = 1;  
    for (int i = 1; i != n; i ++ ) {  
        product = product * i;  
    }  
    return product;  
}
```

Computing Factorials: A Recursive Solution

Base Case: Clearly $1! = 1$.

Recursion: The recursion may be found by noticing that

$$\prod_{i=1}^n i = n \times \prod_{i=1}^{n-1} i.$$

This gives us

$$n! = (n - 1)! \times n.$$

Combining the Base Case and Recursive Case

$$n! = \begin{cases} 1 & \text{if } n = 1; \\ (n-1)! \times n & \text{if } n > 1. \end{cases}$$

Java

```
public static int factorial( int n ) {  
    final int result;  
  
    if (n == 1) {  
        result = 1; // Base Case  
    } else {  
        result = factorial( n - 1 ) * n; // Recursion  
    }  
  
    return result;  
}
```


Simulating a Computation

```
factorial( 4 ) = ( factorial( 3 ) * 4 ) )  
               = ( ( factorial( 2 ) * 3 ) * 4 )  
               = ( ( ( factorial( 1 ) * 2 ) * 3 ) * 4 )  
               = ( ( ( 1 * 2 ) * 3 ) * 4 )  
               = ( ( 2 * 3 ) * 4 )  
               = ( 6 * 4 )  
               = 24.
```

Yer Man



Software Development

M. R. C. van Dongen

Outline

Recursion

Factorial Computation

Fibonacci Numbers

A Fibonacci Problem

Fibonacci's Solution

The Fibonacci Sequence

Tracing the Calls

Towers of Hanoi

Binary Search

Quicksort

For Wednesday

Acknowledgements

About this Document

Facts about Fibonacci

- Born: about 1175 AD.
- Died: 1250 AD.
- Famous mathematician.
- Introduced the Decimal System into Europe.
- Well known for many of his problems.

Rabbits

A pair of rabbits are put in a field and, if rabbits take a month to become mature and then produce a new pair every month after that, how many pairs will there be in twelve months time?



Rabbits do not Escape and Don't Die

A pair of rabbits are put in a field and, if rabbits take a month to become mature and then produce a new pair every month after that, how many pairs will there be in twelve months time?



Fibonacci's Solution

Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1			

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0		

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2			

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1		

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2

Fibonacci's Solution




Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3			

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	1	2

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	2	

Outline

Recursion

Factorial Computation

Fibonacci Numbers

A Fibonacci Problem

Fibonacci's Solution

The Fibonacci Sequence

Tracing the Calls

Towers of Hanoi

Binary Search


Quicksort

For Wednesday

Acknowledgements

About this Document

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	2	3

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	2	3
4			

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	2	3
4	2		

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	2	3
4	2	3	

Fibonacci's Solution




Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	2	3
4	2	3	5

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	2	3
4	2	3	5
5			

Fibonacci's Solution




Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	2	3
4	2	3	5
5	3	5	8

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	2	3
4	2	3	5
5	3	5	

Fibonacci's Solution



Month (n)	Pairs of Rabbits		
	Babies	Mature	Total (F_n)
0	1	0	1
1	0	1	1
2	1	1	2
3	1	2	3
4	2	3	5
5	3	5	8

The Fibonacci Sequence

- Fibonacci's solution involves the series of numbers:

1, 1, 2, 3, 5, 8, 13, 21, . . .


- Given the first two we can compute the remaining numbers:

$$F_n = \begin{cases} 1 & \text{if } n = 0; \\ 1 & \text{if } n = 1; \\ F_{n-1} + F_{n-2} & \text{if } n > 1. \end{cases}$$

Java


```
public static int fibonacci( int n ) {  
    final int result;  
  
    if (n <= 1) { /* Base Case */  
        result = 1;  
    } else {      /* Recursion */  
        result = fibonacci( n - 1 ) + fibonacci( n - 2 );  
    }  
  
    return result;  
}
```

Tracing the Calls




The Towers of Hanoi

- We're given a tower of 8 disks and three pegs: *A*, *B*, and *C*.
- Each disk has a hole in the centre.
- Initially, the disks are stacked in decreasing size on Peg *A*.
- The objective is to transfer the stack to a different peg, but
 - We're only allowed to stack disks on pegs,
 - We're only allowed to move one disk at a time, and
 - We can only stack a smaller disk on top of a larger disk.



Simulation



A




B




C


Simulation




Simulation




Simulation




Simulation




Simulation



Simulation




Simulation




Simulation



A




B




C


Simulation




Simulation




Simulation




Simulation



Simulation




Simulation



Intermediate State of the 3-Disk Version



A




B




C

Intermediate State of the 3-Disk Version



□ Here we *recursively* moved disks from *C* to *B* and were done!

Intermediate State of the 3-Disk Version



- Here we *recursively* moved disks from *C* to *B* and were done!
- So, how did we arrive at the intermediate state?
- If we can solve this subproblem, we can solve the whole problem:

Intermediate State of the 3-Disk Version

M. R. C. van Dongen

Recursion

Fibonacci Numbers


Binary Search

Quicksort


For Wednesday

Acknowledgements

About this Document



Intermediate State of the 3-Disk Version




- Here we *recursively* moved disks from *C* to *B* and were done!
- So, how did we arrive at the intermediate state?
- If we can solve this subproblem, we can solve the whole problem:
 - 1 Start at initial state.
 - 2 Solve the sub-problem to arrive at the intermediate state.

Intermediate State of the 3-Disk Version



A




B



C

- Here we *recursively* moved disks from C to B and were done!
- So, how did we arrive at the intermediate state?
- If we can solve this subproblem, we can solve the whole problem:
 - 1 Start at initial state.
 - 2 Solve the sub-problem to arrive at the intermediate state.
 - 3 Use recursion to go from the intermediate to the target state.

Intermediate State of the 3-Disk Version




- Here we *recursively* moved disks from *C* to *B* and were done!
- So, how did we arrive at the intermediate state?
- If we can solve this subproblem, we can solve the whole problem:
 - 1 Start at initial state.
 - 2 Solve the sub-problem to arrive at the intermediate state.
 - 3 Use recursion to go from the intermediate to the target state.
- So, how did we get at the intermediate state?

Intermediate State of the 3-Disk Version



A




B



C


- Here we *recursively* moved disks from C to B and were done!
- So, how did we arrive at the intermediate state?
- If we can solve this subproblem, we can solve the whole problem:
 - 1 Start at initial state.
 - 2 Solve the sub-problem to arrive at the intermediate state.
 - 3 Use recursion to go from the intermediate to the target state.
- So, how did we get at the intermediate state?
 - 1 We started with all disks stacked on Peg A.
 - 2 We moved all disks except for the largest one from A to C.

Intermediate State of the 3-Disk Version



- Here we *recursively* moved disks from *C* to *B* and were done!
- So, how did we arrive at the intermediate state?
- If we can solve this subproblem, we can solve the whole problem:
 - 1 Start at initial state.
 - 2 Solve the sub-problem to arrive at the intermediate state.
 - 3 Use recursion to go from the intermediate to the target state.
- So, how did we get at the intermediate state?
 - 1 We started with all disks stacked on Peg *A*.
 - 2 We moved all disks except for the largest one from *A* to *C*.
 - 3 We moved the largest disk to Peg *B*.

Intermediate State of the 3-Disk Version



- Here we *recursively* moved disks from *C* to *B* and were done!
- So, how did we arrive at the intermediate state?
- If we can solve this subproblem, we can solve the whole problem:
 - 1 Start at initial state.
 - 2 Solve the sub-problem to arrive at the intermediate state.
 - 3 Use recursion to go from the intermediate to the target state.
- So, how did we get at the intermediate state?
 - 1 We started with all disks stacked on Peg *A*.
 - 2 We moved all disks except for the largest one from *A* to *C*.
 - But this is just the 2-disk version: move 2 disks from *A* to *C*.
 - 3 We moved the largest disk to Peg *B*.

Designing the Algorithm

Base case: If $n = 1$:

- 1 Move disk n to target peg.

Recursion: If $n > 1$:

- 1 Move disks $1, \dots, n - 1$ to intermediate peg.
- 2 Move disk n to target peg.
- 3 Move disks $1, \dots, n - 1$ to target peg.

Designing the Algorithm

Base case: If $n = 1$:

- 1 Move disk n to target peg.

Recursion: If $n > 1$:

- 1 Move disks $1, \dots, n - 1$ to intermediate peg.
- 2 Move disk n to target peg.
- 3 Move disks $1, \dots, n - 1$ to target peg.

Alternative solution

□ If $n \geq 1$ then

- 1 Move disks 1, ..., $n - 1$ from source to intermediate peg.
- 2 Move disk n to target disk.
- 3 Move disks 1, ..., $n - 1$ from intermediate to target peg.

Java

```
/**
 * @param n Number of disks.
 * @param source The source peg: should be 0, 1, or 2.
 * @param target The target peg: should be 0, 1, or 2.
 * <PAR> {@code source} and {@code target} should be different.</PAR>
 */
private static
void hanoi( int n, int source, int target ) {
    if ( n >= 1 ) {
        // Compute the number of the intermediate peg:
        final int intermediate = 3 - source - target;
        hanoi( n - 1, source, intermediate );
        moveDisk( n, source, target );
        hanoi( n - 1, intermediate, target );
    }
}

public static
void hanoi( int n ) {
    // move n disks from Peg 0 to Peg 1.
    hanoi( n, 0, 1 );
}
```

[Outline](#)[Recursion](#)[Factorial Computation](#)[Fibonacci Numbers](#)[Towers of Hanoi](#)[Binary Search](#)[Quicksort](#)[For Wednesday](#)[Acknowledgements](#)[About this Document](#)

Java

```
/**
 * @param n Number of disks.
 * @param source The source peg: should be 0, 1, or 2.
 * @param target The target peg: should be 0, 1, or 2.
 * <PAR> {@code source} and {@code target} should be different.</PAR>
 */
private static
void hanoi( int n, int source, int target ) {
    if ( n >= 1 ) {
        // Compute the number of the intermediate peg:
        final int intermediate = 3 - source - target;
        hanoi( n - 1, source, intermediate );
        moveDisk( n, source, target );
        hanoi( n - 1, intermediate, target );
    }
}

public static
void hanoi( int n ) {
    // move n disks from Peg 0 to Peg 1.
    hanoi( n, 0, 1 );
}
```

[Outline](#)[Recursion](#)[Factorial Computation](#)[Fibonacci Numbers](#)[Towers of Hanoi](#)[Binary Search](#)[Quicksort](#)[For Wednesday](#)[Acknowledgements](#)[About this Document](#)

Java

```
/**
 * @param n Number of disks.
 * @param source The source peg: should be 0, 1, or 2.
 * @param target The target peg: should be 0, 1, or 2.
 * <PAR> {@code source} and {@code target} should be different.</PAR>
 */
private static
void hanoi( int n, int source, int target ) {
    if ( n >= 1 ) {
        // Compute the number of the intermediate peg:
        final int intermediate = 3 - source - target;
        hanoi( n - 1, source, intermediate );
        moveDisk( n, source, target );
        hanoi( n - 1, intermediate, target );
    }
}

public static
void hanoi( int n ) {
    // move n disks from Peg 0 to Peg 1.
    hanoi( n, 0, 1 );
}
```

[Outline](#)[Recursion](#)[Factorial Computation](#)[Fibonacci Numbers](#)[Towers of Hanoi](#)[Binary Search](#)[Quicksort](#)[For Wednesday](#)[Acknowledgements](#)[About this Document](#)

Back to Java

Java

```
private static void moveDisk( int disk, int source, int target ) {  
    final String pegNames[] = { "A", "B", "C" };  
    System.out.println( "Move disk " + disk  
                        + " from " + pegNames[ source ]  
                        + " to " + pegNames[ target ] );  
}
```

Binary Search

- *Binary search* is an algorithm that:
 - Determines whether a given item is in a sorted list, and
 - If it is, returns the position of that element in the list.
- It works like the “dictionary search” algorithm.
- It repeatedly halves the number of elements.
 - It is a typical case of a *divide and conquer* algorithm.
 - Because of the halving it is sometimes called *dichotomic*.
- Requires (worst-case) time that is logarithmic in size of the input.

The Basic Idea

- Before studying the algorithm let's define its main task.

Input: The input of the algorithm consists of:

- An item; and
- A list of items sorted in non-decreasing order.
- For simplicity the items in list are unique.

Output: The output of the algorithm is an `int`.

The output depends on one of the following cases.

Item is in list: The index of item in the list.

Item is not in list: A negative number.

- For simplicity we'll assume that all items are `ints`.
- Furthermore, we'll assume that the list is presented as an array.

Software Development

M. R. C. van Dongen

Outline

Recursion

Factorial Computation

Fibonacci Numbers

Towers of Hanoi

Binary Search

The Basic Idea

The Algorithm

Implementation

Simulation

Comparable Interface

Quicksort

For Wednesday

Acknowledgements

About this Document

The Algorithm

```
binSearch( item, items, lo, hi )
```

lo > hi: Return -1.

lo <= hi: 1 Determine “the” middle index.

- We implement this as $\text{mid} = (\text{lo} + \text{hi}) / 2$.
- Unfortunately, this is not correct due to overflow.
- You can fix this by implementing it as
 - ‘ $\text{mid} = \text{lo} + (\text{hi} - \text{lo}) / 2$ ’ or as
 - ‘ $\text{mid} = (\text{hi} + \text{lo}) \ggg 1$ ’.

2 Compare `item` and `items[mid]`.

- **`item == items[mid]`:**
 - Return `mid`.
- **`item < items[mid]`:**
 - Return `binSearch(item, items, lo, mid - 1)`.
- **`item > items[mid]`:**
 - Return `binSearch(item, items, mid + 1, hi)`.

[Outline](#)[Recursion](#)[Factorial Computation](#)[Fibonacci Numbers](#)[Towers of Hanoi](#)[Binary Search](#)[The Basic Idea](#)[The Algorithm](#)[Implementation in Java](#)[Simulation](#)[Comparable Interface](#)[Quicksort](#)[For Wednesday](#)[Acknowledgements](#)[About this Document](#)


Implementation in Java

Java

```
public static int binSearch( int item, int[] items ) {  
    return binSearch( item, items, 0, items.length - 1 );  
}  
  
public static int binSearch( int item, int[] items, int lo, int hi ) {  
    final int result;  
  
    if (lo > hi) {  
        result = - 1;  
    } else {  
        int mid = (lo + hi) / 2;  
        if (item == items[ mid ]) {  
            result = mid;  
        } else if (item < items[ mid ]) {  
            result = binSearch( item, items, lo, mid - 1 );  
        } else {  
            result = binSearch( item, items, mid + 1, hi );  
        }  
    }  
  
    return result;  
}
```


binSearch(4, {1,2,4,5,6,8,9}, 0, 6)

Initial Situation




```
binSearch( 4, {1,2,4,5,6,8,9}, 0, 6 )
```

```
mid = (lo + hi) / 2
```




```
binSearch( 4, {1,2,4,5,6,8,9}, 0, 6 )
```

```
item < item[ mid ]
```




binSearch(4, {1,2,4,5,6,8,9}, 0, 6)

Search to Left of mid





```
binSearch( 4, {1,2,4,5,6,8,9}, 0, 6 )
```

```
mid = (lo + hi) / 2
```




```
binSearch( 4, {1,2,4,5,6,8,9}, 0, 6 )
```

```
item > item[ mid ]
```




binSearch(4, {1,2,4,5,6,8,9}, 0, 6)

Search to Right of mid




```
binSearch( 4, {1,2,4,5,6,8,9}, 0, 6 )
```

```
mid = (lo + hi) / 2
```




```
binSearch( 4, {1,2,4,5,6,8,9}, 0, 6 )
```

Celebration




binSearch(3, {1,2,4,5,6,8,9}, 0, 6)

Initial Situation




```
binSearch( 3, {1,2,4,5,6,8,9}, 0, 6 )
```

```
mid = (lo + hi) / 2
```




```
binSearch( 3, {1,2,4,5,6,8,9}, 0, 6 )
```

```
item < item[ mid ]
```





```
binSearch( 3, {1,2,4,5,6,8,9}, 0, 6 )
```

Search to Left of mid




```
binSearch( 3, {1,2,4,5,6,8,9}, 0, 6 )
```

```
mid = (lo + hi) / 2
```




```
binSearch( 3, {1,2,4,5,6,8,9}, 0, 6 )
```

```
item > item[ mid ]
```




binSearch(3, {1,2,4,5,6,8,9}, 0, 6)

Search to Right of mid




```
binSearch( 3, {1,2,4,5,6,8,9}, 0, 6 )
```

```
mid = (lo + hi) / 2
```




```
binSearch( 3, {1,2,4,5,6,8,9}, 0, 6 )
```

```
item < item[ mid ]
```




binSearch(3, {1,2,4,5,6,8,9}, 0, 6)

Search to Left of mid



```
binSearch( 3, {1,2,4,5,6,8,9}, 0, 6 )
```

Bummer



The Comparable Interface

- We've seen how to use binary search for ints.
- We should be able to generalise it for other *comparable* things.
- *Implementing an interface* is almost the same as extending a class.
 - If class *B* implements interface *A*, *B* behaves as *A*.
- A class *implements* the Comparable *interface* if it overrides
`int compareTo(Object that)`
- Many classes implement the Comparable interface:
 - Integer,
 - Double,
 - String,
 -

A Comparable-Compatible Version

Java

```
public static int binSearch( Comparable item, Comparable[] items, int lo, int hi ) {
    final int result;

    if (lo > hi) {
        result = - 1;
    } else {
        int mid = (lo + hi) / 2;
        int compare = item.compareTo( items[ mid ] );
        if (compare == 0) {
            result = mid;
        } else if (compare < 0) {
            result = binSearch( item, items, lo, mid - 1 );
        } else {
            result = binSearch( item, items, mid + 1, hi );
        }
    }

    return result;
}
```

The Quicksort Algorithm

- Sorting algorithms are a very important class of algorithms.
 - Sorting efficiently is crucial to many applications.
- Quicksort is a simple but efficient sorting algorithm.
- Given n random items its requires $O(n \log n)$ comparisons (on average).
- But, it requires $O(n^2)$ comparisons in the worst case.
- If the input is given as an array, we can sort the array in-situ.
- The algorithm was invented by C. A. R. Hoare in 1962.
- For simplicity we shall study the version for sorting `int` arrays.
- Arrays defines several quicksort-based sorting methods.

Main Idea

Base case: If $n \leq 1$ then the input is sorted.

Recursion: If $n > 1$:

- 1 Select any item from the input.
- 2 Partition remaining items into classes L and G .
 - L are the items less than or equal to the pivot.
 - G are the remaining items.
- 3 Members of L should end up before those of G .
- 4 Put the pivot between L and G .
- 5 Recursively sort L and G .

The Wrapper

Java

```
public static void qsort( int[] items ) {  
    qsort( items, 0, items.length - 1 );  
}
```

Main Algorithm

Java

```
// Sorts items[ lo .. hi ] in non-descending order.
private static void qsort( int[] items, int lo, int hi ) {
    if (hi - lo >= 1) {
        int pivotPosition = partition( items, lo, hi );
        qsort( items, lo, pivotPosition - 1 );
        qsort( items, pivotPosition + 1, hi );
    }
}
```

Main Algorithm: Any Sorting to Do?

Java

```
// Sorts items[ lo .. hi ] in non-descending order.
private static void qsort( int[] items, int lo, int hi ) {
    if (hi - lo >= 1) {
        int pivotPosition = partition( items, lo, hi );
        qsort( items, lo, pivotPosition - 1 );
        qsort( items, pivotPosition + 1, hi );
    }
}
```


Main Algorithm: Sort Items to Left of Pivot

Divide and Conquer

Java

```
// Sorts items[ lo .. hi ] in non-descending order.
private static void qsort( int[] items, int lo, int hi ) {
    if (hi - lo >= 1) {
        int pivotPosition = partition( items, lo, hi );
        qsort( items, lo, pivotPosition - 1 );
        qsort( items, pivotPosition + 1, hi );
    }
}
```

Main Algorithm: Sort Items to Right of Pivot

Divide and Conquer

Java

```
// Sorts items[ lo .. hi ] in non-descending order.
private static void qsort( int[] items, int lo, int hi ) {
    if (hi - lo >= 1) {
        int pivotPosition = partition( items, lo, hi );
        qsort( items, lo, pivotPosition - 1 );
        qsort( items, pivotPosition + 1, hi );
    }
}
```

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

[Outline](#)[Recursion](#)[Factorial Computation](#)[Fibonacci Numbers](#)[Towers of Hanoi](#)[Binary Search](#)[Quicksort](#)[Main Ideas](#)[Implementation in Java](#)[A Call Trace Study](#)[For Wednesday](#)[Acknowledgements](#)[About this Document](#)

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

[Outline](#)[Recursion](#)[Factorial Computation](#)[Fibonacci Numbers](#)[Towers of Hanoi](#)[Binary Search](#)[Quicksort](#)[Main Ideas](#)[Implementation in Java](#)[A Call Trace Study](#)[For Wednesday](#)[Acknowledgements](#)[About this Document](#)

Partition: Pivot Selection and Exchange

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

Partition: Partitioning of Lower Elements

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

Partition: Move Item to Left?

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

Partition: Move Item to Left? Exchange

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```


Partition: Move Item to Left? Adjust Destination

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

Partition: Loop Invariant

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

Partition: Consequence of Loop Invariant

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

Partition: Move Pivot to Destination

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

Partition: Final Invariant

Java


```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= hi.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

Partition: Return Pivot Position

Java

```
private static int partition( int[] items, int lo, int hi ) {
    int destination = lo;
    swop( items, (hi + lo) >>> 1, hi );
    // The pivot is now stored in items[ hi ].
    for (int index = lo; index != hi; index ++) {
        if (items[ hi ] >= items[ index ]) {
            // Move current item to start.
            swop( items, destination, index );
            destination ++;
        }
        // items[ i ] <= items[ hi ] if lo <= i < destination.
        // items[ i ] > items[ hi ] if destination <= i <= index.
    }
    // items[ i ] <= items[ hi ] if lo <= i < destination.
    // items[ i ] > items[ hi ] if destination <= i < hi.
    swop( items, destination, hi );
    // items[ i ] <= items[ destination ] if lo <= i <= destination.
    // items[ i ] > items[ destination ] if destination < i <= hi.
    return destination;
}
```

Call Trace of `qsort({2,5,4,1,3,8} , 0, 5)`



For Wednesday

Software Development

M. R. C. van Dongen

Outline

Recursion

Factorial Computation

Fibonacci Numbers

Towers of Hanoi

Binary Search

Quicksort

For Wednesday

Acknowledgements

About this Document

- Study [Horstmann 2013, Sections 12.1–12.2].

Acknowledgements

Software Development

M. R. C. van Dongen

Outline

Recursion

Factorial Computation

Fibonacci Numbers

Towers of Hanoi

Binary Search

Quicksort

For Wednesday

Acknowledgements

About this Document

- This lecture corresponds to [Horstmann 2013, Sections 12.1–12.2].

About this Document

Software Development

M. R. C. van Dongen

Outline

Recursion

Factorial Computation

Fibonacci Numbers

Towers of Hanoi

Binary Search

Quicksort

For Wednesday

Acknowledgements

About this Document

- This document was created with pdf \LaTeX atex.
- The \LaTeX document class is beamer.