

# Introduction to Java (cs2514)

## Lecture 3 & 4: Classes and Objects

M. R. C. van Dongen

January 23, 2017

# Monday 4–5 in WGB G24

Ahmad  
Barrett  
Bhayla  
Bowen  
Buckley  
Cheung  
Corcoran  
Crowley  
Cullinane  
Cussen  
Davis  
Donnellan  
Dunlea  
Egan  
Foley  
Fox  
Greer  
Harrington  
Hassan Osman Ali  
Hayes  
Houston

Kashif  
David James  
Javed  
Catherine Teresa  
Niall John  
Jason  
Pádraig David  
Brendan John  
Sinéad Rose  
David Jeremiah  
Jack Francis  
David James  
Ben James  
Adam Michael  
Eimear Catherine  
Mia Alice  
Gary  
Olivia Margaret  
Khansaa  
Ronan David  
Shane Leo

Armstrong  
Barry–O'Donovan  
Bourke  
Brownlow  
Carroll  
Condon  
Coughlan  
Crowley  
Curzon  
Czechowicz  
Derham  
Drugan  
Dunphy  
Erkal  
Foran  
Goggin  
Hamid  
Harrington  
Hayes  
Hedayatpour  
Hutchinson

Christopher Daniel  
Adam Joseph  
Noel Francis  
Philip David  
Alan  
Dillon Cian  
Alan Paul  
David Edward  
Sean  
Mikolaj Tomasz  
Aaron Marc  
Sam  
Conor Richard  
Ryan Lokman  
Claire Margaret  
Thomas  
Abdul  
Séan Thomas  
Liam Anthony  
Arash  
Bryan John

## Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Question Time

For Next Friday

Acknowledgements

References

About this Document

# Monday 5–6 in WGB G24

## Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Question Time

For Next Friday

Acknowledgements

References

About this Document

Keatinge  
Killoughy  
Lordan  
Lyons  
Mason  
Mc Grath  
Mc Keever  
Morrissey  
Murphy  
Neylon  
O'Connor  
O'Keeffe  
O'Regan  
O'Riordan  
O'Sullivan  
Parker Lynch  
Prout  
Sheehan  
Stephanov  
Tan  
Young

Joseph Stephen  
David Alan  
Douglas Matthew Maxford  
Thomas Maurice  
Conor  
Jonathan  
Henry James  
Luke John  
David Gerard  
Síle  
Christopher Jude  
Christopher Anthony  
Euan Philip  
Oisin Gearoid  
Fintan Michael  
Jordan Daniel  
Peter Anthony  
Donnachadh Barry  
Gabrielle Svetoslavova  
Yong Hen  
Evan Gerard

Kidney  
Kreicz  
Lyons  
Mangan  
Matthews  
Mc Hugh-Jewell  
Mc Mahon  
Moynihan  
Nardotto  
O'Brien  
O'Donoghue  
O'Leary  
O'Reilly  
O'Sullivan  
O'Sullivan  
Piatek  
Rossiter  
Sheil  
Stuart  
Van Dam

Donnacha Oisín  
Botond  
Colin David  
Sarah Johanna  
Michael  
Eóin Michael  
Darragh Gerard  
Bríd  
Alessia  
Denis Paul  
Aaron Timothy  
Aidan  
Stephen Edward  
Daragh  
Tomás  
Jakub  
Aaron David  
Conor Sean  
Ben Stephen  
Shay

# Objects and Classes

- Programmers construct their Java program from *objects*.
- Similar to a builder building a house from parts:
  - Doors;
  - Windows;
  - Walls;
  - ...
- Each part has its own function.
- The parts work together to form the house:
  - The house is the *sum* of the parts.
- The builder doesn't have to construct the parts.
- All he does is composing them.

# Using Objects

- ❑ Objects are the first citizens of Java programs.
- ❑ You make an object work by calling its methods.
- ❑ Each method is a sequence of instructions.
- ❑ You can call a method even if you don't know its instructions.

## Java

```
System.out.println( "Hello world!" );
```


- ❑ Each method provides a service.
  - ❑ The method performs the service if you call the method.
- ❑ Different methods may provide different services:
  - ❑ Draw a picture;
  - ❑ Print text;
  - ❑ Set up a connection with another computer;
  - ❑ Compute something and return it;
  - ❑ ...

- Each object belongs to a unique class.
- Different objects may belong to different classes.
  - `System.out`
  - `"Hello world!"`
- An object that belongs to a class is called an *instance* of the class.
- A class may have more than one instance:
  - `"Hello world!"`
  - `"What's up Doc?"`
  - ...



# Classes

- Each object belongs to a unique class.
- Different objects may belong to different classes.
  - `System.out`
  - `"Hello world!"`
- An object that belongs to a class is called an *instance* of the class.
- A class may have more than one instance:
  - `"Hello world!"`
  - `"What's up Doc?"`
  - ...



- Each object belongs to a unique class.
- Different objects may belong to different classes.
  - `System.out`
  - `"Hello world!"`
- An object that belongs to a class is called an *instance* of the class.
- A class may have more than one instance:
  - `"Hello world!"`
  - `"What's up Doc?"`
  - ...





- Each object belongs to a unique class.
- Different objects may belong to different classes.
  - `System.out`
  - `"Hello world!"`
- An object that belongs to a class is called an *instance* of the class.
- A class may have more than one instance:
  - `"Hello world!"`
  - `"What's up Doc?"`
  - ...



# Classes (Continued)

- Each class has its own *Application Programming Interface* (API).
- The API describes how to use the class:
  - The names of the methods;
  - The types of the arguments;
  - The purpose of the arguments;
  - The return value;
  - Side effects;
  - ...
- The API defines a common protocol:

## Java

```
System.out.println( "Hello world!" );  
System.err.println( "Fatal error." );
```

- Different classes may have different APIs.
  - E.g. an instance of the String class cannot print.

## Don't Try This at Home

```
"Hello world!".println( "What's up Doc?" );
```

- Most programs require computations.
  - Add 13% VAT to the price;
  - Add 2 penalty points;
  - Determine the maximum input value;
  - ...
- A single computation may require many sub-computations.
- You (usually) store the results of a computation in a *variable*.
- A variable has several properties:
  - A name;
  - A memory location to store its value;
  - Its current value.
- To change a variable's value, you *assign* it a new value.

# Java

```
⟨variable's name⟩ = ⟨expression that determines the value⟩;
```

# Variables

- ❑ Before you can use a variable, you must *declare* it.
- ❑ A variable declaration determines:
  - ❑ The variable's name;
  - ❑ The variable's type (the kind of its values);

## Java

```
int counter;  
double interest;
```

- ❑ A variable declaration may also determine the initial value;

## Java

```
String greetings = "Hello world!";
```

# Assignment and Equality

- In mathematics you use = for equality.
- In Java you use = for assignment.



# Assignment and Equality

- In mathematics you use = for equality.
- In Java you use = for assignment.
- **But assignment and equality are not the same.**



# Assignment and Equality

- In mathematics you use = for equality.
- In Java you use = for assignment.
- But assignment and equality are not the same.
- The symbols are the “same” but they don’t mean the same.



# Assignment and Equality

- In mathematics you use  $=$  for equality.
- In Java you use  $=$  for assignment.
- But assignment and equality are not the same.
- The symbols are the “same” but they don’t mean the same.
- **Mathematical equality is commutative: if  $a = b$ , then  $b = a$ .**





# Assignment and Equality

- In mathematics you use  $=$  for equality.
- In Java you use  $=$  for assignment.
- But assignment and equality are not the same.
- The symbols are the “same” but they don’t mean the same.
- Mathematical equality is commutative: if  $a = b$ , then  $b = a$ .
- However, you can’t write the following in Java:

## Don’t Try This at Home

```
1 = a; // ?
```




# Assignment and Equality

- ❑ In mathematics you use  $=$  for equality.
- ❑ In Java you use  $=$  for assignment.
- ❑ But assignment and equality are not the same.
- ❑ The symbols are the “same” but they don’t mean the same.
- ❑ Mathematical equality is commutative: if  $a = b$ , then  $b = a$ .
- ❑ However, you can’t write the following in Java:

## Don’t Try This at Home

```
1 = a; // ?
```

- ❑ In mathematics  $a = a + 1$  is impossible.



# Assignment and Equality

- ❑ In mathematics you use  $=$  for equality.
- ❑ In Java you use  $=$  for assignment.
- ❑ But assignment and equality are not the same.
- ❑ The symbols are the “same” but they don’t mean the same.
- ❑ Mathematical equality is commutative: if  $a = b$ , then  $b = a$ .
- ❑ However, you can’t write the following in Java:

## Don’t Try This at Home

```
1 = a; // ?
```

- ❑ In mathematics  $a = a + 1$  is impossible.
- ❑ However, writing the following is valid in Java.

## Java

```
counter = counter + 1;
```



- Java has different numeric types.

whole numbers

- byte;
- short;
- int;
- long.

floating point

- float;
- double.

- For whole numbers, int is usually a good choice.
- For floating point numbers, use double.

# Operations on Numbers

unary plus  $+ \langle \text{operand} \rangle;$

unary minus  $- \langle \text{operand} \rangle;$

adding  $\langle \text{operand \#1} \rangle + \langle \text{operand \#2} \rangle;$

subtracting  $\langle \text{operand \#1} \rangle - \langle \text{operand \#2} \rangle;$

multiplying  $\langle \text{operand \#1} \rangle * \langle \text{operand \#2} \rangle;$

dividing  $\langle \text{operand \#1} \rangle / \langle \text{operand \#2} \rangle;$

...

■ Multiplicative operators bind more tightly:

■  $a * b + c$  equals  $c + a * b$  equals  $(a * b) + c$ .

■  $a / b + c$  equals  $c + a / b$  equals  $(a / b) + c$ .

# Primitive Types and Object Reference Types

- A type starting with a lowercase letter is a *primitive* variable.
  - `int`, `bool`, `char`, `float`, ...
- A type starting with an uppercase letter is an *object/reference* variable.
  - `Integer`, `Boolean`, `Character`, `Float`, ...
  - Object variables have objects (primitive variables don't).

## Java

```
Integer number = new Integer( 1 );  
String string = number.toString( );
```

- Best view these types as wrapper classes for primitive type values.

# Wrapper Classes

- Java has a *wrapper class* for each primitive type.

**Integer** For ints:

```
final Integer iObject = new Integer( 42 );  
final int val = iObject.intValue( );
```

**Double** For doubles:

```
final Double dObject = new Double( 3.14 );  
final double val = dObject.doubleValue( );
```

**Boolean** For booleans:

```
final Boolean bObject = new Boolean( true );  
final boolean val = bObject.booleanValue( );
```

....

# Autoboxing and Unboxing

- Writing code to convert to and from wrapper classes is tedious.
  - You must type more.
  - It increases the code size.
- That's why Java automates (some) conversions.
  - Automatic conversion to the wrapper class is called *autoboxing*.
  - Automatic conversion from the wrapper class is called *unboxing*.
- The conversion is done at runtime.



# Autoboxing

- Let `val` be an value with primitive type `type`.
  - If you use `val` and Java expects an object, Java will autobox `val`.
- The type of `val` determines the wrapper class:
  - `int`  $\mapsto$  `Integer`;
  - `double`  $\mapsto$  `Double`;
  - `boolean`  $\mapsto$  `Boolean`;
  - ...

# Unboxing

- Unboxing turns wrapper class objects to primitive type values.
- The wrapper class type determines the primitive type.
  - `Integer`  $\mapsto$  `int`;
  - `Double`  $\mapsto$  `double`;
  - `Boolean`  $\mapsto$  `boolean`;
  - ...
- The conversion is done at runtime.

# Caching

- Java *caches* a limited number of wrapper class values.
- Guarantees shallow equality for small number of boxed values.
  - If `o1.equals( o2 )` then `o1 == o2`.
- For example, `new Integer( 0 ) == new Integer( 0 )`.
- In general this may not always work:
  - Almost always: `new Integer( 666 ) != new Integer( 666 )`.
- Caching is implemented because it saves memory.
- In general caching works for “small” primitive values.
  - `boolean`: `true` and `false`.
  - `byte`: `0–255`.
  - `char`: `\u0000–\u007f`.
  - `short`: `-128, -127, ..., 127`.
  - `int`: `-128, -127, ..., 127`.

# Constant Variables

- ❑ A *constant* (variable) can only be assigned a value once.
- ❑ You declare a constant by adding the keyword `final`.

## Java

```
final int ANSWER = 42;
```

- ❑ Making a variable constant is a form of documentation.
- ❑ It lets the compiler help you detect logic errors:

## Java

```
final int ACCELERATION = 9.8;  
...  
ACCELERATION = 9.9;
```

# Using Variables in Methods

- You cannot use an unassigned variable in a method.

## Don't Try This at Home

```
int number;  
int square = number * number;
```

# Comments

- A *comment* is text that is ignored by the compiler.
- Comments have several purposes:
  - They describe the purpose of a variable or a method.
  - They describe a relationship between two or more variables.
    - This is called an invariant.
  - They are used to create API documentation.
- You should always document your programs.

# One Line Comments

## Java

```
// number of centimetres per inch  
final double CENTIMETRES_PER_INCH = 2.56;
```

# Multi-Line Line Comments

## Java

```
/* Encrypted user password.  
 * Use the changePassword( ) method to change the password.  
 */  
String password;
```

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Wrapper Classes

Autoboxing & Unboxing

Caching

Types Matter

Working with Objects

Encapsulation

Arrays

Question Time

For Next Friday

Acknowledgements

References

About this Document



# JavaDoc Comments

## Java

```
/**  
 * ...  
 */
```

[Introduction to Java](#)

[M. R. C. van Dongen](#)

[Lab Sessions](#)

[Objects and Classes](#)

[Variables](#)

[Wrapper Classes](#)

[Autoboxing & Unboxing](#)

[Caching](#)

[Types Matter](#)

[Working with Objects](#)

[Encapsulation](#)

[Arrays](#)

[Question Time](#)

[For Next Friday](#)

[Acknowledgements](#)

[References](#)

[About this Document](#)

# Variable Names

- Use names that are meaningful.
- The name should describe the variable's purpose.
- By convention each variable name should be a noun.
  - non-constant
    - Each name should start with a lowercase letter.
    - The rest should be letters and digits.
    - At word boundaries, you use an uppercase letter.
    - All other letters should be lowercase.
    - E.g. `sum`, `currentColour`, ...
  - constant
    - Use sequences of words, digits, and underscores.
    - Each word is spelt with uppercase letters.
    - At word boundaries, you use an underscore.
    - E.g. `CENT`, `CENTIMETRES_PER_INCH`, ....

# Choosing Variable Names

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Wrapper Classes

Autoboxing & Unboxing

Caching

Types Matter

Working with Objects

Encapsulation

Arrays

Question Time

For Next Friday

Acknowledgements

References

About this Document


# Choosing Variable Names

- Variable names should be descriptive.



# Choosing Variable Names

- Variable names should be descriptive.
- **This is a form of documentation:**
  - It helps you remember what the variable does.
  - It helps others understand the purpose of the variable.



# Choosing Variable Names

- Variable names should be descriptive.
- This is a form of documentation:
  - It helps you remember what the variable does.
  - It helps others understand the purpose of the variable.



# Choosing Variable Names

- Variable names should be descriptive.
- This is a form of documentation:
  - It helps you remember what the variable does.
  - It helps others understand the purpose of the variable.



# Choosing Variable Names

- Variable names should be descriptive.
- This is a form of documentation:
  - It helps you remember what the variable does.
  - It helps others understand the purpose of the variable.
- Choosing a good name helps you understand the purpose.





# Choosing Variable Names

- Variable names should be descriptive.
- This is a form of documentation:
  - It helps you remember what the variable does.
  - It helps others understand the purpose of the variable.
- Choosing a good name helps you understand the purpose.
  - If you can't find a good name, do you really know the purpose?



# Java Cares about its Types

## Java


```
Dog barney = new Dog( );  
Dog pluto = new Dog( );  
Giraffe giraffe = new Giraffe( );
```



# Java Cares about its Types

## Java


```
Dog barney = new Dog( );  
Dog pluto = new Dog( );  
Giraffe giraffe = new Giraffe( );
```



# Java Cares about its Types

## Java


```
Dog barney = new Dog( );  
Dog pluto = new Dog( );  
Giraffe giraffe = new Giraffe( );
```



# Java Cares about its Types

## Java

```
Dog barney = new Dog( );  
Dog pluto = new Dog( );  
Giraffe giraffe = new Giraffe( );
```



# Types Really Matter

## Don't Try This at Home


```
Dog barney = new Giraffe( );
```



# Types Really Matter

## Don't Try This at Home


```
Dog barney = new Giraffe( );
```



# Types Really Matter

## Don't Try This at Home

```
Dog barney = new Giraffe( );  
barney.bark( );
```






# Types Really Matter

## Don't Try This at Home


```
Dog barney = new Giraffe( );  
barney.bark( ); // ???
```



# Types Really Matter

## Don't Try This at Home

```
Dog barney = new Giraffe( ); // Impossible  
barney.bark( ); // ???
```



# Working with Objects

- ❑ Before you can use an object, you must construct (create) it.
- ❑ To construct an object, you call its constructor.
  - ❑ The constructor constructs and initialises the object.
- ❑ There may be different ways to construct an object.

## Java

```
final Rectangle bar = new Rectangle( x, y, width, height );
```

# Constructing the Rectangle

## Java

```
Rectangle bar = new Rectangle( x, y, width, height )
```

- 1 The new operator creates memory to represents the object;
- 2 The constructor uses its arguments to initialise the object;
- 3 The constructor returns a *reference* to the object;
- 4 The reference is assigned to the object reference value bar.
- 5 The reference may be used to call the object's instance methods.

# Method Declarations

- ❑ To define/declare a method you provide:
  - ❑ The name of the method;
  - ❑ The return type;
  - ❑ The names and types of the formal parameters;
  - ❑ The types of the formal parameters.

## Java

```
public int getWidth( ) { /* Implementation omitted. */ }
```

- ❑ You use void for a method without return value.

## Java

```
public void println( String output ) { /* Implementation omitted. */ }
```

- ❑ If the argument types are different, the names may overlap.
  - ❑ This is called *overloading*:

## Java

```
public void println( int output ) { /* Implementation omitted. */ }
```

# Accessor and Mutator Methods

- A method that returns information about an object without modifying the object is an *accessor method*.
  - `double width = rectangle.getWidth( );`
- A method that modifies an object's instance variables is a *mutator method*.
  - `rectangle.setWidth( 4.0 );`

# Implementing a Tally Counter Class

- Let's implement a tally counter object class.
- The name of the class should be a noun.
  - The name should start with an uppercase letter.
  - The name should continue with letters and digits.
  - At each word boundary, you use an uppercase letter.
  - All other letters should be lowercase.
  - The name should describe the instances of the class.
  - For example, `StringBuilder`, `FullAdder`, ...

# State and Behaviour

- Let's use Counter for our class name.
- How do we implement the class?
- We must determine what the Counter instances do and know.
- What the instance does is its *behaviour*.
  - Object behaviour is implemented as *instance methods*.
- What the instance knows is its *state*.
  - Object state is implemented as *instance variables*.





# State and Behaviour

- Let's use Counter for our class name.
- How do we implement the class?
- We must determine what the Counter instances do and know.
- What the instance does is its *behaviour*.
  - Object behaviour is implemented as *instance methods*.
- What the instance knows is its *state*.
  - Object state is implemented as *instance variables*.
- Too much (object) state slows down the JVM.



# State and Behaviour

- Let's use Counter for our class name.
- How do we implement the class?
- We must determine what the Counter instances do and know.
- What the instance does is its *behaviour*.
  - Object behaviour is implemented as *instance methods*.
- What the instance knows is its *state*.
  - Object state is implemented as *instance variables*.
- Too much (object) state slows down the JVM.
- An object's behaviour should determine its state:



# State and Behaviour

- Let's use Counter for our class name.
- How do we implement the class?
- We must determine what the Counter instances do and know.
- What the instance does is its *behaviour*.
  - Object behaviour is implemented as *instance methods*.
- What the instance knows is its *state*.
  - Object state is implemented as *instance variables*.
- Too much (object) state slows down the JVM.
- An object's behaviour should determine its state:
  - **Never, ever start with object state.**



# State and Behaviour

- Let's use Counter for our class name.
- How do we implement the class?
- We must determine what the Counter instances do and know.
- What the instance does is its *behaviour*.
  - Object behaviour is implemented as *instance methods*.
- What the instance knows is its *state*.
  - Object state is implemented as *instance variables*.
- Too much (object) state slows down the JVM.
- An object's behaviour should determine its state:
  - Never, *ever* start with object state.
  - **Start thinking about the behaviour.**



# State and Behaviour

- Let's use Counter for our class name.
- How do we implement the class?
- We must determine what the Counter instances do and know.
- What the instance does is its *behaviour*.
  - Object behaviour is implemented as *instance methods*.
- What the instance knows is its *state*.
  - Object state is implemented as *instance variables*.
- Too much (object) state slows down the JVM.
- An object's behaviour should determine its state:
  - Never, *ever* start with object state.
  - Start thinking about the behaviour.
  - If behaviour requires state, you implement the state.



# State and Behaviour

- Let's use Counter for our class name.
- How do we implement the class?
- We must determine what the Counter instances do and know.
- What the instance does is its *behaviour*.
  - Object behaviour is implemented as *instance methods*.
- What the instance knows is its *state*.
  - Object state is implemented as *instance variables*.
- Too much (object) state slows down the JVM.
- An object's behaviour should determine its state:
  - Never, *ever* start with object state.
  - Start thinking about the behaviour.
  - If behaviour requires state, you implement the st
  - **Otherwise, you don't.**



# Behaviour

## What Should a Counter Object Do?

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Question Time

For Next Friday

Acknowledgements

References

About this Document



# Behaviour

## What Should a Counter Object Do?

- Compute its next counter value:
  - `public void incrementValue( )`
- Return its current counter value:
  - `public int getValue( )`





# Behaviour

## What Should a Counter Object Do?

- Compute **its** next counter value:
  - `public void incrementValue( )`
- Return **its** current counter value:
  - `public int getValue( )`



# Behaviour

What Should a Counter Object Do? This indicates **its** state.

- Compute its next counter value:
  - `public void incrementValue( )`
- Return its current counter value:
  - `public int getValue( )`



# What Should a Counter Object Know?

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays


Question Time

For Next Friday

Acknowledgements

References

About this Document



# What Should a Counter Object Know?

- Its counter value:
  - `private int value;`



# The Class

## Class Definition

### Java

```
// Class for representing tally counter objects.
public class Counter {
    // The current tally counter value.
    private int value;

    // Returns the current counter value.
    public int getValue( ) {
        return value;
    }

    // Increment the counter value.
    public void incrementValue( ) {
        value = value + 1;
    }
}
```

# The Class

## Instance Attribute Declaration

### Java

```
// Class for representing tally counter objects.
public class Counter {
    // The current tally counter value.
    private int value;

    // Returns the current counter value.
    public int getValue( ) {
        return value;
    }

    // Increment the counter value.
    public void incrementValue( ) {
        value = value + 1;
    }
}
```

# The Class

## Instance Method Declarations

### Java

```
// Class for representing tally counter objects.
public class Counter {
    // The current tally counter value.
    private int value;

    // Returns the current counter value.
    public int getValue( ) {
        return value;
    }

    // Increment the counter value.
    public void incrementValue( ) {
        value = value + 1;
    }
}
```

# The Class

## Access/Visibility Specifiers

### Java

```
// Class for representing tally counter objects.
public class Counter {
    // The current tally counter value.
    private int value;

    // Returns the current counter value.
    public int getValue( ) {
        return value;
    }

    // Increment the counter value.
    public void incrementValue( ) {
        value = value + 1;
    }
}
```



# The Class

## Types

### Java

```
// Class for representing tally counter objects.
public class Counter {
    // The current tally counter value.
    private int value;

    // Returns the current counter value.
    public int getValue( ) {
        return value;
    }

    // Increment the counter value.
    public void incrementValue( ) {
        value = value + 1;
    }
}
```

# The Class

Comments: You should use JavaDoc Here

## Java

```
// Class for representing tally counter objects.
public class Counter {
    // The current tally counter value.
    private int value;

    // Returns the current counter value.
    public int getValue( ) {
        return value;
    }

    // Increment the counter value.
    public void incrementValue( ) {
        value = value + 1;
    }
}
```

# Instance Variables

- Each Counter object has its own value variable.
- Let's assume tally is a Counter object reference (variable):
  - To access its value you write `tally.value`.
- The Counter object owns the variable.
- Different Counter objects may have different values for value.

# Instance Methods

- Counter objects can call Counter instance methods.
- Calling them is similar to accessing the instance variable:
  - `tally.incrementValue( );`
  - `int current = tally.getValue( );`

# Encapsulation

- Objects should be self-governing.
- They should control their own instance variables.
- An object is self-governing if its instance variables are private.
- This is called *hiding* the instance variables.
  - Variable hiding prevents direct variable access by external clients.
- Hiding the instance variables makes the object self-contained.
  - It's as if the object's instance variables are in a capsule.
  - This is why instance variable hiding is usually called *encapsulation*.

# Why Do We Need Encapsulation?

- ❑ Direct attribute access is unsafe/dangerous.
  - ❑ A malicious external agent may corrupt the attribute's value.
- ❑ Encapsulation simplifies the complexity of the API.
  - ❑ Makes learning the API easier.
  - ❑ Makes using the API easier.
  - ❑ Makes designing the API easier.
  - ❑ Makes reasoning about the API easier.
  - ❑ Makes testing the API easier.
- ❑ Prevents clients from *depending* on the implementation.
  - ❑ Allows implementation changes without breaking clients.

# Contract

- We hide all instance variables.
- We hide all methods that aren't/shouldn't be part of the API.

# Hiding Methods

- Java also lets you hide method declarations.

## Java

```
public int squareOfAnswer( ) {  
    return answer( ) * answer( );  
}  
  
private int answer( ) {  
    return 42;  
}
```

- Hiding methods has similar advantages as hiding attributes.



# Automatic Variables

- A variable that is declared in a method is called *automatic*.
  - It only lives for the lifespan of its block during its method call.



# Automatic Variables

- A variable that is declared in a method is called *automatic*.
  - It only lives for the lifespan of its block during its method call.
- Use automatic variables for intermediate computations.



# Automatic Variables

- A variable that is declared in a method is called *automatic*.
  - It only lives for the lifespan of its block during its method call.
- Use automatic variables for intermediate computations.
- **Don't use instance attributes for intermediate computations.**



- Arrays are a special data type in Java.
- Arrays are **objects** that contain other things.
- There are two kinds of arrays:
  - 1 Arrays consisting of primitive data type values;
  - 2 Arrays consisting of object reference values;
- The type of the array determines the type of its values.
- Before you can use an array you must create it (it's an **object**).
  - When doing this, you must specify the array's length.
  - The length remains fixed.
- You can put things into the array.
- You can retrieve things from the array.
- You can only access arrays with index values:
  - Only `int` index values are allowed.
  - They must be non-negative;
  - They must be smaller than the length of the array.

## Lab Sessions

## Objects and Classes

## Variables

## Types Matter

## Working with Objects

## Encapsulation

## Arrays

## Introduction

## Initialisation

## Getting & Putting

## Arrays do Not Grow

### Partially Filled Arrays

### Common Errors

## Question Time

For Next Friday

## Acknowledgements

## References

## About this Document

# Initialisation

## Java

```
final int[] numbers = new int[ 10 ];  
System.out.println( "length of numbers: " + numbers.length );  
  
final String[] words = new String[ 5 ];  
System.out.println( "length of words: " + words.length );
```

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Introduction

Initialisation

Getting & Putting

Arrays do Not Grow

Partially Filled Arrays

Common Errors

Question Time

For Next Friday

Acknowledgements

References

About this Document

# Initialisation

## Java

```
final int[] numbers = new int[ 10 ];  
System.out.println( "length of numbers: " + numbers.length );  
  
final String[] words = new String[ 5 ];  
System.out.println( "length of words: " + words.length );
```

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Introduction

Initialisation

Getting & Putting

Arrays do Not Grow

Partially Filled Arrays

Common Errors

Question Time

For Next Friday

Acknowledgements

References

About this Document

# Getting Stuff from the Array

- An array is best viewed as a tray/sequence with cups.
- Each cup has a number: 0, 1, ...
- The cups contain what's in the array:
  - Object references.
- The number of cups is the length of the array.
- Let array be a Java array.
- Then `array[ i ]` is the *i*th cup of array.

## Java

```
final int[] numbers = new int[ 10 ];  
...  
System.out.println( "The first value is " + numbers[ 0 ] );  
System.out.println( "The last value is " + numbers[ 9 ] );
```

# Getting Stuff from the Array

- An array is best viewed as a tray/sequence with cups.
- Each cup has a number: 0, 1, ...
- The cups contain what's in the array:
  - Object references.
- The number of cups is the length of the array.
- Let array be a Java array.
- Then `array[ i ]` is the *i*th cup of array.

## Java

```
final int[] numbers = new int[ 10 ];  
...  
System.out.println( "The first value is " + numbers[ 0 ] );  
System.out.println( "The last value is " + numbers[ 9 ] );
```



# Getting Stuff from the Array

- An array is best viewed as a tray/sequence with cups.
- Each cup has a number: 0, 1, ...
- The cups contain what's in the array:
  - Object references.
- The number of cups is the length of the array.
- Let array be a Java array.
- Then `array[ i ]` is the *i*th cup of array.

## Java

```
final int[] numbers = new int[ 10 ];  
...  
System.out.println( "The first value is " + numbers[ 0 ] );  
System.out.println( "The last value is " + numbers[ 9 ] );
```

# Writing Stuff to the Array

- The notation `array[ index ]` works just as with getting.
- Cups in the arrays work just like variables, so
  - `array[ index ] = value` assigns a value to the “indexth” cup.

# Writing Stuff to the Array

- The notation `array[ index ]` works just as with getting.
- Cups in the arrays work just like variables, so
  - `array[ index ] = value` assigns a value to the “indexth” cup.

## Java

```
final int[] numbers = new int[ 10 ];  
  
numbers[ 0 ] = 1;  
numbers[ 9 ] = 42;  
System.out.println( numbers[ 0 ] + " == 1" );  
System.out.println( numbers[ 9 ] + " == 42" );
```

# Writing Stuff to the Array

- The notation `array[ index ]` works just as with getting.
- Cups in the arrays work just like variables, so
  - `array[ index ] = value` assigns a value to the “indexth” cup.

## Java

```
final int[] numbers = new int[ 10 ];  
  
numbers[ 0 ] = 1;  
numbers[ 9 ] = 42;  
System.out.println( numbers[ 0 ] + " == 1" );  
System.out.println( numbers[ 9 ] + " == 42" );
```

# Writing Stuff to the Array

- The notation `array[ index ]` works just as with getting.
- Cups in the arrays work just like variables, so
  - `array[ index ] = value` assigns a value to the “indexth” cup.

## Java

```
final int[] numbers = new int[ 10 ];  
  
numbers[ 0 ] = 1;  
numbers[ 9 ] = 42;  
System.out.println( numbers[ 0 ] + " == 1" );  
System.out.println( numbers[ 9 ] + " == 42" );
```

# Writing Stuff to the Array

- The notation `array[ index ]` works just as with getting.
- Cups in the arrays work just like variables, so
  - `array[ index ] = value` assigns a value to the “indexth” cup.

## Java

```
final int[] numbers = new int[ 10 ];  
  
numbers[ 0 ] = 1;  
numbers[ 9 ] = 42;  
System.out.println( numbers[ 0 ] + " == 1" );  
System.out.println( numbers[ 9 ] + " == 42" );
```

# Default Values

- When the JVM creates an array, it initialises the array's contents.
- Each cup in the array is filled with the same value.
- This value depends on the type of the array.

```
Numeric 0;  
boolean false;  
char '\u0000';  
Object null.
```

# Arrays with Primitive Type Values

## Java

```
byte[] nums = new byte[ 5 ];  
nums[ 1 ] = 4;  
nums[ 4 ] = 17;
```






# Arrays with Primitive Type Values

## Java


```
byte[] nums = new byte[ 5 ];  
nums[ 1 ] = 4;  
nums[ 4 ] = 17;
```



# Arrays with Primitive Type Values

## Java


```
byte[] nums = new byte[ 5 ];  
nums[ 1 ] = 4;  
nums[ 4 ] = 17;
```



# Arrays with Primitive Type Values

## Java

```
byte[] nums = new byte[ 5 ];  
nums[ 1 ] = 4;  
nums[ 4 ] = 17;
```



# Arrays with Objects

## Java


```
Dog[] dogs = new Dog[ 3 ];  
dogs[ 1 ] = new Dog( );  
dogs[ 1 ].bark( );  
dogs[ 0 ].bark( );
```



# Arrays with Objects

## Java


```
Dog[] dogs = new Dog[ 3 ];  
dogs[ 1 ] = new Dog( );  
dogs[ 1 ].bark( );  
dogs[ 0 ].bark( );
```



# Arrays with Objects

## Java


```
Dog[] dogs = new Dog[ 3 ];  
dogs[ 1 ] = new Dog( );  
dogs[ 1 ].bark( );  
dogs[ 0 ].bark( );
```



# Arrays with Objects

## Java


```
Dog[] dogs = new Dog[ 3 ];  
dogs[ 1 ] = new Dog( );  
dogs[ 1 ].bark( );  
dogs[ 0 ].bark( );
```



# Arrays with Objects

## Java

```
Dog[] dogs = new Dog[ 3 ];  
dogs[ 1 ] = new Dog( );  
dogs[ 1 ].bark( );  
dogs[ 0 ].bark( ); // Run-time error!
```





# Arrays do Not Grow

- The `length` attribute of a Java array is `final`.
- So you cannot assign values to `⟨array⟩.length`.
- The minimum size of any array is 0.
- The maximum size of any array is `Integer.MAX_VALUE`.

# Partially Filled Arrays

- ❑ You must fill the array before you can use it.
- ❑ You usually start filling at the bottom (index 0).
- ❑ Then fill the next position (index 1).
- ❑ And so on.
- ❑ You need a counter to keep track of the current index.

## Java

```
final Scanner scanner = new Scanner( System.in );
final int[] values = new int[ scanner.nextInt( ) ];

int size = 0;
int next = 0;
while ((size != values.length) && (next >= 0)) {
    System.err.println( "Next value (negative value to stop): " );
    next = scanner.next( );
    if (next >= 0) {
        values[ size++ ] = next;
    }
}

final double percentage = 100.0 * size / values.length ;
System.out.println( "Percentage filled is " + percentage );
```

# Partially Filled Arrays

- ❑ You must fill the array before you can use it.
- ❑ You usually start filling at the bottom (index 0).
- ❑ Then fill the next position (index 1).
- ❑ And so on.
- ❑ You need a counter to keep track of the current index.

## Java

```
final Scanner scanner = new Scanner( System.in );
final int[] values = new int[ scanner.nextInt( ) ];

int size = 0;
int next = 0; // We need this to enter the loop.
while ((size != values.length) && (next >= 0)) {
    System.err.println( "Next value (negative value to stop): " );
    next = scanner.next( );
    if (next >= 0) {
        values[ size++ ] = next;
    }
}

final double percentage = 100.0 * size / values.length );
System.out.println( "Percentage filled is " + percentage );
```

# Common Errors

Index too Large

## Don't Try This at Home

```
int[] values = new int[ 10 ];  
values[ 10 ] = 1;
```

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Introduction

Initialisation

Getting & Putting

Arrays do Not Grow

Partially Filled Arrays

Common Errors

Question Time

For Next Friday

Acknowledgements

References

About this Document

# Common Errors

Index too Small

## Don't Try This at Home

```
int[] values = new int[ 10 ];  
values[ -1 ] = 1;
```

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Introduction

Initialisation

Getting & Putting

Arrays do Not Grow

Partially Filled Arrays

Common Errors

Question Time

For Next Friday

Acknowledgements

References

About this Document

# Common Errors

## Uninitialised Values

### Don't Try This at Home

```
String[] words = new String[ 10 ];  
  
if (words[ 0 ].equals( "yes" )) {  
    System.out.println( "This isn't printed." );  
} else {  
    System.out.println( "This also isn't printed." );  
}
```

# Representing Bank Accounts

- Consider a bank account application.
- Each account has an owner and a balance.
  - We could represent the owners using a `String` array;
  - We could represent the balance using a `double` array.

# Parallel Array Implementation

The for Loop Declares Its Own index Variable

## Java

```
public class AccountManager {  
    private final String[] owners;  
    private final double[] balances;  
  
    public AccountManager( final int size ) {  
        final Scanner scanner = new Scanner( System.in );  
        owners = new String[ size ];  
        balances = new double[ size ];  
        for (int index = 0; index != size; index++) {  
            owners[ index ] = scanner.next( );  
            balances[ index ] = scanner.nextDouble( );  
        }  
    }  
  
    ...  
}
```

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Introduction

Initialisation

Getting & Putting

Arrays do Not Grow

Partially Filled Arrays

Common Errors

Question Time

For Next Friday

Acknowledgements

References

About this Document



# Parallel Array Implementation

The for Loop Declares Its Own index Variable

## Java

```
public class AccountManager {
    private final String[] owners;
    private final double[] balances;

    public AccountManager( final int size ) {
        final Scanner scanner = new Scanner( System.in );
        owners = new String[ size ];
        balances = new double[ size ];
        for (int index = 0; index != size; index++) {
            owners[ index ] = scanner.next( );
            balances[ index ] = scanner.nextDouble( );
        }
    }

    ...
}
```

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Introduction

Initialisation

Getting & Putting

Arrays do Not Grow

Partially Filled Arrays

Common Errors

Question Time

For Next Friday

Acknowledgements

References

About this Document

# Parallel Array Implementation

The for Loop Declares Its Own index Variable

## Java

```
public class AccountManager {
    private final String[] owners;
    private final double[] balances;

    public AccountManager( final int size ) {
        final Scanner scanner = new Scanner( System.in );
        this.owners = new String[ size ];
        this.balances = new double[ size ];
        for (int index = 0; index != size; index++) {
            owners[ index ] = scanner.next( );
            balances[ index ] = scanner.nextDouble( );
        }
    }

    ...
}
```

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Introduction

Initialisation

Getting & Putting

Arrays do Not Grow

Partially Filled Arrays

Common Errors

Question Time

For Next Friday

Acknowledgements

References

About this Document

# Parallel Array Implementation

The for Loop Declares Its Own index Variable

## Java

```
public class AccountManager {  
    private final String[] owners;  
    private final double[] balances;  
  
    public AccountManager( final int size ) {  
        final Scanner scanner = new Scanner( System.in );  
        owners = new String[ size ];  
        balances = new double[ size ];  
        for (int index = 0; index != size; index++) {  
            owners[ index ] = scanner.next( );  
            balances[ index ] = scanner.nextDouble( );  
        }  
    }  
  
    ...  
}
```

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Introduction

Initialisation

Getting & Putting

Arrays do Not Grow

Partially Filled Arrays

Common Errors

Question Time

For Next Friday

Acknowledgements

References

About this Document

# Class-Based Implementation

## Java

```
public class AccountManager {  
    private final Account[] accounts;  
  
    public AccountManager( final int size ) {  
        final Scanner scanner = new Scanner( System.in );  
        accounts = new Account[ size ];  
        for (int index = 0; index != size; index++) {  
            final String owner = scanner.next( );  
            final double balance = scanner.nextDouble( );  
            accounts[ index ] = new Account( owner, balance );  
        }  
    }  
  
    ...  
}
```

# Class-Based Implementation

## Java

```
public class AccountManager {  
    private final Account[] accounts;  
  
    public AccountManager( final int size ) {  
        final Scanner scanner = new Scanner( System.in );  
        accounts = new Account[ size ];  
        for (int index = 0; index != size; index++) {  
            final String owner = scanner.next( );  
            final double balance = scanner.nextDouble( );  
            accounts[ index ] = new Account( owner, balance );  
        }  
    }  
  
    ...  
}
```

# Class-Based Implementation

## Java

```
public class AccountManager {
    private final Account[] accounts;

    public AccountManager( final int size ) {
        final Scanner scanner = new Scanner( System.in );
        this.accounts = new Account[ size ];
        for (int index = 0; index != size; index++) {
            final String owner = scanner.next( );
            final double balance = scanner.nextDouble( );
            accounts[ index ] = new Account( owner, balance );
        }
    }

    ...
}
```

# Class-Based Implementation

## Java

```
public class AccountManager {  
    private final Account[] accounts;  
  
    public AccountManager( final int size ) {  
        final Scanner scanner = new Scanner( System.in );  
        accounts = new Account[ size ];  
        for (int index = 0; index != size; index++) {  
            final String owner = scanner.next( );  
            final double balance = scanner.nextDouble( );  
            accounts[ index ] = new Account( owner, balance );  
        }  
    }  
  
    ...  
}
```

## Comparison

**Stability** The parallel array implementation is “unstable:”

- If we need addresses we must change the constructor.

**Security** The parallel array implementation is not safe:

- ❑ Parallel array clients need access to all arrays:
  - ❑ `withdraw( owners, balances, nr, amount );`
  - ❑ This gives the client access to all account details.
  - ❑ They can even modify the array.
  - ❑ It violates encapsulation.
- ❑ Direct access for Account clients:
  - ❑ `account.withdraw( amount ).`
- ❑ Perhaps better to add service at AccountManager level:

# Java

```
public void withdraw( final Account account, final double amount ) {
    if ((conditions are right)) {
        account.withdraw( amount );
    }
}
```



## Comparison

**Stability** The parallel array implementation is “unstable:”

- If we need addresses we must change the constructor.

**Security** The parallel array implementation is not safe:

- ❑ Parallel array clients need access to all arrays:
  - ❑ `withdraw( owners, balances, nr, amount );`
  - ❑ This gives the client access to all account details.
  - ❑ They can even modify the array.
  - ❑ It violates encapsulation.
- ❑ Direct access for Account clients:
  - ❑ `account.withdraw( amount );`
- ❑ Perhaps better to add service at AccountManager level:

# Java

```
public void withdraw( final Account account, final double amount ) {
    if ((conditions are right)) {
        account.withdraw( amount );
    }
}
```

## Comparison

**Stability** The parallel array implementation is “unstable:”

- If we need addresses we must change the constructor.

**Security** The parallel array implementation is not safe:

- ❑ Parallel array clients need access to all arrays:
  - ❑ `withdraw( owners, balances, nr, amount );`
  - ❑ This gives the client access to all account details.
  - ❑ They can even modify the array.
  - ❑ It violates encapsulation.
- ❑ Direct access for Account clients:
  - ❑ `account.withdraw( amount );`
- ❑ Perhaps better to add service at AccountManager level:

# Java

```
public void withdraw( final Account account, final double amount ) {
    if ((conditions are right)) {
        account.withdraw( amount );
    }
}
```

## Comparison

**Stability** The parallel array implementation is “unstable:”

- If we need addresses we must change the constructor.

**Security** The parallel array implementation is not safe:

- Parallel array clients need access to all arrays:
  - `withdraw( owners, balances, nr, amount );`
  - This gives the client access to all account details.
  - They can even modify the array.
  - It violates encapsulation.
- Direct access for Account clients:
  - `account.withdraw( amount ).`
- Perhaps better to add service at AccountManager level:

# Java

```
public void withdraw( final Account account, final double amount ) {
    if ((conditions are right)) {
        account.withdraw( amount );
    }
}
```

## Comparison

**Stability** The parallel array implementation is “unstable:”

- If we need addresses we must change the constructor.

**Security** The parallel array implementation is not safe:

- ❑ Parallel array clients need access to all arrays:
  - ❑ `withdraw( owners, balances, nr, amount );`
  - ❑ This gives the client access to all account details.
  - ❑ They can even modify the array.
  - ❑ It violates encapsulation.
- ❑ Direct access for Account clients:
  - ❑ `account.withdraw( amount ).`

- Perhaps better to add service at AccountManager level:

# Java

```
public void withdraw( final Account account, final double amount ) {
    if ((conditions are right)) {
        account.withdraw( amount );
    }
}
```

# Questions Anybody?

# For Next Monday

- Study Chapters 2 and 3.

Introduction to Java

M. R. C. van Dongen

Lab Sessions

Objects and Classes

Variables

Types Matter

Working with Objects

Encapsulation

Arrays

Question Time

For Next Friday

Acknowledgements


References

About this Document

# Acknowledgements

- This lecture is partially based on
  - [Sierra, and Bates 2004].
  - [Horstmann 2013].

## Bibliography I





# About this Document

- This document was created with pdf $\text{\LaTeX}$ atex.
- The  $\text{\LaTeX}$  document class is beamer.