

Software Development (cs2500)

Lecture 18: Class Design

M. R. C. van Dongen

November 1, 2013

Objectives

- Study methods and why they are useful.
- Learn the *pass-by-value rule*.
 - Describes how methods should be evaluated.
- Simulate the evaluation of methods.
- Write classes by carrying out a case study.

Why do we Need Methods?

- Methods are interfaces for parameterised computations.
- Method calls provide reusable computations.
- Building blocks of complex computations.
- Calls are the only mechanism to change private variables.
- Methods encapsulate computations.
 - Classes encapsulate method definitions.
 - This lets you hide the implementation.

Parameter Taxonomy

Formal parameter: A parameter in the method's definition.

Java

```
<visibility modifier> <static option>
<type> <method name>( <type>1 <formal parameter>1,
                        ...,
                        <type>n <formal parameter>n ) {
    <body>
}
```

Actual parameter: A parameter in the method calls.

Java

```
<reference>.<method name>( <actual parameter>1,
                           ...,
                           <actual parameter>n );
```

Actual Parameters

Java

```
System.out.println( "The answer is " + 42 + "." );
```

Actual Parameters are Expressions

Java

```
System.out.println( "The answer is " + 42 + "." );
```

Example

Java

```
public static int f( int a, int b ) {  
    return a + b;  
}
```

```
public static void g( int c ) {  
    int a = f( 1, 2 + c );  
    int d = f( 1 + 3, a );  
}
```

Example: Formal Parameters

Java

```
public static int f( int a, int b ) {  
    return a + b;  
}
```

```
public static void g( int c ) {  
    int a = f( 1, 2 + c );  
    int d = f( 1 + 3, a );  
}
```


Example: Actual Parameters

Java

```
public static int f( int a, int b ) {  
    return a + b;  
}
```

```
public static void g( int c ) {  
    int a = f( 1, 2 + c );  
    int d = f( 1 + 3, a );  
}
```

The Pass-by-Value Mechanism

Carrying out a Call with n Parameters

Introduction

Why Methods?

Pass-by-Value

Parameter Taxonomy

The Mechanism

Examples

Playing with Toys

For Monday

About this Document

- 1 Create a fresh variable for each parameter.
- 2 For i from 1 to n (from left to right):
 - 1 Evaluate the i th actual parameter.
 - 2 Assign the result of the i th evaluation to the i th fresh variable.
- 3 Carry out statements in the method body.
- 4 Return result (if any).
- 5 Remove fresh variables.

The Pass-by-Value Mechanism

Carrying out a Call with n Parameters

Introduction

Why Methods?

Pass-by-Value

Parameter Taxonomy

The Mechanism

Examples

Playing with Toys

For Monday

About this Document

- 1 Create a fresh variable for each parameter.
- 2 For i from 1 to n (from left to right):
 - 1 Evaluate the i th actual parameter.
 - 2 Assign the result of the i th evaluation to the i th fresh variable.
- 3 Carry out statements in the method body.
- 4 Return result (if any).
- 5 Remove fresh variables.

The Pass-by-Value Mechanism

Carrying out a Call with n Parameters

- 1 Create a fresh variable for each parameter.
- 2 For i from 1 to n (from left to right):
 - 1 Evaluate the i th actual parameter.
 - 2 Assign the result of the i th evaluation to the i th fresh variable.
- 3 Carry out statements in the method body.
- 4 Return result (if any).
- 5 Remove fresh variables.

The Pass-by-Value Mechanism

Carrying out a Call with n Parameters

Software Development

M. R. C. van Dongen

Introduction

Why Methods?

Pass-by-Value

Parameter Taxonomy

The Mechanism

Examples

Playing with Toys

For Monday

About this Document

- 1 Create a fresh variable for each parameter.
- 2 For i from 1 to n (from left to right):
 - 1 Evaluate the i th actual parameter.
 - 2 Assign the result of the i th evaluation to the i th fresh variable.
- 3 Carry out statements in the method body.
- 4 Return result (if any).
- 5 Remove fresh variables.

The Pass-by-Value Mechanism

Carrying out a Call with n Parameters

- 1 Create a fresh variable for each parameter.
- 2 For i from 1 to n (from left to right):
 - 1 Evaluate the i th actual parameter.
 - 2 Assign the result of the i th evaluation to the i th fresh variable.
- 3 Carry out statements in the method body.
- 4 Return result (if any).
- 5 Remove fresh variables.

The Pass-by-Value Mechanism

Carrying out a Call with n Parameters

- 1 Create a fresh variable for each parameter.
- 2 For i from 1 to n (from left to right):
 - 1 Evaluate the i th actual parameter.
 - 2 Assign the result of the i th evaluation to the i th fresh variable.
- 3 Carry out statements in the method body.
- 4 Return result (if any).
- 5 Remove fresh variables.

The Pass-by-Value Mechanism

Carrying out a Call with n Parameters

Introduction

Why Methods?

Pass-by-Value

Parameter Taxonomy

The Mechanism

Examples

Playing with Toys

For Monday

About this Document

- 1 Create a fresh variable for each parameter.
- 2 For i from 1 to n (from left to right):
 - 1 Evaluate the i th actual parameter.
 - 2 Assign the result of the i th evaluation to the i th fresh variable.
- 3 Carry out statements in the method body.
- 4 Return result (if any).
- 5 Remove fresh variables.

Storing the Value of a Temporary Variable

The Stack


- Actual parameter values are stored on the *stack*.
 - When method is called, variables are created on top of stack.
 - When method returns this scratch space is released.
- The stack is also used to represent local variables in blocks.
 - When block is entered, variable are created on top of the stack.
 - When control leaves the block this scratch space is released.

Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```



stack


Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```

`g.b`




stack

Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```




Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```




Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```




Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```




Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```




Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```




Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```




Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```




Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```



Example #1

Calling g(5)

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```

f.b	3
f.a	2
g.c	3
g.a	1
g.b	5

stack

Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```

f.b	3
f.a	2
g.c	3
g.a	1
g.b	5

stack

Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```

f.b	3
f.a	4
g.c	3
g.a	1
g.b	5

stack

Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```

f.b	3
f.a	4
g.c	3
g.a	1
g.b	5


stack

Example #1

Calling `g(5)`

Java

```
public static int f( int a ) {  
    int b = a + 1;  
    a = a + 2;  
    return a * b;  
}  
  
public static void g( int b ) {  
    int a = 1;  
    int c = 3;  
  
    c = f( a + a );  
    System.out.println( a + " " + c );  
    // Prints: 1 12  
}
```



Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




stack

Example #2

Initial Call is `fib(2)`

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```



Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```



Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```




Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```



Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```



Example #2

Initial Call is fib(2)

Java

```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```



Example #2

Initial Call is fib(2)

Java


```
public static int fib( int n ) {  
    if ( n <= 1 ) {  
        return 1;  
    } else {  
        int f1 = fib( n - 1 );  
        int f2 = fib( n - 2 );  
        return f1 + f2;  
    }  
}
```



Example #3:

Java


```
public class Example {  
    private int a;  
  
    public Example( ) {  
        a = 1;  
    }  
  
    public static void main( String[] args ) {  
        Example example = new Example( );  
        example.g( );  
    }  
  
    public int f( int b ) {  
        b = 2;  
        a = 2;  
        return a + b;  
    }  
  
    public void g( ) {  
        int c = f( a );  
        System.out.println( a + " " + c );  
    }  
}
```



Example #3: The JVM Creates an Object

Java

```
public class Example {  
    private int a;  
  
    public Example( ) {  
        a = 1;  
    }  
  
    public static void main( String[] args ) {  
        Example example = new Example( );  
        example.g( );  
    }  
  
    public int f( int b ) {  
        b = 2;  
        a = 2;  
        return a + b;  
    }  
  
    public void g( ) {  
        int c = f( a );  
        System.out.println( a + " " + c );  
    }  
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }


    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
    }
}
```



Example #3:

Java

```
public class Example {  
    private int a;  
  
    public Example( ) {  
        a = 1;  
    }  
  
    public static void main( String[] args ) {  
        Example example = new Example( );  
        example.g( );  
    }  
  
    public int f( int b ) {  
        b = 2;  
        a = 2;  
        return a + b;  
    }  
  
    public void g( ) {  
        int c = f( a );  
        System.out.println( a + " " + c );  
    }  
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }


    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
    }
}
```



Example #3:

Java


```
public class Example {  
    private int a;  
  
    public Example( ) {  
        a = 1;  
    }  
  
    public static void main( String[] args ) {  
        Example example = new Example( );  
        example.g( );  
    }  
  
    public int f( int b ) {  
        b = 2;  
        a = 2;  
        return a + b;  
    }  
  
    public void g( ) {  
        int c = f( a );  
        System.out.println( a + " " + c );  
    }  
}
```



Example #3:

Java


```
public class Example {  
    private int a;  
  
    public Example( ) {  
        a = 1;  
    }  
  
    public static void main( String[] args ) {  
        Example example = new Example( );  
        example.g( );  
    }  
  
    public int f( int b ) {  
        b = 2;  
        a = 2;  
        return a + b;  
    }  
  
    public void g( ) {  
        int c = f( a );  
        System.out.println( a + " " + c );  
    }  
}
```



Example #3:

Java

```
public class Example {  
    private int a;  
  
    public Example( ) {  
        a = 1;  
    }  
  
    public static void main( String[] args ) {  
        Example example = new Example( );  
        example.g( );  
    }  
  
    public int f( int b ) {  
        b = 2;  
        a = 2;  
        return a + b;  
    }  
  
    public void g( ) {  
        int c = f( a );  
        System.out.println( a + " " + c );  
    }  
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }

    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
    }
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }

    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
    }
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }

    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
    }
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }

    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
    }
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }

    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
    }
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }

    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
    }
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }

    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
    }
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }

    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
    }
}
```



Example #3:

Java


```
public class Example {
    private int a;

    public Example( ) {
        a = 1;
    }

    public static void main( String[] args ) {
        Example example = new Example( );
        example.g( );
    }

    public int f( int b ) {
        b = 2;
        a = 2;
        return a + b;
    }

    public void g( ) {
        int c = f( a );
        System.out.println( a + " " + c );
        // Prints: 2 4.
    }
}
```



Class Design: How To?

- When we design an application, how do we choose the classes?
- Once we've decided on the classes,
 - How do we choose the attributes, and
 - How do we choose the methods?
- The answer is in the problem specification.

- To find classes: look for actors in the spec.
 - This works, because the actors correspond to the objects,
 - And each object is an instance of its class.
 - We may implement the object in a class named after the actor:
 - Toy and Toy;
 - Writer and Writer;
 - Dog and Dog;
 - ...
- The actors do things (verbs): these are the methods.
- The actors own things, these are the attributes.

- To find classes: look for actors in the spec.
 - This works, because the actors correspond to the objects,
 - And each object is an instance of its class.
 - We may implement the object in a class named after the actor:
 - Toy and Toy;
 - Writer and Writer;
 - Dog and Dog;
 - ...
- The actors **do** things (**verbs**): these are the **methods**.
- The actors own things, these are the attributes.

Clues

- To find classes: look for actors in the spec.
 - This works, because the actors correspond to the objects,
 - And each object is an instance of its class.
 - We may implement the object in a class named after the actor:
 - Toy and Toy;
 - Writer and Writer;
 - Dog and Dog;
 - ...
- The actors do things (verbs): these are the methods.
- The actors **own** things, these are the **attributes**.

Playing with Toys

- There are hands and toys;
- Toys are either used or free;
- Initially toys are free;
- Hands cannot take used toys;
- Hands can only take free toys;
- If a toy is taken by a hand it becomes used;
- A hand can drop its toy;
- Dropping a toy makes it free;
- Each toy has its own name; and
- Each hand has its own type: left or right.

Playing with Toys

How do we find the Classes?

- There are hands and toys;
- Toys are either used or free;
- Initially toys are free;
- Hands cannot take used toys;
- Hands can only take free toys;
- If a toy is taken by a hand it becomes used;
- A hand can drop its toy;
- Dropping a toy makes it free;
- Each toy has its own name; and
- Each hand has its own type: left or right.

Playing with Toys

How do we find the Classes? Look for Actors.

- ❑ There are hands and toys;
- ❑ Toys are either used or free;
- ❑ Initially toys are free;
- ❑ Hands cannot take used toys;
- ❑ Hands can only take free toys;
- ❑ If a toy is taken by a hand it becomes used;
- ❑ A hand can drop its toy;
- ❑ Dropping a toy makes it free;
- ❑ Each toy has its own name; and
- ❑ Each hand has its own type: left or right.

Playing with Toys

How do we find the Actors?

- There are hands and toys;
- Toys are either used or free;
- Initially toys are free;
- Hands cannot take used toys;
- Hands can only take free toys;
- If a toy is taken by a hand it becomes used;
- A hand can drop its toy;
- Dropping a toy makes it free;
- Each toy has its own name; and
- Each hand has its own type: left or right.

Software Development

M. R. C. van Dongen

Introduction

Why Methods?

Pass-by-Value

Playing with Toys

The Toy Class

The Hand Class

The main Method

For Monday

About this Document

Playing with Toys

How do we find the Actors? **Look for Nouns!**

- ❑ There are hands and toys;
- ❑ Toys are either used or free;
- ❑ Initially toys are free;
- ❑ Hands cannot take used toys;
- ❑ Hands can only take free toys;
- ❑ If a toy is taken by a hand it becomes used;
- ❑ A hand can drop its toy;
- ❑ Dropping a toy makes it free;
- ❑ Each toy has its own name; and
- ❑ Each hand has its own type: left or right.

Playing with Toys

How do we find the Actors? Look for Nouns!

- There are **hands** and **toys**;
- **Toys** are either used or free;
- Initially **toys** are free;
- **Hands** cannot take used **toys**;
- **Hands** can only take free **toys**;
- If a **toy** is taken by a **hand** it becomes used;
- A **hand** can drop its **toy**;
- Dropping a **toy** makes it free;
- Each **toy** has its own **name**; and
- Each **hand** has its own **type**: left or right.

The Toy Class

How do we find the Attributes and Methods?

- Toys are either used or free;
- Initially toys are free; and
- Each toy has its own name.

Software Development

M. R. C. van Dongen

Introduction

Why Methods?

Pass-by-Value

Playing with Toys

The Toy Class

The Hand Class

The main Method

For Monday

About this Document

The Toy Class

How do we find the Attributes and Methods? Look for **Properties** and **(Active) Verbs**.

- ❑ Toys are either used or free;
- ❑ Initially toys are free; and
- ❑ Each toy has its own name.

The Toy Class

How do we find the Attributes and Methods? Look for **Properties** and **(Active) Verbs**.

- Toys are either **used** or **free**;
- Initially toys are **free**; and
- Each toy has **its own name**.

The Toy Class

How do we find the Attributes and Methods? Look for **Properties** and **(Active) Verbs**.

- ❑ Toys are either **used** or **free**;
- ❑ Initially toys are **free**; and
- ❑ Each toy has **its own name**.

Java

```
public class Toy {
    private final String name;
    private boolean used;

    public Toy( String name ) {
        this.name = name;
        used = false;
    }

    // Getter and setter methods omitted.

    @Override
    public String toString( ) {
        return "Toy[ name = " + name + " ]";
    }
}
```

The Toy Class

How do we find the Attributes and Methods? Look for **Properties** and **(Active) Verbs**.

- ❑ Toys are either **used** or **free**;
- ❑ Initially toys are **free**; and
- ❑ Each toy has **its own name**.

Java

```
public class Toy {
    private final String name;
    private boolean used;

    public Toy( String name ) {
        this.name = name;
        used = false;
    }

    // Getter and setter methods omitted.

    @Override
    public String toString( ) {
        return "Toy[ name = " + name + " ]";
    }
}
```

The Hand Class

How do we find the Attributes and Methods?

- Hands cannot take used toys;
- Hands can only take free toys;
- If a toy is taken by a hand it becomes used;
- A hand can drop its toy;
- Dropping a toy makes it free; and
- Each hand has its own type.

Software Development

M. R. C. van Dongen

Introduction

Why Methods?

Pass-by-Value

Playing with Toys

The Toy Class

The Hand Class

The main Method

For Monday

About this Document

The Hand Class

How do we find the Attributes and Methods? Look for **Properties** and **(Active) Verbs**.

- Hands cannot take used toys;
- Hands can only take free toys;
- If a toy is taken by a hand it becomes used;
- A hand can drop its toy;
- Dropping a toy makes it free; and
- Each hand has its own type.

The Hand Class

How do we find the Attributes and Methods? Look for **Properties** and **(Active) Verbs**.

- ❑ Hands cannot **take** used toys;
- ❑ Hands can only **take** free toys;
- ❑ If a toy **is taken** by a hand it becomes used;
- ❑ A hand can **drop its toy**;
- ❑ **Dropping** a toy makes it free; and
- ❑ Each hand has **its own type**.

The Hand Class

Java

```
public class Hand {
    private final String type;
    private Toy toy;

    public Hand( String type ) {
        this.type = type;
        toy = null;
    }

    public void take( Toy toy ) { <to do> }
    public void drop( ) { <to do> }
    // Getters and setters omitted.

    @Override
    public String toString( ) {
        return "Hand[ type = " + type + ", toy = " + toy + " ]";
    }
}
```

The take() Method

Java

```
public void take( Toy toy ) {
```

```
}
```


The take() Method

Java

[illegible]

The take() Method

Java

```
public void take( Toy toy ) {  
    if (this.toy != null) {  
        // We cannot take a Toy if Hand is full.  
        System.err.println( "*** " + this + " is full." );  
        System.err.println( "*** Cannot take " + toy + "." );  
    }  
}
```

```
}
```

The take() Method

Java

```
public void take( Toy toy ) {  
    if (this.toy != null) {  
        // We cannot take a Toy if Hand is full.  
        System.err.println( "** " + this + " is full." );  
        System.err.println( "** Cannot take " + toy + "." );  
    }  
    // We cannot take a used Toy.  
  
}
```

The take() Method

Java

```
public void take( Toy toy ) {  
    if (this.toy != null) {  
        // We cannot take a Toy if Hand is full.  
        System.err.println( "** " + this + " is full." );  
        System.err.println( "** Cannot take " + toy + "." );  
    } else if (toy.getUsed( )) {  
        // We cannot take a used Toy.  
        System.err.println( "** " + toy + " is taken." );  
        System.err.println( "** Cannot take it." );  
    }  
  
}
```

The take() Method

Java

```
public void take( Toy toy ) {  
    if (this.toy != null) {  
        // We cannot take a Toy if Hand is full.  
        System.err.println( "** " + this + " is full." );  
        System.err.println( "** Cannot take " + toy + "." );  
    } else if (toy.getUsed( )) {  
        // We cannot take a used Toy.  
        System.err.println( "** " + toy + " is taken." );  
        System.err.println( "** Cannot take it." );  
    } else {  
        // Take toy.  
    }  
}
```

The take() Method

Java

```
public void take( Toy toy ) {  
    if (this.toy != null) {  
        // We cannot take a Toy if Hand is full.  
        System.err.println( "** " + this + " is full." );  
        System.err.println( "** Cannot take " + toy + "." );  
    } else if (toy.getUsed() ) {  
        // We cannot take a used Toy.  
        System.err.println( "** " + toy + " is taken." );  
        System.err.println( "** Cannot take it." );  
    } else {  
        // Take toy.  
        // Formally mark toy as used.  
        toy.setUsed( true );  
        // Make toy our current Toy.  
        this.toy = toy;  
    }  
}
```

The take() Method

Java

```
public void take( Toy toy ) {
    if (this.toy != null) {
        // We cannot take a Toy if Hand is full.
        System.err.println( "** " + this + " is full." );
        System.err.println( "** Cannot take " + toy + "." );
    } else if (toy.getUsed( )) {
        // We cannot take a used Toy.
        System.err.println( "** " + toy + " is taken." );
        System.err.println( "** Cannot take it." );
    } else {
        // Take toy.
        // Formally mark toy as used.
        toy.setUsed( true );
        // Make toy our current Toy.
        this.toy = toy;
    }
}
```

Introduction

Why Methods?

Pass-by-Value

Playing with Toys

The Toy Class

The Hand Class

The main Method

For Monday

About this Document

Java

```
public void drop( ) {
```

}

Introduction

Why Methods?

Pass-by-Value

Playing with Toys

The Toy Class

The Hand Class

The main Method

For Monday

About this Document

Java

```
public void drop( ) {  
  
    // We cannot drop a toy if we don't have one.  
  
  
  
  
  
  
  
  
  
}
```

The drop() Method

Java

```
public void drop( ) {  
    if (toy == null) {  
        // We cannot drop a toy if we don't have one.  
        System.err.println( "** " + this + " is empty." );  
        System.err.println( "** Cannot drop any toy." );  
    }  
  
}
```

The drop() Method

Java

```
public void drop( ) {  
    if (toy == null) {  
        // We cannot drop a toy if we don't have one.  
        System.err.println( "** " + this + " is empty." );  
        System.err.println( "** Cannot drop any toy." );  
    } else {  
        // Drop our current toy.  
    }  
}
```

The drop() Method

Java

```
public void drop( ) {  
    if (toy == null) {  
        // We cannot drop a toy if we don't have one.  
        System.err.println( "** " + this + " is empty." );  
        System.err.println( "** Cannot drop any toy." );  
    } else {  
        // Drop our current toy.  
        // Formally mark toy as free.  
        toy.setUsed( false );  
        // Make hand empty.  
        toy = null;  
    }  
}
```

The drop() Method

Java

```
public void drop( ) {  
    if (toy == null) {  
        // We cannot drop a toy if we don't have one.  
        System.err.println( "** " + this + " is empty." );  
        System.err.println( "** Cannot drop any toy." );  
    } else {  
        // Drop our current toy.  
        // Formally mark toy as free.  
        toy.setUsed( false );  
        // Make hand empty.  
        toy = null;  
    }  
}
```

The main

Java

```
public static void main( String[] args ) {  
    Hand left = new Hand( "left" );  
    Hand right = new Hand( "right" );  
    Toy game = new Toy( "computer game" );  
    Toy puzzle = new Toy( "puzzle" );  
  
    left.take( game );  
    right.take( game ); // Results in error message  
    right.take( puzzle );  
    left.drop( );  
    left.drop( );      // Results in error message  
}
```

The main: Magic Constants

Java

```
public static void main( String[] args ) {
    Hand left = new Hand( "left" );
    Hand right = new Hand( "right" );
    Toy game = new Toy( "computer game" );
    Toy puzzle = new Toy( "puzzle" );

    left.take( game );
    right.take( game ); // Results in error message
    right.take( puzzle );
    left.drop( );
    left.drop( );      // Results in error message
}
```

The main: Constant Class Attributes

Java

```
private static final String LEFT = "left";
private static final String RIGHT = "right";
private static final String GAME = "computer game";
private static final String PUZZLE = "puzzle";
```

```
public static void main( String[] args ) {
    Hand left = new Hand( LEFT );
    Hand right = new Hand( RIGHT );
    Toy game = new Toy( GAME );
    Toy puzzle = new Toy( PUZZLE );

    left.take( game );
    right.take( game ); // Results in error message
    right.take( puzzle );
    left.drop( );
    left.drop( );      // Results in error message
}
```


For Monday

- Study the notes.
- Study Sections 7.1 and 7.2.

About this Document

- This document was created with `pdflatex`.
- The \LaTeX document class is `beamer`.