

Problem J. Is-A? Has-A? Who Knowz-A?

Time limit 3000 ms
Mem limit 1048576 kB
OS Linux

Two familiar concepts in object oriented programming are the is-a and has-a relationships. Given two classes A and B, we say that A is-a B if A is a subclass of B; we say A has-a B if one of the fields of A is of type B. For example, we could imagine an object-oriented language (call it ICPC++) with code like that in Figure 1, where the class Day is-a Time, the class Appointment is both a DateBook and a Reminder, and class Appointment has-a Day.

```
class Day extends Time    class Appointment extends Datebook, Reminder
{
    ...
}
    {
        private Day date;
        ...
    }
```

Figure 1: Two ICPC++ classes.

These two relationships are transitive. For example if A is-a B and B is-a C then it follows that A is-a C. This holds as well if we change all the is-a's in the last sentence to has-a's. It also works with combinations of is-a's and has-a's: in the example above, Appointment has-a Time, since it has-a Day and Day is-a Time. Similarly, if class DateBook has-a Year then Appointment has-a Year, since Appointment is-a DateBook.

In this problem you will be given a set of is-a and has-a relationships and a set of queries of the form A is/has-a B. You must determine if each query is true or false.

Input:

Input starts with two integers n and m , ($1 \leq n, m \leq 10\,000$), where n specifies the number of given is-a and has-a relationships and m specifies the number of queries. The next n lines each contain one given relationship in the form $c_1 \ r \ c_2$ where c_1 and c_2 are single-word class names, and r is either the string "is-a" or "has-a". Following this are m queries, one per line, using the same format. There will be at most 500 distinct class names in the $n + m$ lines, and all class names in the last m lines will appear at least once in the initial n lines. All is-a and has-a relationships between the given classes can be deduced from the n given relationships. Is-a relationships can not be circular (apart from the trivial identity " x is-a x ").

Output

For each query, display the query number (starting at one) and whether the query is true or false.

Sample 1

Input	Output
5 5 Day is-a Time Appointment is-a Datebook Appointment is-a Reminder Appointment has-a Day Datebook has-a Year Day is-a Time Time is-a Day Appointment has-a Time Appointment has-a Year Day is-a Day	Query 1: true Query 2: false Query 3: true Query 4: true Query 5: true