Jarvis-to-Jarvis change promotion roadmap

Proposed delivery scope, 21 October 2026. Not implemented or enabled by this plan.

TriageNorth should turn an observed production issue into a reproducible, reviewed change. GitHub and GitLab connections belong in the standard user-bound connection framework. A workstation's Git login is not the portal's authorization. Existing external ticket synchronization does not establish permission to write repository content, open a pull request, merge, or deploy.

The upper swarm owns the operational incident and the target environment. Its Jarvis delegates a defined investigation to a lower development or test swarm's Jarvis. “Upper” and “lower” describe environment and promotion responsibility; they do not imply that all administrators or all child tasks inherit authority. An upper swarm with a fault must remain recoverable through a separate control plane and lower environment; it must not be required to repair itself first.

Intended operator experience

1. Open an incident and its sealed evidence packet. Select the connected repository, target environment, approved lower swarm, branch baseline and allowed operations. 2. Review a delegation card: original requester, affected resources, sanitized evidence, task deadline, token/cost ceiling and proposed acceptance checks. 3. Lower Jarvis creates a linked child ticket, reproduces the issue and proposes a branch and pull/merge request. Its workflow generates scripts and artifacts in the standard shared workspace. The agent receives the selected packet and explicitly granted tools; it does not browse the upper cluster freely. 4. See reproduction, patch, CI, security checks and lower-environment verification on one parent/child evidence chain. An unproven cause remains an unproven cause. 5. Upper Jarvis presents the exact commit, artifact digest, test results, deployment plan, rollback target and remaining uncertainty for the configured approval. 6. Promote that tested artifact after current permission and environment checks. Record health verification, rollback if required, and synchronize linked ticket status through the selected connector's established field mapping.

Proposed communication contract

Use a versioned delegation envelope over the registered swarm/node communication boundary, rather than treating a chat message as authority. Each request names: original user and tenant, parent/child ticket IDs, delegation ID, sender/receiver swarm IDs, workflow revision, repository/ref and environment scope, immutable input digests, allowed tool operations, deadline, maximum hops and resource budget. Only necessary evidence crosses the boundary; credentials remain with their owning environment. Tool execution rechecks current authorization.

Return a durable result envelope with the same delegation ID, exact commit and build digests, evidence/artifact references, test receipts, observations, proposed rollback and explicit success/failure/unknown state. Correlate parent and child activity without merging their identities. Durable inbox/outbox records and idempotency keys prevent duplicate work and promotion. Cancellation, expiry, revocation, stale source revisions and uncertain network outcomes hold the task for reconciliation. A child result never grants deployment authority.

Delivery sequence and dependencies

Item	Deliverable	Done when
H1 — Git connection	User-bound GitHub/GitLab repository selection and operation grants; branch/PR/MR links in the incident	Original-user read/write scopes verified; revoked or wrong-repository access refused; no reliance on operator CLI credentials
H2 — Delegation	Registered Jarvis endpoints, versioned envelopes, linked tickets, durable bounded delivery	Two isolated swarms exchange a task/result; duplicates, expiry, cancellation, wrong tenant and lost acknowledgements are exercised
H3 — Lower validation	Reproduction scenario, workspace-generated patch/scripts, CI and test-environment verification	A seeded lab incident reproduces, fails before the patch and passes after it; all receipts name the same commit/artifact
H4 — Promotion	Exact-change approval, deployment receipt, health check and rollback	Red CI, changed patch, withdrawn permission or stale approval prevents deployment; rollback restores the previous known artifact
H5 — Recovery	Independent recovery entry point and bounded hierarchy	Upper Jarvis outage does not erase incident/delegation state; a separately authorized recovery workflow can restore it; hop/budget limits terminate cycles

Dependencies: standard connections/vault and granular grants; registered swarm identities and enrollment; canonical workflow/tickets; shared workspace artifacts; CI/build attestations; environment-specific deploy/rollback adapters; durable transport and audit receipts. Protocol and authority gaps belong in reusable platform services. TriageNorth owns incident policy, evidence presentation, repository/environment selection and the promotion experience.

For the hackathon, demonstrate two isolated lab environments and one reviewed promotion. Do not describe a single local swarm, a mocked exchange, ticket sync, or a successful lower test as a deployed hierarchy. Production auto-remediation requires an explicit policy for that action; otherwise the promotion gate remains human approval. No new remote writes or cloud provisioning occur from this roadmap.

Response-policy extension

[ADR0031](adr/0031-response-paths-and-verification-branch.md) and the [four-screen response design](RESPONSE-PATH-DESIGN.md) add paired mitigation/permanent repair, emergency runtime patches, expedited Git hotfixes and a bounded verification branch. These are proposed paths, not deployed capabilities.