Every incident deserves its evidence.

TriageNorth is an intelligent operations experience for mixed infrastructure.

Turn a flood of signals into a small set of explainable incidents—with the context needed to act.

The product

Named sources, noise reduction, dependency context and controlled response.

The foundation

An independently installed OSHAL container supplies identity, connections, tickets, workflows and workspaces.

The problem is the gap between alert and action.

An isolated alarm rarely explains the system that failed.

Too much noise

Repeated symptoms compete with genuinely new issues.

Vanishing context

Pods disappear, logs roll and the original failure window is lost.

Unclear authority

Evidence, generated proposals and permission to execute need distinct boundaries.

One path from infrastructure to an accountable decision.

The application reuses shared platform controls rather than holding broad cluster credentials.

Sources

Hosts / cloud / containers

OTLP / CloudWatch

Detection

Stored queries

Suppress repeated symptoms

Context

Dependency paths

Three telemetry banks

Evidence

Bounded durable packet

Source / time / hashes

Next boundary: canonical investigation workflow → generated deliverables → exact-action approval → recovery verification.

The replay demonstrates filtering through persistent evidence. Full unattended remediation is not claimed.

A failure crosses the datacenter boundary.

Synthetic scenario, actual native Kubernetes services: datacenter host → cloud database → network path.

Occurrences	Rule matches	Symptoms	Incident groups
100	40	4	2

60 routine occurrences filtered. 36 repeated symptoms suppressed. 4 persistent context packets.

An independent disk-pressure host stays in a separate incident group.

Keep the first fifteen minutes available.

A → B → C → A, with protected context before safe reuse.

A / active

Bounded byte and record budget
Grow within an approved ceiling
Keep original provenance

B / retained

Bounded byte and record budget
Grow within an approved ceiling
Keep original provenance

C / retained

Bounded byte and record budget
Grow within an approved ceiling
Keep original provenance

Never erase a bank whose newest receipt is younger than 900 seconds. At the ceiling, retry the whole batch. Pin incident evidence outside the ring.

Three logical data banks reuse the application store; physical database/PVC autoscaling is separate work.

Real data keeps the claims honest.

Recorded BGL sample: 2,000 HPC log lines; labels withheld from the severity-only query.

Precision

35.5%
260 false positives

Recall

100.0%
0 labeled alerts missed

Reduction

403 matches
74 repeated occurrences suppressed

A severity label alone is a poor incident decision. This measured baseline gives us a target for better rules, temporal context and anomaly evaluation.

Loghub research samples remain outside the product bundle. This is not a trained anomaly detector or root-cause accuracy score.

A demo you can inspect, not just watch.

Each stage shows its sources, actual decisions and retained evidence.

Scenario lab

Run the host/cloud scenario and inspect the result.

Live context

Inspect all three bank generations and their budgets.

Data & topology

Trace filter decisions, symptom keys and dependency paths.

Login and grants belong to the signed-in user. The investigation receives a preprocessed packet, not unrestricted infrastructure access.

Explore the estate. Follow the real work.

Real monitoring from a synthetic workload; three analysis phases await human report approval.

Six graph queries

Perspective depth + orbit/pan/zoom.

Recorded dependencies, impact and placement.

Keyboard selection and phone layout.

Inspect each decision

Named investigate / review / revise bots.

Exact admitted packet and prior reports.

Evidence citations + proposed diagnostics.

Current position in graphical Studio.

Review work and cost

Three shared reports, byte/hash checked.

39,166 measured tokens.

$0.050048 reference estimate.

$0 recorded spend; reference is not billed cost.

Reports and observed correlation do not establish infrastructure recovery. Generated executable remediation and external status synchronization remain delivery gates.

Connect accountable work to an existing issue.

Development-installed services; full release certification and live Jira account validation remain open.

Review an exact mapping

Owned workflow revision + phase.

Personal named account.

Explicit Jira / GitLab / ServiceNow state mapping.

Confirm one update

Reserve before dispatch.

Use shared native connector Actions.

Read state before and after.

Hold uncertain responses.

Notify through shared services

SMS / brief phone / Telegram.

Three approved tests accepted once.

All test topics muted.

Operator confirmed the call.

SMS blocked: Twilio30034.

Telegram receipt unverified.

Automatic two-way sync, verified webhooks and infrastructure recovery remain delivery gates. The acceptance runner never repeats an attempted test send.

The next three weeks focus on function and evidence.

Build on the demonstrated source-to-context path.

Evaluate

Replay recorded host and cloud metrics.

Calibrate anomalies on time-separated data.

Keep failures and false alerts visible.

Complete response

Continuous delegated producers.

Automatic evidence-to-workflow dispatch.

Generated scripts, exact approvals and failed-recovery checks.

Expand environments

External ticket synchronization.

Read-only AWS / Azure / GCP discovery.

Educational cloud environments after the product path is ready.