

品名 规格 数量 单位 备注

2026 Edition




Table of Contents

I. In-situ Electrochemical Equipment Series

In-situ Raman Spectroelectrochemical Cell	
(Basic Type) Model: C031-1	Page 4
In-situ Raman Spectroelectrochemical Cell	
(2H Removable Membrane Type) Model: C031-2	Page 5
In-situ Raman Spectroelectrochemical Cell	
(3H Gas Diffusion Type) Model: C031-3	Page 6
In-situ Raman Spectroelectrochemical Cell	
(3H Gas Diffusion Type) Model: C031-3S	Page 7
In-situ Raman Spectroelectrochemical Cell	
(Gas Diffusion - Serpentine Flow Channel Type) Model: C031-S	Page 8
In-situ Raman Spectroelectrochemical Cell	
(Disc Electrode Type) Model: C031-4	Page 9

In-situ Observation Cell for Powder Samples

Model: C031-6	Page 9
In-situ IR Internal & External Reflection Electrochemical Cell	Page 10
In-situ IR High-Pressure External Reflection Electrochemical Cell	Page 11
In-situ IR Transmission Electrochemical Cell & Price Summary Sheet	Page 12
In-situ XRD Spectroelectrochemical Cell	Page 13
In-situ X-ray Absorption Reaction Cell	Page 14 & 15
In-situ Sum Frequency Generation Spectroelectrochemical Cell	Page 16
Mass Spectrometry - In-situ IR Coupling Cell	Page 16
In-situ UV Electrochemical Cell	Page 17
In-situ Mass Spectrometry Electrochemical Cell	Page 18
Multifunctional In-situ Test Electrochemical Cell	Page 19

II. Lithium Battery In-situ Equipment Series

In-situ Raman/XRD Two-Electrode Battery Test Cell	Page 20
In-situ Raman/XRD Three-Electrode Battery Test Cell	Page 21
In-situ Raman Pressure Two/Three-Electrode Battery Test Cell	Page 22
In-situ IR Lithium Battery Test Cell	Page 23
In-situ Battery Simulation Observation Cell (Lithium Single Crystal)	Page 24
Solid-State Battery Test Fixture	Page 25

III. MEA Membrane Electrode Assembly Electrolysis Cell Series

Bipolar Plate Membrane Electrode Electrolysis Cell (Metal Version)	Page 26
Bipolar Plate Membrane Electrode Electrolysis Cell (Graphite Version)	Page 26
Visualized Membrane Electrode Electrolysis Cell	Page 27 & 28
Thermostatic Water Bath Equipped Membrane Electrode Electrolysis Cell	Page 29
In-situ Raman Membrane Electrode Electrolysis Cell	Page 30
Removable Flow Channel Membrane Electrode Electrolysis Cell	Page 31
Electrolysis Cell Stack Electrochemical Cell	Page 32 & 33
High-Current Solution for Membrane Electrode Electrolysis Cell	Page 34
Complete Equipment Solution for Membrane Electrode Electrolysis Cell	Page 34
Price Summary Sheet for Membrane Electrode Electrolysis Cells & Complete Solutions	Page 35

IV. Gas Diffusion Cell Series

Entry-level Gas Diffusion Electrolysis Cell Model: 101014	Page 36
Basic Gas Diffusion Electrolysis Cell Model: CP10 & CP20	Page 37
Advanced Gas Diffusion Electrolysis Cell Model: 101016、17-1、17-1.2	Page 38 & 39
Premium Gas Diffusion Electrolysis Cell Model: 101018	Page 40、41、42 & 43
Ultimate Gas Diffusion Electrolysis Cell Model: 101019	Page 44
Complete Equipment Solution for Gas Diffusion Systems	Page 45
Price Summary Sheet for Gas Diffusion Electrolysis Cells & Supporting Systems	Page 46
Solid Electrolyte Electrochemical Cell & Price List	Page 47 & 48
Single-Chamber & Dual-Chamber Gas Diffusion Electrolysis Cell	Page 49
Gas Diffusion Photoelectrochemical Cell	Page 50
Membrane-Replaceable Gas Diffusion Photoelectrochemical Flow Cell ...	Page 51

V. Pressure Cell High-Pressure Electrochemical Cell Series

Single-Chamber High-Pressure Electrochemical Cell	Page 52
Dual-Chamber High-Pressure Electrochemical Cell (Internally Replaceable Membrane)	Page 53
Dual-Chamber High-Pressure Electrochemical Cell (Externally Replaceable Membrane)	Page 54
High-Pressure Flow Test Cell with Gas Diffusion Function	Page 55
Photocatalytic High-Pressure Electrochemical Cell	Page 56

VI. Special-Function Cell Series

Swagelok-type Battery Test Cell	Page 57 & 58
Metal-Air Battery Test Cell	Page 59
Membrane Conductivity Test Cell	Page 60
Capacitive Deionization Device	Page 61
All-Vanadium Flow Battery Test Cell	Page 62
Electrochemiluminescence Electrolysis Cell	Page 63

VII. Instrument & Equipment Series

Dual-position Magnetic Stirrer	Page 64
Peristaltic Pump	Page 64
Gas-Liquid Mixing Pump	Page 65
High-Pressure Constant Flow Pump	Page 65
Membrane Electrode Heating & Temperature Controller	Page 66
Mass Flow Meter & Controller	Page 66
Rotating Disk / Ring-Disk Electrode Assembly	Page 67 & 68
Electrochemical Workstation	Page 69
Current Amplifier for Electrochemical Workstation	Page 70
In-situ Differential Electrochemical Mass Spectrometry	Page 71
Supporting Reaction Cells for Various Electrochemical Mass Spectrometers	Page 71、72 & 73
Foam Metal Level Regulator	Page 74
Custom Assembly of Various Flow Reaction Equipment Platforms	Page 74

In-situ Electrochemical Equipment Series

In-situ Raman Spectroelectrochemical Cell (Basic Model)

Model No.: C031-1

This in-situ electrochemical cell is designed to investigate the in-situ spectral and morphological evolution of electrode materials during electrochemical experiments. The working electrode (WE) is placed directly beneath the viewing window, allowing optical instruments to observe the working electrode through the quartz window.

The cell body is made of PEEK material. It supports rapid assembly and disassembly for easy cleaning.

It is applicable to in-situ electrochemical measurements under flow systems, and electrolyte can also be conveniently injected to fill the cell chamber.

Optical window diameter: 37 mm

Distance between working electrode and optical window: less than 6 mm

Default working electrode area: 1 cm²; customized dimensions are available upon request.

The working electrode is a sheet-type electrode (gold sheet, platinum sheet, glassy carbon sheet, ITO, FTO, carbon paper, etc.), which needs to be purchased separately.

Standard accessories include reference electrode (AgCl or Ag electrode) and counter electrode (platinum wire electrode).

€ : 1600



In-situ Electrochemical Equipment Series

In-situ Raman Spectroelectrochemical Cell (2H Removable Membrane Type)

Model: C031-2

This in-situ electrochemical cell is designed to characterize the in-situ spectral and morphological changes of electrode materials during electrochemical tests. The working electrode (WE) is placed directly underneath the viewing window, enabling optical instruments to observe the working electrode through the quartz window.

The cell main body is constructed from PEEK, featuring quick assembly and disassembly for effortless cleaning.

Its two compartments are sealed and fastened with screws to facilitate diaphragm replacement. The cathode and anode chambers are separated by an ion-exchange membrane (to be prepared by the user), which effectively eliminates interference from the anode to the cathode.

The reference electrode is placed in the same compartment as the working electrode to minimize IR drop.

It is compatible with in-situ electrochemical testing under flow conditions; electrolyte can also be easily injected into the cell.

Distance between working electrode and optical window: < 6 mm

Optical window diameter: 37 mm


Standard working electrode area: 1 cm²; customized sizes are available on demand

Compatible with sheet working electrodes (gold foil, platinum foil, glassy carbon plate, ITO, FTO, carbon paper, etc.)

Standard configuration includes an AgCl reference electrode and imported graphite rod counter electrode.

Free-of-charge replacement options are available: Ag reference electrode or platinum wire counter electrode.

€ : 2300



In-situ Raman Spectroelectrochemical Cell (3H Gas Diffusion Type)

Model No.: C031-3

This in-situ electrochemical cell is designed to investigate the in-situ spectral and morphological evolution of electrode materials during electrochemical experiments. The working electrode (WE) is placed directly below the viewing window, allowing optical instruments to observe the working electrode through the quartz window.

The two compartments of the cell are sealed and connected with screws for convenient diaphragm replacement. The cathode and anode chambers are separated by an ion-exchange membrane (to be supplied by the user), which effectively avoids interference of the anode on the cathode.

A gas channel is added at the bottom layer of the cathode chamber, endowing the cell with gas diffusion capability.

It supports in-situ electrochemical measurements for flow systems, and electrolyte can also be conveniently injected to fill the cell cavity.

Distance between working electrode and optical window: < 6 mm

Optical window diameter: 37 mm


Default working electrode area: 1 cm²; customized specifications are available upon request.

A gas diffusion electrode is normally adopted as the working electrode to match the gas channel. Sheet materials including metal foil, glassy carbon plate, ITO and FTO can also be used as working electrodes. Working electrode materials need to be purchased separately.

Standard accessories: AgCl reference electrode and imported graphite rod counter electrode.

Free-of-charge alternative options: Ag reference electrode or platinum wire counter electrode.

€ : 3000



Committed to the R&D and manufacturing of electrochemical equipment.

In-situ Electrochemical Equipment Series

In-situ Raman Spectroelectrochemical Cell (Gas Diffusion Type with Serpentine Flow Channel)

Model: C031-3S

This model is an upgraded version of the C031-3 in-situ Raman electrochemical cell. Its gas chamber adopts a serpentine flow channel design, which extends the contact duration between gas and catalyst, enabling gas to participate in experimental reactions more efficiently.

Distance between working electrode and optical window: < 6 mm

Optical window diameter: 37 mm


Standard working electrode area: 1 cm²; customized sizes are available on demand

A gas diffusion electrode is generally used as the working electrode to match the gas flow channel. Sheet materials such as metal foil, glassy carbon plate, ITO and FTO are also acceptable. Working electrode materials need to be purchased separately.

Standard configuration includes AgCl reference electrode and imported graphite rod counter electrode.

These can be replaced with Ag reference electrode or platinum counter electrode at no extra cost.

€ : 3000



In-situ Electrochemical Equipment Series

In-situ Raman Spectroelectrochemical Cell (Gas Diffusion Serpentine Flow Channel Type)

Model No.: C031-S

This in-situ electrochemical cell is designed to characterize the in-situ spectral and morphological changes of electrode materials during electrochemical experiments. The working electrode (WE) is placed directly beneath the viewing window, so optical instruments can observe the working electrode through the quartz window.

The cell consists of three independent chambers: gas chamber, working electrode chamber, and counter electrode chamber. The three compartments are separated respectively by a gas diffusion electrode (to be prepared by the user) and an ion-exchange membrane (to be prepared by the user). It is specially developed for in-situ Raman testing on gas diffusion electrodes.

The gas chamber adopts a serpentine flow field, which greatly prolongs the contact time between gas and the gas diffusion electrode compared with Model C031-3, enabling more sufficient catalytic reactions.

For Model C031-S Raman spectroelectrochemical cell, the working electrode is a user-supplied gas diffusion electrode with a fixed effective area of 1 cm². It is equipped with an imported flat sapphire window with a light transmittance above 95%. The flat window has a diameter of 45 mm, and the distance between the window surface and the working electrode is less than 3 mm. This optimized design makes the cell compatible with most commercial Raman spectrometers. The reference electrode (standard AgCl or Ag electrode) shares the same compartment with the working electrode to effectively reduce IR drop.

~~Cell body material:~~ Polyetheretherketone (PEEK)


Window material: Sapphire; Window diameter: 45 mm

Normally, a gas diffusion electrode is used as the working electrode to match the gas flow channel. Sheet materials such as metal foil, glassy carbon plate, ITO and FTO are also applicable. Working electrode materials need to be purchased separately.

Standard configuration includes AgCl reference electrode and imported graphite rod counter electrode.

They can be replaced with Ag reference electrode or platinum wire counter electrode at no extra cost.

€ : 3000



In-situ Electrochemical Equipment Series

In-situ Raman Spectroelectrochemical Cell (Disc Electrode Type)

Model No.: C031-4

This in-situ electrochemical cell is designed to investigate the in-situ spectral and morphological evolution of electrode materials during electrochemical experiments. The working electrode (WE) is placed directly below the viewing window, allowing optical instruments to observe the working electrode through the quartz window. The cell body is made of PEEK and high-purity titanium. It supports rapid assembly and disassembly for easy cleaning.



It is applicable to in-situ electrochemical testing under flow systems; electrolyte can also be conveniently injected to fill the cell chamber.

Optical window diameter: 25 mm

Distance between working electrode and optical window: less than 3 mm

The standard working electrode is a 5 mm glassy carbon disc electrode. It can be replaced with disc electrodes such as gold disc, platinum disc and silver disc upon request (price difference will be charged if applicable).

Standard accessories include reference electrode (AgCl or Ag electrode) and counter electrode (platinum wire electrode).



€ : 1600

In-situ Observation Cell for Powder Samples

Model No.: C031-6

€ : 400



Committed to the R&D and manufacturing of electrochemical equipment.

In-situ Electrochemical Equipment Series

H-type Removable Membrane In-situ IR Test Cell

Model No.:

IFA-1 (Internal Reflection Mode)

IFA-2 (External Reflection Mode)

Internal Reflection Mode

A nano-gold film is deposited via chemical plating on window substrates such as monocrystalline silicon (Si) to serve as a conductive base. The electrocatalyst is loaded onto its surface to form the working electrode.

External Reflection Mode

The electrocatalyst is coated on the surface of a base glassy carbon electrode to fabricate the working electrode. A micrometer is integrated into the electrode to flexibly adjust the gap between the working electrode and the crystal, so as to regulate the thickness of the infrared liquid layer and the intensity of reflected signals.

Electrode & Cell Parameters

Working electrode for internal reflection cell: Monocrystalline silicon (without gold plating)

Working electrode for external reflection cell: 10 mm core glassy carbon electrode (with integrated micrometer)

Counter electrode: Graphite electrode

Reference electrode: Silver/Silver Chloride (Ag/AgCl) electrode

Infrared window material: Monocrystalline silicon

Anode & cathode gas inlet/outlet ports: Equipped

Cell volume: Less than 20 mL

IFA-1 : Internal Reflection

Internal Reflection Cell € : 3000

External Reflection Cell € : 5300



Optical Path Matching for Internal Reflection Cell



IFA-2 : External Reflection



External Reflection Cell Matching Optical Path

In-situ High-Pressure IR Test Cell

Model No.: IFA-P

This reaction cell is upgraded for high pressure resistance based on the atmospheric-pressure H-type in-situ IR test cell. The cell body is fabricated from high-purity titanium and sealed and fastened with stainless steel bolts. Electrodes are fixed internally to ensure safety and reliability.

IR window material: Monocrystalline silicon (customizable windows of calcium fluoride or zinc selenide are available)

Housing material: High-purity titanium

Chamber material: High-purity polytetrafluoroethylene (PTFE)

Chamber volume: 20 mL + 20 mL


Observation window material: High-pressure-resistant sapphire

Maximum working pressure: 6 MPa

Standard high-pressure resistant three-electrode system for electrochemistry: glassy carbon electrode holder, silver chloride electrode, platinum sheet electrode

Note: This reaction cell must be used with a matched optical path.

€ : 17000



In-situ Electrochemical Equipment Series

In-situ IR Test Cell (Transmission Mode)

Model: Infraredlight

Working Electrode: Platinum Mesh

Counter Electrode: Platinum Electrode


Reference Electrode: Platinum Electrode

IR Window: Calcium Fluoride (CaF)

Solution Thickness: 0.5 mm

Cell Body Material: PEEK

Equipped with gas inlet and outlet ports



Product Name	Model	Price	Remarks
Infrared ATR (H-type Removable Membrane Cell)	IFA-1 (Internal Reflection)	3000	Supplied with reference electrode and counter electrode
Infrared ATR (H-type Removable Membrane Cell)	IFA-2 (External Reflection)	5300	Equipped with micrometer and 10 mm glassy carbon electrode
Infrared ATR (H-type Removable Membrane Cell)	IFA-P (High-pressure Internal Reflection)	16400	Electrodes included
Infraredlight (Transmission Mode Cell)		1600	Electrodes included
Variable Incident Angle Optical Stage		3000	Supports side and bottom refraction
Crystal Gold Plating Cell		50	
Crystal Gold Plating Solution	50ml	540	
Our company provides optical path retrofitting services for customers' existing setups to achieve magnetic stirring and infrared signal enhancement. Please contact our customer service for more details.a			
All dimensions listed are standard sizes. Custom fabrication is available per specific requirements. Prices are subject to adjustment, and the latest price quotation shall prevail.			

In-situ XRD Spectroelectrochemical Cell

In-situ Electrochemical Equipment Series

Model No.: C031-XRD

This in-situ electrochemical cell is designed to investigate the spectral and morphological evolution of electrode materials during electrochemical experiments. The working electrode (WE) is positioned directly beneath the optical window, enabling optical instruments to characterize the working electrode through the window.

The cell body is constructed from PEEK and high-purity titanium. It supports rapid assembly, disassembly and easy cleaning.

It is applicable to in-situ electrochemical testing in flow systems; electrolyte can also be conveniently injected and filled via a syringe.


Optical window material: PI (Polyimide)

Distance between working electrode and optical window: less than 3 mm

Standard working electrode: 5 mm glassy carbon electrode. Alternative disk electrodes (Au, Pt, Ag, etc.) are available upon request with price difference applicable.

Standard accessories: reference electrode (Ag/AgCl or Ag electrode) and counter electrode (platinum electrode)

€ : 1600



In-situ Electrochemical Equipment Series

In-situ X-ray Absorption Spectroscopy Reaction Cell

Model: XAFS

Model : XAFS-1

This is an in-situ electrochemical reaction cell designed for synchrotron radiation X-ray absorption spectroscopy tests.

Core Features

The main body is fabricated from PEEK material; the internal cell volume can be customized according to customer specifications.

The device supports both two-electrode and three-electrode working configurations. The working electrode is tailor-made, while the other two electrodes can be configured on demand.

Inlet and outlet gas ports are reserved on the cell body, to meet the atmosphere control and airtightness requirements for diverse electrochemical reaction environments.



Model Differences

XAFS-1: Single-chamber cell

XAFS-2: H-type dual-chamber cell

XAFS-3: Electrode-free version, dedicated to pure gas-phase experiments


XAFS-4: Gas diffusion type cell

Optical window material: Kapton film (to be provided by the user)

Model : XAFS-2



Model : XAFS-3



In-situ Electrochemical Equipment Series

In-situ X-ray Absorption Spectroscopy Reaction Cell (Gas Diffusion Type)

Model: XAFS-4


The electrolytic cell adopts a high-efficiency gas diffusion design to ensure uniform delivery of reaction gas, improving the response speed and stability of experiments.

Wide-angle Kapton window: Kapton film is applied as the viewing window, offering an ultra-wide viewing angle of 120° and a larger window area, which greatly enhances observation and detection performance.

Optimized electrode gap design: The distance between Kapton film and gas diffusion electrode is minimized, effectively boosting signal sensitivity and real-time monitoring precision.

Replaceable chamber structure: The gas diffusion chamber can be flexibly swapped with a transmission chamber to meet diverse electrochemical characterization needs and broaden applicable scenarios.

Compatibility with classic configurations: It retains replaceable membrane structures for single-cell and H-type setups, compatible with traditional electrolytic testing systems.



Model	Type	Price	Remarks
XAFS-1	Single-Chamber Type	1600	
XAFS-2	Dual-Chamber Type	2300	
XAFS-3	For Gas Reaction Only	800	
XAFS-4	Gas Diffusion Type	300	
All listed dimensions are standard specifications. Custom tailor-made sizes are available upon request. Prices are subject to change, and the latest quotation shall prevail.			

Committed to the R&D and manufacturing of electrochemical equipment.

In-situ Electrochemical Equipment Series

In-situ Sum Frequency Generation Spectroscopy Electrochemical Cell

Model: 19008


Internal dimension: 20×5×5 mm

The cell is compatible with flow-phase measurement.

The working electrode holder of the cell can be customized according to experimental demands.

Standard configuration includes a reference electrode (Ag/AgCl or Ag electrode) and a counter electrode (platinum wire electrode).

€ : 1600



MS-In-situ IR Hyphenated Electrochemical Cell

Model: MS-IFA

This electrochemical cell integrates mass spectrometry and in-situ infrared spectroscopy technologies. It supports flow-phase testing.

Window material: Monocrystalline silicon.

Standard accessories: reference electrode (Ag/AgCl or Ag electrode) and counter electrode (platinum wire electrode).

€ : 4000



Committed to the R&D and manufacturing of electrochemical equipment.

In-situ Electrochemical Equipment Series

In-situ UV Electrochemical Cell

Model : UV2600-1

This electrochemical cell is co-developed with Lanzhou University, and it is compatible with Shimadzu UV2600 spectrophotometer from Japan.


Reference electrode: standard electrode with a diameter of 6 mm

Counter electrode: platinum wire electrode or graphite rod electrode is optional

Working electrode: ITO electrode

Cell body material: Polyetheretherketone (PEEK)


Window material: Sapphire glass



In-situ UV Electrochemical Cell

Model: UV2600-2

This model is upgraded from UV2600-1 to an H-type cell structure, which is an H-type in-situ UV electrochemical cell with replaceable diaphragm. The working chamber is equipped with gas inlet and outlet ports.



Model	Specification	Price	Remarks
UV2600-1	Single-chamber	1600	
UV2600-2	H-type dual-chamber	2300	
All listed dimensions are standard sizes. Customized specifications are available upon request. Prices are subject to adjustment, and the latest quotation shall prevail.			

In-situ Electrochemical Equipment Series

In-situ Mass Spectrometry Flow Electrochemical Cell

Model: MS-FC

This is a new-generation integrated multifunctional in-situ differential electrochemical mass spectrometer (PM-DEMS), designed for online qualitative and quantitative analysis of gaseous products, volatile intermediates and final products generated during electrochemical reactions. The in-situ differential electrochemical mass spectrometer is an on-site electrochemical testing technique combining electrochemistry and mass spectrometry. It adopts a hydrophobic gas-permeable membrane as the interface between electrochemical reaction and mass spectrometry, paired with a high-performance vacuum system to realize ultrafast detection immediately after electrochemical products are generated. It can in-situ detect volatile gaseous products, kinetic parameters, intermediates and their structural properties in electrochemical reactions. When multiple products are generated simultaneously from electrode reactions, this technique can quantify the Faradaic current variation of each product with electrode potential or reaction time. During potential scanning, the ion current corresponding to specific substances is recorded synchronously with Faradaic electrode current to obtain mass spectrometric voltammograms.

Product Features

Integrated sampling and detection for both gas and liquid phases, applicable to electrocatalysis, photocatalysis, thermocatalysis and battery gas evolution without requiring multiple sets of instruments.

High sensitivity with precise real-time monitoring; test results are fully consistent with reaction behaviors with zero detection delay.

Millisecond-level response time and scanning speed to support rapid online analysis.

Dual detectors consisting of Faraday cup and electron multiplier enable high-sensitivity detection covering a wide concentration range from 100 % down to ppb level.

Professional analytical software supports multi-component sampling for qualitative and quantitative analysis of gas species.

Temperature-controllable gas inlet pipeline effectively prevents condensation of sampled gas during delivery.

Bakeable mass spectrometry chamber greatly reduces interference from background gas.

Multi-channel input and output signals support automatic linkage and control with external instruments.


Built-in filament pressure protection mechanism extends the service life of the filament.

Customizable sampling system to realize pre-treatment of inlet gas and multi-channel sampling detection as required.

Customizable electrochemical cells and battery molds according to user demands.

Standard configuration: reference electrode (Ag/AgCl or Ag electrode) and counter electrode (platinum wire electrode)

€ : 4000



Committed to the R&D and manufacturing of electrochemical equipment.

In-situ Electrochemical Equipment Series

Multi-functional In-situ Test Electrochemical Cell

Model: In-situ-X

This is a versatile FlowCell electrochemical cell. The electrolyte flows into the cell cavity through the reference electrode, makes contact with the working electrode, then passes the counter electrode and drains out of the cell body to form a complete closed circulation loop.

The working electrode module supports two contact configurations: standard type and gas diffusion type.

Its multi-functional feature is realized by replacing the front optical window; different window materials are selected to match various characterization experiments:

UV & Raman testing: Quartz or sapphire window


XAFS testing: Kapton film

XRD testing: Beryllium window

Cell body material: High-purity titanium and PEEK


Cavity dimension: 15×15×1.2 mm

Standard accessories: Ag/AgCl reference electrode and sapphire optical window



Schematic Diagram of Standard Configuration

€:2300



Schematic Diagram of Gas Diffusion Configuration

In-situ Electrochemical Equipment Series

In-situ Raman Two-Electrode Battery Test Cell Model: B002-RM

This in-situ Raman electrochemical cell is designed to investigate the in-situ spectral and morphological evolution of electrode materials during electrochemical experiments.

The cell body is made of high-purity titanium. Internal spring components are adopted to adjust the compression load for performance evaluation.

The cell features excellent sealing performance and assembly repeatability.

When connected to charge/discharge testing equipment, it is applicable to a wide range of battery cycling and performance characterization tests.

Tighten the screws to compress the chemically resistant O-ring and guarantee airtight sealing.


It can be assembled inside a glove box and then operated under ambient atmosphere.

Supports rapid assembly, disassembly and easy cleaning.

Distance between working electrode and optical window: less than 2 mm

Diameter of optical window: 8 mm

Overall dimension (Length × Width × Height): 50 × 50 × 20 mm



In-situ XRD Two-Electrode Battery Test Cell Model: B002-XRD

The cell body is made of high-purity titanium. The compression load can be adjusted via internal springs for performance evaluation, and the cell delivers outstanding airtight sealing and assembly reproducibility.

When connected to charge/discharge test instruments, it is suitable for a wide range of battery cycling and performance characterization tests.

It can be assembled inside a glove box and then applied under open ambient conditions.

Easy to disassemble; the cell can be taken apart after charge/discharge testing without damaging the sample.

It supports fast assembly and disassembly for convenient cleaning.

Distance between the working electrode and optical window: less than 2 mm

Diameter of the optical window: 8 mm

Channel width of the cell: 8 mm

Overall dimension (Length × Width × Height): 50 × 50 × 20 mm



Model	Specification	Price	Remarks
B002-RM		1600	
B002-XRD		1600	
All listed dimensions are standard specifications. Custom tailor-made sizes are available upon request. Prices are subject to adjustment, and the latest quotation shall prevail.			

In-situ Electrochemical Equipment Series

In-situ Raman Three-Electrode Battery Test Cell



Model: B003-RM

This electrochemical cell is upgraded on the basis of B002-RM with an additional reference electrode.

Distance between the working electrode and optical window: less than 2 mm

Diameter of the optical window: 8 mm

Overall dimension (Length × Width × Height): 50 × 50 × 24 mm



In-situ XRD Three-Electrode Battery Test Cell

Model: B003-XRD



This electrochemical cell is upgraded from B002-XRD with an extra reference electrode added.

Distance between working electrode and optical window: less than 2 mm

Optical window diameter: 8 mm

Channel width of the cell: 8 mm

Overall dimension (Length × Width × Height): 50 × 50 × 24 mm



Model	Specification	Price	Remarks
B003-RM		1800	
B003-XRD		1800	
All listed dimensions are standard sizes. Customized specifications are available upon request. Prices are subject to revision, and the latest quotation shall prevail.			

In-situ Electrochemical Equipment Series

In-situ Raman Pressurized Two-Electrode Battery Test Cell


Model: PB002-RM

Equipped with an extra pressure system based on the B002-RM model, with a maximum withstand pressure of 6 MPa. It is specially designed to investigate the in-situ spectral and morphological evolution of electrode materials under high-pressure electrochemical conditions.

Distance between the working electrode and optical window: less than 2 mm

Diameter of the optical window: 8 mm

Overall dimension (Length × Width × Height): 50 × 50 × 24 mm



In-situ Raman Pressurized Three-Electrode Battery Test Cell


Model: PB003-RM

This electrochemical cell is upgraded from B003-RM with an added pressure system, with a maximum bearing pressure of 6 MPa. It is designed to study the in-situ spectral and morphological changes of electrode materials under high-pressure electrochemical experiments.

Distance between the working electrode and optical window: less than 2 mm

Diameter of the optical window: 8 mm

Overall dimension (Length × Width × Height): 50 × 50 × 24 mm



	pecification	Price	Remarks
PB002-RM		13800	
PB003-RM		13800	
All standard dimensions are provided; customized sizes are available on demand. Prices are subj ect to change, and the latest quotation s hall prevail.			

In-situ Infrared Lithium Battery Test Cell

Model: B-IFA

Infrared window material: Monocrystalline silicon


Cell body material: High-purity titanium

Cell dimension: 50 × 50 × 20 mm

Crystal material: Si

Among conventional infrared window materials including Ge, ZnSe and Si, Ge is relatively chemically active. Cu and Ag thin-film electrodes deposited on Ge substrates can only deliver acceptable electrochemical responses at potentials negative to open-circuit potential. During anodic potential scanning, the high anodic current of the Ge substrate will mask the electrochemical signal of the metallic electrode and even cause peeling of the metal thin film. In addition, ZnSe is unstable in acidic and alkaline solutions, so it is not suitable as the window material for electrochemical ATR-SEIRAS measurements.

The electrochemical cell adopts a spring structure to adjust compression load, enabling tight contact between positive/negative electrode sheets and the separator inside the test battery. Double O-rings are applied to ensure airtight sealing. After assembly inside a glove box, the cell can be taken out and operated under ambient atmosphere with excellent sealing performance and assembly repeatability.



Variable Incident Angle Optical Stage

It provides continuously variable incident angles and multiple crystal plates to selectively control the penetration depth.

High throughput (over 50% for 45° ZnSe crystal), which greatly shortens sampling time and enables component detection in low-concentration samples with complex compositions.

Continuously adjustable incident angle range: 30° to 80°.

Penetration depth ranges from 0.4 μm to 46 μm, offering ideal depth selection for analytical research.

High throughput for high-quality spectrum acquisition.

Optional high-pressure fixture is available for sampling thin films, coatings or powder samples.

Reserved mounting position for integrating manual or automatic polarizers.



Product Name	Model	Price	Remarks
In-situ Infrared Lithium Battery Test Cell	B-IFA	4000	
Variable Incident Angle Optical Stage		30000	
The company provides optical path retrofitting service for customers' existing equipment to realize magnetic stirring and infrared enhancement effects. Please contact customer service for details.			
All listed dimensions are standard specifications. Customized products are available upon request. Prices are subject to change, and the latest quotation shall prevail.			

Committed to the R&D and manufacturing of electrochemical equipment.

In-situ Battery Simulation Observation Cell (for Lithium Dendrite Observation) In-situ Assembly System for Lithium Batteries

Model: C031-5


The conductive substrate of this electrochemical cell is made of high-purity titanium.

This cell simulates a lithium-ion coin cell to observe the growth of lithium dendrites on the cross-section of lithium foil.

The optical window is made of sapphire glass with a light transmittance above 95%.

Size of the working lithium foil: 10 × 10 mm

€:1000



In-situ Battery Simulation Observation Cell (for Lithium Dendrite Observation)

Model: C031-5-1

A reference electrode is added on the basis of model C031-5.


The conductive substrate is made of high-purity titanium.

This electrochemical cell simulates a lithium-ion coin cell to observe the growth of lithium dendrites on the cross-section of lithium foil.

The optical window adopts sapphire glass with a light transmittance of over 95%.

Size of the lithium foil used in the cell: 10 × 10 mm

€:1000



Committed to the R&D and manufacturing of electrochemical equipment.

Solid State Battery Fixture

In-situ Assembly System for Lithium Batteries

Model: B004

This is a dedicated device designed for pressure testing of solid state batteries.

Product Features

Compact structure with quick-release design, facilitating fixture disassembly, assembly and battery powder loading.

The mold is made of high-purity titanium, featuring corrosion resistance, high mechanical strength and capability to withstand heavy pressure.


Equipped with a unique self-leveling mechanism to ensure uniform pressure distribution on the electrode surface, preventing electrolyte cracking or electrode delamination caused by excessive local pressure.

Adopt detachable gold-plated copper tabs to improve electrical conductivity and simplify after-sales replacement.

Large frame structure allows side loading and unloading of the battery fixture without removing the column fixing nuts.

The built-in pressure sensor integrates multi-stage amplification chips and is powered by an independent power supply. It supports flexible input and quick switching of multiple sensitivity parameters, with fast pressure feedback, high dynamic response frequency, excellent stability and strong anti-interference performance.

€:1000



8MHz



Metal Bipolar Plate Membrane Electrode Electrolysis Cell

Model: MEA-TI-TI

This electrolytic cell is mainly applied to research-oriented tests for electrochemical CO reduction, alkaline anion exchange membrane water electrolysis and other electrochemical processes.



The cell body is equipped with double O-ring sealing grooves for excellent sealing performance.

The bipolar plates are prefabricated with heating and temperature measuring holes to facilitate electrochemical tests under temperature-controlled conditions.

The entire cell body is made of high-purity titanium. High-purity nickel plates are also available for electrochemical tests under special environments.

The reactor supports serpentine, parallel, vein-type flow channels; customized flow patterns including spiral, mesh and comb structures are acceptable.

Price: Refer to the summary table on Page 35



Graphite Bipolar Plate Membrane Electrode Electrolysis Cell


Model: MEA-GP

This electrolytic cell is mainly used for research tests on electrochemical carbon dioxide reduction, alkaline anion exchange membrane water electrolysis and other electrochemical processes.

The flow field plates of the cell are made of imported isostatic graphite plates, and the outermost fixing plates are titanium plates. Heating and temperature measuring holes are reserved on the top of titanium plates to facilitate electrochemical tests under temperature-controlled conditions.

The reactor is equipped with serpentine, parallel and vein-type flow channels; customized flow channel types such as spiral, mesh and comb structures are available.

Price: Refer to the summary table on Page 35



Committed to the R&D and manufacturing of electrochemical equipment.

Membrane Electrode Electrolysis Cell System

Visualizable Membrane Electrode Electrolysis Cell

Model: MEA-Visualization Type A


This electrolytic cell is mainly applied to research-oriented tests for electrochemical CO reduction, alkaline anion exchange membrane water electrolysis and other electrochemical processes.

Both anode and cathode are equipped with optical visualization windows for in-situ observation and high-speed photography.

The visualizable MEA is divided into Type A with circular windows and Type B with square windows according to experimental requirements.

The cathode adopts a hollow serpentine flow channel, and the anode adopts a hollow multi-parallel flow channel.

Price: Refer to the summary table on Page 35



Committed to the R&D and manufacturing of electrochemical equipment.

Visualizable Membrane Electrode Electrolysis Cell Membrane Electrode Electrolysis Cell System

Model: MEA-Visualization Type B


This electrolytic cell is mainly used for research tests of electrochemical carbon dioxide reduction, alkaline anion exchange membrane water electrolysis and other electrochemical processes.

Both anode and cathode are equipped with optical visualization windows for in-situ observation and high-speed photography.

The visualizable MEA is divided into Type A with circular windows and Type B with square windows according to experimental requirements.

The cathode adopts a hollow serpentine flow channel, and the anode adopts a hollow multi-parallel flow channel.

Price: Refer to the general price list on Page 35



Committed to the R&D and manufacturing of electrochemical equipment.

Membrane Electrode Electrolysis Cell System

Membrane Electrode Electrolysis Cell with Thermostatic Water Bath

Model : MEA-TI-VB

This electrolytic cell is mainly applied to research-based electrochemical tests for electrochemical CO reduction and water electrolysis.



It is commonly used for temperature-controlled electrochemical measurements on large-flow-channel membrane electrode assemblies with dimensions of 50×50 mm, 100×100 mm, 200×200 mm, etc.

Equipped with a dual temperature control system consisting of a thermostatic water bath jacket (purple interlayer), heating rods and thermocouples.

The anode and cathode flow channels adopt a multi-serpentine large recirculation design. The serpentine channels incorporate a proprietary shear force structure, which can effectively reduce cell resistance when paired with the company's high-pressure pump (operating pressure up to nearly 1 MPa).

Detachable gold-plated copper tabs are adopted for easy replacement.

Price: Refer to the summary table on Page 35



Membrane Electrode Electrolysis Cell System

In-situ Raman Membrane Electrode Electrolysis Cell

Model: MEA-TI-RM

A membrane electrode electrolysis cell designed for in-situ Raman characterization.

Window material: Quartz plate or sapphire.

Plate material: High-purity titanium plate; high-purity nickel plate is available for customization upon experimental demand for superior corrosion resistance against alkaline solutions.


Tab material: Gold-plated copper to improve electrical conductivity and reduce resistance.

Fitting type: 1/8 inch British standard PEEK quick-connect fitting, corrosion resistant with internal shear force structure.

Flow channel size: 14×14 mm, customizable as required.

Distance from window to sample: Less than 5 mm.

Price: Refer to the summary table on Page 35



Membrane Electrode Electrolysis Cell System

Replaceable Flow Channel Membrane Electrode Electrolysis Cell

Model: MEA-Replaceable Flow Channel


This electrolytic cell is applied to research-oriented tests for carbon dioxide reduction, water electrolysis and other electrochemical processes.

Both anode and cathode bipolar plates are made of imported high-purity PTFE with excellent corrosion resistance.

The fastening protective plates are manufactured from high-purity titanium.

The cell flow channels are made of PTFE, typically adopting serpentine design. The minimum thickness of the flow channel can reach 0.1 mm, and flow channels with various thicknesses are replaceable according to experimental requirements.

Price: Refer to the general list on Page 35



Committed to the R&D and manufacturing of electrochemical equipment.

Membrane Electrolysis Stack Electrochemical Cell

Membrane Electrode Electrolysis Cell System

Model: MEA-TI-X

This electrolytic cell achieves higher voltage and power by stacking individual flow field plates. It is applicable to research tests on electrochemical CO reduction, water electrolysis, organic electrosynthesis and other electrochemical processes.

The flow field plates are made of high-purity titanium; materials such as high-purity nickel and PEEK can be customized according to customer requirements.

The plates adopt internal hidden flow channels, supporting series connection, parallel connection, and combined series-parallel connection. Heating and temperature measuring holes are reserved on flow field plates to facilitate electrochemical tests under temperature-controlled conditions.

Gold-plated tabs with excellent corrosion resistance.

Available flow channel patterns include serpentine, parallel and vein types; customized patterns such as spiral, mesh and comb structures are acceptable.

Standard flow channel sizes: 10×10 mm, 20×20 mm, 22.4×22.4 mm, 30×30 mm, 50×50 mm, 100×100 mm; other sizes are customizable.

Unique Design Feature

Stackable structure with evenly distributed pressure between each plate.

Price: Refer to the summary table on Page 35



Membrane Electrode Electrolysis Cell System

Flow Path Design for Membrane Electrolysis Stack Electrochemical Cell


To accommodate diverse experimental requirements across different research fields, our company provides two types of flow path designs for the electrolyzer stack:

Series connection of cathode and anode flow channels

Cathode series connection + anode parallel connection


Schematic Diagram of Series Flow Channel

Both cathode and anode flow channels adopt series connection, which is commonly applied to hydrogen production via water electrolysis.



Series + Parallel Flow Channel Schematic Diagram

w channel has a series-connected cathode and a parallel-connected anode with independent flow passages, which can effectively and quickly exhaust the gas produced at the anode. The electrolytic cell is generally used for carbon dioxide reduction.



Membrane Electrode Electrolysis Cell System

High-Current Solution for Membrane Electrode Electrolysis Cell


This device enables flexible regulation and recording of temperature (heating and cooling), current and voltage parameters, and is especially suitable for CO reduction reactions under high current density and large active area conditions. It can effectively control the influence of electrolysis temperature changes on reaction selectivity and help improve the stability of the device. The relevant parameter indicators are as follows:

Maximum output voltage: 32V; Maximum output current: 10A; Maximum measurable voltage: 20V; Maximum measurable current: 20A;
Measurement accuracy: 0.01V (A)

Maximum controllable temperature: 100°C; Temperature accuracy: 0.1°C

The software supports recording and plotting of up to 12 physical parameters, with real-time recording and automatic data saving. It avoids data loss caused by sudden power failure, and the data acquisition interval is 0.02S to ensure detection sensitivity.


The system is modifiable and upgradable. Additional sensors can be added as required to record more parameters during the electrolysis process, such as gas flow rate, gas humidity, gas purity, etc.



Supporting Equipment Package Solution for Membrane Electrode Electrolysis Cell

For flow-type membrane electrode electrolysis cells, our company provides a complete one-stop turnkey solution, including electrochemical workstation, membrane electrode electrolysis cell, peristaltic pump, gas-liquid mixing pump, heating and temperature controller, as well as various required electrochemical consumables.

It enables researchers to build experimental platforms conveniently and efficiently, laying a solid foundation for the smooth and rapid advancement of experiments.



Committed to the R&D and manufacturing of electrochemical equipment.

Membrane Electrode Electrolysis Cell System

General Price List for Membrane Electrode Electrolysis Cells

Product Name	Model	Flow Channel Specification	Price	Remarks
Titanium Metal Bipolar Plate Type	MEA-TI-TI	10*10mm; 20*20mm; 5cm ²	2300	Can be replaced with high-purity nickel plate; price to be quoted separately
		30*30mm	2600	
		50*50mm	3300	
		100*100mm	4300	
Graphite Bipolar Plate Type	MEA-GP	10*10mm; 20*20mm; 5cm ²	2300	
		30*30mm; 50*50mm	Inquiry	
Visualizable Type	可视化型	10*10mm; 20*20mm; 5cm ²	2600	
		30*30mm; 50*50mm	Inquiry	
With Thermostatic Water Bath	MEA-TI-WB	50*50mm	3300	Can be replaced with high-purity nickel plate; price to be quoted separately
		100*100mm	5600	
		200*200mm	14000	
Replaceable Flow Channel Type	MEA-TI-RM	14*14mm	3000	
Replaceable Flow Channel	Replaceable Flow Channel	30*30mm	2600	Minimum size 30×30 mm; no smaller flow channel specifications available
		50*50mm; 100*100mm	Inquiry	
Electrolyzer Stack	MEA-TI-X	10*10mm、20*20mm、5cm ² 5 flow field plates	Inquiry	Customization for larger sizes is supported
Integrated Control Workstation	EC-MEA		9400	

Integrated Solution Table for Membrane Electrode Assembly Electrolyzers

Product Name	Brand	Specification & Model	Price	Remarks
Membrane Electrode Electrolysis Cell	gaossunion	opt iona		Select one model as needed
Peristaltic Pump	gaossunion	EC200-01	1100	
Anion Exchange Membrane	Fumatech (Germany)	Fuma-FAA-3-50	270	
Cation Exchange Membrane	DuPont (USA)	117-100*100	200	
Kapton Tape	3M (USA)	8mm*30m	120	
Hydrophobic Carbon Paper	SGL 22BB (Germany)	100*100mm	340	10 pieces per box
Copper Tape	gaossunion	5mm*50mm	14	
Liquid Flow Cell	gaossunion	YL-1	300	
PTFE Tube	3M (USA)	3mm*5mm	100	
Electrolysis Cell Humidifier	gaossunion		310	
Gas-Liquid Mixing Pump	gaossunion	EC200-02	740	
Heating & Temperature Controller	gaossunion	EC200-03	940	
Mass Flow Meter	Sevenstar Huachuang		2200	

Entry-Level Gas Diffusion Electrolytic Cell

Model: 101014

This electrolytic cell is an entry-level product of gas diffusion flow cells.

Application Scenario: For beginners to get started with gas diffusion experiments.



Cell Material: PEEK (PEEK is the only available material to meet the wall thickness requirement of the cell).

Adopts a quick-open design to facilitate opening and closing of the cell lid.

It features a three-electrode system: the working electrode is a gas diffusion electrode, while the counter electrode is a conventional rod electrode.

Gas inlet and outlet ports as well as spare plugs are pre-installed on both the anode and cathode sides for use in other experimental scenarios.

€:1600



Committed to the R&D and manufacturing of electrochemical equipment.

Primary Gas Diffusion Electrolytic Cell

Gas Diffusion Electrolyzer Series

Model: CP10/CP20

This is a primary version gas diffusion electrolytic cell.

Upgraded from the entry-level gas diffusion electrolytic cell to a Flow Cell structure. In this Flow Cell, gas flows in from the top and exits from the bottom, while electrolyte liquid enters from the bottom and flows out from the top.


Standard channel sizes are 10×10 mm and 20×20 mm; customized dimensions are available upon request.

Distance between anode and cathode: 20 mm

Available cell materials: Polymethyl Methacrylate (PMMA), Polytetrafluoroethylene (PTFE), Polyetheretherketone (PEEK)

Price : PMMA& PTFE : 430

Peek : 830



Committed to the R&D and manufacturing of electrochemical equipment.

Gas Diffusion Electrolyzer Series

Advanced Gas Diffusion Electrolytic Cell

Model No.: 101016

This is a classic three-chamber gas diffusion electrolytic cell.

Cell body material: PEEK with excellent corrosion resistance.


Chamber dimension: 5×20 mm

Reaction area: 1 cm²

Distance between anode and cathode: 7 mm

Flooding viewing window: Not equipped

€:1600



Committed to the R&D and manufacturing of electrochemical equipment.

Gas Diffusion Electrolyzer Series

This is a classic three-chamber gas diffusion electrolytic cell.

Cell body material: PEEK with outstanding corrosion resistance.

Chamber size: 5×20 mm


Reaction area: 1 cm²

Anode-cathode spacing: 7 mm for model 101017-1; 3 mm for model 101017-1.2

Flooding observation window: Equipped with high-purity quartz glass

101017-1 : 2000

101017-1.2 : 2300



High-End Multifunctional Gas Diffusion Electrolytic Cell

Model: 101018

This reactor adopts a sandwich structure, which can be freely configured into four functional modes according to experimental requirements: CO reduction gas diffusion electrolytic cell, solid-state electrolytic cell for producing pure liquid products, membrane electrode reactor, zinc-air battery and lithium-air battery.

Reaction chamber dimension: 10×10 mm


Reactor material: High-purity titanium + PEEK

Reaction area: 1 cm²

Thickness of PEEK chamber: 1.2 mm

Standard reference electrode: AgCl electrode

€:2934





Function 1: CO₂ Reduction Gas Diffusion Mode

For this CO₂ reduction gas diffusion electrolytic cell (as shown in the figure), Plate A serves as the chamber for humidified CO gas inlet. A gas diffusion electrode (carbon paper) is placed between Plate A and Plate B, while Plate B acts as the flow chamber for cathodic liquid.

An anion exchange membrane and the anode are installed between Plate B and Plate C. The anode can be a metal mesh loaded with water splitting catalyst, or foam metal with water oxidation activity.

Neutral or alkaline electrolyte is circulated through Part C to carry out the water oxidation reaction.

Part D holds the reference electrode and serves as the inlet and outlet for liquid in the cathode chamber. The reference electrode is inserted at a 45° inverted angle to quickly eliminate bubble interference.



Gas Diffusion Electrolyzer Series

Function 2: Solid Electrolyte Mode



Assemble parts A, B and C. Solid electrolyte based on ion exchange resin is adopted to replace liquid electrolyte, so as to avoid introducing extra ions and directly prepare high-purity liquid products. The detailed structure is as follows:

Parts A and C are equipped with serpentine channels to prolong gas residence time and boost gas conversion efficiency.

Plate A serves as the chamber for feeding humidified CO₂ gas. A gas diffusion electrode (carbon paper) and an anion exchange membrane are placed between Plate A and Plate B (cold pressing or hot pressing can be applied to ensure sufficient interfacial contact).

A cation exchange membrane and an anode are arranged between Plate B and Plate C. The anode can be a metal mesh loaded with water splitting catalyst or foam metal with water oxidation activity. Acidic electrolyte is pumped into Part C to proceed with water oxidation reaction.

Part B is the core component of the solid-state electrolytic cell. Its overall cavity is I-shaped with a middle section thickness of 1.2 mm, which contains a 1×1 cm square through-hole. Granular ion exchange resin can be filled into the through-hole as solid electrolyte to substitute liquid electrolyte and directly produce pure liquid fuels. Pure water is fed into Part B to flush liquid products out of the reactor, yielding pure aqueous liquid products free of anions and cations.



Function 3: Membrane Electrode Electrolytic Cell Mode


Assemble Part A and Part C while removing Part B and Part D to set up a membrane electrode electrolytic cell.

The specific structure is as follows:


Part A and Part C are equipped with serpentine channels to extend gas residence time and improve gas conversion rate.

Plate A serves as the chamber for feeding humidified CO gas. Between Plate A and Plate C, components are placed in sequence from A to C: gas diffusion electrode (carbon paper), anion exchange membrane or proton exchange membrane (cold pressing or hot pressing can be adopted to ensure full contact between the gas diffusion electrode and ion exchange membrane), as well as metal mesh loaded with water splitting catalyst (or foam metal with water oxidation activity).

Neutral or alkaline electrolyte is circulated into Part C to carry out the water oxidation reaction.



Ultra-long Duration Continuous Operation Stability Test
Adopting the latest generation Model 101018 membrane electrode electrolytic cell from Gaossunion together with independently developed electrodes, the system has achieved continuous and stable electrochemical CO reduction to CO for more than 1000 hours.



Gas Diffusion Electrolyzer Series

Function 4: Zinc-Air & Lithium-Air Mode

Assemble plates A, B and C.


Place carbon paper between Plate A and Plate B.

Insert zinc sheet or lithium sheet between Plate B and Plate C.

Plate A is used for gas inlet and outlet.

Plate B is used for electrolyte inlet and outlet.

This assembly forms a standard zinc-air or lithium-air electrolytic cell.



Ultimate Version Membrane Electrode Gas Diffusion Electrolytic Cell

Model: 101019

As a new-type gas diffusion electrolytic cell, this product is comprehensively upgraded on the basis of membrane electrode electrolytic cells. The gas chamber adopts the serpentine flow channel commonly used in MEA cells, which greatly extends the contact duration between reaction gas and the cathode to boost reaction efficiency. With a brand-new flow path design for the cathode compartment, the gap between working electrode and counter electrode is reduced to 0.4 mm.

Plate material: High-purity titanium

Flow channel type: Serpentine flow channel (default), customized channels are available

Distance between working electrode and counter electrode: 0.4 mm

Electrode reaction area sizes: 10×10 mm, 20×20 mm and other options

Working electrode: Gas diffusion electrode (to be prepared by the user)


Reference electrode: Silver-silver chloride electrode (standard configuration)

Counter electrode: Porous materials such as iridium oxide mesh (to be prepared by the user)

Standard accessory: Torque wrench

10×10 mm version: €:2660

20×20 mm version: €:2860



Committed to the R&D and manufacturing of electrochemical equipment.


Gas Diffusion Electrolyzer Series

Complete Supporting Equipment Solution for Gas Diffusion Experiment Setup

For convection flow-through gas-diffusion electrolytic cells, our company provides a one-stop integrated turnkey solution.

The full package includes an electrochemical workstation, reaction electrolytic cell, peristaltic pump, gas-liquid mixing pump, humidifier, heating & temperature controller, mass flow meter, as well as all required electrochemical consumables.

This enables researchers to build experimental platforms conveniently and efficiently, laying solid groundwork for the smooth and rapid execution of relevant experiments.



Price List of Turnkey Solution for CO Electroreduction System

Table of Items

Product Name	Model	Price	Remarks
Entry-Level Gas Diffusion Electrolytic Cell	101014	1600	
Primary Gas Diffusion Electrolytic Cell CP10/CP20	PMMA	430	Single-chamber; Chamber size: 101010 mm or 202010 mm
	PTFE	430	
	PEEK	830	
Standard Gas Diffusion Electrolytic Cell	101016	1600	No observation window
Observable Gas Diffusion Electrolytic Cell	101017-1	2000	With observation window; Anode-cathode spacing <7 mm
Observable Gas Diffusion Electrolytic Cell	101017-1.2	2300	With observation window; Anode-cathode spacing <3 mm
MEA-based Multifunctional Gas Diffusion Electrolytic Cell	101018	3000	Anode-cathode spacing: 1.2 mm
MEA-type Gas Diffusion Electrolytic Cell	101019	2700/2700	Anode-cathode spacing: 0.4 mm
Select one electrolytic cell from the list above			
Water Circuit Management System	101015	600	
PEEK-shaft Ag/AgCl Reference Electrode	PK-1038	190	
PEEK-shaft Hg/HgO Reference Electrode	Hg-1038	190	
Platinum Plate Electrode	15*35*0.2	680	
Peristaltic Pump	EC200-01	1100	
Anion Exchange Membrane	Fuma-FAA-3-50	270	
Cation Exchange Membrane	N117 100*100mm	200	
Hydrophobic Carbon Paper	100*100mm	340	10 pieces per box
Iridium Oxide Coated Mesh Electrode	100*100mm	400	Titanium substrate; Ir loading: 0.2 mg/cm ²
Salt Bridge	CP-1038	100	
Copper Conductive Tape	5mm*50 mm	14	
Liquid Flow Cell	YL-1	300	
PTFE Tubing	3mm*5 mm	100	
Flow Stabilization Reservoir	30ml	230	
Gas-Liquid Mixing Pump	EC200-02	320	Built-in shear force structure
Mass Flow Controller		2200	
All listed dimensions are standard sizes. Custom chamber volumes are available upon request with price adjustments; final pricing shall prevail.			

Solid Electrolyte Electrochemical Cell (Two-Electrode System)

Gas Diffusion Electrolyzer Series

Model: QG-20-1

As illustrated in the figure, the solid electrolyte cell adopts an overall sandwich structure to construct a gas-solid interface. It replaces liquid electrolyte with solid electrolyte, eliminating the introduction of anions and cations, and directly enables the preparation of high-purity aqueous liquid products. The detailed structure is specified as follows:

1. Cell Body 1 & 3: Bipolar Plates

The inner side is machined with serpentine gas flow channels, which effectively raise the concentration of gaseous reactants on the catalyst surface and thus achieve high current density.

2. Membrane & Gas Diffusion Layer Assemblies

Between Cell Body 1 and 2: A dual-layer structure consisting of anion exchange membrane (dioxide material) and gas diffusion layer loaded with anode catalyst is adopted to form the gas-solid interface and facilitate anion transport.

Note: Thermal pressing is required for forming to ensure sufficient interfacial contact.

Between Cell Body 2 and 3: A dual-layer structure composed of Nafion 115 cation exchange membrane and gas diffusion layer loaded with cathode catalyst is used to construct the gas-solid interface and realize cation transport.


Note: Thermal pressing is required for forming to ensure sufficient interfacial contact.

3. Core Component □ Cell Body 2

Cell Body 2 serves as the core unit of the solid electrolyte cell. It contains a square hollow cavity (4 cm² in area, 3 mm in thickness), which can be filled with shaped solid electrolyte to substitute liquid electrolyte and support direct synthesis of liquid fuels.

The solid electrolyte is typically high-conductivity polymer composites or porous ceramics. Pure water flows through the cavity to carry away liquid products, shifting the chemical equilibrium forward and yielding impurity-free aqueous product solutions.

Species generated from Cell Body 1 and Cell Body 3 permeate through their respective ion-exchange membranes, undergo combination reactions inside the intermediate Cell Body 2 to form target products, which are subsequently flushed out by circulating pure water.




Solid Electrolyte Electrochemical Cell (Three-Electrode System)

Model: QG-20-2

This cell is developed on the basis of model QG-20-1 with an additional reference electrode. The plate thickness of the reference electrode compartment is 3 mm.

The solid electrolyte electrochemical cell adopts an integral sandwich structure to construct a gas-solid interface. It replaces liquid electrolyte with solid electrolyte to avoid the introduction of anions and cations, enabling the direct preparation of high-purity aqueous liquid products.




Committed to the R&D and manufacturing of electrochemical equipment.

Gas Diffusion Electrolyzer Series

Solid Electrolyte Electrochemical Cell (Serpentine Flow Channel System)

Model: QG-20-3


As shown in the figure, this model optimizes the No.2 plate on the basis of QG-20-1 by adding serpentine flow channels. The solid electrolyte cell adopts an overall sandwich structure to construct a gas-solid interface. It replaces liquid electrolyte with solid electrolyte to eliminate the introduction of anions and cations, so as to directly prepare high-purity aqueous solutions of liquid-phase products.



Solid Electrolyte Electrochemical Cell (Visualizable Version)

Model: QG-20-4

As shown in the figure, this model is upgraded on the basis of QG-20-3. A high-transmittance quartz observation window is installed on the cathode compartment, which supports optical observation of the working electrode inside the cathode chamber or external light irradiation experiments.



Model	Specification	Price	Remarks
QG-20-1	20*20mm	2100	
QG-20-2	20*20mm	2300	Equipped with reference electrode
QG-20-3	20*20mm	2300	
QG-20-4	20*20mm	2600	
All listed dimensions are standard specifications. Custom dimensions are available upon request. Prices are subject to change without prior notice; the latest official quotation shall prevail.			


Single Liquid Chamber Gas Diffusion Electrolysis Cell **Gas Diffusion Electrolyzer Series**

Model: MTR-4-1

This electrolysis cell is applicable to electrochemical tests under flowing phase conditions. The cell is composed of one liquid cavity compartment and one serpentine flow channel compartment. The serpentine channel is generally adopted as the gas flow path. Gas passes through the gas diffusion layer and undergoes electrochemical reaction inside the liquid cavity. Channel dimension: 20×20 mm.

The electrodes shown in the figure are for demonstration only. The platinum mesh electrode and reference electrode are not included in the quoted price and need to be purchased separately.

€:1600



Dual Liquid Chamber Gas Diffusion Electrolytic Cell

Model: MTR-4-2


Compared with model MTR-4-1, Model -2 separates the working electrode, reference electrode and counter electrode via ion exchange membrane.

This electrolytic cell is designed for electrochemical tests under flowing phase conditions.

The cell consists of one liquid cavity compartment and one serpentine flow channel compartment. The serpentine channel is generally used as the gas inlet path; reactant gas permeates through the gas diffusion layer to carry out reactions inside the liquid cavity.

The electrodes shown in the diagram are for demonstration only. Platinum mesh electrode and reference electrode are not included in the listed price and need to be purchased separately.

€:1900



Gas Diffusion Photoelectrochemical Cell

Model: MTR-QW

This electrolytic cell enables photoelectrocatalytic reaction tests with gas diffusion electrodes.


The cathode of the cell must adopt gas diffusion electrodes made of waterproof and gas-permeable materials such as carbon cloth and carbon paper.

A platinum wire counter electrode is equipped for the cathode (standard configuration: platinum wire of 0.5 mm × 230 mm).

A silver/silver chloride reference electrode is included as standard accessory.

A serpentine flow channel is designed for gas feeding on the cathode side to achieve sufficient contact and reaction between reactant gas and catalyst. If humidified gas is required, it is recommended to be used together with the custom gas humidifier developed by Corrtest Instruments.

€:1500



Committed to the R&D and manufacturing of electrochemical equipment.

Gas Diffusion Electrolyzer Series

Gas Diffusion Membrane-Replaceable Photoelectrochemical Flow Cell

Model: MTR-FC-QW

This electrolytic cell addresses the drawback of conventional Flowcell gas diffusion electrolytic cells, where the loaded catalyst faces away from light irradiation.

It is mainly applied to flow system tests for photoelectrocatalytic reactions such as CORR and NRR.


Counter Electrode: Graphite Rod Electrode (Standard Configuration)

Reference Electrode: Silver/Silver Chloride Electrode (Standard Configuration)

Working Electrode: Gas Diffusion Electrode (User-supplied)

Price of the reaction cell: 3000

Electric Water Management System: 100



Committed to the R&D and manufacturing of electrochemical equipment.

PressureCell High-Pressure Electrochemical Cell Series

Single-Chamber High-Pressure Electrochemical Cell

Model: P001-1

- Material: Titanium (Ti)
- Rated working pressure: 6 MPa
- Maximum pressure resistance: 6 MPa
- Volume options: 50 mL & 100 mL; custom volumes available on request
- Valve material: 304 stainless steel
- Reference Electrode: Ag/AgCl electrode (to be purchased separately)
- Counter Electrode: Platinum plate electrode (to be purchased separately)
- Working Electrode: Glassy carbon electrode holder (to be purchased separately)



Single-Chamber High-Pressure Electrochemical Cell

Model: P001-2


- This cell is upgraded from model P001-1 with an additional optical window.
- Available volumes: 50 mL & 100 mL; customized volumes are acceptable upon request.
- It is a photoelectrochemical cell equipped with a quartz glass optical window whose light transmittance is higher than 95%.
- Valve material: 304 stainless steel.
- Reference Electrode: Ag/AgCl electrode (purchased separately).
- Counter Electrode: Platinum plate electrode (purchased separately).
- Working Electrode: Glassy carbon electrode holder (purchased separately).



Small-Volume Single-Chamber High-Pressure Electrochemical Cell

Model: P001-10

- Material: Titanium (Ti)
- Maximum pressure resistance: 6 MPa
- Standard volume: 10 mL; custom volumes are available upon request
- Valve material: 304 stainless steel
- Reference Electrode: Silver/Silver Chloride Electrode (to be purchased separately)
- Counter Electrode: Platinum Plate Electrode (to be purchased separately)
- Working Electrode: Glassy Carbon Electrode Holder (to be purchased separately)



Model	Specification	Price	Remarks
P001-1	50&100ml	16000	
P001-2	50 mL & 100 mL, with optical window	17500	
P001-10	10ml	18500	
High-Pressure Resistant Electrode Holder		680	
High-Pressure Resistant Platinum Plate Electrode		780	
High-Pressure Resistant Reference Electrode		560	
All listed dimensions are standard specifications. Customized specifications are available upon request. Prices are subject to adjustment without prior notice, and the latest official quotation shall prevail.			


Committed to the R&D and manufacturing of electrochemical equipment.

PressureCell High-Pressure Electrochemical Cell Series

Dual-Chamber High-Pressure Electrochemical Cell (Internally Replaceable Membrane)


Model: P002-1

- Material: Titanium (Ti)
- Maximum pressure resistance: 6 MPa
- Standard volume: 20 mL + 20 mL
- Valve material: 304 stainless steel
- Single chamber volume: 20 mL; customized volumes are available on request
- Adopts a three-electrode system
- The reference electrode and working electrode are placed in one chamber, while the counter electrode is arranged in a separate chamber
- Reference Electrode: Ag/AgCl electrode (to be purchased separately)
- Counter Electrode: Platinum plate electrode (to be purchased separately)
- Working Electrode: Glassy carbon electrode holder (to be purchased separately)



Dual-Chamber High-Pressure Electrochemical Cell (Internally Replaceable Membrane)

Model: P002-2



- This cell is upgraded from model P002-1 with an added optical window.
- Material: Titanium (Ti)
 - Maximum pressure resistance: 6 MPa
 - Standard volume: 20 mL + 20 mL
 - The optical window is made of quartz glass with a light transmittance higher than 95%.
 - Valve material: 304 stainless steel
 - Single chamber volume: 20 mL; customized specifications are available upon request.
 - Equipped with a three-electrode system.
 - The reference electrode and working electrode are placed in one chamber, while the counter electrode is arranged in an independent separate chamber.
 - Reference Electrode: Silver/Silver Chloride Electrode (to be purchased separately)
 - Counter Electrode: Platinum Plate Electrode (to be purchased separately)
 - Working Electrode: Glassy Carbon Electrode Holder (to be purchased separately)

Model	Specification	Price	Remarks
P002-1	20+20ml	5900	
P002-2	20+20ml	6600	
High-pressure Resistant Electrode Holder		230	
High-pressure Resistant Platinum Plate Electrode		260	
High-pressure Resistant Reference Electrode		190	
All listed dimensions are standard sizes, and customized specifications are available upon request. Prices are subject to revision without prior notice, and the latest official quotation shall prevail.			


Committed to the R&D and manufacturing of electrochemical equipment.

PressureCell High-Pressure Electrochemical Cell Series

Dual-Chamber High-Pressure Electrochemical Cell (Externally Replaceable Membrane)


Model: P003-1

- Material: Titanium (Ti)
- Maximum pressure resistance: 6 MPa
- Optional volumes: 50 mL + 50 mL, 100 mL + 100 mL
- Valve material: 304 stainless steel
- Adopts a three-electrode system
- The reference electrode and working electrode are placed in one chamber, while the counter electrode is housed in a separate independent chamber
- Reference Electrode: Silver/Silver Chloride Electrode (to be purchased separately)
- Counter Electrode: Platinum Plate Electrode (to be purchased separately)
- Working Electrode: Glassy Carbon Electrode Holder (to be purchased separately)



Dual-Chamber High-Pressure Electrochemical Cell (Externally Replaceable Membrane)

Model: P003-2



- This cell is upgraded from Model P003-1 with an additional optical window.
- Material: Titanium (Ti)
 - Maximum pressure resistance: 6 MPa
 - Available volume options: 50 mL + 50 mL, 100 mL + 100 mL
 - The optical window is made of quartz glass with a light transmittance greater than 95%.
 - Valve material: 304 stainless steel
 - It adopts a three-electrode system.
 - The reference electrode and working electrode are placed in one chamber, and the counter electrode is arranged in an independent separate chamber.
 - Reference Electrode: Ag/AgCl electrode (to be purchased separately)
 - Counter Electrode: Platinum plate electrode (to be purchased separately)
 - Working Electrode: Glassy carbon electrode holder (to be purchased separately)

Model	Specification	Price	Remarks
P003-1	50+50ml	12000	
P003-1	100+100ml	13000	
P003-2	50+50ml	13000	
P003-2	100+100ml	14000	
High-pressure Resistant Electrode Holder		230	
High-pressure Resistant Platinum Plate Electrode		260	
耐高压参比电极		20	
所有尺寸为常用尺寸，可根据要求特殊定做；价格若有变化，以最新价格为准			

Committed to the R&D and manufacturing of electrochemical equipment.

PressureCell High-Pressure Electrochemical Cell Series

Gas Diffusion High-Pressure Flow Test Cell

Model: PFC- 1 / PFC-2

Performance Specifications

- Flow rate setting range: 0.01~50.00 mL/min, setting step: 0.01 mL/min
- Flow rate accuracy: ± 1.0% (test condition: 10.00 mL/min, 8.5 MPa, water, ambient temperature)
- Flow rate stability: RSD ≤ 0.3% (test condition: 10.00 mL/min, 8.5 MPa, water, ambient temperature)
- Maximum operating pressure:
 - 30 MPa (flow rate 0.10~20.00 mL/min)
 - 20 MPa (flow rate 20.01~50.00 mL/min)
- Pressure accuracy: Displayed pressure error within ±3% or 0.5 MPa
- Pressure pulsation: ≤0.4 MPa (flow rate 10.00 mL/min, pressure 8.5±1.5 MPa)
- Pump sealing performance: Under 30 MPa pressure for 10 minutes, pressure drop ≤ 1.5 MPa
- Communication interface: RS485

Flow Cell Parameters

- Cell body material: Titanium (Ti)
- Cell volume: 1 mL
- Cell dimension: 50 mm × 50 mm
- Internal channel size: 10 mm × 10 mm × 10 mm

Physical Specifications

- Weight: 12 kg
- Power supply: AC 220V(± 10%), 50 Hz
- Power consumption: 200 W
- Overall dimension: 420 mm × 300 mm × 175 mm (Length × Width × Height)



Model : PFC-1



Model : PFC-2

Model	Specification	Price	Remarks
PFC-1	10*10	42000	Shared channel for anode and cathode
PFC-2	10*10	62000	Separate independent channels for anode and cathode
All listed dimensions are standard specifications; customized dimensions are available upon request. Prices are subject to revision without prior notice, and the latest official quotation shall prevail.			

Committed to the R&D and manufacturing of electrochemical equipment.

PressureCell High-Pressure Electrochemical Cell Series

Photocatalytic High-Pressure Electrochemical Cell

Model: P004

Cell body material: High-purity Titanium

Optical window material: Quartz glass (light transmittance > 95%)

Inner cell material: High borosilicate glass

This electrolytic cell supports vacuum pumping operation.




Model	Specification	Price	Remarks
P004-1	单层 50ml	2000	
P004-1	双层 50ml	4300	
All listed dimensions are standard specifications. Customized specifications are available upon request. Prices are subject to adjustment without prior notice, and the latest official quotation shall prevail.			

Swagelok-Type Battery Test Cell (Three-Electrode System)

Single-Function Cell Series

Model: B001-1


Cell body material: PEEK
Reference electrode: Silver/Silver Chloride (Ag/AgCl) electrode
The conductive medium connecting the positive and negative electrodes is a glassy carbon electrode (GC, diameter 3 mm)
The positive and negative electrodes are test sample wafers, with a separator membrane sandwiched between the two sample wafers
Designed for simulative testing of coin cells
Tighten the glassy carbon electrodes on both sides to compress the positive and negative electrodes for electrical conduction, so as to realize battery testing
Unscrew the reference electrode port to add electrolyte externally
Applicable sample wafer diameters: 10 mm / 12 mm / 16 mm



Swagelok-Type Battery Test Cell (Two-Electrode System)

Model: B001-2

Cell body material: PEEK
The conductive medium connecting the positive and negative electrodes is glassy carbon electrode (GC, diameter 3 mm)
The positive and negative electrodes are test sample wafers, with a separator membrane sandwiched between the two sample wafers
Applied to simulated testing of coin cells
Tighten the glassy carbon electrodes on both sides to compress the positive and negative electrodes for electric conduction and realize battery testing
Unscrew the liquid inlet/outlet screw on the top, which is equipped with a gas phase gasket inside
Compatible sample wafer sizes: 10 mm / 12 mm / 16 mm



Model	Specification	Price	Remarks
B001-1		940	
B001-2		840	
All listed dimensions are standard sizes, and customized specifications are available upon customer request. Prices are subject to revision without prior notice, and the latest official quotation shall prevail.			

Committed to the R&D and manufacturing of electrochemical equipment.

Single-Function Cell Series

[illegible]

Model: B001-3


[illegible]

000 000000000 0 0000 000000000 00 0000000 000 0000000 000000000 0 00000 00000 00000000 000000 000000 00000000 000000 0000 0 0


000 0000000 000 00000000 0000000000 000 0000 000 000 0000000 000 0 0000000 000 0 0000000000000000 00000 0000 0000 000 00 0 000 000 00000

[illegible]

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 104

[illegible][illegible][illegible]

□ □ □ □ □ □ □ □ □ □

[illegible]

Model	Specification	Price	Remarks
B001-3		1100	
B001-4		1100	
All listed dimensions are standard common sizes; customized specifications are available upon request. Prices are subject to change without prior notice, and the latest quotation shall prevail.			


Single-Function Cell Series

1. 该系列电解池采用全不锈钢材质，耐腐蚀性强，使用寿命长。

2. 该系列电解池结构紧凑，操作简便，维护方便。

3. 该系列电解池适用于各种电化学实验，如电沉积、电氧化、电还原等。

4. 该系列电解池可根据客户需求进行定制，满足不同实验需求。




1. 该系列电解池采用全不锈钢材质，耐腐蚀性强，使用寿命长。

2. 该系列电解池结构紧凑，操作简便，维护方便。

3. 该系列电解池适用于各种电化学实验，如电沉积、电氧化、电还原等。

4. 该系列电解池可根据客户需求进行定制，满足不同实验需求。



Model	Specification	Price	Remarks
Zn-1	30ml、50ml	300	
Zn-2	30ml、50ml	300	
All listed sizes are standard specifications; customized fabrication is available upon demand. Prices are subject to adjustment, and the latest quotation shall prevail.			

Single-Function Cell Series

一、产品概述

二、产品特点

三、产品应用


四、产品优势

五、产品规格

六、产品参数

七、产品使用

八、产品维护



一、产品概述

二、产品特点

三、产品应用


四、产品优势

五、产品规格

六、产品参数

七、产品使用

八、产品维护




Model	Specification	Price	Remarks
C034-1		1950	
C034-2		1950	
本产品为实验室常用电极，适用于各种电化学实验。本产品采用优质材料制造，性能稳定，使用寿命长。本产品结构紧凑，操作方便，是实验室必备的电极之一。			

Single-Function Cell Series


Single-Function Cell Series

Single-Function Cell Series



Single-Function Cell Series


Single-Function Cell Series



Model	Specification	Price	Remarks
DQ-1	50*50mm	950	
DQ-2	50*50mm	1300	
All listed dimensions are standard common sizes, and customized production is available upon specific requirements. Prices are subject to change, and the latest quotation shall be taken as the valid standard.			

Single-Function Cell Series

A row of ten rectangular boxes. From left to right, the first box is empty. The second box contains a single vertical line. The third box is empty. The fourth box contains a single vertical line. The fifth box contains two vertical lines. The sixth box is empty. The seventh box contains two vertical lines. The eighth box is empty. The ninth box is empty. The tenth box is empty.

[illegible]

Single-Function Cell Series

该系列电化学池适用于各种电化学实验。

该系列电化学池具有以下特点：

- 1. 采用高品质材料制造，耐腐蚀性强。
- 2. 设计紧凑，占地面积小。
- 3. 操作简便，易于维护。
- 4. 具有良好的密封性能，防止电解液泄漏。
- 5. 适用于各种电化学实验，如电沉积、电氧化、电还原等。
- 6. 可根据客户需求定制不同规格和配置。
- 7. 价格实惠，性价比高。

€:560



Committed to the R&D and manufacturing of electrochemical equipment.

Instrument & Equipment Series

□ □ □ □ □ □ □ □

በጣም የሚታዩት ምንም ዓይነት ምርመራ ሲያደርጉ ለራሳችን ምርመራ ማድረግ አለብን። ምንም ዓይነት ምርመራ ሲያደርጉ ለራሳችን ምርመራ ማድረግ አለብን። ምንም ዓይነት ምርመራ ሲያደርጉ ለራሳችን ምርመራ ማድረግ አለብን።

[illegible][illegible]

□ □ □ □ □ □ □ □ □ □ □ □ □

€ :940



□ □ □ □ □ □ □ □ □ □ □ □

[illegible][illegible]

1111111111111111


☐ ☐ ☐ ☒ ☐ ☐ ☐ ☐ ☒ ☒ ☐ ☐ ☐ ☐ ☐ ☐

□□□□ □□□□ □□□□□□□□ □□ □□□□ □□

[illegible]

□□□ □□□□□□□□ □□□ □


€:1100



Committed to the R&D and manufacturing of electrochemical equipment.

Instrument & Equipment Series

□ □ □ □ □ □ □ □ □ □ □ □

[illegible]

Schematic Diagram of Shearing Force

0000000000000000 000000
 0000 0000 0000000000 000 0 000 00
 0 00000 00000000000 000
 0000 00000000000 000 0
 00000 00000000000 00 0
 0000 00000000000 0 0
 0 000000 00 00000000000 0 000 0 000 0 0

€:740

[illegible][illegible]

1. 2019 年 12 月 31 日，本公司 2019 年度股东大会审议通过《关于 2019 年度利润分配预案的议案》，以 2019 年 12 月 31 日总股本 100,000,000 股为基数，向全体股东每 10 股派发现金股利 1.00 元（含税），共计派发现金股利 10,000,000.00 元。

€ :2400



Committed to the R&D and manufacturing of electrochemical equipment.

Instrument & Equipment Series

[illegible]

□ □

QUESTION

[illegible][illegible][illegible]

A barcode consisting of vertical black bars of varying widths on a white background.

[illegible]

Abstract

[illegible][illegible][illegible]

— 100 —

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □

0000 00000000 0 00000000 0000 00000000000000 0000 00 000000 0000 0000

[illegible][illegible][illegible]

00 00000000000000 00000000000000

[illegible]

A standard linear barcode consisting of vertical black bars of varying widths on a white background.

□ □ □ □ □ □ □ □ □ □

00000000 0 000 0 00000000 000 00000000 0000 000 0000 00000000000000000000000000000000 0 0000 00000000 000000000000 0000000000 00000000 00000000

[illegible][illegible][illegible]

Abstract

[illegible][illegible][illegible]

€ :2200



Instrument & Equipment Series

该系列仪器为电化学研究提供了全面的解决方案。

一、仪器特点

该系列仪器具有高精度、高稳定性、高灵敏度等特点。其采用先进的电化学理论和技术，能够实现多种电化学测试，如恒电位扫描、恒电流扫描、循环伏安法等。此外，该系列仪器还具有操作简便、维护方便、使用寿命长等优点。其广泛应用于材料科学、化学、生物、环境等领域，为科研人员提供了强大的研究工具。

该系列仪器的核心部件均采用进口名牌材料，确保了仪器的稳定性和精度。同时，我们还配备了专业的技术支持团队，为用户提供全方位的服务。无论是仪器的选型、安装、调试，还是日常使用中的故障排除，我们都将竭诚为您服务。

该系列仪器的外观设计简洁大方，操作界面友好。通过内置的触摸屏，用户可以轻松设置实验参数，实时监控实验进程。此外，我们还提供了丰富的实验模板，方便用户快速上手。对于数据记录和分析，我们配备了专业的软件，能够实现数据的自动采集、存储和分析，大大提高了实验效率。

该系列仪器的性能卓越，能够满足各种复杂的实验需求。无论是基础研究还是应用研究，该系列仪器都是您的不二之选。我们相信，通过使用该系列仪器，您将能够获得更加准确、可靠的实验结果，为您的科研工作提供有力支持。

€:25000

二、仪器应用

该系列仪器广泛应用于材料科学、化学、生物、环境等领域。

在材料科学领域，该系列仪器可用于研究材料的电化学性能。

在化学领域，该系列仪器可用于研究化学反应的机理。

在生物领域，该系列仪器可用于研究生物电化学过程。

三、仪器优势

该系列仪器具有以下优势：

1. 高精度：采用先进的电化学理论和技术，能够实现高精度的电化学测试。

2. 高稳定性：核心部件采用进口名牌材料，确保了仪器的稳定性和精度。



3. 高灵敏度：能够检测到微弱的电化学信号，提高了实验的灵敏度。

4. 操作简便：配备专业的技术支持团队，为用户提供全方位的服务。

5. 维护方便：采用模块化设计，方便用户进行日常维护和故障排除。


6. 使用寿命长：采用优质材料，确保了仪器的使用寿命。

7. 数据记录和分析：配备专业的软件，能够实现数据的自动采集、存储和分析。




Shaft Section Inert Gas Purging Mechanism


该装置主要用于在电解过程中对电解液进行惰性气体（如氮气）的连续吹扫，以防止电解液在电极表面发生氧化或还原反应，从而保证测试结果的准确性和稳定性。



该装置主要用于在电解过程中对电解液进行惰性气体（如氮气）的连续吹扫，以防止电解液在电极表面发生氧化或还原反应，从而保证测试结果的准确性和稳定性。

该装置主要用于在电解过程中对电解液进行惰性气体（如氮气）的连续吹扫，以防止电解液在电极表面发生氧化或还原反应，从而保证测试结果的准确性和稳定性。该装置主要用于在电解过程中对电解液进行惰性气体（如氮气）的连续吹扫，以防止电解液在电极表面发生氧化或还原反应，从而保证测试结果的准确性和稳定性。



[illegible]

Potentiostat/Galvanostat ECstat-302 (Product Code: 21050)

	Item	Specification
P.S.	Max Output Voltage / Max Output Current	±13 V/ ±30 <u>mA</u>
P.S.	Max Output Voltage / Max Output Current	±13 V/ ±30 <u>mA</u>
P.S.	Control Potential	±6.4 V
P.S.	Current Range	±3 <u>μA</u> , ±30 <u>μA</u> , ±300 <u>μA</u> , ±3 <u>mA</u> , ±30 <u>mA</u> (Total 5 ranges + Auto range)
P.S.	Min Potential Resolution / Min Current Resolution	0.2 <u>mV</u> / approx. 180 <u>fA</u> (at 3 <u>μA</u> range)
G.S.	Max Output Current / Max Output Voltage	±30 <u>mA</u> / ±13 V
G.S.	Potential Range	±12.8 V (Total 1 range)
G.S.	Min Setting Resolution / Min Potential Resolution	100 <u>pA</u> (below 3 <u>μA</u>) / approx. 800 <u>nV</u>
	Noise Filter	1 Hz, 10 Hz, 100 Hz, OFF
	Noise Filter	1 Hz, 10 Hz, 100 Hz, OFF
	Control Interface	USB / Wireless LAN IEEE802.11b/g/n
	Power	DC6V 1.8A AC adapter included
	Dimensions / Weight	W190 mm×D100 mm×H43 mm (excluding protrusions) / approx. 0.9 kg
	Dimensions / Weight	USB memory (<u>ECstat</u> Software / manual), battery cable, AC adapter, alligator clips, lead resistor
	Accessories	USB memory (<u>ECstat</u> Software / manual), battery cable, AC adapter, alligator clips, lead resistor, USB data cable, test certificate

Committed to the R&D and manufacturing of electrochemical equipment.

Instrument & Equipment Series

Software (ECstat Advance) (Product Code: 21051)

PC Specification	OS: Windows7, Windows8.1, Windows10, Windows11
PC Specification	OS: Windows7, Windows8.1, Windows10, Windows11
Internet Connection	Required only during installation, depending on OS status
Required Interface	USB 2.0 or 3.0×2 slots or more
Accessories	USB memory, USB dongle

ECstat Current Booster ECboost-4002 (Product Code: 21064)


	Item	Specification
P.S.	Max Output Voltage / Max Output Current	± 13 V/ ± 300 mA
P.S.	Max Output Voltage / Max Output Current	± 13 V/ ± 300 mA
P.S.	Control Potential	± 6.4 V
P.S.	Current Range	± 3 μ A, ± 30 μ A, ± 300 μ A, ± 3 mA, ± 30 mA, ± 300 mA (Total 6 ranges)
P.S.	Min Potential Resolution / Min Current Resolution	0.2 mV/ 100 pA (at 3 μ A range)
G.S.	Min Potential Resolution / Min Current Resolution	± 300 mA/ ± 13 V
G.S.	Max Output Current / Max Output Voltage	± 0.64 V, ± 1.28 V, ± 6.4 V, ± 12.8 V (Total 4 ranges)
G.S.	Voltage Range	100 pA/ 20 μ V (at ± 0.64 V range)
G.S.	Min Setting Resolution / Min Potential Resolution	100 pA/ 20 μ V (at ± 0.64 V range)
	Control Interface	Connector harness
	Control Interface	Connector harness
	Power Supply	100~240 VAC, 50/60 Hz
	Dimensions / Weight	W190 mm×D100 mm×H75 mm (excluding protrusions) / approx. 0.85 kg
	Dimensions / Weight	W190 mm×D100 mm (no condensation) (excluding protrusions) / approx. 0.85 kg
	Operating Temperature/Humidity	5~40°C/ 10~90% (no condensation)

Committed to the R&D and manufacturing of electrochemical equipment.

Instrument & Equipment Series


该系列设备主要用于实验室电化学测试，具有结构紧凑、操作简便、性能稳定等特点。

该系列设备广泛应用于材料科学、化学、生物等领域。



该系列设备采用高品质材料制造，具有良好的耐腐蚀性和机械强度。

该系列设备具有多种规格，可根据实验需求进行选择。




Committed to the R&D and manufacturing of electrochemical equipment.

Instrument & Equipment Series


该系列设备为实验室提供高精度、高稳定性的电化学测试平台。

该系列设备 140 系列为实验室提供高精度、高稳定性的电化学测试平台。



该系列设备为实验室提供高精度、高稳定性的电化学测试平台。

€ 4100






Instrument & Equipment Series

Electrochemical Instrument

The electrochemical instrument is a specialized device used for studying electrochemical reactions and processes. It typically consists of a power source (potentiostat/galvanostat), a reference electrode, a working electrode, and a counter electrode. The instrument is used to measure the current and potential of an electrochemical cell under various conditions, such as different electrolyte concentrations, temperatures, and electrode materials. It is widely used in fields like materials science, chemistry, and environmental science for the study of corrosion, electrocatalysis, and energy storage.

€ 70




Electrochemical Instrument

The electrochemical instrument is a specialized device used for studying electrochemical reactions and processes. It typically consists of a power source (potentiostat/galvanostat), a reference electrode, a working electrode, and a counter electrode. The instrument is used to measure the current and potential of an electrochemical cell under various conditions, such as different electrolyte concentrations, temperatures, and electrode materials. It is widely used in fields like materials science, chemistry, and environmental science for the study of corrosion, electrocatalysis, and energy storage.

Electrochemical Instrument



Electrochemical Instrument



High-Current Water Electrolysis