
THE MEANING MODEL: MINIMIZED GRAMMAR

TECHNICAL APPENDIX

Henrik Westerberg
Emergent Wisdom
henrik.westerberg@emergentwisdom.org

September 4, 2026

ABSTRACT

This appendix is a compact restatement of the definitions and rules explained in *The Meaning Model: Constructing Worlds and Stories at Progressive Resolution*. It adds no requirements: the paper is self-contained, and this reference groups the same account into record forms, obligations, selected-profile axioms, perspective queries, surface records, and operations. Book-specific choices remain non-normative, and profile rules bind only constructions that select them. Both presentations specify the target contract, not the current Rust host schema. Cut weights are the grammar’s only semantic numbers; externally grounded measurements remain typed Event data rather than another weighted relation.

Keywords Meaning Model, Grammar, Specification, Cut, Remainder, Lifecycle, Containment, Realization

Reading map. The paper’s *Grammar and Progressive Construction* section explains the records, context rules, lifecycle profile, and refinement contract collected here. *Concepts and Examples* covers grounding and its operators; *World, Understanding, and Story* covers projections, access, surfaces, and transactions. The Book profile and Appendix A explain the non-normative person vocabulary and constants. A substantive rule change must be reflected in both presentations; this reference is not a separate source of theory.

1 Conventions

Model.

A Meaning Model at declared resolution ρ is a finite tuple $\mathcal{M}_\rho = (\mathcal{C}, \mathcal{X}, \mathcal{E}, \mathcal{B}, \mathcal{K}, \mathcal{R}, \mathcal{L})$ of Concepts, Things, Events, Bindings, Cuts, Realizations, and typed links.

Shared address space.

A complete construction is the typed graph $\mathcal{G}_\rho = (\mathcal{M}_\rho, \mathcal{U}, \mathcal{D}, \mathcal{L}_\times)$, where $\mathcal{U}$ contains Understanding Nodes, $\mathcal{D}$ contains Document Nodes, and $\mathcal{L}_\times$ contains links within and across the world, understanding, and document surfaces. All three surfaces use one identifier space. Membership in the same graph permits exact reference; it does not give an Understanding Node, Document Node, and Event the same authority, clock, composition rule, or validation contract.

Identity.

Every record reference identifies a logical identity and an exact revision; `id` below abbreviates the immutable revision address. Under the selected construction profile, a change creates a new revision address and a supersedes link (A11); the logical identity of a Thing or Concept does not thereby change. A Concept identifier is stable across grounding versions. A profile may identify a grounding version g by the content hash of its declared bundle serialized in canonical order, as the Book does with Sema; a Realization’s g names the exact bundle it used. Content addressing is an identity convention, not a seventh record form or a universal requirement of the core grammar.

Provenance.

Every record carries p = (author or generator identifier, commit, construction time, evidence references).

Clocks.

Story time T_s (intervals of Events), construction time T_c (commits), discourse order T_d (Document Node positions). A record states which clock each of its times uses.

Intervals.

A resolved interval is $I = [t_0, t_1) \subset T_s$. An ongoing end or unknown bound is explicitly tagged; duration $|I| = t_1 - t_0$ is computed only for two finite resolved bounds. A moment Event has a tagged instant t with support $\{t\}$, not a positive duration. Unresolved interval checks return **untestable**, not **pass**. Imagined and counterfactual timelines name their own temporal frame; comparisons and temporal containment require the same frame.

Roots (selected profile).

The Universe U is a Thing and History $H = \ell(U) \in \mathcal{E}$ is its lifecycle Event. Every accepted-world lifecycle and Event is contained by History. Time is expressed through History and the intervals of its descendants, not by a separate Thing. A candidate is not part of History because it carries a date; it enters only through an accepted commit (A11).

2 Record forms

```

Concept { id, names, typed relations, constraints,
          grounding records, provenance }
Thing { id, kind, identity boundary, continuity criterion,
        typed links, provenance }
Event { id, kind, interval, typed world data, optional description,
        direction, typed links, provenance }
Binding { id, event, role, thing, interval, provenance }
Cut { id, parent Event, question, profile, divided unit,
      keyed weighted answers, keyed remainder, optional conditioning address,
      constraints, provenance }
Realization { id, purpose, context parent, target, concept,
              grounding version, optional alignment, evidence, provenance }

```

Answer and remainder addresses pair the Cut revision with a local key; they are not additional record forms.

Concept

$c = (\text{id}, N, \text{Rel}, \text{Constr}, G, p)$. N names; $\text{Rel} \subseteq \text{Kind} \times \mathcal{C}$ typed relations (specialization, opposition, expression, and other declared kinds); Constr constraints; G grounding records, each of depth relational, representative prototype, exemplar, or canonical model, each versioned.

Thing

$x = (\text{id}, \text{kind}, \partial x, \kappa_x, \mathcal{L}_x, p)$. ∂x identity boundary; κ_x continuity criterion.

Event

$e = (\text{id}, \text{kind}, I_e, S_e, d_e, D_e, \mathcal{L}_e, p)$. State S_e is a finite map from fields to categorical conditions or typed world data. A numeric datum is admissible only when it has an independently interpretable unit or measurement protocol, such as a date, duration, count, currency amount, distance, or physical measurement; measurement uncertainty may accompany it. The optional text d_e is a readable description of this exact Event record and version; it is not a Document Node and does not change the structured record. A candidate description acquires accepted-world authority only if its candidate is committed. Interpretive judgments such as trust, intelligence, importance, and concept fit are Events and Cuts, not numerically anchored entries in S_e . Direction D_e is a typed continuation specification (law, constraint set, predictor, or a reference to a direction Cut) or $\perp$; every numerical forecast allocation is a direction Cut.

Binding

$b = (\text{id}, e, r, x, I_b, p)$ with $I_b \subseteq I_e$; r a typed role.

Cut $K = (\text{id}, P, q, \pi, u_K, \{(k_i, a_i, w_i)\}_{i=1}^n, (k_\perp, w_\perp), h, \text{Constr}, p)$. Parent $P \in \mathcal{E}$ is an Event; q the question; $\pi \in \{\text{allocation}, \text{sequential}, \text{direction}\}$; children a_i as fixed by π (Axiom A6); u_K the one divided unit.

Distinct local keys $k_i, k_{\perp}$ make each answer and the remainder addressable as (id, k) , including zero-weight slots. These are addresses within a Cut revision, not additional world records. Optional h names the answer whose share this Cut conditions on; P remains its Event parent. A judgment about another record or fragment uses an assessment Event contained by the process whose perspective it expresses as P and an about link to its target.

Realization

$r = (\text{id}, \text{purpose}, P, \tau, c, g, \sigma, \text{ev}, p)$. $\text{purpose} \in \{\text{define}, \text{describe}\}$; P is the Event or surface node that supplies its structural context; τ an addressable subgraph of $\mathcal{M}_\rho$; g a grounding version of c ; σ optional role alignment. The correspondence is unweighted. A graded judgment of fit is a separate Cut on an assessment Event under A10.

Typed links.

Link	Domain $\times$ codomain	Meaning
contains	Event $\times$ Event	temporal containment of occurrences in one frame
occurs-within	Event $\times$ Event	episode located inside a lifecycle or period
context-parent	record $\times$ context root or record	unweighted authority ancestry; not a claim of temporal inclusion
updates	Event $\times$ Event field or condition	unweighted assertion that the first Event changes the named datum or condition of the second
about	record $\times$ record	reference without participation or state change
supersedes	record $\times$ record	predecessor preserved; lineage changes; carries scope and clock
realizes-forecast	Event $\times$ Cut slot	identifies the selected direction answer, including the remainder

A multi-Thing relation is written as a joint Event, with a Binding for every role; the grammar does not author direct edges between Things. Outside Event mereology, records use unweighted context-parent links. Context roots have labels such as *accepted-world*, *inner*, *understanding*, *document*, and *candidate*; authority inheritance stops at the nearest such root. A model-context Event may additionally declare *remembered*, *imagined*, or *counterfactual* mode and a source reference. Its represented Events need not occur during the mental act that hosts this context. Thus an inner Event can be connected to History through a person’s life without becoming a public-world claim.

Only a Cut creates weighted parenthood: it partitions one stated unit among exclusive sibling answers and a remainder. Event containment and ordinary typed links remain unweighted, so linked Events may overlap or coexist. Event payloads with external units are data, not a third kind of parent relation.

3 Core obligations and selected-profile axioms

A3–A5, A10, and A12 are core obligations of every Meaning Model. A1, A2, A6–A9, A11, and A13 are axioms of the selected construction profile. The labels below keep that boundary visible: using the six records alone does not commit another construction to this lifecycle, time, or transaction policy.

A1 Profile—Lifecycle. For every $x \in \mathcal{X}$ there is exactly one $\ell(x) \in \mathcal{E}$ of kind *lifecycle* with Binding $(\ell(x), \text{subject}, x, I_{\ell(x)})$. $I_{\ell(x)}$ is the modeled lifetime in the selected branch’s active view. Superseded lifecycle revisions remain addressable but are not additional current lives. All state of x is carried by $\ell(x)$ or by Events bound to x . The declared continuity criterion κ_x decides whether a change preserves this Thing or creates a successor; split and merge Events bind the distinct identities they connect.

A2 Profile—Agency boundary. For every Binding (e, r, x, I_b) with r an ordinary participant role, $I_b \subseteq I_{\ell(x)}$. Explicit created and terminated boundary roles may bind the appropriate lifecycle endpoint; they do not imply activity beyond it. A moment participant must lie inside its life interval. Other references outside that interval use about.

A3 Core—Perspective by containment. Every Cut has an Event parent P . A perspective-dependent belief, appraisal, estimate, or judgment is a distinct Event beneath a declared perspective root. The Event’s Cuts inherit that context from P . Only edges explicitly declared *authority-parent* participate in this inheritance: context-parent links and any containment links assigned that role by the profile. Every path must resolve to the same nearest context root, or the record is rejected as ambiguous. Occurrence, reference, evidence, and grounding links alone confer neither authority nor access. Profiles define admissible roots and paths; the selected lifecycle profile requires a person’s perspective process to descend through that person’s lifecycle, while a constructor or evaluator process descends from its named understanding-process root. A joint or public Event remains in shared History and

identifies people or other Things through Bindings. No independently authored perspective field may contradict these structural paths.

A4 Core—Local simplex. For every Cut,

$$w_i \geq 0, \quad w_{\perp} \geq 0, \quad \sum_{i=1}^n w_i + w_{\perp} = 1, \quad (1)$$

the children are mutually exclusive as shares of the declared unit u_K , and a record appearing under two Cuts has one weight in each. There is no global mass. Exclusivity concerns the allocated portions, not whether the referenced Events can coexist. An attribution over interacting causes must declare how shared responsibility is assigned, for example to an explicit joint answer; normalization alone cannot resolve double counting. Conditioning addresses must resolve, form no cycle, and identify the precise share whose conditional unit is divided.

A5 Core—Event processes and world data. When a longer Event-process is opened into shorter happenings without a divided unit, the shorter Events are connected by `contains`, `occurs-within`, or `updates`; `about` is a reference, not a part relation. These links carry no weights, need not be exclusive, and assert no numerical recomposition. A numerical allocation over the same Events requires a separate Cut naming its question and unit. Events may also carry categorical facts and externally interpretable measurements. Such data record what happened; they do not assign semantic degree, importance, or psychological intensity.

A6 Profile—Named Cut families. allocation Children reference existing records or items of a frozen vocabulary V_q . Named questions: *facet* ($a_i \in V_q$, closed), *contribution* (a_i among Things bound to P), *cause* (a_i among existing wants, beliefs, actions, circumstances, or Events; u_K is explanatory responsibility in the parent assessment’s perspective).

sequential Children $e_1, \dots, e_n \in \mathcal{E}$ with $I_{e_i} \subseteq I_P$ pairwise disjoint and ordered;

$$w_i = \frac{|I_{e_i}|}{|I_P|}, \quad w_{\perp} = 1 - \sum_i w_i. \quad (2)$$

Shares are derived, never elicited. The parent interval must have finite positive duration. An open lifecycle is partitioned only over an explicitly bounded observation Event; an infinite or unresolved denominator is never used.

direction Children are candidate continuations of P at a declared horizon τ ; they are not parts of P . Weights are declared either a proposal policy or a forecast probability distribution before observing the outcome. A proposal policy guides construction; it does not assert world likelihood. Forecasts can be scored before they are well calibrated; calibration is an empirical property, not permission to call them probabilities. Alternatives must be exclusive at the stated horizon. At most one answer is realized, as a new Event with a `realizes-forecast` link to its slot; unrealized siblings are retained. Drawing the remainder requests an unnamed continuation, not silent renormalization over named answers.

A7 Profile—Encapsulation and inherited presence. Write $B(e, r, x, t)$ when a Binding assigns x role r in e and t lies in both the Event and Binding intervals. For $x \in \mathcal{X}$ and $t \in T_s$,

$$\begin{aligned} \text{Enc}(x, t) = \{ & y : \exists e \in \mathcal{E} [(\text{kind}(e) = \text{physical-part} \wedge B(e, \text{whole}, x, t) \wedge B(e, \text{part}, y, t)) \\ & \vee (\text{kind}(e) = \text{membership} \wedge B(e, \text{group}, x, t) \wedge B(e, \text{member}, y, t)) \\ & \vee (\text{kind}(e) = \text{presence} \wedge B(e, \text{place}, x, t) \wedge B(e, \text{occupant}, y, t))] \}. \end{aligned} \quad (3)$$

Enc is unweighted. Rosters and co-presence are defined from the same Bindings. No containment among Things is authored directly. A location-propagating physical-part relation may derive the part’s coarse presence from the whole until a detach Event ends that relation. When extents are modeled, the child’s extent lies inside the whole’s at the profile’s declared tolerance. Social, institutional, and documentary membership never propagates location.

A8 Profile—Periods and episodes. The periods of x are the children of one authoritative sequential Cut of a bounded lifecycle interval, using an observation Event when the whole life is not resolved. An episode is an Event with an `occurs-within` link to $\ell(x)$ or to a period; episodes may overlap. Phases are children of sequential Cuts of episodes.

A9 Profile—Mixture law. Let K be a sequential Cut of a finite, positive-duration P with children e_i , and let F_i be facet Cuts on the e_i with the same question, unit, vocabulary, remainder meaning, and governing perspective. If the children fully cover P , the facet vector is

$$f_P = \sum_i \lambda_i f_i, \quad \lambda_i = \frac{|I_{e_i}|}{|I_P|}. \quad (4)$$

If uncovered duration has share $\lambda_\perp > 0$, the complete vector is defined only when an explicit compatible facet vector $f_\perp$ describes that uncovered interval, in which case $f_P = \sum_i \lambda_i f_i + \lambda_\perp f_\perp$. Otherwise the derived view reports the known partial contribution $\sum_i \lambda_i f_i$, coverage $1 - \lambda_\perp$, and temporal remainder; it does not invent or claim a complete parent vector. When F_P is already committed, even partial detail must leave a feasible residual:

$$r = f_P - \sum_i \lambda_i f_i \geq 0 \quad \text{componentwise,} \quad \sum_v r_v = \lambda_\perp. \quad (5)$$

If $\lambda_\perp > 0$, $r/\lambda_\perp$ is the required residual composition, not evidence about the unobserved interval. For full coverage $r = 0$ recovers the mixture equation. A declared numerical tolerance may bound these tests; it cannot authorize hidden renormalization. Infeasible detail is rejected or submitted as an explicit revision of F_P . Tolerances are validator settings, not world facts. The general conservative-opening contract is given below the interface table; A9 is its temporal specialization.

A10 Core—Realization. A Realization is an unweighted correspondence between an addressable fragment and a Concept at grounding version g . **define** associates c with an idealized fragment written in the record forms of Section 2; **describe** requires the grounding version used. The optional σ records the role alignment. When graded fit is required, create an assessment Event beneath the relevant declared perspective process, link it about the target, and attach a Cut under the question “how does one unit of this assessment of fit to c divide?” Its mutually exclusive answers are **matches**, **does-not-match**, and **remainder**:

$$w_{\text{match}} + w_{\text{nonmatch}} + w_\perp = 1. \quad (6)$$

The fit degree is w_{match} , meaningful only beside its siblings. Different Concepts are evaluated by separate assessment Events and Cuts and need not compete. A canonical fragment may itself be opened structurally; component-level match judgments use one assessment Event and local Cut per component. No independent Realization degree exists. Fit and confidence answer different questions. When needed, a separate assessment Cut allocates evidential confidence among declared rival interpretations and unresolved evidence. Its weights never multiply or replace the fit Cut. A strongly supported mismatch and a weakly supported match are therefore distinct. A fit remainder means unassigned fit under its own question, not automatically lack of evidence; missing evidence is reported separately.

A11 Profile—Decide. A candidate envelope names its base commit and branch, proposed records and links, replacement map, read dependencies, applicable contracts and tolerances, and refinement witness when needed. This is transaction metadata, not a seventh world record. A branch has one active revision per logical identity. A stale base or changed read dependency rejects the candidate; rebasing requires renewed validation. Reject leaves the active graph unchanged, although a construction log may retain the rejected candidate and explanation. Commit appends one immutable cross-surface snapshot and advances its head atomically. Revision explicitly replaces named active revisions, preserves their history, and revalidates dependents under the profile’s declared dependency rules. Affected derived views and passages must be regenerated or marked stale, never silently treated as current. Opaque operators must declare their read dependencies. Branches never merge merely because identifiers match.

A12 Core—Parsimony. A new record form is admitted only when a validator must distinguish two cases that differ in admissible targets, composition, authority, inference, or validation, and no existing form with typed fields can preserve the distinction.

A13 Profile—Progressive externalization. At declared purpose and resolution, a construction externalizes a record when it must persist across later commits, constrain a later Event, differ across perspective processes, or remain controllable and auditable. Other detail remains implicit until an opening condition is met. If a governing Cut exists, its unallocated share remains in that Cut’s remainder; no remainder is invented for an unweighted relation. This is a stopping rule, not a completeness claim.

4 Structural context, perspective projections, and estimates

Q1 Context paths. Authority-parent edges form an acyclic graph and obey A3’s unique-context rule. Temporal ancestry is queried separately. A record query returns its permitted parents and typed paths to the governing root, filtered by the requesting principal’s access policy before traversal or serialization. A rejected private reference does not expose the referenced content or its private ancestry. A Cut or slot query returns the complete permitted local Cut—parent Event, question, unit, keyed siblings, remainder, optional conditioning address, and recomposition rule—or denies that view as a whole. A semantic weight is never returned alone. An about, evidence, renders, or Realization target link is not a permission to traverse its target.

Q2 Projection. For an actor a , the full actor projection $\mathcal{M}_a(t)$ is derived from the belief, appraisal, expectation, and other representational Events under a ’s perspective root that are active at t , together with the accepted records reachable under Q3. Hypothetical targets remain linked from those inner Events rather than being promoted into accepted History. The operative model $\mathcal{M}_a^*(t) \subseteq \mathcal{M}_a(t)$ is the subset recruited for one decision or action. These projections represent and organize the actor’s conduct without assigning a separate perspective field to every record.

Q3 Access. $\text{Acc}(a, t)$ contains the exact content exposed by observations available to a , communications delivered to a , and a ’s own eligible earlier records, each available by cutoff t . The profile records observation scope and delivery time; presence merely makes an observation possible and does not reveal another actor’s inner state or every field of a nearby Event. A communication grants its delivered content, not its author’s whole model. Later evidence and constructor knowledge are excluded. Generation of a ’s speech, choice, or action conditions on an explicitly selected $\mathcal{M}_a^*(t)$ and $\text{Acc}(a, t)$ only.

Q4 Estimate. Observer o ’s estimate of a record θ associated with actor a is an Event e_{est} of kind **estimate**, under o ’s perspective root, with an about link to θ and evidence $\subseteq \text{Acc}(o, t)$. An estimate of categorical or externally measured world data may use the corresponding typed Event payload, with measurement error where applicable. An estimate of a semantic composition is instead a Cut K_{est} on e_{est} , compatible with the target Cut’s question, unit, vocabulary, and remainder; no interpretive vector is stored as Event payload. θ may itself be an estimate; nesting depth is frozen (first construction: ≤ 2).

Q5 Divergence (derived). For compatible Cuts K_{est} and K_θ ,

$$\delta = \text{TV}(K_{\text{est}}, K_\theta) = \frac{1}{2} \sum_{v \in V \cup \{\perp\}} |w_{\text{est}}(v) - w_\theta(v)|; \quad (7)$$

for comparable discrete fields $\delta = \mathbb{K}[\text{est} \neq \theta]$. An incompatible claim in $\mathcal{M}_a$ and accepted History may be queried as misperception; incompatible claims in $\mathcal{M}_a$ and $\mathcal{M}_b$ may be queried as disagreement. Absence, an unopened region, or unequal coverage is ignorance or noncoverage, not automatically error. δ is an external query or validation metric computed from Cut weights or categorical equality; it is not stored semantic content, an Event measurement, or a Cut.

5 Surface records (inside the construction graph)

Understanding Nodes and Document Nodes occupy the shared address space of $\mathcal{G}_\rho$ but remain outside the six world-record forms of $\mathcal{M}_\rho$.

```
UnderstandingNode { id, type, text, created at, typed parents, typed links, provenance }
DocumentNode { id, role, text, discourse position, optional narrator and viewpoint,
  typed parents, typed links, provenance }
```

S1 Understanding links: about, supports, contradicts, refines, answers, learned-from, supersedes. Document links: renders (story passage to Events), shaped-by (to Understanding Nodes), document-scoped contains and next.

S2 An Understanding Node is not an Event and carries no simplex or story-time interval. Its perspective and clock follow the unambiguous authority-parent paths to its named understanding-process root. Its governing interval may be derived from the commits that create and supersede it.

S3 A Document Node with role **story-passage** is not the record it renders. Document contains is not the Event containment of Section 2.

- S4** If a physical carrier of a stored thought must itself be modeled, the note, document, or other representational token is a Thing; its creation, reading, revision, and supersession are Events. Its text is not an Event.
- S5** The Understanding Nodes beneath a named understanding-process root and their links form that process's Understanding Graph. A node may discuss any addressed record without borrowing that record's authority. Actor-inner Events remain the separate perspective projection defined by Q2, while story-passage Document Nodes retain what a character or narrator actually expresses.
- S6** A Concept's reasoning history is not stored as an opaque Concept field. For one understanding root, it is the ordered subgraph of nodes that address the Concept identifier, grounding versions, **define** Realizations, evidence, and predecessors. A revision node records the alternatives and evidence behind continuity, split, or merge. Different roots may preserve incompatible histories.
- S7** The profile chooses cognitive coverage for the whole construction or per subgraph. Understanding Nodes may be absent, selective, or dense. Absence means that reasoning was not externalized there, not that no reasoning occurred. A claimed rationale trace must state which commitments require nodes and which links make the trace checkable. Node density never changes world authority.
- S8** A rendering route is a profile, not a world record. It specifies a source commit and epistemic status, an ordered Event route and open frontier, narrator and viewpoint, evidence cutoff, disclosure rule, and target story-passage node. Records outside the route's access set remain hidden even though they exist elsewhere in $\mathcal{G}_\rho$.
- S9** Read-back reconstructs the records implied by a passage in a fresh context and compares them with the source commit. Any discrepancy is kept as an Understanding Node until a candidate revises the passage, revises the addressed records, or marks the ambiguity explicitly.
- S10** Decide under A11 applies to a whole cross-surface candidate. Acceptance and rejection therefore cannot leave world, rationale, and document records at different commit states.

6 Interface

Operation	Effect on the construction graph $\mathcal{G}_\rho$
Register($c \mid x \mid e$)	stages an addressable Concept, Thing, or Event; under A1 a Thing and its lifecycle enter the same candidate
Bind(e, r, x, I)	stages a Binding subject to A2
Open(P) Compose($\{e_i\}$)	refines a frozen parent, or proposes a new parent over existing Events
Cut($P, q, \pi, u_K, \text{slots}, h$)	stages keyed answers and remainder subject to A3–A6 and A9
Decide(Δ) $\in$ {reject, commit, revise}	A11
Realize(purpose, $P, \tau, c, g, \text{evidence}$)	stages a Realization subject to A10

Convenient names (presence, membership, part-whole, update, roll, roster, render, and read back) specialize these operations or the surface rules and add no world-record form.

Conservative opening and Close. An opening declares a finite witness W : the base snapshot, protected coarse queries and their observation times and resolution, a fine-to-coarse address map, a typed projection called Close_W , and a comparison rule for each query. Each protected answer must be reconstructed from the addressed fine records, not merely read from a cached coarse answer. Acceptance as refinement requires

$$\text{Close}_W(\mathcal{G}_{\text{base}} \oplus \Delta)(q, t, \rho) \simeq_{\varepsilon_q} \mathcal{G}_{\text{base}}(q, t, \rho) \quad \text{for every declared } (q, t, \rho). \quad (8)$$

Identity, categorical data, and protected links normally require exact agreement; measured data use same-unit tolerances. Close is a validation projection within Open and Decide, not a seventh construction operation. For a Cut, mapped fine shares sum to the addressed coarse share, including any part opened from the remainder. Conditional child Cuts multiply by the share at their conditioning address; their sibling sums remain local. For unweighted structure, Close preserves the named identities, roles, and coarse relations through a declared projection; it does not add happenings as though they were weights. For temporal opening it uses A9 and checks residual feasibility before all periods have been filled. No claim of conservative refinement is made without such a witness. Passing protects the stated finite observations, not every possible future query; a failed opening may instead be proposed as an explicit revision under A11.

The repository's `examples/refinement-trial` supplies a small JavaScript reference fixture for these checks. Its purpose is to make the contract executable and inspectable, not to certify the Rust host or supply an independent empirical evaluation of narrative quality.

7 Derived views, permitted patterns, and operators

Derived views are computed from committed records, carry derivation lineage, and hold no authority of their own. Permitted patterns constrain how ordinary records may be combined, while operators transform or propose records; neither category introduces another record form.

Item	Kind	Definition
Encapsulation, roster, inherited presence	derived view	A7
Actor perspective projection	derived view	Q2
Concept-understanding history	derived view	the Understanding Node subgraph specified by S6, projected over the addressed grounding lineage of Concept c and ordered in its understanding root's clock
Divergence	derived diagnostic	Q5
Want satisfaction	derived view	compare a want's desired Event condition or typed world datum with committed state; any graded judgment is a local Cut
Capacity and exchange	permitted pattern	an externally measured stock is typed Event data; allocation is a Cut over one declared unit; transfer is a joint Event. Direct reciprocity or conservation requires a shared external unit and accounting rule; subjective energy is not presumed conserved
Shock profile	mixed view	unweighted links identify changed processes; typed data record objective changes where available; an optional Cut allocates attributed impact; anticipation comes from a prior direction Cut
Life-change allocation	permitted pattern	allocation Cut over one explicitly named attribution unit among affected processes; heterogeneous objective changes remain separately typed and are not standardized into one scalar
Problem-solving profile	derived profile	duration-weighted mixture of scene-level module Cuts over framing, deciding, and their opened modes; decision Events retain strategy families used as unweighted Realizations, while recruitment counts are a theory-only cross-check
Recognizer Γ_c	operator	maps an addressable fragment to an unweighted describe Realization, role alignment, evidence, and optional local match Cuts
Instantiator ι_c	operator	maps a desired concept state and available support to a candidate fragment under Decide

8 Book-specific person profile (non-normative)

A person is a Thing whose life is its lifecycle Event. The Book profile opens that life into state, orientation, problem solving, feeling, and conditional change using only ordinary records. Its principals share one concern vocabulary so their Cuts can be compared, and the remainder tests that vocabulary's coverage. Another construction may use different questions, different answers, or no person profile. Only the Cut contract is general.

P1 State (IS). The Book tracks body, kin, partnership, work, place, means, knowledge, standing, and meaning as concurrent Event-processes within a lifecycle. They may overlap and do not sum. Shorter Events may occur within, constitute, or update them through unweighted links. A causal interpretation belongs in an Understanding Node or a separately posed attribution Cut. Money, location, dates, counts, and physical measurements may be Event data; no life domain receives a free-standing psychological score. World Events and actor-believed Events use different ancestry paths.

P2 Concerns and wants (WHAT). At scene s , a motivational Event e_s^{what} contained by the actor's lifecycle parents every Cut in the WHAT tree. Its top Cut divides one unit of scene motivational attention among the five first-run concerns and remainder. For each opened concern i , another Cut on the same Event divides the conditional unit “attention within concern i ” among approach, threat-avoidance, and remainder:

$$\sum_i c_i + r_C = 1, \quad a_i + v_i + r_i = 1. \quad (9)$$

An opened pole uses another Cut on that Event whose unit is “attention within concern i and pole p ”; it divides among AtomicWant leaves ℓ_{ipj} and remainder r_{ip} with $\sum_j \ell_{ipj} + r_{ip} = 1$. The composed path share within that scene's declared attention unit is $c_i p_{ip} \ell_{ipj}$, where $p_{i,\text{approach}} = a_i$ and $p_{i,\text{avoidance}} = v_i$.

Top, pole, and leaf remainders remain explicit; across opened leaves their combined unresolved path mass is $r_C + \sum_i c_i r_i + \sum_{i,p} c_i p_{ip} r_{ip}$. The conditional five-concern approach view renormalizes $c_i a_i$ by $Z_A = \sum_i c_i a_i$, and the threat-avoidance view renormalizes $c_i v_i$ by $Z_V = \sum_i c_i v_i$. If its denominator is zero, that conditional view is absent or remainder-only rather than fabricated. At most eight leaves are live for one person in one scene. Derived conditional views retain their conditioning mass so their scope remains explicit. Thus no concern or answer label becomes a Cut parent; every local weight is interpreted under the conditional unit named on its Event-parented Cut. Each opened concern or pole Cut records its conditioning slot address h , so the path is recoverable without interpreting the label text.

P3 Appraisal chain. A threat-avoidance leaf remains a want: its endpoint keeps one named threat from obtaining. A different Event records belief in that threat, and fear is a fast appraisal that may follow. Fear is neither the concern nor the pole. The chain is concern $\rightarrow$ threat belief $\rightarrow$ fear $\rightarrow$ decision or action, with one record per link. Want satisfaction has a world-relative view and an actor-believed view.

P4 Problem solving (HOW). A scene assessment Event beneath the actor's lifecycle parents the HOW Cuts. Its top Cut divides problem-solving attention among framing, deciding, and a remainder. Conditional Cuts on that same Event divide "attention within framing" among concrete, abstract, and a remainder, and "attention within deciding" among impartial, personal, and a remainder. Cross-cut combinations such as abstract and personal may coexist. A strategy family is an unweighted describe Realization unless a separate Event-parented Cut asks a genuine comparison question.

P5 Feeling (FEELS). A scene appraisal Event parents an emotion Cut. The Cut is elicited as a check against the actor's concerns, beliefs, and Events. In particular, the Book checks whether an active threat belief supports fear; it does not calculate nine emotion shares from five concern shares.

P6 Time and conditionality. Scene profiles are elicited. Episode, period, and life profiles are derived only across disjoint intervals under their authoritative sequential Cuts. Every result reports coverage and leaves uncovered duration unresolved. Situation and participants select conditional views. Drift, recovery, consolidation, instability or cascade, anticipated transition, and terminal transition label shapes rather than impose equations.

P7 Numbers. A Cut weight means a local share under its Event, question, unit, siblings, and remainder. Event-process links carry no weights. World measurements retain their external units on Events. The profile introduces no anchored psychological coordinate and no Realization degree; validator tolerances and derived diagnostics are not world facts. Compatible slow profiles come from duration, not another round of elicitation.

9 Additional non-normative conventions

Description An Event may carry a readable account of its own version. That text neither changes world state nor becomes an Understanding or Document Node. Profiles may require descriptions for material Events while leaving unopened or mechanical records terse.

Solvers inside a person A later profile could model problem-solving modules as Things within a life, with recruitment Events and dispositions. The Book does not do this; its HOW Cuts are only the simpler projection.

10 Book-specific constants (non-normative)

Concurrent human-life process domains.

body, kin, partnership, work, place, means, knowledge, standing, meaning. These are first-construction Event-process lenses, not universal categories or numerical coordinates.

Emotion vocabulary V_{emo} .

joy, sadness, fear, anger, disgust, surprise, trust, anticipation, neutral.

First-run concern vocabulary V_{concern} .

belonging, competence, autonomy, understanding, well-being. These are shared first-run comparison categories with a tested remainder, not universal concerns. Each may be opened through approach and threat-avoidance poles.

Problem-solving modes.

framing (concrete, abstract) and deciding (impartial, personal), with a remainder at every opened Cut.

Event kinds (initial registry).

lifecycle, presence, membership, physical-part, perception, belief, appraisal, want, estimate, decision, action, interaction, communication, travel, consequence, creation, destruction, split, merge, replacement, succession.

AtomicWant.

A view over Event, Binding, Cut, and provenance records:

```
AtomicWant { id, parent motivational Event, actor (derived), interval,
             concern, pole, operation, target,
             target field or Event condition, desired endpoint, horizon, depth,
             leaf cut, local leaf weight,
             evidence, provenance }
```

The lifecycle ancestry of the parent Event identifies the actor. Operation is preserve, create, transform, or end; preserving can include keeping an absent outcome absent. A target is a registered Thing or Event and may be registered before its lifecycle starts. Concern comes from V_{concern} , and pole is approach or threat-avoidance. The endpoint is categorical or uses a real world-data unit, never a free-standing psychological score. Satisfaction follows by categorical or same-unit comparison; uncertain evidence about that comparison is a separate assessment, not an overwritten world state. No more than eight leaves are opened in one scene. The referenced Cut supplies local leaf weight, and multiplying the concern, pole, and leaf shares gives the scene path share. Context uses a crossing Cut and conflict uses an unweighted link. A care leaf may target another person's process, but kindness remains a separate episode-level evaluation under A10.

Completed Book selections.

The construction used exact integer-tick Cut normalization, a recorded .10 elicitation grid with supported .05 refinement, flat content-addressed concept bundles, no continuous extents, an estimate-depth cap of two, and full scene profiles only for its three principals. One concept was opened experimentally; none of these choices is a core grammar obligation.