


Board Name Fabrication Document

Layer Stack Legend

	Material	Layer	Thickness	Dielectric	Type	Gerber
	F.Paste				Paste Mask	
	F.Silkscreen				Legend	GBR
	F.Mask		0.02mm	Solder Resist	Solder Mask	GBR
	Copper	L1 (Sig, PWR)	0.035mm (1.00oz)		Signal	GBR
	Prepreg		0.1855mm	FR4_7628	Dielectric	
	Copper	L2 (GND)	0.035mm (1.00oz)		Plane	GBR
	Prepreg		1.1mm	FR4	Dielectric	
	Copper	L3 (GND)	0.035mm (1.00oz)		Signal	GBR
	Prepreg		0.1855mm	FR4_7628	Dielectric	
	Copper	L4 (Sig, PWR)	0.035mm (1.00oz)		Signal	GBR
	B.Mask		0.02mm	Solder Resist	Solder Mask	GBR
	B.Silkscreen			Direct Printing	Legend	GBR
	B.Paste				Paste Mask	

Total thickness: 1.651mm
Note: external layer thicknesses are specified after plating

Top Fabrication (Scale 1:1)



Impedance Table

Transmission Line	Impedance [ohms]	Tolerance [ohms]	Layer	Trace Width [mm]	Gap [mm]	Ref. Layers
Edge-Coupled Coated Microstrip	100	±10 %	L1	0.2032	0.28	L2

FABRICATION NOTES (UNLESS OTHERWISE SPECIFIED)

1) FABRICATE PER IPC-6012A CLASS 2.

2) OUTLINE DEFINED IN SEPARATE GERBER FILE WITH "Edge_Cuts.GBR" SUFFIX.

DIMENSIONS OF CIRCUMSIZED RECTANGLE SHOWN ON THIS DRAWING FOR REFERENCE ONLY.

3) SEE SEPARATE DRILL FILES WITH ".DRL" SUFFIX FOR HOLE LOCATIONS.

SELECTED HOLE LOCATIONS SHOWN ON THIS DRAWING FOR REFERENCE ONLY.

4) SURFACE FINISH: IMMERSION GOLD

5) SOLDERMASK ON BOTH SIDES OF THE BOARD SHALL BE LPI, COLOR BLACK.

6) SILK SCREEN LEGEND TO BE APPLIED PER LAYER STACKUP USING YELLOW NON-CONDUCTIVE EPOXY INK.

7) ALL VIAS ARE TENTED ON BOTH SIDES UNLESS SOLDERMASK OPENED IN GERBER.

8) VENDOR SHOULD FOLLOW ROHS COMPLIANT PROCESS AND Pb FREE FOR MANUFACTURING

9) PCB MATERIAL REQUIREMENTS:

- A. FLAMMABILITY RATING MUST MEET OR EXCEED UL94V-0 REQUIREMENTS.
- B. Tg 170 C OR EQUIVALENT.
- C. EQUIVALENT MATERIAL SHALL BE RoHS COMPLIANT, HALOGEN FREE AND APPROVED BY COMPANY NAME.

10) DESIGN GEOMETRY MINIMUM FEATURE SIZES:

BOARD SIZE	34.000 × 28.000 mm
BOARD THICKNESS	1.651 mm
TRACE WIDTH	0.200 mm
TRACE TO TRACE	0.200 mm
MIN. HOLE (PTH)	0.250 mm
MIN. HOLE (NPTH)	N/A mm
ANNULAR RING	0.150 mm
COPPER TO HOLE	0.254 mm
COPPER TO EDGE	0.250 mm
HOLE TO HOLE	0.254 mm

11) REFER TO IMPEDANCE TABLE FOR IMPEDANCE CONTROL REQUIREMENTS.

12) CONFIRM SPACE WIDTHS AND SPACINGS.

All dimensions are in millimeters unless otherwise specified.

	Comments:	Company:		Variant:	Git Hash:	
		Company Name		CHECKED	239d01b	
	Sheet Title:	Board Name:			Project Name:	
		Board Name			Project Name	
	Top Fabrication (Scale 1:1)	File Name:	Designer:	Date:	Revision:	
	KiBot_Project_Test.kicad_pcb	Author	2024-04-13	+ (Unreleased)		
Sheet Path:		Reviewer:	Size:	Sheet:		
			A4	1 of 9		