
Layer Name	Type	Material	Thickness (mm)	Color	Epsilon R	Loss Tangent
F.Silkscreen	Top Silk Screen	Not specified	0 mm	White	1	0
F.Paste	Top Solder Paste		0 mm		1	0
F.Mask	Top Solder Mask	Not specified	0.01 mm	Red	3.3	0
F.Cu	copper		0.035 mm		1	0
Dielectric	core	FR4	1.51 mm	Not specified	4.5	0.02
B.Cu	copper		0.035 mm		1	0
B.Mask	Bottom Solder Mask	Not specified	0.01 mm	Red	3.3	0
B.Paste	Bottom Solder Paste		0 mm		1	0
B.Silkscreen	Bottom Silk Screen	Not specified	0 mm	White	1	0

BOARD CHARACTERISTICS

Copper Layer Count:	2	Board Thickness:	1.6000 mm
Board overall dimensions:	66.6200 mm x 41.3100 mm		
Min track/spacing:	0.0000 mm / 0.0000 mm	Min hole diameter:	0.2000 mm
Copper Finish:	None	Impedance Control:	No
Castellated pads:	No	Plated Board Edge:	No
Edge card connectors:	No		




Board2Pdf: Black And White TOP – Page 1/2

E.Mert Çakır

Sheet: Black And White TOP
File: uPIC46.kicad_pcb

Title: uPIC46

Size: A4	Date: 2025-09-25	**Rev: V0**
KiCad E.D.A. 9.0.2		Id: /1



Board2Pdf: Black And White BOT – Page 2/2

E.Mert Çakır

Sheet: Black And White BOT
File: uPIC46.kicad_pcb

Title: uPIC46

Size: A4	Date: 2025-09-25	**Rev: V0**
KiCad E.D.A. 9.0.2		Id: /1