## Problem1

## January 25, 2023


```
In [2]: import fetcher3 as fetch
        import networkx as nx
        import matplotlib.pyplot as plt
        import time
        from tqdm import tqdm
        import numpy as np
        import pickle
In [3]: def save_graph(graph,file_name):
            #initialze Figure
            plt.figure(num=None, figsize=(20, 20), dpi=80)
            plt.axis('off')
            fig = plt.figure(1)
            pos = nx.spring_layout(graph)
            nx.draw_networkx_nodes(graph,pos)
            nx.draw_networkx_edges(graph,pos)
            # nx.draw_networkx_labels(graph,pos)
            plt.savefig(file_name + ".jpg",bbox_inches="tight")
            with open(file_name + ".pickle", 'wb') as handle:
                pickle.dump(graph, handle)
In []:
In [8]: # Does not do the "only add ones you crawl"
        stack = [("", "https://www.caltech.edu/")]
        visited = set()
        G = nx.DiGraph()
        with tqdm(total=2000) as pbar:
            while stack and G.number_of_nodes() < 2000:</pre>
                parent, url = stack.pop()
                if url in visited:
                    if parent:
                        G.add_edge(parent, url)
                    continue
                visited.add(url)
```

```
G.add_node(url)
pbar.update(1)
if parent:
        G.add_edge(parent, url)
links = fetch.fetch_links(url)
if not links:
        continue
links = list(filter(lambda x: "caltech.edu" in x, links))
edges = [(url, link) for link in links]
stack.extend(edges)

# print("num_nodes: {}".format(G.number_of_nodes()))
# time.sleep(0.5)

save_graph(G,"web_graph_full")

100%|| 2000/2000 [11:58<00:00, 2.78it/s]</pre>
```




The selection policy is primarily whether the domain is caltech.edu. Besides that, I make sure I don't re-crawl already visited nodes, but if a node I visited shows up again I will add the theoretical new edge, since if I'm seeing a node again it's because it's from a parent that links to it that did not exist before, so the edge is new. If a node does not have any links, it's a leaf and I continue.


Advantages: Simple, keeps us within the caltech domain for the most part (aside from edge cases of a query having caltech.edu within it which shouldn't really happen?)


Disadvantages: Sees plenty of useless pages, keeps revisiting certain pages (division home pages, actual home page, etc.), does not properly filter out dynamic pages (there are enough other pages it's not a problem with only 2000 nodes). It also does not deal with http vs https and caltech.edu vs caltech.edu/ and similar cases.


```
x = np.concatenate([np.sort(list(in_degrees))])
   plt.plot(x, np.linspace(1, 0, len(x)))
   plt.show()
def plot_out_degree_dist(G):
    out_degrees = np.array([G.out_degree(n) for n in G.nodes()])
   plt.hist(out_degrees)
   plt.show()
    # cdf = out_degrees.cumsum() / out_degrees.sum()
    \# ccdf = 1 - cdf
    # plt.plot(range(len(out_degrees)), ccdf)
    # plt.show()
    x = np.concatenate([np.sort(list(out_degrees))])
   plt.plot(x, np.linspace(1, 0, len(x)))
   plt.show()
```

plot\_in\_degree\_dist(G) plot\_out\_degree\_dist(G)









My clustering coefficients are pretty similar to problem 2's in that both graphs are very highly clustered, but mine is slightly less so. The average and max diameters are also extremely similar. Both graphs definitely have a large component, and ahve small diameters. They also definitely have high clustering coefficients and are heavy tailed.