Call Center Connect API (1.1)

Download OpenAPI specification: Download

URL: https://ccc.mmdsmart.com/

API for initiating outbound calls.

General description

The Call Center Connect (CCC) API enables seamless call initiation directly from external applications such as CRMs and other business platforms. This short guide provides an overview of the key endpoints and core functionality, helping you quickly integrate and start making calls through the CCC system.

Getting Started

Once the feature is enabled for your organization, the Org Admin can generate an API key by navigating to the My Company section and opening the API KEYS tab.

API Key Generation

To begin using the CCC API, you'll need an integration API key. This key is generated once for your organization (Contact Support team for that) and can be shared with team members who require access. The API key must be included in the header of every request made to the CCC server to ensure proper authentication and access to the platform.

Click to call

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json
required

`phone` required	string The phone number where to call
`agent_id` required	string The username of the agent assigned to handle the call
`caller_id`	string Phone number from which the call originates. If provided, the system verifies whether it matches a DID number assigned to the organization.

Responses

> **201** Call successfully created

> **400** Invalid request

> **500** Internal server error

POST `/api/ctc`

Request samples

Payload | HTTP | cURL

Content type
application/json

Copy

```
{
   "phone": "972547645345",
   "agent_id": "agent_007"
}
```

Response samples

201 | **400** | **500**

Content type
application/json

Copy

```
"call_1234567890"
```

Voice Message Call

AUTHORIZATIONS: > *bearerAuth*

REQUEST BODY SCHEMA: application/json

required

`phone` required	string The phone number to call.
`clip_url` required	string The URL of the audio/video file to play during the call. Supported formats: • Audio: MP3, WAV, AAC • Video: MP4, AVI, MOV (audio track extracted)
`webhook`	string The webhook URL for sending DTMF choices
`caller_id`	string Phone number from which the call originates. If provided, the system verifies whether it matches a DID number assigned to the organization.
`tag`	string Some additional information to use with a webhook.

Responses

> **201** Call successfully created

> **400** Invalid request

> **500** Internal server error

Callbacks

POST DTMF alert

Notify the registered URL with details of DTMF.

POST `{$request.body#/webhook}`

REQUEST BODY SCHEMA: application/json
required

phone required	string The lead phone number
code required	string The DTMF tone pressed by lead
tag	string Additional metadata from the organisation's system.

Callback responses

— **200** Notification received by external service.

POST /api/call

Request samples

Payload | HTTP | cURL

Content type
application/json

Copy

```
{
   "phone": "381643072303",
   "clip_url": "https://firebasestorage.googleapis.com/v0/b/geo-attendance-b
   "webhook": "https://webhook.site/3a0a9fde-d246-467b-95d1-8eaa9915bd2d",
   "tag": "Some additional information to use with a webhook"
}
```

Response samples

201 | 400 | 500

Content type
application/json

Copy

```
{
   "message": "string"
}
```


Callback payload samples

Callback

POST: DTMF alert

Content type

application/json

Copy


```
{
   "phone": "972547645345",
   "agent_id": "agent_007",
   "tag": "Some additional information to use with a webhook"
}
```