

YData: Introduction to Data Science



Class 08: Pandas continued

Overview

Quick review of pandas:

- Tuples and dictionaries
- Series and DataFrames

Continuation of pandas:

- Sorting values and adding new columns
- Calculating aggregate statistics for separate groups
- Joining DataFrames



Announcement: Homework 3

Homework 2 is due on Gradescope on **Sunday February 11th at 11pm**

- **Be sure to mark each question on Gradescope!**



Quick review: tuples and dictionaries

Tuples are like lists but they are immutable

- `my_tuple = (10, 20, 30)` # Creating a tuple
- `my_tuple[1]` # accessing items
- `my_tuple[1] = 50` # Error! Tuples are immutable
- `val1, val2, val3 = my_tuple` # tuple unpacking



Dictionaries allow you to look up **values** based on a **key**

- `my_dict = { 'key1': 5, 'key2': 20 }`
- `my_dict['key2']`

Let's do some very quick warm-up exercise in Jupyter!

Review: pandas Series and DataFrames

There are two main data structures in pandas:

- **Series:** represent one-dimensional data
- **DataFrames:** represent data tables
 - i.e., relational data



Example: egg_prices

pandas Series are: One-dimensional ndarray
with an Index

- `egg_prices.iloc[0]` # use index location
- `egg_prices.loc["1980-01-01"]` # use Index names

DATE	
1980-01-01	0.879
1980-02-01	0.774
1980-03-01	0.812

Index



values (ndarray)



pandas DataFrames

Pandas DataFrame hold Table data

Extracting columns:

- `my_df["my_col"]` # returns a Series!
- `my_df[["my_col"]]` # returns a DataFrame
- `my_df[["col1", "col2"]]` # multiple columns

Extracting rows

- `my_df.iloc[0]` # by position
- `my_df.loc["index_name"]` # by index name

The diagram illustrates a DataFrame structure. A bracket at the top groups the column headers under the label 'Variables'. A bracket on the left groups the rows under the label 'Cases'.

PLAYER	POSITION	TEAM	SALARY
str	str	str	f64
"Paul Millsap"	"PF"	"Atlanta Hawks"	18.671659
"Al Horford"	"C"	"Atlanta Hawks"	12.0
"Tiago Splitter..."	"C"	"Atlanta Hawks"	9.75625
"Jeff Teague"	"PG"	"Atlanta Hawks"	8.0
"Kyle Korver"	"SG"	"Atlanta Hawks"	5.746479

Let's do a few warm-up exercise in Jupyter!

Sorting rows from a DataFrame

We can sort values in a DataFrame using `.sort_values("col_name")`

- `my_df.sort_values("col_name")`

We can sort from highest to lowest by setting the argument `ascending = False`

- `my_df.sort_values("col_name", ascending = False)`

Let's explore this in Jupyter!

Adding new columns and renaming columns

We can add a column to a data frame using square brackets. For example:

- `my_df["new_col"] = values_array`
- `my_df["new col"] = my_df["col1"] + my_df["col2"]`

We can rename columns by passing a dictionary to the `.rename()` method

- `rename_dictionary = {"old_col_name": "new_col_name"}`
- `my_df.rename(columns = rename_dictionary)`

Let's explore this in Jupyter!


Creating aggregate statistics by group

We can get statistics separately by group using the `.groupby()` and `.agg()` methods

- E.g. `nba_salaries.groupby("TEAM").agg("sum")`

This implements:

“Split-apply-combine”



Creating aggregate statistics by group

There are several ways to get multiple statistics by group

Perhaps the most useful way is to use the syntax:




```
my_df.groupby("group_col_name").agg(  
    new_col1 = ('col_name1', 'statistic_name1'),  
    new_col2 = ('col_name2', 'statistic_name2'),  
    new_col3 = ('col_name3', 'statistic_name3')  
)
```

```
nba_salaries.groupby("TEAM").agg(  
    max_salary = ("SALARY", "max"),  
    min_salary = ("SALARY", "min"),  
    first_player = ("PLAYER", "min")  
)
```

Let's explore this in Jupyter!




Joining data frames



Left and right tables

Suppose we have two DataFrames (or Series) called **x_df** and **y_df**


- **x_df** have one column called **x_vals**
- **y_df** has one column called **y_vals**



A diagram of a DataFrame with two columns. The first column is labeled 'Index' with a red arrow pointing to it. The second column is labeled 'x_vals' with a red arrow pointing to it. The DataFrame contains three rows: the first row has index 1 and value x1; the second row has index 2 and value x2; the third row has index 3 and value x3.

Index	x_vals
1	x1
2	x2
3	x3

DataFrame: x_df



A diagram of a DataFrame with two columns. The first column is labeled 'Index' with a red arrow pointing to it. The second column is labeled 'y_vals' with a red arrow pointing to it. The DataFrame contains three rows: the first row has index 1 and value y1; the second row has index 2 and value y2; the third row has index 4 and value y3.

Index	y_vals
1	y1
2	y2
4	y3

DataFrame: y_df


We can join these two DataFrames into a single DataFrame by aligning rows with the same Index value using the general syntax: **x_df.join(y_df)**

- i.e., the new joined data frame will have two columns: **x_vals**, and **y_vals**

Left joins

Left joins keep all rows in the left table.

Data from right table is added when there is a matching Index value, otherwise NA as added




```
x_df.join(y_df, how = "left")
```

Right joins

Right joins keep all rows in the right table.


Data from left table added when there is a matching Index value otherwise NA as added



```
x_df.join(y_df, how = "right")
```

Inner joins

Inner joins only keep rows in which there are matches between the Index values in both tables.




```
x_df.join(y_df, how = "inner")
```


Full (outer) joins


Full joins keep all rows in both table

NAs are added where there are no matches




```
x_df.join(y_df, how = "outer")
```


Summary




INNER JOIN



FULL OUTER JOIN



LEFT JOIN



RIGHT JOIN

“Merging” data frames

We can also join DataFrames based on values in columns rather than based on the DataFrames Index values

To do this we can use the merge method which has the form:

- `x_df.merge(y_df, how = "left", left_on = "x_col", right_on = "y_col")`

All the same types of joins still work

- i.e., we can do: left, right, inner and outer joins

Let's explore this in Jupyter!

Questions?

