

OPERATIONAL QUALIFICATION (OQ)

Project No : EMG-20-040

Date : 24.02.2021

Document Ref Number : EMG-20-040.OQ

AUTOMATIC LINEAR SINGLE MODULE SELF TOP LABELING MACHINE

M-ETK-A04













EMG-20-040.OQ Rev.No 01 Rev.Date 24.February.2021 Page No 2

1.	Purpose and Scope	3
	OQ Test Specification	
	OperationalQualificationsTest	
	Additional Test	
5.	Alert Test	8
6.	Test Report Approved	g
7.	Comments and Explanation	10









EMG-20-040.OQ	Rev.No	01	Rev.Date	24.February.2021	Page No	3
---------------	--------	----	----------	------------------	---------	---

1. Purpose and Scope

The purpose of this operational qualification document is to provide evidence that the operational qualification work for the Top Labelling Machine and its components has been completed.

Equipment Name	Equipment Code	Equipment / Serial No
Top Labelling Machine	M-ETK-A02	3848

2. OQ Test Specifications

Points to Consider in Test Protocols

- Fill all procedurs used with a blue ballpoint pen, never use a course pen.
- Never delete or doodle incorrect entries or typos. Just draw the wrong entry and type the correct entry.
 Please do it date and paragh.
- Test forms must be completed by authorized personnel simultaneously with the application. Must be approved by authorized personnel
- All supporting documents used and created during the implementation of tests are considered part of the qualification package and must be added to the end of the test.
- All protocols must be approved by the customer. All tests must be given the latest approval by the customer.

Deviation / Erros

Errors/deviations encountered during tests should include the following information.

- · Reference information to the test where deviation/error is seen,
- Estimates for deviation/error
- Prescribed corrective action for deviation/error
- Signature and date information of the person who detected the deviation/error
- · Confirmation information provided by customer regarding deviation / error









EMG-20-040.OQ Rev.No 01 Rev.Date 24.February.2021 Page No 4

3. Operational Qualification Test

Customer Co.Name :	Equipment Serial No :	Test Applied No : 01
Customer Co.Name.	Equipment Senai No.	rest Applied No. 01
Test Name :	Operational Test	
Purpose :	proving that its functions work as designation	igned
Necessary Materials/Documents : San	nple Products, packaging products	
Test Acceptance Criteria: Each of the	operational qualification steps meet its own acceptance cr	riteria
Pre Condition : Completion Of Installation	on Qualification Work	

Top Labelling Machine-3848

Test No	Test Step	Acceptance Criteria	Has the Ac	-	Applied	Approver
1.1	Open the Paco Switch	Energy must come to the machine and the HMI project must be opened.	test n	No[]	Par./Date	Par./Date
1.2	Reset the Alert if Exist	Reseting Alerts	Yes []	No []		
1.3	Open The Machine Door	The Automatic Functione mustnt be work.lt must be shown on Alert menü.	Yes []	No []		
1.4	Check the enter photocell	The Helix must stop while the product is absent, and the machine must wait for the input to fill up.	Yes[]	No []		
1.5	Check the exit Photocell	The Helix must stop while the product is exist, and the machine must wait for the input to fill up	Yes []	No []		
1.6	Check the label finish photocell	it Should be stop working machine when output, stop machine should not work.	Yes []	No []		
1.7	Feed 1pcs carton and press machine start button.	Start photocell should give the label after seeing the product.	Yes []	No []		
1.8	Check whether the label is properly sticked on the carton.	The label should be sticked properly.	Yes []	No []		









EMG-20-040.OQ

Rev.No

01

Rev.Date 24.

24.February.2021

Page No

5

Üstten Etiketleme Makinesi-3848

Test No	Test Step	Acceptance Criteria	Has the Acceptance test met?	Applied Par./Date	Approver Par./Date
1.10	Give the machine 10 products and see that the coding is done	The desired encoding must be performed.	Yes [] No []		
1.11	Make the Machine see 1pcs. OCR incorrectly.	The faulty label should be rejected.	Yes [] No []		
1.12	Make machine see 1 unlabeled carton.	Unlabeled carton should be rejected	Yes [] No []		
1.13	Make the Machine see faulty OCR 3 times in a consecutive.	Machine should be stop.	Yes [] No []		
1.14	Make the Machine see faulty PHC 3 times in a consecutive.	Machine should be stop.	Yes [] No []		
1.15	Feed 1 carton and close the hose of eject piston.	Reject box machine it has to stop.	Yes [] No []		
1.16	In the event of a power failure, show that the system has the ability to automatically stop other sources (air, vacuum, etc.) in the machine, allowing the operator to start the machine again.	In case of power failure, the system has the ability to automatically stop other sources (air, vacuum, etc.) in the machine, allowing the operator to start the machine again he should be able to recognize it.	Yes[] No[]		









EMG-20-040.OQ Rev.No 01 Rev.Date 24.February.2021 Page No 6

4. Additional Test

Test No	Test Step	Acceptance Criteria	Has the Acceptance test met?	Applied Par./Date	Approver Par./Date
			Yes[] No[]		
			Yes [] No []		
			Yes [] No []		
			Yes [] No []		









EMG-20-040.OQ Rev.No 01 Rev.Date 24.February.2021 Page No 7

5. Alert Test

Test No	Test Step	Acceptance Criteria	Has the Acceptance test met?	Applied Par./Date	Approver Par./Date
A.1	Press the emergency stop button.	The "Emergency stop pressed" alarm should be given, the running machine should stop, and the machine should not run when the emergency stop is pressed.	Yes[] No[]		
A.2	Leave the machine doors open.	'The "doors open" alarm should be given, the running machine should stop. When the alarm is active the machine should not work.	Yes[] No[]		
A.3	Cut the air connection.	"There is no air" alarm should be given, the running machine should stop. When the alarm is active the machine should not be running.	Yes[] No[]		
A.4	To empty to the enter conveyor.	The "Entry is empty" alarm should be given, and the machine should put itself into standby.	Yes[] No[]		
A.5	Feed 1 carton and close the hose of eject piston.	it should give alarm "Product esca- ped". The machine should not work while on alert, the working machine should stop.	Yes[] No[]		
A.6	To feed the exit conveyor	'The machine that should give the 'full output' alarm must put itself on hold.	Yes [] No []		
A.7	Finish the label of the module group	It should give the alarm "Label over". While in alarm, the machine should not work, the running machine should stop.	Yes[] No[]		
A.8	Make the Machine see faulty OCR 3 times in a consecutive.	It should give the alarm "3 consecutive bad OCR" While in alarm, the machine should not work, the running machine should stop.	Yes[] No[]		
A.9	Make the Machine see the bottle without label 3 times in a consecutive.	It should give an alarm "3 consecutive unlabeled bottles" While in alarm, the machine should not work, the running machine should stop.	Yes[] No[]		
A.10	Take the machine into manual mode.	It should give the "manual mode active" alarm. While in alarm, the machine should not work, the running machine should stop.	Yes[] No[]		
A.11	Send reject until the pieces written in the HMI to the Eject box.	"Eject box full" alarm should give. While in alarm, the machine should not work, the running machine should stop.	Yes[] No[]		









EMG-20-040.OQ Rev.No 01 Rev.Date 24.February.2021 Page No 8

6. Test Report Approved

Prepared by

Name	Department/Function	Date	Sign

Approved by

Name	Department/Function	Date	Sign





7. Comments and Explanation

