



Active Light

Active Light Euroasfalt (ALE)

Virk lýsing er lausn sem eykur öryggi á gangbrautum. Þökk sé hreyfiskynjurum, stillir tækið sjálfkrafa birtustig lýsingarinnar – það kviknar aðeins af fullum krafti þegar gangandi vegfarandi er við gangbraut, eykur sýnileika og sparar orku um leið. Virk ALE lýsing tryggir bestu lýsingu í öllum aðstæðum.



Eiginleikar Vöru



- Meira öryggi
- Bætur sýnileika
- Fækkar slysum
- Stillanlegt stýrikerfi
- Sveigjanlegur orkugjafi
- Aflmikið
- Langur lífstími
- Auðvelt uppsetningar
- Samkvæmt reglugerð



Active Light

Active Light Euroasfalt (ALE)

Module luminaire

Housing material	die-cast aluminium, powder-coated
Sealed	IP 66
Mechanical resistance	IK 09
Supply	SELV 24V DC (230V on request)
Efficiency	~ 145 lm/W
Luminous flux	according to requirements and photometry
Conforms to	PN-EN 13201, PN-76/E-02032

Motion detector module

Detection method	PIR
Operation	NO
Sensor type	Curtain
Temperature range	-20 °C to + 50 °C
Sealed to	IP 54
Complies with	EN50130-4:1995 + A1:1998 + A2:2003, EN55022: 2006

Enclosure

Material	polyester with glass fibre SMC in compliance with DIN 14598
Protection class	II class
Insulation voltage	690 V
Mechanical resistance	IK10
Air tightness	IP44
Conforms to	PN-EN 61439-1:2021-10

Pole

Type	S-50PC-3
Horizontal load resistance	Mp=3,5 [kNm]
Vehicle impact characteristics	passive safety class 0
Compliant	EN-1461