

Introduction in MATLAB (TSRT04)

2020

Emil Björnson

Division of Communication Systems
Department of Electrical Engineering (ISY)
Linköping University, Sweden

www.commsys.isy.liu.se/en/student/kurser/TSRT04



MATLAB Basics

Vectors and Matrices

Using Built-In Functions

Scripts and Functions

Visualization

Control Structures

Summary

What is MATLAB?

MATrix LABoratory (MATLAB)

- ▶ Advanced calculator for technical computing
- ▶ Simple but powerful programming language
- ▶ Numerical calculations (not symbolic as Mathematica)
- ▶ Available for Windows, Mac, Linux
- ▶ New versions twice/year: 2019a, 2019b, 2020a

What is MATLAB?

MATrix LABoratory (MATLAB)

- ▶ Advanced calculator for technical computing
- ▶ Simple but powerful programming language
- ▶ Numerical calculations (not symbolic as Mathematica)
- ▶ Available for Windows, Mac, Linux
- ▶ New versions twice/year: 2019a, 2019b, 2020a

- ▶ Pros: Easy to get started, easy to visualize results
- ▶ Pros: Many examples and toolboxes for various topics (e.g., math, statistics, optimization, telecom, control, biology, finance)
- ▶ Cons: Not the fastest code - but usually fast enough!

What is MATLAB?

MATrix LABoratory (MATLAB)

- ▶ Advanced calculator for technical computing
- ▶ Simple but powerful programming language
- ▶ Numerical calculations (not symbolic as Mathematica)
- ▶ Available for Windows, Mac, Linux
- ▶ New versions twice/year: 2019a, 2019b, 2020a

- ▶ Pros: Easy to get started, easy to visualize results
- ▶ Pros: Many examples and toolboxes for various topics (e.g., math, statistics, optimization, telecom, control, biology, finance)
- ▶ Cons: Not the fastest code - but usually fast enough!

- ▶ Suitable for testing ideas, solving scientific problems, developing/validating algorithms

What is MATLAB?

MATrix LABoratory (MATLAB)

- ▶ Advanced calculator for technical computing
- ▶ Simple but powerful programming language
- ▶ Numerical calculations (not symbolic as Mathematica)
- ▶ Available for Windows, Mac, Linux
- ▶ New versions twice/year: 2019a, 2019b, 2020a

- ▶ Pros: Easy to get started, easy to visualize results
- ▶ Pros: Many examples and toolboxes for various topics (e.g., math, statistics, optimization, telecom, control, biology, finance)
- ▶ Cons: Not the fastest code - but usually fast enough!

- ▶ Suitable for testing ideas, solving scientific problems, developing/validating algorithms

- ▶ **GNU Octave:** Open source option — MATLAB compatible

2/31

My research: 5G Wireless Communications


Goal: Develop design principles for the next generation cellular networks.

Understand interplay between


- ▶ Data rate per user (bit/s/user)
- ▶ Area data rate (bit/s/km²)
- ▶ Energy efficiency (bit/Joule)

Role of MATLAB:

- ▶ Test models
- ▶ Develop algorithms
- ▶ Visualize tradeoffs



MATLAB Interface



MATLAB as Pocket Calculator

Use *Command Window* as a scientific pocket calculator

- ▶ Simple numbers: 30, pi (π), 1e2 ($1 \cdot 10^2$)
- ▶ Simple operators: + - / *
- ▶ Simple functions: cosine (cos()), absolute value (abs(.))

MATLAB as Pocket Calculator

Use *Command Window* as a scientific pocket calculator

- ▶ Simple numbers: 30, pi (π), 1e2 ($1 \cdot 10^2$)
- ▶ Simple operators: + - / *
- ▶ Simple functions: cosine (cos()), absolute value (abs(.))

Examples:

```
>> 2e3 + 300
```

MATLAB as Pocket Calculator

Use *Command Window* as a scientific pocket calculator

- ▶ Simple numbers: 30, pi (π), 1e2 ($1 \cdot 10^2$)
- ▶ Simple operators: + - / *
- ▶ Simple functions: cosine (cos()), absolute value (abs(.))

Examples:

```
>> 2e3 + 300
```

```
ans = 2300
```

MATLAB as Pocket Calculator

Use *Command Window* as a scientific pocket calculator

- ▶ Simple numbers: 30, pi (π), 1e2 ($1 \cdot 10^2$)
- ▶ Simple operators: + - / *
- ▶ Simple functions: cosine (cos()), absolute value (abs(.))

Examples:

```
>> 2e3 + 300
```

```
ans = 2300
```

```
>> cos(pi)
```

MATLAB as Pocket Calculator

Use *Command Window* as a scientific pocket calculator

- ▶ Simple numbers: 30, pi (π), 1e2 ($1 \cdot 10^2$)
- ▶ Simple operators: + - / *
- ▶ Simple functions: cosine (cos()), absolute value (abs(.))

Examples:

```
>> 2e3 + 300
```

```
ans = 2300
```

```
>> cos(pi)
```

```
ans = -1
```

MATLAB as Pocket Calculator

Use *Command Window* as a scientific pocket calculator

- ▶ Simple numbers: 30, pi (π), 1e2 ($1 \cdot 10^2$)
- ▶ Simple operators: + - / *
- ▶ Simple functions: cosine (cos()), absolute value (abs(.))

Examples:

```
>> 2e3 + 300
```

```
ans = 2300
```

```
>> cos(pi)
```

```
ans = -1
```

```
>> abs(1+1i)
```

MATLAB as Pocket Calculator

Use *Command Window* as a scientific pocket calculator

- ▶ Simple numbers: 30, pi (π), 1e2 ($1 \cdot 10^2$)
- ▶ Simple operators: + - / *
- ▶ Simple functions: cosine (cos()), absolute value (abs(.))

Examples:

```
>> 2e3 + 300
```

```
ans = 2300
```

```
>> cos(pi)
```

```
ans = -1
```

```
>> abs(1+1i)
```

```
ans = 1.4142
```

Variables

- ▶ A “container” to save values in.
- ▶ Has a name and a value.

```
>> a = 5
```


Variables

- ▶ A “container” to save values in.
- ▶ Has a name and a value.

```
>> a = 5
```

```
a = 5
```

Variables

- ▶ A “container” to save values in.
- ▶ Has a name and a value.

```
>> a = 5
```

```
a = 5
```

```
>> b = a + 3
```

Variables

- ▶ A “container” to save values in.
- ▶ Has a name and a value.

```
>> a = 5
```

```
a = 5
```

```
>> b = a + 3
```

(That to the right of = is computed first

Variables

- ▶ A “container” to save values in.
- ▶ Has a name and a value.

```
>> a = 5
```

```
a = 5
```

```
>> b = a + 3
```

```
b = 8
```

(That to the right of `=` is computed first, and the result stored in `b`.)

Variables

- ▶ A “container” to save values in.
- ▶ Has a name and a value.

```
>> a = 5
```

```
a = 5
```

```
>> b = a + 3
```

```
b = 8
```

(That to the right of `=` is computed first, and the result stored in `b`.)

What is the result of:

```
>> a = a + 2
```

Variables

- ▶ A “container” to save values in.
- ▶ Has a name and a value.

```
>> a = 5
```

```
a = 5
```

```
>> b = a + 3
```

```
b = 8
```

(That to the right of `=` is computed first, and the result stored in `b`.)


What is the result of:

```
>> a = a + 2
```

```
a = 7
```

Workspace

Variables are stored in the “Workspace”, cf., a filing cabinet.



The screenshot shows the MATLAB Workspace window. It has a title bar 'Workspace' with a dropdown arrow. Below the title bar is a table with four columns: 'Name', 'Value', 'Min', and 'Max'. There are three rows of variables: 'a' with value 7, 'ans' with value 1.4142, and 'b' with value 8. Each row has a small icon to the left of the variable name.

Name	Value	Min	Max
a	7	7	7
ans	1.4142	1.4142	1.4142
b	8	8	8

Investigate your workspace


- ▶ If you don't give a variable name: Result is stored in `ans`
- ▶ You can click on variables in workspace to find out more.
- ▶ You can list all available variables with `>>whos`.

Vectors and Matrices

Vectors and matrices are a fundamental to MATLAB.

- $a = \begin{bmatrix} 4 & 5 & 6 \end{bmatrix}$ is written as `>>a = [4 5 6]`
(or `[4, 5, 6]`)

These are stored in Workspace — just as any variable:



The screenshot shows the MATLAB Workspace window with a table of variables. The table has four columns: Name, Value, Min, and Max. There are three rows of variables: A, a, and b. Each variable name is preceded by a small grid icon. The 'Value' column shows the MATLAB representation of each variable: [1 2;3 4] for A, [4 5 6] for a, and [1;2;3] for b. The 'Min' and 'Max' columns show the minimum and maximum values for each variable.

Name ▲	Value	Min	Max
A	[1 2;3 4]	1	4
a	[4 5 6]	4	6
b	[1;2;3]	1	3


Vectors and Matrices

Vectors and matrices are a fundamental to MATLAB.

► $a = \begin{bmatrix} 4 & 5 & 6 \end{bmatrix}$ is written as `>>a = [4 5 6]`
(or `[4, 5, 6]`)

► $b = \begin{bmatrix} 1 \\ 2 \\ 3 \end{bmatrix}$ is written as `>>b = [1; 2; 3]`

These are stored in Workspace — just as any variable:



The screenshot shows the MATLAB Workspace window with a table of variables. The table has four columns: Name, Value, Min, and Max. There are three rows of variables: A, a, and b. Each variable name is preceded by a small icon representing its shape (a square for A, a row vector for a, and a column vector for b).

Name ▲	Value	Min	Max
A	[1 2;3 4]	1	4
a	[4 5 6]	4	6
b	[1;2;3]	1	3

Vectors and Matrices

Vectors and matrices are a fundamental to MATLAB.

► $a = [4 \ 5 \ 6]$ is written as `>>a = [4 5 6]`
(or `[4, 5, 6]`)

► $b = \begin{bmatrix} 1 \\ 2 \\ 3 \end{bmatrix}$ is written as `>>b = [1; 2; 3]`

► $A = \begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix}$ is written as `>>A = [1 2; 3 4]`

These are stored in Workspace — just as any variable:



The screenshot shows the MATLAB Workspace window with a table of variables. The table has four columns: Name, Value, Min, and Max. There are three rows of data for variables A, a, and b. Each variable name in the Name column is preceded by a small matrix icon.

Name ▲	Value	Min	Max
A	[1 2;3 4]	1	4
a	[4 5 6]	4	6
b	[1;2;3]	1	3

Vectors and Matrices

- Suppress output from a MATLAB command by semicolon:

```
>> a = [4 5 6];
```

Vectors and Matrices

- ▶ Suppress output from a MATLAB command by semicolon:

```
>> a = [4 5 6];
```

- ▶ To get the matrix transpose write `.'`:

```
>> a.'
```

Vectors and Matrices

- Suppress output from a MATLAB command by semicolon:

```
>> a = [4 5 6];
```

- To get the matrix transpose write `.'`:

```
>> a.'
```

```
ans =
```

```
4
```

```
5
```

```
6
```

Vectors and Matrices

- Suppress output from a MATLAB command by semicolon:

```
>> a = [4 5 6];
```

- To get the matrix transpose write `.'`:

```
>> a.'
```

```
ans =
```

```
4
```

```
5
```

```
6
```

Generate special matrices and vectors:

Vectors and Matrices

- Suppress output from a MATLAB command by semicolon:

```
>> a = [4 5 6];
```

- To get the matrix transpose write `.'`:

```
>> a.'
```

```
ans =
```

```
4
```

```
5
```

```
6
```

Generate special matrices and vectors:

- `>>C = eye(2)` yields $C = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$.

Vectors and Matrices

- ▶ Suppress output from a MATLAB command by semicolon:

```
>> a = [4 5 6];
```

- ▶ To get the matrix transpose write `.'`:

```
>> a.'
```

```
ans =
```

```
4
```

```
5
```

```
6
```

Generate special matrices and vectors:

- ▶ `>>C = eye(2)` yields $C = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$.

- ▶ `>>x = 3:6` yields $x = [3 \ 4 \ 5 \ 6]$.

Vectors and Matrices

- ▶ Suppress output from a MATLAB command by semicolon:

```
>> a = [4 5 6];
```

- ▶ To get the matrix transpose write `.'`:

```
>> a.'
```

```
ans =
```

```
4
```

```
5
```

```
6
```

Generate special matrices and vectors:

- ▶ `>>C = eye(2)` yields $C = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$.

- ▶ `>>x = 3:6` yields $x = [3 \ 4 \ 5 \ 6]$.

- ▶ `>>y = 2:3:11` yields $y = [2 \ 5 \ 8 \ 11]$.

Matrix Operations

Original purpose of MATLAB: Matrix operations

- ▶ Define matrices:

```
>> A = [1 2; 3 4];
```

```
>> B = eye(2);
```

- ▶ Compute multiplications:

```
>> A*B
```

Matrix Operations

Original purpose of MATLAB: Matrix operations

- ▶ Define matrices:

```
>> A = [1 2; 3 4];
```

```
>> B = eye(2);
```

- ▶ Compute multiplications:

```
>> A*B
```

```
ans =
```

```
1 2
```

```
3 4
```

Matrix Operations

Original purpose of MATLAB: Matrix operations

- ▶ Define matrices:

```
>> A = [1 2; 3 4];
```

```
>> B = eye(2);
```

- ▶ Compute multiplications:

```
>> A*B
```

```
ans =
```

```
1 2  
3 4
```

$$\text{i.e., } \begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

(normal matrix multiplication)

Matrix Operations

Original purpose of MATLAB: Matrix operations

- ▶ Define matrices:

```
>> A = [1 2; 3 4];
```

```
>> B = eye(2);
```

- ▶ Compute multiplications:

```
>> A*B
```

```
>> A.*B
```

```
ans =
```

```
1 2  
3 4
```

i.e., $\begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$

(normal matrix multiplication)

Matrix Operations

Original purpose of MATLAB: Matrix operations

- Define matrices:

```
>> A = [1 2; 3 4];
```

```
>> B = eye(2);
```

- Compute multiplications:

```
>> A*B
```

```
ans =
```

```
1 2  
3 4
```

i.e., $\begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$

(normal matrix multiplication)

```
>> A.*B
```

```
ans =
```

```
1 0  
0 4
```

Matrix Operations

Original purpose of MATLAB: Matrix operations

- Define matrices:

```
>> A = [1 2; 3 4];
```

```
>> B = eye(2);
```

- Compute multiplications:

```
>> A*B
```

```
ans =
```

```
1 2
3 4
```

$$\text{i.e., } \begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

(normal matrix multiplication)

```
>> A.*B
```

```
ans =
```

```
1 0
0 4
```

$$\text{i.e., } \begin{bmatrix} 1 \cdot 1 & 2 \cdot 0 \\ 3 \cdot 0 & 4 \cdot 1 \end{bmatrix}$$

(element-wise multiplication)

Matrix Operations

Original purpose of MATLAB: Matrix operations

- Define matrices:

```
>> A = [1 2; 3 4];
```

```
>> B = eye(2);
```

- Compute multiplications:

```
>> A*B
```

```
ans =
```

```
1 2  
3 4
```

$$\text{i.e., } \begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

(normal matrix multiplication)

```
>> A.*B
```

```
ans =
```

```
1 0  
0 4
```

$$\text{i.e., } \begin{bmatrix} 1 \cdot 1 & 2 \cdot 0 \\ 3 \cdot 0 & 4 \cdot 1 \end{bmatrix}$$

(element-wise multiplication)

- Similar: $\wedge 2$ vs. $\cdot \wedge 2$, and $/$ vs. $\cdot /$

Matrix Operations

There are tons of functions that handle matrices:

- ▶ Classic functions: `exp()` `log()` `sin()` `cos()` `tan()`
- ▶ Ordering functions: `min()` `max()` `mean()` `sort()`

Matrix Operations

There are tons of functions that handle matrices:

- ▶ Classic functions: `exp()` `log()` `sin()` `cos()` `tan()`
- ▶ Ordering functions: `min()` `max()` `mean()` `sort()`

Some functions work element-wise:

```
>> x = 0:(pi/2):(2*pi)
```

```
x = 0      1.5708      3.1416      4.7124      6.2832
```

Matrix Operations

There are tons of functions that handle matrices:

- ▶ Classic functions: `exp()` `log()` `sin()` `cos()` `tan()`
- ▶ Ordering functions: `min()` `max()` `mean()` `sort()`

Some functions work element-wise:

```
>> x = 0:(pi/2):(2*pi)
```

```
x = 0      1.5708      3.1416      4.7124      6.2832
```

```
>> y = sin(x)
```

Matrix Operations

There are tons of functions that handle matrices:

- ▶ Classic functions: `exp()` `log()` `sin()` `cos()` `tan()`
- ▶ Ordering functions: `min()` `max()` `mean()` `sort()`

Some functions work element-wise:

```
>> x = 0:(pi/2):(2*pi)
```

```
x = 0      1.5708      3.1416      4.7124      6.2832
```

```
>> y = sin(x)
```

```
y = 0      1.0000      0.0000     -1.0000     -0.0000
```

Matrix Operations

There are tons of functions that handle matrices:

- ▶ Classic functions: `exp()` `log()` `sin()` `cos()` `tan()`
- ▶ Ordering functions: `min()` `max()` `mean()` `sort()`

Some functions work element-wise:

```
>> x = 0:(pi/2):(2*pi)
```

```
x = 0      1.5708      3.1416      4.7124      6.2832
```

```
>> y = sin(x)
```

```
y = 0      1.0000      0.0000     -1.0000     -0.0000
```

Some functions process all elements at once:

```
>> z = max(x)
```

Matrix Operations

There are tons of functions that handle matrices:

- ▶ Classic functions: `exp()` `log()` `sin()` `cos()` `tan()`
- ▶ Ordering functions: `min()` `max()` `mean()` `sort()`

Some functions work element-wise:

```
>> x = 0:(pi/2):(2*pi)
```

```
x = 0      1.5708      3.1416      4.7124      6.2832
```

```
>> y = sin(x)
```

```
y = 0      1.0000      0.0000     -1.0000     -0.0000
```

Some functions process all elements at once:

```
>> z = max(x)
```

```
z = 6.2832
```

Matrix Indexing

How to access specific elements in vectors and matrices?

```
>> y = [0 1 0 -1 0];
```

```
>> y(4)
```

Matrix Indexing

How to access specific elements in vectors and matrices?

```
>> y = [0 1 0 -1 0];
```

```
>> y(4)
```

```
ans = -1
```


Matrix Indexing

How to access specific elements in vectors and matrices?

```
>> y = [0 1 0 -1 0];
```

```
>> y(4)
```

```
ans = -1
```

```
>> A = [3 5 2; 7 8 6];
```

$$A = \begin{bmatrix} 3 & 5 & 2 \\ 7 & 8 & 6 \end{bmatrix}$$

Matrix Indexing

How to access specific elements in vectors and matrices?

```
>> y = [0 1 0 -1 0];
```

```
>> y(4)
```

```
ans = -1
```

```
>> A = [3 5 2; 7 8 6];
```

```
>> A(1,2)
```

$$A = \begin{bmatrix} 3 & 5 & 2 \\ 7 & 8 & 6 \end{bmatrix}$$

Matrix Indexing

How to access specific elements in vectors and matrices?

```
>> y = [0 1 0 -1 0];
```

```
>> y(4)
```

```
ans = -1
```

```
>> A = [3 5 2; 7 8 6];
```

```
>> A(1,2)
```

```
ans = 5
```

$$A = \begin{bmatrix} 3 & 5 & 2 \\ 7 & 8 & 6 \end{bmatrix}$$

How to find a function?

If you are looking for a function:

- ▶ How do you know if it exists in MATLAB?
- ▶ “lookfor term” searches the documentation for the string “term”
- ▶ Example: `lookfor determinant` to look for the matrix determinant function

How to find a function?

If you are looking for a function:

- ▶ How do you know if it exists in MATLAB?
- ▶ “lookfor term” searches the documentation for the string “term”
- ▶ Example: `lookfor determinant` to look for the matrix determinant function

How do you know how it works?

How to find a function?

If you are looking for a function:

- ▶ How do you know if it exists in MATLAB?
- ▶ “lookfor term” searches the documentation for the string “term”
- ▶ Example: `lookfor determinant` to look for the matrix determinant function

How do you know how it works?

- ▶ “help command” displays a help text for “command”
- ▶ “doc command” gives more thorough information

How to find a function?

If you are looking for a function:

- ▶ How do you know if it exists in MATLAB?
- ▶ “lookfor term” searches the documentation for the string “term”
- ▶ Example: `lookfor determinant` to look for the matrix determinant function

How do you know how it works?

- ▶ “help command” displays a help text for “command”
- ▶ “doc command” gives more thorough information

General documentation:

- ▶ “doc” opens up the MATLAB documentation
- ▶ “help” gives a list of “toolboxes” (collections of commands organized by usage)

Beyond the Pocket Calculator: Scripts

- ▶ A way to perform several commands at once.

Beyond the Pocket Calculator: Scripts

- ▶ A way to perform several commands at once.
- ▶ Save some commands in an m-file (the filename must end with `.m`) and run all at once by simply typing the name of the file at the command line.

Beyond the Pocket Calculator: Scripts

- ▶ A way to perform several commands at once.
- ▶ Save some commands in an m-file (the filename must end with `.m`) and run all at once by simply typing the name of the file at the command line.
- ▶ `>>edit` start an editor suitable for writing m-files.

Beyond the Pocket Calculator: Scripts

- ▶ A way to perform several commands at once.
- ▶ Save some commands in an m-file (the filename must end with `.m`) and run all at once by simply typing the name of the file at the command line.
- ▶ `>>edit` start an editor suitable for writing m-files.
- ▶ Documentation: Comments are written as `% Comment`

Beyond the Pocket Calculator: Scripts

- ▶ A way to perform several commands at once.
- ▶ Save some commands in an m-file (the filename must end with `.m`) and run all at once by simply typing the name of the file at the command line.
- ▶ `>>edit` start an editor suitable for writing m-files.
- ▶ Documentation: Comments are written as `% Comment`

Strong recommendation:

- ▶ Always use scripts!
- ▶ Easy to reproduce result and write documentation.
- ▶ Easy to make small changes and rerun everything.

Example: Script

Lina has run 5 km in 23 min and 15 s.

- ▶ She wants to compute the time per km.
- ▶ She wants to do the same thing next week.

Example: Script

Lina has run 5 km in 23 min and 15 s.

- ▶ She wants to compute the time per km.
- ▶ She wants to do the same thing next week.

m-file computeRunPace.m

```
distance = 5; % Distance in km
minutes = 23; % Total time expressed in
seconds = 15; % minutes and seconds

% Compute time per km in minutes:
totalminutes = minutes + seconds/60;
minperkm = totalminutes/distance
```

Scripts vs. Functions

Nature of scripts

- ▶ Just a collection of commands.
- ▶ Uses MATLAB's general Workspace.
- ▶ Can overwrite previous variables (overlapping name).
- ▶ Can unintendedly use previous variables (coding error).

Scripts vs. Functions

Nature of scripts

- ▶ Just a collection of commands.
- ▶ Uses MATLAB's general Workspace.
- ▶ Can overwrite previous variables (overlapping name).
- ▶ Can unintendedly use previous variables (coding error).
- ▶ Simplest solution: Begin scripts with `clear`, which empties workspace.

Scripts vs. Functions

Nature of scripts

- ▶ Just a collection of commands.
- ▶ Uses MATLAB's general Workspace.
- ▶ Can overwrite previous variables (overlapping name).
- ▶ Can unintendedly use previous variables (coding error).
- ▶ Simplest solution: Begin scripts with `clear`, which empties workspace.

Nature of functions

- ▶ Another concept: Have their own local Workspaces.
- ▶ Works just like MATLAB's own functions.
- ▶ Excellent way to reusing the same code multiple times.

Example: Function

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km in minutes, given
% the distance and the total time expressed
% in minutes and seconds.

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Example: Function

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km in minutes, given
% the distance and the total time expressed
% in minutes and seconds.

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

- `function` — indicates the beginning of a function

Example: Function

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km in minutes, given
% the distance and the total time expressed
% in minutes and seconds.

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

- *function name* — should be the same as the m-file name

Example: Function

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km in minutes, given
% the distance and the total time expressed
% in minutes and seconds.

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

- *input* — data needed by the function

Example: Function

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km in minutes, given
% the distance and the total time expressed
% in minutes and seconds.

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

- *output* — result delivered by the function

Example: Function Execution

>>

Workspace:
MATLAB

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

Workspace:
MATLAB

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```


Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

Workspace:
MATLAB

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Workspace:
computeRunPace

Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

Workspace:
MATLAB

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Workspace:
computeRunPace

```
dist = 5
```

Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

Workspace:
MATLAB

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Workspace:
computeRunPace

```
dist = 5
min = 23
```

Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

Workspace:
MATLAB

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Workspace:
computeRunPace

```
dist = 5
min = 23
s = 15
```

Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

Workspace:
MATLAB

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Workspace:
computeRunPace

```
dist = 5
min = 23
s = 15
totalMinutes =
23.25
```

Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

Workspace:
MATLAB

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Workspace:
computeRunPace

```
dist = 5
min = 23
s = 15
totalMinutes =
23.25
minperkm = 4.65
```

Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

Workspace:
MATLAB

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Workspace:
computeRunPace

```
dist = 5
min = 23
s = 15
totalMinutes =
23.25
minperkm = 4.65
```

Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

Workspace:
MATLAB

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Workspace:
computeRunPace

```
dist = 5
min = 23
s = 15
totalMinutes =
23.25
minperkm = 4.65
```


Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

```
mpkm = 4.65
```

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Workspace: MATLAB

```
mpkm = 4.65
```

Workspace: computeRunPace

```
dist = 5
min = 23
s = 15
totalMinutes =
23.25
minperkm = 4.65
```

Example: Function Execution

```
>>mpkm=computeRunPace(5,23,15)
```

```
mpkm = 4.65
```

Workspace:
MATLAB

```
mpkm = 4.65
```

m-file computeRunPace.m

```
function minperkm = computeRunPace(dist, min, s)
% Computes the time per km...

    totalMinutes = min + s/60;
    minperkm = totalMinutes/dist;
end
```

Combine Scripts and Functions

Functions

- ▶ Create functions whenever a certain “algorithm” or multi-row computation takes place more than once
- ▶ Built-in MATLAB functions are written in this way
(write `type functionName` to see)

Scripts

- ▶ Define input values
- ▶ Call different functions
- ▶ Process and visualize output from functions

Combine Scripts and Functions

Functions

- ▶ Create functions whenever a certain “algorithm” or multi-row computation takes place more than once
- ▶ Built-in MATLAB functions are written in this way
(write `type functionName` to see)

Scripts

- ▶ Define input values
- ▶ Call different functions
- ▶ Process and visualize output from functions

This is how I work

- ▶ Check out my MATLAB code:
<https://github.com/emilbjornson/>
- ▶ I publish research code online — simple reproducibility

Visualization

Suppose we want to plot (visualize) the mathematical function $y = \sin(x)$ for $0 \leq x \leq 10$:

m-file plotSine.m

Visualization

Suppose we want to plot (visualize) the mathematical function $y = \sin(x)$ for $0 \leq x \leq 10$:

m-file plotSine.m

```
x = 0:0.1:10; % The x for which y should be computed
```

Visualization

Suppose we want to plot (visualize) the mathematical function $y = \sin(x)$ for $0 \leq x \leq 10$:

m-file plotSine.m

```
x = 0:0.1:10; % The x for which y should be computed  
y = sin(x);
```

Visualization

Suppose we want to plot (visualize) the mathematical function $y = \sin(x)$ for $0 \leq x \leq 10$:

m-file plotSine.m

```
x = 0:0.1:10; % The x for which y should be computed
y = sin(x);

figure; % Open a new figure ready for plotting
```


Visualization

Suppose we want to plot (visualize) the mathematical function $y = \sin(x)$ for $0 \leq x \leq 10$:

m-file plotSine.m

```
x = 0:0.1:10; % The x for which y should be computed
y = sin(x);

figure; % Open a new figure ready for plotting
plot(x,y) % Plot y as a function of x
```

Visualization

Suppose we want to plot (visualize) the mathematical function $y = \sin(x)$ for $0 \leq x \leq 10$:

m-file plotSine.m

```
x = 0:0.1:10; % The x for which y should be computed  
y = sin(x);
```

```
figure; % Open a new figure ready for plotting  
plot(x,y) % Plot y as a function of x  
xlabel('x') % Give a name to the horizontal axis
```

Visualization

Suppose we want to plot (visualize) the mathematical function $y = \sin(x)$ for $0 \leq x \leq 10$:

m-file plotSine.m

```
x = 0:0.1:10; % The x for which y should be computed
y = sin(x);

figure; % Open a new figure ready for plotting
plot(x,y) % Plot y as a function of x
xlabel('x') % Give a name to the horizontal axis
ylabel('y = sin(x)') % Give a name to the vertical axis
```

Visualization

Suppose we want to plot (visualize) the mathematical function $y = \sin(x)$ for $0 \leq x \leq 10$:

m-file plotSine.m

```
x = 0:0.1:10; % The x for which y should be computed
y = sin(x);

figure; % Open a new figure ready for plotting
plot(x,y) % Plot y as a function of x
xlabel('x') % Give a name to the horizontal axis
ylabel('y = sin(x)') % Give a name to the vertical axis
title('My first plot') % Give a name to the whole figure
```

Visualization: Many types

Many functions for plotting data:

- ▶ 2D line graphs: `plot`, `semilogx` (horizontal log-scale)
- ▶ 2D bar graphs: `bar`, `histogram`

Visualization: Many types

Many functions for plotting data:

- ▶ 2D line graphs: `plot`, `semilogx` (horizontal log-scale)
- ▶ 2D bar graphs: `bar`, `histogram`
- ▶ 3D line graphs: `plot3`
- ▶ 3D bar and mesh graphs: `bar3`, `mesh`
- ▶ 3D surface graphs: `surf`, `sphere`, `ellipsoid`

Visualization: Many types

Many functions for plotting data:

- ▶ 2D line graphs: `plot`, `semilogx` (horizontal log-scale)
- ▶ 2D bar graphs: `bar`, `histogram`
- ▶ 3D line graphs: `plot3`
- ▶ 3D bar and mesh graphs: `bar3`, `mesh`
- ▶ 3D surface graphs: `surf`, `sphere`, `ellipsoid`

Use `help` to read more!

Visualization: Many types

Many functions for plotting data:

- ▶ 2D line graphs: `plot`, `semilogx` (horizontal log-scale)
- ▶ 2D bar graphs: `bar`, `histogram`
- ▶ 3D line graphs: `plot3`
- ▶ 3D bar and mesh graphs: `bar3`, `mesh`
- ▶ 3D surface graphs: `surf`, `sphere`, `ellipsoid`

Use `help` to read more!

Adapt plots:

- ▶ Almost everything can be tailored.
- ▶ Use the “Property Editor” in menu “View” of a figure

Control Structures

Some “behaviors” depend strongly on the input:

- ▶ Does your bank account have enough money or not?

Some pieces of code is repeated:

- ▶ Do you need to run the same lines of code multiple times?
- ▶ Do you know how many times in advance?

Control Structures

Some “behaviors” depend strongly on the input:

- ▶ Does your bank account have enough money or not?

Some pieces of code is repeated:

- ▶ Do you need to run the same lines of code multiple times?
- ▶ Do you know how many times in advance?

MATLAB has several *control structures*:

- ▶ if statements
- ▶ while loops
- ▶ for loops

These are similar to other programming languages.

if Clauses

General syntax:

```
if condition
    % statements/commands if condition is true
else
    % statements/commands if condition is false
end
```

if Clauses

General syntax:

```
if condition
    % statements/commands if condition is true
else
    % statements/commands if condition is false
end
```

Writing conditions using logics

- ▶ Use operators such as: `>` `>=` `==` `&&` `||` `~=` `<` `<=`
- ▶ Suppose `savings` is a variable with the amount on your bank account.
- ▶ Examples: `savings >= 0`, `(savings >= 0) || (salary > 35000)`

Example: if Clauses

Example

A bank account has 2% interest on savings and charges 14% interest for credits. Write a function to compute the interest given an amount.

Example: if Clauses

Example

A bank account has 2% interest on savings and charges 14% interest for credits. Write a function to compute the interest given an amount.

m-file computeBankInterest.m

```
function interest = computeBankInterest(amount)
% Computes annual interest for a given amount

if amount >= 0
    interest = 0.02*amount;
else
    interest = 0.14*amount;
end

end
```

Guard Towards Errors

If statements can be used to avoid unexpected behaviors

- ▶ **Example:** `computeBankInterest(amount)` **cannot** handle complex numbers

Guard Towards Errors

If statements can be used to avoid unexpected behaviors

- ▶ **Example:** `computeBankInterest(amount)` cannot handle complex numbers
- ▶ Can be checked and handled as:

```
if imag(amount) ~= 0
    error('There is no imaginary money!');
end
```


Guard Towards Errors

If statements can be used to avoid unexpected behaviors

- ▶ **Example:** `computeBankInterest(amount)` cannot handle complex numbers
- ▶ Can be checked and handled as:

```
if imag(amount) ~= 0
    error('There is no imaginary money!');
end
```

- ▶ `imag()` gives the imaginary part of a scalar/vector/matrix
- ▶ `error()` displays an error message
- ▶ Text strings are written as 'message'
- ▶ Alternative: `disp()` displays a non-error-related message

while Loops

- ▶ Repeat similar computations *while* a condition is fulfilled
 - ▶ Condition is checked only at beginning of each loop
 - ▶ Be sure that the condition will eventually be false — otherwise the loop runs forever!

while Loops

- ▶ Repeat similar computations *while* a condition is fulfilled
 - ▶ Condition is checked only at beginning of each loop
 - ▶ Be sure that the condition will eventually be false — otherwise the loop runs forever!

- ▶ General syntax:

```
while condition
    % statement/commands to be repeated
end
```

Example: while Loops

Example

Suppose you have borrowed 1 million kr from the bank. The bank charges 0.25% interest per month. You amortize 5,000 kr per month. How many months will it take to repay the loan?

Example: while Loops

Example

Suppose you have borrowed 1 million kr from the bank. The bank charges 0.25% interest per month. You amortize 5,000 kr per month. How many months will it take to repay the loan?

m-file predictLoan.m

```
currentLoan = 1e6; % The initial loan is 1,000,000 kr
monthlyPayment = 5000; % You pay 5000 kr each month
monthlyInterest = 0.0025; % The bank charges 0.25% per month
monthNumber = 0; % Keep track of month number

while currentLoan >= 0
    currentLoan = currentLoan + currentLoan*monthlyInterest; %Apply interest rate
    currentLoan = currentLoan - monthlyPayment; %Reduce loan by monthly payment
    monthNumber = monthNumber + 1;
end

% monthNumber will now contain the month when you have repaid your loan
% Be sure that monthlyPayment > currentLoan*monthlyInterest, otherwise it never stops!
```

for Loops

- ▶ If you know how many time to repeat commands
 - ▶ More compact to use `for`-loops instead of `while`

for Loops

- ▶ If you know how many time to repeat commands
 - ▶ More compact to use `for`-loops instead of `while`

- ▶ General syntax:

```
for var = vector with values  
    % statement/commands to be repeated  
end
```

Example: for Loops

Example

Suppose you start saving 500 kr per month when your kid is born. The monthly interest is 0.17% (2% per year). How much will the kid have at the age of 18?

Example: for Loops

Example

Suppose you start saving 500 kr per month when your kid is born. The monthly interest is 0.17% (2% per year). How much will the kid have at the age of 18?

m-file predictSavings.m

```
currentSaving = 0; % Bank account is empty in advance
monthlySaving = 500; % You save 500 kr per month
montlyInterest = 0.0017; % The bank interest is 0.17% per month

numberOfMonths = 12*18; % Compute number of months before turning 18

for index = 1:numberOfMonths
    currentSaving = currentSaving + currentSaving*montlyInterest; %Apply interest rate
    currentSaving = currentSaving + monthlySaving; % Add monthly saving
end

% currentSaving will now contain the savings at the age of 18
```

Summary

- ▶ MATLAB is useful in many different computations

Summary

- ▶ MATLAB is useful in many different computations
- ▶ Standard tool at universities and many companies — more than 1 million users

Summary

- ▶ MATLAB is useful in many different computations
- ▶ Standard tool at universities and many companies — more than 1 million users
- ▶ Choose variable names carefully — and write comments

Summary

- ▶ MATLAB is useful in many different computations
- ▶ Standard tool at universities and many companies — more than 1 million users
- ▶ Choose variable names carefully — and write comments
- ▶ Use scripts and functions, it *will save you time*

Summary

- ▶ MATLAB is useful in many different computations
- ▶ Standard tool at universities and many companies — more than 1 million users
- ▶ Choose variable names carefully — and write comments
- ▶ Use scripts and functions, it *will save you time*
- ▶ Control statements:
 - ▶ `if` statements — do different things depending on a condition
 - ▶ `for` loops — repeat computations for a predetermined set of values
 - ▶ `while` loops — repeat computations until a condition is no longer fulfilled

Summary

- ▶ MATLAB is useful in many different computations
- ▶ Standard tool at universities and many companies — more than 1 million users
- ▶ Choose variable names carefully — and write comments
- ▶ Use scripts and functions, it *will save you time*
- ▶ Control statements:
 - ▶ `if` statements — do different things depending on a condition
 - ▶ `for` loops — repeat computations for a predetermined set of values
 - ▶ `while` loops — repeat computations until a condition is no longer fulfilled
- ▶ Make use of the help system to extend your knowledge!!!

Good luck with the course!

Have fun with MATLAB!

Learn by exploration!