

How to create a .pem file for SSL Certificate Installations

 [suse.com/support/kb/doc](https://www.suse.com/support/kb/doc)

SUSE Support

Here When You Need Us

This document (**7013103**) is provided subject to the [disclaimer](#) at the end of this document.

Environment

SUSE Linux Enterprise Server

Situation

How to create a .pem file for SSL Certificate Installations

Resolution

Privacy Enhanced Mail (PEM) files are concatenated certificate containers frequently used in certificate installations when multiple certificates that form a complete chain are being imported as a single file. They are a defined standard in RFCs [1421](#) through [1424](#). They can be thought of as a layered container of chained certificates. A *.pem* file is a container format that may just include the public certificate or the entire certificate chain (private key, public key, root certificates):

- Private Key
- Server Certificate (crt, public key)
- *(optional) Intermediate CA and/or bundles if signed by a 3rd party*

How to create a self-signed PEM file

```
openssl req -newkey rsa:2048 -new -nodes -x509 -days 3650 -keyout key.pem -out cert.pem
```

How to create a PEM file from existing certificate files that form a chain

- (optional) Remove the password from the Private Key by following the steps listed below:

```
openssl rsa -in server.key -out nopassword.key
```

Note: Enter the pass phrase of the Private Key.

- Combine the private key, public certificate and any 3rd party intermediate certificate files:

```
cat nopassword.key > server.pem
cat server.crt >> server.pem
```

Note: Repeat this step as needed for third-party certificate chain files, bundles, etc:

```
cat intermediate.crt >> server.pem
```

Cause

Additional Information

How to create a PEM file with the help of an automated script:

- Download NetIQ Cool Tool [OpenSSL-Toolkit](#).
- Select Create Certificates | PEM with key and entire trust chain
- Provide the full path to the directory containing the certificate files.
- Provide the filenames of the following:
 - private key
 - public key (server crt)
 - (conditional) password for private key
 - (conditional) any intermediate certificate chain file(s)

For additional information, please see [TID 7015502](#) - Common Mistakes in SSL Certificate Management & Implementation.

The following details the structure of a typical .pem file (including the entire certificate chain):

```
-----BEGIN RSA PRIVATE KEY-----
(Private Key: domain_name.key contents)
-----END RSA PRIVATE KEY-----
-----BEGIN CERTIFICATE-----
(Primary SSL certificate: domain_name.crt contents)
-----END CERTIFICATE-----
-----BEGIN CERTIFICATE-----
(Intermediate certificate: certChainCA.crt contents)
-----END CERTIFICATE-----
```

Disclaimer

This Support Knowledgebase provides a valuable tool for SUSE customers and parties interested in our products and solutions to acquire information, ideas and learn from one another. Materials are provided for informational, personal or non-commercial use within your organization and are presented "AS IS" WITHOUT WARRANTY OF ANY KIND.

- **Document ID:**7013103
- **Creation Date:** 26-Aug-2013
- **Modified Date:**03-Mar-2020
-

SUSE Linux Enterprise Server

[< Back to Support Search](#)

For questions or concerns with the SUSE Knowledgebase please contact:
tidfeedback@suse.com

SUSE Support Forums

Get your questions answered by experienced Sys Ops or interact with other SUSE community experts.

[Join Our Community](#)

Open an Incident

Open an incident with SUSE Technical Support, manage your subscriptions, download patches, or manage user access.

[Go to Customer Center](#)