

```
sudo apt update
sudo apt install openjdk-17-jdk -y
```

```
sudo apt update
sudo apt install tesseract-ocr tesseract-ocr-spa -y
sudo apt install imagemagick -y
which convert
which tesseract
tesseract --version
java --version
```

```
tar -xvzf solr-9.9.0.tgz
cp solr-9.9.0.tgz /home/benja/solr-9.9.0
cd solr-9.9.0/
sudo bash bin/install_solr_service.sh ../solr-9.9.0.tgz
cd /opt/solr-9.9.0
cd modules/
cd extraction/lib
sudo unzip tika-parsers-1.28.5.jar
"org/apache/tika/parser/ocr/TesseractOCRConfig.properties" -d ./extracted
sudo vim extracted/org/apache/tika/parser/ocr/TesseractOCRConfig.properties
cd extracted/
sudo jar uf ../tika-parsers-1.28.5.jar
org/apache/tika/parser/ocr/TesseractOCRConfig.properties
cd ..
sudo rm -rf extracted
sudo unzip -p tika-app-3.0.0-BETA.jar org/apache/tika/parser/ocr/TesseractOCRConfig.properties
sudo unzip -p tika-app-3.0.0-BETA.jar org/apache/tika/parser/ocr/TesseractOCRConfig.properties
sudo unzip -p tika-app-3.0.0-BETA.jar org/apache/tika/parser/ocr/TesseractOCRConfig.properties
sudo unzip -p tika-parsers-1.28.5.jar org/apache/tika/parser/ocr/TesseractOCRConfig.properties
TesseractOCRConfig.properties
# Licensed to the Apache Software Foundation (ASF) under one or more
# contributor license agreements. See the NOTICE file distributed with
# this work for additional information regarding copyright ownership.
# The ASF licenses this file to You under the Apache License, Version 2.0
# (the "License"); you may not use this file except in compliance with
# the License. You may obtain a copy of the License at
#
# http://www.apache.org/licenses/LICENSE-2.0
#
# Unless required by applicable law or agreed to in writing, software
# distributed under the License is distributed on an "AS IS" BASIS,
# WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
# See the License for the specific language governing permissions and
# limitations under the License.

# Tesseract properties
tesseractPath=/usr/bin/tesseract
```

```
language=spa
pageSegMode=1
maxFileSizeToOcr=2147483647
minFileSizeToOcr=0
timeout=120
#txt or hocr
outputType=txt
preserveInterwordSpacing=false

# properties for image processing
# to enable processing, set enableImageProcessing to 1
enableImageProcessing=0
ImageMagickPath=/usr/bin/convert
density=300
depth=4
colorspace=gray
filter=triangle
resize=900
applyRotation=false
echo 'vm.swappiness=1' | sudo tee -a /etc/sysctl.conf
cd /opt/solr
bin/solr start -s /var/solr/data
ls -ld /home/benja/solr-9.9.0
sudo mkdir -p /var/solr/data
sudo chown $USER:$USER /var/solr/data

sudo chown -R solr:solr /var/solr

sudo -u solr /opt/solr/bin/solr create \
  -c primer_instancia \
  -d _default \
  --solr-url http://localhost:8983

curl http://localhost:8983/solr/primer_instancia/config \
  -H 'Content-type: application/json' \
  -d '{
    "set-user-property": {
      "update.autoCreateFields":"false"
    }
  }'
curl http://localhost:8983/solr/primer_instancia/config/overlay
```

Definir campos uno por uno

acta

```
curl -X POST -H 'Content-type:application/json' \  
  --data-binary '{  
    "add-field": {  
      "name": "acta",  
      "type": "string",  
      "indexed": true,  
      "stored": true,  
      "multiValued": false,  
      "required": false  
    }  
  }' \  
  "http://localhost:8983/solr/primer_instancia/schema"
```

fecha

```
curl -X POST -H 'Content-type:application/json' \  
  --data-binary '{  
    "add-field": {  
      "name": "fecha",  
      "type": "string",  
      "indexed": true,  
      "stored": true,  
      "multiValued": false,  
      "required": false  
    }  
  }' \  
  "http://localhost:8983/solr/primer_instancia/schema"
```

permanente

```
curl -X POST -H 'Content-type:application/json' \  
  --data-binary '{  
    "add-field": {  
      "name": "permanente",  
      "type": "string",  
      "indexed": true,  
      "stored": true,  
      "multiValued": false,  
      "required": false  
    }  
  }' \  
  "http://localhost:8983/solr/primer_instancia/schema"
```

tipo

```
curl -X POST -H 'Content-type:application/json' \  
  --data-binary '{  
    "add-field": {
```

```

    "name": "tipo",
    "type": "string",
    "indexed": true,
    "stored": true,
    "multiValued": false,
    "required": false
  }
} \
"http://localhost:8983/solr/primer_instancia/schema"

```

contenido

```

curl -X POST -H 'Content-type:application/json' \
--data-binary '{
  "add-field": {
    "name": "contenido",
    "type": "text_general",
    "indexed": true,
    "stored": true,
    "multiValued": false,
    "required": false
  }
} \
"http://localhost:8983/solr/primer\_instancia/schema"

```

vim /etc/default/solr.in.sh

SOLR_MODULES="extraction"

SOLR_OPTS="\$SOLR_OPTS -Dsolr.config.lib.enabled=true"

SOLR_JAVA_MEM="-Xms2g -Xmx2g"

SOLR_OPTS="\$SOLR_OPTS -Djetty.host=127.0.0.1"

vim /var/solr/data/primer_instancia/conf/solrconfig.xml

<lib dir="\${solr.install.dir:../../..}/modules/extraction/lib" regex=".*\.jar"/>

<requestHandler name="/update/extract" class="solr.extraction.ExtractingRequestHandler" startup="lazy">

<lst name="defaults">

<str name="fmap.content">contenido</str>

<str name="uprefix">ignored_</str>

</lst>

</requestHandler>

<requestHandler name="/select" class="solr.SearchHandler">

<lst name="defaults">

<str name="echoParams">explicit</str>

<str name="df">contenido</str> <!-- Campo predeterminado para la consulta -->

<str name="wt">xml</str>

<str name="indent">true</str>

```

<str name="defType">edismax</str> <!-- Usar edismax query parser -->
<str name="q.op">OR</str> <!-- Operador predeterminado -->

<str name="hl">true</str>
<str name="hl.fl">contenido</str>
<str name="hl.fragsize">0</str> <!-- Desactivar la fragmentación -->
<str name="hl.simple.pre"><![CDATA[<span class="highlight">]]></str>
<str name="hl.simple.post"><![CDATA[</span>]]></str>
</lst>
</requestHandler>

```

cp -r /opt/solr/server/solr/configsets /home/benja/proyecto--> segunda instancia previamente

Para crear la segunda instancia

```

cd /home/benja
sudo cp -a solr-9.9.0 /opt/solr2
sudo useradd --system --home /var/solr2 --shell /bin/false solr2 || true
sudo mkdir -p /var/solr2
sudo chown -R solr2:solr2 /var/solr2
sudo cp /etc/default/solr.in.sh /etc/default/solr2.in.sh
sudo vim /etc/default/solr2.in.sh
sudo chown -R solr2:solr2 /opt/solr2
sudo cp /var/solr/log4j2.xml /var/solr2/log4j2.xml
sudo mkdir -p /var/solr2/logs
sudo chown -R solr2:solr2 /var/solr2/logs
sudo vim /etc/systemd/system/solr2.service

```

[Unit]

Description=Apache Solr2 standalone search server

After=network.target

[Service]

Type=simple

User=solr2

Group=solr2

EnvironmentFile=-/etc/default/solr2.[in.sh](#)

WorkingDirectory=/opt/solr2

ExecStart=/opt/solr2/bin/solr start -f -p \${SOLR_PORT} -s \${SOLR_HOME}

ExecStop=/opt/solr2/bin/solr stop -p \${SOLR_PORT}

Restart=on-failure

LimitNOFILE=65535

[Install]

WantedBy=multi-user.target

sudo chown -R solr2:solr2 /opt/solr2

sudo chown -R solr2:solr2 /var/solr2

sudo systemctl daemon-reload

sudo systemctl enable solr2

sudo systemctl restart solr2

sudo systemctl status solr2 --no-pager

sudo vim /etc/default/solr2.in.sh

PIDs de esta instancia

SOLR_PID_DIR="/var/solr2"

Carpeta de datos (cores de solr2)

SOLR_HOME="/var/solr2/data"

Configuración de logs/log4j

LOG4J_PROPS="/var/solr2/log4j2.xml"

SOLR_LOGS_DIR="/var/solr2/logs"

Puerto diferente al solr1 (que usa 8983 por defecto)

SOLR_PORT="8985"

SOLR_HOST="127.0.0.1"

Si quieres usar módulos adicionales como extracción (para Tika, etc.)

SOLR_MODULES="extraction"

Activar librerías externas (como Tika, etc.)

```
SOLR_OPTS="-Dsolr.config.lib.enabled=true"
SOLR_JAVA_MEM="-Xms2g -Xmx2g"
```

```
sudo mkdir -p /var/solr2/data
sudo chown -R solr2:solr2 /var/solr2/data
sudo systemctl daemon-reload
sudo systemctl restart solr2
```

```
sudo systemctl daemon-reload
sudo systemctl restart solr2
sudo systemctl status solr2 --no-pager
sudo -u solr2 /opt/solr2/bin/solr start -f -p 8985 -s /var/solr2/data
```

Ahora configurar tika,tesseract,copiar configsets, crear nucleo,crear campos,desactivar la creacion automatica, y comprobar el overlay.

```
cp -r /home/benja/proyecto/configsets /var/solr2/data
```

```
sudo -u solr2 /opt/solr2/bin/solr create \
  -c segunda_instancia \
  -d _default \
  --solr-url http://localhost:8985
```

```
curl http://localhost:8985/solr/segunda_instancia/config \
  -H 'Content-type: application/json' \
  -d '{
    "set-user-property": {
      "update.autoCreateFields":"false"
    }
  }'
```

```
curl http://localhost:8985/solr/segunda\_instancia/config/overlay
```

Definir campos uno por uno

acta

```
curl -X POST -H 'Content-type:application/json' \  
  --data-binary '{  
    "add-field": {  
      "name": "acta",  
      "type": "string",  
      "indexed": true,  
      "stored": true,  
      "multiValued": false,  
      "required": false  
    }  
  }' \  
  "http://localhost:8985/solr/segunda_instancia/schema"
```

fecha

```
curl -X POST -H 'Content-type:application/json' \  
  --data-binary '{  
    "add-field": {  
      "name": "fecha",  
      "type": "string",  
      "indexed": true,  
      "stored": true,  
      "multiValued": false,  
      "required": false  
    }  
  }' \  
  "http://localhost:8985/solr/segunda_instancia/schema"
```

permanente

```
curl -X POST -H 'Content-type:application/json' \  
  --data-binary '{  
    "add-field": {  
      "name": "permanente",  
      "type": "string",  
      "indexed": true,  
      "stored": true,  
      "multiValued": false,  
      "required": false  
    }  
  }' \  
  "http://localhost:8985/solr/segunda_instancia/schema"
```

tipo

```
curl -X POST -H 'Content-type:application/json' \  
  --data-binary '{
```



```

"add-field": {
  "name": "tipo",
  "type": "string",
  "indexed": true,
  "stored": true,
  "multiValued": false,
  "required": false
}
}\
"http://localhost:8985/solr/segunda_instancia/schema"

```

contenido

```

curl -X POST -H 'Content-type:application/json' \
--data-binary '{
  "add-field": {
    "name": "contenido",
    "type": "text_general",
    "indexed": true,
    "stored": true,
    "multiValued": false,
    "required": false
  }
}' \
"http://localhost:8985/solr/segunda_instancia/schema"

```

```

root@alob:/home/benja# systemctl restart solr
root@alob:/home/benja# systemctl status solr
● solr.service - LSB: Controls Apache Solr as a Service
   Loaded: loaded (/etc/init.d/solr; generated)
   Active: active (exited) since Sat 2026-02-14 21:03:30 CST; 9s ago
     Docs: man:systemd-sysv-generator(8)
  Process: 1300346 ExecStart=/etc/init.d/solr start (code=exited, status=0/SUCCESS)
    CPU: 17ms

feb 14 21:03:20 alob systemd[1]: Starting solr.service - LSB: Controls Apache Solr as a Service...
feb 14 21:03:20 alob su[1300348]: (to solr) root on none
feb 14 21:03:20 alob su[1300348]: pam_unix(su-l:session): session opened for user solr(uid=112) by (uid=0)
feb 14 21:03:29 alob solr[1300412]: Started Solr server on port 8983 (pid=1300405). Happy searching!
feb 14 21:03:30 alob systemd[1]: Started solr.service - LSB: Controls Apache Solr as a Service.
root@alob:/home/benja# sudo cp -a solr-9.9.0 /opt/solr2
root@alob:/home/benja# useradd --system --home /var/solr2 --shell /bin/false solr2 || true
root@alob:/home/benja# mkdir -p /var/solr2
root@alob:/home/benja# chown -R solr2:solr2 /var/solr2
root@alob:/home/benja# cp /etc/default/solr.in.sh /etc/default/solr2.in.sh
root@alob:/home/benja# vim /etc/default/solr2.in.sh
root@alob:/home/benja# vim /etc/default/solr2.in.sh
root@alob:/home/benja# chown -R solr2:solr2 /opt/solr2
root@alob:/home/benja# cp /var/solr/log4j2.xml /var/solr2/log4j2.xml
root@alob:/home/benja# mkdir -p /var/solr2/logs
root@alob:/home/benja# chown -R solr2:solr2 /var/solr2/logs
root@alob:/home/benja# vim /etc/systemd/system/solr2.service
root@alob:/home/benja# chown -R solr2:solr2 /opt/solr2
root@alob:/home/benja# chown -R solr2:solr2 /var/solr2
root@alob:/home/benja# mkdir -p /var/solr2/data
root@alob:/home/benja# chown -R solr2:solr2 /var/solr2/data
root@alob:/home/benja# sudo systemctl daemon-reload
root@alob:/home/benja# systemctl enable solr2
Created symlink /etc/systemd/system/multi-user.target.wants/solr2.service -> /etc/systemd/system/solr2.service.
root@alob:/home/benja#

```

ya le habia dado permisos a /var/solr2 y fallo aun asi

```
root@alob:/home/benja# mkdir -p /var/solr2
root@alob:/home/benja# chown -R solr2:solr2 /var/solr2
root@alob:/home/benja# cp /etc/default/solr.in.sh /etc/default/solr2.in.sh
root@alob:/home/benja# vim /etc/default/solr2.in.sh
root@alob:/home/benja# vim /etc/default/solr2.in.sh
root@alob:/home/benja# chown -R solr2:solr2 /opt/solr2
root@alob:/home/benja# cp /var/solr/log4j2.xml /var/solr2/log4j2.xml
root@alob:/home/benja# mkdir -p /var/solr2/logs
root@alob:/home/benja# chown -R solr2:solr2 /var/solr2/logs
root@alob:/home/benja# vim /etc/systemd/system/solr2.service
root@alob:/home/benja# chown -R solr2:solr2 /opt/solr2
root@alob:/home/benja# chown -R solr2:solr2 /var/solr2
root@alob:/home/benja# mkdir -p /var/solr2/data
root@alob:/home/benja# chown -R solr2:solr2 /var/solr2/data
root@alob:/home/benja# sudo systemctl daemon-reload
root@alob:/home/benja# systemctl enable solr2
Created symlink /etc/systemd/system/multi-user.target.wants/solr2.service → /etc/systemd/system/solr2.service.
root@alob:/home/benja# sudo systemctl restart solr2
root@alob:/home/benja# sudo systemctl status solr2 --no-pager
* solr2.service - Apache Solr2 standalone search server
   Loaded: loaded (/etc/systemd/system/solr2.service; enabled; preset: enabled)
   Active: failed (Result: exit-code) since Sat 2026-02-14 21:25:02 CST; 766ms ago
     Duration: 921ms
    Process: 1301548 ExecStart=/opt/solr2/bin/solr start -f -p ${SOLR_PORT} -s ${SOLR_HOME} (code=exited, status=1/FAILURE)
   Main PID: 1301548 (code=exited, status=1/FAILURE)
      CPU: 3.423s

feb 14 21:25:02 alob systemd[1]: solr2.service: Scheduled restart job, restart counter is at 10.
feb 14 21:25:02 alob systemd[1]: solr2.service: Start request repeated too quickly.
feb 14 21:25:02 alob systemd[1]: solr2.service: Failed with result 'exit-code'.
feb 14 21:25:02 alob systemd[1]: Failed to start solr2.service - Apache Solr2 standalone search server.
feb 14 21:25:02 alob systemd[1]: solr2.service: Consumed 3.423s CPU time.
root@alob:/home/benja# sudo chown -R solr2:solr2 /opt/solr2
sudo chown -R solr2:solr2 /var/solr2
```

volvi a ejecutar los mismos comandos menos enable y ahora si quiso

```
root@alob:/home/benja# systemctl enable solr2
Created symlink /etc/systemd/system/multi-user.target.wants/solr2.service → /etc/systemd/system/solr2.service.
root@alob:/home/benja# sudo systemctl restart solr2
root@alob:/home/benja# sudo systemctl status solr2 --no-pager
* solr2.service - Apache Solr2 standalone search server
   Loaded: loaded (/etc/systemd/system/solr2.service; enabled; preset: enabled)
   Active: failed (Result: exit-code) since Sat 2026-02-14 21:25:02 CST; 766ms ago
     Duration: 921ms
    Process: 1301548 ExecStart=/opt/solr2/bin/solr start -f -p ${SOLR_PORT} -s ${SOLR_HOME} (code=exited, status=1/FAILURE)
   Main PID: 1301548 (code=exited, status=1/FAILURE)
      CPU: 3.423s

feb 14 21:25:02 alob systemd[1]: solr2.service: Scheduled restart job, restart counter is at 10.
feb 14 21:25:02 alob systemd[1]: solr2.service: Start request repeated too quickly.
feb 14 21:25:02 alob systemd[1]: solr2.service: Failed with result 'exit-code'.
feb 14 21:25:02 alob systemd[1]: Failed to start solr2.service - Apache Solr2 standalone search server.
feb 14 21:25:02 alob systemd[1]: solr2.service: Consumed 3.423s CPU time.
root@alob:/home/benja# sudo chown -R solr2:solr2 /opt/solr2
sudo chown -R solr2:solr2 /var/solr2
sudo systemctl daemon-reload
sudo systemctl restart solr2
sudo systemctl status solr2 --no-pager
* solr2.service - Apache Solr2 standalone search server
   Loaded: loaded (/etc/systemd/system/solr2.service; enabled; preset: enabled)
   Active: active (running) since Sat 2026-02-14 21:26:44 CST; 35ms ago
     Main PID: 1301699 (bash)
       Tasks: 2 (limit: 9431)
      Memory: 844.0K (peak: 2.0M)
         CPU: 30ms
        CGroup: /system.slice/solr2.service
                └─1301699 bash /opt/solr2/bin/solr start -f -p 8985 -s /var/solr2/data

feb 14 21:26:44 alob systemd[1]: Started solr2.service - Apache Solr2 standalone search server.
root@alob:/home/benja#
```