

The Effect of Contamination on Contamination Limit Regulation: US Coal Mining and Drinking Water Utilities

Emil Kee-Tui

Charles H. Dyson School of Applied Economics and Management, Cornell University

August 2026

Abstract

How do firms and regulators respond to increases in contamination under contamination control regulation monitored through self reported compliance? Firms have an incentive to under-report to avoid the costs of self reporting and conceal violations; both incentives increase as contamination rises, undermining contamination monitoring and enforcement. I study this in the context of US drinking water utilities and regulators after exogenous increases in water contamination from coal mining between 1985 and 2005. I construct an instrumental variable for coal production upstream of utility water intakes based on changes in coal production following the Acid Rain Program. I find that coal mining increases utility water contamination but does not lead to observable contaminant concentration violations. Upstream coal mining increases utilities under-reporting, partly due to self-reporting costs rising with contamination. Regulators substitute the firm's monitoring obligations by conducting more sanitary visits at firms that reduce self reporting due to contamination. Regulators fail to increase formal enforcement on under-reporting as contamination rises despite increasing sanitary visits and enforcement visits, displaying an imperfect conversion between inspections and enforcement.

1 Introduction

Environmental regulation often seeks to induce firms to reduce environmental contamination and self report contamination compliance. Compliance monitoring is the first step in enforcing the regulation and in ensuring that the regulation has any effectiveness. A first order question is how self monitoring responds when contamination increases. Self reported compliance is common throughout regulatory regimes besides water quality. Regulations as diverse as income taxes and drinking water quality require regulated entities to self-report compliance. In this paper, I identify the response of firms and regulators to increasing contamination of a firm's regulated output in the context of US drinking water utilities exposed to an exogenous increase in water contamination from coal mining between 1985 and 2005.

Regulators, faced with constrained resources, favor self-reporting, which shifts the information gathering costs onto the regulated. However, self-reporters lack the incentive to disclose when the penalties for revealed non-compliance exceed the penalties for non-disclosure and when self-reporting requires costly effort. Regulators generate compliance through a combination of inspections and penalties. Successful inspections identify concealed violations, but any inspection shifts the cost of monitoring onto regulators, the efficiency of which is discussed in the literature on fiscal federalism. Successful penalties offset the firm's incentives to under-report and contaminate at levels that regulators deem unsafe. When the costs of self-reporting increase as contamination increases, for example, due to increasing self-reporting requirements, the firm's incentives to under-report also increase. Enforcement needs to keep up with the incentives to under-report. Contamination control regulations that increase self-monitoring requirements without increasing penalties for under-reporting can induce under-reporting, undermine the regulation's monitoring, and raise regulator's costs through inspections.

I confirm that coal mining raises contaminant concentrations measured at a subset of utilities between 1997 and 2005. Comparing utilities that experienced more upstream coal mining to those that experienced less upstream coal mining, I find that every additional 10 million short tons of coal mined upstream since 1985 increases mean arsenic concentrations by 0.0023 mg/L, approximately 100 percent of the average arsenic concentration level in the sample, selenium by 69 percent, and barium by 24 percent of their respective sample means.

Empirically identifying the impact of contamination on firm behavior requires separating the firm's choices over output and contamination. Separating a firm's output and contamination in most industries is challenging since firms can reduce contamination by

reducing output. For example, in the U.S., the Toxic Release Inventory requires firms to report emissions, handling, and use of chemicals above a reportable quantity. Firms can avoid the reporting requirement by emitting less or producing less (Zou 2021; Mu, Rubin, and Zou 2026). The contamination of drinking water at utilities from coal mining is the ideal setting to study the effect of contamination on self-reporting firms since the main source of water contamination that utilities face arises upstream as an externality of a production process that the utility does not directly control.

Identifying the causal effect of upstream coal mining on utilities is complicated by two sources of endogeneity. First, coal mines are located in areas with particular geological characteristics, such as coal seam accessibility and transportation corridors, that may also independently predict water quality and utility characteristics. Second, utilities may indirectly control coal production by successfully resisting upstream mine siting. Systems that successfully resist upstream mines may be better at maintaining compliance, generating a negative correlation between upstream mining and utility ability that understates the true contamination from mining.¹

I address these identification challenges by instrumenting for the number of coal mines upstream of a drinking water utility's water intakes, using the shift in the location of coal production caused by the Acid Rain Program (ARP). The ARP is federal legislation that forced coal fired power plants, the main consumers of coal, to reduce sulfur dioxide emissions by 1995. Plants complied by switching from high sulfur coal, with sulfur greater than two percent by weight, to low sulfur coal, with sulfur less than two percent by weight. The ARP created a nationally-determined shift in the demand for each mine's coal based on its sulfur content and independent of the characteristics of downstream drinking water utilities. I construct a panel of drinking water utilities downstream of active coal mines from 1985 to 2005. I measure the sulfur levels of coal and the annual coal production occurring in the watershed upstream of a utility's water intakes. Utility behavior is measured by drinking water quality violations and self-reporting violations.

Coal mining significantly raises the incidence of under-reporting but has no detectable effect on contaminant concentration violations. In particular, coal mining reduces utility self-reporting of water contamination from inorganic chemicals (IOC), arsenic, and nitrates by seven to nine percentage points. Utilities receive a self-reporting violation and not a water quality violation when they do not self-report water quality. Since self-reports are required to determine a contamination exceedance violation, the lack of violations

¹For example, the EPA Source Water Protection program can designate areas where drinking water is sourced and take an inventory of pollution from human activities or natural sources that pose the greatest threat to source water quality, making it more difficult to site pollution producing activities in these areas.

does not, by itself, demonstrate that coal mining does not lead to violations.

I investigate whether utilities reduce self-reporting rates following mining contamination due to the rising costs of self-reporting or to conceal a contamination exceedance violation. The literature has mainly found evidence of under-reporting being used to conceal non-compliance (Wallsten and Kosec 2008; S. A. Foster et al. 2019; Zou 2021; Mu, Rubin, and Zou 2026). I find that some reduction in self-reporting occurs due to the costs of self-reporting. Water utilities are required to increase self-monitoring for nitrates when nitrate concentrations exceed 50% of the contamination limit. I estimate the likelihood that a utility fails to self-report nitrate water quality increases by 26 percentage points when contaminant concentrations are greater than 50% of the contamination limit. These results are not causal, and the direction, rather than the magnitude, should be interpreted as suggestive evidence of under-reporting due to the costs of self-reporting.

I investigate regulator enforcement against utilities that experience rising contamination by measuring regulator inspections and enforcement. Regulator enforcement does not increase as contamination and under-reporting increase. I find that an additional active coal mine reduces the likelihood that a utility receives formal enforcement, despite the likelihood of receiving an enforcement visit increasing by 4 percentage points. Enforcement visits do not always translate into enforcement, such as fines and court ordered water treatment technology installation. This does not offset utilities' incentives to under-report as contamination rises.

Under-reporting of water quality presents a health risk of unknown contamination. As contamination increases and self-reporting falls, regulators substitute utility self-reporting with sanitary visits, shifting the burden of monitoring the regulation to the regulators. An additional active coal mine upstream of a utility increases the likelihood that a utility receives a sanitary visit from a regulator by 14 percentage points. This suggests that enforcement visits do not translate into actual enforcement and that sanitary visits are not, in themselves, enough of a deterrent to maintain self-reporting. Sanitary visits would not reveal contamination violations if utilities were not violating contamination limits or inspections they were ineffective at identifying violations (Mi, Zhang, and Liu 2026). I cannot distinguish these from each other. Monitoring gaps can be overcome by continuous monitoring technology that the regulator controls, making violations easier to spot and successful enforcement more likely. Literature on monitoring finds that regulated entities exploit gaps in monitoring coverage. Zou (2021) shows that ambient air quality deteriorates on days when monitors are not scheduled to operate, and Mu, Rubin, and Zou (2026) documents strategic shutdowns of pollution monitors.

My paper contributes to the literature on drinking water quality, particularly US drink-

ing water quality. US drinking water quality has improved substantially since the passage of the Safe Drinking Water Act ("SDWA") (David A Keiser and Shapiro 2019a); yet notable exceptions remain, such as the crisis in Flint, Michigan (Christensen, David A. Keiser, and Lade 2023). In addition, between 9 and 34 million people per year are served by utilities in violation of health-based standards (Allaire, Wu, and Lall 2018). Health-based standard violations do not include under-reported water quality and would undercount the contamination of water quality. The benefits of improving drinking water outweigh the costs due to the large health costs of contaminated drinking water (E. Hill and Ma 2017; David A Keiser and Shapiro 2019b; DiSalvo and E. L. Hill 2024; Marcus 2025).

I find that point source pollution from coal mining has an impact on drinking water quality. This is in contradiction to the literature that finds the gains from point source pollution in the modern era are often thought to be quite small. (Bingham et al. 2000) finds that point source pollution is already well regulated in the US and achieving zero emissions from point sources would only improve 10 percent of U.S. rivers and streams in EPA quality ladder rankings. The benefits of surface water regulation may be undervalued due to the difficulty of measuring them. Poor data might contribute to benefit undervaluation, although this can be overcome with IV (David A Keiser 2019). I similarly use an IV to estimate water contamination.

This paper contributes to work documenting the harmful impacts of coal mining. Since utilities provide drinking water to 85 percent of US households, their response to coal mining contamination is important for public health, especially as US federal energy policy under President Donald Trump has expanded mining access on federal lands and intervened to prevent planned coal-fired power plant retirements (U.S. President (Trump) 2025a; U.S. President (Trump) 2025b; U.S. President (Trump) 2025c; Daly 2025). Existing work documents coal mining's effects on air quality, greenhouse gas emissions, and health (Muller, Mendelsohn, and Nordhaus 2011; Parfitt 2024). The physical mechanism linking mining to water contamination is well established in the geochemical literature (J. G. Skousen, Ziemkiewicz, and McDonald 2019; Akcil and Koldas 2006; Ceto and Mahmud 2000; Rouhani, J. Skousen, and Tack 2023; Liang et al. 2017; Boente, Baragaño, and Gallego 2020). This literature has not established whether this contamination affects utility treated water and reaches households. This paper provides the first causal estimates of coal mining's downstream effect on drinking water quality at treated utilities in the United States, identifying that coal mining pollution crosses the gap from environmental contamination to piped household water.

I contribute to the literature on the economics of enforcement and monitoring of environmental regulation (Shimshack 2014). This is the first study to identify the effect of

contamination on enforcement and monitoring. The literature on monitoring and reporting has considered firms' motivations to underreport. In the literature studying water utility underreporting, it has been identified that the cause is attributed to hiding a contamination violation (Benneer, Jessoe, and Olmstead 2009; Naylor and Deaton n.d.; Andarge et al. 2025). The same motivations underlie underreporting at oil and gas firms (Lee 2020). The small cement industries are excluded from air quality reporting and their air quality goes unmonitored while having large health damages nonetheless (Ziorgiannis et al. 2023). I provide evidence about what makes an effective self reporting regulation which is discussed in other self reporting contexts, under reporting can still send signals about firms costs and self reporting programs can support command and control regulation (A. D. Foster and Gutierrez 2013; Anton, Deltas, and Khanna 2004). This is the first study to identify the cost of self reporting as one of the reasons for underreporting from drinking water utilities; the cost of self reporting has been identified as a reason for underreporting in tax regulation (Tazhitdinova 2018). The literature on monitoring and reporting has considered how to induce firms to self report and what constitutes efficient self reporting (Innes 1999). I find strong supporting evidence that low penalties and high sanitary visits lead firms to undercomply with the regulation. Low visits and high penalties are found to induce better self reporting (Malik 1993).

The literature on enforcement has found that enforcement is effective when its severity is non-linear and higher violations receive higher enforcement (Harford 1987). The literature has focused on on dynamic enforcement that increases fines when firms are repeat violators. It has been found that firm compliance improves when regulators target repeat offenders and dispense stricter enforcement to them (Blundell, Gowrisankaran, and Langer 2020; Blundell 2020). Duflo et al. 2018 find that regulators use inspections at plants selectively to target the worst polluters, and targeting enforcement increases future abatement. I show that enforcement ineffectively induces firms to comply when it does not respond by increasing enforcement at firms under-reporting while contamination is rising.

2 Institutional background

2.1 Drinking water utilities, regulators, and the Safe Drinking Water Act

I focus on drinking water utilities downstream of coal mines between 1985 and 2005. In particular, I focus on a class of drinking water utilities known legally as community wa-

ter systems that serve at least 25 consumers through at least 15 connections throughout the year, since these are regulated by the SDWA. The SDWA is a federal regulation that requires utilities to remove contaminants and self-report compliance to state regulators. Regulators issue a maximum contaminant level ("MCL") violation to a utility that self-reports a contaminant above the MCL. MCL violations are serious threats to public health and require timely rectification, and they often trigger enforcement. Regulators cannot issue MCL violations until a utility self-reports, creating an opportunity to conceal an MCL violation with a violation for not self-reporting, known as a monitoring and reporting ("MR") violation. Utilities have an incentive to under-report to avoid self-reporting costs, which are expensive in and of themselves and require hiring technical and administrative staff and paying laboratories. Utilities found self-reporting requirements to be difficult to meet due to the administrative and technical burden. Utilities needed to be administratively organized to conduct the right tests and report them on schedule. Technical staff were required to conduct separate tests for contaminants or to prepare samples to be sent to laboratories. Indiana drinking water utility managers who responded to a 1980 survey on the impact of the SDWA said that its reporting requirements had the greatest impact on their systems (Oleckno 1982).

Nitrate and arsenic MR requirements changed during this period; however, they changed nationally as part of the three-year compliance reporting schedule. Arsenic and nitrate MCLs did not change during this period, and both are contaminants that may be related to coal mining. The IOC rule contains all IOCs during this period, some of which are subject to changing MCLs and some of which may be contaminant byproducts of coal mining. Nitrate and arsenic MR requirements changed during this period; however, they changed nationally as part of the three-year compliance reporting schedule. Year fixed effects in empirical models are used to address the concerns that changes in MR violations would be the result of changing MR requirements.

Utility's under-reporting incentives increase as contamination increases. Contamination increases the likelihood that a utility's water quality exceeds the MCL, increasing the incentive to underreport in order to conceal an MCL violation. Self-reporting requirements, and therefore self-reporting costs, increase with contamination. The number of tests a utility was required to conduct varied according to the regulator-assessed risk of contamination to its water supply. Utilities assessed as having impaired water were required to self-report more tests than a utility with less impaired water. As self-reporting costs rise, the utility's cost savings and incentives from underreporting increase.

The states enforce the SDWA and are responsible for bringing violating utilities into compliance with the SDWA. With the exception of a subset of violating circumstances

and mandatory notifications to consumers that utilities must provide when in violation, the SDWA gives states wide discretionary powers to tailor compliance and enforcement plans to each utility and violation; the intention is for the violation to be resolved quickly enough to reduce the health impacts of contamination. MCL violations are treated seriously and receive comparably stricter enforcement than MR violations. However, an intentional MR violation concealing an MCL violation is punished more harshly than a regular MR violation. Enforcement is frequently remedial rather than punitive in addressing the cause of the violation. Enforcement can be informal (letters, notices of violation, compliance plans), formal (court mandated consent decrees, legal prosecution, fines), or involve visits (sanitary, sampling, technical assistance) to the utility. Non-fine enforcement is still costly to utilities. Public notifications for violations have large reputation costs that deter violations (Bennear and Olmstead 2008). Consent decrees can require installing expensive treatment infrastructure or hiring technical personnel. The replacement of an existing arsenic filtration system at a utility with baseline arsenic levels of 0.029 mg/L, serving 250 people in Pennsylvania in 2011, cost \$191,970, including \$136,744 for equipment, \$21,726 for site engineering, and \$33,500 for installation. In addition, it cost an average of \$60 a day in chemical, electricity, and labor costs (*Arsenic Removal from Drinking Water by Coagulation/Filtration U.S. EPA Demonstration Project at Conneaut Lake Park in Conneaut Lake, PA Final Performance Evaluation Report* 2011).

I focus on the regulation of water contamination by arsenic, nitrates, barium, and selenium, as they are contaminants that can be generated by coal mining; in addition, their MCLs did not change between 1985 and 2005.² Arsenic, nitrates, barium, and selenium are inorganic chemicals that are commonly produced during coal mining through acid mine drainage (AMD) (Liang et al. 2017; Boente, Baragaño, and Gallego 2020; Rouhani, J. Skousen, and Tack 2023). AMD occurs when rocks containing sulfides are exposed to air and water, beginning the process of oxidation and decomposition (Ceto and Mahmud 2000). The oxidized minerals form sulfuric acid, which dissolves metal ions and sulfates that can then be carried into surface or ground water (Akcil and Koldas 2006; J. G. Skousen, Ziemkiewicz, and McDonald 2019). Mines can reduce AMD by covering excavated material with water in tailing ponds. Contamination enters water systems when tailing ponds fail. Coal mining can also generate pollution through coal wash slurry. Coal washing processes coal with water and chemicals to remove impurities and improve combustibility. The slurry waste is often mixed with water and stored in retaining ponds or abandoned mine shafts. Dissolved pollutants enter groundwater and surface water by

²The list of regulated contaminants has been added to over time: in 1985, there were 23 regulated contaminants, and by 2005, there were 93.

seeping through porous rocks or through retaining pond failures (Sealey 2000).

3 Theoretical model

3.1 Setup

I build a theoretical model to formalize a utility's decisions to comply with water contamination regulation under rising contamination.

Utilities are required to meet contamination requirements and self report their compliance. I follow Mookherjee and Png (1994) and assume that utilities find contamination regulation costly to comply with. A compliance cost is determined by both a utility's ability to manage a drinking water system, such as the skills of its managerial and technical staff, and the costs of water treatment, including the cost of filtration equipment and sterilization chemicals. Utility compliance cost, θ , is a random variable drawn from $F(\cdot; m)$, a strictly increasing and continuously differentiable cumulative distribution function with support $(0, \bar{\theta})$, density $f(\cdot; m)$, and contamination m . A larger θ represents higher compliance costs. When compliance is costless, there are no financial benefits to negligence and $a = 0$. Increasing m weakly lowers the probability that a utility's compliance cost falls at or below any given level so that $\partial F(\theta; m)/\partial m \leq 0$ for every θ . Utilities know their draw of θ , but regulators only know the distribution of θ .

Utilities receive a benefit from neglecting their contamination control requirements. The utility chooses a negligence level $a \in [0, \bar{a}]$, which measures how much it avoids the requirements of drinking water quality regulations, from avoiding every requirement $\bar{a}$ to full compliance 0. Regulators do not directly observe a utility's choice of a . A utility receives a benefit $\theta b(a)$ from having compliance costs θ and choosing a negligence level a , where $b'(a) > 0$ and $b''(a) < 0$. A utility's benefits from negligent contamination control are the savings on wages and chemicals. The opportunity cost to the utility of choosing a compliance level a relative to maximum negligence $\bar{a}$ is $\theta[b(\bar{a}) - b(a)]$. The financial benefit of a certain level of negligence to a profit maximizing privately owned utility is obvious. Publicly owned utilities also benefit from cost savings that allow them to forgo rate increases or tax collection, which may be unpopular with residents.

Utilities face N required self-reporting events per year. Given negligence a , each self-reporting event would reveal an MCL exceedance with a probability $q(a)$, with $q(0) = 0$, $q' > 0$, and $q'' \geq 0$. I modify the penalty structure from Kaplow and Shavell (1994) by assuming that self-reporting is costly. A utility's self-reporting costs $c \sim G(\cdot; m)$ are drawn from a strictly increasing and continuously differentiable cumulative distribution

function with density $g(\cdot; m)$. Regulators require utilities to increase sampling with rising contamination so that the distribution $G()$ depends on upstream contamination m where $\partial G(c; m)/\partial m \leq 0$ for every c . Raising m weakly lowers the probability that a utility's self-reporting cost is at or below any given level.

Regulators perfectly observe under reporting. Unlike Mookherjee and Png (1994), I assume regulators do not observe MCL violations unless utilities self report water quality or the regulator conducts an inspection. Regulators use penalties and investigations for under-reporting and for exceeding regulatory standards for water quality. Utilities receive a sanction r if they self-report a contamination level above the MCL and a penalty t for an MR violation. Regulators investigate under-reporting utilities with a probability p and issue a sanction s for a discovered MCL violation, where $s > r$.

For each required self-reporting event, the utility chooses to self-report at a cost c or not report and receive an MR violation. Per-event expected costs are the sum of expected penalties and self-reporting costs

$$\begin{aligned} \text{self-report: } & c + q(a)r \\ \text{do not self-report (MR): } & t + p[q(a)s] \end{aligned}$$

The utility self-reports if and only if

$$c \leq \hat{c}(a) \equiv t - (r - ps)q(a). \quad (1)$$

$(r - ps)q(a)$ is the wedge between disclosing a violation and hiding it. Even a system with no MCL violations, $q(a) = 0$, stops self-reporting once $c > t$ when self-reporting is more expensive than the expected sanction for skipping it, and there is no MCL violation to conceal. The self-reporting threshold is decreasing in $q(a)$, so systems with a higher probability of exceeding the MCL reduce self-reporting at lower cost thresholds. The expected penalty is

$$e(a) = N \min \{ c + q(a)r, \quad t + psq(a) \}, \quad (2)$$

which is increasing in a .

3.2 Optimal negligence

The utility's problem is to minimize the losses of the opportunity cost of choosing a negligence below $\bar{a}$ and the penalty of $e(a)$. Therefore, the utility maximizes $-\theta[b(\bar{a}) - b(a)] -$

$e(a)$ with respect to a . The first-order condition is piecewise:

$$\theta b'(a) = Nr q'(a) \quad (\text{self-reporting region, } c \leq \hat{c}(a)) \quad (3)$$

$$\theta b'(a) = Nps q'(a) \quad (\text{do not self-report (MR) region, } c > \hat{c}(a)) \quad (4)$$

Assuming $r > ps$, the marginal penalty is lower when the utility is in the MR region than when it is in the self-reporting region. An exogenous decrease in $\hat{c}(a)$ increases the size of the MR region. Utilities that draw a higher self-reporting cost c are more likely to fall in the MR region. An increase in the population's cost distribution raises the share of utilities in that region without moving the boundary $\hat{c}(a)$ itself.

3.3 The propositions

The model predicts that when water quality deteriorates due to increased contamination, self-reporting rates fall.

Proposition 1: Negligence is globally increasing in compliance costs, $\partial a / \partial \theta = b'(a) / [-\theta b''(a) + N\rho q''(a)] > 0$ within each region, where $\rho \in \{r, ps\}$ is the region's sanction, and where the denominator is assumed positive to satisfy the second-order condition of maximizing the utility's negligence problem.

Proposition 2: The number of under-reporting utilities increases as contamination increases $\partial MR / \partial m \geq 0$.

For a given compliance-cost type θ , the negligence choice $a_{SR}(\theta)$ in the self-reporting region solves $\theta b'(a) = Nr q'(a)$. This gives the type specific switching cost

$$c^*(\theta) \equiv \hat{c}(a_{SR}(\theta)) = t - (r - ps) q(a_{SR}(\theta)). \quad (5)$$

A type- θ utility under-reports if and only if its cost draw exceeds this cutoff, $c > c^*(\theta)$, so the aggregate number of utilities under-reporting and receiving an MR violation is

$$MR(m) = \int_0^{\bar{\theta}} [1 - G(c^*(\theta); m)] f(\theta; m) d\theta \equiv \int_0^{\bar{\theta}} h(\theta, m) f(\theta; m) d\theta. \quad (6)$$

Differentiating (6) splits into two channels:

$$\frac{\partial MR}{\partial m} = \underbrace{\int_0^{\bar{\theta}} \frac{\partial h(\theta, m)}{\partial m} f(\theta; m) d\theta}_{\text{Channel A: cost-distribution shift}} + \underbrace{\int_0^{\bar{\theta}} h(\theta, m) \frac{\partial f(\theta; m)}{\partial m} d\theta}_{\text{Channel B: type-distribution shift}}. \quad (7)$$

Channel A:

$$\frac{\partial h(\theta, m)}{\partial m} = -\frac{\partial G(c^*(\theta); m)}{\partial m} \geq 0 \quad \text{for every } \theta,$$

since $\partial G(\cdot; m)/\partial m \leq 0$ pointwise.

Channel B:

Proceed via integration by parts

$$\int_0^{\bar{\theta}} h(\theta, m) \frac{\partial f(\theta; m)}{\partial m} d\theta = - \int_0^{\bar{\theta}} h'(\theta) \frac{\partial F(\theta; m)}{\partial m} d\theta. \quad (8)$$

Signing (8) therefore requires the slope of h in θ . Differentiating (5),

$$c^{*'}(\theta) = -(r - ps) q'(a_{SR}(\theta)) a'_{SR}(\theta) < 0,$$

since $a'_{SR}(\theta) > 0$ by Proposition 1, $q' > 0$, and $r > ps$. Then

$$h'(\theta) = -g(c^*(\theta); m) c^{*'}(\theta) \geq 0,$$

so h is non-decreasing in θ : higher-cost types choose more negligence, which lowers their own switching cutoff and makes them more likely to under-report.

$$\text{Channel B} = - \int_0^{\bar{\theta}} \underbrace{h'(\theta)}_{\geq 0} \underbrace{\frac{\partial F(\theta; m)}{\partial m}}_{\leq 0} d\theta \geq 0.$$

By assumption $\partial F(\theta; m)/\partial m \leq 0$. $\partial MR/\partial m = \text{Channel A} + \text{Channel B} \geq 0$.

Contamination from mining can raise MR violations by increasing self-reporting costs relative to each type's fixed cutoff and by shifting the population toward higher-cost types who are already structurally closer to their own cutoff.

Corollary 1: Suppose the true-exceedance probability along the self-reporting locus is invariant to compliance-cost type, $q(a_{SR}(\theta)) \equiv \bar{q}$ for all $\theta \in (0, \bar{\theta})$. Then $\partial MR/\partial m$ collapses to Channel A alone, and the entire increase in under-reporting operates through self-reporting costs, holding the composition of compliance-cost types fixed.

Under this condition the switching cutoff is type-invariant, $c^*(\theta) \equiv \bar{c} = t - (r - ps)\bar{q}$, so $h(\theta, m) = 1 - G(\bar{c}; m)$ does not vary with θ . Pulling this constant outside the integral in

Channel B leaves

$$\begin{aligned}
\text{Channel B} &= \int_0^{\bar{\theta}} h(\theta, m) \frac{\partial f(\theta; m)}{\partial m} d\theta \\
&= [1 - G(\bar{c}; m)] \int_0^{\bar{\theta}} \frac{\partial f(\theta; m)}{\partial m} d\theta \\
&= [1 - G(\bar{c}; m)] \frac{d}{dm} \left[\int_0^{\bar{\theta}} f(\theta; m) d\theta \right] \quad (\text{Leibniz's rule: the limits } 0, \bar{\theta} \text{ do not depend on } m) \\
&= [1 - G(\bar{c}; m)] \frac{d}{dm} [1] = 0, \quad (f(\cdot; m) \text{ is a density for every } m)
\end{aligned}$$

Channel A collapses to a constant pulled outside its own integral,

$$\frac{\partial MR}{\partial m} = \text{Channel A} = -\frac{\partial G(\bar{c}; m)}{\partial m} \geq 0.$$

Proposition 3: Increasing all penalties increases the number of utilities self-reporting.

Consider scaling every sanction by a common factor $\lambda > 0$: $(r, s, t) \rightarrow \lambda(r, s, t)$, holding $q(\cdot)$, $b(\cdot)$, N , p , and the cost draws θ, c fixed. Per-event penalties $e(a)$ become

$$\begin{aligned}
\text{self-report:} & \quad c + q(a) \lambda r \\
\text{do not self-report (MR):} & \quad \lambda t + p [q(a) \lambda s]
\end{aligned}$$

Differentiating within self-reporting region,

$$\begin{aligned}
e'_\lambda(a) &= N\lambda r q'(a) = \lambda e'(a) & (\text{self-reporting region}) \\
e'_\lambda(a) &= N\lambda p s q'(a) = \lambda e'(a) & (\text{MR region})
\end{aligned}$$

Negligence falls in λ .

$$\frac{\partial a}{\partial \lambda} = \frac{N\rho q'(a)}{\theta b''(a) - \lambda N\rho q''(a)}.$$

The second-order condition invoked in Proposition 1, $\lambda N\rho q''(a) - \theta b''(a) \geq 0$, required for a to be a maximum, makes the denominator non-positive, so $\partial a / \partial \lambda \leq 0$: negligence is weakly decreasing in the enforcement scale, within each region.

The self-reporting cutoff scales by λ . The self-report condition with the scaled penalties, $c + \lambda r q(a) \leq \lambda [t + p s q(a)]$ rearranges to

$$c \leq \hat{c}_\lambda(a) \equiv \lambda [t - (r - p s) q(a)] = \lambda \hat{c}(a). \quad (9)$$

Unlike $\hat{c}(a)$ itself, the self-report cost c does not scale with λ since it is a technology/labor cost, not a legal penalty, so scaling λ up moves the threshold $\hat{c}_\lambda(a)$ relative to a fixed distribution of c .

Assume $t \geq (r - ps)q(\bar{a})$. Then $\hat{c}(a) \geq 0$ for all $a \in [0, \bar{a}]$. Without this assumption, it is possible for $(r - ps)q(a) > t$ to lead to $\hat{c}(a) \leq 0$ at large a . When $\hat{c}(a) \leq 0$, since self-report cost $c \geq 0$, a negative threshold means no utility with any cost draw would self-report.

Evaluating $\hat{c}(\cdot)$ at the negligence a_λ from Step 2, the self-reporting threshold is $C^*(\lambda) \equiv \hat{c}_\lambda(a_\lambda) = \lambda \hat{c}(a_\lambda)$. Its total derivative is

$$\frac{dC^*}{d\lambda} = \hat{c}(a_\lambda) + \lambda \hat{c}'(a_\lambda) \frac{da_\lambda}{d\lambda}.$$

The first term is ≥ 0 by step 4. The second term is also ≥ 0 : $\hat{c}'(a) = -(r - ps)q'(a) < 0$ and $da_\lambda/d\lambda \leq 0$ from Step 2, so their product is non-negative, and $\lambda > 0$. Raising the enforcement scale raises the self-report threshold at the optimal negligence level, holding the population's cost draws fixed, increasing the number of utilities with $c \leq C^*(\lambda)$, and expanding the self-reporting region. Higher enforcement intensity reduces negligence and increases self-reporting.

4 Data

I measure the behavior of utilities and regulators under a contamination self-reporting regulation when contamination increases in a panel dataset of drinking water utilities downstream of at least one active coal mine from 1985 to 2005. Utility behavior and performance are measured with annual self-reporting violations, contamination violations, and contaminant concentration measurements. Regulator action is measured through enforcement and utility visits. A utility's exposure to coal mining is measured by taking the sum of active coal mines and the total coal produced at each mine in the watershed directly upstream of the utility's water source. I measure the characteristics of coal within watersheds by the percentage of its weight composed of sulfur. I describe in the instrumental variable section how this variable is important for creating an exogenous measurement of a utility's exposure to coal production.

4.1 Utility characteristic, regulator, and violation data

The EPA's Safe Drinking Water Information System (SDWIS) Enforcement and Compliance History Online (ECHO) provides data on the universe of utilities active between

1985 and 2005. This time period lacks time-varying utility characteristic data, except for data on the number of active facilities such as water intakes and treatment plants run by each utility. I use the number of active facilities as the only time-varying utility characteristic.

SDWIS ECHO provides the data source for utility self-reporting violations, contamination violations, and regulator enforcement and utility visits. The SDWIS accurately records violations but does not contain every violation ever issued due to state regulators underreporting to the EPA SDWIS. A survey of 1,800 utilities in 2000 found that 10 percent of MR violations and 50 percent of MCL violations were in SDWIS but that 95 percent of violations in SDWIS were accurately reported (*Data Reliability Analysis of the EPA Safe Drinking Water Information System/Federal Version 2000*).

I construct outcome variables for MR and MCL violations for a general IOC water contamination rule, the arsenic contaminant rule, and the nitrate contaminant rule. SDWIS ECHO uniquely identifies utility violations with information on the start and end dates of the violation, the type of SDWA rule violated, and the contaminant. To avoid double counting violations, I exclude any IOC violations that occur at the same time and at the same utility as an arsenic or nitrate violation. I measure utility violations during a year with a binary variable equal to one if the utility experienced a violation of that type at any time during the year. I measure the number of days per year a utility was in violation as a robustness check because SDWIS ECHO often records violations as starting when utilities fail to meet regular testing schedules and then continue for a set period after they are issued rather than recording the precise dates a contaminant was elevated.

Table 1 presents summary statistics for two measurements of annual utility violations: whether there is any violation in a year and the number of days in a year. The summary statistics are calculated from utility-year cells. MCL violations rarely occur; between four and twenty MCL violations occur over the entire panel. MR violations occur several orders of magnitude more frequently than MCL violations; between 250 and 377 MR violations occur during the panel. The mean length of MR violations of 10 to 15 days out of the year conceals the bimodal distribution of the length of MR violations. When an MR violation occurs, it tends to last the entire year; the 90th percentile of the days in a year experiencing an MR violation is 0, and the 99th percentile is 365. The rarity of MCL violations results in a zero 99th percentile.

I measure regulator enforcement of violations with a binary variable equal to one for every year a utility experienced enforcement. SDWIS enforcement records include the date they began and ended, and whether they were formal or informal. The “Whole panel” columns of Panel A of table 2 summarize the share and number of cells where a

utility received an enforcement action. Any enforcement occurs 21% of the time; most of that enforcement is informal, which occurs 19% of the time compared to 3.5% of the time when formal enforcement occurs. Enforcement responds to violations; a violation increases the likelihood of enforcement by 2 to 3.5 times the baseline likelihood. Enforcement is more likely to occur during years when a utility is violating a contaminant level or self reporting requirement compared to the unrestricted sample. The "During MR year" and "During MCL year" columns of Panel A restrict the sample to utility-years where an MR or MCL violation of any type occurs. The likelihood of any enforcement increases from 20% in the unrestricted sample to 71% and 65% for the samples restricted to utility years with an MR and MCL violation respectively.

I measure regulator visits to utilities with a binary variable, which is equal to one during a year when a utility received a regulator visit and zero otherwise. SDWIS ECHO records the date of the visit and reasons for visits, including sanitary survey, technical assistance, enforcement, sample collection, and inspections. The "Whole panel" columns of Panel B of table 2 summarize the share and number of cells in the utility-year sample where a utility received a visit from the regulator. Sanitary survey visits are the most common type of regulatory visit at 14% compared to the second most common, inspection visits at 4%. Technical assistance, enforcement, and inspection visits are generally more likely to occur during years when utilities receive an MR violation, increasing the likelihood by 1.5 to 2 times the unrestricted likelihood. Sample collection visits are less likely to occur during years with an MR violation compared to other years. This is counterintuitive since MR violations occur precisely when utilities do not self report their water quality, and sampling information would reveal contamination levels. Sanitary survey visits occur with a similar likelihood during an MR violation and at all times. This suggests that regulators use sanitary survey visits that include more activities than just sampling water quality when a utility underreports. Regulators rarely use visits to respond to MCL violations. Visits rarely coincide with MCL violations; two sanitary visits were the most that occurred during an MCL violation. I cannot draw a definitive conclusion given the infrequency of MCL violations.

4.2 Utility contaminant measurement data

I measure contaminant concentrations at utilities with annual mean contaminant concentrations of arsenic, nitrates, barium, and selenium in raw and treated utility water using the second Six-Year Review data (SYR2, sample years 1998-2005). Although this data only covers a subset of utilities and years, it allows me to test whether coal mining raises water

contamination at downstream utilities.

Starting in 1991, the USEPA began conducting reviews of all National Primary Drinking Water Regulations every six years to determine whether the rules needed revisions. The SYR2 was the second round of the six-year review covering 1998 to 2005 and is the earliest to be made publicly available. The SYR2 data contained contaminant data for 89 percent of the total population served by a drinking water system but excluded Pennsylvania, Mississippi, Kansas, and Louisiana due to the state EPA's failing to submit records. Unrelated to the SYR and to ensure compliance with the SDWA, states were required to collect compliance monitoring data from utilities but were not required to submit that data to the USEPA alongside the SDWA violation reports.

I retain utilities and drop transient and non-transient non-community systems. This removes roughly 23 percent of raw monitoring records. I clean the SYR2 data following the procedure of Ravalli et al. (2022) for cleaning chemical test data where it is possible that contaminants exist below levels detectable with testing equipment. For each contaminant, I compute the national share of records above the maximum laboratory detectable level (MDL), the threshold that a contaminant must be present in a sample to be detected at a laboratory, and retain only contaminants detected in more than 10 percent of records. I replace the observations below the MDL of any contaminant with the $MDL/\sqrt{2}$; this prevents records from being dropped or mistakenly reported as zero without meaningfully inflating contaminant levels. Records reporting a concentration greater than 100 times the contaminant's MCL are dropped as data-entry errors. Among the IOCs that can be produced during coal mining, this keeps arsenic, nitrate, barium, and selenium. All mass-concentration readings are converted to mg/L.

After cleaning, sample-level records are collapsed to the utility $\times$ contaminant $\times$ year level. The annual concentration of a particular contaminant is the mean of that year's samples at a particular utility.

Panel A of table 3 summarizes the contaminants included in my analysis. The maximum value of all contaminant readings is below their MCL. The maximum arsenic reading of 0.0110 mg/L would exceed the stricter arsenic MCL of 0.01 mg/L, which became regulation in 2006, but would not exceed the pre-2006 MCL of 0.05 mg/L. The fact that mean concentrations do not exceed the MCL is consistent with the low rates of MCL violations at utilities. Conditional on testing, the water contaminants appear to be within the regulatory limits. These summary statistics do not provide information on the contaminant concentrations that would be measured when a test was required by regulation but was not conducted by the utility.

This does not confirm that water contamination never exceeded the MCL. Most MR

violations were issued for failure to test water quality. The SYR2 necessarily reflects the results from water tests and does not account for tests not undertaken that were subsequently punished with an MR violation. However, if these results are more likely to reveal the contamination at the most negligent utilities since the SYR2 represents an oversampling of the more negligent utilities that are more likely to have below average water quality. Utilities that appear in the SYR2 data are more likely to violate the SDWA than those utilities that never appear in the data. Table 4 reports a two-sample t-test to compare the shares of utilities that appear in the SYR2 and have any SDWA violation to the share of utilities that never appear in the SYR2 data and have any SDWA violation. Utilities that appear in the SYR2 data are 18 to 22 percent more likely to experience any type of MR violation than those utilities that never appear in the SYR2 data. The lack of SYR2 observations does not mean the utility was not self-reporting, since utilities can be compliant with MR rules and not have any SYR2 observations. The utilities that are more likely to self-report data are also more likely to have contaminant concentration observations in SYR2. Utilities in the SYR2 are between 1.3 percent and 3.7 percent more likely to experience any type of MCL violation than those utilities that never appear in the SYR2 data. SYR2 does not contain all test results submitted to regulators, but it is more likely to contain the test results of utilities that, at some point during my sample, fail to self-report their water quality and receive an MR violation.

4.3 River and stream connectivity data

Drinking water utilities are exposed to water pollution from coal mining when the locations from which they source their water are downstream of coal mines. The exposure is strongest when a utility draws from surface water. Groundwater sources downstream of coal mining are also exposed to upstream pollution since groundwater is recharged by water flow from above. I identify utilities' water source watersheds that are downstream of coal mining using the NHDplus hydrological connectivity dataset, which identifies the boundaries and connectivity of watersheds across the US, as well as an EPA dataset on the watershed-level location of utility water intakes. The NHDplus assigns watersheds a unique 2-12 digit code known as a HUC (hydrological unit code). The number of digits corresponds to the size of the area, with the geographical area decreasing with the number of digits; for example, the lower 48 US states are divided into 18 HUC02s and over 87,000 HUC12s (see Figure 2). I use HUC12 watersheds to identify utility water intakes. HUC12 watersheds are the smallest mapped watersheds available for the entire continental US and are small enough that coal mining activities may impact the water in the

HUC12 directly downstream. To ensure that a utility intake is downstream of a coal mine, I exclude those utilities with an intake located in the same HUC12 as a coal mine; a utility intake at HUC12 inflow may not be affected by mining at the HUC12 outflow. I limit my sample to utilities with at least one water intake in a HUC12 directly downstream from a HUC12 with a coal mine.

4.4 Coal mine and coal sulfur data

My IV relies on predicting coal production from the sulfur content of coal and whether the time period is before or after the 1995 deadline for coal fired power plants to reduce sulfur emissions under the ARP.

I identify the number of coal mines and the tons of coal extracted in the HUC12 watershed directly upstream of the HUC12 watershed where a utility's water intake is located, using individual coal mine production data from the Energy Information Administration (EIA). It includes the tons of coal produced by each mine in each year from 1985 to 2005. I merge EIA coal mine data with Mine Safety and Health Administration (MSHA) data containing mine latitude and longitude coordinates. In cases where a utility has multiple intakes downstream of multiple HUC12's I measure the amount of coal production upstream as the sum of all HUC12's.

The propensity for coal production to take place upstream of a utility depends on the sulfur level of the HUC12 watershed directly upstream of the HUC12 watershed where a utility's water intake is located. I use the USGS COALQUAL dataset to measure the percentage of coal weight consisting of sulfur in a HUC12. In cases where a utility has water intakes in multiple HUC12's I measure the upstream sulfur as the mean sulfur level across upstream HUC12's. The USGS COALQUAL dataset consists of geospatially explicit drilled coal core samples across the US. Samples measure characteristics, including the percentage of coal weight consisting of sulfur. I match a HUC12 to USGS COALQUAL samples within 20 km of the HUC12 boundary and assign the mean sulfur percentage of matched samples to each HUC12. This approximates coal quality in watersheds that may not have coal production during the sample time period but are likely to contain coal deposits. The mismeasurement of sulfur levels from extreme variation within HUC12s, where some high-sulfur coal HUC12s may actually host low-sulfur coal, is not an issue since HUC12s have low variation in measured coal sulfur levels.

Figure 6 plots a histogram of the sulfur percentage of the coal bed within the HUC12s where a utility water intake and coal production are located. The sulfur content of HUC12 coal beds ranges from zero to 4.5 percent, with most of the HUC12 watersheds below 1.5

percent. Slightly more than half of the HUC12s are low sulfur coal beds. HUC12s are only included in my dataset if I can match COALQUAL samples. Map 4 shows the location of HUC12s in the sample that have utility intakes and COALQUAL samples.

5 The impact of coal mining on downstream utility contamination

5.1 Empirical framework

I measure the effect of coal mining on IOC water contaminant concentrations at utilities. This establishes whether coal mining is a convincing source of contamination to study the effect of contamination on utility and regulator behavior under a self-reporting contamination control regulation. I limit the estimation to arsenic, nitrates, barium, and selenium, as the MCL for these IOC contaminants did not change between 1985 and 2005, and these were the IOC contaminants that were retained after cleaning the SYR2 data.

Higher levels of cumulative coal production, the total amount of coal extracted since 1985, are associated with higher average contamination levels. Panel B of table 3 summarizes contaminant concentration readings at utilities downstream of higher than median cumulative tons of coal production, 90,000 cumulative short tons. Nitrate, arsenic, and barium concentrations are slightly higher at utilities exposed to higher than median cumulative coal production relative to all utilities. The difference is small.

In order to account for utility and regional effects that influence contamination levels, I estimate the impact of coal mining on the mean concentration of contaminants within downstream utilities using the regression equation

$$Concen_{cht} = \beta \cdot \sum_{\tau=1985}^t \text{upstream coal prod}_{c\tau} + \rho_c + HUC02_h \cdot \tau_t + \epsilon_{cht} \quad (10)$$

$Concen_{cht}$ is the mean concentration of a contaminant measured at utility c in HUC02 h in year t using SYR2 data from 1998 to 2005. $\sum_{\tau=1985}^t \text{upstream coal prod}_{c\tau}$ is the cumulative tons of coal mined in all HUC12s directly upstream of all utility c intakes from 1985 until year t. β is the effect of an additional 10 million cumulative tons of coal mined upstream of utility c in year t since 1985. Utility fixed effects are included as ρ_c . To control for annual industrial contamination trends that affected the entire watershed, I include HUC02 fixed effects interacted with time fixed effects $HUC02_h \cdot \tau_t$. Standard errors are clustered at the utility level.

Equation 10 identifies the β from relative differences in exposure to cumulative coal

production rather than comparing treated units to a control, since there are no control observations. The identifying assumption requires that the contamination concentrations at utilities that experience a large decline in coal production would have trended the same as the pollution concentrations at utilities with a small decline.

5.2 Results

Table 10 contains the results of regression 10 on IOC contaminant concentration tests throughout utility water processing stages. An additional 10 million cumulative short tons of coal mined upstream since 1985 increase mean concentrations of IOC contaminants at utilities. The effect is significant for all IOC contaminants except for nitrates, which I lack the power to identify at a statistically significant level. However, cumulative upstream coal production does not raise contaminant concentrations above the MCL.

Arsenic increases by 0.0023 mg/L after an additional 10 million short tons of coal mined upstream. This is economically significant, equivalent to almost a 100 percent increase over the mean arsenic concentration of 0.0029 mg/L, and is statistically significant at the 1% level. The effect represents 23 percent of the EPA arsenic MCL of 0.010 mg/L after 2005 and 4.6 percent of the MCL before 2006, which is 0.050 mg/L. An additional 10 million cumulative short tons of coal increase selenium and barium levels by 0.0033 mg/L and 0.0171 mg/L, respectively. The effects are statistically significant at the 5% level for selenium and the 10% level for barium and are large relative to the mean contaminant levels, representing increases of 50 percent, 69 percent, and 24 percent, respectively.

An additional 10 million short tons of coal increases nitrate concentrations by 0.05 mg/L; however, the effect is not statistically significant. The effect represents a 5 percent increase in concentration levels relative to the mean contaminant concentration of 0.75 mg/L. This small increase could explain why the coefficient lacks significance. Assuming the contaminant concentrations increase linearly with each additional 10 million short tons of coal mined, an increase in coal production from zero to 100 million short tons would result in the nitrate contaminant concentration exceeding 50 percent of the nitrate MCL; however, the maximum amount of coal mined upstream of a utility in any single year is 10 million short tons.

The results are more modest when scaled for the average amount of cumulative upstream coal production of 4 million tons. With average cumulative upstream coal production, contaminant levels of arsenic, barium, and selenium increase by 30 percent, 9 percent, and 28 percent of their respective mean contaminant concentration levels.

Mining thus raises utility costs to completely remove contaminants, and utilities down-

stream of mines face costlier SDWA compliance since regulators require utilities' self reporting schedules to depend on potential impairment, such as upstream coal production.

6 Coal mining instrumental variable

I have demonstrated that coal production raises water contamination at drinking water utilities. I will use an instrumental variable for coal production to investigate the effect of contamination on utilities. An IV for coal mining overcomes omitted variable bias that affects estimating the effect of coal mining on utility violations with OLS. Utilities undertake source water protection and would oppose the siting of a coal mine, resulting in coal mines being systematically less likely to be sited upstream of a utility. A utility's ability to influence industrial siting is correlated with its ability to meet or avoid violations and regulations, leading to a positive correlation between utility SDWA violations and upstream coal mining. Without data on utility political power, an OLS estimate of coal production on utility behavior leads to omitted variable bias.

My IV predicts coal production from the sulfur content of coal and whether the time period is before or after the 1995 deadline for coal fired power plants to reduce sulfur emissions under the ARP, which led to an increase in low sulfur coal production relative to high sulfur coal production. The IV is independent of the utility's ability to meet the water quality regulation.

6.1 The Acid Rain Program (ARP) on utility exposure to coal mining

The ARP was signed on November 15, 1990, as an amendment to the Clean Air Act, with the intention of reducing acid rain by limiting emissions of acid rain precursors: sulfur dioxide (SO₂) and nitrogen oxides (NO_x) from coal-fired power plants. The regulation capped total national SO₂ and NO_x emissions. Power plants were given emission allowances, for which they were fined if they exceeded the limit. Although compliance could be achieved with trading allowances, SO₂ scrubbers, and NO_x scrubbers, fuel switching to low sulfur coal was the primary abatement response. The ARP achieved 100 percent compliance (Lattanzio 2022).

Emissions were capped in two phases. In phase I, the EPA issued emission permits and allowances to 110 high polluting, mostly coal-fired electricity generating facilities. Facilities targeted under phase I were required to achieve compliance with SO₂ emission reductions by 1995. Phase II included smaller power generating units that used oil, coal, and gas. The deadline for compliance with phase II was January 1, 2000. I focus on

the phase I deadline because it targeted the largest coal-fired power plants, which were the largest customers for coal since the electric power industry accounted for 90 percent of coal demand in 2000 (Freme 2000). The ARP increased the demand for low sulfur coal and reduced the demand for high sulfur coal (*Impacts of the Acid Rain Program on Coal Industry Employment* 2001; Douglas and Wiggins 2015). Coal mines with high sulfur had a limited ability to post-process the coal to remove sulfur since part of the sulfur is integral to the chemical structure of the coal and cannot be removed (Wheelock and Markuszewski 1984).

Figure 5 plots coal production from high- and low sulfur HUC12 watersheds from 1983 until 2005. The mean quantity of coal produced in HUC12's with low sulfur coal increased over this time period while falling in HUC12's with high sulfur coal. This trend is also reflected in the total national quantity of coal produced in HUC12's with low sulfur coal. The average number of coal mines active within HUC12's with low sulfur coal fell from 2 in 1983 to 1.5 in 1995, when the number of active coal mines stabilized and slightly increased. The number of coal mines in HUC12's with high sulfur coal fell continuously over the same period.

The impact of coal production on utilities over this time period is not a consequence of regional shifts in the location of coal production, since coal's sulfur content and the shock to production from coal demand changes vary within coal regions. Figure 7 plots the change in coal production at the HUC12 watershed level between 1985 and 2005, with circles sized proportionately to the change. Production increased in both the western coal fields and the eastern coal fields. Within states, coal production rarely experienced a uniform decline or increase.

6.2 Instrumenting coal production

I now measure the effect of coal mining on utility self reporting and contamination exceedances. The theoretical model predicts that coal mining reduces utility self-reporting of water quality by increasing the incentives to avoid self-reporting costs and to conceal a contamination exceedance.

I measure the effect of upstream coal mining on utility self-reporting rates with an IV regression of SDWA violations on the instrumented number of active coal mines upstream of the utility water intake. I construct the instrument for the number of active coal mines in the HUC12 upstream of a utility water intake by interacting the average percent of sulfur by weight in the coal deposits in HUC12's directly upstream of the utility intake, with a binary variable equal to one for all years after 1995 and zero otherwise. The instru-

ment exploits the shift in coal-fired power plants' demand for coal with lower sulfur after 1995 in order to meet the sulfur dioxide emission standards of the ARP to identify variation in the location and size of coal production that is exogenous to unobserved utility characteristics affecting violations.

The first stage specification of my IV is

$$\begin{aligned} \text{NumMines}_{ct} = & \alpha_0 + \alpha_1 \text{NumFacility}_{ct} + \alpha_2 \text{UpstreamCoalSulfur}\%_c \cdot \text{Post95}_t \\ & + Y_t + C_c + \nu_{ct} \end{aligned} \quad (11)$$

The number of mines that are in the HUC12 directly upstream of utility c 's intake in year t is NumMines_{ct} . The exogenous covariates are the number of utility facilities active in year t , NumFacility_{ct} , year fixed effects Y_t , and utility fixed effects C_c . Acid mine drainage is more common when the minerals contain high levels of sulfur, making the incidence of acid mine drainage increase with coal sulfur levels (Schweinfurth 2009). The endogeneity of upstream sulfur is controlled for with utility fixed effects since sulfur levels do not change over time.

The excluded variable is the interaction between the average sulfur as a percentage of weight in the HUC12s directly upstream of all utility c 's water intakes, $\text{UpstreamCoalSulfur}\%_c$, and a dummy variable equal to one for the years after the deadline to implement stage I of the ARP, 1995, and zero otherwise, Post95_t . During the pre-1995 period, all observations of $\text{UpstreamCoalSulfur}\%_c \cdot \text{Post95}_t$ are zero, and after 1995, the observations are the percent of sulfur in upstream coal. Standard errors are clustered at the utility level.

The second stage of the regression is

$$\begin{aligned} \text{Violation}_{vct} = & \beta_0 + \beta_1 \text{NumFacility}_{ct} + \gamma \widehat{\text{NumMines}}_{ct} \\ & + Y_t + C_c + \epsilon_{ct} \end{aligned} \quad (12)$$

In the second stage, the dependent variable is a binary variable equal to one if utility c experienced an SDWA violation in year t , Violation_{vct} .

6.3 Instrument validity

6.4 Random assignment of the instrument

instrument is randomly assigned because the timing is random from the perspective of utilities. But since proximity to sulfur is not random then random assignment is condi-

tional on utility fixed effects that would be important for sulfur proximity.

The instrument is independent if the relationship between utility characteristics important for water quality and the siting of upstream coal mines is independent of the upstream coal sulfur content in 1995, so that $f(UpstreamCoalSulfur\%_c \cdot Post95_t, \text{utility characteristic}) = f(UpstreamCoalSulfur\%_c \cdot Post95_t)f(\text{utility characteristic})$. Conditional on the control variables, $UpstreamCoalSulfur\% \times Post95$ is independent of the omitted variables in ϵ_{ct} that determine utility drinking water quality violations. The ARP and the timing of the first phase were both exogenous to utility drinking water quality and utility characteristics. The ARP was a national clean air policy that was not written or enacted to address water quality issues. The effects of the ARP on coal production were determined by national and international energy markets that local utilities or local utility water quality did not affect. Local utility characteristics regarding water quality or local power over source protection did not affect the scope of the ARP, nor how stringent the ARP law was, nor the degree to which low sulfur coal should be part of the abatement technology, nor the date of phase I of the ARP. The timing of the ARP did not coincide with major drinking water regulations.

The instrument would violate independence if the unobserved utility characteristics that affect drinking water quality violations and the siting of coal mines changed after 1995 for utilities with different amounts of sulfur as a percentage of coal weight. Knowing about sulfur as a percentage of coal weight upstream of a utility after 1995 tells us nothing about how much political power a local utility has over mine siting. Thus, $Cov(\text{political power of utility}_c, UpstreamCoalSulfur\%_c \cdot Post95_t) = 0$.

The instrument only affects utilities through its effect on the number of coal mines. A threat to this would be if utility SDWA regulation changed after 1995 and had a differential impact on utilities downstream of high sulfur coal before and after 1995 compared to utilities downstream of low sulfur coal before and after 1995. Changes in SDWA rules that affected all utilities the same way are controlled for with time fixed effects. For example, in 1991, the monitoring and reporting schedule changed for all utilities and is controlled for with time fixed effects. Any change to an MCL would apply to all utilities and be controlled for with time fixed effects. The SDWA amendments that were passed in 1996 increased the use of consumer confidence reports as an enforcement tool when a utility violated a drinking water regulation. Utilities downstream of high sulfur coal will experience less upstream coal mining after 1995 compared to before 1995, and therefore less upstream water contamination, whereas utilities downstream of low sulfur coal will experience more upstream coal mining after 1995 compared to before 1995. Utilities downstream of high sulfur coal may experience fewer SDWA violations from upstream

pollution compared to before 1995, meaning the burden of a consumer confidence report is smaller than it would have been before 1995, whereas utilities downstream of low sulfur coal will experience more upstream pollution after 1995 compared to before, meaning the burden of the consumer confidence report is higher than it would have been before 1995. This difference is likely small since all utilities in the sample are downstream of coal mining and have more similar pollution exposure and burden from consumer confidence reports compared to the average utility in the country.

I test this directly by regressing the number of a utility's active intake facilities, an observable proxy for the negligence that determines self-reporting behavior in the theoretical model, on the instrument. Table 6 reports the results. The coefficient on the instrument is small and statistically indistinguishable from zero both in the specification with utility and year fixed effects that matches the main estimating equation and in a levels specification restricted to utilities observed throughout the sample period. This is consistent with the instrument affecting utility self-reporting only through its effect on the number of upstream coal mines rather than through a separate change in self-reporting requirements after 1995.

The instrument does predict the location and size of coal production. Figure 9 is a scatter plot of the number of coal mines and the coal sulfur percent in the HUC12s upstream of utilities before and after 1995, with plotted linear lines of best fit for each period. The change in production away from high sulfur coal production after the ARP is strongly demonstrated by the line of best fit flattening after 1995, indicating that while there was more coal production in higher sulfur coal areas before 1995, there was a large shift to areas with low sulfur coal after 1995. The number of coal mines in a HUC12 increased with the percent of sulfur as the weight of coal in the HUC12 before 1995. The time-contingent switch in coal production based on sulfur content supports the structure of the variable $UpstreamCoalSulfur\%_c \cdot Post95_t$.

The strength of the instrument is still evident after controlling for covariates. Figure 10 is a scatter plot of the residualized number of upstream coal mines and the residualized instrumental variable. There is a negative relationship between the residualized number of upstream coal mines and $UpstreamCoalSulfur\%_c \cdot Post95_t$.

6.4.1 Assessing monotonicity

The instrument requires monotonicity and for there to be no defiers to recover the local average treatment effect (LATE) estimate of the instrument. A defier in this context is a utility that is upstream of a high-sulfur coal watershed where coal production increased after 1995 but would have decreased production after 1995 if it had instead been

a low-sulfur coal watershed. An example of a never-taker is a high-HUC12 that maintains production after 1995 because its customers are electricity generators that install scrubbers. As long as scrubber adoption is not positively correlated with sulfur in a way that causes production to increase post-ARP in high-sulfur areas, this is not a violation of monotonicity and only reduces first-stage power. To be a defier with scrubber installation requires a power plant to expand production after installing scrubbers and increase electricity market share. Power plants that rely on high sulfur coal and scrubbers are more likely to lose market share and reduce production since scrubbers are expensive to install, increase operating costs, and require higher electricity rates to retain profits. If some high-sulfur regions had a comparative advantage in low-cost production that offset the ARP cost increase, such as very low labor costs or transportation advantages, they might expand production even as ARP made their coal relatively more expensive. Unless this expansion would not have occurred if the low-cost high-sulfur regions had been low-sulfur coal regions, this would not create defiers and would instead create never-takers.

In this setting, the instrument is $Z_i = \text{post95}_i \times \text{sulfur}_h$, which equals zero before 1995 and sulfur_h after. For a given sulfur level w , monotonicity requires either $\text{num_mines}_i(0) \leq \text{num_mines}_i(w)$ for all i , or $\text{num_mines}_i(0) \geq \text{num_mines}_i(w)$ for all i .³ This permits the direction of the response to vary with sulfur content. For example, at sulfur = 1 (low sulfur), mines may expand after 1995, so monotonicity requires $\text{num_mines}_i(0) \leq \text{num_mines}_i(1)$ for all i . At sulfur = 4 (high sulfur), mines likely contract after 1995, so monotonicity requires $\text{num_mines}_i(0) \geq \text{num_mines}_i(4)$ for all i . These two conditions are compatible: monotonicity is satisfied so long as each pairwise comparison is uniform across units, even when low- and high-sulfur areas respond in opposite directions.

7 The impact of coal mining on utility self-reporting

This tests whether increasing mining causes utilities to under-report water quality. Upstream mining increases the costs of compliance by raising the level of contamination, which increases underreporting by raising the costs of self-reporting and lowering the cost of underreporting. Upstream mining lowers the cost of underreporting by increasing the cost of complying with water quality requirements and therefore increasing the benefit from negligence. This leads to a reduction in the expected cost of underreporting

³Stating monotonicity more formally and following Angrist and Imbens (1994), let Ψ be the support of the instrument Z_i , and for each $z \in \Psi$ define a random variable $D_i(z)$. The monotonicity assumption requires that for all $z, w \in \Psi$, either $D_i(z) \leq D_i(w)$ for all i , or $D_i(z) \geq D_i(w)$ for all i . This condition applies pairwise to elements of Ψ and imposes no restriction on the ordering of z and w .

and a reduction in the cost threshold for underreporting, above which a utility receives greater benefits from underreporting compared to self-reporting.

Table 7 reports the results of Equation 12 estimating the impact of the number of active upstream coal mines on the likelihood that in a year a utility receives either an MCL or MR violation for nitrates, arsenic, and inorganic chemicals using OLS, reduced form, and two stage least squares regressions.

The first-stage F -statistic, computed as the squared clustered t -statistic on the excluded instrument, is numerically equivalent to the effective F -statistic of Montiel Olea and Pflueger (2013) in this just-identified setting. It exceeds their critical value of 23.1 for a 5%-level test against 10% worst-case bias, well above the conventional rule-of-thumb threshold of 10 proposed by Staiger and Stock (1997). An additional active coal mine upstream increases the likelihood of nitrate, arsenic, and IOC SDWA violations by roughly 2 percentage points out of the year when using OLS.

Coal production fell most acutely in high sulfur coal areas after 1995, and a positive relationship between coal production and SDWA violations predicts that IOC violations would fall with increasing upstream sulfur after 1995 relative to before 1995. The reduced form effect of the instrument measures how much more (or less) a one-percentage-point increase in upstream sulfur affects the likelihood of violations after ARP Phase I relative to before. An additional percent of coal sulfur upstream leads to a 2.4 percentage point reduction in the likelihood a utility experiences a nitrate, arsenic, or inorganic chemical violation of any kind after 1995 compared to before 1995. This suggests that in areas where the number of coal mines is more likely to decrease, the likelihood of violation in a year falls.

The instrumental variable estimate of an additional active coal mine upstream on nitrates and arsenic violations is an additional 10 and 7.5 percentage point increases, respectively. The instrument has a relatively strong first stage with an F statistic of 27.5. The OLS results underestimate the effect of coal mines on violations relative to the IV results. In general, the OLS impact of coal mines is five times smaller than the IV coefficient, suggesting that the omitted variable bias is negative. A negative omitted variable bias is consistent with utilities that are able to influence the siting of upstream mines being better at avoiding violations.

The entire increase in violations from upstream mining is driven by MR violations rather than MCL violations. The regressions presented in Table 8 estimate Equation 12 on MR arsenic, nitrate, and IOC violations. An additional coal mine upstream of a utility leads to 9, 7, and 7 percentage point increases in the likelihood of an MR violation in a year for nitrates, arsenic, and general IOC contaminants, respectively, comprising the

entire effect observed when the dependent variable combines MR violations with MCL violations. IOC violations are statistically significant at the 10 percent level when violations are limited to MR violations and statistically insignificant when the violations refer to the share of the year spent in either MCL or MR violations. Violations are more than twice as likely to occur relative to the average rate of MR violations after an additional mine operates upstream. Table ?? reports the mean summary rates of arsenic, nitrate, and inorganic chemical violations at 4 percent, 6 percent, and 4.6 percent.

The impact of coal mining on downstream utility MCL violations for nitrates, arsenic, and general IOC contaminants is presented in Table 9. The IV regression of the effect of the number of coal mines upstream estimates statistically and economically insignificant changes in the likelihood a utility experiences an arsenic or nitrate MCL violation. The point estimate for the effect of an additional mine on the likelihood a utility spends a year in a nitrate MCL violation is -0.02 percentage points, and for an inorganic chemical MCL it is -0.7 percentage points. None of these effects are statistically significant due to the extreme rarity of MCLs in the sample.

Despite all the significant effects of coal mining being concentrated in MR violations and not in MCL violations, I cannot conclude that coal mining does not impact actual contaminant levels. Coal mining can increase contaminant levels, but they can remain below an MCL. A maximum contaminant level violation is only issued by the regulator when they receive the results of a test that a utility conducted. Consistently failing to conduct tests or report the results of tests and incurring an MR violation prevents an MCL from being issued, even if contaminant concentration legitimately exceeds the MCL. The SDWA ECHO violation dataset is, for that reason, unable to measure drinking water contamination when systems do not monitor and report tests.

The theoretical model predicts that lapses in self-reporting can occur without contaminant concentration violations occurring when contamination increases following mining and testing costs rise or utilities seek to avoid MCL penalties by hiding MCL violations in MR violations, or if penalties fall. I next test whether contamination rises with mining.

If coal mining affects contamination exceedances then this provides evidence of . The expected penalty for underreporting is driven by compliance types and which leads to higher negligence and MCL's are detected more often at higher negligence. I have shown that coal mining does not appear to raise contamination levels above the MCL suggesting that, all else being equal, coal mining increases self reporting costs. Coal mining can lower self-reporting even if it does not raise contamination above the MCL, but it raises self-reporting costs.

8 robustness test of contamination and MR and MCL violations

I estimate the effect of SYR2 contaminant concentrations of nitrates on the likelihood of nitrate self-reporting violations. After 1991, the cost of self-reporting rose with contaminant concentrations. Nitrate self-reporting requirements required increased monitoring if nitrate concentrations were detected at 50 percent of the nitrate MCL.

Table 11 reports regressions of linear probability models of the likelihood of a utility failing to monitor and report their water for nitrate levels within 6 months and a year of a contaminant reading. I find that when nitrate contaminant readings are greater than 50 percent of the nitrate MCL, a utility is 0.5 percentage points more likely to fail to self-report water tests for nitrates in the following year and 0.2 percentage points more likely to fail to monitor and report nitrate water tests within six months. The failures after a nitrate reading has exceeded 50 percent occur during a time of enhanced nitrate monitoring at the utility since these results are from 1997 to 2005. This suggests that utilities are more likely to fail to keep up with marginal increases in monitoring and reporting schedules. Enforcement does not increase.

9 Regulator responses to increased utility self-reporting violations

The theoretical model predicts that utilities' self-reporting depends on the expected penalties from regulator enforcement. To investigate the penalties and disincentives for missing self-reporting requirements, I estimate the impact of coal mining on the likelihood that a utility receives enforcement and regulatory visits. This measures the enforcement received by the utilities which underreport due to coal mining contamination.

Formal enforcement is a large cost burden to utilities. It involves fines, court orders, and prosecution. To summarize the likelihood of receiving formal enforcement, table ?? calculates the rate of formal enforcement at utilities downstream of coal mines. Rates are calculated across the utility-year panel. Formal enforcement is more likely to be used when a utility fails to self-report, and formal enforcement is even more likely to be used when a utility fails to self-report and receives a sanitary visit. However, receiving a sanitary visit and being downstream of more coal mines, which induces more self-reporting violations, does not induce any more likelihood of receiving formal enforcement. Increases in self-reporting failures are not penalized any more harshly than standard rates

of self-reporting non-compliance.

9.1 Instrumental variable

I have established that coal mining increases utilities' violations of the SDWA. Violations increase as contaminant concentrations rise, which I have also established occurs when mining increases. The theoretical model predicts that violations will rise when enforcement or penalties for underreporting are relatively low. I estimate whether regulatory enforcement action is less costly as coal mining increases upstream of utilities.

Coal mine siting and production could be endogenous to regulator enforcement of SDWA at utilities. For example, utilities that are able to protect their water sources from upstream mining would, on average, be better able to reduce the cost of regulatory enforcement they would face from SDWA violations. I construct an instrument as in equation 11 to address the endogeneity of mine siting and regulator action at utilities. I estimate the effect of upstream coal mining on the likelihood of formal and informal enforcement using this IV for upstream coal mining. Formal enforcement is more severe and costlier than informal enforcement since it can involve legal cases against the utility.

Part of any effect that I find of coal mining on regulator enforcement of the SDWA at utilities is the effect of water pollution from coal mining on regulator enforcement. Regulators are more likely to be responding to pollution caused by upstream coal mining rather than to upstream coal mining itself, since utility water quality is regulated by state and federal authorities, and mine safety is regulated by the federal MSHA. It is possible that state environmental regulators are aware of coal mining pollution through their primacy to enforce point source pollution in the Clean Water Act.

The first stage is

$$\text{NumMines}_{ct} = \alpha_0 + \alpha_1 \text{NumIntakes}_{ct} + \alpha_2 \text{UpstreamCoalSulfur}\%_c \cdot \text{Post95}_t + Y_t + C_c + \nu_{ct} \quad (13)$$

And the second stage is

$$\text{Regulatory Action}_{ct} = \beta_0 + \beta_1 \text{NumIntakes}_{ct} + \gamma \widehat{\text{NumMines}}_{ct} + Y_t + C_c + \epsilon_{ct} \quad (14)$$

The number of mines that are one HUC12 upstream of a utility c water intake in year t , NumMines_{ct} , is predicted by a function of the number of utility intake facilities, NumIntakes_{ct} , the average coal sulfur percentage in upstream HUC12s where coal sul-

fur can be calculated, $UpstreamCoalSulfur\%_c$, interacted with a dummy indicator for the years after 1995, stage I of the ARP, $Post95_t$, year fixed effects, Y_t , utility fixed effects, C_c , and an error term, v_{ct} . Standard errors are clustered at the utility level.

The utility fixed effects control for the effect that upstream sulfur is associated with a higher baseline of AMD which could increase pollution and therefore enforcement action outside of the effect of the instrument on coal mines.

The exclusion restriction fails when the instrument affects regulator behavior through another path outside of its effect on coal mining. The exclusion restriction would be threatened if the ARP Phase I directly changed state EPA enforcement practices in a way that affected utilities differently according to the percent of sulfur by weight in upstream coal. However, states were not primarily responsible for enforcing the ARP; it was a federally regulated program that, by itself, would not have affected state primacy enforcement of the SDWA.

Any national regulatory changes to the SDWA that affected all utilities are controlled for with time fixed effects. The threat to the exogeneity of the instrument would occur if regulatory enforcement in low sulfur regions before and after 1995 changed differently from the change in regulatory enforcement in high sulfur regions before and after 1995.

Table 13 presents the coefficients from estimating Equation 14 on the likelihood of formal and informal enforcement. Upstream coal mining leads to a five percentage point reduction in formal enforcement at the 1% level of statistical significance and a reduction in informal enforcement close to zero, which is not statistically significant.

The OLS regression measures a 1.69 percentage point fall in any formal enforcement occurring at a utility in the year when an additional mine operates upstream. Given that the IV estimates a larger reduction in the likelihood of formal enforcement, this implies the omitted variable bias is positive and is consistent with the bias from omitting utility ability to protect upstream water sources and influence SDWA regulatory enforcement.

The coefficient of $UpstreamCoalSulfur\%_c \times Post95_t$ in the reduced form regression compares the enforcement at utilities with higher sulfur levels after 1995 to those with lower sulfur levels. A one-percentage point increase in $UpstreamCoalSulfur\%_c$ is associated with a 1.45 percentage point increase in formal enforcement after 1995, compared to before 1995. Mining declines with sulfur after 1995; this means that places that likely experienced declines in mining after 1995 also experienced increases in formal enforcement compared to places that experienced mining increases; formal enforcement is less likely to be used as upstream mining increases. This is not counterintuitive when considering that formal enforcement such as legal action is hard to conduct without evidence of an MCL or strong evidence of wrongdoing, and previous results show that utilities

downstream of mining increases underreport, thus providing less evidence for regulator formal enforcement.

Regulators increase the likelihood of conducting enforcement visits when the number of upstream coal mines increases. Table 14 presents the coefficients from estimating equation 14 on enforcement visits. Enforcement visits, however, do not translate into formal enforcement.

The regulator necessarily lacks information about the quality of water at a utility incurring an MR violation. If the actual contaminant concentration is above the MCL, then the violation requires urgent action to protect public health. However, if the actual contaminant concentration is below the MCL, then the violation does not require urgent action to protect public health. The regulator can use sanitary inspections of utilities to determine the risk to public health and determine the type of action that must be taken to enforce compliance.

Table 14 presents the coefficients from estimating equation 14 on the likelihood of a regulator conducting a sanitary visit to a utility following an increase in upstream coal mining. Coal mining leads to a 14 percentage point increase in sanitary visits by the regulator to the utility. This is statistically significant at the 1 percent level. The absence of an increase in formal enforcement rates at the utilities where sanitary visits take place suggests that regulators do not uncover hidden MCLs.

10 Discussion

Coal mining reduces utility self-reporting of water quality while it increases the contaminant concentration of inorganic chemicals in the water. The theoretical model predicts that utilities reduce self-reporting when contamination rises to reduce onerous self-reporting costs and to hide MCL violations.

The evidence suggests that utilities are underreporting to avoid onerous self-reporting costs and not to hide MCLs. Coal mining contamination does not raise contaminant concentrations above MCLs in the limited SYR2 data. However, this result is limited to a subset of utilities and a subset of the time period.

Regulators conduct sanitary and enforcement visits at utilities that are underreporting while not bringing formal enforcement action against those utilities. Hidden MCLs would likely attract formal enforcement. This is additional evidence that utilities are underreporting to avoid onerous self-reporting costs rather than being used to hide MCL violations.

There is suggestive evidence that nitrate violations are more likely to occur when con-

taminant tests exceed 50% of the MCL, requiring more self-reporting, than when contaminant levels are below 50% of the MCL. This suggests that underreporting occurs as a way to avoid more onerous self-reporting requirements.

The behavior of the utilities in response to penalties and enforcement suggests that the penalties for utilities not self-reporting are too low to deter the reduction in self-reporting that occurs from self-reporting cost increases. The result is that regulators are required to increase sanitary visits to utilities to determine the health risk of an underreporting utility. The welfare effects of this are not a priori clear. The regulators may be able to monitor with economies of scale that are lower than the utilities' cost of self-reporting. However, the economies of scale would have to overcome the large amount of resources the regulator would have to devote to monitoring all utilities in a timely manner.

I do not address the efficiency of shifting monitoring onto the regulators. Water quality is generally perceived as a local issue with limited externalities (Olmstead 2010). Without externalities, it may be inefficient for a state regulator to expend resources to monitor a local utility. However, regulators may be able to conduct monitoring at a lower marginal cost than small utilities. Small utilities find the burden of water quality management particularly heavy. I would need to take into account the regulators' preferences in order to say something about efficiency. Regulator preferences affect enforcement and not only violation severity alone (Kang and Silveira 2021).

11 Conclusion

I present evidence that under a self-reporting regulatory framework designed to monitor a quality target, self-reporting falls if contamination increases even if that quality does not fall below regulatory standards. I show this in the context of coal mining and utilities: utility SDWA self-reporting of water quality falls as water quality exogenously deteriorates. Utility SDWA self-reporting becomes costlier as coal mining increases, since an increase in coal mining leads to increases in inorganic chemical water contamination at utilities, which increases the cost of self-monitoring. I do not detect mean contaminant levels increasing above maximum contaminant levels and cannot conclude that upstream coal mining is increasing pollution to the extent that utilities need to install improved abatement technology to meet SDWA maximum contaminant level compliance.

I find that penalties for not self-reporting are not high enough to induce utilities to self-report as self-reporting costs rise. The regulator can use sanitary visits to assess the threat posed to public health by an MR violation and can implement a less costly type of enforcement when the threat is discovered to be low. However, without punishing non-

self-reporting at high levels, regulators will have to conduct more sanitary visits to ensure that contaminant concentration levels do not exceed health limits.

The findings here suggest that the regulatory design of the SDWA, which relies on utility self-monitoring and assigns substantially lower penalties to non-monitoring than to detected contamination, creates systematic incentives to underreport. Strengthening the monitoring schedule or increasing penalties for non-monitoring in high-pollution areas may be a more effective lever for improving drinking water outcomes than increases in MCL stringency alone.

References

- Akcil, Ata and Soner Koldas (2006). "Acid Mine Drainage (AMD): causes, treatment and case studies". In: *Journal of cleaner production* 14.12-13, pp. 1139–1145.
- Allaire, Maura, Haowei Wu, and Upmanu Lall (2018). "National trends in drinking water quality violations". In: *Proceedings of the National Academy of Sciences* 115.9, pp. 2078–2083.
- Andarge, Tihitina et al. (2025). "Quantifying Threshold Manipulation in the Presence of Rounding: The Case of Lead Monitoring in US Drinking Water". In: *American Economic Review: Insights* 7.3, pp. 285–305.
- Angrist, Joshua and Guido Imbens (1994). "Estimation and identification of local average treatment effects". In: *Econometrica*.
- Anton, Wilma Rose Q, George Deltas, and Madhu Khanna (2004). "Incentives for environmental self-regulation and implications for environmental performance". In: *Journal of environmental economics and management* 48.1, pp. 632–654.
- Arsenic Removal from Drinking Water by Coagulation/Filtration U.S. EPA Demonstration Project at Conneaut Lake Park in Conneaut Lake, PA Final Performance Evaluation Report* (July 2011). EPA/600/R-11/073. USEPA Office of Research and Development.
- Benneer, Lori S, Katrina K Jessoe, and Sheila M Olmstead (2009). *Sampling out: Regulatory avoidance and the total coliform rule*.
- Benneer, Lori S and Sheila M Olmstead (2008). "The impacts of the "right to know": Information disclosure and the violation of drinking water standards". In: *Journal of Environmental Economics and Management* 56.2, pp. 117–130.
- Bingham, Tayler et al. (2000). "A benefits assessment of water pollution control programs since 1972: Part 1, the benefits of point source controls for conventional pollutants in rivers and streams". In: *Research Triangle Institute for the U.S. Environmental Protection Agency, Office of Water, Research Triangle Park, NC*.
- Blundell, Wesley (2020). "When threats become credible: A natural experiment of environmental enforcement from Florida". In: *Journal of Environmental Economics and Management* 101, p. 102288.
- Blundell, Wesley, Gautam Gowrisankaran, and Ashley Langer (2020). "Escalation of scrutiny: The gains from dynamic enforcement of environmental regulations". In: *American Economic Review* 110.8, pp. 2558–2585.
- Boente, Carlos, Diego Baragaño, and JR Gallego (2020). "Benzo [a] pyrene sourcing and abundance in a coal region in transition reveals historical pollution, rendering soil screening levels impractical". In: *Environmental pollution* 266, p. 115341.

- Ceto, Nick and Shahid Mahmud (2000). "Abandoned mine site characterization and cleanup handbook". In: *Agency, EP (Ed.). USEPA, Seattle, WA* 129.
- Christensen, Peter, David A. Keiser, and Gabriel E. Lade (Feb. 2023). "Economic Effects of Environmental Crises: Evidence from Flint, Michigan". In: *American Economic Journal: Economic Policy* 15.1, pp. 196–232. DOI: 10.1257/pol.20190391. URL: <https://www.aeaweb.org/articles?id=10.1257/pol.20190391>.
- Daly, Matthew (Sept. 2025). *Trump to Open More Federal Land for Coal Mining, Provide Industry \$625M to Boost Coal Plants*. PBS NewsHour / Associated Press. URL: <https://www.pbs.org/newshour/nation/trump-to-open-more-federal-land-for-coal-mining-provide-industry-625m-to-boost-coal-plants>.
- Data Reliability Analysis of the EPA Safe Drinking Water Information System/Federal Version* (Oct. 2000). EPA 816-R-00-020. USEPA Office of Water.
- DiSalvo, Richard W and Elaine L Hill (2024). "Drinking water contaminant concentrations and birth outcomes". In: *Journal of Policy Analysis and Management* 43.2, pp. 368–399.
- Douglas, Stratford and Seth Wiggins (2015). "Effects of Acid Rain Regulations on Production of Eastern Coals of Varying Sulfur Content". In: *College of Business and Economics Working Paper Series*.
- Duflo, Esther et al. (2018). "The value of regulatory discretion: Estimates from environmental inspections in India". In: *Econometrica* 86.6, pp. 2123–2160.
- Foster, Andrew D and Emilio Gutierrez (2013). "The informational role of voluntary certification: evidence from the Mexican clean industry program". In: *American Economic Review* 103.3, pp. 303–308.
- Foster, Stephanie A et al. (2019). "Arsenic drinking water violations decreased across the United States following revision of the maximum contaminant level". In: *Environmental science & technology* 53.19, pp. 11478–11485.
- Freme, Fred (2000). *US coal supply and demand: 2000 review*. US Department of Energy, Energy Information Administration.
- Harford, Jon D (1987). "Self-reporting of pollution and the firm's behavior under imperfectly enforceable regulations". In: *Journal of Environmental Economics and Management* 14.3, pp. 293–303.
- Hill, Elaine and Lala Ma (2017). "Shale gas development and drinking water quality". In: *American Economic Review* 107.5, pp. 522–525.
- Impacts of the Acid Rain Program on Coal Industry Employment* (Mar. 2001). EPA 430-R-01-002. USEPA.
- Innes, Robert (1999). "Remediation and self-reporting in optimal law enforcement". In: *Journal of Public Economics* 72.3, pp. 379–393.

- Kang, Karam and Bernardo S Silveira (2021). "Understanding disparities in punishment: Regulator preferences and expertise". In: *Journal of Political Economy* 129.10, pp. 2947–2992.
- Kaplow, Louis and Steven Shavell (1994). "Optimal law enforcement with self-reporting of behavior". In: *Journal of Political Economy* 102.3, pp. 583–606.
- Keiser, David A (2019). "The missing benefits of clean water and the role of mismeasured pollution". In: *Journal of the Association of Environmental and Resource Economists* 6.4, pp. 669–707.
- Keiser, David A and Joseph S Shapiro (2019a). "Consequences of the Clean Water Act and the demand for water quality". In: *The Quarterly Journal of Economics* 134.1, pp. 349–396.
- (2019b). "US water pollution regulation over the past half century: burning waters to crystal springs?" In: *Journal of Economic Perspectives* 33.4, pp. 51–75.
- Lattanzio, Richard K (2022). *Clean Air Act: A Summary of the Act and Its Major Requirements*. Congressional Research Service.
- Lee, Ruiwen (2020). *Essays on the regulation and remote sensing of natural gas flaring*. Columbia University.
- Liang, Jie et al. (2017). "Spatial distribution and source identification of heavy metals in surface soils in a typical coal mine city, Lianyuan, China". In: *Environmental Pollution* 225, pp. 681–690.
- Malik, Arun S (1993). "Self-reporting and the design of policies for regulating stochastic pollution". In: *Journal of Environmental Economics and Management* 24.3, pp. 241–257.
- Marcus, Michelle (2025). "Testing above the limit: Drinking water contamination and test scores". In: *Journal of Public Economics* 243, p. 105313.
- Mi, Shuying, Bing Zhang, and Mengdi Liu (2026). "Technology, enforcement resources allocation, and environmental performance". In: *Journal of Environmental Economics and Management* 139, p. 103388. DOI: 10.1016/j.jeem.2026.103388.
- Montiel Olea, José Luis and Carolin Pflueger (2013). "A Robust Test for Weak Instruments". In: *Journal of Business & Economic Statistics* 31.3, pp. 358–369.
- Mookherjee, Dilip and Ivan PL Png (1994). "Marginal deterrence in enforcement of law". In: *Journal of Political Economy* 102.5, pp. 1039–1066.
- Mu, Yingfei, Edward Rubin, and Eric Yongchen Zou (May 2026). "What's Missing in Environmental Self-Monitoring: Evidence from Strategic Shutdowns of Pollution Monitors". In: *The Review of Economics and Statistics* 108.3, pp. 597–612. ISSN: 0034-6535. DOI: 10.1162/rest_a_01477. eprint: https://direct.mit.edu/rest/article-pdf/108/3/597/2466972/rest_a_01477.pdf. URL: https://doi.org/10.1162/rest_a_01477.

- Muller, Nicholas Z, Robert Mendelsohn, and William Nordhaus (2011). "Environmental accounting for pollution in the United States economy". In: *American Economic Review* 101.5, pp. 1649–1675.
- Naylor, Jamie and Brady J Deaton (n.d.). "Strategic Under-reporting of Arsenic Contamination in Drinking Water". In: *Available at SSRN 5537637* ().
- Oleckno, William A (1982). "The National Interim Primary Drinking Water Standards: Part II Impact on Community Water Systems: The Indiana Experience". In: *Journal of Environmental Health*, pp. 240–244.
- Olmstead, Sheila M (2010). "The economics of water quality". In: *Review of environmental economics and policy*.
- Parfitt, Parfitt (2024). "There's Something in the Water: Gold Rush, Illegal Mining, Mercury Pollution, and Infant Health in the Amazon Rainforest". In: *Illegal Mining, Mercury Pollution, and Infant Health in the Amazon Rainforest**(August 20, 2024).
- Ravalli, Filippo et al. (2022). "Sociodemographic inequalities in uranium and other metals in community water systems across the USA, 2006–11: a cross-sectional study". In: *The Lancet Planetary Health* 6.4, e320–e330.
- Rouhani, Abdulmannan, Jeff Skousen, and Filip MG Tack (2023). "An overview of soil pollution and remediation strategies in coal mining regions". In: *Minerals* 13.8, p. 1064.
- Schweinfurth, Stanley P (2009). "An introduction to coal quality". In: *The National Coal Resource Assessment Overview: US Geological Survey Professional Paper*, p. 16.
- Sealey, Geraldine (2000). "Sludge Spill Pollutes Ky., W. Va. Waters". In: *ABC News*.
- Shimshack, Jay P (2014). "The economics of environmental monitoring and enforcement". In: *Annu. Rev. Resour. Econ.* 6.1, pp. 339–360.
- Skousen, Jeffrey G, Paul F Ziemkiewicz, and Louis M McDonald (2019). "Acid mine drainage formation, control and treatment: Approaches and strategies". In: *The Extractive Industries and Society* 6.1, pp. 241–249.
- Staiger, Douglas and James H. Stock (1997). "Instrumental Variables Regression with Weak Instruments". In: *Econometrica* 65.3, pp. 557–586.
- Tazhitdinova, Alisa (2018). "Reducing evasion through self-reporting: Evidence from charitable contributions". In: *Journal of Public Economics* 165, pp. 31–47.
- U.S. President (Trump) (Apr. 2025a). "Executive Order No. 14260: Protecting American Energy from State Overreach". In: *Federal Register* 90. Signed April 8, 2025, p. 15513. URL: <https://www.whitehouse.gov/presidential-actions/2025/04/protecting-american-energy-from-state-overreach/>.
- (Apr. 2025b). "Executive Order No. 14261: Reinvigorating America's Beautiful Clean Coal Industry and Amending Executive Order No. 14241". In: *Federal Register* 90.

- Signed April 8, 2025, p. 15517. URL: <https://www.whitehouse.gov/presidential-actions/2025/04/reinvigorating-americas-beautiful-clean-coal-industry-and-amending-executive-order-14241/>.
- U.S. President (Trump) (Apr. 2025c). "Proclamation No. 10914: Regulatory Relief for Certain Stationary Sources to Promote American Energy". In: *Federal Register* 90. Presidential proclamation, signed April 8, 2025, p. 16777. URL: <https://www.whitehouse.gov/presidential-actions/2025/04/regulatory-relief-for-certain-stationary-sources-to-promote-american-energy/>.
- Wallsten, Scott and Katrina Kosec (2008). "The effects of ownership and benchmark competition: An empirical analysis of US water systems". In: *International Journal of Industrial Organization* 26.1, pp. 186–205.
- Wheelock, TD and R Markuszewski (1984). "Coal preparation and cleaning". In: *The science and technology of coal and coal utilization*. Springer, pp. 47–123.
- Zirogiannis, Nikolaos et al. (2023). "Polluting under the radar: emissions, inequality, and concrete batch plants in Houston". In: *Environmental Science & Technology* 57.31, pp. 11410–11419.
- Zou, Eric Yongchen (2021). "Unwatched pollution: The effect of intermittent monitoring on air quality". In: *American Economic Review* 111.7, pp. 2101–2126. DOI: 10.1257/aer.20181346.

Tables and Figures

Table 1: Coal Mining Exposed Utilities' Inorganic Chemical Water Violations 1985–2005

Panel A: Any violation in year								
Contaminant	MR				MCL			
	%	N			%	N		
Nitrates	6.05	377			0.06	4		
Arsenic	4.01	250			0.03	2		
IOCs	4.59	286			0.32	20		

Panel B: Days in year								
Contaminant	MR				MCL			
	Mean	SD	P90	P99	Mean	SD	P90	P99
Nitrates	15.53	67.32	0.00	365.00	0.18	8.01	0.00	0.00
Arsenic	10.69	56.01	0.00	365.00	0.04	2.59	0.00	0.00
IOCs	12.27	60.15	0.00	365.00	0.78	15.83	0.00	0.00

Notes: Sample of drinking water utilities downstream of a coal mine between 1985–2005. MR = monitoring and reporting violation; MCL = maximum contaminant level violation. Panel A: % Non-zero is the share of utility-year observations with a nonzero violation share for that category, in percent; Num. Violations is the corresponding count of utility-year observations. Panel B: Mean, SD, P90, and P99 describe the number of days in a year in violation. Number of observations = Number of utilities $\times$ Number of years. $N = 6,232 = 340 \text{ utilities} \times \text{up to 21 years (1985–2005)}$.

Table 2: Enforcement Actions and Site Visits, Coal Mining Exposed Utilities 1985–2005

	Whole panel		During MR year		During MCL year	
	%	N	%	N	%	N
Panel A: Enforcement type						
Formal	3.50	218	9.53	43	7.69	2
Informal	19.02	1,184	67.63	305	53.85	14
Any	21.37	1,330	70.73	319	65.38	17
Panel B: Visit type						
Sanitary	14.55	906	14.19	64	7.69	2
Technical assistance	2.33	145	4.88	22	0.00	0
Enforcement	1.16	72	2.44	11	3.85	1
Sample collection	0.90	56	0.44	2	0.00	0
Inspection	4.05	252	5.76	26	3.85	1

Notes: Sample of drinking water utilities downstream of a coal mine between 1985–2005. MR = monitoring and reporting violation; MCL = maximum contaminant level violation. Whole panel columns report the share and count of utility-year cells with a given enforcement action or site visit type, among all 6,225 cells. During MR year and During MCL year columns restrict to the 451 and 26 cells, respectively, with a nitrate, arsenic, or inorganic chemical violation of that category, before computing the same share and count. Panel A: Formal and Informal enforcement follow the EPA SDWIS enforcement-action classification; Any is a cell with an enforcement action of either category. Panel B: Sanitary visits are sanitary surveys and follow-up sanitary surveys; Technical assistance covers technical assistance, engineering, and operations and maintenance visits; Enforcement visits are formal-enforcement, investigation, and emergency site visits; Sample collection is a sample-collection visit; Inspection covers site, regularly scheduled, and informal system inspections. An enforcement action or visit type may co-occur with others in the same cell, so rows need not sum to the Any/whole-panel total. Number of observations = 6,225.

Table 3: Summary statistics: mean concentration for inorganic chemicals and cumulative upstream coal production

Variable	MCL	Mean	Max	Std. Dev.	N	Near MCL
Panel A: Full sample						
Arsenic (mg/L)	Pre-2006: 0.050 mg/L, 2006+: 0.010 mg/L	0.0029	0.0110	0.0023	378	0.0%
Nitrate (mg/L)	10.0 mg/L	0.7520	5.5400	0.8482	444	0.5%
Barium (mg/L)	2.000 mg/L	0.0748	0.7071	0.0671	369	0.0%
Selenium (mg/L)	0.050 mg/L	0.0048	0.0354	0.0051	367	0.5%
Cumul. upstream coal prod. (10M ST)	—	0.4402	14.1792	1.4162	518	—
Panel B: Utility exposed to above median cumulative tons of coal extraction						
Arsenic (mg/L)	Pre-2006: 0.050 mg/L, 2006+: 0.010 mg/L	0.0031	0.0100	0.0026	177	0.0%
Nitrate (mg/L)	10.0 mg/L	0.7770	5.5400	0.8175	236	0.4%
Barium (mg/L)	2.000 mg/L	0.0754	0.3320	0.0579	169	0.0%
Selenium (mg/L)	0.050 mg/L	0.0040	0.0346	0.0043	169	0.6%
Cumul. upstream coal prod. (10M ST)	—	0.8822	14.1792	1.9089	258	—

Notes: SYR2 sample from 1998–2005. Cumulative upstream coal production (10M ST) is cumulative coal production since 1985, in units of 10 million short tons, in the watershed immediately upstream of the utility’s intake. For cumulative upstream coal production, statistics are computed over unique utility×year pairs that appear in at least one regression sample. “Near MCL” is the share of utility-year mean concentrations exceeding 50% of the applicable MCL. Panel B restricts Panel A’s sample to utility-year observations with cumulative upstream coal production above the sample median of 0.0094 (10M ST).

Table 4: MR and MCL violation rates by SYR2 contaminant reporting status

	(1) Has SYR2 reading	(2) No SYR2 reading	Diff. (1)–(2)	<i>p</i> -value
Ever MR violation, 1997–2005	32.4%	9.8%	22.6%***	0.000
Ever MR violation, 1985–2005	51.1%	32.8%	18.3%***	0.001
Ever MCL violation, 1997–2005	1.3%	0.0%	1.3%*	0.083
Ever MCL violation, 1985–2005	5.3%	1.6%	3.7%*	0.052
Mean annual violations (count, 0–6), 1997–2005	0.09	0.11	-0.02	0.663

Notes: Sample restricted to utilities strictly downstream of a coal mine. *Has SYR2 reading:* at least one Six-Year Review contaminant reading for arsenic, nitrate, selenium, or barium. *No SYR2 reading:* utility is in a state where at least one utility has a SYR2 reading but the utility itself does not. MR violation: IOC monitoring and reporting violation. MCL violation: IOC maximum contaminant violation. Mean annual violations: sum of MR and MCL violation indicators across arsenic, nitrate, and inorganic chemicals categories (maximum of 6 per utility-year). *N* utilities: group 1 = 225, group 2 = 122. Diff. stars from two-sample *t*-test: *** $p < 0.01$, ** $p < 0.05$, * $p < 0.1$.

Table 5: First stage: effect of the Acid Rain Program on the number of upstream coal mines (summed across upstream watersheds, CWSs at most one HUC12 down-stream)

	Upstream coal mines (sum) (1)
post95 $\times$ Upstream sulfur %	-0.2404*** (0.0458)
F-test (1st stage, clustered)	27.52
Observations	6,225

Notes: The dependent variable is the number of coal mines in watersheds upstream of the community water system's intake, summed across upstream watersheds. The instrument interacts an indicator for the post-1995 period with the sum of coal sulfur content across upstream watersheds. The sample is community water systems at most one watershed downstream of a coal mine. All specifications include CWS and year fixed effects. Standard errors clustered at the CWS level. Sample period 1985–2005. ***

p<0.01, ** p<0.05, * p<0.1.

Table 6: Effect of instrument on utility characteristics

	Number of Intake Facilities	
	(1)	(2)
Upstream sulfur		0.0384 (0.0735)
Post-1995 $\times$ Upstream sulfur	-0.0016 (0.0016)	-0.0016 (0.0017)
Utility fixed effects	✓	
Year fixed effects	✓	✓
Balanced panel		✓
Utilities	333	260
Observations	6,225	5,460

Notes: Standard errors, clustered at the utility level, are shown in parentheses below each coefficient. Sample period 1985–2005. *** $p < 0.01$, ** $p < 0.05$, * $p < 0.1$.

Table 7: Effect of coal mines on inorganic chemical violations at utilities

	Any violation		
	Nitrates	Arsenic	Inorganic chemicals
	(1)	(2)	(3)
OLS			
Upstream coal mines (sum)	1.94*** (0.72)	1.67** (0.65)	1.75*** (0.65)
2SLS			
Upstream coal mines (sum)	9.91*** (3.72)	7.50** (3.06)	6.34* (3.32)
RF			
post95 $\times$ Upstream sulfur %	-2.38*** (0.84)	-1.80** (0.73)	-1.52* (0.80)

Notes: Dependent variable equals 1 if the utility had any violation of that type during the year, 0 otherwise; coefficients and standard errors multiplied by 100 to show percentage point change. The instrument interacts an indicator for the post-1995 period with the sum of coal sulfur content across upstream watersheds. All specifications include utilities and year fixed effects. Standard errors clustered at the utilities level. The first-stage F-statistic (clustered at the utility level) for the instrumented variable, Upstream coal mines (sum), is 27.52. Sample period 1985–2005. Number of observations = 6,225. *** $p < 0.01$, ** $p < 0.05$, * $p < 0.1$.

Table 8: Effect of coal mines on inorganic chemical monitoring and reporting violations at utilities

	Any MR violation		
	Nitrates	Arsenic	Inorganic chemicals
	(1)	(2)	(3)
OLS			
Upstream coal mines (sum)	1.95*** (0.72)	1.70*** (0.65)	1.80*** (0.66)
2SLS			
Upstream coal mines (sum)	9.93*** (3.73)	7.43** (3.05)	7.07** (3.23)
RF			
post95 $\times$ Upstream sulfur %	-2.39*** (0.84)	-1.79** (0.73)	-1.70** (0.77)

Notes: Dependent variable equals 1 if the utility had any violation of that type during the year, 0 otherwise; coefficients and standard errors multiplied by 100 to show percentage point change. The instrument interacts an indicator for the post-1995 period with the sum of coal sulfur content across upstream watersheds. All specifications include utilities and year fixed effects. Standard errors clustered at the utilities level. The first-stage F-statistic (clustered at the utility level) for the instrumented variable, Upstream coal mines (sum), is 27.52. Sample period 1985–2005. Number of observations = 6,225. *** $p < 0.01$, ** $p < 0.05$, * $p < 0.1$.

Table 9: Effect of coal mines on inorganic chemical maximum contaminant level violations at utilities

	Any MCL violation		
	Nitrates	Arsenic	Inorganic chemicals
	(1)	(2)	(3)
OLS			
Upstream coal mines (sum)	-0.02 (0.02)	-0.02 (0.04)	-0.00 (0.14)
2SLS			
Upstream coal mines (sum)	-0.02 (0.02)	0.08 (0.06)	-0.78 (0.69)
RF			
post95 $\times$ Upstream sulfur %	0.00 (0.00)	-0.02 (0.01)	0.19 (0.16)

Notes: Dependent variable equals 1 if the utility had any violation of that type during the year, 0 otherwise; coefficients and standard errors multiplied by 100 to show percentage point change. The instrument interacts an indicator for the post-1995 period with the sum of coal sulfur content across upstream watersheds. All specifications include utilities and year fixed effects. Standard errors clustered at the utilities level. The first-stage F-statistic (clustered at the utility level) for the instrumented variable, Upstream coal mines (sum), is 27.52. Sample period 1985–2005. Number of observations = 6,225. *** $p < 0.01$, ** $p < 0.05$, * $p < 0.1$.

Table 10: Effect of cumulative upstream coal production on Inorganic Chemicals, SYR2 1998–2005

	Mean conc.			
	Arsenic (1)	Nitrate (2)	Barium (3)	Selenium (4)
Cumul. upstream coal prod. (10M ST)	0.0023*** (0.0004)	0.0572 (0.0922)	0.0171* (0.0093)	0.0033** (0.0016)
Observations	334	432	322	319
Utility fixed effects	✓	✓	✓	✓
huc02-year fixed effects	✓	✓	✓	✓

Notes: Standard errors clustered at the utility level. *** $p < 0.01$, ** $p < 0.05$, * $p < 0.1$.

Table 11: Monitoring and Reporting (MR) violations following contaminant concentration readings

	Arsenic MR (1-yr) (1)	Arsenic MR (6-mon) (2)	Nitrate MR (1-yr) (3)	Nitrate MR (6-mon) (4)	Pooled IOC (1-yr) (5)	Pooled IOC (6-mon) (6)
Mean concen. (z-score)	0.2622 (0.3250)	0.2665 (0.2495)	1.2804 (1.4274)	0.0482 (0.8741)		
Concen. > 50% MCL			58.9693** (24.6040)	26.1081** (10.5298)	0.4033 (2.4182)	-2.1966 (1.4172)
Concen./MCL					-5.9684 (8.1107)	-5.7062 (4.0256)
Observations	419	419	851	851	3,705	3,705
CWS fixed effects	✓	✓	✓	✓	✓	✓
Year fixed effects	✓	✓	✓	✓	✓	✓
Contaminant fixed effects					✓	✓

Notes: SYR2 only (1998–2005). Outcome: same-contaminant MR violation within the year following the contaminant reading or the 6 months following the contaminant reading, equal to 100 if a violation occurred and 0 otherwise; coefficients and standard errors are in percentage points. Pooled IOC MR violations exclude arsenic and nitrate, which have their own rule codes. Mean concentration z-scored within chemical. *** $p < 0.01$, ** $p < 0.05$, * $p < 0.1$. SEs clustered at the CWS level.

Table 12: Nitrate MR violations following a reading above 50% of the MCL (national sample, downstream-2SLS-sample states)

	Nitrate MR (1-yr) (1) OLS	Nitrate MR (6-mon) (2) OLS	Nitrate MR (1-yr) Logit (3) Logit	Nitrate MR (6-mon) Logit (4) Logit
Concen. > 50% MCL	0.4226* (0.2498)	0.1529* (0.0840)	0.1568** (0.0761)	0.0969 (0.0676)
Mean concen. (z-score)	2.1957** (0.9297)	1.0630*** (0.3789)	0.5452*** (0.1906)	0.3686*** (0.1327)
Observations	541,483	541,483	86,940	65,317

Notes: National SYR2 sample restricted to states with at least one CWS in the main downstream 2SLS sample (community water systems strictly downstream of a coal mine, 1985–2005), nitrate only. Outcome: nitrate MR (monitoring/reporting) violation in the forward window (1–365 days for the 1-yr column; 1–182 days for the 6-mon column) following the sample date. Concen. > 50% MCL = reading at 50–100% of the MCL, the quarterly-monitoring trigger. States retained: 18. Unique CWSs: 53335. N of readings with concentration above 50 percent of the MCL: 85766. Mean concentration = CWS-year mean reading, z-scored across the sample. Cols 1–2 are linear probability models, coefficients and standard errors in percentage points; cols 3–4 are logit models on the underlying 0/1 outcome. All specifications include CWS and year fixed effects. *** $p < 0.01$, ** $p < 0.05$, * $p < 0.1$. SEs clustered at the CWS level.

Table 13: Effect of Coal Mining on Enforcement Actions by Type (Downstream Sample)

	Any enforcement		
	Informal (1)	Formal (2)	None (3)
OLS			
Upstream coal mines (sum)	0.84 (0.79)	-1.69*** (0.45)	-0.78 (0.86)
2SLS			
Upstream coal mines (sum)	-0.56 (4.00)	-5.65*** (2.05)	-0.10 (4.23)
RF			
post95 $\times$ Upstream sulfur %	0.14 (1.02)	1.45*** (0.52)	0.03 (1.08)

Notes: Sample restricted to utilities strictly downstream of a coal mine. Each outcome is equal to 100 if the enforcement event occurred in the utility-year and 0 otherwise; coefficients and standard errors are in percentage points. Informal enforcement actions occur in 19.0% of the panel, formal enforcement actions in 3.5% of the panel, and no enforcement in 78.7% of the panel. The instrument interacts an indicator for the post-1995 period with mean upstream coal sulfur content. All specifications include utilities and year fixed effects. SEs clustered at the utilities level. *** $p < 0.01$, ** $p < 0.05$, * $p < 0.1$.

Table 14: Effect of Coal Mining on Regulator Visit Probability by Visit Type (Downstream Sample, LPM)

	Any visits				
	Sanitary	Technical assistance	Enforcement	Sample collection	Inspection
	(1)	(2)	(3)	(4)	(5)
OLS					
Upstream coal mines (sum)	1.06 (0.67)	-0.38 (0.42)	-0.71** (0.32)	-0.19 (0.12)	-0.33 (0.47)
2SLS					
Upstream coal mines (sum)	14.06*** (4.87)	1.41 (1.96)	3.67* (1.88)	1.35 (1.15)	-1.88 (2.41)
RF					
post95 × Upstream sulfur %	- 3.60*** (1.03)	-0.36 (0.48)	-0.94** (0.40)	-0.34 (0.27)	0.48 (0.60)

Notes: Sample restricted to utilities strictly downstream of a coal mine. N = 6232 utility-years. Panels (OLS, 2SLS, reduced form) report coefficients for each visit-type outcome shown in the columns, equal to 100 if any visit of that type occurred in the utility-year and 0 otherwise; coefficients and standard errors are in percentage points. Sanitary visits are sanitary surveys and follow-up sanitary surveys. Technical assistance includes technical assistance, engineering determination/advice/plan review, and operation and maintenance visits. Enforcement visits include formal enforcement, investigation, and emergency assistance visits. Sample collection is sample collection visits. Inspection includes site inspections, regularly scheduled visits, and informal system inspections. The instrument interacts an indicator for the post-1995 period with mean upstream coal sulfur content. All specifications include utilities and year fixed effects. SEs clustered at the utilities level. *** p<0.01, ** p<0.05, * p<0.1.




Figure 1: Distribution of violation lengths, by contaminant

Notes: Panels show the distribution of the number of days each violation lasts for the arsenic, nitrate, and inorganic chemical contaminant categories analyzed in this paper. Violation length is measured as the number of days between a violation's recorded start and end dates.



Figure 2: Hierarchical structure of USGS hydrologic unit codes

Notes: Illustrates how a hydrologic region is nested into progressively smaller watershed units, from two-digit units covering large multi-state regions down to twelve-digit units covering a few square miles. Each smaller unit is fully contained within the boundaries of the larger unit above it.

HUC12s with MSHA and EIA Mine Data




Figure 3: Watersheds matched to coal mine location and production data

Notes: Shading indicates whether a watershed contains a mine with only location data, only production data, both matched together, or a mine that has since closed. Only watersheds matched to both mine location and mine production data are used to measure coal production in the main analysis.

HUC12 watersheds containing coal mines, 1985-2005




Figure 4: Shading distinguishes HUC12 watersheds that lie directly upstream of a water utility intake and contain a coal mine from HUC12 watersheds containing a coal mine with no water utility located downstream.




Figure 5: Coal production trends by HUC12 watershed sulfur content, 1983 to 2005.




Figure 6: Histogram of the percentage of sulfur in coal weight in HUC12 watersheds downstream of coal production and where a water utility intake is located. The top two panels show histograms of utility-year observations.




Figure 7: Change in coal production by watershed, 1985 to 2005

Notes: Circles are centered on watersheds with at least one active coal mine between 1985 and 2005 and are sized proportionate to the change in total coal production over the period. Red circles indicate an increase in production and blue circles indicate a decrease.





Figure 8: Change in upstream coal production weighted by downstream population

Notes: Circles are centered on coal-mining watersheds located directly upstream of a water utility intake and are sized proportionate to the population served by the downstream utility. Red circles indicate an increase in production and blue circles indicate a decrease. Watersheds with no water utility directly downstream are omitted. The total population one watershed downstream of an active coal mine was 1,257,836 in 1985 and 218,874 in 2005, a net decrease of 1,038,962.

Descriptive evidence of first-stage relevance



Sample: HUC12 watersheds directly upstream of drinking water utility water intakes 1985-2005.
Points show the mean sulfur as a percent of coal weight within each coal-mine-count bin; ranges show ± 1 standard deviation within bin.

Figure 9: Coal mines and coal sulfur content, before and after 1995

Notes: Each point is a watershed-year observation. Lines are separate linear fits of the number of coal mines on coal sulfur content for the periods before and after 1995.




Figure 10: Residualized first-stage relationship

Notes: Each point is a community water system by year observation for the sample strictly downstream of a coal mine, 1985 to 2005. Both axes show residuals from separate regressions of each variable on community water system and year fixed effects, retaining only within-utility variation over time. The vertical axis residualizes the number of upstream coal mines; the horizontal axis residualizes the instrument, the post-1995 indicator interacted with the sulfur content of upstream coal. By the Frisch-Waugh-Lovell theorem, the slope of the fitted line equals the first-stage coefficient from the two-stage least squares specification.