

# Structured Programming

Test 1, 29.10.2015, Group: A

*Each question has exactly **one correct** answer.*

Name: \_\_\_\_\_

ID: \_\_\_\_\_

1. What will be the value of x after the execution of the following code segment?

```
int x, a, b;  
int x = scanf("%d%d", &a, &b);
```

- (a) 0
- (b) 1
- (c) 2
- (d) 3

2. Which of the following expressions **outputs 0.75** on the standard output if the variables are declared as `int a = 3, b = 4`?

- (a) `printf("a/b=%d", a/b)`
- (b) `printf("a/b=%.2f", a/b)`
- (c) `printf("a/b=%0.2f", (float)a/b)`
- (d) `printf("a/b=%0.2f", (float)(a/b))`

3. What will be the output after execution of the following code segment?

```
#include<stdio.h>  
int main (){  
    for (printf ("-1"); printf ("%d", printf("01")); printf ("3"))  
        break;  
    return 0;  
}
```

- (a) -1012
- (b) -10123
- (c) -1
- (d) -1011

4. What will be the output after execution of the following code segment?

```
int x, a, b;  
int x = scanf("%d%d", &a, &b);
```

- (a) `y = 1`
- (b) `y = 2.25`
- (c) `y = 1.00`
- (d) `y = 001`

5. What will be the value of x after the execution of the following code segment?

```
#include<stdio.h>
int main (){
    for (printf ("-1"); printf ("%d", printf("01")); printf ("3"))
        break;
    return 0;
}
```

- (a) 0
- (b) 1
- (c) -1
- (d) 9

6. Which of the following expressions will declare an array of 5 integers?

- (a) `pole int[5];`
- (b) `int pole[];`
- (c) `int pole[] = {1, 2, 3, 4, 5};`
- (d) `array int[5];`

7. What will be the output after the execution of the following code segment?

```
int x = 23;
switch(x) {
    case 1: printf("1"); break;
    case 23: printf("2"); break;
    case 123: printf("3"); break;
}
```

- (a) 123
- (b) 1
- (c) 23
- (d) 2

8. What is the result from the execution of the following code segment?

```
int a, b, d = 2; float c = 0;
for(a = 5, b = a--; a > 0, b < 10; a--, b++) c += 1 / d;
printf("%.3.1f\n", c);
```

- (a) 2.5
- (b) 0.0
- (c) 2.0
- (d) 3.0

9. What will be the output after the execution of the following code segment?

```
if(1 <= x <= 2) printf("YES");  
else printf("NO");
```

- (a) YES
- (b) NO
- (c) cannot predict, will depend on value of variable x
- (d) the code will produce a syntax error

10. Which from the following expressions does not result in 3.5 if the variables are declared as `int a=7, b=2;`

- (a) `a/(float)b`
- (b) `a*1./b`
- (c) `float(a)/b`
- (d) `(float)(a/b)`

# Answer Key for Exam A

1. What will be the value of x after the execution of the following code segment?

```
int x, a, b;  
int x = scanf("%d%d", &a, &b);
```

- (a) 0
- (b) 1
- (c) 2
- (d) 3

2. Which of the following expressions **outputs 0.75** on the standard output if the variables are declared as `int a = 3, b = 4`?

- (a) `printf("a/b=%d", a/b)`
- (b) `printf("a/b=%.2f", a/b)`
- (c) `printf("a/b=%0.2f", (float)a/b)`
- (d) `printf("a/b=%0.2f", (float)(a/b))`

3. What will be the output after execution of the following code segment?

```
#include<stdio.h>  
int main (){  
    for (printf ("-1"); printf ("%d", printf("01")); printf ("3"))  
        break;  
    return 0;  
}
```

- (a) -1012
- (b) -10123
- (c) -1
- (d) -1011

4. What will be the output after execution of the following code segment?

```
int x, a, b;  
int x = scanf("%d%d", &a, &b);
```

- (a) `y = 1`
- (b) `y = 2.25`
- (c) `y = 1.00`
- (d) `y = 001`

5. What will be the value of x after the execution of the following code segment?

```
#include<stdio.h>
int main (){
    for (printf ("-1"); printf ("%d", printf("01")); printf ("3"))
        break;
    return 0;
}
```

- (a) 0
- (b) 1
- ☒ (c) -1
- (d) 9

6. Which of the following expressions will declare an array of 5 integers?

- (a) pole int[5];
- (b) int pole[];
- ☒ (c) int pole[] = {1, 2, 3, 4, 5};
- (d) array int[5];

7. What will be the output after the execution of the following code segment?

```
int x = 23;
switch(x) {
    case 1: printf("1"); break;
    case 23: printf("2"); break;
    case 123: printf("3"); break;
}
```

- (a) 123
- (b) 1
- (c) 23
- ☒ (d) 2

8. What is the result from the execution of the following code segment?

```
int a, b, d = 2; float c = 0;
for(a = 5, b = a--; a > 0, b < 10; a--, b++) c += 1 / d;
printf("%.3.1f\n", c);
```

- (a) 2.5
- ☒ (b) 0.0
- (c) 2.0
- (d) 3.0

9. What will be the output after the execution of the following code segment?

```
if(1 <= x <= 2) printf("YES");  
else printf("NO");
```

- ☒ (a) YES
- (b) NO
- (c) cannot predict, will depend on value of variable x
- (d) the code will produce a syntax error

10. Which from the following expressions does not result in 3.5 if the variables are declared as `int a=7, b=2;`

- (a) `a/(float)b`
- (b) `a*1./b`
- (c) `float(a)/b`
- ☒ (d) `(float)(a/b)`